

Apply filters to SQL queries

Project description

This project is to use the command line to practice applying filters in SQL. This is in order to refine queries. It must be noted that screenshots often contain only the first results of the query in order to keep the demonstration concise. The scenario is “You are a security professional at a large organization. Part of your job is to investigate security issues to help keep the system secure. You recently discovered some potential security issues that involve login attempts and employee machines.

Your task is to examine the organization’s data in their employees and log_in_attempts tables. You’ll need to use SQL filters to retrieve records from different datasets and investigate the potential security issues.”

Retrieve after hours failed login attempts

In order to explore the potential security issues, I needed to query the log_in_attempts table and review after hours login activity. By applying filters in SQL I created a query that identifies all failed login attempts that occurred after 18:00 [login_time > '18:00' and SUCCESS = 0]. As can be seen, the time of the login attempt is found in the login_time column and we can see that the filter was applied successfully - all times are after 6pm. The success column contains a binary value of 0 when a login attempt failed or a 1 when attempts were successful. Here I filtered for all unsuccessful attempts. By applying the WHERE and AND filters I was able to narrow the results.

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE login_time > '18:00' and SUCCESS = 0;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	astrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
52	cjackson	2022-05-10	22:07:07	CAN	192.168.58.57	0
69	wjaffrey	2022-05-11	19:55:15	USA	192.168.100.17	0
82	abernard	2022-05-12	23:38:46	MEX	192.168.234.49	0
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
96	ivelasco	2022-05-09	22:36:36	CAN	192.168.84.194	0
104	asundara	2022-05-11	18:38:07	US	192.168.96.200	0
107	bisles	2022-05-12	20:25:57	USA	192.168.116.187	0
111	astrada	2022-05-10	22:00:26	MEXICO	192.168.76.27	0
127	abellmas	2022-05-09	21:20:51	CANADA	192.168.70.122	0
131	bisles	2022-05-09	20:03:55	US	192.168.113.171	0
155	cgriffin	2022-05-12	22:18:42	USA	192.168.236.176	0
160	jclark	2022-05-10	20:49:00	CANADA	192.168.214.49	0
199	yappiah	2022-05-11	19:34:48	MEXICO	192.168.44.232	0

```
19 rows in set (0.222 sec)
```

Retrieve login attempts on specific dates

It became evident that a suspicious event occurred on 2022-05-09 and to investigate this event I needed to review all login attempts which occurred on this day and the day before.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE login_date = '2022-05-09'  
-> OR login_date = '2022-05-08';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
24	arusso	2022-05-09	06:49:39	MEXICO	192.168.171.192	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
28	astrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
30	yappiah	2022-05-09	03:22:22	MEX	192.168.124.48	1
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0
36	asundara	2022-05-08	09:00:42	US	192.168.78.151	1

I've only included a screenshot of the first rows of data for demonstration, however using the filter WHERE to establish the first login date and OR to establish login attempts made on the previous date, it was established that 75 login attempts were made all day on those two days.

Retrieve login attempts outside of Mexico

It is established by the cybersecurity team that the potential activity did not originate in Mexico, so the goal of the next search is to keep only data that pertains to all countries outside of Mexico.

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0
7	eraab	2022-05-11	01:45:14	CAN	192.168.170.243	1
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
10	jrafael	2022-05-12	09:33:19	CANADA	192.168.228.221	0
11	sgilmore	2022-05-11	10:16:29	CANADA	192.168.140.81	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
13	mrh	2022-05-11	09:29:34	USA	192.168.246.135	1
14	sbaelish	2022-05-10	10:20:18	US	192.168.16.99	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
16	mcouliba	2022-05-11	06:44:22	CAN	192.168.172.189	1
17	pwashing	2022-05-11	02:33:02	USA	192.168.81.89	1
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0

By using the WHERE NOT command I was able to narrow the records down to only those that are based in other countries. By using LIKE filter and MEX followed by the wildcard [%] I made

sure this accounted for all records that represented Mexico because there were inconsistent representations of Mexico in the table (MEXICO/MEX).

Retrieve employees in Marketing

In the scenario I was asked to perform security updates on specific employee machines in the Marketing department who were located in the East offices.

```
MariaDB [organization]> SELECT * FROM employees WHERE department = 'Marketing' AND office LIKE 'East%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

```
7 rows in set (0.001 sec)
```

By applying the WHERE to the department column and LIKE (East%) to the office column, I was able to make sure that only the entries for those employees in marketing working in the various East offices were included in the results.

Retrieve employees in Finance or Sales

I was requested to perform a different security update on machines for employees in the Sales and Finance departments. Here I queried the employees table to get only those employees working in either Sales or Finance, as listed in the department column.

```
MariaDB [organization]> SELECT * FROM employees WHERE department = 'Sales' or department = 'Finance';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlanisky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1029	d336e475f676	ivelasco	Finance	East-156
1035	j236k303l245	bisles	Sales	South-171

By using the OR filter, I was able to get both departments, rather than one or the other obtained in AND queries (OR is used to return multiple queries).

Retrieve all employees not in IT

It has been requested that I make one more update to employee machines, however the employees who are in the Information Technology department already had this update, but employees in all other departments need it.

```
MariaDB [organization]> SELECT * FROM employees WHERE NOT department = 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1016	q793r736s288	sbaelish	Human Resources	North-229
1017	r550s824t230	jclark	Finance	North-188

By applying the WHERE NOT filter to the department column in the employees table I was able to narrow the results down to those who need the updates, ie. those who aren't in the Information Technology department.

Summary

By using WHERE, WHERE NOT, AND, OR as well as wildcard characters, data can be efficiently filtered in SQL to get the relevant results. In the scenario I was able to narrow down dates and times to investigate potential security vulnerabilities. I was able to exclude locations to include only those that were involved in potential security incidents. I was also able to identify specific departments and locations requiring updates. In security it's important that software stays up-to-date so that security vulnerabilities from old editions can't be exploited.