

Codificatorul prioritar – completări

$ab + \bar{a}c = ab + \bar{a}c + bc$

$$\begin{aligned}
 \overline{EI} \cdot \bar{7} + \overline{EI} \cdot \bar{6} \cdot 7 &= \begin{cases} \overline{EI}(\bar{7} + \bar{6} \cdot 7) \\ a = 7, b = \bar{6}, \bar{a} = \bar{7}, c = 1 \end{cases} = \overline{EI}(\bar{7} \cdot 1 + \bar{6} \cdot 7) \\
 &= \overline{EI}(ab + \bar{a}c + bc) = \overline{EI}(\bar{7} \cdot 1 + \bar{6} \cdot 7 + \bar{6} \cdot 1) = \overline{EI}(\bar{7} + \bar{6} + \bar{6} \cdot 7) \\
 &= \overline{EI} \cdot \bar{7} + \overline{EI} \cdot \bar{6}.
 \end{aligned}$$

$$\begin{aligned}
 \overline{EI} \cdot \bar{6} \cdot 7 + \overline{EI} \cdot \bar{5} \cdot 6 \cdot 7 &= \begin{cases} \overline{EI} \cdot 7(\bar{6} + \bar{5} \cdot 6) \\ a = 6, b = \bar{5}, \bar{a} = \bar{6}, c = 1 \end{cases} \\
 &= \overline{EI} \cdot 7(\bar{6} \cdot 1 + \bar{5} \cdot 6 + \bar{5} \cdot 1) = \overline{EI} \cdot 7(\bar{6} + \bar{5}) \\
 &= \overline{EI} \cdot 7 \cdot \bar{6} + \overline{EI} \cdot 7 \cdot \bar{5} + \overline{EI} \cdot 7 + \overline{EI} \cdot \bar{6} \\
 &= \begin{cases} \overline{EI}(7 \cdot \bar{6} + \bar{7}) \\ a = 7, b = \bar{6}, \bar{a} = \bar{7}, c = 1 \end{cases} + \dots = \overline{EI}(\bar{7} \cdot \bar{6} + \bar{7} + \bar{6}) + \dots
 \end{aligned}$$

$$\begin{aligned}
 \overline{EI} \cdot \bar{5} \cdot 6 \cdot 7 + \overline{EI} \cdot \bar{4} \cdot 5 \cdot 6 \cdot 7 &= \begin{cases} \overline{EI} \cdot 6 \cdot 7(\bar{5} + \bar{4} \cdot 5) \\ a = 5, b = \bar{4}, \bar{a} = \bar{5}, c = 1 \end{cases} \\
 &= \overline{EI} \cdot 6 \cdot 7(\bar{5} \cdot 1 + \bar{4} \cdot 5 + \bar{4} \cdot 1) = \overline{EI} \cdot 6 \cdot 7(\bar{5} + \bar{4} \cdot 5 + \bar{4}) \\
 &= \overline{EI} \cdot 6 \cdot 7(\bar{5} + \bar{4}); \dots
 \end{aligned}$$
