

The Earthquake Dissipative Engine: Energy Budget and Partition

Part J: Revision of main concepts and equations



S. Nielsen

Short course on earthquake physics

Geoscienze, Università di Padova Oct 2025

27 Oct. - 16:30-18:30 classroom 2G
28 Oct. - 14:30-16:30 classroom 2H
29 Oct. - 10:30-12:30 classroom Lab Paleo
31 Oct. - 14:30-16:30 classroom 2L

$$\tau(r) = \frac{K_*}{\sqrt{2\pi r}} = \boxed{\frac{1}{\sqrt{2}} \Delta\tau \sqrt{\frac{L}{r}}} (+ \dots \text{weaker singular terms}) \quad \text{stress concentration}$$

$$K_* = K_I = K_{II} = K_{III} = \boxed{\Delta\tau\sqrt{\pi L}} \quad \text{stress intensity factor}$$

$$G_0 = \frac{K_{II}^2}{2\mu} = C_2 \frac{\Delta\tau^2}{2\mu} L \quad \boxed{G_0 = C_2 \frac{\Delta\tau^2}{2\mu} L} = \frac{K_{III}^2}{2\mu} \quad \text{energy release rate, static}$$

$$G(v) = \boxed{G_0 \frac{\sqrt{1 - \frac{v^2}{c^2}}}{1 + \frac{v}{c}} \approx G_0 \left(1 - \frac{v}{c}\right)} \quad \begin{array}{l} \text{energy release rate, dynamic:} \\ \text{Lorentz contraction and Doppler approx.} \end{array}$$

$$\boxed{G(v) \equiv \Gamma} \quad \text{rupture propagation criterion}$$

$$\tau(x, t) = \tau_0(x, t) \left[-\frac{\mu}{c_s} \dot{\delta}(x, t) \right] + \tau_{\text{hist}}(x, t) \quad \text{radiation damping}$$

Two fundamental scaling in earthquake sources:

$$\frac{\Delta\tau}{\mu} \propto \frac{\dot{\delta}}{c_s} \quad (\longrightarrow \dot{\delta} \approx 1 \text{ m/s})$$

$$\frac{\Delta\tau}{\mu} \propto \frac{u}{L} \quad (\longrightarrow \delta \approx 10^{-4} L)$$

$$L_c = \frac{1}{A_0} \frac{\Gamma \mu'}{\Delta \tau^2}$$

$$G(v) \approx G_0 \left(1 - \frac{v}{c}\right) \quad G_0 = C \frac{\Delta \tau^2}{2\mu} L$$

$$\frac{\Gamma}{G_0} = \frac{L_c}{L} \quad G(v) \equiv \Gamma$$

$$\frac{1}{C_{lim}} \frac{\partial L}{\partial t} = \left(1 - \frac{L_c}{L}\right)$$

$$L(t) = L_c \left(1 + W_0 \left[\exp \left(\frac{C_{lim}}{L_c} (t - t_0) \right) \right] \right)$$