Solver-First Deterministic Itinerary Planning for the ChinaTravel Benchmark

First Author[1] , **Second Author**[1]
[1]Team fabiundstefan
{first, second}@example.com

Configuration	FPR	C-LPR	Overall
TODO	–	–	–

Table 1: TODO: main result.

Abstract

TODO. One paragraph: the task, the solver-first approach, the no-oracle Phase 2 contract, and the headline result.

1 Introduction

TODO. The Travel Planning Challenge task, why a deterministic solver rather than an LLM agent loop, and what this report claims.

2 System Overview

TODO. The pipeline: parse and normalise the visible query into branch-local constraint variants, build a deterministic base itinerary, repair and restart under a bounded budget, optionally solve the residual with CP-SAT, then accept only what passes the schema, commonsense and logical checks. Note the two invariants that shape everything else: no oracle field ever reaches the agent path, and every fact is grounded in `WorldEnv` rather than generated.

3 Implementation

TODO. Entry point and packaging (one command, deterministic, zero LLM calls by default), the per-query budget policy under the whole-run wall-clock envelope, and how acceptance gating is enforced at finalisation.

4 Experiments

TODO. Setup: which split, which budget, which evaluator revision. Report the official metric decomposition (EPR-micro, EPR-macro, C-LPR, FPR, DAV, ATT, DDR) and the weighted overall score.

4.1 Ablations

TODO. One row per promoted mechanism, each from a paired same-revision run.

4.2 Error Analysis

TODO. What still fails and why, by failure family.

5 Conclusion

TODO.

Acknowledgements

TODO or delete.

References