

A Container Model of Type Theory

Stefania Damato
j.w.w. Thorsten Altenkirch

University of Nottingham, UK

YaMCATS Meeting 32

14th September 2023

Motivation:
modelling inductive types

Functorial semantics, for ordinary inductive types

```
data  $\mathbb{N}$  : Set where  
  zero :  $\mathbb{N}$   
  succ  :  $\mathbb{N} \rightarrow \mathbb{N}$ 
```

Functorial semantics, for ordinary inductive types

data \mathbb{N} : Set where

zero : \mathbb{N}

succ : $\mathbb{N} \rightarrow \mathbb{N}$

↓

zero : \mathbb{N}^1

succ : $\mathbb{N}^{\mathbb{N}}$

Functorial semantics, for ordinary inductive types

data \mathbb{N} : Set where

zero : \mathbb{N}

succ : $\mathbb{N} \rightarrow \mathbb{N}$

↓

zero : \mathbb{N}^1

succ : $\mathbb{N}^{\mathbb{N}}$

↓

zero × succ : $\mathbb{N}^{1+\mathbb{N}}$

Functorial semantics, for ordinary inductive types

data \mathbb{N} : Set where

zero : \mathbb{N}

succ : $\mathbb{N} \rightarrow \mathbb{N}$

↓

zero : \mathbb{N}^1

succ : $\mathbb{N}^{\mathbb{N}}$

↓

zero × succ : $\mathbb{N}^{1+\mathbb{N}}$

↓

zero × succ : $1 + \mathbb{N} \rightarrow \mathbb{N}$

Functorial semantics, for ordinary inductive types

data \mathbb{N} : Set where

zero : \mathbb{N}

succ : $\mathbb{N} \rightarrow \mathbb{N}$

↓

zero : \mathbb{N}^1

succ : $\mathbb{N}^{\mathbb{N}}$

↓

zero × succ : $\mathbb{N}^{1+\mathbb{N}}$

↓

zero × succ : $1 + \mathbb{N} \rightarrow \mathbb{N}$

↓

$F_{\mathbb{N}} : \mathbf{Set} \rightarrow \mathbf{Set}$

$F_{\mathbb{N}}(X) := 1 + X$

Functorial semantics, for ordinary inductive types

data \mathbb{N} : Set where

zero : \mathbb{N}

succ : $\mathbb{N} \rightarrow \mathbb{N}$

↓

zero : \mathbb{N}^1

succ : $\mathbb{N}^{\mathbb{N}}$

↓

zero \times succ : $\mathbb{N}^{1+\mathbb{N}}$

↓

zero \times succ : $1 + \mathbb{N} \rightarrow \mathbb{N}$

↓

$F_{\mathbb{N}} : \mathbf{Set} \rightarrow \mathbf{Set}$

$F_{\mathbb{N}}(X) := 1 + X$

data C : Set where

c : $((C \rightarrow 2) \rightarrow 2) \rightarrow C$

Functorial semantics, for ordinary inductive types

data \mathbb{N} : Set where

zero : \mathbb{N}

succ : $\mathbb{N} \rightarrow \mathbb{N}$

↓

zero : \mathbb{N}^1

succ : $\mathbb{N}^{\mathbb{N}}$

↓

zero \times succ : $\mathbb{N}^{1+\mathbb{N}}$

↓

zero \times succ : $1 + \mathbb{N} \rightarrow \mathbb{N}$

↓

$F_{\mathbb{N}} : \mathbf{Set} \rightarrow \mathbf{Set}$

$F_{\mathbb{N}}(X) := 1 + X$

data C : Set where

c : $((C \rightarrow 2) \rightarrow 2) \rightarrow C$

↓

c : $((C \rightarrow 2) \rightarrow 2) \rightarrow C$

Functorial semantics, for ordinary inductive types

data \mathbb{N} : Set where

zero : \mathbb{N}

succ : $\mathbb{N} \rightarrow \mathbb{N}$

↓

zero : \mathbb{N}^1

succ : $\mathbb{N}^{\mathbb{N}}$

↓

zero \times succ : $\mathbb{N}^{1+\mathbb{N}}$

↓

zero \times succ : $1 + \mathbb{N} \rightarrow \mathbb{N}$

↓

$F_{\mathbb{N}} : \mathbf{Set} \rightarrow \mathbf{Set}$

$F_{\mathbb{N}}(X) := 1 + X$

data C : Set where

c : $((C \rightarrow 2) \rightarrow 2) \rightarrow C$

↓

c : $((C \rightarrow 2) \rightarrow 2) \rightarrow C$

↓

$F_C : \mathbf{Set} \rightarrow \mathbf{Set}$

$F_C(X) := (X \rightarrow 2) \rightarrow 2$

The W-type

```
data W (S : Set) (P : S → Set) : Set where  
  sup : (s : S) → (P s → W S P) → W S P
```

The W-type

```
data W (S : Set) (P : S → Set) : Set where  
  sup : (s : S) → (P s → W S P) → W S P
```

\mathbb{N} as a W-type

```
data N : Set where  
  zero : N  
  succ : N → N
```

The W-type

```
data W (S : Set) (P : S → Set) : Set where  
  sup : (s : S) → (P s → W S P) → W S P
```

\mathbb{N} as a W-type

```
data  $\mathbb{N}$  : Set where  
  zero :  $\mathbb{N}$   
  succ :  $\mathbb{N} \rightarrow \mathbb{N}$   
  
S := 1 + 1
```

The W-type

```
data W (S : Set) (P : S → Set) : Set where  
  sup : (s : S) → (P s → W S P) → W S P
```

\mathbb{N} as a W-type

```
data  $\mathbb{N}$  : Set where  
  zero :  $\mathbb{N}$   
  succ :  $\mathbb{N} \rightarrow \mathbb{N}$   
  
S := 1 + 1  
P(inl ★) := 0  
P(inr ★) := 1
```

The W-type

```
data W (S : Set) (P : S → Set) : Set where  
  sup : (s : S) → (P s → W S P) → W S P
```

\mathbb{N} as a W-type

```
data  $\mathbb{N}$  : Set where  
  zero :  $\mathbb{N}$   
  succ :  $\mathbb{N} \rightarrow \mathbb{N}$   
  
 $S := 1 + 1$   
 $P(\text{inl } \star) := 0$   
 $P(\text{inr } \star) := 1$   
  
 $\mathbb{N} \cong W S P.$ 
```

The W-type

```
data W (S : Set) (P : S → Set) : Set where  
  sup : (s : S) → (P s → W S P) → W S P
```

\mathbb{N} as a W-type

```
data  $\mathbb{N}$  : Set where  
  zero :  $\mathbb{N}$   
  succ :  $\mathbb{N} \rightarrow \mathbb{N}$   
  
S := 1 + 1  
P(inl ★) := 0  
P(inr ★) := 1
```

$\mathbb{N} \cong WSP.$

$z : WSP$

$z := \text{sup}(\text{inl } \star)(\lambda ())$

$s : WSP \rightarrow WSP$

$sn := \text{sup}(\text{inr } \star)(\lambda _ . n)$

The W-type

```
data W (S : Set) (P : S → Set) : Set where  
  sup : (s : S) → (P s → W S P) → W S P
```

\mathbb{N} as a W-type

```
data  $\mathbb{N}$  : Set where
```

```
  zero :  $\mathbb{N}$ 
```

```
  succ :  $\mathbb{N} \rightarrow \mathbb{N}$ 
```

```
S := 1 + 1
```

```
P(inl ★) := 0
```

```
P(inr ★) := 1
```


$\mathbb{N} \cong WSP.$

```
z : WSP
```

```
z := sup (inl ★) (λ ())
```

```
s : WSP → WSP
```

```
s n := sup (inr ★) (λ _ . n)
```



Containers (a.k.a. polynomial functors)

Definition

A *container* is a pair $S : \text{Set}, P : S \rightarrow \text{Set}$, written as $S \triangleleft P$.

Containers (a.k.a. polynomial functors)

Definition

A *container* is a pair $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$, written as $S \triangleleft P$.

Definition

Extension functor $\llbracket S \triangleleft P \rrbracket : \mathbf{Set} \rightarrow \mathbf{Set}$ is defined by

$$\llbracket S \triangleleft P \rrbracket X := \sum (s : S)(P\ s \rightarrow X).$$

Containers (a.k.a. polynomial functors)

Definition

A *container* is a pair $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$, written as $S \triangleleft P$.

Definition

Extension functor $\llbracket S \triangleleft P \rrbracket : \mathbf{Set} \rightarrow \mathbf{Set}$ is defined by

$$\llbracket S \triangleleft P \rrbracket X := \sum (s : S)(P s \rightarrow X).$$

\mathbb{N} 's container representation

$$S := \mathbf{1} + \mathbf{1}$$

$$P(\text{inl } \star) := \mathbf{0}$$

$$P(\text{inr } \star) := \mathbf{1}$$

$$\llbracket S \triangleleft P \rrbracket : \mathbf{Set} \rightarrow \mathbf{Set}$$

$$\begin{aligned}\llbracket S \triangleleft P \rrbracket X &= \sum (s : \mathbf{1} + \mathbf{1})((\lambda (\text{inl } \star). \mathbf{0}; (\text{inr } \star). \mathbf{1}) \rightarrow X) \\ &\cong \mathbf{1} + X\end{aligned}$$

Containers (a.k.a. polynomial functors)

Definition

A *container* is a pair $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$, written as $S \triangleleft P$.

Definition

Extension functor $\llbracket S \triangleleft P \rrbracket : \mathbf{Set} \rightarrow \mathbf{Set}$ is defined by

$$\llbracket S \triangleleft P \rrbracket X := \sum (s : S)(P\ s \rightarrow X).$$

Containers enforce strict positivity
semantically.

An overview of inductive types

Class of types	Functor type	Category theory semantics	Type theoretic normal form	Universal type
ordinary inductive types e.g. $\mathbb{N} : \mathbf{Set}$	$\mathbf{Set} \rightarrow \mathbf{Set}$	initial algebras of endofunctors on \mathbf{Set}	containers	W-type

An overview of inductive types

Class of types	Functor type	Category theory semantics	Type theoretic normal form	Universal type
ordinary inductive types e.g. $\mathbb{N} : \mathbf{Set}$	$\mathbf{Set} \rightarrow \mathbf{Set}$	initial algebras of endofunctors on \mathbf{Set}	containers	W-type
inductive families e.g. $\mathbf{Fin} : \mathbb{N} \rightarrow \mathbf{Set}$	$(\mathbf{I} \rightarrow \mathbf{Set}) \rightarrow (\mathbf{I} \rightarrow \mathbf{Set})$	initial algebras of endofunctors on $\mathbf{Set}^{\mathbf{I}}$	indexed containers	WI-type

An overview of inductive types

Class of types	Functor type	Category theory semantics	Type theoretic normal form	Universal type
ordinary inductive types e.g. $\mathbb{N} : \mathbf{Set}$	$\mathbf{Set} \rightarrow \mathbf{Set}$	initial algebras of endofunctors on \mathbf{Set}	containers	W-type
inductive families e.g. $\mathbf{Fin} : \mathbb{N} \rightarrow \mathbf{Set}$	$(\mathbf{I} \rightarrow \mathbf{Set}) \rightarrow (\mathbf{I} \rightarrow \mathbf{Set})$	initial algebras of endofunctors on $\mathbf{Set}^{\mathbf{I}}$	indexed containers	WI-type
QIITs e.g. $\mathbf{Con} : \mathbf{Set}$, $\mathbf{Ty} : \mathbf{Con} \rightarrow \mathbf{Set}$?	?	?	?

Quotient inductive-inductive types

$$\text{QIITs} = \begin{cases} \textbf{Quotient} \text{ inductive types} \\ \textbf{Inductive-inductive} \text{ types} \end{cases}$$

Quotient inductive-inductive types

$$\text{QIITs} = \begin{cases} \text{Quotient inductive types} \\ \text{Inductive-inductive types} \end{cases}$$

Example 1.1: (Simplified) intrinsic syntax of type theory

```
data Con : Set
data Ty  : Con → Set
```

```
data Con where
  ◇ : Con
  _,_ : (Γ : Con) (A : Ty Γ) → Con
  eq : (Γ : Con) (A : Ty Γ) (B : Ty (Γ , A)) →
        ((Γ , A) , B) ≡ (Γ , Σ Γ A B)
```

```
data Ty where
  ι : (Γ : Con) → Ty Γ
  Σ : (Γ : Con) (A : Ty Γ) → Ty (Γ , A) → Ty Γ
```

Example 1.1

```
data Con : Set
data Ty  : Con → Set

data Con where
  ◊ : Con
  _,-_ : (Γ : Con) (A : Ty Γ) → Con
  eq : (Γ : Con) (A : Ty Γ) (B : Ty (Γ , A)) →
        ((Γ , A) , B) ≡ (Γ , Σ Γ A B)

data Ty where
  ι : (Γ : Con) → Ty Γ
  Σ : (Γ : Con) (A : Ty Γ) → Ty (Γ , A) → Ty Γ
```

1 Category \mathbf{A}_0 of sorts.

Example 1.1

```
data Con : Set
data Ty  : Con → Set

data Con where
  ◇ : Con
  _⊔_ : (Γ : Con) (A : Ty Γ) → Con
  eq  : (Γ : Con) (A : Ty Γ) (B : Ty (Γ , A)) →
        ((Γ , A) , B) ≡ (Γ , Σ Γ A B)

data Ty where
  ι : (Γ : Con) → Ty Γ
  Σ : (Γ : Con) (A : Ty Γ) → Ty (Γ , A) → Ty Γ
```

- 1 Category \mathbf{A}_0 of sorts.
- 2 Constructor specification. The n^{th} constructor is specified by two functors

$$L_n : \mathbf{A}_n \rightarrow \mathbf{Set},$$

$$R_n : \int L_n \rightarrow \mathbf{Set}.$$

Example 1.1

```
data Con : Set
data Ty  : Con → Set

data Con where
  ◇ : Con
  _⊔_ : (Γ : Con) (A : Ty Γ) → Con
  eq  : (Γ : Con) (A : Ty Γ) (B : Ty (Γ , A)) →
        ((Γ , A) , B) ≡ (Γ , Σ Γ A B)

data Ty where
  ι : (Γ : Con) → Ty Γ
  Σ : (Γ : Con) (A : Ty Γ) → Ty (Γ , A) → Ty Γ
```

- 1 Category \mathbf{A}_0 of sorts.
- 2 Constructor specification. The n^{th} constructor is specified by two functors

$$L_n : \mathbf{A}_n \rightarrow \mathbf{Set},$$

$$R_n : \int L_n \rightarrow \mathbf{Set}.$$

- 3 Category of algebras. \mathbf{A}_{n+1} is the category having objects of type $\sum (A : |\mathbf{A}_n|)(c : (x : L_n A) \rightarrow R_n(A, x))$.

Containerification

Goal: restrict

$$\begin{aligned} L_n &: \mathbf{A}_n \rightarrow \mathbf{Set}, \\ R_n &: \int L_n \rightarrow \mathbf{Set} \end{aligned}$$

to be container functors (+ other restrictions).

Containerification

Goal: restrict

$$\begin{aligned} L_n &: \mathbf{A}_n \rightarrow \mathbf{Set}, \\ R_n &: \int L_n \rightarrow \mathbf{Set} \end{aligned}$$

to be container functors (+ other restrictions).

Definition

Given category \mathbf{C} , a *generalised container* is a pair $S : \mathbf{Set}$, $P : S \rightarrow |\mathbf{C}|$.

The *extension functor* $\llbracket S \triangleleft P \rrbracket : \mathbf{C} \rightarrow \mathbf{Set}$ is defined by

$$\llbracket S \triangleleft P \rrbracket X := \sum (s : S)(\mathbf{C}(P\ s, X)).$$

An overview of inductive types, revisited

Class of types	Representation	Category theory semantics	Type theoretic normal form	Universal type
ordinary inductive types e.g. $\mathbb{N} : \mathbf{Set}$	functor $\mathbf{Set} \rightarrow \mathbf{Set}$	initial algebras of endofunctors on \mathbf{Set}	containers	W-type
inductive families e.g. $\mathbf{Fin} : \mathbb{N} \rightarrow \mathbf{Set}$	functor $(\mathbf{I} \rightarrow \mathbf{Set}) \rightarrow (\mathbf{I} \rightarrow \mathbf{Set})$	initial algebras of endofunctors on $\mathbf{Set}^{\mathbf{I}}$	indexed containers	WI-type
QITs e.g. $\mathbf{Con} : \mathbf{Set}$, $\mathbf{Ty} : \mathbf{Con} \rightarrow \mathbf{Set}$	sequence of functors L_n and R_n and sequence of categories of dialgebras	initial object in last constructed category of dialgebras \mathbf{A}_n	representations constructed via generalised containers	? (QW-type)

The container model

Definition

A category with families (CwF) consists of:

- A category \mathbf{C} , of contexts and context substitutions, having a terminal object.

Definition

A category with families (CwF) consists of:

- A category \mathbf{C} , of contexts and context substitutions, having a terminal object.
- A functor $Ty: \mathbf{C}^{\text{op}} \rightarrow \mathbf{Set}$.

Definition

A category with families (CwF) consists of:

- A category \mathbf{C} , of contexts and context substitutions, having a terminal object.
- A functor $Ty: \mathbf{C}^{\text{op}} \rightarrow \mathbf{Set}$.
- A functor $Tm: (\int Ty)^{\text{op}} \rightarrow \mathbf{Set}$.

Definition

A category with families (CwF) consists of:

- A category \mathbf{C} , of contexts and context substitutions, having a terminal object.
- A functor $Ty: \mathbf{C}^{\text{op}} \rightarrow \mathbf{Set}$.
- A functor $Tm: (\int Ty)^{\text{op}} \rightarrow \mathbf{Set}$.
- For every $\Gamma : |\mathbf{C}|$ and $A : Ty(\Gamma)$,
 - an object $\Gamma.A : |\mathbf{C}|$
 - a morphism $p: \Gamma.A \rightarrow \Gamma$ in \mathbf{C}
 - and a term $q : Tm(\Gamma.A, A[p])$,with a certain universal property.

($-[f]$ denotes the action of Ty and Tm on a morphism f .)

Presheaf model

- Category **Con** whose
 - objects (contexts) are presheaves $\mathbf{C}^{\text{op}} \rightarrow \mathbf{Set}$

Presheaf model

- Category **Con** whose
 - objects (contexts) are presheaves $\mathbf{C}^{\text{op}} \rightarrow \mathbf{Set}$
 - morphisms (substitutions) are natural transformations

Presheaf model

- Category **Con** whose
 - objects (contexts) are presheaves $\mathbf{C}^{\text{op}} \rightarrow \mathbf{Set}$
 - morphisms (substitutions) are natural transformations
 - terminal object (empty context) is the constant **1** presheaf.

Presheaf model

- Category **Con** whose
 - objects (contexts) are presheaves $\mathbf{C}^{\text{op}} \rightarrow \mathbf{Set}$
 - morphisms (substitutions) are natural transformations
 - terminal object (empty context) is the constant **1** presheaf.
- Types in context Γ are presheaves over $\int \Gamma$.

$$Ty: \mathbf{Con}^{\text{op}} \rightarrow \mathbf{Set}$$

$$Ty \Gamma := (\int \Gamma)^{\text{op}} \rightarrow \mathbf{Set}$$

Presheaf model

- Category **Con** whose
 - objects (contexts) are presheaves $\mathbf{C}^{\text{op}} \rightarrow \mathbf{Set}$
 - morphisms (substitutions) are natural transformations
 - terminal object (empty context) is the constant **1** presheaf.
- Types in context Γ are presheaves over $\int \Gamma$.

$$Ty: \mathbf{Con}^{\text{op}} \rightarrow \mathbf{Set}$$

$$Ty \Gamma := (\int \Gamma)^{\text{op}} \rightarrow \mathbf{Set}$$

- Terms in context Γ of type A are dependent natural transformations from Γ to A .

$$Tm: (\int Ty)^{\text{op}} \rightarrow \mathbf{Set}$$

$$Tm(\Gamma, A) := \int_{X: \mathbf{Set}} (\gamma : \Gamma X) \rightarrow A(X, \gamma)$$

Presheaf model

- Category **Con** whose
 - objects (contexts) are presheaves $\mathbf{C}^{\text{op}} \rightarrow \mathbf{Set}$
 - morphisms (substitutions) are natural transformations
 - terminal object (empty context) is the constant **1** presheaf.
- Types in context Γ are presheaves over $\int \Gamma$.

$$Ty: \mathbf{Con}^{\text{op}} \rightarrow \mathbf{Set}$$

$$Ty \Gamma := (\int \Gamma)^{\text{op}} \rightarrow \mathbf{Set}$$

- Terms in context Γ of type A are dependent natural transformations from Γ to A .

$$Tm: (\int Ty)^{\text{op}} \rightarrow \mathbf{Set}$$

$$Tm(\Gamma, A) := \int_{X: \mathbf{Set}} (\gamma : \Gamma X) \rightarrow A(X, \gamma)$$

- Context extension $(\Gamma.A) X = \sum (\gamma : \Gamma X)(A(X, \gamma))$.

Container model

- Category **Con** whose
 - objects (contexts) are set-containers $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$ with extension functor $\llbracket S \triangleleft P \rrbracket : \mathbf{Set} \rightarrow \mathbf{Set}$

Container model

- Category **Con** whose
 - objects (contexts) are set-containers $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$ with extension functor $\llbracket S \triangleleft P \rrbracket : \mathbf{Set} \rightarrow \mathbf{Set}$
 - morphisms (substitutions) are container morphisms

Container model

- Category **Con** whose
 - objects (contexts) are set-containers $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$ with extension functor $\llbracket S \triangleleft P \rrbracket : \mathbf{Set} \rightarrow \mathbf{Set}$
 - morphisms (substitutions) are container morphisms
 - terminal object (empty context) is $\mathbf{1} \triangleleft \mathbf{0}$.

Container model

- Category **Con** whose
 - objects (contexts) are set-containers $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$ with extension functor $\llbracket S \triangleleft P \rrbracket : \mathbf{Set} \rightarrow \mathbf{Set}$
 - morphisms (substitutions) are container morphisms
 - terminal object (empty context) is $\mathbf{1} \triangleleft \mathbf{0}$.
- Types in context Γ are generalised containers $S : \mathbf{Set}, P : S \rightarrow |\int \llbracket \Gamma \rrbracket|$ over $\int \llbracket \Gamma \rrbracket$, with extension functor

$$\llbracket S \triangleleft P \rrbracket : (\int \llbracket \Gamma \rrbracket) \rightarrow \mathbf{Set}.$$

Container model

- Category **Con** whose
 - objects (contexts) are set-containers $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$ with extension functor $\llbracket S \triangleleft P \rrbracket : \mathbf{Set} \rightarrow \mathbf{Set}$
 - morphisms (substitutions) are container morphisms
 - terminal object (empty context) is $\mathbf{1} \triangleleft \mathbf{0}$.
- Types in context Γ are generalised containers $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$ over $\int \llbracket \Gamma \rrbracket$, with extension functor

$$\llbracket S \triangleleft P \rrbracket : (\int \llbracket \Gamma \rrbracket) \rightarrow \mathbf{Set}.$$

- Terms in context Γ of type A are dependent natural transformations from $\llbracket \Gamma \rrbracket$ to $\llbracket A \rrbracket$.

$$Tm : (\int Ty)^{\text{op}} \rightarrow \mathbf{Set}$$

$$Tm(\Gamma, A) := \int_{X : \mathbf{Set}} (\gamma : \llbracket \Gamma \rrbracket X) \rightarrow \llbracket A \rrbracket(X, \gamma)$$

Container model

- Category **Con** whose
 - objects (contexts) are set-containers $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$ with extension functor $\llbracket S \triangleleft P \rrbracket : \mathbf{Set} \rightarrow \mathbf{Set}$
 - morphisms (substitutions) are container morphisms
 - terminal object (empty context) is $\mathbf{1} \triangleleft \mathbf{0}$.
- Types in context Γ are generalised containers $S : \mathbf{Set}, P : S \rightarrow \mathbf{Set}$ over $\int \llbracket \Gamma \rrbracket$, with extension functor

$$\llbracket S \triangleleft P \rrbracket : (\int \llbracket \Gamma \rrbracket) \rightarrow \mathbf{Set}.$$

- Terms in context Γ of type A are dependent natural transformations from $\llbracket \Gamma \rrbracket$ to $\llbracket A \rrbracket$.

$$Tm : (\int Ty)^{\text{op}} \rightarrow \mathbf{Set}$$

$$Tm(\Gamma, A) := \int_{X : \mathbf{Set}} (\gamma : \llbracket \Gamma \rrbracket X) \rightarrow \llbracket A \rrbracket(X, \gamma)$$

- Context extension
$$(\Gamma.A) X = \sum (S) (\Gamma.S)(A.SA) \triangleleft \lambda (s\Gamma, sA). (A.PA) s\Gamma sA$$

Presheaf model

- Contexts: $\mathbf{C}^{\text{op}} \rightarrow \mathbf{Set}$
- Substitutions: natural transformations
- Types: $(\int \Gamma)^{\text{op}} \rightarrow \mathbf{Set}$
- Terms:
 $\int_{X:\mathbf{Set}} (\gamma : \Gamma X) \rightarrow A(X, \gamma)$

Container model

- Contexts: $\mathbf{Set} \rightarrow \mathbf{Set}$
- Substitutions: container morphisms
- Types: $(\int \llbracket \Gamma \rrbracket) \rightarrow \mathbf{Set}$
- Terms:
 $\int_{X:\mathbf{Set}} (\gamma : \llbracket \Gamma \rrbracket X) \rightarrow \llbracket A \rrbracket(X, \gamma)$

To-dos

- Deal with coherence issues.

- Deal with coherence issues.
 - Category of set-containers has a **groupoid** (as opposed to an h-set) of objects.
 - ↪ Add coherences to the CwF.
 - ↪ Strictify objects via an inductive-recursive universe:

```
data U : Set where  
  nat : U
```

```
El : U → Set  
El nat =  $\mathbb{N}$ 
```

- Deal with coherence issues.
 - Category of set-containers has a **groupoid** (as opposed to an h-set) of objects.
 - \hookrightarrow Add coherences to the CwF.
 - \hookrightarrow Strictify objects via an inductive-recursive universe:
data U : Set where
 nat : U

El : U \rightarrow Set
El nat = \mathbb{N}
 - Strictify pullbacks and pushouts (e.g. when proving $A[f \circ g] \equiv A[f][g]$).

- Deal with coherence issues.
 - Category of set-containers has a **groupoid** (as opposed to an h-set) of objects.
 - \hookrightarrow Add coherences to the CwF.
 - \hookrightarrow Strictify objects via an inductive-recursive universe:
data U : Set where
 nat : U

El : U \rightarrow Set
El nat = \mathbb{N}
 - Strictify pullbacks and pushouts (e.g. when proving $A[f \circ g] \equiv A[f][g]$).
- For QIIT semantics, we need **Con** to be the category of generalised containers (as opposed to set-containers).

- Thorsten Altenkirch and Ambrus Kaposi's TYPES abstract 'A container model of type theory'.

- Thorsten Altenkirch and Ambrus Kaposi's TYPES abstract 'A container model of type theory'.
- Tamara von Glehn's polynomial functor model using comprehension categories.

- Thorsten Altenkirch and Ambrus Kaposi's TYPES abstract 'A container model of type theory'.
- Tamara von Glehn's polynomial functor model using comprehension categories.
- Bob Atkey and András Kovács's implementation of the same model as a CwF.

Summary

- QIITs combine set-truncated **equalities** with **induction-induction**.
- We can represent **QIITs semantically** as initial objects in a category of algebras.
- Containerification of QIIT semantics requires as a prerequisite the ability to **express any statement in type theory as a container**. This can be achieved by a **container model** of type theory.
- The container model is a **restricted version of the presheaf model**.

- QIITs combine set-truncated **equalities** with **induction-induction**.
- We can represent **QIITs semantically** as initial objects in a category of algebras.
- Containerification of QIIT semantics requires as a prerequisite the ability to **express any statement in type theory as a container**. This can be achieved by a **container model** of type theory.
- The container model is a **restricted version of the presheaf model**.

Thank you!

References I



Altenkirch, T., Capriotti, P., Dijkstra, G., Kraus, N., and Nordvall Forsberg, F. (2018).

Quotient inductive-inductive types.

In Baier, C. and Dal Lago, U., editors, *FoSSACS*, pages 293–310. Springer.



Altenkirch, T. and Kaposi, A. (2021).

A container model of type theory.

In *TYPES 2021*.



Atkey, R. (2020).

Interpreting dependent types with containers.

Talk at the MSP101 seminar, University of Strathclyde, slides at <https://bentnib.org/docs/tt-in-containers.pdf>, code at <https://gist.github.com/bobatkey/0d1f04057939905d35699f1b1c323736>.



Kovács, A. (2020).

Construction of the containers / polynomials cwf in agda.

Code at <https://gist.github.com/AndrasKovacs/cf7cc88f667c8f0087a4981f6be4eef8>.



von Glehn, T. (2015).

Polynomials and models of type theory.

PhD thesis, University of Cambridge.