

Supplement

1 Read data

The following chunk reads the data and processes it for analysis.

```
gestures <- read_csv("./data/gestures.csv")

gestures_tot <- gestures %>%
  group_by(dyad, background, months, gesture) %>%
  summarise(
    count = sum(count),
    ct = sum(ct)
  ) %>%
  ungroup() %>%
  mutate(
    gesture = factor(gesture, levels = c("reach", "point", "ho_gv"))
  ) %>%
  mutate_if(is.character, as.factor) %>%
  mutate(
    back_o = ordered(background, levels = c("English", "Bangladeshi", "Chinese"))
  )

contrasts(gestures_tot$back_o) <- "contr.treatment"

utterances <- read_csv("./data/utterances.csv")

utterances_tot <- utterances %>%
  group_by(dyad, background, months) %>%
  summarise(
    utterances = sum(utterances) # there are NAs that must be kept
  ) %>%
  ungroup() %>%
  mutate_if(is.character, as.factor) %>%
  mutate(
    back_o = ordered(background, levels = c("English", "Bangladeshi", "Chinese"))
  )

contrasts(utterances_tot$back_o) <- "contr.treatment"

hg_tot <- filter(gestures_tot, gesture == "ho_gv")
reach_tot <- filter(gestures_tot, gesture == "reach")
point_tot <- filter(gestures_tot, gesture == "point")
all_tot <- gestures_tot %>%
  group_by(dyad, back_o, months) %>%
  summarise(count = sum(count), ct = sum(ct))

hg_point_lead <- gestures_tot %>%
  dplyr::select(-ct) %>%
  spread(gesture, count) %>%
  dplyr::select(-reach) %>%
  group_by(dyad) %>%
```

```

mutate(
  lead_point = lead(point)
) %>%
filter(months != 12)

reach_point_lead <- gestures_tot %>%
  dplyr::select(-ct) %>%
  spread(gesture, count) %>%
  dplyr::select(-ho_gv) %>%
  group_by(dyad) %>%
  mutate(
    lead_point = lead(point)
  ) %>%
  filter(months != 12)

reach_point_lead <- gestures_tot %>%
  dplyr::select(-ct) %>%
  spread(gesture, count) %>%
  dplyr::select(-ho_gv) %>%
  group_by(dyad) %>%
  mutate(
    lead_point = lead(point)
  ) %>%
  filter(months != 12)

ct_point_lead <- gestures_tot %>%
  filter(gesture == "point") %>%
  dplyr::select(-gesture) %>%
  rename(point = count) %>%
  group_by(dyad) %>%
  mutate(
    lead_point = lead(point)
  ) %>%
  filter(months != 12)

utter_point_lead <- gestures_tot %>%
  filter(gesture == "point") %>%
  right_join(y = utterances_tot) %>%
  group_by(dyad) %>%
  mutate(
    lead_point = lead(count)
  ) %>%
  filter(months != 12)

pointing <- gestures_tot %>%
  dplyr::select(-ct) %>%
  spread(gesture, count)

gestures <- read_csv("./data/gestures.csv")

gestures_tot_2 <- gestures %>%
  group_by(dyad, background, months, gesture) %>%
  summarise(

```

```

    count = sum(count),
    ct = sum(ct)
  ) %>%
  ungroup() %>%
  mutate(
    gesture = factor(gesture, levels = c("reach", "point", "ho_gv"))
  ) %>%
  mutate_if(is.character, as.factor)

point <- gestures %>%
  filter(gesture == "point") %>%
  group_by(dyad, background, months) %>%
  summarise(
    count = sum(count)
  ) %>%
  ungroup() %>%
  mutate_if(is.character, as.factor)

utter_point <- left_join(utterances_tot, point) %>%
  rename(point = count)

utterances_compl <- utterances %>% na.omit()
utterances_tcompl <- utterances_tot %>% na.omit()

hgp_tot <- gestures_tot_2 %>%
  filter(gesture != "reach") %>%
  group_by(dyad, background) %>%
  summarise(hgp_tot = sum(count))

reach_tot_2 <- gestures_tot_2 %>%
  filter(gesture == "reach") %>%
  group_by(dyad, background) %>%
  summarise(reach_tot = sum(count))

vocab_gest <- gestures_tot_2 %>%
  group_by(dyad, background) %>%
  summarise(count_tot = sum(count), ct_tot = sum(ct)) %>%
  full_join(y = hgp_tot) %>%
  full_join(y = reach_tot_2)

vocab_utt <- utterances_tot %>%
  group_by(dyad, background) %>%
  summarise(utt_tot = sum(utterances))

vocab <- read_csv("../data/vocab.csv") %>%
  full_join(y = vocab_gest) %>%
  full_join(y = vocab_utt) %>%
  arrange(dyad, months) %>%
  mutate_if(is.character, as.factor)

```

2 Analysis 1a. The development of reaches, hold out and gives (HoGs), and points from 10-12 months.

For analysis 1a, we fitted a series of GAMMs using the negative binomial function. The choice of using the negative binomial rather than the Poisson distribution is justified by the overdispersion of the data (and the very long tail in the distribution). The negative binomial distribution requires the specification of the theta parameter. The parameter has been estimated from the data by fitting a generalised linear model with the negative binomial distribution using `MASS::glm.nb`.

2.1 Reaches development

The following models test cultural group.

```
reach_nb <- glm.nb(count ~ months, data = reach_tot)
```

```
reach_gam <- gam(
  count ~
    back_o +
    s(months, k = 3) +
    s(months, k = 3, by = back_o) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = reach_tot,
  method = "ML",
  family = negbin(0.986)
)
```

```
## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
```

```
summary(reach_gam)
```

```
##
## Family: Negative Binomial(0.986)
## Link function: log
##
## Formula:
## count ~ back_o + s(months, k = 3) + s(months, k = 3, by = back_o) +
##       s(months, dyad, k = 2, bs = "fs", m = 1)
##
## Parametric coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    0.6377    0.1920   3.322 0.000895 ***
## back_oBangladeshi 0.5873    0.2601   2.258 0.023930 *
## back_oChinese    0.2402    0.2650   0.906 0.364737
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Approximate significance of smooth terms:
##              edf   Ref.df Chi.sq p-value
## s(months)          1.155     1.286   1.181  0.2854
## s(months):back_oBangladeshi 1.000     1.000   0.437  0.5086
## s(months):back_oChinese    1.000     1.000   0.125  0.7237
## s(months,dyad)        14.509    112.000  20.040  0.0316 *
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## R-sq.(adj) =  0.165   Deviance explained = 21.4%
## -ML = 378.53   Scale est. = 1           n = 173


reach_gam_null <- gam(
  count ~
    # back_o +
    s(months, k = 3) +
    # s(months, k = 3, by = back_o) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = reach_tot,
  method = "ML",
  family = negbin(0.986)
)

## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.

compareML(reach_gam_null, reach_gam)

## reach_gam_null: count ~ s(months, k = 3) + s(months, dyad, k = 2, bs = "fs",
##      m = 1)
##
## reach_gam: count ~ back_o + s(months, k = 3) + s(months, k = 3, by = back_o) +
##      s(months, dyad, k = 2, bs = "fs", m = 1)
##
## Chi-square test of ML scores
## -----
##           Model      Score Edf Difference      Df p.value Sig.
## 1 reach_gam_null 381.3264    5
## 2      reach_gam 378.5345   11      2.792 6.000   0.471
##
## AIC difference: -1.91, model reach_gam_null has lower AIC.
## Warning in compareML(reach_gam_null, reach_gam): Only small difference in ML...

plot_smooths(reach_gam, months, facet_terms = back_o, series_length = 25)
```



The following models test time sample.

```
reach_gam_2 <- gam(
  count ~
    s(months, k = 3) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = reach_tot,
  method = "ML",
  family = negbin(0.1946)
)
```

```
## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
```

```
reach_gam_2_null <- gam(
  count ~
    # s(months, k = 3) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = reach_tot,
  method = "ML",
  family = negbin(0.1946)
)
compareML(reach_gam_2_null, reach_gam_2)
```

```
## reach_gam_2_null: count ~ s(months, dyad, k = 2, bs = "fs", m = 1)
##
## reach_gam_2: count ~ s(months, k = 3) + s(months, dyad, k = 2, bs = "fs",
##      m = 1)
##
```

```
## Chi-square test of ML scores
## -----
##           Model      Score Edf Difference      Df p.value Sig.
## 1 reach_gam_2_null 431.9091   3
## 2      reach_gam_2 431.7370   5      0.172 2.000   0.842
##
## AIC difference: -1.66, model reach_gam_2_null has lower AIC.
## Warning in compareML(reach_gam_2_null, reach_gam_2): Only small difference in ML...
```

2.2 HGs development

The following models test cultural group.

```
hg_nb <- glm.nb(count ~ months, data = hg_tot)
```

```
hg_gam <- gam(
  count ~
    back_o +
    s(months, k = 3) +
    s(months, k = 3, by = back_o) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = hg_tot,
  method = "ML",
  family = negbin(0.6434)
)
```

```
## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
```

```
summary(hg_gam)
```

```
##
## Family: Negative Binomial(0.643)
## Link function: log
##
## Formula:
## count ~ back_o + s(months, k = 3) + s(months, k = 3, by = back_o) +
##       s(months, dyad, k = 2, bs = "fs", m = 1)
##
## Parametric coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    0.7491     0.2316   3.234  0.00122 **
## back_oBangladeshi 0.9117     0.3143   2.901  0.00372 **
## back_oChinese    0.7257     0.3163   2.295  0.02176 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Approximate significance of smooth terms:
##              edf Ref.df Chi.sq p-value
## s(months)          1.0      1  9.707 0.00184 **
## s(months):back_oBangladeshi 1.0      1  0.025 0.87559
## s(months):back_oChinese    1.0      1  0.426 0.51391
## s(months,dyad)          17.7     112 26.330 0.01075 *
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## R-sq.(adj) =  0.335   Deviance explained = 38.5%
## -ML = 451.06   Scale est. = 1           n = 173


hg_gam_null <- gam(
  count ~
    # back_o +
    s(months, k = 3) +
    # s(months, k = 3, by = back_o) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = hg_tot,
  method = "ML",
  family = negbin(0.6434)
)

## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.


compareML(hg_gam_null, hg_gam)

## hg_gam_null: count ~ s(months, k = 3) + s(months, dyad, k = 2, bs = "fs",
##      m = 1)
##
## hg_gam: count ~ back_o + s(months, k = 3) + s(months, k = 3, by = back_o) +
##      s(months, dyad, k = 2, bs = "fs", m = 1)
##
## Chi-square test of ML scores
## -----
##      Model      Score Edf Difference    Df p.value Sig.
## 1 hg_gam_null 455.3697   5
## 2      hg_gam 451.0601  11      4.310 6.000   0.196
##
## AIC difference: -2.20, model hg_gam_null has lower AIC.
## Warning in compareML(hg_gam_null, hg_gam): Only small difference in ML...

plot_smooths(hg_gam, months, facet_terms = back_o, series_length = 25)
```

```
plot_smooths(hg_gam_2, months, series_length = 25)
```



The following models test time sample.

```
hg_gam_2 <- gam(
  count ~
    s(months, k = 3) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = hg_tot,
  method = "ML",
  family = negbin(0.1946)
)
```

```
## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
```

```
hg_gam_2_null <- gam(
  count ~
    # s(months, k = 3) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = hg_tot,
  method = "ML",
  family = negbin(0.1946)
)
compareML(hg_gam_2_null, hg_gam_2)
```

```
## hg_gam_2_null: count ~ s(months, dyad, k = 2, bs = "fs", m = 1)
##
## hg_gam_2: count ~ s(months, k = 3) + s(months, dyad, k = 2, bs = "fs",
##      m = 1)
##
## Chi-square test of ML scores
## -----
##           Model      Score Edf Difference    Df p.value Sig.
## 1 hg_gam_2_null 501.9866    3
## 2      hg_gam_2 497.7652    5      4.221 2.000  0.015  *
##
## AIC difference: 6.44, model hg_gam_2 has lower AIC.
## Warning in compareML(hg_gam_2_null, hg_gam_2): Only small difference in ML...
```

2.3 Points development

The following models test cultural group.

```
point_nb <- glm.nb(count ~ months, data = point_tot)

point_gam <- gam(
  count ~
    back_o +
    s(months, k = 3) +
    s(months, k = 3, by = back_o) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = point_tot,
  method = "ML",
  family = negbin(0.1946)
)
```

```
## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
```

```
summary(point_gam)
```

```
##
## Family: Negative Binomial(0.195)
## Link function: log
##
## Formula:
## count ~ back_o + s(months, k = 3) + s(months, k = 3, by = back_o) +
##       s(months, dyad, k = 2, bs = "fs", m = 1)
##
## Parametric coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    0.6917    0.3953   1.750   0.0802 .
## back_oBangladeshi -0.4993    0.5588  -0.894   0.3716
## back_oChinese    -0.5735    0.5675  -1.011   0.3122
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Approximate significance of smooth terms:
##              edf   Ref.df Chi.sq p-value
## s(months)          1.000     1.000   1.068   0.3014
## s(months):back_oBangladeshi 1.538     1.786   0.726   0.5736
## s(months):back_oChinese     1.000     1.000   2.118   0.1456
## s(months,dyad)        18.373    112.000  26.009   0.0224 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## R-sq.(adj) =  0.332   Deviance explained =  41%
## -ML = 326.23   Scale est. = 1           n = 173
```


```
point_gam_null <- gam(
  count ~
    # back_o +
    s(months, k = 3) +
    # s(months, k = 3, by = back_o) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = point_tot,
  method = "ML",
  family = negbin(0.1946)
)
```

```
## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
```


```
compareML(point_gam_null, point_gam)
```

```
## point_gam_null: count ~ s(months, k = 3) + s(months, dyad, k = 2, bs = "fs",
##       m = 1)
##
## point_gam: count ~ back_o + s(months, k = 3) + s(months, k = 3, by = back_o) +
##       s(months, dyad, k = 2, bs = "fs", m = 1)
##
## Chi-square test of ML scores
```

```
## -----
##           Model      Score Edf Difference    Df p.value Sig.
## 1 point_gam_null 327.9346   5
## 2      point_gam 326.2345  11      1.700 6.000   0.757
##
## AIC difference: -7.40, model point_gam_null has lower AIC.
## Warning in compareML(point_gam_null, point_gam): Only small difference in ML...
plot_smooths(point_gam, months, facet_terms = back_o, series_length = 25)
```



```
plot_smooths(point_gam_2, months, series_length = 25)
```



The following models test time sample.

```
point_gam_2 <- gam(
  count ~
    s(months, k = 3) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = point_tot,
  method = "ML",
  family = negbin(0.1946)
)
```

```
## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
```

```
point_gam_2_null <- gam(
  count ~
    # s(months, k = 3) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = point_tot,
  method = "ML",
  family = negbin(0.1946)
)
compareML(point_gam_2_null, point_gam_2)
```

```
## point_gam_2_null: count ~ s(months, dyad, k = 2, bs = "fs", m = 1)
##
## point_gam_2: count ~ s(months, k = 3) + s(months, dyad, k = 2, bs = "fs",
##      m = 1)
##
```

```
## Chi-square test of ML scores
## -----
##           Model      Score Edf Difference      Df p.value Sig.
## 1 point_gam_2_null 332.5507   3
## 2      point_gam_2 327.9346   5      4.616 2.000  0.010  **
##
## AIC difference: 10.13, model point_gam_2 has lower AIC.
## Warning in compareML(point_gam_2_null, point_gam_2): Only small difference in ML...
```

3 Analysis 1b. Frequency of maternal utterances and contingent talk to infants aged 10-12 months.

For maternal utterances we used a normal distribution, since the distribution of the data was almost normal. For maternal contingent talks instead we used again the negative binomial distribution for the same reasons as above.

3.1 Maternal utterances development

The following models test cultural group.

```
utter_gam <- gam(
  utterances ~
    back_o +
    s(months, k = 3) +
    s(months, k = 3, by = back_o) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = utterances_tot,
  method = "ML"
)

## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
summary(utter_gam)

##
## Family: gaussian
## Link function: identity
##
## Formula:
## utterances ~ back_o + s(months, k = 3) + s(months, k = 3, by = back_o) +
##      s(months, dyad, k = 2, bs = "fs", m = 1)
##
## Parametric coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    284.44     27.10  10.494  <2e-16 ***
## back_oBangladeshi -65.59     37.82  -1.734   0.0865 .
## back_oChinese    -37.80     37.74  -1.002   0.3193
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Approximate significance of smooth terms:
```

```

##              edf  Ref.df      F p-value
## s(months)      1.693   1.880 0.966   0.333
## s(months):back_oBangladeshi 1.001   1.001 1.065   0.305
## s(months):back_oChinese     1.334   1.533 1.924   0.107
## s(months,dyad)      73.930 111.000 7.087  <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## R-sq.(adj) =  0.837   Deviance explained = 91.6%
## -ML = 991.97   Scale est. = 2827.4       n = 167

utter_gam_null <- gam(
  utterances ~
    # back_o +
    s(months, k = 3) +
    # s(months, k = 3, by = back_o) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = utterances_tot,
  method = "ML"
)


## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.

compareML(utter_gam_null, utter_gam)

## utter_gam_null: utterances ~ s(months, k = 3) + s(months, dyad, k = 2, bs = "fs",
##      m = 1)
##
##
## utter_gam: utterances ~ back_o + s(months, k = 3) + s(months, k = 3, by = back_o) +
##      s(months, dyad, k = 2, bs = "fs", m = 1)
##
## Chi-square test of ML scores
## -----
##           Model      Score Edf Difference      Df p.value Sig.
## 1 utter_gam_null 995.3291    5
## 2      utter_gam 991.9724   11      3.357 6.000   0.348
##
## AIC difference: -3.68, model utter_gam_null has lower AIC.
## Warning in compareML(utter_gam_null, utter_gam): Only small difference in ML...

plot_smooths(utter_gam, months, facet_terms = back_o, series_length = 10)

```



The following models test time sample.

```
utter_gam_2 <- gam(
  utterances ~
    s(months, k = 3) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = utterances_tot,
  method = "ML"
)
```

```
## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
```

```
utter_gam_2_null <- gam(
  utterances ~
    # s(months, k = 3) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = utterances_tot,
  method = "ML"
)
```

```
compareML(utter_gam_2_null, utter_gam_2)
```

```
## utter_gam_2_null: utterances ~ s(months, dyad, k = 2, bs = "fs", m = 1)
##
## utter_gam_2: utterances ~ s(months, k = 3) + s(months, dyad, k = 2, bs = "fs",
##   m = 1)
##
## Chi-square test of ML scores
```



```
## -----
##           Model      Score Edf Difference      Df p.value Sig.
## 1 utter_gam_2_null 997.9664   3
## 2      utter_gam_2 995.3291   5      2.637 2.000   0.072
##
## AIC difference: 6.07, model utter_gam_2 has lower AIC.
## Warning in compareML(utter_gam_2_null, utter_gam_2): Only small difference in ML...
```

3.2 Contingent talks development

The following models test cultural group.

```
ct_nb <- glm.nb(ct ~ months, data = all_tot)
```

```
ct_gam <- gam(
  ct ~
    back_o +
    s(months, k = 3) +
    s(months, k = 3, by = back_o) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = all_tot,
  method = "ML",
  family = negbin(0.3845)
)
```

```
## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
```

```
summary(ct_gam)
```

```
##
## Family: Negative Binomial(0.384)
## Link function: log
##
## Formula:
## ct ~ back_o + s(months, k = 3) + s(months, k = 3, by = back_o) +
##       s(months, dyad, k = 2, bs = "fs", m = 1)
##
## Parametric coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    0.6528    0.2977   2.193   0.0283 *
## back_oBangladeshi -0.9863    0.4347  -2.269   0.0233 *
## back_oChinese    -0.2083    0.4226  -0.493   0.6221
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Approximate significance of smooth terms:
##              edf   Ref.df Chi.sq p-value
## s(months)         1.00     1.000   3.039 0.08130 .
## s(months):back_oBangladeshi 1.75     1.937   3.064 0.24025
## s(months):back_oChinese     1.00     1.000   0.391 0.53191
## s(months,dyad)        18.38    112.000  27.596 0.00938 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
##
## R-sq.(adj) = 0.394   Deviance explained = 43.7%
## -ML = 315.49   Scale est. = 1           n = 172


ct_gam_null <- gam(
  ct ~
    # back_o +
    s(months, k = 3) +
    # s(months, k = 3, by = back_o) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = all_tot,
  method = "ML",
  family = negbin(0.3845)
)

## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.

compareML(ct_gam_null, ct_gam)

## ct_gam_null: ct ~ s(months, k = 3) + s(months, dyad, k = 2, bs = "fs", m = 1)
##
## ct_gam: ct ~ back_o + s(months, k = 3) + s(months, k = 3, by = back_o) +
##   s(months, dyad, k = 2, bs = "fs", m = 1)
##
## Chi-square test of ML scores
## -----
##           Model      Score Edf Difference    Df p.value Sig.
## 1 ct_gam_null 318.9151    5
## 2      ct_gam 315.4869   11      3.428 6.000   0.334
##
## AIC difference: 0.60, model ct_gam has lower AIC.
## Warning in compareML(ct_gam_null, ct_gam): Only small difference in ML...

plot_smooths(ct_gam, months, facet_terms = back_o, series_length = 10)
```



The following models test time sample.

```
ct_gam_2 <- gam(
  count ~
    s(months, k = 3) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = all_tot,
  method = "ML",
  family = negbin(0.3845)
)
```

```
## Warning in gam.side(sm, X, tol = .Machine$double.eps^0.5): model has
## repeated 1-d smooths of same variable.
```

```
ct_gam_2_null <- gam(
  count ~
    # s(months, k = 3) +
    s(months, dyad, k = 2, bs = "fs", m = 1),
  data = all_tot,
  method = "ML",
  family = negbin(0.3845)
)
```

```
compareML(ct_gam_2_null, ct_gam_2)
```

```
## ct_gam_2_null: count ~ s(months, dyad, k = 2, bs = "fs", m = 1)
##
## ct_gam_2: count ~ s(months, k = 3) + s(months, dyad, k = 2, bs = "fs",
##      m = 1)
```

```
##
## Chi-square test of ML scores
## -----
##           Model      Score Edf Difference    Df p.value Sig.
## 1 ct_gam_2_null 641.7191    3
## 2      ct_gam_2 637.2383    5      4.481 2.000  0.011  *
##
## AIC difference: 6.96, model ct_gam_2 has lower AIC.
## Warning in compareML(ct_gam_2_null, ct_gam_2): Only small difference in ML...
```

4 Analysis 1c. Predictors of pointing at 12 months

The following GLMMs test the relation between pointing as the outcome variable and reaches/HoGs.

4.1 Reaches


```
reach_point_lead_nb <- glm.nb(lead_point ~ reach, data = reach_point_lead)

reach_point_lm <- glmer(
  lead_point ~
    reach *
    background +
    (1|dyad),
  data = reach_point_lead,
  family = negbin(0.2681)
)
summary(reach_point_lm)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: Negative Binomial(0.268) ( log )
## Formula: lead_point ~ reach * background + (1 | dyad)
## Data: reach_point_lead
##
##      AIC      BIC   logLik deviance df.resid
##    523.3    545.1   -253.7   507.3     104
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -0.5066 -0.4982 -0.3934  0.1437  3.0203
##
## Random effects:
## Groups Name      Variance Std.Dev.
## dyad   (Intercept) 0.1569   0.396
## Number of obs: 112, groups: dyad, 57
##
## Fixed effects:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    0.72163    0.60141   1.200   0.230
## reach          0.06136    0.09716   0.632   0.528
## backgroundChinese 1.10777    0.72841   1.521   0.128
```


```
## backgroundEnglish      0.84357    0.68166    1.238    0.216
## reach:backgroundChinese -0.24686    0.16105   -1.533    0.125
## reach:backgroundEnglish -0.08716    0.13746   -0.634    0.526
##
## Correlation of Fixed Effects:
##          (Intr) reach  bckgrC bckgrE rch:bC
## reach      -0.724
## bckgrndChns -0.709  0.550
## bckgrndEngl -0.557  0.506  0.508
## rch:bckgrnC  0.453 -0.610 -0.710 -0.298
## rch:bckgrnE  0.449 -0.681 -0.366 -0.599  0.412
```

```
plot(fitted(reach_point_lm), residuals(reach_point_lm))
```




```
qqnorm(residuals(reach_point_lm))
```

Normal Q-Q Plot




```
reach_eff <- as_tibble(effect("reach:background", reach_point_lm, xlevels = 100))

ggplot(reach_eff, aes(reach, fit)) +
  geom_ribbon(aes(ymax = upper, ymin = lower), alpha = 0.2) +
  geom_line() +
  facet_grid(~ background) +
  coord_cartesian(ylim = c(0, 100))
```



```
ggplot(reach_eff, aes(reach, fit)) +
  geom_ribbon(aes(ymax = upper, ymin = lower), alpha = 0.2) +
  geom_line() +
  facet_grid(~ background) +
  coord_cartesian(ylim = c(0, 20))
```



4.2 HoGs

```
hg_point_lead_nb <- glm.nb(lead_point ~ ho_gv, data = filter(hg_point_lead, ho_gv < 20))

hg_point_lm <- glmer(
  lead_point ~
    ho_gv *
    background +
    (1|dyad),
  data = filter(hg_point_lead, ho_gv < 20),
  family = negbin(0.2606)
)
```

```
## singular fit
```

```
summary(hg_point_lm)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: Negative Binomial(0.261) ( log )
## Formula: lead_point ~ ho_gv * background + (1 | dyad)
## Data: filter(hg_point_lead, ho_gv < 20)
##
##      AIC      BIC   logLik deviance df.resid
##    503.8    525.3   -243.9   487.8     101
##
## Scaled residuals:
```



```


##      Min      1Q  Median      3Q      Max
## -0.5080 -0.4942 -0.3979  0.1241  6.0969
##
## Random effects:
##   Groups Name      Variance Std.Dev.
## dyad   (Intercept) 1.41e-10 1.187e-05
## Number of obs: 109, groups: dyad, 57
##
## Fixed effects:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)      1.37529    0.46393   2.964  0.00303 **
## ho_gv            -0.10718    0.08031  -1.335  0.18200
## backgroundChinese  0.11400    0.68904   0.165  0.86859
## backgroundEnglish -0.22613    0.62893  -0.360  0.71919
## ho_gv:backgroundChinese 0.12680    0.13875   0.914  0.36081
## ho_gv:backgroundEnglish 0.31880    0.15566   2.048  0.04056 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) ho_gv  bckgrC bckgrE h_gv:C
## ho_gv          -0.681
## bckgrndChns    -0.673  0.459
## bckgrndEngl    -0.738  0.502  0.497
## h_gv:bckgrC    0.394 -0.579 -0.714 -0.291
## h_gv:bckgrE    0.351 -0.516 -0.237 -0.621  0.299
## convergence code: 0
## singular fit

hg_point_lm_null <- glmer(
  lead_point ~
    ho_gv +
    background +
    (1|dyad),
  data = filter(hg_point_lead, ho_gv < 20),
  family = negbin(0.2606)
)
anova(hg_point_lm_null, hg_point_lm)

## Data: filter(hg_point_lead, ho_gv < 20)
## Models:
## hg_point_lm_null: lead_point ~ ho_gv + background + (1 | dyad)
## hg_point_lm: lead_point ~ ho_gv * background + (1 | dyad)
##              Df    AIC    BIC logLik deviance Chisq Chi Df
## hg_point_lm_null  6 504.69 520.84 -246.35  492.69
## hg_point_lm       8 503.79 525.32 -243.89  487.79 4.9055      2
##              Pr(>Chisq)
## hg_point_lm_null
## hg_point_lm      0.08606 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1


plot(fitted(hg_point_lm), residuals(hg_point_lm))

```



```
qqnorm(residuals(hg_point_lm))
```


Normal Q-Q Plot




```
hg_eff <- as_tibble(effect("ho_gv:background", hg_point_lm, xlevels = 100))
```

```
ggplot(hg_eff, aes(ho_gv, fit)) +  
  geom_ribbon(aes(ymax = upper, ymin = lower), alpha = 0.2) +  
  geom_line() +  
  facet_grid(~ background) +
```

```
coord_cartesian(ylim = c(0, 100))
```



```
ggplot(hg_eff, aes(ho_gv, fit)) +  
  geom_ribbon(aes(ymax = upper, ymin = lower), alpha = 0.2) +  
  geom_line() +  
  facet_grid(~ background) +  
  coord_cartesian(ylim = c(0, 20))
```



5 Analysis 2. Predictors of vocabulary scores at 12 and 18 months

5.1 Comprehension at 12 and 18 months

5.1.1 All gestures combined

```
all_gest_lm <- lmer(
  understand ~
    count_tot *
    months *
    background +
    (1|dyad),
  data = vocab
)
summary(all_gest_lm)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: understand ~ count_tot * months * background + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1180.8
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
```

```

## -1.74717 -0.54694 0.01362 0.40251 1.85188
##
## Random effects:
## Groups Name Variance Std.Dev.
## dyad (Intercept) 2671 51.68
## Residual 2299 47.95
## Number of obs: 109, groups: dyad, 55
##
## Fixed effects:
## Estimate Std. Error df
## (Intercept) -11.53326 90.20899 60.50470
## count_tot -1.71945 2.03317 60.50470
## months 10.30257 5.65012 47.87064
## backgroundChinese -215.33019 116.59958 60.50470
## backgroundEnglish -90.30873 106.47214 60.64043
## count_tot:months 0.11738 0.12734 47.87064
## count_tot:backgroundChinese 3.78521 2.52892 60.50470
## count_tot:backgroundEnglish -0.24189 2.31867 60.53955
## months:backgroundChinese 9.90219 7.30306 47.87064
## months:backgroundEnglish 6.81052 6.69456 48.26704
## count_tot:months:backgroundChinese -0.10980 0.15840 47.87064
## count_tot:months:backgroundEnglish 0.01585 0.14537 47.97274
## t value Pr(>|t|)
## (Intercept) -0.128 0.8987
## count_tot -0.846 0.4011
## months 1.823 0.0745 .
## backgroundChinese -1.847 0.0697 .
## backgroundEnglish -0.848 0.3997
## count_tot:months 0.922 0.3613
## count_tot:backgroundChinese 1.497 0.1397
## count_tot:backgroundEnglish -0.104 0.9173
## months:backgroundChinese 1.356 0.1815
## months:backgroundEnglish 1.017 0.3141
## count_tot:months:backgroundChinese -0.693 0.4915
## count_tot:months:backgroundEnglish 0.109 0.9136
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
## (Intr) cnt_tt months bckgrC bckgrE cnt_t: cnt_:C cnt_:E mnth:C
## count_tot -0.888
## months -0.940 0.835
## bckgrndChns -0.774 0.687 0.727
## bckgrndEngl -0.847 0.753 0.796 0.655
## cnt_tt:mnth 0.835 -0.940 -0.888 -0.646 -0.707
## cnt_tt:bckC 0.714 -0.804 -0.671 -0.861 -0.605 0.755
## cnt_tt:bckE 0.779 -0.877 -0.732 -0.603 -0.826 0.824 0.705
## mnths:bckgC 0.727 -0.646 -0.774 -0.940 -0.616 0.687 0.809 0.566
## mnths:bckgE 0.793 -0.705 -0.844 -0.613 -0.940 0.750 0.566 0.775 0.653
## cnt_tt:mn:C -0.671 0.755 0.714 0.809 0.569 -0.804 -0.940 -0.662 -0.861
## cnt_tt:mn:E -0.731 0.823 0.778 0.566 0.777 -0.876 -0.662 -0.940 -0.602
## mnth:E cn_::C
## count_tot
## months

```

```


## bckgrndChns
## bckgrndEngl
## cnt_tt:mnth
## cnt_tt:bckC
## cnt_tt:bckE
## mnths:bckgC
## mnths:bckgE
## cnt_tt:mn:C -0.603
## cnt_tt:mn:E -0.825  0.704

all_gest_lm_2 <- lmer(
  understand ~
    count_tot *
    months +
    (1|dyad),
  data = vocab
)
summary(all_gest_lm_2)

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: understand ~ count_tot * months + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1220.4
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.53820 -0.47681 -0.09134  0.45523  1.97984
##
## Random effects:
## Groups Name Variance Std.Dev.
## dyad (Intercept) 3279 57.26
## Residual 2365 48.63
## Number of obs: 109, groups: dyad, 55
##
## Fixed effects:
##              Estimate Std. Error      df t value Pr(>|t|)
## (Intercept)   -103.79077   40.02556   67.41098  -2.593  0.0117 *
## count_tot      -0.64884    0.83279   67.33012  -0.779  0.4386
## months         15.56858    2.50342   52.42242   6.219 8.42e-08 ***
## count_tot:months  0.08750    0.05192   52.11407   1.685  0.0979 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) cnt_tt months
## count_tot   -0.781
## months      -0.933  0.728
## cnt_tt:mnth  0.731 -0.932 -0.783

plot_model(all_gest_lm_2, type = "pred", terms = c("count_tot", "months"))

```



5.1.2 HoGs + points

```
hgp_lm <- lmer(
  understand ~
    hgp_tot *
    months *
    background +
    (1|dyad),
  data = vocab
)
summary(hgp_lm)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: understand ~ hgp_tot * months * background + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1183.1
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.64675 -0.51967 -0.00448  0.42619  1.76485
##
## Random effects:
## Groups   Name                Variance Std.Dev.
```

```

## dyad      (Intercept) 2890      53.75
## Residual          2304      48.00
## Number of obs: 109, groups: dyad, 55
##
## Fixed effects:
##
##              Estimate Std. Error      df t value
## (Intercept)    -3.025e+01  7.880e+01  6.121e+01  -0.384
## hgp_tot        -1.743e+00  2.377e+00  6.121e+01  -0.733
## months         1.113e+01  4.919e+00  4.790e+01   2.262
## backgroundChinese -1.724e+02  1.018e+02  6.121e+01  -1.694
## backgroundEnglish -8.627e+01  9.437e+01  6.133e+01  -0.914
## hgp_tot:months   1.350e-01  1.484e-01  4.790e+01   0.910
## hgp_tot:backgroundChinese 3.597e+00  2.822e+00  6.121e+01   1.275
## hgp_tot:backgroundEnglish -1.949e-01  2.624e+00  6.123e+01  -0.074
## months:backgroundChinese 9.052e+00  6.353e+00  4.790e+01   1.425
## months:backgroundEnglish 7.037e+00  5.916e+00  4.830e+01   1.189
## hgp_tot:months:backgroundChinese -1.246e-01  1.762e-01  4.790e+01  -0.707
## hgp_tot:months:backgroundEnglish -5.375e-03  1.639e-01  4.797e+01  -0.033
##
##              Pr(>|t|)
## (Intercept)      0.7024
## hgp_tot          0.4664
## months          0.0283 *
## backgroundChinese 0.0954 .
## backgroundEnglish 0.3642
## hgp_tot:months   0.3676
## hgp_tot:backgroundChinese 0.2073
## hgp_tot:backgroundEnglish 0.9410
## months:backgroundChinese 0.1607
## months:backgroundEnglish 0.2401
## hgp_tot:months:backgroundChinese 0.4829
## hgp_tot:months:backgroundEnglish 0.9740
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) hgp_tt months bckgrC bckgrE hgp_t: hgp_:C hgp_:E mnth:C
## hgp_tot      -0.850
## months       -0.936  0.796
## bckgrndChns -0.774  0.658  0.725
## bckgrndEngl -0.835  0.709  0.782  0.647
## hgp_tt:mnth  0.796 -0.936 -0.850 -0.616 -0.664
## hgp_tt:bckC  0.716 -0.842 -0.670 -0.809 -0.597  0.789
## hgp_tt:bckE  0.770 -0.906 -0.721 -0.596 -0.771  0.848  0.763
## mnths:bckgC  0.725 -0.616 -0.774 -0.936 -0.605  0.658  0.758  0.558
## mnths:bckgE  0.779 -0.661 -0.831 -0.603 -0.937  0.706  0.557  0.721  0.644
## hgp_tt:mn:C -0.670  0.789  0.716  0.758  0.559 -0.842 -0.936 -0.715 -0.809
## hgp_tt:mn:E -0.720  0.848  0.769  0.558  0.724 -0.905 -0.714 -0.937 -0.596
##
##              mnth:E hg_::C
## hgp_tot
## months
## bckgrndChns
## bckgrndEngl
## hgp_tt:mnth
## hgp_tt:bckC

```



```


## hgp_tt:bckE
## mnths:bckgC
## mnths:bckgE
## hgp_tt:mn:C -0.595
## hgp_tt:mn:E -0.771 0.763

hgp_lm_2 <- lmer(
  understand ~
    hgp_tot *
    months +
    (1|dyad),
  data = vocab
)
summary(hgp_lm_2)

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: understand ~ hgp_tot * months + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1220.2
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.48779 -0.47461 -0.06162  0.46424  1.92329
##
## Random effects:
## Groups Name Variance Std.Dev.
## dyad (Intercept) 3315 57.58
## Residual 2349 48.47
## Number of obs: 109, groups: dyad, 55
##
## Fixed effects:
## Estimate Std. Error df t value Pr(>|t|)
## (Intercept) -106.62133 34.78108 67.61030 -3.065 0.00312 **
## hgp_tot -0.75634 0.84955 67.53140 -0.890 0.37648
## months 16.16696 2.17268 52.40323 7.441 9.39e-10 ***
## hgp_tot:months 0.09424 0.05290 52.09060 1.782 0.08065 .
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
## (Intr) hgp_tot months
## hgp_tot -0.698
## months -0.932 0.650
## hgp_tot:mnth 0.652 -0.932 -0.700

plot_model(hgp_lm_2, type = "pred", terms = c("hgp_tot", "months"))

```



5.1.3 Reaches

```
reach_lm <- lmer(
  understand ~
    reach_tot *
    months *
    background +
    (1|dyad),
  data = vocab
)
summary(reach_lm)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: understand ~ reach_tot * months * background + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1178.6
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.77264 -0.51430  0.02511  0.54580  1.62157
##
## Random effects:
## Groups   Name                Variance Std.Dev.
```

```

## dyad      (Intercept) 3654      60.45
## Residual          2485      49.85
## Number of obs: 109, groups: dyad, 55
##
## Fixed effects:
##
##              Estimate Std. Error      df t value
## (Intercept)    -31.8808    86.6703   62.7555  -0.368
## reach_tot       -4.2115     6.6556   62.7555  -0.633
## months          12.9846     5.3702   47.8794   2.418
## backgroundChinese -163.7787   118.8588   62.7555  -1.378
## backgroundEnglish -138.0321   108.6959   62.8027  -1.270
## reach_tot:months    0.1727     0.4124   47.8794   0.419
## reach_tot:backgroundChinese 10.3022    10.4027   62.7555   0.990
## reach_tot:backgroundEnglish  4.5599     9.4843   62.7579   0.481
## months:backgroundChinese  8.1027     7.3647   47.8794   1.100
## months:backgroundEnglish  8.3412     6.7510   48.0873   1.236
## reach_tot:months:backgroundChinese -0.2407    0.6446   47.8794  -0.373
## reach_tot:months:backgroundEnglish -0.1323    0.5877   47.8900  -0.225
##
##              Pr(>|t|)
## (Intercept)      0.7142
## reach_tot        0.5292
## months          0.0195 *
## backgroundChinese 0.1731
## backgroundEnglish 0.2088
## reach_tot:months 0.6772
## reach_tot:backgroundChinese 0.3258
## reach_tot:backgroundEnglish 0.6323
## months:backgroundChinese 0.2767
## months:backgroundEnglish 0.2226
## reach_tot:months:backgroundChinese 0.7105
## reach_tot:months:backgroundEnglish 0.8229
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) rch_tt months bckgrC bckgrE rch_t: rch_:C rch_:E mnth:C
## reach_tot    -0.865
## months       -0.929  0.804
## bckgrndChns -0.729  0.631  0.678
## bckgrndEngl -0.797  0.690  0.741  0.581
## rch_tt:mnth  0.804 -0.929 -0.865 -0.586 -0.641
## rch_tt:bckC  0.553 -0.640 -0.514 -0.843 -0.441  0.595
## rch_tt:bckE  0.607 -0.702 -0.564 -0.443 -0.795  0.652  0.449
## mnths:bckgC  0.678 -0.586 -0.729 -0.929 -0.540  0.631  0.783  0.411
## mnths:bckgE  0.739 -0.639 -0.795 -0.539 -0.930  0.688  0.409  0.738  0.580
## rch_tt:mn:C -0.514  0.595  0.553  0.783  0.410 -0.640 -0.929 -0.417 -0.843
## rch_tt:mn:E -0.564  0.652  0.607  0.411  0.739 -0.702 -0.417 -0.929 -0.443
##
##              mnth:E rc_:C
## reach_tot
## months
## bckgrndChns
## bckgrndEngl
## rch_tt:mnth
## rch_tt:bckC

```

```


## rch_tt:bckE
## mnths:bckgC
## mnths:bckgE
## rch_tt:mn:C -0.440
## rch_tt:mn:E -0.794  0.449

reach_lm_2 <- lmer(
  understand ~
    reach_tot *
    months +
    (1|dyad),
  data = vocab
)
summary(reach_lm_2)

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: understand ~ reach_tot * months + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1221.3
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.5140 -0.5941 -0.0561  0.5158  1.7552
##
## Random effects:
## Groups Name Variance Std.Dev.
## dyad (Intercept) 3640 60.34
## Residual 2473 49.73
## Number of obs: 109, groups: dyad, 55
##
## Fixed effects:
##              Estimate Std. Error      df t value Pr(>|t|)
## (Intercept) -143.62983  43.54107  68.11489  -3.299  0.00155 **
## reach_tot    1.65200   3.91756  68.06536   0.422  0.67458
## months      19.44798   2.70583  52.22044   7.187 2.43e-09 ***
## reach_tot:months -0.06093   0.24289  52.00199  -0.251  0.80291
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) rch_tt months
## reach_tot    -0.809
## months      -0.930  0.751
## rch_tt:mnth  0.753 -0.929 -0.809

plot_model(reach_lm_2, type = "pred", terms = c("reach_tot", "months"))

```



5.1.4 Maternal utterances

```
utt_lm <- lmer(
  understand ~
    utt_tot *
    months *
    background +
    (1|dyad),
  data = vocab
)
```

```
## Warning: Some predictor variables are on very different scales: consider
## rescaling
```

```
## Warning: Some predictor variables are on very different scales: consider
## rescaling
```

```
summary(utt_lm)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: understand ~ utt_tot * months * background + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1111.2
##
```

```

## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.51565 -0.49198  0.00639  0.48531  1.73592
##
## Random effects:
##      Groups   Name      Variance Std.Dev.
## dyad      (Intercept) 3872      62.23
## Residual                2410      49.09
## Number of obs: 99, groups: dyad, 50
##
## Fixed effects:
##
##              Estimate Std. Error    df t value
## (Intercept)    -8.473e+01  7.748e+01  5.740e+01  -1.094
## utt_tot         6.841e-03  1.028e-01  5.740e+01   0.067
## months         1.444e+01  4.778e+00  4.322e+01   3.021
## backgroundChinese -1.069e+02  1.257e+02  5.740e+01  -0.851
## backgroundEnglish  1.413e+02  2.405e+02  5.764e+01   0.587
## utt_tot:months    1.704e-03  6.341e-03  4.322e+01   0.269
## utt_tot:backgroundChinese  5.678e-02  1.572e-01  5.740e+01   0.361
## utt_tot:backgroundEnglish -2.117e-01  2.786e-01  5.756e+01  -0.760
## months:backgroundChinese  6.038e+00  7.750e+00  4.322e+01   0.779
## months:backgroundEnglish  1.574e+00  1.511e+01  4.459e+01   0.104
## utt_tot:months:backgroundChinese -1.938e-03  9.693e-03  4.322e+01  -0.200
## utt_tot:months:backgroundEnglish  1.116e-03  1.740e-02  4.414e+01   0.064
##
##              Pr(>|t|)
## (Intercept)    0.27869
## utt_tot         0.94718
## months         0.00422 **
## backgroundChinese  0.39851
## backgroundEnglish  0.55921
## utt_tot:months    0.78945
## utt_tot:backgroundChinese  0.71923
## utt_tot:backgroundEnglish  0.45037
## months:backgroundChinese  0.44021
## months:backgroundEnglish  0.91753
## utt_tot:months:backgroundChinese  0.84243
## utt_tot:months:backgroundEnglish  0.94916
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##      (Intr) utt_tt months bckgrC bckgrE utt_t: utt_:C utt_:E mnth:C
## utt_tot    -0.821
## months     -0.925  0.760
## bckgrndChns -0.617  0.506  0.570
## bckgrndEngl -0.322  0.265  0.298  0.199
## utt_tt:mnth  0.760 -0.925 -0.821 -0.468 -0.245
## utt_tt:bckC  0.537 -0.654 -0.497 -0.867 -0.173  0.605
## utt_tt:bckE  0.303 -0.369 -0.280 -0.187 -0.953  0.341  0.241
## mnths:bckgC  0.570 -0.468 -0.617 -0.925 -0.184  0.506  0.802  0.173
## mnths:bckgE  0.293 -0.240 -0.316 -0.180 -0.927  0.260  0.157  0.881  0.195
## utt_tt:mn:C -0.497  0.605  0.537  0.802  0.160 -0.654 -0.925 -0.223 -0.867
## utt_tt:mn:E -0.277  0.337  0.299  0.171  0.887 -0.364 -0.221 -0.926 -0.185
##
##      mnth:E ut_:C

```

```
## utt_tot
## months
## bckgrndChns
## bckgrndEngl
## utt_tt:mnth
## utt_tt:bckC
## utt_tt:bckE
## mnths:bckgC
## mnths:bckgE
## utt_tt:mn:C -0.170
## utt_tt:mn:E -0.954  0.238
## fit warnings:
## Some predictor variables are on very different scales: consider rescaling
```

```
utt_lm_2 <- lmer(
  understand ~
    utt_tot *
    months +
    (1|dyad),
  data = vocab
)
```


```
## Warning: Some predictor variables are on very different scales: consider
## rescaling
```

```
## Warning: Some predictor variables are on very different scales: consider
## rescaling
```

```
summary(utt_lm_2)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: understand ~ utt_tot * months + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1122.3
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.50968 -0.52981  0.00072  0.46811  1.80340
##
## Random effects:
## Groups Name Variance Std.Dev.
## dyad (Intercept) 3963 62.95
## Residual 2290 47.86
## Number of obs: 99, groups: dyad, 50
##
## Fixed effects:
## Estimate Std. Error df t value Pr(>|t|)
## (Intercept) -1.120e+02 5.767e+01 6.337e+01 -1.943 0.0565 .
## utt_tot -2.221e-03 7.058e-02 6.336e+01 -0.031 0.9750
## months 1.661e+01 3.547e+00 4.711e+01 4.682 2.43e-05 ***
## utt_tot:months 1.959e-03 4.336e-03 4.701e+01 0.452 0.6534
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
##
## Correlation of Fixed Effects:
##          (Intr) utt_tt months
## utt_tot    -0.892
## months     -0.921  0.821
## utt_tt:mnth  0.822 -0.921 -0.891
## fit warnings:
## Some predictor variables are on very different scales: consider rescaling
plot_model(utt_lm_2, type = "pred", terms = c("utt_tot", "months"))
```



5.1.5 Contingent talks

```
ct_lm <- lmer(
  understand ~
    ct_tot *
    months *
    background +
    (1|dyad),
  data = vocab
)
summary(ct_lm)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: understand ~ ct_tot * months * background + (1 | dyad)
```



```

## Data: vocab
##
## REML criterion at convergence: 1158.5
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.5331 -0.5368  0.0162  0.4602  1.6119
##
## Random effects:
##   Groups   Name      Variance Std.Dev.
##   dyad      (Intercept) 3625      60.21
##   Residual                2446      49.46
## Number of obs: 107, groups: dyad, 54
##
## Fixed effects:
##
##              Estimate Std. Error      df t value
## (Intercept)    -110.6215     53.7851   61.5684  -2.057
## ct_tot           9.8165      9.9876   61.5684   0.983
## months          16.6784      3.3313   46.9256   5.007
## backgroundChinese -47.4939    87.2923   61.5684  -0.544
## backgroundEnglish -18.8444    74.4312   61.6706  -0.253
## ct_tot:months     -0.4354      0.6186   46.9256  -0.704
## ct_tot:backgroundChinese -7.3882    11.7782   61.5684  -0.627
## ct_tot:backgroundEnglish -13.0948    10.2215   61.5696  -1.281
## months:backgroundChinese  2.4688      5.4067   46.9256   0.457
## months:backgroundEnglish  2.3351      4.6350   47.3826   0.504
## ct_tot:months:backgroundChinese  0.5818      0.7295   46.9256   0.797
## ct_tot:months:backgroundEnglish  0.6581      0.6331   46.9308   1.039
##
##              Pr(>|t|)
## (Intercept)      0.044 *
## ct_tot           0.330
## months          8.25e-06 ***
## backgroundChinese  0.588
## backgroundEnglish  0.801
## ct_tot:months     0.485
## ct_tot:backgroundChinese  0.533
## ct_tot:backgroundEnglish  0.205
## months:backgroundChinese  0.650
## months:backgroundEnglish  0.617
## ct_tot:months:backgroundChinese  0.429
## ct_tot:months:backgroundEnglish  0.304
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) ct_tot months bckgrC bckgrE ct_tt: ct_t:C ct_t:E mnth:C
## ct_tot        -0.596
## months        -0.929  0.554
## bckgrndChns   -0.616  0.367  0.572
## bckgrndEngl   -0.723  0.431  0.671  0.445
## ct_tt:mnths    0.554 -0.929 -0.596 -0.341 -0.400
## ct_tt:bckgC    0.506 -0.848 -0.470 -0.624 -0.365  0.788
## ct_tt:bckgE    0.583 -0.977 -0.541 -0.359 -0.493  0.908  0.829
## mnths:bckgC    0.572 -0.341 -0.616 -0.929 -0.414  0.367  0.579  0.333

```


```
## mnths:bckgE 0.668 -0.398 -0.719 -0.411 -0.930 0.428 0.338 0.456 0.443
## ct_tt:mnt:C -0.470 0.788 0.506 0.579 0.339 -0.848 -0.929 -0.770 -0.624
## ct_tt:mnt:E -0.541 0.908 0.583 0.333 0.458 -0.977 -0.770 -0.929 -0.359
##          mnth:E ct_::C
## ct_tot
## months
## bckgrndChns
## bckgrndEngl
## ct_tt:mnths
## ct_tt:bckgC
## ct_tt:bckgE
## mnths:bckgC
## mnths:bckgE
## ct_tt:mnt:C -0.363
## ct_tt:mnt:E -0.491 0.829
```

```
ct_lm_2 <- lmer(
  understand ~
    ct_tot *
    months +
    (1|dyad),
  data = vocab
)
summary(ct_lm_2)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: understand ~ ct_tot * months + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1199.7
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.50281 -0.53484 -0.06465  0.45958  1.71123
##
## Random effects:
## Groups Name Variance Std.Dev.
## dyad (Intercept) 3680 60.67
## Residual 2393 48.92
## Number of obs: 107, groups: dyad, 54
##
## Fixed effects:
## Estimate Std. Error df t value Pr(>|t|)
## (Intercept) -105.9926 29.3160 67.3472 -3.616 0.000574 ***
## ct_tot -2.7417 1.9235 67.2909 -1.425 0.158670
## months 17.2216 1.8184 51.2881 9.471 7.53e-13 ***
## ct_tot:months 0.2289 0.1189 51.0070 1.924 0.059887 .
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
## (Intr) ct_tot months
## ct_tot -0.494
## months -0.928 0.457
```

```
## ct_tt:mnths 0.459 -0.927 -0.494
```

```
plot_model(ct_lm_2, type = "pred", terms = c("ct_tot", "months"))
```



5.2 Production at 12 and 18 months


5.2.1 All gestures combined

```
all_gest_lm_2_undsay <- lmer(
  und_say ~
    count_tot *
    months +
    (1|dyad),
  data = vocab
)
summary(all_gest_lm_2_undsay)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: und_say ~ count_tot * months + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1147.1
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
```

```
## -1.6451 -0.2949 -0.0400  0.1150  5.1936
##
## Random effects:
## Groups   Name            Variance Std.Dev.
## dyad      (Intercept)    281      16.76
## Residual                2026     45.01
## Number of obs: 109, groups: dyad, 55
##
## Fixed effects:
##              Estimate Std. Error    df t value Pr(>|t|)
## (Intercept)   -4.40898   35.33834  58.60030  -0.125  0.901137
## count_tot     -2.10393    0.73592  58.32093  -2.859  0.005887 **
## months         0.92064    2.30729  53.64769   0.399  0.691468
## count_tot:months 0.17796    0.04795  53.17912   3.711  0.000495 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) cnt_tt months
## count_tot    -0.781
## months        -0.975  0.761
## cnt_tt:mnth   0.763 -0.975 -0.782
```


```
plot_model(all_gest_lm_2_undsay, type = "pred", terms = c("count_tot", "months"))
```



5.2.2 HoGs + point

```
hgp_lm_2_undsay <- lmer(
  und_say ~
    hgp_tot *
    months +
    (1|dyad),
  data = vocab
)
summary(hgp_lm_2_undsay)

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: und_say ~ hgp_tot * months + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1147.5
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.6473 -0.2989 -0.0408  0.1149  5.2699
##
## Random effects:
## Groups Name Variance Std.Dev.
## dyad (Intercept) 296.9 17.23
## Residual 2024.2 44.99
## Number of obs: 109, groups: dyad, 55
##
## Fixed effects:
## Estimate Std. Error df t value Pr(>|t|)
## (Intercept) -21.53337 30.78529 58.62260 -0.699 0.487025
## hgp_tot -2.16893 0.75263 58.33881 -2.882 0.005525 **
## months 2.40664 2.00891 53.57824 1.198 0.236195
## hgp_tot:months 0.18213 0.04901 53.10111 3.716 0.000488 ***
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
## (Intr) hgp_tt months
## hgp_tot -0.697
## months -0.975 0.680
## hgp_tt:mnth 0.681 -0.975 -0.699
plot_model(hgp_lm_2_undsay, type = "pred", terms = c("hgp_tot", "months"))
```




5.2.3 Reaches

```
reach_lm_2_undsay <- lmer(
  und_say ~
    reach_tot *
    months +
    (1|dyad),
  data = vocab
)
summary(reach_lm_2_undsay)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: und_say ~ reach_tot * months + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1163.4
##
## Scaled residuals:
##   Min       1Q   Median       3Q      Max
## -1.0021 -0.5942 -0.0473  0.0622  4.8782
##
## Random effects:
## Groups   Name                Variance Std.Dev.
## dyad     (Intercept)          301.7    17.37
```

```
## Residual                2548.9   50.49
## Number of obs: 109, groups: dyad, 55
##
## Fixed effects:
##              Estimate Std. Error      df t value Pr(>|t|)
## (Intercept)   -79.18384   42.04927   58.12865   -1.883   0.0647 .
## reach_tot     -0.54333    3.78589   57.92651   -0.144   0.8864
## months         7.00150    2.74140   53.13124    2.554   0.0136 *
## reach_tot:months  0.07302    0.24647   52.79269    0.296   0.7682
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) rch_tt months
## reach_tot   -0.809
## months      -0.976  0.789
## rch_tt:mnth  0.790 -0.976 -0.809
```

```
plot_model(reach_lm_2_undsay, type = "pred", terms = c("reach_tot", "months"))
```



5.2.4 Maternal utterances

```
utt_lm_2_undsay <- lmer(
  und_say ~
    utt_tot *
    months +
```

```
(1|dyad),
data = vocab
)
```

```
## Warning: Some predictor variables are on very different scales: consider
## rescaling
```

```
## Warning: Some predictor variables are on very different scales: consider
## rescaling
```

```
summary(utt_lm_2_undsay)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
```

```
## Formula: und_say ~ utt_tot * months + (1 | dyad)
```

```
## Data: vocab
```

```
##
```

```
## REML criterion at convergence: 1048.3
```

```
##
```

```
## Scaled residuals:
```

```
##      Min       1Q   Median       3Q      Max
## -1.5455 -0.3786 -0.0439  0.0721  4.9551
```

```
##
```

```
## Random effects:
```

```
## Groups   Name                Variance Std.Dev.
```

```
## dyad     (Intercept)    252.7    15.90
```

```
## Residual                    1988.0    44.59
```

```
## Number of obs: 99, groups: dyad, 50
```

```
##
```

```
## Fixed effects:
```

```
##              Estimate Std. Error      df t value Pr(>|t|)
## (Intercept)  -17.010657  50.696871  52.550812  -0.336   0.7386
## utt_tot      -0.078926   0.062078  52.447768  -1.271   0.2092
## months       1.684411   3.301037  47.882950   0.510   0.6122
## utt_tot:months 0.006948   0.004039  47.709819   1.720   0.0919 .
```

```
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
##
```

```
## Correlation of Fixed Effects:
```

```
##              (Intr) utt_tt months
```

```
## utt_tot      -0.892
```


```
## months      -0.976  0.870
```

```
## utt_tt:mnth  0.871 -0.976 -0.892
```

```
## fit warnings:
```

```
## Some predictor variables are on very different scales: consider rescaling
```

```
plot_model(utt_lm_2_undsay, type = "pred", terms = c("utt_tot", "months"))
```


5.2.5 Contingent talks

```
ct_lm_2_undsay <- lmer(
  und_say ~
    ct_tot *
    months +
    (1|dyad),
  data = vocab
)
summary(ct_lm_2_undsay)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: und_say ~ ct_tot * months + (1 | dyad)
## Data: vocab
##
## REML criterion at convergence: 1121.2
##
## Scaled residuals:
##   Min       1Q   Median       3Q      Max
## -1.4538 -0.4998 -0.0264  0.0844  5.0390
##
## Random effects:
## Groups   Name                Variance Std.Dev.
## dyad     (Intercept)          272.8    16.52
```

```
## Residual                2004.2   44.77
## Number of obs: 107, groups: dyad, 54
##
## Fixed effects:
##              Estimate Std. Error      df t value Pr(>|t|)
## (Intercept)  -48.6655   25.4770   57.1883  -1.910 0.061130 .
## ct_tot       -4.9476    1.6731   56.9250  -2.957 0.004514 **
## months        4.6434    1.6602   52.1618   2.797 0.007210 **
## ct_tot:months   0.4205    0.1088   51.7189   3.864 0.000312 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) ct_tot months
## ct_tot       -0.494
## months       -0.975  0.481
## ct_tot:months  0.482 -0.975 -0.494
```

```
plot_model(ct_lm_2_undsay, type = "pred", terms = c("ct_tot", "months"))
```



6 R session

```
devtools::session_info()
```

```
## - Session info -----
```

```
## setting value
## version R version 3.5.2 (2018-12-20)
## os      macOS Mojave 10.14.2
## system  x86_64, darwin15.6.0
## ui      X11
## language (EN)
## collate en_GB.UTF-8
## ctype   en_GB.UTF-8
## tz      Europe/London
## date    2019-01-21
##
## - Packages -----
## package      * version  date      lib
## abind         1.4-5    2016-07-21 [1]
## assertthat    0.2.0    2017-04-11 [1]
## backports     1.1.3    2018-12-14 [1]
## bayesplot     1.6.0    2018-08-02 [1]
## bindr         0.1.1    2018-03-13 [1]
## bindrcpp      * 0.2.2    2018-03-29 [1]
## binom         1.1-1    2014-01-02 [1]
## broom         0.5.1    2018-12-05 [1]
## callr         3.1.1    2018-12-21 [1]
## car           3.0-2    2018-08-23 [1]
## carData       * 3.0-2    2018-09-30 [1]
## cellranger    1.1.0    2016-07-27 [1]
## cli           1.0.1    2018-09-25 [1]
## coda          0.19-2   2018-10-08 [1]
## codetools     0.2-16   2018-12-24 [1]
## coin          1.2-2    2017-11-28 [1]
## colorspace    1.4-0    2019-01-13 [1]
## crayon        1.3.4    2017-09-16 [1]
## curl          3.3      2019-01-10 [1]
## data.table    1.12.0   2019-01-13 [1]
## desc          1.2.0    2018-05-01 [1]
## devtools      2.0.1    2018-10-26 [1]
## digest        0.6.18   2018-10-10 [1]
## dplyr         * 0.7.8    2018-11-10 [1]
## effects       * 4.1-0    2018-11-30 [1]
## emmeans       1.3.1    2018-12-13 [1]
## estimability  1.3      2018-02-11 [1]
## evaluate      0.12     2018-10-09 [1]
## forcats       * 0.3.0    2018-02-19 [1]
## foreign       0.8-71   2018-07-20 [1]
## fs            1.2.6    2018-08-23 [1]
## generics      0.0.2    2018-11-29 [1]
## ggeffects     0.8.0    2019-01-09 [1]
## ggplot2       * 3.1.0    2018-10-25 [1]
## ggribges      0.5.1    2018-09-27 [1]
## glmmTMB       0.2.3    2019-01-11 [1]
## glue          1.3.0    2018-07-17 [1]
## gtable        0.2.0    2016-02-26 [1]
## haven         2.0.0    2018-11-22 [1]
## hms           0.4.2    2018-03-10 [1]
## htmltools     0.3.6    2017-04-28 [1]
```

##	httr	1.4.0	2018-12-11	[1]
##	iterators	1.0.10	2018-07-13	[1]
##	itsadug	* 2.3	2017-08-31	[1]
##	jsonlite	1.6	2018-12-07	[1]
##	knitr	1.21	2018-12-10	[1]
##	labeling	0.3	2014-08-23	[1]
##	lattice	0.20-38	2018-11-04	[1]
##	lazyeval	0.2.1	2017-10-29	[1]
##	lme4	* 1.1-19	2018-11-10	[1]
##	lmerTest	* 3.0-1	2018-04-23	[1]
##	lubridate	1.7.4	2018-04-11	[1]
##	magrittr	1.5	2014-11-22	[1]
##	MASS	* 7.3-51.1	2018-11-01	[1]
##	Matrix	* 1.2-15	2018-11-01	[1]
##	memoise	1.1.0	2017-04-21	[1]
##	mgcv	* 1.8-26	2018-11-21	[1]
##	minqa	1.2.4	2014-10-09	[1]
##	mnormt	1.5-5	2016-10-15	[1]
##	modelr	0.1.2	2018-05-11	[1]
##	modeltools	0.2-22	2018-07-16	[1]
##	multcomp	1.4-8	2017-11-08	[1]
##	munsell	0.5.0	2018-06-12	[1]
##	mvtnorm	1.0-8	2018-05-31	[1]
##	nlme	* 3.1-137	2018-04-07	[1]
##	nloptr	1.2.1	2018-10-03	[1]
##	nnet	7.3-12	2016-02-02	[1]
##	numDeriv	2016.8-1	2016-08-27	[1]
##	openxlsx	4.1.0	2018-05-26	[1]
##	pbkrtest	0.4-7	2017-03-15	[1]
##	pillar	1.3.1	2018-12-15	[1]
##	pkgbuild	1.0.2	2018-10-16	[1]
##	pkgconfig	2.0.2	2018-08-16	[1]
##	pkgload	1.0.2	2018-10-29	[1]
##	plotfunctions	* 1.3	2017-08-30	[1]
##	plotrix	3.7-4	2018-10-03	[1]
##	plyr	1.8.4	2016-06-08	[1]
##	prediction	0.3.6.1	2018-12-04	[1]
##	prettyunits	1.0.2	2015-07-13	[1]
##	processx	3.2.1	2018-12-05	[1]
##	ps	1.3.0	2018-12-21	[1]
##	psych	1.8.12	2019-01-12	[1]
##	purrr	* 0.2.5	2018-05-29	[1]
##	pwr	1.2-2	2018-03-03	[1]
##	R6	2.3.0	2018-10-04	[1]
##	Rcpp	1.0.0	2018-11-07	[1]
##	readr	* 1.3.1	2018-12-21	[1]
##	readxl	1.2.0	2018-12-19	[1]
##	remotes	2.0.2	2018-10-30	[1]
##	reshape2	1.4.3	2017-12-11	[1]
##	rio	0.5.16	2018-11-26	[1]
##	rlang	0.3.1	2019-01-08	[1]
##	RLRsim	3.1-3	2016-11-04	[1]
##	rmarkdown	1.11	2018-12-08	[1]
##	rprojroot	1.3-2	2018-01-03	[1]

```
## rstudioapi      0.9.0      2019-01-09 [1]
## rvest            0.3.2      2016-06-17 [1]
## sandwich        2.5-0      2018-08-17 [1]
## scales          1.0.0      2018-08-09 [1]
## sessioninfo     1.1.1      2018-11-05 [1]
## simr            * 1.0.4      2018-04-30 [1]
## sjlabelled      1.0.16     2019-01-10 [1]
## sjmisc          2.7.7      2019-01-02 [1]
## sjPlot          * 2.6.2      2018-12-18 [1]
## sjstats         0.17.3     2019-01-07 [1]
## snakecase       0.9.2      2018-08-14 [1]
## stringdist      0.9.5.1    2018-06-08 [1]
## stringi         1.2.4      2018-07-20 [1]
## stringr         * 1.3.1      2018-05-10 [1]
## survey          3.35       2018-12-17 [1]
## survival        2.43-3     2018-11-26 [1]
## testthat        2.0.1      2018-10-13 [1]
## TH.data         1.0-9      2018-07-10 [1]
## tibble          * 2.0.1      2019-01-12 [1]
## tidymv          * 2.0.0      2019-01-15 [1]
## tidyr           * 0.8.2      2018-10-28 [1]
## tidyselect      0.2.5      2018-10-11 [1]
## tidyverse       * 1.2.1      2017-11-14 [1]
## TMB             1.7.15     2018-11-09 [1]
## usethis         1.4.0      2018-08-14 [1]
## withr           2.1.2      2018-03-15 [1]
## xfun            0.4        2018-10-23 [1]
## xml2            1.2.0      2018-01-24 [1]
## xtable          1.8-3      2018-08-29 [1]
## yaml            2.2.0      2018-07-25 [1]
## zip             1.0.0      2017-04-25 [1]
## zoo             1.8-4      2018-09-19 [1]
## source
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.2)
## CRAN (R 3.5.0)
## CRAN (R 3.5.2)
## CRAN (R 3.5.0)
## CRAN (R 3.5.2)
## CRAN (R 3.5.2)
## CRAN (R 3.5.0)
```

[illegible]

```
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.2)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.1)
## CRAN (R 3.5.2)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.2)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.2)
## CRAN (R 3.5.2)
## CRAN (R 3.5.2)
## CRAN (R 3.5.0)
## CRAN (R 3.5.2)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.2)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.2)
## Github (stefanocoretta/tidymv@3d427d5)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## CRAN (R 3.5.0)
## [1] /Library/Frameworks/R.framework/Versions/3.5/Resources/libraries
```