

Heading 1

Heading 2

Heading 3

Heading 4

Heading 5

Heading 6

Text

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Feugiat vivamus at augue eget arcu dictum varius. Accumsan sit amet nulla facilisi morbi tempus iaculis. **Bold** Mauris commodo quis imperdiet massa. Pellentesque pulvinar pellentesque habitant morbi tristique. Urna condimentum mattis pellentesque id nibh tortor id aliquet. Viverra tellus in hac habitasse platea dictumst vestibulum rhoncus est. Posuere morbi leo urna molestie *Italic* at elementum. Arcu ac tortor dignissim convallis aenean et. Iaculis eu non diam phasellus vestibulum. Vestibulum mattis ullamcorper ***Bold and italic*** velit sed ullamcorper morbi.

- Unordered list item 1
- Unordered list item 2
- Unordered list item 2

1. Ordered list item 1
 2. Ordered list item 2
 3. Ordered list item 3
-
-

Table column 1	Table column 2	Table column 3
This column is in the center	This column is in the left	This column is in the right
Bar	Bar	Bar
Foo	Foo	Foo

$y = mx/b$

HTML Code

```
# Fizz Buzz
n = input("N ==> ")
for i in range(n+1):
    if i%15 == 0:
        print(i, "FizzBuzz")
    if i%5 == 0:
        print(i, "Fizz")
    if i%3 == 0:
        print(i, "Buzz")
```

The best argument against democracy is a five-minute conversation with the average voter

- Winston Churchill

⚠ Some code might be experimental

- ☐ Study for exam
- ☐ Do the chores
- ☐ Bar
- ☐ Foo

Here is a review of existing methods¹

1. Description footnote