

Draft

Ecma/TC39/2012/0xx

Standard ECMA-262

6th Edition / Draft [September 27, 2012](#)

Draft

**ECMAScript Language
Specification**

Report Errors and Issues at: <https://bugs.ecmascript.org>

Product: Draft for 6th Edition
Component: choose an appropriate one
Version: [September 27, 2012 Draft](#)

Standard

Rue du Rhône 114 CH-1204 Geneva T: +41 22 849 6000 F: +41 22 849 6001

DRAFT



COPYRIGHT PROTECTED DOCUMENT

Contents

	Page
Introduction.....	vii
1 Scope.....	1
2 Conformance.....	1
3 Normative references.....	1
4 Overview	1
4.1 Web Scripting.....	2
4.2 Language Overview	2
4.2.1 Objects	3
4.2.2 The Strict Variant of ECMAScript	4
4.3 Terms and definitions.....	4
5 Notational Conventions.....	7
5.1 Syntactic and Lexical Grammars.....	7
5.1.1 Context-Free Grammars	7
5.1.2 The Lexical and RegExp Grammars.....	8
5.1.3 The Numeric String Grammar	8
5.1.4 The Syntactic Grammar.....	8
5.1.5 The JSON Grammar	9
5.1.6 Grammar Notation.....	9
5.2 Algorithm Conventions	12
5.3 Static Semantic Rules	13
6 Source Text	14
7 Lexical Conventions	15
7.1 Unicode Format-Control Characters.....	16
7.2 White Space.....	16
7.3 Line Terminators	17
7.4 Comments	17
7.5 Tokens.....	18
7.6 Identifier Names and Identifiers.....	19
7.6.1 Reserved Words	20
7.7 Punctuators	21
7.8 Literals.....	21
7.8.1 Null Literals	21
7.8.2 Boolean Literals	21
7.8.3 Numeric Literals	22
7.8.4 String Literals.....	24
7.8.5 Regular Expression Literals	27
7.8.6 Template Literal Lexical Components	28
7.9 Automatic Semicolon Insertion	30
7.9.1 Rules of Automatic Semicolon Insertion	30
7.9.2 Examples of Automatic Semicolon Insertion	31
8 Types	32
8.1 The Undefined Type.....	32
8.2 The Null Type	33
8.3 The Boolean Type	33
8.4 The String Type	33
8.5 The Number Type	33
8.6 The Object Type.....	34
8.6.1 Property Attributes.....	35

8.6.2 Object Internal Properties and Methods	36
8.7 The List and Record Specification Type.....	40
8.8 The Completion Record Specification Type.....	40
8.8.1 Implicit Completion Values.....	41
8.8.2 NormalCompletion	41
8.8.3 Throw an Exception	41
8.8.4 ReturnIfAbrupt	41
8.9 The Reference Specification Type	42
8.9.1 GetValue (V)	42
8.9.2 PutValue (V, W).....	43
8.9.3 GetThisValue (V).....	44
8.10 The Property Descriptor and Property Identifier Specification Types	44
8.10.1 IsAccessorDescriptor (Desc)	44
8.10.2 IsDataDescriptor (Desc).....	44
8.10.3 IsGenericDescriptor (Desc)	45
8.10.4 FromPropertyDescriptor (Desc)	45
8.10.5 ToPropertyDescriptor (Obj).	45
8.11 The Lexical Environment and Environment Record Specification Types	46
8.12 Algorithms for Object Internal Methods.....	46
8.12.1 [[GetOwnProperty]] (P).....	46
8.12.2 [[GetProperty]] (P).....	46
8.12.3 [[Get]] (P [, accessorThisValue])	46
8.12.4 [[CanPut]] (P).....	47
8.12.5 [[Put]] (P, V, Throw[, accessorThisValue])	47
8.12.6 [[HasProperty]] (P)	47
8.12.7 [[Delete]] (P, Throw).....	48
8.12.8 [[DefaultValue]] (hint)	48
8.12.9 [[DefineOwnProperty]] (P, Desc, Throw).....	49
8.12.10 [[Enumerate]] (includePrototype, onlyEnumerable)	50
8.12.11 [[Iterate]] ()	50
8.13 Data Blocks	50
9 Abstract Operations	51
9.1 Type Conversion and Testing.....	51
9.1.1 ToPrimitive	51
9.1.2 ToBoolean	52
9.1.3 ToNumber	53
9.1.4 ToInteger.....	55
9.1.5 ToInt32: (Signed 32 Bit Integer)	56
9.1.6 ToUint32: (Unsigned 32 Bit Integer).....	56
9.1.7 ToUint16: (Unsigned 16 Bit Integer).....	56
9.1.8 ToString	57
9.1.9 ToObject	58
9.1.10 ToPropertyKey.....	58
9.2 Testing and Comparision Operations	58
9.2.1 CheckObjectCoercible	58
9.2.2 IsCallable	59
9.2.3 The SameValue Algorithm	59
9.3 Operations on Objects	59
9.3.1 Invoke	59
10 Executable Code and Execution Contexts	60
10.1 Types of Executable Code.....	60
10.1.1 Strict Mode Code.....	60
10.1.2 Non-ECMAScript Functions	61
10.2 Lexical Environments	61
10.2.1 Environment Records.....	61
10.2.2 Lexical Environment Operations.....	68
10.3 Code Realms	69
10.4 Execution Contexts.....	69

10.4.1 Identifier Resolution	70
10.4.2 GetThisEnvironment	70
10.4.3 This Resolution	70
10.5 Declaration Binding Instantiation	71
10.5.1 Top-Level Declaration Instantiation	71
10.5.2 Module Declaration Instantiation	72
10.5.3 Function Declaration Instantiation	72
10.5.4 Block Declaration Instantiation	73
10.6 Arguments Object	74
11 Expressions	77
11.1 Primary Expressions	77
11.1.1 The this Keyword	78
11.1.2 Identifier Reference	78
11.1.3 Literals	78
11.1.4 Array Initialiser	79
11.1.5 Object Initialiser	82
11.1.6 Function Defining Expressions	85
11.1.7 Generator Comprehensions	86
11.1.8 Regular Expression Literals	86
11.1.9 Template Literals	86
11.1.10 The Grouping Operator	90
11.2 Left-Hand-Side Expressions	90
11.2.1 Property Accessors	92
11.2.2 The new Operator	92
11.2.3 Function Calls	93
11.2.4 The super Keyword	94
11.2.5 Argument Lists	95
11.2.6 Tagged Templates	96
11.3 Postfix Expressions	96
11.3.1 Postfix Increment Operator	97
11.3.2 Postfix Decrement Operator	97
11.4 Unary Operators	98
11.4.1 The delete Operator	98
11.4.2 The void Operator	99
11.4.3 The typeof Operator	99
11.4.4 Prefix Increment Operator	100
11.4.5 Prefix Decrement Operator	100
11.4.6 Unary + Operator	100
11.4.7 Unary - Operator	101
11.4.8 Bitwise NOT Operator (~)	101
11.4.9 Logical NOT Operator (!)	101
11.5 Multiplicative Operators	101
11.5.1 Applying the * Operator	102
11.5.2 Applying the / Operator	102
11.5.3 Applying the % Operator	103
11.6 Additive Operators	103
11.6.1 The Addition operator (+)	103
11.6.2 The Subtraction Operator (-)	104
11.6.3 Applying the Additive Operators to Numbers	104
11.7 Bitwise Shift Operators	105
11.7.1 The Left Shift Operator (<<)	105
11.7.2 The Signed Right Shift Operator (>>)	105
11.7.3 The Unsigned Right Shift Operator (>>>)	106
11.8 Relational Operators	106
11.8.1 Runtime Semantics	107
11.9 Equality Operators	109
11.9.1 Runtime Semantics	110

11.10	Binary Bitwise Operators.....	112
11.11	Binary Logical Operators.....	113
11.12	Conditional Operator (? :)	114
11.13	Assignment Operators	115
	Static Semantics	115
	Runtime Semantics	116
11.13.1	Destructuring Assignment	116
11.14	Comma Operator (,)	120
12	Statements and Declarations	121
	Static Semantics	121
	Runtime Semantics	121
12.1	Block.....	122
12.2	Declarations and the Variable Statement	124
12.2.1	Let and Const Declarations	124
12.2.2	Variable Statement.....	127
12.2.4	Destructuring Binding Patterns.....	129
12.3	Empty Statement.....	134
12.4	Expression Statement	134
12.5	The if Statement	134
12.6	Iteration Statements.....	135
12.6.1	The do-while Statement.....	136
12.6.2	The while Statement	136
12.6.3	The for Statement.....	137
12.6.4	The for-in and for-of Statements.....	138
12.7	The continue Statement.....	141
12.8	The break Statement	142
12.9	The return Statement	142
12.10	The with Statement.....	143
12.11	The switch Statement	144
12.12	Labelled Statements	148
12.13	The throw Statement	149
12.14	The try Statement.....	149
12.15	The debugger statement	151
13	Functions and Generators	152
13.1	Function Definitions	152
13.2	Arrow Function Definitions	157
13.3	Method Definitions.....	159
f13.4	Generator Definitions	162
13.5	Class Definitions	164
13.6	Creating Function Objects and Constructors	167
13.7	Tail Position Calls.....	169
14	Programs and Modules	169
14.1	Directive Prologues and the Use Strict Directive	170
15	Standard Built-in ECMAScript Objects.....	170
15.1	The Global Object	171
15.1.1	Value Properties of the Global Object	172
15.1.2	Function Properties of the Global Object	172
15.1.3	URI Handling Function Properties	174
15.1.4	Constructor Properties of the Global Object	179
15.1.5	Other Properties of the Global Object	180
15.2	Object Objects	180
15.2.1	The Object Constructor Called as a Function	180
15.2.2	The Object Constructor	180
15.2.3	Properties of the Object Constructor	181
15.2.4	Properties of the Object Prototype Object	184
15.2.5	Properties of Object Instances	186

15.3	Function Objects	186
15.3.1	The Function Constructor Called as a Function	186
15.3.2	The Function Constructor	186
15.3.3	Properties of the Function Constructor	187
15.3.4	Properties of the Function Prototype Object	188
15.3.5	Properties of Function Instances	190
15.4	Array Objects	191
15.4.1	The Array Constructor Called as a Function	192
15.4.2	The Array Constructor	192
15.4.3	Properties of the Array Constructor	193
15.4.4	Properties of the Array Prototype Object	194
15.4.5	Properties of Array Instances	213
15.5	String Objects	215
15.5.1	The String Constructor Called as a Function	215
15.5.2	The String Constructor	215
15.5.3	Properties of the String Constructor	215
15.5.4	Properties of the String Prototype Object	217
15.5.5	Properties of String Instances	229
15.6	Boolean Objects	229
15.6.1	The Boolean Constructor Called as a Function	229
15.6.2	The Boolean Constructor	230
15.6.3	Properties of the Boolean Constructor	230
15.6.4	Properties of the Boolean Prototype Object	230
15.6.5	Properties of Boolean Instances	231
15.7	Number Objects	231
15.7.1	The Number Constructor Called as a Function	231
15.7.2	The Number Constructor	231
15.7.3	Properties of the Number Constructor	231
15.7.4	Properties of the Number Prototype Object	233
15.7.5	Properties of Number Instances	237
15.8	The Math Object	237
15.8.1	Value Properties of the Math Object	238
15.8.2	Function Properties of the Math Object	239
15.9	Date Objects	246
15.9.1	Overview of Date Objects and Definitions of Abstract Operators	246
15.9.2	The Date Constructor Called as a Function	251
15.9.3	The Date Constructor	251
15.9.4	Properties of the Date Constructor	252
15.9.5	Properties of the Date Prototype Object	253
15.9.6	Properties of Date Instances	261
15.10	RegExp (Regular Expression) Objects	261
15.10.1	Patterns	261
15.10.2	Pattern Semantics	263
15.10.3	The RegExp Constructor Called as a Function	275
15.10.4	The RegExp Constructor	275
15.10.5	Properties of the RegExp Constructor	276
15.10.6	Properties of the RegExp Prototype Object	276
15.10.7	Properties of RegExp Instances	278
15.11	Error Objects	279
15.11.1	The Error Constructor Called as a Function	279
15.11.2	The Error Constructor	279
15.11.3	Properties of the Error Constructor	279
15.11.4	Properties of the Error Prototype Object	280
15.11.5	Properties of Error Instances	280
15.11.6	Native Error Types Used in This Standard	280
15.11.7	<i>NativeError</i> Object Structure	281
15.12	The JSON Object	283
15.12.1	The JSON Grammar	283
15.12.2	<i>parse</i> (<i>text</i> [, <i>reviver</i>])	285

15.12.3 <code>stringify (value [, replacer [, space]])</code>	286
15.13 Binary Data Objects.....	290
15.13.1 The <code>BinaryData</code> Module.....	290
15.13.2 The <code>BinaryData.Type</code> Object	290
15.13.3 The <code>BinaryData.ArrayType</code> Object	290
15.13.4 The <code>BinaryData.StructType</code> Object	290
15.13.5 <code>ArrayBuffer</code> Objects	290
15.13.6 <code>TypeArray</code> Object Structures	291
15.13.7 <code>DataView</code> Objects	296
15.14 Map Objects	300
15.14.1 Abstract Operations For Map Objects	300
15.14.2 The <code>Map</code> Constructor Called as a Function.....	300
15.14.3 The <code>Map</code> Constructor	301
15.14.4 Properties of the <code>Map</code> Constructor	301
15.14.5 Properties of the <code>Map</code> Prototype Object.....	301
15.14.6 Properties of <code>Map</code> Instances	304
15.14.7 Map Iterator Objects	304
15.15 <code>WeakMap</code> Objects.....	305
15.16 Set Objects	305
15.17 The <code>Reflect</code> Module	305
15.18 Proxy Objects.....	305
16 Errors.....	305
Annex A (informative) Grammar Summary	308
A.1 Lexical Grammar	308
A.2 Number Conversions.....	314
A.3 Expressions	315
A.4 Statements	319
A.5 Functions and Programs	321
A.6 Universal Resource Identifier Character Classes	322
A.7 Regular Expressions	322
A.8 JSON.....	324
A.8.1 JSON Lexical Grammar	324
A.8.2 JSON Syntactic Grammar.....	325
Annex B (normative) Additional ECMAScript Features for Web Browsers.....	328
B.1 Additional Syntax	328
B.1.1 Numeric Literals	328
B.1.2 String Literals	328
B.2 Additional Properties	329
B.2.1 Additional Properties of the Global Object.....	329
B.2.2 Additional Properties of the <code>String.prototype</code> Object.....	330
B.2.3 Additional Properties of the <code>Date.prototype</code> Object.....	333
B.3 Other Additional Features	334
B.3.1 The <code>__proto__</code> pseudo property.....	334
Annex C (informative) The Strict Mode of ECMAScript	336
Annex D (informative) Corrections and Clarifications with Possible Compatibility Impact.....	338
In Edition 6	338
In 5.1 Edition 5.1	338
In 5 th Edition 5	339
Annex E (informative) Additions and Changes that Introduce Incompatibilities with Prior Editions	342
In the 6 th Edition	342
In the 5 th Edition	342
Annex F (informative) Static Semantic Rule Cross Reference	346
Scrap Heap.....	348

DRAFT

Introduction

This Ecma Standard is based on several originating technologies, the most well known being JavaScript (Netscape) and JScript (Microsoft). The language was invented by Brendan Eich at Netscape and first appeared in that company's Navigator 2.0 browser. It has appeared in all subsequent browsers from Netscape and in all browsers from Microsoft starting with Internet Explorer 3.0.

The development of this Standard started in November 1996. The first edition of this Ecma Standard was adopted by the Ecma General Assembly of June 1997.

That Ecma Standard was submitted to ISO/IEC JTC 1 for adoption under the fast-track procedure, and approved as international standard ISO/IEC 16262, in April 1998. The Ecma General Assembly of June 1998 approved the second edition of ECMA-262 to keep it fully aligned with ISO/IEC 16262. Changes between the first and the second edition are editorial in nature.

The third edition of the Standard introduced powerful regular expressions, better string handling, new control statements, try/catch exception handling, tighter definition of errors, formatting for numeric output and minor changes in anticipation of forthcoming internationalisation facilities and future language growth. The third edition of the ECMAScript standard was adopted by the Ecma General Assembly of December 1999 and published as ISO/IEC 16262:2002 in June 2002.

Since publication of the third edition, ECMAScript has achieved massive adoption in conjunction with the World Wide Web where it has become the programming language that is supported by essentially all web browsers. Significant work was done to develop a fourth edition of ECMAScript. Although that work was not completed and not published¹ as the fourth edition of ECMAScript, it informs continuing evolution of the language. The fifth edition of ECMAScript (published as ECMA-262 5th edition) codifies de facto interpretations of the language specification that have become common among browser implementations and adds support for new features that have emerged since the publication of the third edition. Such features include accessor properties, reflective creation and inspection of objects, program control of property attributes, additional array manipulation functions, support for the JSON object encoding format, and a strict mode that provides enhanced error checking and program security.

The edition 5.1 of the ECMAScript Standard has been fully aligned with the third edition of the international standard ISO/IEC 16262:2011.

This present sixth edition of the Standard.....

ECMAScript is a vibrant language and the evolution of the language is not complete. Significant technical enhancement will continue with future editions of this specification.

This Ecma Standard has been adopted by the General Assembly of <month> <year>.

¹ Note: Please note that for ECMAScript Edition 4 the Ecma standard number "ECMA-262 Edition 4" was reserved but not used in the Ecma publication process. Therefore "ECMA-262 Edition 4" as an Ecma International publication does not exist.

"DISCLAIMER

This draft document may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to Ecma International, except as needed for the purpose of developing any document or deliverable produced by Ecma International.

This disclaimer is valid only prior to final version of this document. After approval all rights on the standard are reserved by Ecma International.

The limited permissions are granted through the standardization phase and will not be revoked by Ecma International or its successors or assigns during this time.

This document and the information contained herein is provided on an "AS IS" basis and ECMA INTERNATIONAL DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE."

DRAFT

ECMAScript Language Specification

1 Scope

This Standard defines the ECMAScript scripting language.

2 Conformance

A conforming implementation of ECMAScript must provide and support all the types, values, objects, properties, functions, and program syntax and semantics described in this specification.

A conforming implementation of this Standard shall interpret characters in conformance with the Unicode Standard, Version 5.1.0 or later and ISO/IEC 10646. If the adopted ISO/IEC 10646-1 subset is not otherwise specified, it is presumed to be the [Unicode set](#), collection [10646](#).

A conforming implementation of ECMAScript is permitted to provide additional types, values, objects, properties, and functions beyond those described in this specification. In particular, a conforming implementation of ECMAScript is permitted to provide properties not described in this specification, and values for those properties, for objects that are described in this specification.

A conforming implementation of ECMAScript is permitted to support program and regular expression syntax not described in this specification. In particular, a conforming implementation of ECMAScript is permitted to support program syntax that makes use of the "future reserved words" listed in 7.6.1.2 of this specification.

- Deleted:** 3
- Deleted:** -1 with either UCS-2 or UTF-16 as the adopted encoding form, implementation level 3
- Deleted:** BMP subset
- Deleted:** 300
- Deleted:** If the adopted encoding form is not otherwise specified, it presumed to be the UTF-16 encoding form.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO/IEC 9899:1996, Programming Languages – C, including amendment 1 and technical corrigenda 1 and 2](#)

[ISO/IEC 10646:2003: Information Technology – Universal Multiple-Octet Coded Character Set \(UCS\) plus Amendment 1:2005, Amendment 2:2006, Amendment 3:2008, and Amendment 4:2008, plus additional amendments and corrigenda, or successor](#)

[The Unicode Standard, Version 5.0, as amended by Unicode 5.1.0, or successor](#)

[Unicode Standard Annex #15, Unicode Normalization Forms, version Unicode 5.1.0, or successor](#)

[Unicode Standard Annex #31, Unicode Identifiers and Pattern Syntax, version Unicode 5.1.0, or successor](#)

- Deleted:** ISO/IEC 10646-1:1993, *Information Technology – Universal Multiple-Octet Coded Character Set (UCS) plus its amendments and corrigenda*

4 Overview

This section contains a non-normative overview of the ECMAScript language.

ECMAScript is an object-oriented programming language for performing computations and manipulating computational objects within a host environment. ECMAScript as defined here is not intended to be computationally self-sufficient; indeed, there are no provisions in this specification for input of external data or output of computed results. Instead, it is expected that the computational environment of an ECMAScript program will provide not only the objects and other facilities described in this specification but also certain environment-specific objects, whose description and behaviour are beyond the scope of this specification except to indicate that they may provide certain properties that can be accessed and certain functions that can be called from an ECMAScript program.

- Deleted:** host

A **scripting language** is a programming language that is used to manipulate, customise, and automate the facilities of an existing system. In such systems, useful functionality is already available through a user interface, and the scripting language is a mechanism for exposing that functionality to program control. In this way, the existing system is said to provide a host environment of objects and facilities, which completes the capabilities of the scripting language. A scripting language is intended for use by both professional and non-professional programmers.

ECMAScript was originally designed to be a **Web scripting language**, providing a mechanism to enliven Web pages in browsers and to perform server computation as part of a Web-based client-server architecture. ECMAScript can provide core scripting capabilities for a variety of host environments, and therefore the core scripting language is specified in this document apart from any particular host environment.

Some of the facilities of ECMAScript are similar to those used in other programming languages; in particular Java™, Self, and Scheme as described in:

Gosling, James, Bill Joy and Guy Steele. The Java™ Language Specification. Addison Wesley Publishing Co., 1996.

Ungar, David, and Smith, Randall B. Self: The Power of Simplicity. OOPSLA '87 Conference Proceedings, pp. 227–241, Orlando, FL, October 1987.

IEEE Standard for the Scheme Programming Language. IEEE Std 1178-1990.

4.1 Web Scripting

A web browser provides an ECMAScript host environment for client-side computation including, for instance, objects that represent windows, menus, pop-ups, dialog boxes, text areas, anchors, frames, history, cookies, and input/output. Further, the host environment provides a means to attach scripting code to events such as change of focus, page and image loading, unloading, error and abort, selection, form submission, and mouse actions. Scripting code appears within the HTML and the displayed page is a combination of user interface elements and fixed and computed text and images. The scripting code is reactive to user interaction and there is no need for a main program.

A web server provides a different host environment for server-side computation including objects representing requests, clients, and files; and mechanisms to lock and share data. By using browser-side and server-side scripting together, it is possible to distribute computation between the client and server while providing a customised user interface for a Web-based application.

Each Web browser and server that supports ECMAScript supplies its own host environment, completing the ECMAScript execution environment.

4.2 Language Overview

The following is an informal overview of ECMAScript—not all parts of the language are described. This overview is not part of the standard proper.

ECMAScript is object-based: basic language and host facilities are provided by objects, and an ECMAScript program is a cluster of communicating objects. An ECMAScript **object** is a collection of **properties** each with zero or more **attributes** that determine how each property can be used—for example, when the Writable attribute for a property is set to **false**, any attempt by executed ECMAScript code to change the value of the property fails. Properties are containers that hold other objects, **primitive values**, or **functions**. A primitive value is a member of one of the following built-in types: **Undefined**, **Null**, **Boolean**, **Number**, and **String**; an object is a member of the remaining built-in type **Object**; and a function is a callable object. A function that is associated with an object via a property is a **method**.

ECMAScript defines a collection of **built-in objects** that round out the definition of ECMAScript entities. These built-in objects include the global object, the **Object** object, the **Function** object, the **Array** object, the **String** object, the **Boolean** object, the **Number** object, the **Math** object, the **Date** object, the **RegExp** object, the

JSON object, and the Error objects `Error`, `EvalError`, `RangeError`, `ReferenceError`, `SyntaxError`, `TypeError` and `URIError`.

ECMAScript also defines a set of built-in **operators**. ECMAScript operators include various unary operations, multiplicative operators, additive operators, bitwise shift operators, relational operators, equality operators, binary bitwise operators, binary logical operators, assignment operators, and the comma operator.

ECMAScript syntax intentionally resembles Java syntax. ECMAScript syntax is relaxed to enable it to serve as an easy-to-use scripting language. For example, a variable is not required to have its type declared nor are types associated with properties, and defined functions are not required to have their declarations appear textually before calls to them.

4.2.1 Objects

ECMAScript does not use classes such as those in C++, Smalltalk, or Java. Instead objects may be created in various ways including via a literal notation or via **constructors** which create objects and then execute code that initialises all or part of them by assigning initial values to their properties. Each constructor is a function that has a property named “**prototype**” that is used to implement **prototype-based inheritance** and **shared properties**. Objects are created by using constructors in `new` expressions; for example, `new Date(2009, 11)` creates a new Date object. Invoking a constructor without using `new` has consequences that depend on the constructor. For example, `Date()` produces a string representation of the current date and time rather than an object.

Comment [AWB101]: This description probably need to be tweaked in light of new features such as class declarations and explicit exposure of the [[Prototype]] property

Every object created by a constructor has an implicit reference (called the object’s *prototype*) to the value of its constructor’s “**prototype**” property. Furthermore, a prototype may have a non-null implicit reference to its prototype, and so on; this is called the *prototype chain*. When a reference is made to a property in an object, that reference is to the property of that name in the first object in the prototype chain that contains a property of that name. In other words, first the object mentioned directly is examined for such a property; if that object contains the named property, that is the property to which the reference refers; if that object does not contain the named property, the prototype for that object is examined next; and so on.




Figure 1 — Object/Prototype Relationships

In a class-based object-oriented language, in general, state is carried by instances, methods are carried by classes, and inheritance is only of structure and behaviour. In ECMAScript, the state and methods are carried by objects, while structure, behaviour, and state are all inherited.

Deleted: and

All objects that do not directly contain a particular property that their prototype contains share that property and its value. Figure 1 illustrates this:

CF is a constructor (and also an object). Five objects have been created by using `new` expressions: **cf₁**, **cf₂**, **cf₃**, **cf₄**, and **cf₅**. Each of these objects contains properties named **q₁** and **q₂**. The dashed lines represent the implicit prototype relationship; so, for example, **cf₃**'s prototype is **CF_p**. The constructor, **CF**, has two properties itself, named **P₁** and **P₂**, which are not visible to **CF_p**, **cf₁**, **cf₂**, **cf₃**, **cf₄**, or **cf₅**. The property named **CFP₁** in **CF_p** is shared by **cf₁**, **cf₂**, **cf₃**, **cf₄**, and **cf₅** (but not by **CF**), as are any properties found in **CF_p**'s implicit prototype chain that are not named **q₁**, **q₂**, or **CFP₁**. Notice that there is no implicit prototype link between **CF** and **CF_p**.

Unlike class-based object languages, properties can be added to objects dynamically by assigning values to them. That is, constructors are not required to name or assign values to all or any of the constructed object's properties. In the above diagram, one could add a new shared property for **cf₁**, **cf₂**, **cf₃**, **cf₄**, and **cf₅** by assigning a new value to the property in **CF_p**.

4.2.2 The Strict Variant of ECMAScript

The ECMAScript Language recognises the possibility that some users of the language may wish to restrict their usage of some features available in the language. They might do so in the interests of security, to avoid what they consider to be error-prone features, to get enhanced error checking, or for other reasons of their choosing. In support of this possibility, ECMAScript defines a strict variant of the language. The strict variant of the language excludes some specific syntactic and semantic features of the regular ECMAScript language and modifies the detailed semantics of some features. The strict variant also specifies additional error conditions that must be reported by throwing error exceptions in situations that are not specified as errors by the non-strict form of the language.

The strict variant of ECMAScript is commonly referred to as the *strict mode* of the language. Strict mode selection and use of the strict mode syntax and semantics of ECMAScript is explicitly made at the level of individual ECMAScript code units. Because strict mode is selected at the level of a syntactic code unit, strict mode only imposes restrictions that have local effect within such a code unit. Strict mode does not restrict or modify any aspect of the ECMAScript semantics that must operate consistently across multiple code units. A complete ECMAScript program may be composed for both strict mode and non-strict mode ECMAScript code units. In this case, strict mode only applies when actually executing code that is defined within a strict mode code unit.

In order to conform to this specification, an ECMAScript implementation must implement both the full unrestricted ECMAScript language and the strict mode variant of the ECMAScript language as defined by this specification. In addition, an implementation must support the combination of unrestricted and strict mode code units into a single composite program.

4.3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.3.1 type

set of data values as defined in Clause 8 of this specification

4.3.2 primitive value

member of one of the types Undefined, Null, Boolean, Number, or String as defined in Clause 8

NOTE A primitive value is a datum that is represented directly at the lowest level of the language implementation.

4.3.3 object

member of the type Object

NOTE An object is a collection of properties and has a single prototype object. The prototype may be the null value.

4.3.4

constructor

function object that creates and initialises objects

NOTE The value of a constructor's "prototype" property is a prototype object that is used to implement inheritance and shared properties.

4.3.5

prototype

object that provides shared properties for other objects

NOTE When a constructor creates an object, that object implicitly references the constructor's "prototype" property for the purpose of resolving property references. The constructor's "prototype" property can be referenced by the program expression `constructor.prototype`, and properties added to an object's prototype are shared, through inheritance, by all objects sharing the prototype. Alternatively, a new object may be created with an explicitly specified prototype by using the `Object.create` built-in function.

4.3.6

ordinary object

object that has the default behaviour for the internal methods that must be supported by all ECMAScript objects.

Deleted: native

Deleted: in an ECMAScript implementation whose semantics are fully defined by this specification rather than by the host environment

Deleted: NOTE Standard native objects are defined in this specification. Some native objects are built-in; others may be constructed during the course of execution of an ECMAScript program.¶

Deleted: Every built-in object is a native object

4.3.7

built-in object

object supplied by an ECMAScript implementation, independent of the host environment, that is present at the start of the execution of an ECMAScript program

NOTE Standard built-in objects are defined in this specification, and an ECMAScript implementation may specify and define others. A built-in constructor is a built-in object that is also a constructor.

Deleted: host

Deleted: supplied by the host environment to complete the execution environment of ECMAScript

Deleted: native

Deleted: host

4.3.8

exotic object

object that has some alternative behaviour for one or more of the internal methods that must be supported by all ECMAScript objects.

NOTE Any object that is not an ordinary object is an exotic object.

4.3.9

undefined value

primitive value used when a variable has not been assigned a value

4.3.10

Undefined type

type whose sole value is the undefined value

4.3.11

null value

primitive value that represents the intentional absence of any object value

4.3.12

Null type

type whose sole value is the null value

4.3.13

Boolean value

member of the Boolean type

NOTE There are only two Boolean values, **true** and **false**.

4.3.14

Boolean type

type consisting of the primitive values **true** and **false**

4.3.15

Boolean object

member of the Object type that is an instance of the standard built-in **Boolean** constructor

NOTE A Boolean object is created by using the **Boolean** constructor in a **new** expression, supplying a Boolean value as an argument. The resulting object has an internal property whose value is the Boolean value. A Boolean object can be coerced to a Boolean value.

4.3.16

String value

primitive value that is a finite ordered sequence of zero or more 16-bit unsigned integer

NOTE A String value is a member of the String type. Each integer value in the sequence usually represents a single 16-bit unit of UTF-16 text. However, ECMAScript does not place any restrictions or requirements on the values except that they must be 16-bit unsigned integers.

4.3.17

String type

set of all possible String values

4.3.18

String object

member of the Object type that is an instance of the standard built-in **String** constructor

NOTE A String object is created by using the **String** constructor in a **new** expression, supplying a String value as an argument. The resulting object has an internal property whose value is the String value. A String object can be coerced to a String value by calling the **String** constructor as a function (15.5.1).

4.3.19

Number value

primitive value corresponding to a double-precision 64-bit binary format IEEE 754 value

NOTE A Number value is a member of the Number type and is a direct representation of a number.

4.3.20

Number type

set of all possible Number values including the special “Not-a-Number” (NaN) value, positive infinity, and negative infinity

Deleted: s

4.3.21

Number object

member of the Object type that is an instance of the standard built-in **Number** constructor

NOTE A Number object is created by using the **Number** constructor in a **new** expression, supplying a Number value as an argument. The resulting object has an internal property whose value is the Number value. A Number object can be coerced to a Number value by calling the **Number** constructor as a function (15.7.1).

4.3.22

Infinity

number value that is the positive infinite Number value

4.3.23

NaN

number value that is a IEEE 754 “Not-a-Number” value

4.3.24**function**

member of the Object type that is an instance of the standard built-in **Function** constructor and that may be invoked as a subroutine

NOTE In addition to its named properties, a function contains executable code and state that determine how it behaves when invoked. A function's code may or may not be written in ECMAScript.

4.3.25**built-in function**

built-in object that is a function

NOTE Examples of built-in functions include **parseInt** and **Math.exp**. An implementation may provide implementation-dependent built-in functions that are not described in this specification.

4.3.26**property**

association between a name and a value that is a part of an object

NOTE Depending upon the form of the property the value may be represented either directly as a data value (a primitive value, an object, or a function object) or indirectly by a pair of accessor functions.

4.3.27**method**

function that is the value of a property

NOTE When a function is called as a method of an object, the object is passed to the function as its **this** value.

4.3.28**built-in method**

method that is a built-in function

NOTE Standard built-in methods are defined in this specification, and an ECMAScript implementation may specify and provide other additional built-in methods.

4.3.29**attribute**

internal value that defines some characteristic of a property

4.3.30**own property**

property that is directly contained by its object

4.3.31**inherited property**

property of an object that is not an own property but is a property (either own or inherited) of the object's prototype

5 Notational Conventions

5.1 Syntactic and Lexical Grammars

5.1.1 Context-Free Grammars

A *context-free grammar* consists of a number of *productions*. Each production has an abstract symbol called a *nonterminal* as its *left-hand side*, and a sequence of zero or more nonterminal and *terminal* symbols as its *right-hand side*. For each grammar, the terminal symbols are drawn from a specified alphabet.

Deleted:

A chain production is a production that has exactly one nonterminal symbol on its right-hand side along with zero or more terminal symbols.

Deleted: one

Starting from a sentence consisting of a single distinguished nonterminal, called the *goal symbol*, a given context-free grammar specifies a *language*, namely, the (perhaps infinite) set of possible sequences of terminal symbols that can result from repeatedly replacing any nonterminal in the sequence with a right-hand side of a production for which the nonterminal is the left-hand side.

5.1.2 The Lexical and RegExp Grammars

A *lexical grammar* for ECMAScript is given in clause 7. This grammar has as its terminal symbols characters (Unicode code units) that conform to the rules for *SourceCharacter* defined in Clause 6. It defines a set of productions, starting from the goal symbol *InputElementDiv* or *InputElementRegExp*, that describe how sequences of such characters are translated into a sequence of input elements.

Input elements other than white space and comments form the terminal symbols for the syntactic grammar for ECMAScript and are called ECMAScript *tokens*. These tokens are the reserved words, identifiers, literals, and punctuators of the ECMAScript language. Moreover, line terminators, although not considered to be tokens, also become part of the stream of input elements and guide the process of automatic semicolon insertion (7.9). Simple white space and single-line comments are discarded and do not appear in the stream of input elements for the syntactic grammar. A *MultiLineComment* (that is, a comment of the form “/*...*/” regardless of whether it spans more than one line) is likewise simply discarded if it contains no line terminator; but if a *MultiLineComment* contains one or more line terminators, then it is replaced by a single line terminator, which becomes part of the stream of input elements for the syntactic grammar.

A *RegExp grammar* for ECMAScript is given in 15.10. This grammar also has as its terminal symbols the characters as defined by *SourceCharacter*. It defines a set of productions, starting from the goal symbol *Pattern*, that describe how sequences of characters are translated into regular expression patterns.

Productions of the lexical and RegExp grammars are distinguished by having two colons “::” as separating punctuation. The lexical and RegExp grammars share some productions.

5.1.3 The Numeric String Grammar

Another grammar is used for translating Strings into numeric values. This grammar is similar to the part of the lexical grammar having to do with numeric literals and has as its terminal symbols *SourceCharacter*. This grammar appears in 9.3.1.

Productions of the numeric string grammar are distinguished by having three colons “:::” as punctuation.

5.1.4 The Syntactic Grammar

The *syntactic grammar* for ECMAScript is given in clauses 11, 12, 13 and 14. This grammar has ECMAScript tokens defined by the lexical grammar as its terminal symbols (5.1.2). It defines a set of productions, starting from the goal symbol *Program*, that describe how sequences of tokens can form syntactically correct ECMAScript programs.

When a stream of characters is to be parsed as an ECMAScript program, it is first converted to a stream of input elements by repeated application of the lexical grammar; this stream of input elements is then parsed by a single application of the syntactic grammar. The program is syntactically in error if the tokens in the stream of input elements cannot be parsed as a single instance of the goal nonterminal *Program*, with no tokens left over.

Productions of the syntactic grammar are distinguished by having just one colon “:” as punctuation.

The syntactic grammar as presented in clauses 11, 12, 13 and 14 is actually not a complete account of which token sequences are accepted as correct ECMAScript programs. Certain additional token sequences are also accepted, namely, those that would be described by the grammar if only semicolons were added to the sequence in certain places (such as before line terminator characters). Furthermore, certain token sequences

that are described by the grammar are not considered acceptable if a terminator character appears in certain “awkward” places.

In certain cases in order to avoid ambiguities the syntactic grammar uses generalize productions that permit token sequences that are not valid ECMAScript programs. For example, this technique is used in with object literals and object destructuring patterns. In such cases a more restrictive supplemental grammar is provided that further restricts the acceptable token sequences. In certain contexts, when explicitly specific, the input elements corresponding to such a production are parsed again using a goal symbol of a supplemental grammar. The program is syntactically in error if the tokens in the stream of input elements cannot be parsed as a single instance of the supplemental goal symbol, with no tokens left over.

Deleted:

Deleted: such situations

Deleted: is

5.1.5 The JSON Grammar

The JSON grammar is used to translate a String describing a set of ECMAScript objects into actual objects. The JSON grammar is given in 15.12.1.

The JSON grammar consists of the JSON lexical grammar and the JSON syntactic grammar. The JSON lexical grammar is used to translate character sequences into tokens and is similar to parts of the ECMAScript lexical grammar. The JSON syntactic grammar describes how sequences of tokens from the JSON lexical grammar can form syntactically correct JSON object descriptions.

Productions of the JSON lexical grammar are distinguished by having two colons “::” as separating punctuation. The JSON lexical grammar uses some productions from the ECMAScript lexical grammar. The JSON syntactic grammar is similar to parts of the ECMAScript syntactic grammar. Productions of the JSON syntactic grammar are distinguished by using one colon “:” as separating punctuation.

5.1.6 Grammar Notation

Terminal symbols of the lexical, RegExp, and numeric string grammars, and some of the terminal symbols of the other grammars, are shown in **fixed width** font, both in the productions of the grammars and throughout this specification whenever the text directly refers to such a terminal symbol. These are to appear in a program exactly as written. All terminal symbol characters specified in this way are to be understood as the appropriate Unicode character from the ASCII range, as opposed to any similar-looking characters from other Unicode ranges.

Nonterminal symbols are shown in *italic* type. The definition of a nonterminal (also called a “production”) is introduced by the name of the nonterminal being defined followed by one or more colons. (The number of colons indicates to which grammar the production belongs.) One or more alternative right-hand sides for the nonterminal then follow on succeeding lines. For example, the syntactic definition:

```
WhileStatement :
  while ( Expression ) Statement
```

states that the nonterminal *WhileStatement* represents the token `while`, followed by a left parenthesis token, followed by an *Expression*, followed by a right parenthesis token, followed by a *Statement*. The occurrences of *Expression* and *Statement* are themselves nonterminals. As another example, the syntactic definition:

```
ArgumentList :
  AssignmentExpression
  ArgumentList , AssignmentExpression
```

states that an *ArgumentList* may represent either a single *AssignmentExpression* or an *ArgumentList*, followed by a comma, followed by an *AssignmentExpression*. This definition of *ArgumentList* is recursive, that is, it is defined in terms of itself. The result is that an *ArgumentList* may contain any positive number of arguments, separated by commas, where each argument expression is an *AssignmentExpression*. Such recursive definitions of nonterminals are common.

The subscripted suffix “_{opt}”, which may appear after a terminal or nonterminal, indicates an optional symbol. The alternative containing the optional symbol actually specifies two right-hand sides, one that omits the optional element and one that includes it. This means that:

VariableDeclaration :
*Identifier Initialiser*_{opt}

is a convenient abbreviation for:

VariableDeclaration :
Identifier
Identifier Initialiser

and that:

IterationStatement :
for (*ExpressionNoIn*_{opt} ; *Expression*_{opt} ; *Expression*_{opt}) *Statement*

is a convenient abbreviation for:

IterationStatement :
for (; *Expression*_{opt} ; *Expression*_{opt}) *Statement*
for (*ExpressionNoIn* ; *Expression*_{opt} ; *Expression*_{opt}) *Statement*

which in turn is an abbreviation for:

IterationStatement :
for (; ; *Expression*_{opt}) *Statement*
for (; *Expression* ; *Expression*_{opt}) *Statement*
for (*ExpressionNoIn* ; ; *Expression*_{opt}) *Statement*
for (*ExpressionNoIn* ; *Expression* ; *Expression*_{opt}) *Statement*

which in turn is an abbreviation for:

IterationStatement :
for (; ;) *Statement*
for (; ; *Expression*) *Statement*
for (; *Expression* ;) *Statement*
for (; *Expression* ; *Expression*) *Statement*
for (*ExpressionNoIn* ; ;) *Statement*
for (*ExpressionNoIn* ; ; *Expression*) *Statement*
for (*ExpressionNoIn* ; *Expression* ;) *Statement*
for (*ExpressionNoIn* ; *Expression* ; *Expression*) *Statement*

so the nonterminal *IterationStatement* actually has eight alternative right-hand sides.

When the words “**one of**” follow the colon(s) in a grammar definition, they signify that each of the terminal symbols on the following line or lines is an alternative definition. For example, the lexical grammar for ECMAScript contains the production:

NonZeroDigit :: **one of**
 1 2 3 4 5 6 7 8 9

which is merely a convenient abbreviation for:

NonZeroDigit ::

1
2
3
4
5
6
7
8
9

If the phrase “[empty]” appears as the right-hand side of a production, it indicates that the production's right-hand side contains no terminals or nonterminals.

If the phrase “[lookahead \notin set]” appears in the right-hand side of a production, it indicates that the production may not be used if the immediately following input token is a member of the given *set*. The *set* can be written as a list of terminals enclosed in curly braces. For convenience, the set can also be written as a nonterminal, in which case it represents the set of all terminals to which that nonterminal could expand. For example, given the definitions

DecimalDigit :: **one of**
0 1 2 3 4 5 6 7 8 9

DecimalDigits ::
DecimalDigit
DecimalDigits *DecimalDigit*

the definition

LookaheadExample ::
n [lookahead \notin {1, 3, 5, 7, 9}] *DecimalDigits*
DecimalDigit [lookahead \notin *DecimalDigit*]

matches either the letter **n** followed by one or more decimal digits the first of which is even, or a decimal digit not followed by another decimal digit.

If the phrase “[no LineTerminator here]” appears in the right-hand side of a production of the syntactic grammar, it indicates that the production is a **restricted production**: it may not be used if a *LineTerminator* occurs in the input stream at the indicated position. For example, the production:

ThrowStatement :
throw [no LineTerminator here] *Expression* ;

indicates that the production may not be used if a *LineTerminator* occurs in the program between the **throw** token and the *Expression*.

Unless the presence of a *LineTerminator* is forbidden by a restricted production, any number of occurrences of *LineTerminator* may appear between any two consecutive tokens in the stream of input elements without affecting the syntactic acceptability of the program.

The lexical grammar has multiple goal symbols and the appropriate goal symbol to use depends upon the syntactic grammar context. If a phrase of the form “[lexical goal LexicalGoalSymbol]” appears on the right-hand-side of a syntactic production then the next token must be lexically recognized using the indicated goal symbol. In the absence of such a phrase the default lexical goal symbol is used.

When an alternative in a production of the lexical grammar or the numeric string grammar appears to be a multi-character token, it represents the sequence of characters that would make up such a token.

The right-hand side of a production may specify that certain expansions are not permitted by using the phrase “**but not**” and then indicating the expansions to be excluded. For example, the production:

Identifier ::
IdentifierName **but not** *ReservedWord*

means that the nonterminal *Identifier* may be replaced by any sequence of characters that could replace *IdentifierName* provided that the same sequence of characters could not replace *ReservedWord*.

Finally, a few nonterminal symbols are described by a descriptive phrase in sans-serif type in cases where it would be impractical to list all the alternatives:

SourceCharacter ::
any Unicode character

Deleted: code unit

5.2 Algorithm Conventions

The specification often uses a numbered list to specify steps in an algorithm. These algorithms are used to precisely specify the required semantics of ECMAScript language constructs. The algorithms are not intended to imply the use of any specific implementation technique. In practice, there may be more efficient algorithms available to implement a given feature.

Algorithms may be explicitly parameterized, in which case the names and usage of the parameters must be provided as part of the algorithm's definition. In order to facilitate their use in multiple parts of this specification, some algorithms, called *abstract operations*, are named and written in parameterised functional form so that they may be referenced by name from within other algorithms.

Deleted: the

Algorithms may be associated with productions of one of the ECMAScript grammars. A production that has multiple alternative definitions will typically have a distinct algorithm for each alternative. When an algorithm is associated with a grammar production, it may reference the terminal and non-terminal symbols of the production alternative as if they were parameters of the algorithm. When used in this manner, non-terminal symbols refer to the actual alternative definition that is matched when parsing the program source code.

Unless explicitly specified otherwise, all chain productions have an implicit associated definition for every algorithm that might be applied to that production's left-hand side nonterminal. The implicit simply reapplies the same algorithm name with the same parameters, if any, to the chain production's sole right-hand side nonterminal and then result. For example, assume there is a production

Deleted: ra

Block :
{ *StatementList* }

but there is no evaluation algorithm that is explicitly specified for that production. If in some algorithm there is a statement of the form: “Return the result of evaluating *Block*” it is implicit that the algorithm has an evaluation algorithm of the form:

Runtime Semantics: Evaluation

Block : { *StatementList* }

1. Return the result of evaluating *StatementList*

For clarity of expression, algorithm steps may be subdivided into sequential substeps. Substeps are indented and may themselves be further divided into indented substeps. Outline numbering conventions are used to identify substeps with the first level of substeps labelled with lower case alphabetic characters and the second level of substeps labelled with lower case roman numerals. If more than three levels are required these rules repeat with the fourth level using numeric labels. For example:

1. Top-level step
 - a. Substep.

Deleted: When an algorithm is to produce a value as a result, the directive “return *x*” is used to indicate that the result of the algorithm is the value of *x* and that the algorithm should terminate. The notation *Result(n)* is used as shorthand for “the result of step *n*”. ¶

- b. Substep
 - i. Subsubstep.
 - ii. Subsubstep.
 - 1. Subsubsubstep
 - a Subsubsubsubstep

A step or substep may be written as an "if" predicate that conditions its substeps. In this case, the substeps are only applied if the predicate is true. If a step or substep begins with the word "else", it is a predicate that is the negation of the preceding "if" predicate step at the same level.

A step may specify the iterative application of its substeps.

A step may assert an invariant condition of its algorithm. Such assertions are used to make explicit algorithmic invariants that would otherwise be implicit. Such assertions add no additional semantic requirements and hence need not be checked by an implementation. They are used simply to clarify algorithms.

Mathematical operations such as addition, subtraction, negation, multiplication, division, and the mathematical functions defined later in this clause should always be understood as computing exact mathematical results on mathematical real numbers, which do not include infinities and do not include a negative zero that is distinguished from positive zero. Algorithms in this standard that model floating-point arithmetic include explicit steps, where necessary, to handle infinities and signed zero and to perform rounding. If a mathematical operation or function is applied to a floating-point number, it should be understood as being applied to the exact mathematical value represented by that floating-point number; such a floating-point number must be finite, and if it is $+0$ or -0 then the corresponding mathematical value is simply 0 .

The mathematical function $\text{abs}(x)$ yields the absolute value of x , which is $-x$ if x is negative (less than zero) and otherwise is x itself.

The mathematical function $\text{sign}(x)$ yields 1 if x is positive and -1 if x is negative. The sign function is not used in this standard for cases when x is zero.

The notation " x modulo y " (y must be finite and nonzero) computes a value k of the same sign as y (or zero) such that $\text{abs}(k) < \text{abs}(y)$ and $x-k = q \times y$ for some integer q .

The mathematical function $\text{floor}(x)$ yields the largest integer (closest to positive infinity) that is not larger than x .

NOTE $\text{floor}(x) = x - (x \text{ modulo } 1)$.

If an algorithm is defined to "throw an exception", execution of the algorithm is terminated and no result is returned. The calling algorithms are also terminated, until an algorithm step is reached that explicitly deals with the exception, using terminology such as "If an exception was thrown...". Once such an algorithm step has been encountered the exception is no longer considered to have occurred.

5.3 Static Semantic Rules

Context-free grammars are not sufficiently powerful to express all the rules that define whether a stream of input elements make up a valid ECMAScript program that may be evaluated. In some situations additional rules are needed that may be expressed using either ECMAScript algorithm conventions or prose requirements. Such rules are always associated with a production of a grammar and are called the *static semantics* of the production.

Static Semantic Rules have names and typically are defined using an algorithm. Named Static Semantic Rules are associated with grammar productions and a production that has multiple alternative definitions will typically have for each alternative a distinct algorithm for each applicable named static semantic rule.

Deleted: Such algorithms may be parameterized.

Unless otherwise specified every grammar production alternative in this specification implicitly has a definition for a static semantic rule named `Contains` which takes an argument named `symbol` whose value is a terminal or non-terminal of the grammar that includes the associated production. The default definition of `Contains` is:

1. For each terminal and non-terminal grammar symbol, *sym*, in the definition of this production do
 - a. If *sym* is the same grammar symbol as *symbol*, return **true**.
 - b. If *sym* is a non-terminal, then
 - i. Let *contained* be the result of Contains for *sym* with argument *symbol*.
 - ii. If *contained* is **true**, return **true**.
2. Return **false**.

The above definition is explicitly over-ridden for specific productions.

A special kind of static semantic rule is an Early Error Rule. Early error rules define early error conditions (see clause 16) that are associate with specific grammar productions. Evaluation of most early error rules are not explicitly invoked within the algorithms of this specification. A conforming implementation must, prior to the first evaluation of a *Program*, validate all of the early error rules of the productions used to parse that *Program*. If any of the early error rules are violated the *Program* is invalid and can not be evaluated.

6 Source Text

Syntax

SourceCharacter ::=
any Unicode character

The ECMAScript code is expressed using Unicode, version 5.1 or later. ECMAScript source text is a sequence of Unicode characters. The phrase “Unicode character” refers to the abstract linguistic or typographical unit represented by a single Unicode scalar value. The actual encodings used to store and interchange ECMAScript source text is not relevant to this specification. Any well defined encoding such as UTF-32 or UTF-16 may be used. Source text might even be externally represented using a non-Unicode character encoding. Regardless of the external source text encoding, a conforming ECMAScript implementation processes the source text as if it was an equivalent sequence of *SourceCharacter* values. Each *SourceCharacter* being an abstract Unicode character with a corresponding Unicode scalar value. Conforming ECMAScript implementations are not required to perform any normalisation of text, or behave as though they were performing normalisation of text.

The phrase “code point” refers to such a Unicode scalar value. “Unicode character” only refers to entities represented by single Unicode scalar values: the components of a combining character sequence are still individual “Unicode characters,” even though a user might think of the whole sequence as a single character.

In string literals, regular expression literals, template literals and identifiers, any *Unicode* characters may also be expressed as a Unicode escape sequence *that explicitly express a code point's numeric value*. Within a comment, such an escape sequence is effectively ignored as part of the comment. *Within other contexts, such an escape sequence contextually contributes one *Unicode* character*.

NOTE ECMAScript differs from the Java programming language in the behaviour of Unicode escape sequences. In a Java program, if the Unicode escape sequence \u000a, for example, occurs within a single-line comment, it is interpreted as a line terminator (Unicode character 000a is line feed) and therefore the next *Unicode* character is not part of the comment. Similarly, if the Unicode escape sequence \u000a occurs within a string literal in a Java program, it is likewise interpreted as a line terminator, which is not allowed within a string literal—one must write \n instead of \u000a to cause a line feed to be part of the string value of a string literal. In an ECMAScript program, a Unicode escape sequence occurring within a comment is never interpreted and therefore cannot contribute to termination of the comment. Similarly, a Unicode escape sequence occurring within a string literal in an ECMAScript program always contributes a *Unicode* character to the literal and is never interpreted as a line terminator or as a quote mark that might terminate the string literal.

ECMAScript String values (8.4) are computational sequences of 16-bit integer values called “code units”. ECMAScript language constructs that generate string values from *SourceCharacter* sequences use UTF-16 encoding to generate the code unit values.

Static Semantics: UTF-16 Encoding

The UTF-16 Encoding of a numeric code point value, *cp*, is determined as follows:

Deleted:
Deleted: I
Deleted: An
Deleted: static semantic
Deleted: used to
Deleted: a
Deleted: prior to the first evaluation of that <i>Program</i>
Comment [AW2]: Perhaps this should be somewhere else. Currently we don't have a section that enumerates all the steps in loading and evaluating a program.
Deleted: static semantic
Deleted: Static semantic rule violations are early errors (see clause 16) and reported in the same manner as syntax errors.
Deleted: ECMAScript source text is represented as a sequence of characters in the Unicode character encoding, version 3.0 or later. The text is expected to have been normalised to Unicode Normalization Form (canonical composition), as described in Unicode Technical Report #15. Conforming ECMAScript implementations are not required to perform any normalisation of text, or behave as though they were performing normalisation of text, themselves. ECMAScript source text is assumed to be a sequence of 16-bit code units for the purposes of this specification. Such a source text may include sequences of 16-bit code units that are not valid UTF-16 character encodings. If actual source text is encoded in a form other than 16-bit code units it must be processed as if it was first converted to UTF-16. ¹¹
Deleted: code unit
Deleted: source character
Deleted: s
Deleted: Throughout the rest of this document, the phrase “code unit” and the word “character” will be used to refer to a 16-bit unsigned value used to represent a single 16-bit unit of text. The phrase “Unicode character” will be used to refer to the abstract linguistic or typographical unit represented by a single Unicode scalar value (which may be longer than 16 bits and thus may be represented by more than one code unit).
Deleted: quasi
Deleted: (code unit)
Deleted: consisting
Deleted: of six characters, namely \u plus four hexadecimal digits.
Deleted: Within a string literal or regular expression literal, the Unicode escape sequence contributes one character to the value of the literal. Within an identifier,
Deleted: the
Deleted: to the identifier
Deleted: ¶
Formatted: Note
Deleted: NOTE Although this document sometimes refers to a “transformation” between a “character” within “string” and the 16-bit unsigned integer that is the code unit of that character, there is actually no transformation.
Deleted: String value of the

1. Assert: $0 \leq cp \leq 0x10FFFF$
2. If $cp \leq 65535$, then return cp .
3. Let $cu1$ be $\text{floor}((cp - 65536) / 1024) + 55296$. NOTE 55296 is 0xD800.
4. Let $cu2$ be $((cp - 65536) \bmod 1024) + 56320$. NOTE 56320 is 0xDC00.
5. Return the code unit sequence consisting of $cu1$ followed by $cu2$.

7 Lexical Conventions

The source text of an ECMAScript program is first converted into a sequence of input elements, which are tokens, line terminators, comments, or white space. The source text is scanned from left to right, repeatedly taking the longest possible sequence of characters as the next input element.

There are several situations where the identification of lexical input elements is sensitive to the syntactic grammar context that is consuming the input elements. This requires multiple goal symbols for the lexical grammar. The `InputElementDiv` goal symbol is the default goal symbol and is used in those syntactic grammar contexts where a leading division (/) or division-assignment (/=) operator is permitted. The `InputElementRegExp` goal symbol is used in all syntactic grammar contexts where a `RegularExpressionLiteral` is permitted. The `InputElementTemplateTail` goal is used in syntactic grammar contexts where a `TemplateLiteral` logically continues after a substitution element.

NOTE There are no syntactic grammar contexts where both a leading division or division-assignment, and a leading `RegularExpressionLiteral` are permitted. This is not affected by semicolon insertion (see 7.9); in examples such as the following:

```
a = b
/hi/g.exec(c).map(d);
```

where the first non-whitespace, non-comment character after a `LineTerminator` is slash (/) and the syntactic context allows division or division-assignment, no semicolon is inserted at the `LineTerminator`. That is, the above example is interpreted in the same way as:

```
a = b / hi / g.exec(c).map(d);
```

Syntax

InputElementDiv ::
WhiteSpace
LineTerminator
Comment
Token
DivPunctuator
RightBracePunctuator

InputElementRegExp ::
WhiteSpace
LineTerminator
Comment
Token
RightBracePunctuator
RegularExpressionLiteral

InputElementTemplateTail ::
WhiteSpace
LineTerminator
Comment
Token
DivPunctuator
TemplateSubstitutionTail

Deleted: o
Deleted: There
Deleted: are two
Deleted: other
Deleted: Quasi
Deleted: Quasi

Comment [AWB93]: May need to also say something about `TemplateSubstitutionTail`. Also need to consider with there are any ASI issues concerning it.

7.1 Unicode Format-Control Characters

The Unicode format-control characters (i.e., the characters in category “Cf” in the Unicode Character Database such as LEFT-TO-RIGHT MARK or RIGHT-TO-LEFT MARK) are control codes used to control the formatting of a range of text in the absence of higher-level protocols for this (such as mark-up languages).

It is useful to allow format-control characters in source text to facilitate editing and display. All format control characters may be used within comments, and within string literals, [template literals](#), and regular expression literals.

<ZWNJ> and <ZWJ> are format-control characters that are used to make necessary distinctions when forming words or phrases in certain languages. In ECMAScript source text, <ZWNJ> and <ZWJ> may also be used in an identifier after the first character.

<BOM> is a format-control character used primarily at the start of a text to mark it as Unicode and to allow detection of the text's encoding and byte order. <BOM> characters intended for this purpose can sometimes also appear after the start of a text, for example as a result of concatenating files. <BOM> characters are treated as white space characters (see 7.2).

The special treatment of certain format-control characters outside of comments, string literals, and regular expression literals is summarised in [Table 1](#).

Table 1 — Format-Control Character Usage

Code Point	Name	Formal Name	Usage
U+200C	Zero width non-joiner	<ZWNJ>	IdentifierPart
U+200D	Zero width joiner	<ZWJ>	IdentifierPart
U+FEFF	Byte Order Mark	<BOM>	Whitespace

7.2 White Space

White space characters are used to improve source text readability and to separate tokens (indivisible lexical units) from each other, but are otherwise insignificant. White space characters may occur between any two tokens and at the start or end of input. White space characters may occur within a [StringLiteral](#), a [RegularExpressionLiteral](#), a [Template](#), or a [TemplateSubstitutionTail](#), where they are considered significant characters forming part of a literal value. They may also occur within a [Comment](#), but cannot appear within any other kind of token.

The ECMAScript white space characters are listed in [Table 2](#).

Table 2 — Whitespace Characters

Code Point	Name	Formal Name
U+0009	Tab	<TAB>
U+000B	Vertical Tab	<VT>
U+000C	Form Feed	<FF>
U+0020	Space	<SP>
U+00A0	No-break space	<NBSP>
U+FEFF	Byte Order Mark	<BOM>
Other category “Zs”	Any other Unicode “space separator”	<USP>

ECMAScript implementations must recognise all of the white space characters defined in [Unicode 5.1](#). Later editions of the Unicode Standard may define other white space characters. ECMAScript implementations may recognise white space characters from later editions of the Unicode Standard.

Deleted: , quasi

Deleted: Unit

Deleted: Value

Deleted: \u

Deleted: \u

Deleted: \u

Deleted: also

Deleted: or

Deleted:

Deleted: Quasi

Deleted: Quasi

Deleted: (

Deleted: the

Deleted:)

Deleted: or

Deleted: Unit

Deleted: Value

Deleted: \u

Deleted: \u

Deleted: \u

Deleted: \u

Deleted: \u

Deleted: 3

Deleted: 0

Syntax

```
WhiteSpace ::=
    <TAB>
    <VT>
    <FF>
    <SP>
    <NBSP>
    <BOM>
    <USP>
```

7.3 Line Terminators

Like white space characters, line terminator characters are used to improve source text readability and to separate tokens (indivisible lexical units) from each other. However, unlike white space characters, line terminators have some influence over the behaviour of the syntactic grammar. In general, line terminators may occur between any two tokens, but there are a few places where they are forbidden by the syntactic grammar. Line terminators also affect the process of automatic semicolon insertion (7.9). A line terminator cannot occur within any token except a *StringLiteral*, *Template*, or *TemplateSubstitutionTail*. Line terminators may only occur within a *StringLiteral* token as part of a *LineContinuation*.

A line terminator can occur within a *MultiLineComment* (7.4) but cannot occur within a *SingleLineComment*.

Line terminators are included in the set of white space characters that are matched by the \s class in regular expressions.

The ECMAScript line terminator characters are listed in [Table 3](#).

Table 3 — Line Terminator Characters

Code Point	Name	Formal Name
U+000A	Line Feed	<LF>
U+000D	Carriage Return	<CR>
U+2028	Line separator	<LS>
U+2029	Paragraph separator	<PS>

Only the [Unicode](#) characters in [Table 3](#) are treated as line terminators. Other new line or line breaking [Unicode](#) characters are treated as white space but not as line terminators. The sequence <CR><LF> is commonly used as a line terminator. It should be considered a single [SourceCharacter](#) for the purpose of reporting line numbers.

Syntax

```
LineTerminator ::=
    <LF>
    <CR>
    <LS>
    <PS>
```

```
LineTerminatorSequence ::=
    <LF>
    <CR> [lookahead &lt;LF> ]
    <LS>
    <PS>
    <CR> <LF>
```

7.4 Comments

Comments can be either single or multi-line. Multi-line comments cannot nest.

Comment [AWB94]: Need to talk about line terminators in Templates

Deleted: Quasi

Deleted: Quasi

Deleted: Unit

Deleted: Value

Deleted: \u

Deleted: \u

Deleted: \u

Deleted: \u

Deleted: character

Deleted: character

Because a single-line comment can contain any [Unicode](#) character except a *LineTerminator* character, and because of the general rule that a token is always as long as possible, a single-line comment always consists of all characters from the `//` marker to the end of the line. However, the *LineTerminator* at the end of the line is not considered to be part of the single-line comment; it is recognised separately by the lexical grammar and becomes part of the stream of input elements for the syntactic grammar. This point is very important, because it implies that the presence or absence of single-line comments does not affect the process of automatic semicolon insertion (see 7.9).

Comments behave like white space and are discarded except that, if a *MultiLineComment* contains a line terminator character, then the entire comment is considered to be a *LineTerminator* for purposes of parsing by the syntactic grammar.

Syntax

Comment ::

MultiLineComment
 SingleLineComment

MultiLineComment ::

`/* MultiLineCommentCharsopt */`

MultiLineCommentChars ::

MultiLineNotAsteriskChar *MultiLineCommentChars_{opt}*
 `* PostAsteriskCommentCharsopt`

PostAsteriskCommentChars ::

MultiLineNotForwardSlashOrAsteriskChar *MultiLineCommentChars_{opt}*
 `* PostAsteriskCommentCharsopt`

MultiLineNotAsteriskChar ::

SourceCharacter **but not** `*`

MultiLineNotForwardSlashOrAsteriskChar ::

SourceCharacter **but not one of** `/` `*`

SingleLineComment ::

`// SingleLineCommentCharsopt`

SingleLineCommentChars ::

SingleLineCommentChar *SingleLineCommentChars_{opt}*

SingleLineCommentChar ::

SourceCharacter **but not** *LineTerminator*

7.5 Tokens

Syntax

Token ::

IdentifierName
 Punctuator
 NumericLiteral
 StringLiteral
 Template

Deleted: *Quasi*

Deleted: *and*

Deleted: *Quasi*

NOTE The *DivPunctuator*, *RegularExpressionLiteral*, *RightBracePunctuator*, and *TemplateSubstitutionTail* productions define tokens, but are not included in the *Token* production.

7.6 Identifier Names and Identifiers

IdentifierName, *Identifier*, and *ReservedWord* are tokens that are interpreted according to the [Default Identifier Syntax given in Unicode Standard Annex #31, Identifier and Pattern Syntax](#), with some small modifications. *ReservedWord* is an enumerated subset of *IdentifierName* and *Identifier* is an *IdentifierName* that is not a *ReservedWord* (see 7.6.1). The Unicode identifier grammar is based on character *properties* specified by the Unicode Standard. The [Unicode](#) characters in the specified categories in version 5.1.0 of the Unicode standard must be treated as in those categories by all conforming ECMAScript implementations.

NOTE This standard specifies specific character additions: The dollar sign ([U+0024](#)) and the underscore ([U+005f](#)) are permitted anywhere in an *IdentifierName*, and the characters zero width non-joiner ([U+200C](#)) and zero width joiner ([U+200D](#)) are permitted anywhere after the first character of an *IdentifierName*.

Unicode escape sequences are permitted in an *IdentifierName*, where they contribute a single [Unicode](#) character to the *IdentifierName*. The code point of the contributed character is expressed by the *HexDigits* of the [UnicodeEscapeSequence](#) (see 7.8.4). The \ preceding the [UnicodeEscapeSequence](#) and the u and {} characters, if they appear, do not contribute characters to the *IdentifierName*. A [UnicodeEscapeSequence](#) cannot be used to put a character into an *IdentifierName* that would otherwise be illegal. In other words, if a \ [UnicodeEscapeSequence](#) sequence were replaced by the [Unicode character it contributes](#), the result must still be a valid *IdentifierName* that has the exact same sequence of characters as the original *IdentifierName*. All interpretations of *IdentifierName* within this specification are based upon their actual characters regardless of whether or not an escape sequence was used to contribute any particular characters.

Two *IdentifierName* that are canonically equivalent according to the Unicode standard are not equal unless they are represented by the exact same sequence of code units (in other words, conforming ECMAScript implementations are only required to do bitwise comparison on *IdentifierName* values).

ECMAScript implementations may recognise identifier characters defined in later editions of the Unicode Standard. If portability is a concern, programmers should only employ identifier characters defined in Unicode 3.0.

Syntax

Identifier ::
 IdentifierName but not *ReservedWord*

IdentifierName ::
 IdentifierStart
 IdentifierName *IdentifierPart*

IdentifierStart ::
 [UnicodeIDStart](#)
 \$
 \ [UnicodeEscapeSequence](#)

IdentifierPart ::
 [UnicodeIDContinue](#)
 \$
 \ [UnicodeEscapeSequence](#)
<ZWNJ>
<ZWJ>

UnicodeIDStart ::
 any [Unicode](#) character with the [Unicode](#) property "ID_Start".

UnicodeIDContinue ::
 any [Unicode](#) character with the [Unicode](#) property "ID_Continue".

- Deleted:** Identifier,
- Deleted:** Identifier Names
- Deleted:** grammar given in the "Identifiers" section of chapter 5 of the Unicode standard
- Deleted:** An
- Deleted:** both normative and informative
- Deleted:** categories
- Deleted:** 3
- Formatted:** Note
- Deleted:** (\$)
- Deleted:** ()
- Deleted:** also
- Deleted:** ,
- Deleted:** as computed by the CV of the
- Deleted:** es
- Deleted:** a
- Deleted:** its
- Deleted:** [UnicodeEscapeSequence](#)'s CV
- Deleted:** identifiers
- Deleted:** The intent is that the incoming source text has been converted to normalised form C before it reaches the compiler.
- Comment [AWB95]:** Norbert suggests changing this to 5.1.0. Would be really be better for "portability"?
- Deleted:** [UnicodeLetter](#)
- Deleted:** [IdentifierStart](#)
- Deleted:** [Identifier](#)
- Deleted:** [UnicodeCombiningMark](#) .. [UnicodeDigit](#) [UnicodeConnectorPunctuation](#)
- Deleted:** [UnicodeLetter](#)
- Deleted:** in
- Deleted:** categories
- Deleted:** Uppercase letter (Lu)
- Deleted:** , "Lowercase letter (Ll)", "Titlecase letter (Lt)", "Modifier letter (Lm)", "Other letter (Lo)", or "Letter number (Nl)"
- Deleted:** Start
- Deleted:** [UnicodeCombiningMark](#)
- Deleted:** in
- Deleted:** categories
- Deleted:** Non-spacing mark (Mn)
- Deleted:** or "Combining spacing mark (Mc)"

The definitions of the nonterminal *UnicodeEscapeSequence* is given in 7.8.4

Static Semantics: StringValue

Identifier :: *IdentifierName* but not *ReservedWord*

1. Return the StringValue of *IdentifierName*.

IdentifierName ::

IdentifierStart
IdentifierName IdentifierPart

1. Return the String value consisting of the sequence of code units corresponding to *IdentifierName*. In determining the sequence any occurrences of \ *UnicodeEscapeSequence* are first replaced with the code point represented by the *UnicodeEscapeSequence* and and then the code points of the entire *IdentifierName* are converted to code units by UTF-16 Encoding (clause 6) each code point.

7.6.1 Reserved Words

A reserved word is an *IdentifierName* that cannot be used as an *Identifier*.

Syntax

ReservedWord ::
 Keyword
 FutureReservedWord
 NullLiteral
 BooleanLiteral

The *ReservedWord* definitions are specified as literal sequences of Unicode characters. However, any Unicode character in a *ReservedWord* can also be expressed by a \ *UnicodeEscapeSequence* that expresses that same Unicode character's code point. Use of such escape sequences does not change the meaning of the *ReservedWord*.

7.6.1.1 Keywords

The following tokens are ECMAScript keywords and may not be used as *Identifiers* in ECMAScript programs.

Syntax

<i>Keyword</i> :: one of			
break	delete	import	this
case	do	in	throw
catch	else	instanceof	try
<u>class</u>	<u>export</u>	<u>let</u>	<u>typeof</u>
<u>continue</u>	finally	new	var
<u>const</u>	for	return	void
debugger	function	<u>super</u>	while
default	if	switch	with

7.6.1.2 Future Reserved Words

The following words are used as keywords in proposed extensions and are therefore reserved to allow for the possibility of future adoption of those extensions.

Deleted: *UnicodeDigit* :: any character in the Unicode category "Decimal number (Nd)"
UnicodeConnectorPunctuation :: any character in the Unicode category "Connector punctuation (Pc)"
Deleted:
Deleted: *Semantics*
 The String value of the production
Deleted: is determined as follows:
Deleted:
Deleted: v
Deleted: consisting
Deleted: The String value of *IdentifierName* is determined as follows:
Deleted: characters
Deleted: a

Syntax

FutureReservedWord :: one of

```
enum      extends
```

The following tokens are also considered to be *FutureReservedWords* when they occur within strict mode code (see 10.1.1). The occurrence of any of these tokens within strict mode code in any context where the occurrence of a *FutureReservedWord* would produce an error must also produce an equivalent error:

```
implements      private      public      yield
interface       package      protected     static
```

Comment [AWB86]: It isn't clear that *extends* actually needs to be reserved. It's only usage is highly contextual.

Deleted: class

Deleted: super

Deleted: const

Deleted: export

Deleted: import

Comment [AWB87]: Move to keywords

Deleted: let

7.7 Punctuators

Syntax

Punctuator :: one of

```
{   (   )   [
     ;   ,
     <   >   <=
     .   ;
     >=   ==   !=   ===   !==
     +   -   *   %
     <<   >>   >>>
     !   ~   &&   ||
     =   +=   -=   *=   %=   ^=   ^=
     >>=   >>>=   &=   |=   ^=   =>
```

Deleted: }

DivPunctuator :: one of

```
/   /=
```

RightBracePunctuator ::

```
}
```

7.8 Literals

7.8.1 Null Literals

Syntax

NullLiteral ::

```
null
```

Deleted: Syntax¶

Literal ::¶

NullLiteral

ValueLiteral ..

¶

ValueLiteral ::¶

BooleanLiteral

NumericLiteral ..

StringLiteral

RegularExpressionLiteral¶

7.8.2 Boolean Literals

Syntax

BooleanLiteral ::

```
true
```

```
false
```

Deleted: Semantics¶

The value of the null literal `null` is the sole value of the Null type, namely `null`.¶

7.8.3 Numeric Literals

Syntax

NumericLiteral ::

- DecimalLiteral*
- BinaryIntegerLiteral*
- OctalIntegerLiteral*
- HexIntegerLiteral*

DecimalLiteral ::

- DecimalIntegerLiteral* . *DecimalDigits_{opt}* *ExponentPart_{opt}*
- . *DecimalDigits* *ExponentPart_{opt}*
- DecimalIntegerLiteral* *ExponentPart_{opt}*

DecimalIntegerLiteral ::

- 0
- NonZeroDigit* *DecimalDigits_{opt}*

DecimalDigits ::

- DecimalDigit*
- DecimalDigits* *DecimalDigit*

DecimalDigit :: one of

- 0 1 2 3 4 5 6 7 8 9

NonZeroDigit :: one of

- 1 2 3 4 5 6 7 8 9

ExponentPart ::

- ExponentIndicator* *SignedInteger*

ExponentIndicator :: one of

- e E

SignedInteger ::

- DecimalDigits*
- + *DecimalDigits*
- *DecimalDigits*

BinaryIntegerLiteral ::

- 0b BinaryDigit
- 0B BinaryDigit
- BinaryIntegerLiteral BinaryDigit

BinaryDigit :: one of

- 0 1

OctalIntegerLiteral ::

- 0o OctalDigit
- 0O OctalDigit
- OctalIntegerLiteral OctalDigit

OctalDigit :: one of

- 0 1 2 3 4 5 6 7

HexIntegerLiteral ::

- 0x HexDigits
- 0X HexDigits

Deleted: Semantics¶

The value of the Boolean literal `true` is a value of the Boolean type, namely `true`.¶
The value of the Boolean literal `false` is a value of the Boolean type, namely `false`.¶

Comment [AWB78]:

From March 29 meeting notes:

Hex floating point literals:

Waldemar: Other languages include these things.

They're rarely used but when you want one, you really want one. Use cases are similar to that of hex literals.

Will explore adding them.

MarkM: `0x.p1` currently evaluates to undefined. This would be a breaking change.

Waldemar: Not clear anyone would notice. How did other languages deal with this?

Comment [AWB79]:

The various Digit productions could be refactored to have less redundancy

[HexDigits ::](#)[HexDigit](#)[HexDigits HexDigit](#)[HexDigit :: one of](#)[0 1 2 3 4 5 6 7 8 9 a b c d e f A B C D E F](#)**Deleted:****Deleted:** IntegerLiteralThe [SourceCharacter](#), immediately following a [NumericLiteral](#) must not be an [IdentifierStart](#) or [DecimalDigit](#).

NOTE For example:

3in

is an error and not the two input elements 3 and in.

Deleted: source characterA conforming implementation, when processing strict mode code (see 10.1.1), must not extend the syntax of [NumericLiteral](#) to include [OctalIntegerLiteral](#) as described in B.1.1.**Static Semantics: MV's**

A numeric literal stands for a value of the Number type. This value is determined in two steps: first, a mathematical value (MV) is derived from the literal; second, this mathematical value is rounded as described below.

- The MV of [NumericLiteral :: DecimalLiteral](#) is the MV of [DecimalLiteral](#).
- [The MV of NumericLiteral :: BinaryIntegerLiteral is the MV of BinaryIntegerLiteral.](#)
- [The MV of NumericLiteral :: OctalIntegerLiteral is the MV of OctalIntegerLiteral.](#)
- The MV of [NumericLiteral :: HexIntegerLiteral](#) is the MV of [HexIntegerLiteral](#).
- The MV of [DecimalLiteral :: DecimalIntegerLiteral .](#) is the MV of [DecimalIntegerLiteral](#).
- The MV of [DecimalLiteral :: DecimalIntegerLiteral . DecimalDigits](#) is the MV of [DecimalIntegerLiteral](#) plus (the MV of [DecimalDigits](#) times 10^{-n}), where n is the number of characters in [DecimalDigits](#).
- The MV of [DecimalLiteral :: DecimalIntegerLiteral . ExponentPart](#) is the MV of [DecimalIntegerLiteral](#) times 10^e , where e is the MV of [ExponentPart](#).
- The MV of [DecimalLiteral :: DecimalIntegerLiteral . DecimalDigits ExponentPart](#) is (the MV of [DecimalIntegerLiteral](#) plus (the MV of [DecimalDigits](#) times 10^{-n})) times 10^e , where n is the number of characters in [DecimalDigits](#) and e is the MV of [ExponentPart](#).
- The MV of [DecimalLiteral :: . DecimalDigits](#) is the MV of [DecimalDigits](#) times 10^{-n} , where n is the number of characters in [DecimalDigits](#).
- The MV of [DecimalLiteral :: . DecimalDigits ExponentPart](#) is the MV of [DecimalDigits](#) times 10^{e-n} , where n is the number of characters in [DecimalDigits](#) and e is the MV of [ExponentPart](#).
- The MV of [DecimalLiteral :: DecimalIntegerLiteral](#) is the MV of [DecimalIntegerLiteral](#).
- The MV of [DecimalLiteral :: DecimalIntegerLiteral ExponentPart](#) is the MV of [DecimalIntegerLiteral](#) times 10^e , where e is the MV of [ExponentPart](#).
- The MV of [DecimalIntegerLiteral :: 0](#) is 0.
- The MV of [DecimalIntegerLiteral :: NonZeroDigit](#) is the MV of [NonZeroDigit](#).
- The MV of [DecimalIntegerLiteral :: NonZeroDigit DecimalDigits](#) is (the MV of [NonZeroDigit](#) times 10^n) plus the MV of [DecimalDigits](#), where n is the number of characters in [DecimalDigits](#).
- The MV of [DecimalDigits :: DecimalDigit](#) is the MV of [DecimalDigit](#).
- The MV of [DecimalDigits :: DecimalDigits DecimalDigit](#) is (the MV of [DecimalDigits](#) times 10) plus the MV of [DecimalDigit](#).
- The MV of [ExponentPart :: ExponentIndicator SignedInteger](#) is the MV of [SignedInteger](#).
- The MV of [SignedInteger :: DecimalDigits](#) is the MV of [DecimalDigits](#).
- The MV of [SignedInteger :: + DecimalDigits](#) is the MV of [DecimalDigits](#).
- The MV of [SignedInteger :: - DecimalDigits](#) is the negative of the MV of [DecimalDigits](#).
- The MV of [DecimalDigit :: 0 or of HexDigit :: 0 or of OctalDigit :: 0 or of BinaryDigit :: 0](#) is 0.
- The MV of [DecimalDigit :: 1 or of NonZeroDigit :: 1 or of HexDigit :: 1 or of OctalDigit :: 1 or of BinaryDigit :: 1](#) is 1.

Deleted:

- The MV of *DecimalDigit* :: 2 or of *NonZeroDigit* :: 2 or of *HexDigit* :: 2 [or of *OctalDigit* :: 2](#) is 2.
- The MV of *DecimalDigit* :: 3 or of *NonZeroDigit* :: 3 or of *HexDigit* :: 3 [or of *OctalDigit* :: 3](#) is 3.
- The MV of *DecimalDigit* :: 4 or of *NonZeroDigit* :: 4 or of *HexDigit* :: 4 [or of *OctalDigit* :: 4](#) is 4.
- The MV of *DecimalDigit* :: 5 or of *NonZeroDigit* :: 5 or of *HexDigit* :: 5 [or of *OctalDigit* :: 5](#) is 5.
- The MV of *DecimalDigit* :: 6 or of *NonZeroDigit* :: 6 or of *HexDigit* :: 6 [or of *OctalDigit* :: 6](#) is 6.
- The MV of *DecimalDigit* :: 7 or of *NonZeroDigit* :: 7 or of *HexDigit* :: 7 [or of *OctalDigit* :: 7](#) is 7.
- The MV of *DecimalDigit* :: 8 or of *NonZeroDigit* :: 8 or of *HexDigit* :: 8 is 8.
- The MV of *DecimalDigit* :: 9 or of *NonZeroDigit* :: 9 or of *HexDigit* :: 9 is 9.
- The MV of *HexDigit* :: a or of *HexDigit* :: A is 10.
- The MV of *HexDigit* :: b or of *HexDigit* :: B is 11.
- The MV of *HexDigit* :: c or of *HexDigit* :: C is 12.
- The MV of *HexDigit* :: d or of *HexDigit* :: D is 13.
- The MV of *HexDigit* :: e or of *HexDigit* :: E is 14.
- The MV of *HexDigit* :: f or of *HexDigit* :: F is 15.
- [The MV of *BinaryIntegerLiteral* :: 0b *BinaryDigit*](#) is the MV of *BinaryDigit*.
- [The MV of *BinaryIntegerLiteral* :: 0B *BinaryDigit*](#) is the MV of *BinaryDigit*.
- [The MV of *BinaryIntegerLiteral* :: *BinaryIntegerLiteral* *BinaryDigit*](#) is (the MV of *BinaryIntegerLiteral* times 2) plus the MV of *BinaryDigit*.
- [The MV of *OctalIntegerLiteral* :: 0o *OctalDigit*](#) is the MV of *OctalDigit*.
- [The MV of *OctalIntegerLiteral* :: 0O *OctalDigit*](#) is the MV of *OctalDigit*.
- [The MV of *OctalIntegerLiteral* :: *OctalIntegerLiteral* *OctalDigit*](#) is (the MV of *OctalIntegerLiteral* times 8) plus the MV of *OctalDigit*.
- The MV of *HexIntegerLiteral* :: 0x *HexDigits* is the MV of *HexDigits*.
- The MV of *HexIntegerLiteral* :: 0X *HexDigits* is the MV of *HexDigits*.
- [The MV of *HexDigits* :: *HexDigit*](#) is the MV of *HexDigit*.
- The MV of *HexDigits* :: *HexDigits* *HexDigit* is (the MV of *HexDigits* times 16) plus the MV of *HexDigit*.

Once the exact MV for a numeric literal has been determined, it is then rounded to a value of the Number type. If the MV is 0, then the rounded value is +0; otherwise, the rounded value must be the Number value for the MV (as specified in 8.5), unless the literal is a *DecimalLiteral* and the literal has more than 20 significant digits, in which case the Number value may be either the Number value for the MV of a literal produced by replacing each significant digit after the 20th with a 0 digit or the Number value for the MV of a literal produced by replacing each significant digit after the 20th with a 0 digit and then incrementing the literal at the 20th significant digit position. A digit is *significant* if it is not part of an *ExponentPart* and

- it is not 0; or
- there is a nonzero digit to its left and there is a nonzero digit, not in the *ExponentPart*, to its right.

7.8.4 String Literals

NOTE A string literal is zero or more [Unicode code points](#) enclosed in single or double quotes. [Unicode code points](#) may also be represented by an escape sequence. All characters may appear literally in a string literal except for the closing quote character, backslash, carriage return, line separator, paragraph separator, and line feed. Any character may appear in the form of an escape sequence. [String literals evaluate to ECMAScript String values. When generating these string values \[Unicode code points\]\(#\) are UTF-16 encoded as defined in clause 6. Code points belonging to Basic Multilingual Plane are encoded as a single code unit element of the string. All other code points are encoded as two code unit elements of the string.](#)

Syntax

```
StringLiteral ::  
  " DoubleStringCharactersopt "  
  ' SingleStringCharactersopt '
```

```
DoubleStringCharacters ::  
  DoubleStringCharacter DoubleStringCharactersopt
```

Deleted: <#>The MV of *NumericLiteral* :: *BinaryIntegerLiteral* is the MV of *BinaryIntegerLiteral*.
 <#>The MV of *BinaryDigit* :: 0 is 0.
 <#>The MV of *BinaryDigit* :: 1 is 1.
 <#>The MV of *BinaryIntegerLiteral* :: 0ob *BinaryDigit* is the MV of *BinaryDigit*.
 <#>The MV of *BinaryIntegerLiteral* :: 0OB *BinaryDigit* is the MV of *BinaryDigit*.
 <#>The MV of *BinaryIntegerLiteral* :: *BinaryIntegerLiteral* *BinaryDigit* is (the MV of *BinaryIntegerLiteral* times 2) plus the MV of *BinaryDigit*.
 <#>The MV of *NumericLiteral* :: *OctalIntegerLiteral* is the MV of *OctalIntegerLiteral*.
 <#>The MV of *OctalDigit* :: 0 is 0.
 <#>The MV of *OctalDigit* :: 1 is 1.
 <#>The MV of *OctalDigit* :: 2 is 2.
 <#>The MV of *OctalDigit* :: 3 is 3.
 <#>The MV of *OctalDigit* :: 4 is 4.
 <#>The MV of *OctalDigit* :: 5 is 5.
 <#>The MV of *OctalDigit* :: 6 is 6.
 <#>The MV of *OctalDigit* :: 7 is 7.
 <#>The MV of *OctalIntegerLiteral* :: 0o *OctalDigit* is the MV of *OctalDigit*.
 <#>The MV of *OctalIntegerLiteral* :: 0O *OctalDigit* is the MV of *OctalDigit*.
 <#>The MV of *OctalIntegerLiteral* :: *OctalIntegerLiteral* *OctalDigit* is (the MV of *OctalIntegerLiteral* times 8) plus the MV of *OctalDigit*.
Deleted: *HexIntegerLiteral*
Deleted: *HexIntegerLiteral*
Deleted: *HexIntegerLiteral*

Deleted: A conforming implementation, when processing strict mode code (see 10.1.1), must not extend the syntax of *NumericLiteral* to include *OctalIntegerLiteral* as described in B.1.1.
Formatted: Note
Deleted: characters
Deleted: Each
Deleted: characters
Deleted: characters
Deleted: d
Deleted: Unicode characters
Deleted: d
Deleted: using UTF-16

SingleStringCharacters ::
SingleStringCharacter SingleStringCharacters_{opt}

DoubleStringCharacter ::
SourceCharacter but not one of " or \ or LineTerminator
\ EscapeSequence
LineContinuation

SingleStringCharacter ::
SourceCharacter but not one of ' or \ or LineTerminator
\ EscapeSequence
LineContinuation

LineContinuation ::
\ LineTerminatorSequence

EscapeSequence ::
CharacterEscapeSequence
0 [lookahead \notin DecimalDigit]
HexEscapeSequence
UnicodeEscapeSequence

A conforming implementation, when processing strict mode code (see 10.1.1), must not extend the syntax of *EscapeSequence* to include *OctalEscapeSequence* as described in B.1.2.

CharacterEscapeSequence ::
SingleEscapeCharacter
NonEscapeCharacter

SingleEscapeCharacter :: **one of**
' " **** *b f n r t v*

NonEscapeCharacter ::
SourceCharacter but not one of EscapeCharacter or LineTerminator

EscapeCharacter ::
SingleEscapeCharacter
DecimalDigit
x
u

HexEscapeSequence ::
x HexDigit HexDigit

UnicodeEscapeSequence ::
u HexDigit HexDigit HexDigit HexDigit
u{ HexDigits }

The definition of the nonterminal *HexDigit* is given in 7.8.3. *SourceCharacter* is defined in clause 6.

NOTE A line terminator character cannot appear in a string literal, except as part of a *LineContinuation* to produce the empty character sequence. The correct way to cause a line terminator character to be part of the String value of a string literal is to use an escape sequence such as *\n* or *\u000a*.

Deleted: A conforming implementation, when processing strict mode code (see 10.1.1), must not extend the syntax of *EscapeSequence* to include *OctalEscapeSequence* as described in B.1.2.¶

Static Semantics

Static Semantics: Early Errors

UnicodeEscapeSequence :: *u{ HexDigits }*

- It is a Syntax Error if the MV of *HexDigits* > 1114111.

Static Semantics: SV's and CV's

A string literal stands for a value of the String type. The String value (SV) of the literal is described in terms of code unit values (CV) contributed by the various parts of the string literal. As part of this process, some Unicode characters within the string literal are interpreted as having a mathematical value (MV), as described below or in 7.8.3.

- The SV of *StringLiteral* :: "" is the empty code unit sequence.
- The SV of *StringLiteral* :: '' is the empty code unit sequence.
- The SV of *StringLiteral* :: " *DoubleStringCharacters* " is the SV of *DoubleStringCharacters*.
- The SV of *StringLiteral* :: ' *SingleStringCharacters* ' is the SV of *SingleStringCharacters*.
- The SV of *DoubleStringCharacters* :: *DoubleStringCharacter* is a sequence of one or two code units that is, the CV of *DoubleStringCharacter*.
- The SV of *DoubleStringCharacters* :: *DoubleStringCharacter DoubleStringCharacters* is a sequence of one or two code units that is the CV of *DoubleStringCharacter* followed by all the code units in the SV of *DoubleStringCharacters* in order.
- The SV of *SingleStringCharacters* :: *SingleStringCharacter SingleStringCharacters* is a sequence of one or two code units that is, the CV of *SingleStringCharacter* followed by all the code units in the SV of *SingleStringCharacters* in order.
- The SV of *LineContinuation* :: \ *LineTerminatorSequence* is the empty code unit sequence.
- The CV of *DoubleStringCharacter* :: *SourceCharacter but not one of " or \ or LineTerminator* is the UTF-16 Encoding (clause 6) of the code point value of SourceCharacter.
- The CV of *DoubleStringCharacter* :: \ *EscapeSequence* is the CV of the *EscapeSequence*.
- The CV of *DoubleStringCharacter* :: *LineContinuation* is the empty character sequence.
- The CV of *SingleStringCharacter* :: *SourceCharacter but not one of ' or \ or LineTerminator* is the UTF-16 Encoding (clause 6) of the code point value of SourceCharacter.
- The CV of *SingleStringCharacter* :: \ *EscapeSequence* is the CV of the *EscapeSequence*.
- The CV of *SingleStringCharacter* :: *LineContinuation* is the empty character sequence.
- The CV of *EscapeSequence* :: *CharacterEscapeSequence* is the CV of the *CharacterEscapeSequence*.
- The CV of *EscapeSequence* :: 0 [lookahead \notin *DecimalDigit*] is the code unit value 0.
- The CV of *EscapeSequence* :: *HexEscapeSequence* is the CV of the *HexEscapeSequence*.
- The CV of *EscapeSequence* :: *UnicodeEscapeSequence* is the CV of the *UnicodeEscapeSequence*.
- The CV of *CharacterEscapeSequence* :: *SingleEscapeCharacter* is the character whose code unit value is determined by the *SingleEscapeCharacter* according to Table 4.

Table 4 — String Single Character Escape Sequences

Escape Sequence	Code Unit Value	Name	Symbol
\b	0x0008	backspace	<BS>
\t	0x0009	horizontal tab	<HT>
\n	0x000A	line feed (new line)	<LF>
\v	0x000B	vertical tab	<VT>
\f	0x000C	form feed	<FF>
\r	0x000D	carriage return	<CR>
\"	0x0022	double quote	"
\'	0x0027	single quote	'
\\	0x005C	backslash	\

- The CV of *CharacterEscapeSequence* :: *NonEscapeCharacter* is the CV of the *NonEscapeCharacter*.

Deleted: character

Deleted: character

Deleted: character

Deleted: character

Deleted: ,

Deleted: characters

Deleted: character,

Deleted: characters

Deleted: character

Deleted: *SourceCharacter* character itself.

Deleted: character itself

Deleted: a <NUL> character

Deleted: (Unicode value 0000).

Formatted: Font: (Default) Arial

Deleted: Table 4

Formatted Table

Deleted: \u0000

Deleted: \u0000

Deleted: \u0000

Deleted: \u0000B

Deleted: \u0000

Deleted: \u0000

Deleted: \u0000

Deleted: \u0000

Deleted: \u0000

- The CV of *NonEscapeCharacter :: SourceCharacter but not one of EscapeCharacter or LineTerminator* is the [UTF-16 Encoding \(clause 6\) of the code point value of SourceCharacter](#).
- The CV of *HexEscapeSequence :: x HexDigit HexDigit* is the [code unit value that](#) is (16 times the MV of the first *HexDigit*) plus the MV of the second *HexDigit*.
- The CV of *UnicodeEscapeSequence :: u HexDigit HexDigit HexDigit HexDigit* is the [code unit value that](#) is (4096 times the MV of the first *HexDigit*) plus (256 times the MV of the second *HexDigit*) plus (16 times the MV of the third *HexDigit*) plus the MV of the fourth *HexDigit*.
- [The CV of UnicodeEscapeSequence :: u{ HexDigits } is the is the UTF-16 Encoding \(clause 6\) of the MV of HexDigits.](#)

Deleted: character itself
Deleted: character whose
Deleted: character whose
Deleted: 1

7.8.5 Regular Expression Literals

NOTE A regular expression literal is an input element that is converted to a `RegExp` object (see 15.10) each time the literal is evaluated. Two regular expression literals in a program evaluate to regular expression objects that never compare as `==` to each other even if the two literals' contents are identical. A `RegExp` object may also be created at runtime by `new RegExp` (see 15.10.4) or calling the `RegExp` constructor as a function (15.10.3).

The productions below describe the syntax for a regular expression literal and are used by the input element scanner to find the end of the regular expression literal. The [source code](#) comprising the *RegularExpressionBody* and the *RegularExpressionFlags* are [subsequently parsed using the more stringent ECMAScript Regular Expression grammar \(15.10.1\)](#).

An implementation may extend the [ECMAScript Regular Expression grammar defined in 15.10.1](#), but it must not extend the *RegularExpressionBody* and *RegularExpressionFlags* productions [defined below](#) or the productions used by these productions.

Syntax

RegularExpressionLiteral ::
/ RegularExpressionBody / RegularExpressionFlags

RegularExpressionBody ::
RegularExpressionFirstChar RegularExpressionChars

RegularExpressionChars ::
[empty]
RegularExpressionChars RegularExpressionChar

RegularExpressionFirstChar ::
*RegularExpressionNonTerminator but not one of * or \ or / or [*
RegularExpressionBackslashSequence
RegularExpressionClass

RegularExpressionChar ::
RegularExpressionNonTerminator but not one of \ or / or [
RegularExpressionBackslashSequence
RegularExpressionClass

RegularExpressionBackslashSequence ::
\ RegularExpressionNonTerminator

RegularExpressionNonTerminator ::
SourceCharacter but not LineTerminator

RegularExpressionClass ::
[RegularExpressionClassChars]

RegularExpressionClassChars ::
[empty]
RegularExpressionClassChars RegularExpressionClassChar

Deleted: A conforming implementation, when processing strict mode code (see 10.1.1), may not extend the syntax of *EscapeSequence* to include *OctalEscapeSequence* as described in B.1.2.
NOTE A line terminator character cannot appear in a string literal, except as part of a *LineContinuation* to produce the empty character sequence. The correct way to cause a line terminator character to be part of the String value of a string literal is to use an escape sequence such as `\n` or `\u000A`.
Formatted: Note
Deleted: Strings of characters
Deleted: passed uninterpreted to the regular expression constructor, which interprets them according to its own grammar.
Deleted: regular expression constructor's grammar

RegularExpressionClassChar ::

RegularExpressionNonTerminator **but not one of** `]` or `\`
 RegularExpressionBackslashSequence

RegularExpressionFlags ::

`[empty]`
 RegularExpressionFlags IdentifierPart

NOTE Regular expression literals may not be empty; instead of representing an empty regular expression literal, the characters `//` start a single-line comment. To specify an empty regular expression, use: `/(?:)/`.

Static Semantics: BodyText

RegularExpressionLiteral :: / *RegularExpressionBody* / *RegularExpressionFlags*

1. Return the source code that was recognized as *RegularExpressionBody*.

Static Semantics: FlagText

RegularExpressionLiteral :: / *RegularExpressionBody* / *RegularExpressionFlags*

1. Return the source code that was recognized as *RegularExpressionFlags*.

7.8.6 Template Literal Lexical Components

Syntax

Template ::

NoSubstitutionTemplate
 TemplateHead

NoSubstitutionTemplate ::

 ` *TemplateCharacters_{opt}* `

TemplateHead ::

 ` *TemplateCharacters_{opt}* \${

TemplateSubstitutionTail ::

TemplateMiddle
 TemplateTail

TemplateMiddle ::

 \${ *TemplateCharacters_{opt}* \${

TemplateTail ::

 \${ *TemplateCharacters_{opt}* `

TemplateCharacters ::

TemplateCharacter *TemplateCharacters_{opt}*

TemplateCharacter ::

SourceCharacter **but not one of** ``` or `\` or `$`
 \$ _lookahead \notin `t`
 \ *EscapeSequence*
 LineContinuation

Static Semantics: TV's and TRV's

A template literal component is interpreted as a sequence of Unicode characters. The *Template Value (TV)* of a literal component is described in terms of code unit values (CV, 7.8.4) contributed by the various parts of the

Deleted: Semantics¶

A regular expression literal evaluates to a value of the Object type that is an instance of the standard built-in constructor `RegExp`. This value is determined in two steps: first, the characters comprising the regular expression's *RegularExpressionBody* and *RegularExpressionFlags* production expansions are collected uninterpreted into two Strings *Pattern* and *Flags*, respectively. Then each time the literal is evaluated, a new object is created as if by the expression `new RegExp(Pattern, Flags)` where `RegExp` is the standard built-in constructor with that name. The newly constructed object becomes the value of the *RegularExpressionLiteral*. If the call to `new RegExp` would generate an error as specified in 15.10.4.1, the error must be treated as an early error (Clause 16). ¶

Deleted: Quasi

Deleted:

Deleted: 7.9

Deleted: Quasi

Deleted: FullQuasi

Deleted: Quasi

Deleted: FullQuasi

Deleted: Quasi

Deleted:

template literal component. As part of this process, some Unicode characters within the template component are interpreted as having a mathematical value (MV, 7.8.3). In determining a TV, escape sequences are replaced by the code unit of the Unicode characters represented by the escape sequence. The Template Raw Value (TRV) is similar to a Template Value with the difference that in TRVs escape sequences are interpreted literally.

- The TV and TRV of NoSubstitutionTemplate :: `` is the empty code unit sequence.
- The TV and TRV of TemplateHead :: \${ is the empty code unit sequence.
- The TV and TRV of TemplateMiddle :: \${ is the empty code unit sequence.
- The TV and TRV of TemplateTail :: }` is the empty code unit sequence.
- The TV of NoSubstitutionTemplate :: `TemplateCharacters` is the TV of TemplateCharacters.
- The TV of TemplateHead :: `TemplateCharacters \${ is the TV of TemplateCharacters.
- The TV of TemplateMiddle :: }TemplateCharacters \${ is the TV of TemplateCharacters.
- The TV of TemplateTail :: }TemplateCharacters ` is the TV of TemplateCharacters.
- The TV of TemplateCharacters:: TemplateCharacter is the TV of TemplateCharacter.
- The TV of TemplateCharacters:: TemplateCharacter TemplateCharacters is a sequence consisting of the code units in the TV of TemplateCharacter followed by all the code units in the TV of TemplateCharacters in order.
- The TV of TemplateCharacter :: SourceCharacter but not one of ` or \ or \$ is the UTF-16 Encoding (clause 6) of the code point value of SourceCharacter.
- The TV of TemplateCharacter :: \$ [lookahead \notin {1} is the code unit value 0x0024.
- The TV of TemplateCharacter :: \ EscapeSequence is the CV of EscapeSequence.
- The TV of TemplateCharacter :: LineContinuation is the TV of LineContinuation.
- The TV of LineContinuation :: \ LineTerminatorSequence is the empty code unit sequence.
- The TRV of NoSubstitutionTemplate :: `TemplateCharacters` is the TRV of TemplateCharacters.
- The TRV of TemplateHead :: `TemplateCharacters \${ is the TRV of TemplateCharacters.
- The TRV of TemplateMiddle :: }TemplateCharacters \${ is the TRV of TemplateCharacters.
- The TRV of TemplateTail :: }TemplateCharacters ` is the TRV of TemplateCharacters.
- The TRV of TemplateCharacters:: TemplateCharacter is the TRV of TemplateCharacter.
- The TRV of TemplateCharacters:: TemplateCharacter TemplateCharacters is a sequence consisting of the code units in the TRV of TemplateCharacter followed by all the code units in the TRV of TemplateCharacters, in order.
- The TRV of TemplateCharacter :: SourceCharacter but not one of ` or \ or \$ is the UTF-16 Encoding (clause 6) of the code point value of SourceCharacter.
- The TRV of TemplateCharacter :: \$ [lookahead \notin {1} is the code unit value 0x0024.
- The TRV of TemplateCharacter :: \ EscapeSequence is the sequence consisting of the code unit value 0x005C followed by the code units of TRV of EscapeSequence.
- The TRV of TemplateCharacter:: LineContinuation is the TRV of LineContinuation.
- The TRV of EscapeSequence :: CharacterEscapeSequence is the TRV of the CharacterEscapeSequence.
- The TRV of EscapeSequence :: 0 [lookahead \notin DecimalDigit] is the code unit value 0x0030.
- The TRV of EscapeSequence :: HexEscapeSequence is the TRV of the HexEscapeSequence.
- The CRV of EscapeSequence :: UnicodeEscapeSequence is the CRV of the UnicodeEscapeSequence.
- The TRV of CharacterEscapeSequence :: SingleEscapeCharacter is the TRV of the SingleEscapeCharacter.
- The TRV of CharacterEscapeSequence :: NonEscapeCharacter is the CV of the NonEscapeCharacter.
- The TRV of SingleEscapeCharacter :: one of ' " \ b f n r t v is the CV of the SourceCharacter that is that single character.
- The TRV of HexEscapeSequence :: x HexDigit HexDigit is the sequence consisting of code unit value 0x0078 followed by TRV of the first HexDigit followed by the TRV of the second HexDigit.
- The TRV of UnicodeEscapeSequence :: u HexDigit HexDigit HexDigit HexDigit is the sequence consisting of code unit value 0x0075 followed by TRV of the first HexDigit followed by the TRV of the second HexDigit followed by TRV of the third HexDigit followed by the TRV of the fourth HexDigit.

Deleted: quasi...emplate literal cmponent.

Deleted: QV...V and QRV...RV of FullQuasi

Deleted: QV...V and QRV...RV of Quasi

Deleted: QV...V and QRV...RV of Quasi

Deleted: QV...V and QRV...RV of Quasi

Deleted: QV...V of

Deleted: QV...V of Quasi...emplateHead :: `

Deleted: QV...V of Quasi...emplateMiddle :: }

Deleted: QV...V of Quasi...emplateTail :: }`

Deleted: QV...V of Quasi...emplateCharacter

Deleted: QV...V of Quasi...emplateCharacter

Deleted: QV...V of Quasi...emplateCharacter

Deleted: QV...V of Quasi...emplateCharacter

Deleted: QV...V of Quasi

- The TRV of *UnicodeEscapeSequence* :: *u{ HexDigits }* is the sequence consisting of code unit value 0x007B followed by code unit value 0x007B followed by TRV of *HexDigit* followed by code unit value 0x007D.
- The TRV of *HexDigits* :: *HexDigit* is the TRV of *HexDigit*.
- The TRV of *HexDigits* :: *HexDigits HexDigit* is the sequence consisting of TRV of *HexDigits* followed by TRV of *HexDigit*.
- The TRV of a *HexDigit* is CV of the *SourceCharacter* that is that *HexDigit*.
- The TRV of *LineContinuation* :: \LineTerminatorSequence is the sequence consisting of the code unit value 0x005C followed by the code units of TRV of *LineTerminatorSequence*.
- The TRV of *LineTerminatorSequence* :: <LF> is the code unit value 0x000A.
- The TRV of *LineTerminatorSequence* :: <CR>[lookahead <LF>] is the code unit value 0x000D.
- The TRV of *LineTerminatorSequence* :: <LS> is the code unit value 0x2028.
- The TRV of *LineTerminatorSequence* :: <PS> is the code unit value 0x2029.
- The TRV of *LineTerminatorSequence* :: <CR><LF> is the sequence consisting of the code unit value 0x000D followed by the code unit value 0x000A.

NOTE TV excludes the code units of *LineContinuation* while TRV includes them.

7.9 Automatic Semicolon Insertion

Certain ECMAScript statements (empty statement, variable statement, expression statement, `do-while` statement, `continue` statement, `break` statement, `return` statement, and `throw` statement) must be terminated with semicolons. Such semicolons may always appear explicitly in the source text. For convenience, however, such semicolons may be omitted from the source text in certain situations. These situations are described by saying that semicolons are automatically inserted into the source code token stream in those situations.

7.9.1 Rules of Automatic Semicolon Insertion

There are three basic rules of semicolon insertion:

1. When, as the program is parsed from left to right, a token (called the *offending token*) is encountered that is not allowed by any production of the grammar, then a semicolon is automatically inserted before the offending token if one or more of the following conditions is true:
 - The offending token is separated from the previous token by at least one *LineTerminator*.
 - The offending token is `}`.
2. When, as the program is parsed from left to right, the end of the input stream of tokens is encountered and the parser is unable to parse the input token stream as a single complete ECMAScript *Program*, then a semicolon is automatically inserted at the end of the input stream.
3. When, as the program is parsed from left to right, a token is encountered that is allowed by some production of the grammar, but the production is a *restricted production* and the token would be the first token for a terminal or nonterminal immediately following the annotation “[no *LineTerminator* here]” within the restricted production (and therefore such a token is called a *restricted token*), and the restricted token is separated from the previous token by at least one *LineTerminator*, then a semicolon is automatically inserted before the restricted token.

However, there is an additional overriding condition on the preceding rules: a semicolon is never inserted automatically if the semicolon would then be parsed as an empty statement or if that semicolon would become one of the two semicolons in the header of a `for` statement (see 12.6.3).

NOTE The following are the only restricted productions in the grammar:

```
PostfixExpression :
  LeftHandSideExpression [no LineTerminator here] ++
  LeftHandSideExpression [no LineTerminator here] --
```

Deleted: QRV
Deleted: consisting of the code units
Deleted: QRV
Deleted: QV
Deleted: QRV
Deleted:

ContinueStatement :
 continue [no *LineTerminator* here] *Identifier* ;

BreakStatement :
 break [no *LineTerminator* here] *Identifier* ;

ReturnStatement :
 return [no *LineTerminator* here] *Expression* ;

ThrowStatement :
 throw [no *LineTerminator* here] *Expression* ;

The practical effect of these restricted productions is as follows:

When a `++` or `--` token is encountered where the parser would treat it as a postfix operator, and at least one *LineTerminator* occurred between the preceding token and the `++` or `--` token, then a semicolon is automatically inserted before the `++` or `--` token.

When a `continue`, `break`, `return`, or `throw` token is encountered and a *LineTerminator* is encountered before the next token, a semicolon is automatically inserted after the `continue`, `break`, `return`, or `throw` token.

The resulting practical advice to ECMAScript programmers is:

A postfix `++` or `--` operator should appear on the same line as its operand.

An *Expression* in a `return` or `throw` statement should start on the same line as the `return` or `throw` token.

An *Identifier* in a `break` or `continue` statement should be on the same line as the `break` or `continue` token.

7.9.2 Examples of Automatic Semicolon Insertion

The source

```
{ 1 2 } 3
```

is not a valid sentence in the ECMAScript grammar, even with the automatic semicolon insertion rules. In contrast, the source

```
{ 1  
2 } 3
```

is also not a valid ECMAScript sentence, but is transformed by automatic semicolon insertion into the following:

```
{ 1  
;2 ;} 3;
```

which is a valid ECMAScript sentence.

The source

```
for (a; b  
)
```

is not a valid ECMAScript sentence and is not altered by automatic semicolon insertion because the semicolon is needed for the header of a `for` statement. Automatic semicolon insertion never inserts one of the two semicolons in the header of a `for` statement.

The source

```
return  
a + b
```

is transformed by automatic semicolon insertion into the following:

```
return;  
a + b;
```

NOTE The expression `a + b` is not treated as a value to be returned by the `return` statement, because a *LineTerminator* separates it from the token `return`.

The source

```
a = b
++c
```

is transformed by automatic semicolon insertion into the following:

```
a = b;
++c;
```

NOTE The token `++` is not treated as a postfix operator applying to the variable `b`, because a *LineTerminator* occurs between `b` and `++`.

The source

```
if (a > b)
else c = d
```

is not a valid ECMAScript sentence and is not altered by automatic semicolon insertion before the `else` token, even though no production of the grammar applies at that point, because an automatically inserted semicolon would then be parsed as an empty statement.

The source

```
a = b + c
(d + e).print()
```

is *not* transformed by automatic semicolon insertion, because the parenthesised expression that begins the second line can be interpreted as an argument list for a function call:

```
a = b + c(d + e).print()
```

In the circumstance that an assignment statement must begin with a left parenthesis, it is a good idea for the programmer to provide an explicit semicolon at the end of the preceding statement rather than to rely on automatic semicolon insertion.

8 Types

Algorithms within this specification manipulate values each of which has an associated type. The possible value types are exactly those defined in this clause. Types are further subclassified into ECMAScript language types and specification types.

An ECMAScript language type corresponds to values that are directly manipulated by an ECMAScript programmer using the ECMAScript language. The ECMAScript language types are Undefined, Null, Boolean, String, Number, and Object.

A specification type corresponds to meta-values that are used within algorithms to describe the semantics of ECMAScript language constructs and ECMAScript language types. The specification types are Reference, List, Completion, Property Descriptor, Property Identifier, Lexical Environment, Environment Record, [and Data Block](#). Specification type values are specification artefacts that do not necessarily correspond to any specific entity within an ECMAScript implementation. Specification type values may be used to describe intermediate results of ECMAScript expression evaluation but such values cannot be stored as properties of objects or values of ECMAScript language variables.

Deleted: and

Within this specification, the notation “`Type(x)`” is used as shorthand for “the type of `x`” where “type” refers to the ECMAScript language and specification types defined in this clause.

8.1 The Undefined Type

The Undefined type has exactly one value, called `undefined`. Any variable that has not been assigned a value has the value `undefined`.

8.2 The Null Type

The Null type has exactly one value, called **null**.

8.3 The Boolean Type

The Boolean type represents a logical entity having two values, called **true** and **false**.

8.4 The String Type

The String type is the set of all finite ordered sequences of zero or more 16-bit unsigned integer values ("elements"). The String type is generally used to represent textual data in a running ECMAScript program, in which case each element in the String is treated as a UTF-16 code unit value. Each element is regarded as occupying a position within the sequence. These positions are indexed with nonnegative integers. The first element (if any) is at position 0, the next element (if any) at position 1, and so on. The length of a String is the number of elements (i.e., 16-bit values) within it. The empty String has length zero and therefore contains no elements.

Deleted: Unicode

Deleted: (see Clause 6)

Where ECMAScript operations interpret String values, each element is interpreted as a single UTF-16 code unit. However, ECMAScript does not place any restrictions or requirements on the sequence of code units in a String value, so they may be ill-formed when interpreted as UTF-16 code unit sequences. Operations that do not interpret String contents treat them as sequences of undifferentiated 16-bit unsigned integers. No operations ensure that Strings are in a normalized form. Only operations that are explicitly specified to be language or locale sensitive produce language-sensitive results

NOTE The rationale behind this design was to keep the implementation of Strings as simple and high-performing as possible. If ECMAScript source code is in Normalised Form C, string literals are guaranteed to also be normalised, as long as they do not contain any Unicode escape sequences.

Some operations interpret String contents as UTF-16 encoded Unicode code points. In that case the interpretation is:

- A code unit in the range 0 to 0xD7FF or in the range 0xE000 to 0xFFFF is interpreted as a code point with the same value.
- A sequence of two code units, where the first code unit c_1 is in the range 0xD800 to 0xDBFF and the second code unit c_2 is in the range 0xDC00 to 0xDFFF, is a surrogate pair and is interpreted as a code point with the value $(c_1 - 0xD800) \times 0x400 + (c_2 - 0xDC00) + 0x10000$.
- A code unit that is in the range 0xD800 to 0xDFFF, but is not part of a surrogate pair, is interpreted as a code point with the same value.

8.5 The Number Type

The Number type has exactly 18437736874454810627 (that is, $2^{64}-2^{53}+3$) values, representing the double-precision 64-bit format IEEE 754 values as specified in the IEEE Standard for Binary Floating-Point Arithmetic, except that the 9007199254740990 (that is, $2^{53}-2$) distinct "Not-a-Number" values of the IEEE Standard are represented in ECMAScript as a single special **NaN** value. (Note that the **NaN** value is produced by the program expression **NaN**.) In some implementations, external code might be able to detect a difference between various Not-a-Number values, but such behaviour is implementation-dependent; to ECMAScript code, all **NaN** values are indistinguishable from each other.

Deleted: <#>When a String contains actual textual data, each element is considered to be a single UTF-16 code unit. Whether or not this is the actual storage format of a String, the characters within a String are numbered by their initial code unit element position as though they were represented using UTF-16. All operations on Strings (except as otherwise stated) treat them as sequences of undifferentiated 16-bit unsigned integers; they do not ensure the resulting String is in normalized form, nor do they ensure language-sensitive results.¶

Deleted: The intent is that textual data coming into the execution environment from outside (e.g., user input, text read from a file or received over the network, etc.) be converted to Unicode Normalized Form C before the running program sees it. Usually this would occur at the same time incoming text is converted from its original character encoding to Unicode (and would impose no additional overhead). Since it is recommended that

Deleted: be

Deleted: (if source text is guaranteed to be normalized)

There are two other special values, called **positive Infinity** and **negative Infinity**. For brevity, these values are also referred to for expository purposes by the symbols $+\infty$ and $-\infty$, respectively. (Note that these two infinite Number values are produced by the program expressions **+Infinity** (or simply **Infinity**) and **-Infinity**.)

The other 18437736874454810624 (that is, $2^{64}-2^{53}$) values are called the finite numbers. Half of these are positive numbers and half are negative numbers; for every finite positive Number value there is a corresponding negative value having the same magnitude.

Note that there is both a **positive zero** and a **negative zero**. For brevity, these values are also referred to for expository purposes by the symbols **+0** and **-0**, respectively. (Note that these two different zero Number values are produced by the program expressions **+0** (or simply **0**) and **-0**.)

The 18437736874454810622 (that is, $2^{64}-2^{53}-2$) finite nonzero values are of two kinds:

18428729675200069632 (that is, $2^{64}-2^{54}$) of them are normalised, having the form

$$s \times m \times 2^e$$

where s is $+1$ or -1 , m is a positive integer less than 2^{53} but not less than 2^{52} , and e is an integer ranging from -1074 to 971 , inclusive.

The remaining 9007199254740990 (that is, $2^{53}-2$) values are denormalised, having the form

$$s \times m \times 2^e$$

where s is $+1$ or -1 , m is a positive integer less than 2^{52} , and e is -1074 .

Note that all the positive and negative integers whose magnitude is no greater than 2^{53} are representable in the Number type (indeed, the integer **0** has two representations, **+0** and **-0**).

A finite number has an *odd significand* if it is nonzero and the integer m used to express it (in one of the two forms shown above) is odd. Otherwise, it has an *even significand*.

In this specification, the phrase “the Number value for x ” where x represents an exact nonzero real mathematical quantity (which might even be an irrational number such as π) means a Number value chosen in the following manner. Consider the set of all finite values of the Number type, with **-0** removed and with two additional values added to it that are not representable in the Number type, namely 2^{1024} (which is $+1 \times 2^{53} \times 2^{971}$) and -2^{1024} (which is $-1 \times 2^{53} \times 2^{971}$). Choose the member of this set that is closest in value to x . If two values of the set are equally close, then the one with an even significand is chosen; for this purpose, the two extra values 2^{1024} and -2^{1024} are considered to have even significands. Finally, if 2^{1024} was chosen, replace it with $+\infty$; if -2^{1024} was chosen, replace it with $-\infty$; if **+0** was chosen, replace it with **-0** if and only if x is less than zero; any other chosen value is used unchanged. The result is the Number value for x . (This procedure corresponds exactly to the behaviour of the IEEE 754 “round to nearest” mode.)

Some ECMAScript operators deal only with integers in the range -2^{31} through $2^{31}-1$, inclusive, or in the range 0 through $2^{32}-1$, inclusive. These operators accept any value of the Number type but first convert each such value to one of 2^{32} integer values. See the descriptions of the `ToInt32` and `ToInt32` operators in 9.5 and 9.6, respectively.

8.6 The Object Type

An Object is a collection of properties. Each property is either a named data property, a named accessor property, or an internal property:

- A *named data property* associates a name with an ECMAScript language value and a set of Boolean attributes.
- A *named accessor property* associates a name with one or two accessor functions, and a set of Boolean attributes. The accessor functions are used to store or retrieve an ECMAScript language value that is associated with the property.
- An *internal property* has no name and is not directly accessible via ECMAScript language operators. Internal properties exist purely for specification purposes.

There are two kinds of access for named (non-internal) properties: *get* and *put*, corresponding to retrieval and assignment, respectively.

8.6.1 Property Attributes

Attributes are used in this specification to define and explain the state of named properties. A named data property associates a name with the attributes listed in [Table 5](#).

Table 5 — Attributes of a Named Data Property

Attribute Name	Value Domain	Description
<code>[[Value]]</code>	Any ECMAScript language type	The value retrieved by reading the property.
<code>[[Writable]]</code>	Boolean	If <code>false</code> , attempts by ECMAScript code to change the property's <code>[[Value]]</code> attribute using <code>[[Put]]</code> will not succeed.
<code>[[Enumerable]]</code>	Boolean	If <code>true</code> , the property will be enumerated by a for-in enumeration (see 12.6.4). Otherwise, the property is said to be non-enumerable.
<code>[[Configurable]]</code>	Boolean	If <code>false</code> , attempts to delete the property, change the property to be an accessor property, or change its attributes (other than <code>[[Value]]</code>) will fail.

A named accessor property associates a name with the attributes listed in [Table 6](#).

Table 6 — Attributes of a Named Accessor Property

Attribute Name	Value Domain	Description
<code>[[Get]]</code>	Object or Undefined	If the value is an Object it must be a function Object. The function's <code>[[Call]]</code> internal method (8.6.2) is called with an empty arguments list to return the property value each time a get access of the property is performed.
<code>[[Set]]</code>	Object or Undefined	If the value is an Object it must be a function Object. The function's <code>[[Call]]</code> internal method (8.6.2) is called with an arguments list containing the assigned value as its sole argument each time a set access of the property is performed. The effect of a property's <code>[[Set]]</code> internal method may, but is not required to, have an effect on the value returned by subsequent calls to the property's <code>[[Get]]</code> internal method.
<code>[[Enumerable]]</code>	Boolean	If <code>true</code> , the property is to be enumerated by a for-in enumeration (see 12.6.4). Otherwise, the property is said to be non-enumerable.
<code>[[Configurable]]</code>	Boolean	If <code>false</code> , attempts to delete the property, change the property to be a data property, or change its attributes will fail.

If the value of an attribute is not explicitly specified by this specification for a named property, the default value defined in [Table 7](#) is used.

Table 7 — Default Attribute Values

Attribute Name	Default Value
<code>[[Value]]</code>	<code>undefined</code>
<code>[[Get]]</code>	<code>undefined</code>
<code>[[Set]]</code>	<code>undefined</code>
<code>[[Writable]]</code>	<code>false</code>
<code>[[Enumerable]]</code>	<code>false</code>
<code>[[Configurable]]</code>	<code>false</code>

8.6.2 Object Internal Properties and Methods

This specification uses various internal properties to define the semantics of object values. These internal properties are not part of the ECMAScript language. They are defined by this specification purely for expository purposes. An implementation of ECMAScript must behave as if it produced and operated upon internal properties in the manner described here. The names of internal properties are enclosed in double square brackets [[]]. When an algorithm uses an internal property of an object and the object does not implement the indicated internal property, a **TypeError** exception is thrown.

[Table 8](#) summarises the internal properties used by this specification that are applicable to all ECMAScript objects. [Table 9](#) summarises the internal properties used by this specification that are only applicable to some ECMAScript objects.

[Clause 8.12 provides the algorithms that defined the default behaviour for the internal methods in Table 8. An ordinary object is an object that uses all of these default algorithms. An exotic object is an object that uses some other algorithm to provide alternative behaviour for one or more of these internal methods.](#)

The “Value Type Domain” columns of the following tables define the types of values associated with internal properties. The type names refer to the types defined in Clause 8 augmented by the following additional names. “any” means the value may be any ECMAScript language type. “primitive” means Undefined, Null, Boolean, String, or Number. “SpecOp” means the internal property is an internal method, an implementation provided procedure defined by an abstract operation specification. “SpecOp” is followed by a list of descriptive parameter names. If a parameter name is the same as a type name then the name describes the type of the parameter. If a “SpecOp” returns a value, its parameter list is followed by the symbol “→” and the type of the returned value.

Deleted: The

Deleted: The

Deleted: .

Deleted: The descriptions in these tables indicate their behaviour for native ECMAScript objects, unless stated otherwise in this document for particular kinds of native ECMAScript objects.

Deleted: Host objects may support these internal properties with any implementation-dependent behaviour as long as it is consistent with the specific host object restrictions stated in this document.¶

Table 8 — Internal Properties Common to All Objects

Internal Property	Value Type Domain	Description
<code>[[Prototype]]</code>	Object or Null	The prototype of this object.
<code>[[Extensible]]</code>	Boolean	If <code>true</code> , own properties may be added to the object.
<code>[[Get]]</code>	<code>SpecOp(propertyName) → any</code>	Returns the value of the named property.
<code>[[GetOwnProperty]]</code>	<code>SpecOp(propertyName) → Undefined or Property Descriptor</code>	Returns the Property Descriptor of the named own property of this object, or <code>undefined</code> if absent.
<code>[[GetProperty]]</code>	<code>SpecOp(propertyName) → Undefined or Property Descriptor</code>	Returns the fully populated Property Descriptor of the named property of this object, or <code>undefined</code> if absent.
<code>[[Put]]</code>	<code>SpecOp(propertyName, any, Boolean)</code>	Sets the specified named property to the value of the second parameter. The flag controls failure handling.
<code>[[CanPut]]</code>	<code>SpecOp(propertyName) → Boolean</code>	Returns a Boolean value indicating whether a <code>[[Put]]</code> operation with <code>PropertyName</code> can be performed.
<code>[[HasProperty]]</code>	<code>SpecOp(propertyName) → Boolean</code>	Returns a Boolean value indicating whether the object already has a property with the given name.
<code>[[Delete]]</code>	<code>SpecOp(propertyName, Boolean) → Boolean</code>	Removes the specified named own property from the object. The flag controls failure handling.
<code>[[DefaultValue]]</code>	<code>SpecOp(Hint) → primitive</code>	Hint is a String. Returns a default value for the object.
<code>[[DefineOwnProperty]]</code>	<code>SpecOp(propertyName,PropertyDescriptor,Boolean) → Boolean</code>	Creates or alters the named own property to have the state described by a Property Descriptor. The flag controls failure handling.
<code>[[Enumerate]]</code>	<code>SpecOp() → Object</code>	Returns an object that can enumerate the string values of the keys of the enumerable properties of the object. The returned object is an Iterator object.
<code>[[Iterate]]</code>	<code>SpecOp() → Object</code>	Returns an object that can enumerate the logical component values of the object. The returned object is an Iterator object.

Formatted Table

Deleted: `[[Class]]`

Every object must implement all of the internal properties listed in Table 8. However, the `[[DefaultValue]]` internal method may, for some objects, simply throw a `TypeError` exception.

Deleted: (including host objects)

All objects have an internal property called `[[Prototype]]`. The value of this property is either `null` or an object and is used for implementing inheritance. Whether or not an `ordinary` object can have an `exotic` object as its `[[Prototype]]` depends on the implementation. Every `[[Prototype]]` chain must have finite length (that is, starting from any object, recursively accessing the `[[Prototype]]` internal property must eventually lead to a `null` value). Named data properties of the `[[Prototype]]` object are inherited (are visible as properties of the child object) for the purposes of get access, but not for put access. Named accessor properties are inherited for both get access and put access.

Deleted: native

Deleted: host

Every ECMAScript object has a Boolean-valued `[[Extensible]]` internal property that controls whether or not named properties may be added to the object. If the value of the `[[Extensible]]` internal property is `false` then additional named properties may not be added to the object. In addition, if `[[Extensible]]` is `false` the value of `[[Prototype]]` internal properties of the object may not be modified. Once the value of an `[[Extensible]]` internal property has been set to `false` it may not be subsequently changed to `true`.

Deleted: the `[[Class]]` and

NOTE This specification defines no ECMAScript language operators or built-in functions that permit a program to modify an object's `[[Prototype]]` internal properties or to change the value of `[[Extensible]]` from `false` to `true`.

Deleted: `[[Class]]` or

Implementation specific extensions that modify `[[Prototype]]` or `[[Extensible]]` must not violate the invariants defined in the preceding paragraph.

Unless otherwise specified, the common internal methods of native ECMAScript objects behave as described in 8.12. Array objects have a slightly different implementation of the `[[DefineOwnProperty]]` internal method (see 15.4.5.1) and String objects have a slightly different implementation of the `[[GetOwnProperty]]` internal method (see 15.5.5.2). Arguments objects (10.6) have different implementations of `[[Get]]`, `[[GetOwnProperty]]`, `[[DefineOwnProperty]]`, and `[[Delete]]`. Function objects (15.3) have a different implementation of `[[Get]]`.

Exotic objects may implement these internal methods in any manner unless specified otherwise; for example, one possibility is that `[[Get]]` and `[[Put]]` for a particular exotic object indeed fetch and store property values but `[[HasProperty]]` always generates `false`. However, if any specified manipulation of an exotic object's internal properties is not supported by an implementation, that manipulation must throw a `TypeError` exception when attempted.

The `[[GetOwnProperty]]` internal method of all objects must conform to the following invariants for each property of the object:

- If a property is described as a data property and it may return different values over time, then either or both of the `[[Writable]]` and `[[Configurable]]` attributes must be `true` even if no mechanism to change the value is exposed via the other internal methods.
- If a property is described as a data property and its `[[Writable]]` and `[[Configurable]]` are both `false`, then the `SameValue` (according to 9.12) must be returned for the `[[Value]]` attribute of the property on all calls to `[[GetOwnProperty]]`.
- If the attributes other than `[[Writable]]` may change over time or if the property might disappear, then the `[[Configurable]]` attribute must be `true`.
- If the `[[Writable]]` attribute may change from `false` to `true`, then the `[[Configurable]]` attribute must be `true`.
- If the value of the object's `[[Extensible]]` internal property has been observed by ECMAScript code to be `false`, then if a call to `[[GetOwnProperty]]` describes a property as non-existent all subsequent calls must also describe that property as non-existent.

The `[[DefineOwnProperty]]` internal method of all objects must not permit the addition of a new property to an object if the `[[Extensible]]` internal property of that object has been observed by ECMAScript code to be `false`.

If the `[[Extensible]]` internal property of an object has been observed by ECMAScript code to be `false` then it must not subsequently become `true`.

Deleted: `[[Class]]`.

Deleted: The value of the `[[Class]]` internal property is defined by this specification for every kind of built-in object. The value of the `[[Class]]` internal property of a host object may be any String value except one of `"Arguments"`, `"Array"`, `"Boolean"`, `"Date"`, `"Error"`, `"Function"`, `"JSON"`, `"Math"`, `"Number"`, `"Object"`, `"RegExp"`, and `"String"`. The value of a `[[Class]]` internal property is used internally to distinguish different kinds of objects. Note that this specification does not provide any means for a program to access that value except through `Object.prototype.toString` (see 15.2.4.2).¶

Deleted: Host

Deleted: that

Deleted: host

Deleted: that

Deleted: host

Table 9 — Internal Properties Only Defined for Some Objects

Internal Property	Value Type Domain	Description
<code>[[NativeBrand]]</code>	Members of the <code>NativeBrand</code> enumeration.	A tag value used by this specification to categorize various kinds of native ECMAScript objects defined in this specification. Host objects do not have this internal property.
<code>[[PrimitiveValue]]</code>	<code>primitive</code>	Internal state information associated with this object. Of the standard built-in ECMAScript objects, only Boolean, Date, Number, and String objects implement <code>[[PrimitiveValue]]</code> .
<code>[[Construct]]</code>	<code>SpecOp(a List of <i>any</i>) → Object</code>	Creates an object. Invoked via the <code>new</code> operator. The arguments to the SpecOp are the arguments passed to the <code>new</code> operator. Objects that implement this internal method are called <i>constructors</i> .
<code>[[Call]]</code>	<code>SpecOp(<i>any</i>, a List of <i>any</i>) → <i>any</i> or Reference</code>	Executes code associated with the object. Invoked via a function call expression. The arguments to the SpecOp are this object and a list containing the arguments passed to the function call expression. Objects that implement this internal method are <i>callable</i> . Only callable objects that are host objects may return Reference values.
<code>[[HasInstance]]</code>	<code>SpecOp(<i>any</i>) → Boolean</code>	Returns a Boolean value indicating whether the argument is likely an Object that was constructed by this object. Of the standard built-in ECMAScript objects, only Function objects implement <code>[[HasInstance]]</code> .
<code>[[Scope]]</code>	Lexical Environment	A lexical environment that <i>is</i> the environment in which a Function object is executed. Of the standard built-in ECMAScript objects, only Function objects implement <code>[[Scope]]</code> .
<code>[[FormalParameters]]</code>	<u>Parse Tree</u>	<u>A parse tree for ECMAScript code parsed with <code>FormalParameterList</code> as the goal symbol.</u> Of the standard built-in ECMAScript objects, only Function objects implement <code>[[FormalParameters]]</code> .
<code>[[Code]]</code>	<u>Parse Tree</u>	<u>A parse tree for ECMAScript code parsed with <code>FunctionBody</code> as the goal symbol.</u> Of the standard built-in ECMAScript objects, only Function objects implement <code>[[Code]]</code> .
<code>[[Strict]]</code>	<u>Boolean</u>	<u>True if a Function object is a strict mode function.</u> Of the standard built-in ECMAScript objects, only Function objects implement <code>[[Strict]]</code> .
<code>[[TargetFunction]]</code>	Object	The target function of a function object created using the standard built-in <code>Function.prototype.bind</code> method. Only ECMAScript objects created using <code>Function.prototype.bind</code> have a <code>[[TargetFunction]]</code> internal property.
<code>[[BoundThis]]</code>	<code>any</code>	The pre-bound <code>this</code> value of a function Object created using the standard built-in <code>Function.prototype.bind</code> method. Only ECMAScript objects created using <code>Function.prototype.bind</code> have a <code>[[BoundThis]]</code> internal property.
<code>[[BoundArguments]]</code>	List of <code>any</code>	The pre-bound argument values of a function Object created <u>by</u> the standard built-in <code>Function.prototype.bind</code> method. Only objects created <u>by</u> <code>Function.prototype.bind</code> have a <code>[[BoundArguments]]</code> internal property.
<code>[[Match]]</code>	<code>SpecOp(String, index) → MatchResult</code>	Tests for a regular expression match and returns a <code>MatchResult</code> value (see 15.10.2.1). Of the standard built-in ECMAScript objects, only <code>RegExp</code> objects implement <code>[[Match]]</code> .
<code>[[ParameterMap]]</code>	Object	Provides a mapping between the properties of an arguments object (see 10.6) and the formal parameters of the associated function. Only objects that are arguments objects have a <code>[[ParameterMap]]</code> internal property.

Formatted Table

Comment [AWB911]: Hopefully we can eliminate functions returning References

Deleted: defines

Deleted: List of Strings

Deleted: A possibly empty List containing the identifier Strings of a Function's

Deleted: `FormalParameterList`

Deleted: ECMAScript code

Deleted: The ECMAScript code of a function

Deleted: using

Deleted: ECMAScript

Deleted: using

The `[[NativeBrand]]` internal property is used to identify native ECMAScript objects as objects that conform to specific parts of this specification. The value of a `[[NativeBrand]]` property is a single member of this set of enumerated values: `NativeFunction`, `NativeArray`, `StringWrapper`, `BooleanWrapper`, `NumberWrapper`, `NativeMath`, `NativeDate`, `NativeRegExp`, `NativeError`, `NativeJSON`, `NativeArguments`, `NativePrivateName`. The actual value of the `[[NativeBrand]]` internal property is only used to identify specific kinds of native ECMAScript objects. Host objects do not have this internal property.

Table 10 — Values of the `[[NativeBrand]]` Internal Property.

Value	Category	Description
<code>NativeFunction</code>	<code>Function objects</code>	
<code>NativeArray</code>	<code>Array objects</code>	
<code>StringWrapper</code>	<code>String objects</code>	
<code>BooleanWrapper</code>	<code>Boolean objects</code>	
<code>NumberWrapper</code>	<code>Number objects</code>	
<code>NativeMath</code>	<code>The Math object</code>	
<code>NativeDate</code>	<code>Date objects</code>	
<code>NativeRegExp</code>	<code>RegExp objects</code>	
<code>NativeError</code>	<code>Error objects</code>	
<code>NativeJSON</code>	<code>The JSON object</code>	
<code>NativeArguments</code>	<code>Arguments objects</code>	
<code>NativePrivateName</code>	<code>Private Name objects</code>	

8.7 The List and Record Specification Type

The List type is used to explain the evaluation of argument lists (see 11.2.4) in `new` expressions, in function calls, and in other algorithms where a simple list of values is needed. Values of the List type are simply ordered sequences of values. These sequences may be of any length.

The Record type is used to describe data aggregations within the algorithms of this specification. A Record type value consists of one or more named fields. The value of each field is either an ECMAScript value or an abstract value represented by a name associated with the Record type. Field names are always enclosed in double brackets, for example `[[value]]`.

For notational convenience within this specification, an object literal-like syntax can be used to express a Record value. For example, `{[[field1]]: 42, [[field2]]: false, [[field3]]: empty}` defines a Record value that has three fields each of which is initialized to a specific value. Field name order is not significant. Any fields that are not explicitly listed are considered to be absent.

In specification text and algorithms, dot notation may be used to refer to a specific field of a Record value. For example, if `R` is the record shown in the previous paragraph then `R.[[field2]]` is shorthand for "the field of `R` named `[[field2]]`".

Schema for commonly used Record field combinations may be named, and that name may be used as a prefix to a literal Record value to identify the specific kind of aggregations that is being described. For example: Property Descriptor `{[[Value]]: 42, [[Writable]]: false, [[Configurable]]: true}`.

8.8 The Completion Record Specification Type

The Completion type is a Record used to explain the runtime propagation of values and control flow such as the behaviour of statements (`break`, `continue`, `return` and `throw`) that perform nonlocal transfers of control.

Values of the Completion type are Record values whose fields are defined as by Table 11.

- Deleted:** Table 10 summarises internal properties used by this specification to categorize various kinds of native objects.
- Deleted:** these
- Deleted:** ies
- Deleted:** are not
- Deleted:** used
- Deleted:** may
- Deleted:** any of these
- Deleted:** ies
- Deleted:** Internal Properties
- Deleted:** that Categorize Native Object
- Deleted:** s
- Deleted:** Internal Property
- Formatted Table**
- Deleted:** `[[IsFunction]]`
- Deleted:** `]`
- Deleted:** `[[IsArray]]`
- Deleted:** `[[IsString]]`
- Deleted:** `[[IsBoolean]]`
- Deleted:** `[[IsNumber]]`
- Deleted:** `[[IsMath]]`
- Deleted:** c
- Deleted:** `[[IsDate]]`
- Deleted:**]
- Deleted:**]
- Deleted:** `[[IsRegExp]]`
- Deleted:** `[[IsError]]`
- Deleted:** `[[IsJSON]]`
- Deleted:** `[[IsArguments]]`
- Deleted:** `[]`
- Deleted:** aggregations
- Deleted:** the
- Deleted:** type
- Deleted:** a
- Deleted:** at
- Deleted:** .
- Deleted:** F
- Deleted:** ,
- Deleted:** fields
- Deleted:** why
- Deleted:** D
- Deleted:** D
- Deleted:** D
- Deleted:** F
- Deleted:** aggregations
- Deleted:** ie

Table 11 — Completion Record Fields

Field Name	Value	Meaning
<code>[[type]]</code>	One of <code>normal</code> , <code>break</code> , <code>continue</code> , <code>return</code> , or <code>throw</code>	The type of completion that occurred.
<code>[[value]]</code>	any ECMAScript language value or <code>empty</code>	The value that was produced.
<code>[[target]]</code>	any ECMAScript identifier or <code>empty</code>	The target label for directed control transfers.

The term “abrupt completion” refers to any completion with a `[[type]]` value other than `normal`.

8.8.1 Implicit Completion Values

The algorithms of this specification often implicitly return Completion Records whose `[[type]]` is `normal`. Unless it is otherwise obvious from the context, an algorithm statement that returns a value that is not a Completion Record, such as:

1. Return the String `"Infinity"`.

mean the same things as:

1. Return Completion `{[[type]]: normal, [[value]]: String "Infinity", [[target]]:empty}`.

Similarly, any reference to a Completion Record value that is in a context that does not explicitly require a complete Completion Record value is equivalent to an explicit reference to the `[[value]]` field of the Completion Record value unless the Completion Record is an abrupt completion.

8.8.2 NormalCompletion

The abstract operation `NormalCompletion` with a single `argument`, such as:

1. Return `NormalCompletion(argument)`.

Is a short hand that is defined as follows:

1. Return Completion `{[[type]]: normal, [[value]]: argument, [[target]]:empty}`.

8.8.3 Throw an Exception

Algorithms steps that say to throw an exception, such as

1. Throw a `TypeError` exception.

Mean the same things as:

1. Return Completion `{[[type]]: throw, [[value]]: a newly created TypeError object, [[target]]:empty}`.

8.8.4 ReturnIfAbrupt

Algorithms steps that say,

1. `ReturnIfAbrupt(argument)`.

mean the same things as:

1. If `argument` is an abrupt completion, then return `argument`.
2. Else if `argument` is a Completion Record, then let `argument` be `argument.[[value]]`.

Deleted: I

Deleted: y

Deleted: The abstraction operation `NormalValue` with a single `argument` is a short hand that is defined as follows:
 <#> If `argument` is not a Completion Record, return `argument`.
 <#> If `argument` is an abrupt completion, return `argument`.
 <#> Return `argument.[[value]]`.

Deleted: The abstraction operation `NormalCompletion` with a single `argument`, such as:
 <#> Return `NormalCompletion(argument)`.

Deleted:

Deleted: ,

Deleted: ,

Deleted: ,

8.9 The Reference Specification Type

NOTE The Reference type is used to explain the behaviour of such operators as `delete`, `typeof`, the assignment operators, [the `super` keyword and other language features](#). For example, the left-hand operand of an assignment is expected to produce a reference.

A **Reference** is a resolved name binding. A Reference consists of three components, the *base* value, the *referenced name* and the Boolean valued *strict reference* flag. The *base* value is either **undefined**, an Object, a Boolean, a String, a Number, or an environment record (10.2.1). A *base* value of **undefined** indicates that the *Reference* could not be resolved to a binding. The *referenced name* is a String.

[A Super Reference is a Reference that is used to represents a name binding that was expressed using the `super` keyword. A Super Reference has an additional `thisValue` component and its `base` value will never be an environment record.](#)

The following abstract operations are used in this specification to access the components of references:

- `GetBase(V)`. Returns the base value component of the reference *V*.
- `GetReferencedName(V)`. Returns the referenced name component of the reference *V*.
- `IsStrictReference(V)`. Returns the strict reference component of the reference *V*.
- `HasPrimitiveBase(V)`. Returns **true** if the base value is a Boolean, String, or Number.
- `IsPropertyReference(V)`. Returns **true** if either the base value is an object or `HasPrimitiveBase(V)` is **true**; otherwise returns **false**.
- [`IsUnresolvableReference\(V\)`](#). Returns **true** if the base value is **undefined** and **false** otherwise.
- [`IsSuperReference\(V\)`](#). Returns **true** if this reference has a `thisValue` component.

The following abstract operations are used in this specification to operate on references:

8.9.1 GetValue (V)

1. [`ReturnIfAbrupt\(V\)`](#).
2. If `Type(V)` is not Reference, return *V*.
3. Let *base* be the result of calling `GetBase(V)`.
4. If `IsUnresolvableReference(V)`, throw a **ReferenceError** exception.
5. If `IsPropertyReference(V)`, then
 - a. If `HasPrimitiveBase(V)` is **false**, then let *get* be the `[[Get]]` internal method of *base*, otherwise let *get* be the special `[[Get]]` internal method defined below.
 - b. If [`IsSuperReference\(V\)`](#) is **false**, then
 - i. Return the result of calling *get* as an internal method of *base* passing `GetReferencedName(V)` for the argument.
 - c. Else,
 - i. Return the result of calling *get* as an internal method of *base* passing `GetReferencedName(V)` and `GetThisValue(V)` as the arguments.
6. Else, *base* must be an environment record.
 - a. Return the result of calling the `GetBindingValue` (see 10.2.1) concrete method of *base* passing `GetReferencedName(V)` and `IsStrictReference(V)` as arguments.

The following `[[Get]](P[, accessorThisValue])` internal method is used by `GetValue` when *V* is a property reference with a primitive base value. *base* is the value the internal method is called upon with property name *P* as its argument. The following steps are taken:

1. Let *O* be `ToObject(base)`.
2. Let *desc* be the result of calling the `[[GetProperty]]` internal method of *O* with property name *P*.
3. If *desc* is **undefined**, return **undefined**.
4. If `IsDataDescriptor(desc)` is **true**, return *desc*.`[[Value]]`.
5. Otherwise, `IsAccessorDescriptor(desc)` must be **true** so, let *getter* be *desc*.`[[Get]]` (see 8.10).
6. If *getter* is **undefined**, return **undefined**.
7. If the `accessorThisValue` argument is not present, let `accessorThisValue` be *base*

Deleted: <#>.¶

Deleted: 7

Deleted: and

Deleted: The behaviour of assignment could, instead, explained entirely in terms of a case analysis on the syntactic form of the left-hand operand of an assignment operator, but for one difficulty: function calls are permitted to return references. This possibility is admitted purely the sake of host objects. No built-in ECMAScript function defined by this specification returns a reference and there is no provision for a user-defined function to return a reference. (Another reason not to use a syntactic case analysis is that it would be lengthy and awkward, affecting many parts of the specification.)

Deleted: reference

Deleted: 7

Deleted: <#>Let *V* be `NormalValue(V)`.¶

Deleted: the

Deleted: using

Deleted: as its `this` value, and

Deleted: It is called using

Deleted: as

Deleted: its `this` value and

8. Return the result of calling the [[Call]] internal method of *getter* providing *accessorThisValue* as the *this* value and providing no arguments.

NOTE The object that may be created in step 1 is not accessible outside of the above method. An implementation might choose to avoid the actual creation of the object. The only situation where such an actual property access that uses this internal method can have visible effect is when it invokes an accessor function.

8.9.2 PutValue (V, W)

1. ReturnIfAbrupt(V).
2. ReturnIfAbrupt(W).
3. If Type(V) is not Reference, throw a **ReferenceError** exception.
4. Let *base* be the result of calling GetBase(V).
5. If IsUnresolvableReference(V), then
 - a. If IsStrictReference(V) is **true**, then
 - i. Throw **ReferenceError** exception.
 - b. Return the result of calling the [[Put]] internal method of the global object, passing GetReferencedName(V) for the property name, W for the value, and false for the Throw flag.
6. Else if IsPropertyReference(V), then
 - a. If HasPrimitiveBase(V) is **false**, then let *put* be the [[Put]] internal method of *base*, otherwise let *put* be the special [[Put]] internal method defined below.
 - b. If IsSuperReference(V) is **false**, then
 - i. Return the result of calling *put* as an internal method of *base* passing GetReferencedName(V) for the property name, W for the value, and IsStrictReference(V) for the Throw flag.
 - c. Else,
 - i. Return the result of calling *put* as an internal method of *base* passing GetReferencedName(V) for the property name, W for the value, IsStrictReference(V) for the Throw flag, and GetThisValue(V) as the *accessorThisValue* argument.
7. Else *base* must be a reference whose base is an environment record. So,
 - a. Return the result of calling the SetMutableBinding (10.2.1) concrete method of *base*, passing GetReferencedName(V), W, and IsStrictReference(V) as arguments.
8. Return **undefined**.

The following [[Put]] internal method is used by PutValue when V is a property reference with a primitive base value. *base* is the value the internal method is called upon with property *name P*, value *W*, and Boolean flag *Throw* as required arguments and optional argument *accessorThisValue*. The following steps are taken:

1. Let *O* be ToObject(*base*).
2. If the result of calling the [[CanPut]] internal method of *O* with argument *P* is **false**, then
 - a. If *Throw* is **true**, then throw a **TypeError** exception.
 - b. Else return **undefined**.
3. Let *ownDesc* be the result of calling the [[GetOwnProperty]] internal method of *O* with argument *P*.
4. If IsDataDescriptor(*ownDesc*) is **true**, then
 - a. If *Throw* is **true**, then throw a **TypeError** exception.
 - b. Else return **undefined**.
5. Let *desc* be the result of calling the [[GetProperty]] internal method of *O* with argument *P*. This may be either an own or inherited accessor property descriptor or an inherited data property descriptor.
6. If IsAccessorDescriptor(*desc*) is **true**, then
 - a. Let *setter* be *desc*.[[Set]] (see 8.10) which cannot be **undefined**.
 - b. If *accessorThisValue* is not present, then let *accessorThisValue* be *base*.
 - c. Return the result of calling the [[Call]] internal method of *setter* providing *accessorThisValue* as the *this* value and an argument list containing only *W*.
7. Else, this is a request to create an own property on the transient object *O*
 - a. If *Throw* is **true**, then throw a **TypeError** exception.
8. Return **undefined**.

NOTE The object that may be created in step 1 is not accessible outside of the above method. An implementation might choose to avoid the actual creation of that transient object. The only situations where such an actual property assignment that uses this internal method can have visible effect are when it either invokes an accessor function or is in violation of a *Throw* predicated error check. When *Throw* is **true** any property assignment that would create a new property on the transient object throws an error.

Deleted: *base*

Deleted: 7

Deleted: <#>Let *V* be NormalValue(*V*).
<#>Let *W* be NormalValue(*W*).¶

Deleted: Call

Deleted: Call

Deleted: the

Deleted: using

Deleted: as its *this* value, and

Deleted: Call

Deleted: It is called using

Deleted: as its *this* value and

Deleted: Call

Deleted: *base*

8.9.3 GetThisValue (V)

1. ReturnIfAbrupt(V).
2. If Type(V) is not Reference, return V.
3. If IsUnresolvableReference(V), throw a **ReferenceError** exception.
4. If IsSuperReference(V), then
 - a. Return the value of the *thisValue* component of the reference V.
5. Return GetBase(V).

8.10 The Property Descriptor and Property Identifier Specification Types

The Property Descriptor type is used to explain the manipulation and reification of named property attributes. Values of the Property Descriptor type are records composed of named fields where each field's name is an attribute name and its value is a corresponding attribute value as specified in 8.6.1. In addition, any field may be present or absent.

Property Descriptor values may be further classified as data property descriptors and accessor property descriptors based upon the existence or use of certain fields. A data property descriptor is one that includes any fields named either **[[Value]]** or **[[Writable]]**. An accessor property descriptor is one that includes any fields named either **[[Get]]** or **[[Set]]**. Any property descriptor may have fields named **[[Enumerable]]** and **[[Configurable]]**. A Property Descriptor value may not be both a data property descriptor and an accessor property descriptor; however, it may be neither. A generic property descriptor is a Property Descriptor value that is neither a data property descriptor nor an accessor property descriptor. A fully populated property descriptor is one that is either an accessor property descriptor or a data property descriptor and that has all of the fields that correspond to the property attributes defined in either 8.6.1 [Table 5](#) or [Table 6](#).

For notational convenience within this specification, an object literal-like syntax can be used to define a property descriptor value. For example, `Property Descriptor {[[Value]]: 42, [[Writable]]: false, [[Configurable]]: true}` defines a data property descriptor. Field name order is not significant. Any fields that are not explicitly listed are considered to be absent.

In specification text and algorithms, dot notation may be used to refer to a specific field of a Property Descriptor. For example, if D is a property descriptor then `D.[[Value]]` is shorthand for "the field of D named **[[Value]]**".

The Property Identifier type is used to associate a property name with a Property Descriptor. Values of the Property Identifier type are pairs of the form **(name, descriptor)**, where name is a String and descriptor is a Property Descriptor value.

The following abstract operations are used in this specification to operate upon Property Descriptor values:

8.10.1 IsAccessorDescriptor (Desc)

When the abstract operation **IsAccessorDescriptor** is called with property descriptor *Desc*, the following steps are taken:

2. If *Desc* is **undefined**, then return **false**.
3. If both *Desc.[[Get]]* and *Desc.[[Set]]* are absent, then return **false**.
4. Return **true**.

8.10.2 IsDataDescriptor (Desc)

When the abstract operation **IsDataDescriptor** is called with property descriptor *Desc*, the following steps are taken:

1. If *Desc* is **undefined**, then return **false**.
2. If both *Desc.[[Value]]* and *Desc.[[Writable]]* are absent, then return **false**.
3. Return **true**.

Comment [AWB12]: The ES5 use of Property Identifier in specifying object literals has been removed. If no new usage is added they should be removed from the spec.

Deleted: 8.8 The List Specification Type¶

The List type is used to explain the evaluation of argument lists (see 11.2.4) in **new** expressions, in function calls, and in other algorithms where a simple list of values is needed. Values of the List type are simply ordered sequences of values. These sequences may be of any length.¶

8.9 The Completion Specification Type¶

The Completion type is used to explain the behaviour of statements (**break**, **continue**, **return** and **throw**) to perform nonlocal transfers of control. Values of the Completion type are triples of the form **(type, value, target)**, where **type** is one of **normal**, **break**, **continue**, **return**, or **throw**, **value** is any ECMAScript language value or **empty**, and **target** is any ECMAScript identifier or **empty**. If **cv** is a completion value then **cv.type**, **cv.value** and **cv.target** may be used to directly refer to its constituent values.¶

The term "abrupt completion" refers to any completion with a type other than **normal**.¶

8.10.3 IsGenericDescriptor (Desc)

When the abstract operation `IsGenericDescriptor` is called with property descriptor `Desc`, the following steps are taken:

1. If `Desc` is **`undefined`**, then return **`false`**.
2. If `IsAccessorDescriptor(Desc)` and `IsDataDescriptor(Desc)` are both **`false`**, then return **`true`**.
3. Return **`false`**.

8.10.4 FromPropertyDescriptor (Desc)

When the abstract operation `FromPropertyDescriptor` is called with property descriptor `Desc`, the following steps are taken:

The following algorithm assumes that `Desc` is a fully populated Property Descriptor, such as that returned from `[[GetOwnProperty]]` (see 8.12.1).

1. If `Desc` is **`undefined`**, then return **`undefined`**.
2. Let `obj` be the result of [the abstract operation `ObjectCreate` \(15.2\)](#).
3. If `IsDataDescriptor(Desc)` is **`true`**, then
 - a. Call the `[[DefineOwnProperty]]` internal method of `obj` with arguments **"value"**, Property Descriptor `{[[Value]]: Desc.[[Value]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and **`false`**.
 - b. Call the `[[DefineOwnProperty]]` internal method of `obj` with arguments **"writable"**, Property Descriptor `{[[Value]]: Desc.[[Writable]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and **`false`**.
4. Else, `IsAccessorDescriptor(Desc)` must be **`true`**, so
 - a. Call the `[[DefineOwnProperty]]` internal method of `obj` with arguments **"get"**, Property Descriptor `{[[Value]]: Desc.[[Get]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and **`false`**.
 - b. Call the `[[DefineOwnProperty]]` internal method of `obj` with arguments **"set"**, Property Descriptor `{[[Value]]: Desc.[[Set]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and **`false`**.
5. Call the `[[DefineOwnProperty]]` internal method of `obj` with arguments **"enumerable"**, Property Descriptor `{[[Value]]: Desc.[[Enumerable]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and **`false`**.
6. Call the `[[DefineOwnProperty]]` internal method of `obj` with arguments **"configurable"**, Property Descriptor `{[[Value]]: Desc.[[Configurable]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and **`false`**.
7. Return `obj`.

Deleted: ion

Deleted: creating a new object as if by the expression `new Object()` where `Object` is the standard built-in constructor with that name

8.10.5 ToPropertyDescriptor (Obj)

When the abstract operation `ToPropertyDescriptor` is called with object `Obj`, the following steps are taken:

1. [ReturnIfAbrupt\(Obj\)](#).
2. If `Type(Obj)` is not `Object` throw a **`TypeError`** exception.
3. Let `desc` be the result of creating a new Property Descriptor that initially has no fields.
4. If the result of calling the `[[HasProperty]]` internal method of `Obj` with argument **"enumerable"** is **`true`**, then
 - a. Let `enum` be the result of calling the `[[Get]]` internal method of `Obj` with **"enumerable"**.
 - b. [ReturnIfAbrupt\(enum\)](#).
 - c. Set the `[[Enumerable]]` field of `desc` to `ToBoolean(enum)`.
5. If the result of calling the `[[HasProperty]]` internal method of `Obj` with argument **"configurable"** is **`true`**, then
 - a. Let `conf` be the result of calling the `[[Get]]` internal method of `Obj` with argument **"configurable"**.
 - b. [ReturnIfAbrupt\(conf\)](#).
 - c. Set the `[[Configurable]]` field of `desc` to `ToBoolean(conf)`.
6. If the result of calling the `[[HasProperty]]` internal method of `Obj` with argument **"value"** is **`true`**, then
 - a. Let `value` be the result of calling the `[[Get]]` internal method of `Obj` with argument **"value"**.
 - b. [ReturnIfAbrupt\(value\)](#).
 - c. Set the `[[Value]]` field of `desc` to `value`.
7. If the result of calling the `[[HasProperty]]` internal method of `Obj` with argument **"writable"** is **`true`**, then
 - a. Let `writable` be the result of calling the `[[Get]]` internal method of `Obj` with argument **"writable"**.
 - b. [ReturnIfAbrupt\(writable\)](#).

Deleted: g

- c. Set the `[[Writable]]` field of `desc` to `ToBoolean(writable)`.
- 8. If the result of calling the `[[HasProperty]]` internal method of `Obj` with argument `"get"` is `true`, then
 - a. Let `getter` be the result of calling the `[[Get]]` internal method of `Obj` with argument `"get"`.
 - b. `ReturnIfAbrupt(getter)`.
 - c. If `IsCallable(getter)` is `false` and `getter` is not `undefined`, then throw a `TypeError` exception.
 - d. Set the `[[Get]]` field of `desc` to `getter`.
- 9. If the result of calling the `[[HasProperty]]` internal method of `Obj` with argument `"set"` is `true`, then
 - a. Let `setter` be the result of calling the `[[Get]]` internal method of `Obj` with argument `"set"`.
 - b. `ReturnIfAbrupt(setter)`.
 - c. If `IsCallable(setter)` is `false` and `setter` is not `undefined`, then throw a `TypeError` exception.
 - d. Set the `[[Set]]` field of `desc` to `setter`.
- 10. If either `desc.[[Get]]` or `desc.[[Set]]` are present, then
 - a. If either `desc.[[Value]]` or `desc.[[Writable]]` are present, then throw a `TypeError` exception.
- 11. Return `desc`.

8.11 The Lexical Environment and Environment Record Specification Types

The Lexical Environment and Environment Record types are used to explain the behaviour of name resolution in nested functions and blocks. These types and the operations upon them are defined in Clause 10.

8.12 Algorithms for Object Internal Methods

In the following algorithm descriptions, assume `O` is a native ECMAScript object, `P` is a String, `Desc` is a Property Description record, and `Throw` is a Boolean flag.

8.12.1 `[[GetOwnProperty]] (P)`

When the `[[GetOwnProperty]]` internal method of `O` is called with property name `P`, the following steps are taken:

1. If `O` doesn't have an own property with name `P`, return `undefined`.
2. Let `D` be a newly created Property Descriptor with no fields.
3. Let `X` be `O`'s own property named `P`.
4. If `X` is a data property, then
 - a. Set `D.[[Value]]` to the value of `X`'s `[[Value]]` attribute.
 - b. Set `D.[[Writable]]` to the value of `X`'s `[[Writable]]` attribute
5. Else `X` is an accessor property, so
 - a. Set `D.[[Get]]` to the value of `X`'s `[[Get]]` attribute.
 - b. Set `D.[[Set]]` to the value of `X`'s `[[Set]]` attribute.
6. Set `D.[[Enumerable]]` to the value of `X`'s `[[Enumerable]]` attribute.
7. Set `D.[[Configurable]]` to the value of `X`'s `[[Configurable]]` attribute.
8. Return `D`.

Deleted: `<#>ReturnIfAbrupt(O);`

However, if `O` is a String object it has a more elaborate `[[GetOwnProperty]]` internal method defined in 15.5.5.2.

8.12.2 `[[GetProperty]] (P)`

When the `[[GetProperty]]` internal method of `O` is called with property name `P`, the following steps are taken:

1. Let `prop` be the result of calling the `[[GetOwnProperty]]` internal method of `O` with property name `P`.
2. If `prop` is not `undefined`, return `prop`.
3. Let `proto` be the value of the `[[Prototype]]` internal property of `O`.
4. If `proto` is `null`, return `undefined`.
5. Return the result of calling the `[[GetProperty]]` internal method of `proto` with argument `P`.

Deleted: `<#>ReturnIfAbrupt(O);`

8.12.3 `[[Get]] (P, accessorThisValue)`

When the `[[Get]]` internal method of `O` is called with property name `P`, the following steps are taken:

1. Let `desc` be the result of calling the `[[GetProperty]]` internal method of `O` with property name `P`.

Deleted: `<#>ReturnIfAbrupt(O);`

2. If *desc* is **undefined**, return **undefined**.
3. If *IsDataDescriptor*(*desc*) is **true**, return *desc*.[[Value]].
4. Otherwise, *IsAccessorDescriptor*(*desc*) must be true so, let *getter* be *desc*.[[Get]].
5. If *getter* is **undefined**, return **undefined**.
6. **If *accessorThisValue* is not present, then let *accessorThisValue* be *O*.**
7. Return the result calling the [[Call]] internal method of *getter* providing *accessorThisValue* as the **this** value and providing no arguments.

Deleted: *O*

8.12.4 [[CanPut]] (*P*)

When the [[CanPut]] internal method of *O* is called with property name *P*, the following steps are taken:

1. Let *desc* be the result of calling the [[GetOwnProperty]] internal method of *O* with argument *P*. **Deleted:** <#>ReturnIfAbrupt(*O*).¶
2. If *desc* is not **undefined**, then
 - a. If *IsAccessorDescriptor*(*desc*) is **true**, then
 - i. If *desc*.[[Set]] is **undefined**, then return **false**.
 - ii. Else return **true**.
 - b. Else, *desc* must be a DataDescriptor so return the value of *desc*.[[Writable]].
3. Let *proto* be the [[Prototype]] internal property of *O*.
4. If *proto* is **null**, then return the value of the [[Extensible]] internal property of *O*.
5. Let *inherited* be the result of calling the [[GetProperty]] internal method of *proto* with property name *P*.
6. If *inherited* is **undefined**, return the value of the [[Extensible]] internal property of *O*.
7. If *IsAccessorDescriptor*(*inherited*) is **true**, then
 - a. If *inherited*.[[Set]] is **undefined**, then return **false**.
 - b. Else return **true**.
8. Else, *inherited* must be a DataDescriptor
 - a. If the [[Extensible]] internal property of *O* is **false**, return **false**.
 - b. Else return the value of *inherited*.[[Writable]].

Exotic objects may define additional constraints upon [[Put]] operations. If possible, **exotic** objects should not allow [[Put]] operations in situations where this definition of [[CanPut]] returns false.

Deleted: Host

Deleted: host

8.12.5 [[Put]] (*P, V, Throw, accessorThisValue*)

When the [[Put]] internal method of *O* is called with property *P*, value *V*, and Boolean flag *Throw*, the following steps are taken:

1. **If the result of calling the [[CanPut]] internal method of *O* with argument *P* is **false**, then** **Deleted:** <#>ReturnIfAbrupt(*O*).¶
 - a. If *Throw* is **true**, then throw a **TypeError** exception.
 - b. Else return **undefined**.
2. Let *ownDesc* be the result of calling the [[GetOwnProperty]] internal method of *O* with argument *P*.
3. If *IsDataDescriptor*(*ownDesc*) is **true**, then
 - a. Let *valueDesc* be the Property Descriptor {[[Value]]: *V*}.
 - b. **Return the result of calling the [[DefineOwnProperty]] internal method of *O* passing *P, valueDesc*, and *Throw* as arguments.** **Deleted:** Call
4. Let *desc* be the result of calling the [[GetProperty]] internal method of *O* with argument *P*. This may be **undefined** or either an own or inherited accessor property descriptor or an inherited data property descriptor. **Deleted:** <#>Return.¶
5. If *IsAccessorDescriptor*(*desc*) is **true**, then
 - a. Let *setter* be *desc*.[[Set]] which cannot be **undefined**.
 - b. **If *accessorThisValue* is not present, then let *accessorThisValue* be *O*.**
 - c. **Return the result of calling the [[Call]] internal method of *setter* providing *accessorThisValue* as the **this** value and providing *V* as the sole argument.** **Deleted:** Call
6. Else, create a named data property named *P* on object *O* as follows
 - a. Let *newDesc* be the Property Descriptor {[[Value]]: *V*, [[Writable]]: **true**, [[Enumerable]]: **true**, [[Configurable]]: **true**}.
 - b. **Return the result of calling the [[DefineOwnProperty]] internal method of *O* passing *P, newDesc*, and *Throw* as arguments.** **Deleted:** Call

Deleted: *thisValueO*

8.12.6 [[HasProperty]] (*P*)

When the [[HasProperty]] internal method of *O* is called with property name *P*, the following steps are taken:

1. Let *desc* be the result of calling the **[[GetProperty]]** internal method of *O* with property name *P*.
2. If *desc* is **undefined**, then return **false**.
3. Else return **true**.

Deleted: <#>ReturnIfAbrupt(*O*).¶

8.12.7 **[[Delete]]** (*P*, *Throw*)

When the **[[Delete]]** internal method of *O* is called with property name *P* and the Boolean flag *Throw*, the following steps are taken:

1. Let *desc* be the result of calling the **[[GetOwnProperty]]** internal method of *O* with property name *P*.
2. If *desc* is **undefined**, then return **true**.
3. If *desc*.**[[Configurable]]** is **true**, then
 - a. Remove the own property with name *P* from *O*.
 - b. Return **true**.
4. Else if *Throw*, then throw a **TypeError** exception.
5. Return **false**.

Deleted: <#>ReturnIfAbrupt(*O*).¶

8.12.8 **[[DefaultValue]]** (*hint*)

When the **[[DefaultValue]]** internal method of *O* is called with hint **String**, the following steps are taken:

1. Let *toString* be the result of calling the **[[Get]]** internal method of object *O* with argument "**toString**".
2. [ReturnIfAbrupt\(*toString*\)](#).
3. If **IsCallable**(*toString*) is **true** then,
 - a. Let *str* be the result of calling the **[[Call]]** internal method of *toString*, with *O* as the **this** value and an empty argument list.
 - b. [ReturnIfAbrupt\(*str*\)](#).
 - c. If *str* is a primitive value, return *str*.
4. Let *valueOf* be the result of calling the **[[Get]]** internal method of object *O* with argument "**valueOf**".
5. [ReturnIfAbrupt\(*valueOf*\)](#).
6. If **IsCallable**(*valueOf*) is **true** then,
 - a. Let *val* be the result of calling the **[[Call]]** internal method of *valueOf*, with *O* as the **this** value and an empty argument list.
 - b. [ReturnIfAbrupt\(*val*\)](#).
 - c. If *val* is a primitive value, return *val*.
7. Throw a **TypeError** exception.

Deleted: <#>ReturnIfAbrupt(*O*).¶

When the **[[DefaultValue]]** internal method of *O* is called with hint **Number**, the following steps are taken:

1. Let *valueOf* be the result of calling the **[[Get]]** internal method of object *O* with argument "**valueOf**".
2. [ReturnIfAbrupt\(*valueOf*\)](#).
3. If **IsCallable**(*valueOf*) is **true** then,
 - a. Let *val* be the result of calling the **[[Call]]** internal method of *valueOf*, with *O* as the **this** value and an empty argument list.
 - b. [ReturnIfAbrupt\(*val*\)](#).
 - c. If *val* is a primitive value, return *val*.
4. Let *toString* be the result of calling the **[[Get]]** internal method of object *O* with argument "**toString**".
5. [ReturnIfAbrupt\(*toString*\)](#).
6. If **IsCallable**(*toString*) is **true** then,
 - a. Let *str* be the result of calling the **[[Call]]** internal method of *toString*, with *O* as the **this** value and an empty argument list.
 - b. [ReturnIfAbrupt\(*str*\)](#).
 - c. If *str* is a primitive value, return *str*.
7. Throw a **TypeError** exception.

Deleted: <#>ReturnIfAbrupt(*O*).¶

When the **[[DefaultValue]]** internal method of *O* is called with no hint, then it behaves as if the hint were **Number**, unless *O* is a **Date** object (see 15.9.6), in which case it behaves as if the hint were **String**.

- The above specification of **[[DefaultValue]]** for **ordinary** objects can return only primitive values. If an **exotic** object implements its own **[[DefaultValue]]** internal method, it must ensure that its **[[DefaultValue]]** internal method can return only primitive values.

Deleted: native

Deleted: host

8.12.9 [[DefineOwnProperty]] (P, Desc, Throw)

In the following algorithm, the term “Reject” means “If *Throw* is **true**, then throw a **TypeError** exception, otherwise return **false**”. The algorithm contains steps that test various fields of the Property Descriptor *Desc* for specific values. The fields that are tested in this manner need not actually exist in *Desc*. If a field is absent then its value is considered to be **false**.

When the [[DefineOwnProperty]] internal method of *O* is called with property name *P*, property descriptor *Desc*, and Boolean flag *Throw*, the following steps are taken:

1. Let *current* be the result of calling the [[GetOwnProperty]] internal method of *O* with property name *P*.
2. Let *extensible* be the value of the [[Extensible]] internal property of *O*.
3. If *current* is **undefined** and *extensible* is **false**, then Reject.
4. If *current* is **undefined** and *extensible* is **true**, then
 - a. If IsGenericDescriptor(*Desc*) or IsDataDescriptor(*Desc*) is **true**, then
 - i. Create an own data property named *P* of object *O* whose [[Value]], [[Writable]], [[Enumerable]] and [[Configurable]] attribute values are described by *Desc*. If the value of an attribute field of *Desc* is absent, the attribute of the newly created property is set to its default value.
 - b. Else, *Desc* must be an accessor Property Descriptor so,
 - i. Create an own accessor property named *P* of object *O* whose [[Get]], [[Set]], [[Enumerable]] and [[Configurable]] attribute values are described by *Desc*. If the value of an attribute field of *Desc* is absent, the attribute of the newly created property is set to its default value.
 - c. Return **true**.
5. Return **true**, if every field in *Desc* is absent.
6. Return **true**, if every field in *Desc* also occurs in *current* and the value of every field in *Desc* is the same value as the corresponding field in *current* when compared using the SameValue algorithm (9.12).
7. If the [[Configurable]] field of *current* is **false** then
 - a. Reject, if the [[Configurable]] field of *Desc* is **true**.
 - b. Reject, if the [[Enumerable]] field of *Desc* is present and the [[Enumerable]] fields of *current* and *Desc* are the Boolean negation of each other.
8. If IsGenericDescriptor(*Desc*) is **true**, then no further validation is required.
9. Else, if IsDataDescriptor(*current*) and IsDataDescriptor(*Desc*) have different results, then
 - a. Reject, if the [[Configurable]] field of *current* is **false**.
 - b. If IsDataDescriptor(*current*) is **true**, then
 - i. Convert the property named *P* of object *O* from a data property to an accessor property. Preserve the existing values of the converted property’s [[Configurable]] and [[Enumerable]] attributes and set the rest of the property’s attributes to their default values.
 - c. Else,
 - i. Convert the property named *P* of object *O* from an accessor property to a data property. Preserve the existing values of the converted property’s [[Configurable]] and [[Enumerable]] attributes and set the rest of the property’s attributes to their default values.
10. Else, if IsDataDescriptor(*current*) and IsDataDescriptor(*Desc*) are both **true**, then
 - a. If the [[Configurable]] field of *current* is **false**, then
 - i. Reject, if the [[Writable]] field of *current* is **false** and the [[Writable]] field of *Desc* is **true**.
 - ii. If the [[Writable]] field of *current* is **false**, then
 1. Reject, if the [[Value]] field of *Desc* is present and SameValue(*Desc*.[[Value]], *current*.[[Value]]) is **false**.
 - b. else, the [[Configurable]] field of *current* is **true**, so any change is acceptable.
11. Else, IsAccessorDescriptor(*current*) and IsAccessorDescriptor(*Desc*) are both **true** so,
 - a. If the [[Configurable]] field of *current* is **false**, then
 - i. Reject, if the [[Set]] field of *Desc* is present and SameValue(*Desc*.[[Set]], *current*.[[Set]]) is **false**.
 - ii. Reject, if the [[Get]] field of *Desc* is present and SameValue(*Desc*.[[Get]], *current*.[[Get]]) is **false**.
12. For each attribute field of *Desc* that is present, set the correspondingly named attribute of the property named *P* of object *O* to the value of the field.
13. Return **true**.

Deleted: <#>ReturnIfAbrupt(*O*).¶

However, if O has an `[[NativeBrand]]` internal property whose value is `NativeArray`, O also has a more elaborate `[[DefineOwnProperty]]` internal method defined in 15.4.5.1.

NOTE Step 10.b allows any field of Desc to be different from the corresponding field of current if $\text{current}[[\text{Configurable}]]$ field is `true`. This even permits changing the `[[Value]]` of a property whose `[[Writable]]` attribute is `false`. This is allowed because a `true` `[[Configurable]]` attribute would permit an equivalent sequence of calls where `[[Writable]]` is first set to `true`, a new `[[Value]]` is set, and then `[[Writable]]` is set to `false`.

Deleted: `IsArray`

Deleted: is an `Array` object,

Deleted: `it`

8.12.10 `[[Enumerate]] (includePrototype, onlyEnumerable)`

When the `[[Enumerate]]` internal method of O is called with Boolean arguments `includePrototype` and `onlyEnumerable`, the following steps are taken:

1. Return an Iterator object (reference `xxxx`) whose next method iterates over all the keys of enumerable property keys of O . If `includePrototype` is `false`, then only own properties of O are included. If `onlyEnumerable` is `false`, then all properties that do not have private name keys are included. The mechanics and order of enumerating the properties is not specified but must conform to the rules specified below.

Comment [AWB613]: This is an experiment to see if we can use this internal method to define `Object.key`, `Object.getOwnPropertyNames`, and perhaps some other things

Comment [AWB614]: TODO

Enumerated properties do not include properties whose property key is a private name. Properties of the object being enumerated may be deleted during enumeration. If a property that has not yet been visited during enumeration is deleted, then it will not be visited. If new properties are added to the object being enumerated during enumeration, the newly added properties are not guaranteed to be visited in the active enumeration. A property name must not be visited more than once in any enumeration.

Enumerating the properties of an object includes enumerating properties of its prototype, and the prototype of the prototype, and so on, recursively; but a property of a prototype is not enumerated if it is "shadowed" because some previous object in the prototype chain has a property with the same name. The values of `[[Enumerable]]` attributes are not considered when determining if a property of a prototype object is shadowed by a previous object on the prototype chain.

The following is an informative algorithm that conforms to these rules

1. Let obj be O .
2. Let $proto$ be the value of the `[[Prototype]]` internal property of O .
3. If `includePrototype` is `false` or $proto$ is the value `null`, then
 - a. Let $propList$ be a new empty List.
4. Else
 - a. Let $propList$ be the result of calling the `[[Enumerate]]` internal method of $proto$ with arguments `true` and `onlyEnumerable`.
5. For each string $name$ that is the property key of an own property of O
 - a. Let $desc$ be the result of calling the `[[GetOwnProperty]]` internal method of O with argument $name$.
 - b. If $name$ is an element of $propList$, then remove $name$ as an element of $propList$.
 - c. If `onlyEnumerable` is `false` or $desc[[\text{Enumerable}]]$ is `true`, then add $name$ as an element of $propList$.
6. Order the elements of $propList$ in an implementation defined order.
7. Return $propList$.

Comment [AWB615]: TODO: Finish this up, and turn into iterator definition include a next method

Deleted: `op`

8.12.11 `[[Iterate]] ()`

When the `[[Iterate]]` internal method of O is called the following steps are taken:

1. Let itr be the result of performing `Invoke` with arguments `%iterator%`, O and an empty argument List.
2. Return itr .

Comment [AWB616]: Notation for private names known to the implementation

8.13 Data Blocks

This section is a placeholder for describing the Data Block internal type. The following material is verbatim from the the Binary Data ES wiki proposal. The material has not yet been reviewed or integrated with the rest of this spec.

This spec introduces a new, spec-internal block datatype, intuitively representing a contiguously allocated block of binary data. Blocks are not ECMAScript values and appear only in the program store (aka heap).

A block is one of:

- a number-block
- an array-block[t, n]
- a struct-block[t1, ..., tn]

A number-block is one of:

- an unsigned-integer; i.e., one of uint8, uint16, uint32, or uint64
- a signed-integer; i.e., one of int8, int16, int32, or int64
- a floating-point; i.e., one of float32 or float64

A uintk is an integer in the range [0, 2k). An intk is an integer in the range [-2k-1, 2k-1). A floatk is a floating-point number representable as a k-bit IEE754 value.

An array-block[t, n] is an ordered sequence of n blocks of homogeneous block type t. Each element of the array is stored at an independently addressable location in the program store, and multiple Data objects may contain references to the element.

A struct-block[t1, ..., tn] is an ordered sequence of n blocks of heterogeneous types t1 to tn, respectively. Each field of the struct is stored at an independently addressable location in the program store, and multiple Data objects may contain references to the field.

The spec also introduces a datatype of Data objects, which are ECMAScript values that encapsulate references to block data in the program store. Every Data object has the following properties:

- [[Class]] = "Data"
- [[Value]] : reference[block] – a reference to a block in the program store
- [[DataType]] : reference[Type] – a reference to a Type object describing this object's data block

9 Abstract Operations

These operations are not a part of the ECMAScript language; they are defined here to solely to aid the specification of the semantics of the ECMAScript Language. Other, more specialized abstract operations are defined throughout this specification.

9.1 Type Conversion and Testing

The ECMAScript language implicitly performs automatic type conversion as needed. To clarify the semantics of certain constructs it is useful to define a set of conversion abstract operations. The conversion abstract operations are polymorphic; that is, they can accept a value of any ECMAScript language type, but not of specification types.

9.1.1 ToPrimitive

The abstract operation ToPrimitive takes an input argument and an optional argument PreferredType. The abstract operation ToPrimitive converts its input argument to a non-Object type. If an object is capable of converting to more than one primitive type, it may use the optional hint PreferredType to favour that type. Conversion occurs according to [Table 12](#):

Deleted: runtime system

Deleted: These abstract operations are not part of the language; they are defined here to aid the specification of the semantics of the language

Deleted:

Table 12 — ToPrimitive Conversions

Input Type	Result
Completion Record	If <i>argument</i> is an abrupt completion, return <i>argument</i> . Otherwise return <code>ToPrimitive(argument.[[value]])</code>
Undefined	Return <i>argument</i> (no conversion).
Null	Return <i>argument</i> (no conversion).
Boolean	Return <i>argument</i> (no conversion).
Number	Return <i>argument</i> (no conversion).
String	Return <i>argument</i> (no conversion).
Object	<p>Perform the following steps:</p> <ol style="list-style-type: none"> 1. Let <i>default</i> be the result of calling the <code>[[DefaultValue]]</code> internal method of <i>argument</i>, passing the optional hint <i>PreferredType</i>. 2. Return <code>ToPrimitive(default)</code>. <p>The behaviour of the <code>[[DefaultValue]]</code> internal method is defined by this specification for all native ECMAScript objects in 8.12.8.</p>

- Deleted:** The result equals
- Deleted:** the *input* argument
- Deleted:** The result equals
- Deleted:** the *input* argument
- Deleted:** The result equals
- Deleted:** the *input* argument
- Deleted:** The result equals
- Deleted:** the *input* argument
- Deleted:** The result equals
- Deleted:** the *input* argument
- Deleted:** The result equals
- Deleted:** the *input* argument
- Deleted:** Return a default value for the Object. The default value of an object is retrieved by calling the `[[DefaultValue]]` internal method of the object, passing optional hint *PreferredType*.

9.1.2 ToBoolean

The abstract operation ToBoolean converts its *argument* to a value of type Boolean according to [Table 13](#):

Table 13 — ToBoolean Conversions

Argument Type	Result
Completion Record	If <i>argument</i> is an abrupt completion, return the argument. Otherwise return <code>ToBoolean(argument.[[value]])</code>
Undefined	Return <code>false</code>
Null	Return <code>false</code>
Boolean	Return the input argument (no conversion).
Number	Return <code>false</code> if the argument is <code>+0</code> , <code>-0</code> , or <code>Nan</code> ; otherwise return <code>true</code> .
String	Return <code>false</code> if the argument is the empty String (its length is zero); otherwise return <code>true</code> .
Object	Return <code>true</code>

- Deleted:** The result equals
- Deleted:** The result is

9.1.3 ToNumber

The abstract operation ToNumber converts its *argument* to a value of type Number according to [Table 14](#):

Table 14 — To Number Conversions

Argument Type	Result
Completion Record	If <i>argument</i> is an abrupt completion, return <i>argument</i> . Otherwise return ToNumber(<i>argument</i> .[value]).
Undefined	Return NaN
Null	Return +0
Boolean	Return 1 if <i>argument</i> is true. Return +0 if <i>argument</i> is false.
Number	Return <i>argument</i> (no conversion).
String	See grammar and note below.
Object	Apply the following steps: 1. Let <i>primValue</i> be ToPrimitive(<i>argument</i> , hint Number). 2. Return ToNumber(<i>primValue</i>).

- Deleted:** The result is
- Deleted:** the
- Deleted:** The result is
- Deleted:** the
- Deleted:** The result equals
- Deleted:** the *input*
- Deleted:** *input*

9.1.3.1 ToNumber Applied to the String Type

ToNumber applied to Strings applies the following grammar to the input String. If the grammar cannot interpret the String as an expansion of *StringNumericLiteral*, then the result of ToNumber is NaN.

Syntax

```

StringNumericLiteral ::=
  StrWhiteSpaceopt
  StrWhiteSpaceopt StrNumericLiteral StrWhiteSpaceopt

StrWhiteSpace ::=
  StrWhiteSpaceChar StrWhiteSpaceopt

StrWhiteSpaceChar ::=
  WhiteSpace
  LineTerminator

StrNumericLiteral ::=
  StrDecimalLiteral
  HexIntegerLiteral

StrDecimalLiteral ::=
  StrUnsignedDecimalLiteral
  + StrUnsignedDecimalLiteral
  - StrUnsignedDecimalLiteral

StrUnsignedDecimalLiteral ::=
  Infinity
  DecimalDigits . DecimalDigitsopt ExponentPartopt
  . DecimalDigits ExponentPartopt
  DecimalDigits ExponentPartopt

DecimalDigits ::=
  DecimalDigit
  DecimalDigits DecimalDigit

DecimalDigit :::
 one of
  0 1 2 3 4 5 6 7 8 9

```

ExponentPart ::::
ExponentIndicator *SignedInteger*

ExponentIndicator :::: one of
 e E

SignedInteger ::::
DecimalDigits
+ *DecimalDigits*
- *DecimalDigits*

HexIntegerLiteral ::::
0x *HexDigit*
0X *HexDigit*
HexIntegerLiteral *HexDigit*

HexDigit :::: one of
0 1 2 3 4 5 6 7 8 9 a b c d e f A B C D E F

| **NOTE** Some differences should be noted between the syntax of a *StringNumericLiteral* and a *NumericLiteral* (see 7.8.3):

- A *StringNumericLiteral* may be preceded and/or followed by white space and/or line terminators.
- A *StringNumericLiteral* that is decimal may have any number of leading 0 digits.
- A *StringNumericLiteral* that is decimal may be preceded by + or - to indicate its sign.
- A *StringNumericLiteral* that is empty or contains only white space is converted to +0.
- [Infinity](#) and [-Infinity](#) are recognized as a *StringNumericLiteral* but not as a *NumericLiteral*.

Runtime Semantics

The conversion of a String to a Number value is similar overall to the determination of the Number value for a numeric literal (see 7.8.3), but some of the details are different, so the process for converting a String numeric literal to a value of Number type is given here in full. This value is determined in two steps: first, a mathematical value (MV) is derived from the String numeric literal; second, this mathematical value is rounded as described below.

- The MV of *StringNumericLiteral* :::: [empty] is 0.
- The MV of *StringNumericLiteral* :::: *StrWhiteSpace* is 0.
- The MV of *StringNumericLiteral* :::: *StrWhiteSpace*_{opt} *StrNumericLiteral* *StrWhiteSpace*_{opt} is the MV of *StrNumericLiteral*, no matter whether white space is present or not.
- The MV of *StrNumericLiteral* :::: *StrDecimalLiteral* is the MV of *StrDecimalLiteral*.
- The MV of *StrNumericLiteral* :::: *HexIntegerLiteral* is the MV of *HexIntegerLiteral*.
- The MV of *StrDecimalLiteral* :::: *StrUnsignedDecimalLiteral* is the MV of *StrUnsignedDecimalLiteral*.
- The MV of *StrDecimalLiteral* :::: + *StrUnsignedDecimalLiteral* is the MV of *StrUnsignedDecimalLiteral*.
- The MV of *StrDecimalLiteral* :::: - *StrUnsignedDecimalLiteral* is the negative of the MV of *StrUnsignedDecimalLiteral*. (Note that if the MV of *StrUnsignedDecimalLiteral* is 0, the negative of this MV is also 0. The rounding rule described below handles the conversion of this signless mathematical zero to a floating-point +0 or -0 as appropriate.)
- The MV of *StrUnsignedDecimalLiteral*:::: **Infinity** is 10^{10000} (a value so large that it will round to +∞).
- The MV of *StrUnsignedDecimalLiteral*:::: *DecimalDigits* . is the MV of *DecimalDigits*.
- The MV of *StrUnsignedDecimalLiteral*:::: *DecimalDigits* . *DecimalDigits* is the MV of the first *DecimalDigits* plus (the MV of the second *DecimalDigits* times 10^{-n}), where *n* is the number of characters in the second *DecimalDigits*.
- The MV of *StrUnsignedDecimalLiteral*:::: *DecimalDigits* . *ExponentPart* is the MV of *DecimalDigits* times 10^e , where *e* is the MV of *ExponentPart*.
- The MV of *StrUnsignedDecimalLiteral*:::: *DecimalDigits* . *DecimalDigits* *ExponentPart* is (the MV of the first *DecimalDigits* plus (the MV of the second *DecimalDigits* times 10^{-n})) times 10^e , where *n* is the number of characters in the second *DecimalDigits* and *e* is the MV of *ExponentPart*.

- The MV of *StrUnsignedDecimalLiteral*:::. *DecimalDigits* is the MV of *DecimalDigits* times 10^{-n} , where *n* is the number of characters in *DecimalDigits*.
- The MV of *StrUnsignedDecimalLiteral*:::. *DecimalDigits ExponentPart* is the MV of *DecimalDigits* times 10^{e-n} , where *n* is the number of characters in *DecimalDigits* and *e* is the MV of *ExponentPart*.
- The MV of *StrUnsignedDecimalLiteral*:::. *DecimalDigits* is the MV of *DecimalDigits*.
- The MV of *StrUnsignedDecimalLiteral*:::. *DecimalDigits ExponentPart* is the MV of *DecimalDigits* times 10^e , where *e* is the MV of *ExponentPart*.
- The MV of *DecimalDigits* :::. *DecimalDigit* is the MV of *DecimalDigit*.
- The MV of *DecimalDigits* :::. *DecimalDigits DecimalDigit* is (the MV of *DecimalDigits* times 10) plus the MV of *DecimalDigit*.
- The MV of *ExponentPart* :::. *ExponentIndicator SignedInteger* is the MV of *SignedInteger*.
- The MV of *SignedInteger* :::. *DecimalDigits* is the MV of *DecimalDigits*.
- The MV of *SignedInteger* :::. + *DecimalDigits* is the MV of *DecimalDigits*.
- The MV of *SignedInteger* :::. - *DecimalDigits* is the negative of the MV of *DecimalDigits*.
- The MV of *DecimalDigit* :::. 0 or of *HexDigit* :::. 0 is 0.
- The MV of *DecimalDigit* :::. 1 or of *HexDigit* :::. 1 is 1.
- The MV of *DecimalDigit* :::. 2 or of *HexDigit* :::. 2 is 2.
- The MV of *DecimalDigit* :::. 3 or of *HexDigit* :::. 3 is 3.
- The MV of *DecimalDigit* :::. 4 or of *HexDigit* :::. 4 is 4.
- The MV of *DecimalDigit* :::. 5 or of *HexDigit* :::. 5 is 5.
- The MV of *DecimalDigit* :::. 6 or of *HexDigit* :::. 6 is 6.
- The MV of *DecimalDigit* :::. 7 or of *HexDigit* :::. 7 is 7.
- The MV of *DecimalDigit* :::. 8 or of *HexDigit* :::. 8 is 8.
- The MV of *DecimalDigit* :::. 9 or of *HexDigit* :::. 9 is 9.
- The MV of *HexDigit* :::. a or of *HexDigit* :::. A is 10.
- The MV of *HexDigit* :::. b or of *HexDigit* :::. B is 11.
- The MV of *HexDigit* :::. c or of *HexDigit* :::. C is 12.
- The MV of *HexDigit* :::. d or of *HexDigit* :::. D is 13.
- The MV of *HexDigit* :::. e or of *HexDigit* :::. E is 14.
- The MV of *HexDigit* :::. f or of *HexDigit* :::. F is 15.
- The MV of *HexIntegerLiteral* :::. 0x *HexDigit* is the MV of *HexDigit*.
- The MV of *HexIntegerLiteral* :::. 0x *HexDigit* is the MV of *HexDigit*.
- The MV of *HexIntegerLiteral* :::. *HexIntegerLiteral HexDigit* is (the MV of *HexIntegerLiteral* times 16) plus the MV of *HexDigit*.

Once the exact MV for a String numeric literal has been determined, it is then rounded to a value of the Number type. If the MV is 0, then the rounded value is +0 unless the first non white space character in the String numeric literal is ‘-’, in which case the rounded value is -0. Otherwise, the rounded value must be the Number value for the MV (in the sense defined in 8.5), unless the literal includes a *StrUnsignedDecimalLiteral* and the literal has more than 20 significant digits, in which case the Number value may be either the Number value for the MV of a literal produced by replacing each significant digit after the 20th with a 0 digit or the Number value for the MV of a literal produced by replacing each significant digit after the 20th with a 0 digit and then incrementing the literal at the 20th digit position. A digit is *significant* if it is not part of an *ExponentPart* and

- it is not 0; or
- there is a nonzero digit to its left and there is a nonzero digit, not in the *ExponentPart*, to its right.

9.1.4 ToInteger

The abstract operation *ToInteger* converts its argument to an integral numeric value. This abstract operation functions as follows:

1. Let *number* be the result of calling *ToNumber* on the input argument.
2. [ReturnIfAbrupt](#)(*number*).

3. If *number* is NaN, return +0.
4. If *number* is +0, -0, +∞, or -∞, return *number*.
5. Return the result of computing sign(*number*) × floor(abs(*number*)).

9.1.5 ToInt32: (Signed 32 Bit Integer)

The abstract operation ToInt32 converts its argument to one of 2^{32} integer values in the range -2^{31} through $2^{31}-1$, inclusive. This abstract operation functions as follows:

1. Let *number* be the result of calling ToNumber on the input argument.
2. [ReturnIfAbrupt\(*number*\)](#).
3. If *number* is NaN, +0, -0, +∞, or -∞, return +0.
4. Let *posInt* be sign(*number*) × floor(abs(*number*)).
5. Let *int32bit* be *posInt* modulo 2^{32} ; that is, a finite integer value *k* of Number type with positive sign and less than 2^{32} in magnitude such that the mathematical difference of *posInt* and *k* is mathematically an integer multiple of 2^{32} .
6. If *int32bit* is greater than or equal to 2^{31} , return *int32bit* - 2^{32} , otherwise return *int32bit*.

NOTE Given the above definition of ToInt32:

- The ToInt32 abstract operation is idempotent: if applied to a result that it produced, the second application leaves that value unchanged.
- ToInt32(ToInt32(*x*)) is equal to ToInt32(*x*) for all values of *x*. (It is to preserve this latter property that +∞ and -∞ are mapped to +0.)
- ToInt32 maps -0 to +0.

9.1.6 ToUint32: (Unsigned 32 Bit Integer)

The abstract operation ToUint32 converts its argument to one of 2^{32} integer values in the range 0 through $2^{32}-1$, inclusive. This abstract operation functions as follows:

Deleted: ion

1. Let *number* be the result of calling ToNumber on the input argument.
2. [ReturnIfAbrupt\(*number*\)](#).
3. If *number* is NaN, +0, -0, +∞, or -∞, return +0.
4. Let *posInt* be sign(*number*) × floor(abs(*number*)).
5. Let *int32bit* be *posInt* modulo 2^{32} ; that is, a finite integer value *k* of Number type with positive sign and less than 2^{32} in magnitude such that the mathematical difference of *posInt* and *k* is mathematically an integer multiple of 2^{32} .
6. Return *int32bit*.

NOTE Given the above definition of ToUint32:

- Step 5 is the only difference between ToUint32 and ToInt32.
- The ToUint32 abstract operation is idempotent: if applied to a result that it produced, the second application leaves that value unchanged.
- ToUint32(ToInt32(*x*)) is equal to ToUint32(*x*) for all values of *x*. (It is to preserve this latter property that +∞ and -∞ are mapped to +0.)
- ToUint32 maps -0 to +0.

9.1.7 ToUint16: (Unsigned 16 Bit Integer)

The abstract operation ToUint16 converts its argument to one of 2^{16} integer values in the range 0 through $2^{16}-1$, inclusive. This abstract operation functions as follows:

1. Let *number* be the result of calling ToNumber on the input argument.
2. [ReturnIfAbrupt\(*number*\)](#).
3. If *number* is NaN, +0, -0, +∞, or -∞, return +0.
4. Let *posInt* be sign(*number*) × floor(abs(*number*)).
5. Let *int16bit* be *posInt* modulo 2^{16} ; that is, a finite integer value *k* of Number type with positive sign and less than 2^{16} in magnitude such that the mathematical difference of *posInt* and *k* is mathematically an integer multiple of 2^{16} .

6. Return *int16bit*.

NOTE Given the above definition of ToUint16:

- The substitution of 2^{16} for 2^{32} in step 4 is the only difference between ToUint32 and ToUint16.
- ToUint16 maps **-0** to **+0**.

9.1.8 ToString

The abstract operation ToString converts its *argument* to a value of type String according to [Table 15](#):

[Table 15](#) — ToString Conversions

Argument Type	Result
Completion Record	If <i>argument</i> is an abrupt completion, return <i>argument</i> . Otherwise return <code>Tostring(argument.[[value]])</code>
Undefined	"undefined"
Null	"null"
Boolean	If <i>argument</i> is true , then <code>return "true"</code> . If <i>argument</i> is false , then <code>return "false"</code> .
Number	See 9.8.1.
String	Return <i>argument</i> (no conversion)
Object	Apply the following steps: 1. Let <i>primValue</i> be <code>ToPrimitive(argument, hint String)</code> . 2. Return <code>Tostring(primValue)</code> .

Deleted: the
Deleted: the result is
Deleted: the
Deleted: the result is
Deleted: the input
Deleted: input

9.1.8.1 ToString Applied to the Number Type

The abstract operation ToString converts a Number *m* to String format as follows:

1. If *m* is **NaN**, return the String "**NaN**".
2. If *m* is **+0** or **-0**, return the String "**0**".
3. If *m* is less than zero, return the String concatenation of the String **"-"** and `ToString(-m)`.
4. If *m* is infinity, return the String "**Infinity**".
5. Otherwise, let *n*, *k*, and *s* be integers such that $k \geq 1$, $10^{k-1} \leq s < 10^k$, the Number value for $s \times 10^{n-k}$ is *m*, and *k* is as small as possible. Note that *k* is the number of digits in the decimal representation of *s*, that *s* is not divisible by 10, and that the least significant digit of *s* is not necessarily uniquely determined by these criteria.
6. If $k \leq n \leq 21$, return the String consisting of the *k* digits of the decimal representation of *s* (in order, with no leading zeroes), followed by $n-k$ occurrences of the character '**0**'.
7. If $0 < n \leq 21$, return the String consisting of the most significant *n* digits of the decimal representation of *s*, followed by a decimal point '**.**', followed by the remaining $k-n$ digits of the decimal representation of *s*.
8. If $-6 < n \leq 0$, return the String consisting of the character '**0**', followed by a decimal point '**.**', followed by $-n$ occurrences of the character '**0**', followed by the *k* digits of the decimal representation of *s*.
9. Otherwise, if *k* = 1, return the String consisting of the single digit of *s*, followed by lowercase character '**e**', followed by a plus sign '**+**' or minus sign '**-**' according to whether *n*-1 is positive or negative, followed by the decimal representation of the integer $\text{abs}(n-1)$ (with no leading zeroes).
10. Return the String consisting of the most significant digit of the decimal representation of *s*, followed by a decimal point '**.**', followed by the remaining *k*-1 digits of the decimal representation of *s*, followed by the lowercase character '**e**', followed by a plus sign '**+**' or minus sign '**-**' according to whether *n*-1 is positive or negative, followed by the decimal representation of the integer $\text{abs}(n-1)$ (with no leading zeroes).

NOTE 1 The following observations may be useful as guidelines for implementations, but are not part of the normative requirements of this Standard:

- If *x* is any Number value other than **-0**, then `ToNumber(ToString(x))` is exactly the same Number value as *x*.
- The least significant digit of *s* is not always uniquely determined by the requirements listed in step 5.

NOTE 2 For implementations that provide more accurate conversions than required by the rules above, it is recommended that the following alternative version of step 5 be used as a guideline:

Otherwise, let n , k , and s be integers such that $k \geq 1$, $10^{k-1} \leq s < 10^k$, the Number value for $s \times 10^{n-k}$ is m , and k is as small as possible. If there are multiple possibilities for s , choose the value of s for which $s \times 10^{n-k}$ is closest in value to m . If there are two such possible values of s , choose the one that is even. Note that k is the number of digits in the decimal representation of s and that s is not divisible by 10.

NOTE 3 Implementers of ECMAScript may find useful the paper and code written by David M. Gay for binary-to-decimal conversion of floating-point numbers:

Gay, David M. Correctly Rounded Binary-Decimal and Decimal-Binary Conversions. Numerical Analysis, Manuscript 90-10. AT&T Bell Laboratories (Murray Hill, New Jersey). November 30, 1990. Available as <http://cm.bell-labs.com/cm/cs/doc/90/4-10.ps.gz>. Associated code available as <http://cm.bell-labs.com/netlib/fp/dtoa.c.gz> and as http://cm.bell-labs.com/netlib/fp/g_fmt.c.gz and may also be found at the various `netlib` mirror sites.

9.1.9 ToObject

The abstract operation `ToObject` converts its *argument* to a value of type `Object` according to [Table 16](#):

[Table 16](#) — `ToObject`

Argument Type	Result
Completion Record	If <i>argument</i> is an abrupt completion, return <i>argument</i> . Otherwise return <code>ToObject(argument.[[value]])</code> .
Undefined	Throw a <code>TypeError</code> exception.
Null	Throw a <code>TypeError</code> exception.
Boolean	Return a new Boolean object whose <code>[[PrimitiveValue]]</code> internal property is set to the value of <i>argument</i> . See 15.6 for a description of Boolean objects.
Number	Return a new Number object whose <code>[[PrimitiveValue]]</code> internal property is set to the value of <i>argument</i> . See 15.7 for a description of Number objects.
String	Return a new String object whose <code>[[PrimitiveValue]]</code> internal property is set to the value of <i>argument</i> . See 15.5 for a description of String objects.
Object	Return <i>argument</i> (no conversion).

- Deleted: Create
- Deleted: the
- Deleted: Create
- Deleted: the
- Deleted: Create
- Deleted: the
- Deleted: The result is
- Deleted: the input

9.1.10 ToPropertyKey

The abstract operation `ToPropertyKey` converts its *argument* to a value that can be used as a property key by performing the following steps:

1. ReturnIfAbrupt(*argument*).
2. If `Type(argument)` is `Object`, then
 - a. If *argument* has a `[[NativeBrand]]` internal property whose value is `NativePrivateName`, then
 - i. Return *argument*.
3. Return `ToString(argument)`.

9.2 Testing and Comparison Operations

9.2.1 CheckObjectCoercible

The abstract operation `CheckObjectCoercible` throws an error if its argument is a value that cannot be converted to an `Object` using `ToObject`. It is defined by [Table 17](#):

- Deleted: 0

Table 17 — CheckObjectCoercible Results

Argument Type	Result
Completion Record	If <i>argument</i> is an abrupt completion, return <i>argument</i> . Otherwise return <code>CheckObjectCoercible(argument.[[value]])</code>
Undefined	Throw a TypeError exception.
Null	Throw a TypeError exception.
Boolean	Return <i>argument</i>
Number	Return <i>argument</i>
String	Return <i>argument</i>
Object	Return <i>argument</i>

9.2.2 IsCallable

Deleted: 11

The abstract operation `IsCallable` determines if its *argument*, which must be an ECMAScript language value, is a callable function Object according to [Table 18](#):

Table 18 — IsCallable Results

Argument Type	Result
Completion Record	If <i>argument</i> is an abrupt completion, return <i>argument</i> . Otherwise return <code>IsCallable(argument.[[value]])</code>
Undefined	Return false .
Null	Return false .
Boolean	Return false .
Number	Return false .
String	Return false .
Object	If <i>argument</i> has a <code>[[Call]]</code> internal method, then return true , otherwise return false .

9.2.3 The SameValue Algorithm

Deleted: the
Deleted: object
Deleted: 12

The internal comparison abstract operation `SameValue(x, y)`, where *x* and *y* are ECMAScript language values, produces **true** or **false**. Such a comparison is performed as follows:

1. ReturnIfAbrupt(x).
2. ReturnIfAbrupt(y).
3. If `Type(x)` is different from `Type(y)`, return **false**.
4. If `Type(x)` is `Undefined`, return **true**.
5. If `Type(x)` is `Null`, return **true**.
6. If `Type(x)` is `Number`, then.
 - a. If *x* is `Nan` and *y* is `Nan`, return **true**.
 - b. If *x* is `+0` and *y* is `-0`, return **false**.
 - c. If *x* is `-0` and *y* is `+0`, return **false**.
 - d. If *x* is the same `Number` value as *y*, return **true**.
 - e. Return **false**.
7. If `Type(x)` is `String`, then return **true** if *x* and *y* are exactly the same sequence of characters (same length and same characters in corresponding positions); otherwise, return **false**.
8. If `Type(x)` is `Boolean`, return **true** if *x* and *y* are both **true** or both **false**; otherwise, return **false**.
9. Return **true** if *x* and *y* are the same Object value. Otherwise, return **false**.

Deleted: <#>If *x* is an Completion Record, let *x*:[[value]]. ¶
<#>If *y* is an Completion Record, let *y* be *y*:[[value]].

9.3 Operations on Objects

Deleted: refer to
Deleted: object
Deleted: Property Access
Deleted: Invoke
Deleted: ion
Deleted: abstract

9.3.1 Invoke

The abstract operation `Invoke` is used to call a method property of an object. The operation is called with arguments *P*, *O*, and *args* where *P* is the property key, *O* serves as both the lookup point for the property and

the `this` value of the call, and `args` is the list of arguments values passed to the method. This abstract operation perform, the following steps:

1. Let `obj` be `ToObject(O)`.
2. ReturnIfAbrupt(`obj`).
3. Let `func` be the result of calling the `[[Get]]` internal method of `obj` passing `P` as the argument.
4. ReturnIfAbrupt(`func`).
5. If `IsCallable(func)` is false, throw a `TypeError` exception.
6. Return the result of calling the `[[Call]]` internal method of `func` passing `O` as the `this` value and argument list `args`.

10 Executable Code and Execution Contexts

10.1 Types of Executable Code

There are three types of ECMAScript executable code:

- *Global code* is source text that is treated as an ECMAScript *Program*. The global code of a particular *Program* does not include any source text that is parsed as part of a *FunctionBody*.
- *Eval code* is the source text supplied to the built-in `eval` function. More precisely, if the parameter to the built-in `eval` function is a String, it is treated as an ECMAScript *Program*. The eval code for a particular invocation of `eval` is the global code portion of that *Program*.
- *Function code* is source text that is parsed to supply the value of the `[[Code]]` internal property (see 13.5) of *function* and *generator* objects. The *function code* of a particular *function* or *generator* does not include any source text that is parsed as the *function code* of a nested *function* or *generator*.

NOTE Function code is generally provided as the bodies of Function Definitions (13.1), Arrow Function Definitions (13.2), Method Definitions (13.3) and Generator Definitions (13.4). Function code is also derived from the last argument to the *Function* constructor (15.3).

10.1.1 Strict Mode Code

An ECMAScript *Program* syntactic unit may be processed using either unrestricted or strict mode syntax and semantics. When processed using strict mode the three types of ECMAScript code are referred to as strict global code, strict eval code, and strict function code. Code is interpreted as strict mode code in the following situations:

- Global code is strict global code if it begins with a Directive Prologue that contains a Use Strict Directive (see 14.1).
- Eval code is strict eval code if it begins with a Directive Prologue that contains a Use Strict Directive or if the call to `eval` is a direct call (see 15.1.2.1.1) to the `eval` function that is contained in strict mode code.
- Function code that is part of a *FunctionDeclaration*, *FunctionExpression*, or accessor *PropertyDefinition* is strict function code if its *FunctionDeclaration*, *FunctionExpression*, or *PropertyDefinition* is contained in strict mode code or if the function code begins with a Directive Prologue that contains a Use Strict Directive.
- Function code that is supplied as the last argument to the built-in *Function* constructor is strict function code if the last argument is a String that when processed as a *FunctionBody* begins with a Directive Prologue that contains a Use Strict Directive.

The term “base code” is used to designate code that is not strict code.

Comment [AWB717]: TODO: may need an additional reference to the `[[Code]]` of a generator.

Deleted: as part of a *FunctionBody*.

Deleted: *FunctionBody*

Deleted: part

Deleted: *FunctionBody*

Deleted: *Function code* also denotes the source text supplied when using the built-in *Function* object as a constructor. More precisely, the last parameter provided to the *Function* constructor is converted to a String and treated as the *FunctionBody*. If more than one parameter is provided to the *Function* constructor, all parameters except the last one are converted to Strings and concatenated together, separated by commas. The resulting String is interpreted as the *FormalParameterList* for the *FunctionBody* defined by the last parameter. The function code for a particular instantiation of a *Function* does not include any source text that is parsed as part of a nested *FunctionBody*.

Formatted: Note

Deleted: *PropertyAssignment*

Deleted: *PropertyAssignment*

Comment [AWB18]: Need to replace this with a statement about module bodies being strict code

Deleted: <#>Unless specified otherwise, extended code (10.21.12) is also considered strict mode code.||

Deleted: 10.1.2 Extended Code||

Extended code is any any code contained in an ECMAScript *Program* syntactic unit that contains occurrences of lexical or syntactic productions defined subsequent to the Fifth Edition of the ECMAScript specification. Code is interpreted as extended code in the following situations:||

<#>Global code is extended global code if it is contained in an ECMAScript *Program* syntactic unit that has been designated as an extended *Program* unit in an implementation defined manner or if ????.||

<#>Eval code is extended eval code if the call to eval is a direct call (see 15.1.2.1.1) to the eval function that is contained in extended mode code or if it begins with ????.||

<#>Function code that is part of a *FunctionDeclaration*, *FunctionExpression*, or accessor *PropertyAssignment* is extended function code if its *FunctionDeclaration*, *FunctionExpression*, or *PropertyAssignment* is contained in extended mode code or if the function code begins with ????.||

<#>Function code that is supplied as the last argument to the built-in *Function* constructor is strict function code if the last argument is a String that when processed as a *FunctionBody* begins with ????.||

The term “strict code” includes used to designate both actual strict mode code and extended code while the “extended code” is used to designate only used to mean actual extended code.

Deleted: extended

10.1.2 Non-ECMAScript Functions

An ECMAScript implementation may support the evaluation of function objects whose evaluative behaviour is expressed in some implementation defined form of executable code other than via ECMAScript code. Whether a function object is an ECMAScript code function or a non-ECMAScript function is not semantically observable from the perspective of an ECMAScript code function that calls or is called by such a non-ECMAScript function.

10.2 Lexical Environments

A *Lexical Environment* is a specification type used to define the association of *Identifiers* to specific variables and functions based upon the lexical nesting structure of ECMAScript code. A Lexical Environment consists of an Environment Record and a possibly null reference to an *outer* Lexical Environment. Usually a Lexical Environment is associated with some specific syntactic structure of ECMAScript code such as a *FunctionDeclaration*, a *BlockStatement*, or a *Catch* clause of a *TryStatement* and a new Lexical Environment is created each time such code is evaluated.

Deleted: *WithStatement*

An *Environment Record* records the identifier bindings that are created within the scope of its associated Lexical Environment.

The outer environment reference is used to model the logical nesting of Lexical Environment values. The outer reference of a (inner) Lexical Environment is a reference to the Lexical Environment that logically surrounds the inner Lexical Environment. An outer Lexical Environment may, of course, have its own outer Lexical Environment. A Lexical Environment may serve as the outer environment for multiple inner Lexical Environments. For example, if a *FunctionDeclaration* contains two nested *FunctionDeclarations* then the Lexical Environments of each of the nested functions will have as their outer Lexical Environment the Lexical Environment of the current *evaluation* of the surrounding function.

Deleted: execution

A *global environment* is a Lexical Environment which does not have an outer environment. The global environment's outer environment reference is *null*. A global environment's environment record may be prepopulated with identifier bindings and includes an associated *global object* whose properties provide some of the global environment's identifier bindings. This global object is the value of a global environment's *this* bindingAs ECMAScript code is executed, additional properties may be added to the global object and the initial properties may be modified.

A *method environment* is a Lexical Environment that corresponds to the invocation of an ECMAScript function object that establishes a new *this* binding. A method environment also captures the state necessary to support the *super* method invocations.

Lexical Environments and Environment Record values are purely specification mechanisms and need not correspond to any specific artefact of an ECMAScript implementation. It is impossible for an ECMAScript program to directly access or manipulate such values.

10.2.1 Environment Records

There are two kinds of Environment Record values used in this specification: *declarative environment records* and *object environment records*. Declarative environment records are used to define the effect of ECMAScript language syntactic elements such as *FunctionDeclarations*, *VariableDeclarations*, and *Catch* clauses that directly associate identifier bindings with ECMAScript language values. Object environment records are used to define the effect of ECMAScript elements such as *Program* and *WithStatement* that associate identifier bindings with the properties of some object.

For specification purposes Environment Record values can be thought of as existing in a simple object-oriented hierarchy where Environment Record is an abstract class with two concrete subclasses, declarative environment record and object environment record. The abstract class includes the abstract specification methods defined in [Table 19](#). These abstract methods have distinct concrete algorithms for each of the concrete subclasses.

Table 19 — Abstract Methods of Environment Records

Method	Purpose
HasBinding(N)	Determine if an environment record has a binding for an identifier. Return true if it does and false if it does not. The String value <i>N</i> is the text of the identifier.
CreateMutableBinding(N, D)	Create a new mutable binding in an environment record. The String value <i>N</i> is the text of the bound name. If the optional Boolean argument <i>D</i> is true the binding is may be subsequently deleted.
SetMutableBinding(N,V, S)	Set the value of an already existing mutable binding in an environment record. The String value <i>N</i> is the text of the bound name. <i>V</i> is the value for the binding and may be a value of any ECMAScript language type. <i>S</i> is a Boolean flag. If <i>S</i> is true and the binding cannot be set throw a TypeError exception. <i>S</i> is used to identify strict mode references.
GetBindingValue(N,S)	Returns the value of an already existing binding from an environment record. The String value <i>N</i> is the text of the bound name. <i>S</i> is used to identify strict mode references. If <i>S</i> is true and the binding does not exist or is uninitialised throw a ReferenceError exception.
DeleteBinding(N)	Delete a binding from an environment record. The String value <i>N</i> is the text of the bound name. If a binding for <i>N</i> exists, remove the binding and return true . If the binding exists but cannot be removed return false . If the binding does not exist return true .
<u>CreateVarBinding(N, D)</u>	<u>Used for global <code>var</code> and <code>function</code> bindings. Create a new mutable binding in an environment record. The String value <i>N</i> is the text of the bound name. If the optional Boolean argument <i>D</i> is true the binding is may be subsequently deleted. This is logically equivalent to CreateMutableBinding but it allows <code>var</code> and <code>function</code> declaration to receive special treatment.</u>
<u>HasThisBinding()</u>	<u>Determine if an environment record establishes a <code>this</code> binding. Return true if it does and false if it does not.</u>
<u>HasSuperBinding()</u>	<u>Determine if an environment record establishes a <code>super</code> method binding. Return true if it does and false if it does not.</u>
<u>WithBaseObject()</u>	<u>If this environment record is associated with a <code>with</code> statement, return the <code>with</code> object. Otherwise, return <code>undefined</code>.</u>

10.2.1.1 Declarative Environment Records

Each declarative environment record is associated with an ECMAScript program scope containing variable, constant, and/or function declarations. A declarative environment record binds the set of identifiers defined by the declarations contained within its scope.

In addition to the mutable bindings supported by all Environment Records, declarative environment records also provide for immutable bindings. An immutable binding is one where the association between an identifier and a value may not be modified once it has been established. Creation and initialisation of declarative binding are distinct steps so it is possible for such bindings to exist in either an initialised or uninitialised state. Declarative environment records support the methods listed in [Table 20](#) in addition to the Environment Record abstract specification methods:

Deleted: ImplicitThisValue

Formatted Table

Deleted: Returns the value to use as the `this` value or calls to function objects that are obtained as binding values from this environment record.

Deleted: immutable

Table 20 — Additional Methods of Declarative Environment Records

Method	Purpose
CreateImmutableBinding(N)	Create a new but uninitialised immutable binding in an environment record. The String value <i>N</i> is the text of the bound name.
InitializeBinding(N,V)	Set the value of an already existing but uninitialised binding in an environment record. The String value <i>N</i> is the text of the bound name. <i>V</i> is the value for the binding and is a value of any ECMAScript language type.

Formatted Table

Deleted: Immutable
Deleted: immutable

The behaviour of the concrete specification methods for Declarative Environment Records is defined by the following algorithms.

10.2.1.1.1 HasBinding(N)

The concrete environment record method HasBinding for declarative environment records simply determines if the argument identifier is one of the identifiers bound by the record:

1. Let *envRec* be the declarative environment record for which the method was invoked.
2. If *envRec* has a binding for the name that is the value of *N*, return **true**.
3. If it does not have such a binding, return **false**.

10.2.1.1.2 CreateMutableBinding (N, D)

The concrete Environment Record method CreateMutableBinding for declarative environment records creates a new mutable binding for the name *N* that is initialised to the value **undefined**. A binding must not already exist in this Environment Record for *N*. If Boolean argument *D* is provided and has the value **true** the new binding is marked as being subject to deletion.

1. Let *envRec* be the declarative environment record for which the method was invoked.
2. Assert: *envRec* does not already have a binding for *N*.
3. Create a mutable binding in *envRec* for *N* and record that it is uninitialised. If *D* is true record that the newly created binding may be deleted by a subsequent DeleteBinding call.
4. [Return NormalCompletion\(empty\)](#)

Deleted: set its bound value to **undefined**

10.2.1.1.3 SetMutableBinding (N,V,S)

The concrete Environment Record method SetMutableBinding for declarative environment records attempts to change the bound value of the current binding of the identifier whose name is the value of the argument *N* to the value of argument *V*. A binding for *N* must already exist. If the binding is an immutable binding, a **TypeError** is thrown if *S* is **true**.

1. Let *envRec* be the declarative environment record for which the method was invoked.
2. Assert: *envRec* must have a binding for *N*.
3. Assert: The binding for *N* in *envRec* has already been initialised.
4. If the binding for *N* in *envRec* is a mutable binding, change its bound value to *V*.
5. Else if binding for *N* in *envRec* has not yet been initialised throw a ReferenceError exception.
6. Else this must be an attempt to change the value of an immutable binding so if *S* is **true** throw a **TypeError** exception.
7. [Return NormalCompletion\(**undefined**\)](#).

Deleted: if

10.2.1.1.4 GetBindingValue(N,S)

The concrete Environment Record method GetBindingValue for declarative environment records simply returns the value of its bound identifier whose name is the value of the argument *N*. The binding must already exist. If *S* is **true** and the binding is an uninitialised immutable binding throw a **ReferenceError** exception.

1. Let *envRec* be the declarative environment record for which the method was invoked.
2. Assert: *envRec* has a binding for *N*.
3. If the binding for *N* in *envRec* is an uninitialised binding, then
 - a. If *S* is **false**, return the value **undefined**, otherwise throw a **ReferenceError** exception.
4. Else, return the value currently bound to *N* in *envRec*.

Deleted: immutable

10.2.1.5 DeleteBinding (*N*)

The concrete Environment Record method `DeleteBinding` for declarative environment records can only delete bindings that have been explicitly designated as being subject to deletion.

1. Let *envRec* be the declarative environment record for which the method was invoked.
2. If *envRec* does not have a binding for the name that is the value of *N*, return **true**.
3. If the binding for *N* in *envRec* is cannot be deleted, return **false**.
4. Remove the binding for *N* from *envRec*.
5. Return **true**.

10.2.1.6 CreateVarBinding (*N, D*)

The concrete Environment Record method `CreateVarBinding` for declarative environment records performs the same action as the `CreateMutableBinding` concrete method of the same environment Record.

1. Let *envRec* be the declarative environment record for which the method was invoked.
2. Return the result of calling *envRec*'s `CreateMutableBinding` concrete method with arguments *N* and *D*.

10.2.1.7 HasThisBinding ()

Regular Declarative Environment Records do not provide a `this` binding.

1. Return **false**.

10.2.1.8 HasSuperBinding ()

Regular Declarative Environment Records do not provide a `super` binding.

1. Return **false**.

10.2.1.9 WithBaseObject()

Declarative Environment Records always return **undefined** as their `WithBaseObject`.

1. Return **undefined**.

10.2.1.10 CreateImmutableBinding (*N*)

The concrete Environment Record method `CreateImmutableBinding` for declarative environment records creates a new immutable binding for the name *N* that is initialised to the value **undefined**. A binding must not already exist in this environment record for *N*.

1. Let *envRec* be the declarative environment record for which the method was invoked.
2. Assert: *envRec* does not already have a binding for *N*.
3. Create an immutable binding in *envRec* for *N* and record that it is uninitialised.

Deleted: 6

Deleted: ImplicitThisValue

Deleted: ImplicitThisValue

Comment [AWB19]: This probably needs a *D* option argument, just like `createMutableEnvironment`

Deleted: 7

10.2.1.11 InitializeBinding (*N, V*)

The concrete Environment Record method `InitializeBinding` for declarative environment records is used to set the bound value of the current binding of the identifier whose name is the value of the argument *N* to the value of argument *V*. An uninitialised binding for *N* must already exist.

1. Let *envRec* be the declarative environment record for which the method was invoked.
2. Assert: *envRec* must have an uninitialised binding for *N*.
3. Set the bound value for *N* in *envRec* to *V*.

Deleted: 8

Deleted: Immutable

Deleted: Immutable

Deleted: immutable

Deleted: immutable

4. Record that the binding for N in $envRec$ has been initialised.

Deleted: immutable

10.2.1.2 Object Environment Records

Each object environment record is associated with an object called its *binding object*. An object environment record binds the set of identifier names that directly correspond to the property names of its binding object. Property names that are not an *IdentifierName* are not included in the set of bound identifiers. Both own and inherited properties are included in the set regardless of the setting of their `[[Enumerable]]` attribute. Because properties can be dynamically added and deleted from objects, the set of identifiers bound by an object environment record may potentially change as a side-effect of any operation that adds or deletes properties. Any bindings that are created as a result of such a side-effect are considered to be a mutable binding even if the `Writable` attribute of the corresponding property has the value `false`. Immutable bindings do not exist for object environment records.

Object environment records [created for `with` statements \(12.10\)](#) can provide their binding object as an implicit this value for use in function calls. The capability is controlled by a `withEnvironment` Boolean value that is associated with each object environment record. By default, the value of `withEnvironment` is `false` for any object environment record.

The behaviour of the concrete specification methods for Object Environment Records is defined by the following algorithms.

Deleted: be configured to

Deleted: This capability is used to specify the behaviour of With Statement (12.10) induced bindings.

Deleted: `provideThis`

Deleted: `provideThis`

10.2.1.2.1 HasBinding(N)

The concrete Environment Record method `HasBinding` for object environment records determines if its associated binding object has a property whose name is the value of the argument N :

1. Let $envRec$ be the object environment record for which the method was invoked.
2. Let $bindings$ be the binding object for $envRec$.
3. Return the result of calling the `[[HasProperty]]` internal method of $bindings$, passing N as the property name.

10.2.1.2.2 CreateMutableBinding (N, D)

The concrete Environment Record method `CreateMutableBinding` for object environment records creates in an environment record's associated binding object a property whose name is the String value and initialises it to the value `undefined`. A property named N must not already exist in the binding object. If Boolean argument D is provided and has the value `true` the new property's `[[Configurable]]` attribute is set to `true`, otherwise it is set to `false`.

1. Let $envRec$ be the object environment record for which the method was invoked.
2. Let $bindings$ be the binding object for $envRec$.
3. Assert: The result of calling the `[[HasProperty]]` internal method of $bindings$, passing N as the property name, is `false`.
4. If D is `true` then let `configValue` be `true` otherwise let `configValue` be `false`.
5. [Return the result of calling](#) the `[[DefineOwnProperty]]` internal method of $bindings$, passing N , Property Descriptor `{[[Value]]: undefined, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: configValue}`, and `true` as arguments.

Deleted: Call

10.2.1.2.3 SetMutableBinding (N, V, S)

The concrete Environment Record method `SetMutableBinding` for object environment records attempts to set the value of the environment record's associated binding object's property whose name is the value of the argument N to the value of argument V . A property named N should already exist but if it does not or is not currently writable, error handling is determined by the value of the Boolean argument S .

1. Let $envRec$ be the object environment record for which the method was invoked.
2. Let $bindings$ be the binding object for $envRec$.
3. [Return the result of calling](#) the `[[Put]]` internal method of $bindings$ with arguments N , V , and S .

Deleted: Call

10.2.1.2.4 GetBindingValue(N,S)

The concrete Environment Record method `GetBindingValue` for object environment records returns the value of its associated binding object's property whose name is the String value of the argument identifier `N`. The property should already exist but if it does not the result depends upon the value of the `S` argument:

1. Let `envRec` be the object environment record for which the method was invoked.
2. Let `bindings` be the binding object for `envRec`.
3. Let `value` be the result of calling the `[[HasProperty]]` internal method of `bindings`, passing `N` as the property name.
4. If `value` is `false`, then
 - a. If `S` is `false`, return the value `undefined`, otherwise throw a `ReferenceError` exception.
5. Return the result of calling the `[[Get]]` internal method of `bindings`, passing `N` for the argument.

10.2.1.2.5 DeleteBinding (N)

The concrete Environment Record method `DeleteBinding` for object environment records can only delete bindings that correspond to properties of the environment object whose `[[Configurable]]` attribute have the value `true`.

1. Let `envRec` be the object environment record for which the method was invoked.
2. Let `bindings` be the binding object for `envRec`.
3. Return the result of calling the `[[Delete]]` internal method of `bindings`, passing `N` and `false` as arguments.

10.2.1.2.6 CreateVarBinding (N, D)

Deleted: 1

The concrete Environment Record method `CreateVarBinding` for object environment records performs the same action as the `CreateMutableBinding` concrete method of the same environment Record.

1. Let `envRec` be the declarative environment record for which the method was invoked.
2. Return the result of calling `envRec`'s `CreateMutableBinding` concrete method with arguments `N` and `D`.

10.2.1.2.7 HasThisBinding ()

Regular Object Environment Records do not provide a `this` binding.

1. Return `false`.

10.2.1.2.8 HasSuperBinding ()

Regular Object Environment Records do not provide a `super` binding.

1. Return `false`.

10.2.1.2.9 WithBaseObject()

Deleted: 6

Deleted: ImplicitThisValue

Deleted: ImplicitThisValue

Deleted: provideThis

Deleted: provideThis

Deleted: 4

Object Environment Records return `undefined` as their `WithBaseObject` unless their `withEnvironment` flag is `true`.

1. Let `envRec` be the object environment record for which the method was invoked.
2. If the `withEnvironment` flag of `envRec` is `true`, return the binding object for `envRec`.
3. Otherwise, return `undefined`.

10.2.1.3 Method Environment Records

A method environment record is a declarative environment record that is used to represent the outer most scope of a function that provides a `this` binding. In addition to its identifier bindings, a method environment record contains the `this` value used within its scope. If such a function references `super`, its method environment record also contains the state that is used to perform `super` method invocations from within the function.

Method environment records store their `this` binding as the value of their `thisValue`. If the associated function references `super`, the environment record stores in `HomeObject` the object that the function is bound to as a method and in `MethodName` the property key used for unqualified super invocations from within the function. The default value for `HomeObject` and `MethodName` is `undefined`.

Methods environment records support all of Declarative Environment Record methods listed in Table 19 and Table 20 and share the same specifications for those methods. In addition, declarative environment records support the methods listed in Table 21:

Table 21 — Additional Methods of Method Environment Records

Method	Purpose
<code>GetThisBinding()</code>	Return the value of this environment record's <code>this</code> binding.
<code>GetSuperBase()</code>	Return the object that is the base for <code>super</code> property accesses bound in this environment record. The object is derived from this environment record's <code>HomeObject</code> binding. If the value is Empty, return <code>undefined</code> .
<code>GetMethodname()</code>	Return the value of this environment record's <code>MethodName</code> binding.

Deleted: Home
Deleted: Object
Deleted: value
Deleted: of

The behaviour of the additional concrete specification methods for Method Environment Records is defined by the following algorithms:

10.2.1.3.1 HasThisBinding ()

Regular Method Environment Records always provide a `this` binding.

1. Return `true`.

10.2.1.3.2 HasSuperBinding ()

1. If this environment record's `HomeObject` has the value `Empty`, then return `false`. Otherwise, return `true`.

10.2.1.3.3 GetThisBinding ()

1. Return the value of this environment record's `thisValue`.

10.2.1.3.4 GetSuperBase ()

1. Let `home` be the value of this environment record's `HomeObject`.
2. If `home` has the value `Empty`, then return `undefined`.
3. Assert `Type(home)` is `Object`.
4. Return the value of `home`'s `[[Prototype]]` internal property.

Deleted: HomeObject
Deleted: this environment record's HomeObject
Deleted:
Deleted: Otherwise, r
Deleted: HomeObject value

10.2.1.3.5 GetMethodName ()

1. Return the value of this environment record's `MethodName`.

10.2.1.4 Global Environment Records

A global environment is used to represent the outer most scope of a ECMAScript *Program*. If such a function references `super`, A global environment provides the bindings for built-in globals (15.1), properties of the global object, and for all declarations that are not function code and that occur within *Program* productions.. All ECMAScript *Program* productions that are processed in a specific Realm (10.3) share the same global environment record..

The behaviour of the concrete specification methods for Global Environment Records is defined by the following algorithms:

Comment [AWB720]: TODO

10.2.2 Lexical Environment Operations

The following abstract operations are used in this specification to operate upon lexical environments:

10.2.2.1 GetIdentifierReference (lex, name, strict)

The abstract operation `GetIdentifierReference` is called with a Lexical Environment `lex`, a `String name`, and a Boolean flag `strict`. The value of `lex` may be `null`. When called, the following steps are performed:

1. If `lex` is the value `null`, then
 - a. Return a value of type Reference whose base value is `undefined`, whose referenced name is `name`, and whose strict mode flag is `strict`.
2. Let `envRec` be `lex`'s environment record.
3. Let `exists` be the result of calling the `HasBinding(N)` concrete method of `envRec` passing `name` as the argument `N`.
4. If `exists` is `true`, then
 - a. Return a value of type Reference whose base value is `envRec`, whose referenced name is `name`, and whose strict mode flag is `strict`.
5. Else
 - a. Let `outer` be the value of `lex`'s outer environment reference.
 - b. Return the result of calling `GetIdentifierReference` passing `outer`, `name`, and `strict` as arguments.

Deleted: n

Deleted: identifier

10.2.2.2 NewDeclarativeEnvironment (E)

When the abstract operation `NewDeclarativeEnvironment` is called with either a Lexical Environment or `null` as argument `E` the following steps are performed:

1. Let `env` be a new Lexical Environment.
2. Let `envRec` be a new declarative environment record containing no bindings.
3. Set `env`'s environment record to be `envRec`.
4. Set the outer lexical environment reference of `env` to `E`.
5. Return `env`.

10.2.2.3 NewObjectEnvironment (O, E)

When the abstract operation `NewObjectEnvironment` is called with an Object `O` and a Lexical Environment `E` (or `null`) as arguments, the following steps are performed:

1. Let `env` be a new Lexical Environment.
2. Let `envRec` be a new object environment record containing `O` as the binding object.
3. Set `env`'s environment record to be `envRec`.
4. Set the outer lexical environment reference of `env` to `E`.
5. Return `env`.

10.2.2.4 NewMethodEnvironment (F, T)

When the abstract operation `NewObjectEnvironment` is called with an ECMAScript function Object `F` and a ECMAScript value `T` as arguments, the following steps are performed:

1. Let `env` be a new Lexical Environment.
2. Let `envRec` be a new method environment record containing containing no bindings.
3. Set `envRec`'s `thisValue` to `T`.
4. If `F` has a `[[Home]]` internal property, then
 - a. Set `envRec`'s `HomeObject` to the value of `F`'s `[[Home]]` internal property.
 - b. Set `envRec`'s `MethodName` to the value of `F`'s `[[MethodName]]` internal property.
5. Else, Set `envRec`'s `home` to `Empty`.
6. Set `env`'s environment record to be `envRec`.
7. Set the outer lexical environment reference of `env` to the value of `F`'s `[[Scope]]` internal property.
8. Return `env`.

10.3 Code Realms

Before it is evaluated, all ECMAScript code must be associated with a *Realm*. Conceptually, a realm consists as of an set of intrinsic objects, an ECMAScript global environment, all of the ECMAScript code that is loaded within the scope of that global environment, a *Loader* object that can associate new ECMAScript code with the realm, and other associated state and resources.

A Realm is specified as a Record with the fields specified in [Table 22](#):

[Table 22 — Realm Record Fields](#)

Field Name	Value	Meaning
<code>[[intrinsic]]</code>	A record whose field names are intrinsic keys and whose values are objects	These are the intrinsic values used by code associated with this Realm
<code>[[this]]</code>	An ECMAScript object	The global object for this Realm
<code>[[globalEnv]]</code>	A ECMAScript environment	The global environment for this Realm
<code>[[loader]]</code>	any ECMAScript identifier or <code>empty</code>	The Loader object that can associate ECMAScript code with this Realm

10.4 Execution Contexts

An execution context is an specification device that is used to track the runtime evaluation of code by an ECMAScript implementation. At any point in time, there is at most one execution context that is actually executing code. This is known as the *running* execution context. A stack is used to track execution contexts. The running execution context is always to top element of this stack. A new execution context is created whenever control is transferred from the executable code associated with the currently running execution context to executable code that is not associated with that execution context. The newly created execution context is pushed onto the stack and becomes the running execution context.

An execution context contains whatever implementation specific state is necessary to track the execution progress of its associated code. Each execution context has the state components listed in [Table 23](#).

[Table 23 — State Components for All Execution Contexts](#)

Component	Purpose
<code>code evaluation state</code>	Any state needed to perform, suspend, and resume evaluation of the code associated with this execution context.
<code>Realm</code>	The Realm from which associated code accesses ECMAScript resources.

Evaluation of code by the running execution context may be suspended at various points defined within this specification. Once the running execution context has been suspended a different execution context may become the running execution context and commence evaluating its code. At some latter time a suspended execution context may again become the running execution context and continue evaluating its code at the point where it had previously been suspended. Transition of the running execution context status among execution contexts usually occurs in stack-like last-in/first-out manner. However, some ECMAScript features require non-LIFO transitions of the running execution context.

Execution contexts for ECMAScript code have the additional state components listed in [Table 24](#).

Comment [AWB821]: Other possible terms that have been discussed are "Home" and "Island". We still need to get final agreement terminology.

Deleted: following

Deleted: 10.2.3 The Global Environment

The *global environment* is a unique Lexical Environment which is created before any ECMAScript code is executed. The global environment's Environment Record is an object environment record whose binding object is the global object (15.1). The global environment's outer environment reference is `null`. As ECMAScript code is executed, additional properties may be added to the global object and the initial properties may be modified.

Deleted: 3

Deleted: When control is transferred to ECMAScript executable code implementation control is entering an *execution context*.

Deleted: At any point in time, there is at most one execution context on this logical stack that is actually executing code. This is known as an *running* execution context.

Deleted: t

Deleted: and

Deleted: In addition, e

Deleted: Execution Context

Formatted Table

Deleted: ECMAScript

Deleted: PreviousContext

Deleted: within which the associated

Deleted: code is evaluated

Deleted: LexicalEnvironment

Formatted Table

Deleted: ThisBinding

Deleted: The code evaluation state corresponds to the implementation state needed to perform, suspend, and subsequently resume evaluation of the ECMAScript code associated with the execution context. Only one execution context may be actively evaluating ECMAScript code at any point in time. The execution context is active is called the *current execution context*.

Deleted: current

Deleted: current

Deleted: current

Deleted: ECMAScript

Deleted: current

Deleted: ECMAScript

Deleted: of

Deleted: current

Deleted: changes

Deleted: to

Deleted: current

Table 24 —Additional State Components for ECMAScript Code Execution Contexts

Component	Purpose
LexicalEnvironment	Identifies the Lexical Environment used to resolve identifier references made by code within this execution context.
VariableEnvironment	Identifies the Lexical Environment whose environment record holds bindings created by <i>VariableStatements</i> within this execution context.

The LexicalEnvironment and VariableEnvironment components of an execution context are always Lexical Environments. When an execution context is created its LexicalEnvironment and VariableEnvironment components initially have the same value. The value of the VariableEnvironment component never changes while the value of the LexicalEnvironment component may change during execution of code within an execution context.

In most situations only the running execution context (the top of the execution context stack) is directly manipulated by algorithms within this specification. Hence when the terms “LexicalEnvironment”, and “VariableEnvironment” are used without qualification they are in reference to those components of the running execution context.

Deleted: and “ThisBinding”

An execution context is purely a specification mechanism and need not correspond to any particular artefact of an ECMAScript implementation. It is impossible for an ECMAScript program to directly access or observe an execution context.

10.4.1 Identifier Resolution

Deleted: 3

Identifier resolution is the process of determining the binding of an *IdentifierName* using the LexicalEnvironment of the running execution context. During execution of ECMAScript code, Identifier Resolution is performed using the following algorithm:

Deleted: the syntactic production *PrimaryExpression* : *Identifier* is evaluated

1. Let *env* be the running execution context’s LexicalEnvironment.
2. If the syntactic production that is being evaluated is contained in a strict mode code, then let *strict* be **true**, else let *strict* be **false**.
3. Return the result of calling *GetIdentifierReference abstract operation* passing *env*, the String Value of *IdentifierName*, and *strict* as arguments.

Deleted: function

Deleted:

Deleted: v

Deleted: containing the same sequence of characters as

Deleted: *Identifier*

Deleted: 3

The result of evaluating an identifier is always a value of type Reference with its referenced name component equal to the *Identifier* String.

10.4.2 GetThisEnvironment

Deleted: It starts search with the LexicalEnvironment of the current execution context.

Deleted: current

The abstract operation *GetThisEnvironment* finds the lexical environment that currently supplies the binding of the keyword *this*. *GetThisEnvironment* performs the following steps:

1. Let *lex* be the running execution context’s LexicalEnvironment.
2. Repeat
 - a. Let *envRec* be *lex*’s environment record.
 - b. Let *exists* be the result of calling the *HasThisBinding* concrete method of *envRec*.
 - c. If *exists* is **true**, then return *envRec*.
 - d. Let *outer* be the value of *lex*’s outer environment reference.
 - e. Let *lex* be *outer*.

10.4.3 This Resolution

Deleted: 3

Deleted: 4

Deleted: current

The abstract operation *ThisResolution* is the process of determining the binding of the keyword *this* using the LexicalEnvironment of the running execution context. *ThisResolution* performs the following steps:

1. Let *env* be the result of performing the *GetThisEnvironment* abstract operation.
2. Return the result of calling the *GetThisBinding* concrete method of *env*.

10.5 Declaration Binding Instantiation

10.5.1 Top-Level Declaration Instantiation

NOTE When an execution context is established for evaluating non-function code declarations are instantiated in the current VariableEnvironment. Each top-level level variable, constant, or function declared in the code is instantiated.

Top-level Declaration Instantiation for base code is performed as follows:

1. Let *env* be the environment record component of the *running* execution context's VariableEnvironment.
2. If *code* is eval code, then let *configurableBindings* be **true** else let *configurableBindings* be **false**.
3. If *code* is strict code, then let *strict* be **true** else let *strict* be **false**.
4. For each *FunctionDeclaration f* in *code*, in source text order do
 - a. Let *fn* be the Identifier in *FunctionDeclaration f*.
 - b. Let *fo* be the result of performing Instantiate Function Declaration for *f*.
 - c. Let *funcAlreadyDeclared* be the result of calling *env*'s HasBinding concrete method passing *fn* as the argument.
 - d. If *funcAlreadyDeclared* is **false**, then
 - i. Call *env*'s CreateVarBinding concrete method passing *fn* and *configurableBindings* as the arguments.
 - ii. Call *env*'s InitializeBinding concrete method passing *fn*, and **undefined** as the arguments.
 - e. Else if *env* is the environment record component of the global environment then
 - i. Let *go* be the global object.
 - ii. Let *existingProp* be the result of calling the **[[GetOwnProperty]]** internal method of *go* with argument *fn*.
 - iii. If *existingProp* is **undefined** or *existingProp***[[Configurable]]** is **true**, then
 1. Call the **[[DefineOwnProperty]]** internal method of *go*, passing *fn*, Property Descriptor **{[[Value]]: undefined, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: configurableBindings}**, and **true** as arguments.
 - iv. Else if *IsAccessorDescriptor(existingProp)* or *existingProp* does not have attribute values **[[Writable]]: true, [[Enumerable]]: true**, then
 1. Throw a **TypeError** exception.
 - f. Let *status* be the result of calling *env*'s SetMutableBinding concrete method passing *fn*, *fo*, and *strict* as the arguments.
 - g. ReturnIfAbrupt(*status*).
 5. For each *VariableDeclaration* and *VariableDeclarationNoIn d* in *code*, in source text order do
 - a. Let *dn* be the Identifier in *d*.
 - b. Let *varAlreadyDeclared* be the result of calling *env*'s HasBinding concrete method passing *dn* as the argument.
 - c. If *varAlreadyDeclared* is **false**, then
 - i. Let *status* be the result of calling *env*'s CreateMutableBinding concrete method passing *dn* and *configurableBindings* as the arguments.
 - ii. ReturnIfAbrupt(*status*).
 - iii. Call *env*'s InitializeBinding concrete method passing *dn*, and **undefined** as the arguments.
 - iv. Let *status* be the result of calling *env*'s SetMutableBinding concrete method passing *dn*, **undefined**, and *strict* as the arguments.
 - v. ReturnIfAbrupt(*status*).
 - d. else if *env* is the environment record component of the global environment then
 - i. Let *go* be the global object.
 - ii. Let *existingProp* be the result of calling the **[[GetOwnProperty]]** internal method of *go* with argument *dn*.
 - iii. If *existingProp* is **undefined**, then
 1. Call the **[[DefineOwnProperty]]** internal method of *go*, passing *dn*, Property Descriptor **{[[Value]]: undefined, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: configurableBindings}**, and **true** as arguments.

Deleted: 10.4 Establishing an Execution Context¶

Evaluation of global code or code using the eval function (15.1.2.1) establishes and enters a new execution context. Every invocation of an ECMAScript code function (13.2.1) also establishes and enters a new execution context, even if a function is calling itself recursively. Every return exits an execution context. A thrown exception may also exit one or more execution contexts.¶

When control enters an execution context, the execution context's ThisBinding is set to its VariableEnvironment and initial LexicalEnvironment are defined, and declaration binding instantiation (10.5) is performed. The exact manner in which the actions occur depend on the type of code being entered.¶

10.4.1 . Entering Global Code¶

The following steps are performed when control enters the execution context for global code:¶

Initialise the execution context using the global code as described in 10.4.1.1.¶

Perform Declaration Binding Instantiation described in 10.5 using the global code.¶

10.4.1.1 Initial Global Execution Context¶

Deleted: 10.5 . Declaration Binding Instantiation¶

Comment [AWB22]: It may make sense to split eval code out into a separate subsection

Deleted: Every execution context has an associated VariableEnvironment. Variables are

Deleted: Base Code

Deleted: that is base code

Comment [AWB23]: This algorithm needs to be update to use newly defined static semantics

Deleted: running

Deleted: current

Deleted: mode

Deleted: <#>If *code* is function code, then¶

Deleted: instantiating *FunctionDeclaration*

Deleted: as described in Clause 13

Deleted: call

Deleted: Mutable

Deleted: ing

Deleted:

Deleted: Call

Deleted: <#>Let *argumentsAlreadyDeclared* be the result of calling *env*'s HasBinding concrete

Deleted: Call

Comment [AWB 324]: This calls is needed to force strict mode error detection of object

Deleted: Call

Deleted: ing

Deleted: f

10.5.2 Module Declaration Instantiation

10.5.3 Function Declaration Instantiation

Comment [AWB25]: The exact details of declaration instantiation for module code still need to be worked out.

Deleted: Extended Code Top-Level

NOTE When an execution context is established for evaluating function code a new Declarative Environment Record is created and bindings for each formal parameter, and each function level variable, constant, or function declared in the function are instantiated in the environment record. Formal parameters and functions are initialized as part of this process. All other bindings are initialized during execution of the function code.

Function Declaration Instantiation is performed as follows using arguments *func*, *argumentsList*, and *env*. *func* is the function object that for which the execution context is being established. *env* is the declarative environment record in which bindings are to be created.

1. Let *code* be the value of the *[[Code]]* internal property of *func*.
2. Let *strict* be the value of the *[[Strict]]* internal property of *func*.
3. Let *formals* be the value of the *[[FormalParameterList]]* internal property of *func*.
4. Let *parameterNames* be the *BoundNames* of *formals*.
5. For each String *argName* in *parameterNames*, in list order do
 - a. Let *alreadyDeclared* be the result of calling *env*'s *HasBinding* concrete method passing *argName* as the argument.
 - b. **NOTE** Duplicate parameter names can only occur in non-strict Normal functions.
 - c. If *alreadyDeclared* is false, then
 - i. Let *status* be the result of calling *env*'s *CreateMutableBinding* concrete method passing *argName* as the argument.
 - ii. **ReturnIfAbrupt**(*status*).
 - iii. If *strict* is false, then
 1. Call *env*'s *InitializeBinding* concrete method passing *argName*, and *undefined* as the arguments.
6. Let *declarations* be the LexicalDeclarations of *code*.
7. If *strict* is true, then
 - a. Let *ao* be the result of *CreateStrictArgumentsObject* with argument *argumentsList*.
 - b. Let *formalStatus* be the result of performing *BindingInitialisation* for *formals* with *ao* and *env* as arguments.
8. Else,
 - a. Let *names* be *BoundNames* of *formals*.
 - b. **NOTE** Because F is a non strict function it is not extended code. Hence *formals* does not contain the names of any destructuring *BindingProperties*, rest parameters, or parameters with default value initialisers.
 - c. Let *ao* be the result of performing the abstract operation *CreateMappedArgumentsObject* with arguments *func*, *names*, *env*, and *argumentsList*.
 - d. Let *formalStatus* be the result of performing *BindingInitialisation* for *formals* with *ao* and *undefined* as arguments.
9. **NOTE** *BindingInitialisation* for *formals* is performed prior to instantiating any non-parameter declarations in order to ensure that any such local declarations are not visible to any parameter *Initialisation* code that may be evaluated.
10. **ReturnIfAbrupt**(*formalStatus*).
11. For each element *d* in *declarations* do
 - a. For each element *dn* of the *BoundNames* of *d* do
 - i. Let *alreadyDeclared* be the result of calling *env*'s *HasBinding* concrete method passing *dn* as the argument.
 - ii. If *alreadyDeclared* is false, then
 1. If *IsConstantDeclaration* of *d* is true, then
 - a. Call *env*'s *CreateImmutableBinding* concrete method passing *dn* as the argument.
 2. Else,

Deleted: be

Deleted: *FormalParameterList*

Deleted: *FormalParameterList*

Deleted: *code*

Deleted: *Call*

Comment [AWB926]: TODO see if we can prove that this will never be an abnormal completion.

Comment [AWB27]: In non-extended code this will only contain function declarations

Deleted: .

Deleted: Perform

Deleted: Initialization

Comment [AWB628]: TODO This is no longer true a needs is o be taken into account

Deleted: Perform

Deleted: Initialization

Deleted: initialization

Deleted: to

Deleted: initialization

Comment [AWB29]: Only function declarations may multiply declared

Deleted: a *ConstDeclaration*

- a. Call *env*'s `CreateMutableBinding` concrete method passing *dn* and `false` as the arguments.
12. Let *argumentsAlreadyDeclared* be the result of calling *env*'s `HasBinding` concrete method passing `"arguments"` as the argument.
13. NOTE If *argumentsAlreadyDeclared* is `true` then the value of *ao* is not directly observable to ECMAScript code and need not actually exist. In that case, its use in the above steps is strictly as a device for specifying formal parameter initialisation semantics.
14. If *argumentsAlreadyDeclared* is `false`, then
- a. If *strict* is `true`, then
 - i. Call *env*'s `CreateImmutableBinding` concrete method passing the String `"arguments"` as the argument.
 - b. Else,
 - i. Call *env*'s `CreateMutableBinding` concrete method passing the String `"arguments"` as the argument.
 - c. Call *env*'s `InitializeBinding` concrete method passing `"arguments"` and *ao* as arguments.
15. Let *varNames* be the `VarDeclaredNames` of *code*.
16. For each String *varName* in *varNames*, in list order do
- a. Let *alreadyDeclared* be the result of calling *env*'s `HasBinding` concrete method passing *varName* as the argument.
 - b. NOTE A `VarDeclaredNames` is only instantiated and initialised here if it is not also the name of a formal parameter or a `FunctionDeclarations`. Such duplicate declarations may only occur in non-extended code.
 - c. If *alreadyDeclared* is `false`, then
 - i. Call *env*'s `CreateMutableBinding` concrete method passing *varName* as the argument.
 - ii. Call *env*'s `InitializeBinding` concrete method passing *varName*, and `undefined` as the arguments.
17. Let *initializedFunctions* be an emptyList.
18. For each `FunctionDeclaration` *f* in *declarations*, in reverse list order do
- a. NOTE If there are multiple `FunctionDeclarations` for the same name, the last declaration is used. Multiple `FunctionDeclarations` for the same name is only valid in non-extended code.
 - b. Let *fn* be the sole element of the `BoundNames` of *f*.
 - c. If *fn* is not an element of *initializedFunctions*, then
 - i. Append *fn* to *initializedFunctions*.
 - ii. Let *fo* be the result of performing `Instantiate Function Declaration` for *f*.
 - iii. Call *env*'s `InitializeBinding` concrete method passing *fn*, and *fo* as the arguments.
19. Return `NormalCompletion(empty)`.

10.5.4 Block Declaration Instantiation

NOTE When a `Block` or `CaseBlock` production is evaluated a new Declarative Environment Record is created and bindings for each block scoped variable, constant, or function declared in the block are instantiated in the environment record.

Block Declaration Instantiation is performed as follows using arguments *code* and *env*. *code* is the grammar production corresponding to the body of the block. *env* is the declarative environment record in which bindings are to be.

1. Let *declarations* be the `LexicalDeclarations` of *code*.
2. For each element *d* in *declarations* do
 - a. For each element *dn* of the `BoundNames` of *d* do
 - i. If `IsConstantDeclaration` of *d* is `true`, then
 1. Call *env*'s `CreateImmutableBinding` concrete method passing *dn* as the argument.
 - ii. Else,
 1. Call *env*'s `CreateMutableBinding` concrete method passing *dn* and `false` as the arguments.
3. For each `FunctionDeclaration` *f* in *declarations*, in list order do
 - a. Let *fn* be the sole element of the `BoundNames` of *f*.
 - b. Let *fo* be the result of performing `Instantiate Function Declaration` for *f*.
 - c. Call *env*'s `InitializeBinding` concrete method passing *fn*, and *fo* as the arguments.

Deleted: initialization

Comment [AWB730]: TODO: don't create arguments binding for arrow functions (and perhaps for concise methods)

Deleted: <#>Let `hasArgumentsObject` be the Boolean negation of `argumentsAlreadyDeclared`.

Deleted: *fn*

Deleted: instantiating

Deleted: `FunctionDeclaration`

Deleted: as described in Clause 13

Deleted: `hasArgumentsObject`

Comment [AWB731]: Jan 19 meeting note
Current tentative decision is to support let, const, and local functions in nonstrict ES5 in the same way as in strict ES6. Fallback to either specifying limited cases or doing the ES5 nonstrict status quo (i.e. syntax error + Clause 16) if experiments show this to not be viable. We won't resolve this discussion without running some experiments.

Formatted: Font: 9 pt

Formatted: Font: 9 pt

Deleted: contained in extended code

Deleted: <#>Assert: `parameterNames` has no duplicate entries.¶

Deleted: a `ConstDeclaration`

Deleted: `FunctionDeclaration`

Deleted: instantiating `FunctionDeclaration`

Deleted: as described in Clause 13

Comment [AWB 332]: Why shouldn't function declarations with in blocks be constant bindings? For consistency with function scope bindings? There are already other inconsistencies such as duplicate function declarations being disallowed.

Deleted: <#>Call *env*'s `CreateMutableBinding` concrete method passing *fn* and `configurableBindings` as the arguments.¶

10.6 Arguments Object

When function code is evaluated, an arguments object is created unless (as specified in 10.5) the identifier arguments occurs as an *Identifier* in the function's *FormalParameterList* or occurs as the *BindingIdentifier* of a Declaration contained in the function code.

The abstract operation CreateStrictArgumentsObject called with argument list args performs the following steps:

1. Let len be the number of elements in args.
2. Let obj be the result of the abstract operation InstantiateArgumentsObject with argument len.
3. Let idx = len - 1.
4. Repeat while idx >= 0.
 - a. Let val be the element of args at 0-origin list position idx.
 - b. Call the [[DefineOwnProperty]] internal method on obj passing ToString(idx), the PropertyDescriptor {[[Value]]: val, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}, and false as arguments.
 - c. Let idx = idx - 1.
5. Let thrower be the [[ThrowTypeError]] function Object (13.6.3).
6. Call the [[DefineOwnProperty]] internal method of obj with arguments "caller", PropertyDescriptor {[[Get]]: thrower, [[Set]]: thrower, [[Enumerable]]: false, [[Configurable]]: false}, and false.
7. Call the [[DefineOwnProperty]] internal method of obj with arguments "callee", PropertyDescriptor {[[Get]]: thrower, [[Set]]: thrower, [[Enumerable]]: false, [[Configurable]]: false}, and false.
8. Return obj.

The abstract operation CreateMappedArgumentsObject called with object func, List names, environment record env, and argument list args performs the following steps:

1. Let len be the number of elements in args.
2. Let obj be the result of the abstract operation InstantiateArgumentsObject with argument len.
3. Let map be the result of creating a new ECMAScript object.
4. Set all the internal methods of map as specified in 8.12.
5. Let mappedNames be an empty List.
6. Let idx = len - 1.
7. Repeat while idx >= 0.
 - a. Let val be the element of args at 0-origin list position idx.
 - b. Call the [[DefineOwnProperty]] internal method on obj passing ToString(idx), the PropertyDescriptor {[[Value]]: val, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}, and false as arguments.
 - c. If idx is less than the number of elements in names, then
 - i. Let name be the element of names at 0-origin list position idx.
 - ii. If name is not an element of mappedNames, then
 1. Add name as an element of the list mappedNames.
 2. Let g be the result of calling the MakeArgGetter abstract operation with arguments name and env.
 3. Let p be the result of calling the MakeArgSetter abstract operation with arguments name and env.
 4. Call the [[DefineOwnProperty]] internal method of map passing ToString(idx), the PropertyDescriptor {[[Set]]: p, [[Get]]: g, [[Configurable]]: true}, and false as arguments.
 - d. Let idx = idx - 1.
 - d. Let idx = idx - 1.
8. If mappedNames is not empty, then
 - a. Set the [[ParameterMap]] internal property of obj to map.
 - b. Set the [[Get]], [[GetOwnProperty]], [[DefineOwnProperty]], and [[Delete]] internal methods of obj to the definitions provided below.
9. Call the [[DefineOwnProperty]] internal method on obj passing "callee", the PropertyDescriptor {[[Value]]: func, [[Writable]]: true, [[Enumerable]]: false, [[Configurable]]: true}, and false as arguments.
10. Return obj.

The abstract operation InstantiateArgumentsObject called with an argument len performs the following steps:

Deleted: <#>For each *LetDeclaration* and *ConstDeclaration* d in *code* do
<#>For each element *dn* of the *BoundNames* of *d* do
<#>If *d* is a *LetDeclaration*, then
<#>Call *env*'s *CreateMutableBinding* concrete method passing *dn* and *false* as the arguments.
<#>Else,
<#>Call *env*'s *CreateImmutableBinding* concrete method passing *dn* as the argument.

Deleted: control enters an execution context for

Comment [AWB 233]: Additional modification to this text will probably be need to account for the new declaration statements.

Deleted: *VariableDeclaration* or

Deleted: *Function*

Deleted: ion

Deleted: p

Deleted: d

Deleted: 2

Deleted: ion

Deleted: p

Deleted: d

Deleted: p

Deleted: d

1. Let *obj* be the result of creating a new ECMAScript object.
2. Set all the internal methods of *obj* as specified in 8.12.
3. Add the `[[NativeBrand]]` internal property to *obj* with value `NativeArguments`.
4. Set the `[[Prototype]]` internal property of *obj* to the standard built-in `Object` prototype object (15.2.4).
5. Call the `[[DefineOwnProperty]]` internal method on *obj* passing `"length"`, the Property Descriptor `{[[Value]]: len, [[Writable]]: true, [[Enumerable]]: false, [[Configurable]]: true}`, and `false` as arguments.
6. Return *obj*

The abstract operation `MakeArgGetter` called with String *name* and environment record *env* creates a function object that when executed returns the value bound for *name* in *env*. It performs the following steps:

1. Let *bodyText* be the result of concatenating the Strings `"return "`, *name*, and `";"`.
2. Let *body* be the result of parsing *bodyText* using `FunctionBody` as the goal symbol.
3. Let *parameters* be a `FormalParameterList` : [empty] production.
4. Return the result of creating a function object as described in 13.6 using *parameters* as `FormalParameterList`, *body* for `FunctionBody`, *env* as `Scope`, and `true` for `Strict`.

The abstract operation `MakeArgSetter` called with String *name* and environment record *env* creates a function object that when executed sets the value bound for *name* in *env*. It performs the following steps:

1. Let *paramText* be the String *name* concatenated with the String `"_arg"`.
2. Let *parameters* be the result of parsing *paramText* using `FormalParameterList` as the goal symbol.
3. Let *bodyText* be the String `"<name> = <param>;"` with `<name>` replaced by the value of *name* and `<param>` replaced by the value of *paramText*.
4. Let *body* be the result of parsing *bodyText* using `FunctionBody` as the goal symbol.
5. Return the result of creating a function object as described in 13.6 using *parameters* as `FormalParameterList`, *body* for `FunctionBody`, *env* as `Scope`, and `true` for `Strict`.

The `[[Get]]` internal method of an arguments object for a non-strict mode function with formal parameters when called with a property name *P* performs the following steps:

1. Let *map* be the value of the `[[ParameterMap]]` internal property of the arguments object.
2. Let *isMapped* be the result of calling the `[[GetOwnProperty]]` internal method of *map* passing *P* as the argument.
3. If the value of *isMapped* is `undefined`, then
 - a. Let *v* be the result of calling the default `[[Get]]` internal method (8.12.3) on the arguments object passing *P* as the argument.
 - b. If *P* is `"caller"` and *v* is a strict mode Function object, throw a `TypeError` exception.
 - c. Return *v*.
4. Else, *map* contains a formal parameter mapping for *P* so,
 - a. Return the result of calling the `[[Get]]` internal method of *map* passing *P* as the argument.

The `[[GetOwnProperty]]` internal method of an arguments object for a non-strict mode function with formal parameters when called with a property name *P* performs the following steps:

1. Let *desc* be the result of calling the default `[[GetOwnProperty]]` internal method (8.12.1) on the arguments object passing *P* as the argument.
2. If *desc* is `undefined` then return *desc*.
3. Let *map* be the value of the `[[ParameterMap]]` internal property of the arguments object.
4. Let *isMapped* be the result of calling the `[[GetOwnProperty]]` internal method of *map* passing *P* as the argument.
5. If the value of *isMapped* is not `undefined`, then
 - a. Set *desc.[[Value]]* to the result of calling the `[[Get]]` internal method of *map* passing *P* as the argument.
6. Return *desc*.

The `[[DefineOwnProperty]]` internal method of an arguments object for a non-strict mode function with formal parameters when called with a property name *P*, Property Descriptor *Desc*, and Boolean flag *Throw* performs the following steps:

1. Let *map* be the value of the `[[ParameterMap]]` internal property of the arguments object.

Deleted: Set
Deleted: Class
Deleted: IsArguments
Deleted: of
Deleted: to "Arguments"
Deleted: <code><#>Let Object be the standard built-in Object constructor (15.2.2).¶</code>
Deleted: <code><#>Let indx = len - 1.¶</code>
<code><#>Repeat while <i>indx</i> >= 0, ¶</code>
<code><#>Let <i>val</i> be the element of <i>args</i> at 0-originated list position <i>indx</i>.¶</code>
<code><#>Call the <code>[[DefineOwnProperty]]</code> internal method on <i>obj</i> passing <code>Tostring(indx)</code>, the property descriptor <code>{[[Value]]: <i>val</i>, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}</code>, and <code>false</code> as arguments.¶</code>
<code><#>If <i>indx</i> is less than the number of elements in <i>names</i>, then¶</code>
<code><#>Let <i>name</i> be the element of <i>names</i> at 0-originated list position <i>indx</i>.¶</code>
<code><#>If <i>strict</i> is <code>false</code> and <i>name</i> is not an element of <i>mappedNames</i>, then¶</code>
<code><#>Add <i>name</i> as an element of the list <i>mappedNames</i>.¶</code>
<code><#>Let <i>g</i> be the result of calling the <code>MakeArgGet</code> abstract operation with arguments <i>name</i> and <i>env</i>.¶</code>
<code><#>Let <i>p</i> be the result of calling the <code>MakeArgSet</code> abstract operation with arguments <i>name</i> and <i>env</i>.¶</code>
<code><#>Call the <code>[[DefineOwnProperty]]</code> internal method of <i>map</i> passing <code>Tostring(indx)</code>, the Property Descriptor <code>{[[Set]]: <i>p</i>, [[Get]]: <i>g</i>, [[Configurable]]: true, [[Enumerable]]: true}</code>, and <code>false</code> as arguments.¶</code>
<code><#>Let <i>indx</i> = <i>indx</i> - 1¶</code>
<code><#>If <i>mappedNames</i> is not empty, then¶</code>
<code><#>Set the <code>[[ParameterMap]]</code> internal property of <i>obj</i> to <i>map</i>.¶</code>
<code><#>Set the <code>[[Get]], [[GetOwnProperty]], [[DefineOwnProperty]],</code> and <code>[[Delete]]</code> internal methods of <i>obj</i> to the definitions provided below.¶</code>
<code><#>If <i>strict</i> is <code>false</code>, then¶</code>
<code><#>Call the <code>[[DefineOwnProperty]]</code> internal method on <i>obj</i> passing <code>"callee"</code>, the property descriptor <code>{[[Value]]: <i>func</i>, [[Writable]]: true, [[Enumerable]]: false, [[Configurable]]: true}</code>, and <code>false</code> as arguments.¶</code>
<code><#>Else, <i>strict</i> is <code>true</code> so¶</code>
<code><#>Let <i>thrower</i> be the <code>[[ThrowTypeError]]</code> function Object (13.2.3).¶</code>
<code><#>Call the <code>[[DefineOwnProperty]]</code> internal method of <i>obj</i> with arguments <code>"callee"</code>, PropertyDescriptor <code>{[[Get]]: <i>thrower</i>, [[Set]]: <i>thrower</i>, [[Enumerable]]: false, [[Configurable]]: false}</code>, and <code>false</code>.¶</code>
<code><#>Call the <code>[[DefineOwnProperty]]</code> internal method of <i>obj</i> with arguments <code>"callee"</code>, PropertyDescriptor <code>{[[Get]]: <i>thrower</i>, [[Set]]: <i>thrower</i>, [[Enumerable]]: false, [[Configurable]]: false}</code>, and <code>false</code>.¶</code>
Deleted: 2
Deleted: no <code>FormalParameterList</code>
Deleted: 2
Deleted: a List containing the single String
Deleted: <i>param</i>

2. Let *isMapped* be the result of calling the **[[GetOwnProperty]]** internal method of *map* passing *P* as the argument.
3. Let *allowed* be the result of calling the default **[[DefineOwnProperty]]** internal method (8.12.9) on the arguments object passing *P*, *Desc*, and **false** as the arguments.
4. If *allowed* is **false**, then
 - a. If *Throw* is **true** then throw a **TypeError** exception, otherwise return **false**.
5. If the value of *isMapped* is not **undefined**, then
 - a. If *IsAccessorDescriptor*(*Desc*) is **true**, then
 - i. Call the **[[Delete]]** internal method of *map* passing *P*, and **false** as the arguments.
 - b. Else
 - i. If *Desc*.**[[Value]]** is present, then
 1. Call the **[[Put]]** internal method of *map* passing *P*, *Desc*.**[[Value]]**, and *Throw* as the arguments.
 - ii. If *Desc*.**[[Writable]]** is present and its value is **false**, then
 1. Call the **[[Delete]]** internal method of *map* passing *P* and **false** as arguments.
6. Return **true**.

The **[[Delete]]** internal method of an arguments object for a non-strict mode function with formal parameters when called with a property name *P* and Boolean flag *Throw* performs the following steps:

1. Let *map* be the value of the **[[ParameterMap]]** internal property of the arguments object.
2. Let *isMapped* be the result of calling the **[[GetOwnProperty]]** internal method of *map* passing *P* as the argument.
3. Let *result* be the result of calling the default **[[Delete]]** internal method (8.12.7) on the arguments object passing *P* and *Throw* as the arguments.
4. If *result* is **true** and the value of *isMapped* is not **undefined**, then
 - a. Call the **[[Delete]]** internal method of *map* passing *P*, and **false** as the arguments.
5. Return *result*.

NOTE 1 For non-strict mode functions the array index (defined in 15.4) named data properties of an arguments object whose numeric name values are less than the number of formal parameters of the corresponding function object initially share their values with the corresponding argument bindings in the function's execution context. This means that changing the property changes the corresponding value of the argument binding and vice-versa. This correspondence is broken if such a property is deleted and then redefined or if the property is changed into an accessor property. For strict mode functions, the values of the arguments object's properties are simply a copy of the arguments passed to the function and there is no dynamic linkage between the property values and the formal parameter values.

NOTE 2 The ParameterMap object and its property values are used as a device for specifying the arguments object correspondence to argument bindings. The ParameterMap object and the objects that are the values of its properties are not directly accessible from ECMAScript code. An ECMAScript implementation does not need to actually create or use such objects to implement the specified semantics.

NOTE 3 Arguments objects for strict mode functions define non-configurable accessor properties named "**caller**" and "**callee**" which throw a **TypeError** exception on access. The "**callee**" property has a more specific meaning for non-strict mode functions and a "**caller**" property has historically been provided as an implementation-defined extension by some ECMAScript implementations. The strict mode definition of these properties exists to ensure that neither of them is defined in any other manner by conforming ECMAScript implementations.

11 Expressions

11.1 Primary Expressions

Syntax

PrimaryExpression :

this
Identifier
Literal
ArrayInitialiser
ObjectLiteral
FunctionExpression
ClassExpression
GeneratorExpression
GeneratorComprehension
RegularExpressionLiteral
TemplateLiteral
CoverParenthesizedExpressionAndArrowParameters

Deleted: *ArrayLiteral*

Comment [AWB834]: Max-min classes have not yet been formally approved for ES6, but they appear to be close to it.

Deleted: [*Lexical goal InputElementRegExp*]

Deleted: *Quasi*

Deleted: *(Expression)*

CoverParenthesizedExpressionAndArrowParameters:

(Expression)
()
(... Identifier)
(Expression , ... Identifier)

Supplemental Syntax

When processing the production *PrimaryExpression : CoverParenthesizedExpressionAndArrowParameters* the following grammar is used to refine the interpretation of *CoverParenthesizedExpressionAndArrowParameters*.

ParenthesizedExpression :
 (FormalParameterList)

Static Semantics

Static Semantics: Early Errors

PrimaryExpression : CoverParenthesizedExpressionAndArrowParameterList

- It is a Syntax Error if the lexical token sequence matched by *CoverParenthesizedExpressionAndArrowParameterList* cannot be parsed with no tokens left over using *ParenthesizedExpression* as the goal symbol.
- All Early Errors rules for *ParenthesizedExpression* and its derived productions also apply to the *CoveredParenthesizedExpression* of *CoverParenthesizedExpressionAndArrowParameterList*.

Static Semantics: CoveredParenthesizedExpression

CoverParenthesizedExpressionAndArrowParameters : (Expression)

1. Return the result of parsing the lexical token stream matched by *CoverParenthesizedExpressionAndArrowParameters* using *ParenthesizedExpression* as the goal symbol.

Static Semantics: IsValidSimpleAssignmentTarget

PrimaryExpression :

- this
- Literal
- ArrayInitialiser
- ObjectLiteral
- FunctionExpression
- ClassExpression
- GeneratorExpression
- GeneratorComprehension
- RegularExpressionLiteral
- TemplateLiteral

1. Return false.

PrimaryExpression : Identifier

2. If this PrimaryExpression is contained in strict code and StringValue of Identifier is "eval" or "arguments", then return false.

3. Return true.

PrimaryExpression : CoverParenthesizedExpressionAndArrowParameterList

1. Let expr be CoveredParenthesizedExpression of CoverParenthesizedExpressionAndArrowParameterList.
 2. Return IsValidSimpleAssignmentTarget of expr.

11.1.1 The this Keyword

Runtime Semantics: Evaluation

PrimaryExpression : this

1. Let env be the result of performing the GetThisEnvironment abstract operation.
 2. Return the result of calling the GetThisBinding concrete method of env.

11.1.2 Identifier Reference

Runtime Semantics: Evaluation

PrimaryExpression : Identifier

1. Let ref be the result of performing Identifier Resolution as specified in 10.3.1 using the IdentifierName corresponding to Identifier.
 2. Return ref.

NOTE: The result of evaluating an Identifier is always a value of type Reference.

11.1.3 Literals

Syntax

Literal :

- NullLiteral
- ValueLiteral

ValueLiteral :

- BooleanLiteral
- NumericLiteral
- StringLiteral

Deleted: <#> The this keyword evaluates to Return the value of the ThisBinding of the current execution context.¶

Comment [AWB835]: It may make sense to define some of the static semantic rules related static name resolution

Deleted: An Identifier is evaluated by performing Identifier Resolution as specified in 10.3.1 using the IdentifierName corresponding to Identifier.

Formatted: Font: 9 pt

Deleted: Reference

Deleted:
RegularExpressionLiteral

Runtime Semantics

Runtime Semantics: Evaluation

Literal : *NullLiteral*

1. Return **null**.

ValueLiteral : *BooleanLiteral*

1. Return **false** if *BooleanLiteral* is the token *BooleanLiteral* :: **false**
2. Return **true** if *BooleanLiteral* is the token *BooleanLiteral* :: **true**

ValueLiteral : *NumericLiteral*

1. Return the number whose value is *MV* of *NumericLiteral* as defined in 7.8.3.

ValueLiteral : *StringLiteral*

1. Return the string whose *elements* are the *SV* of *StringLiteral* as defined in 7.8.4.

11.1.4 Array Initialiser

Syntax

ArrayInitialiser :

ArrayLiteral
ArrayComprehension

11.1.4.1 Array Literal

NOTE An *ArrayLiteral* is an expression describing the initialisation of an Array object, using a list, of zero or more expressions, each of which represents an array element, enclosed in square brackets. The elements need not be literals; they are evaluated each time the array initialiser is evaluated.

Array elements may be elided at the beginning, middle or end of the element list. Whenever a comma in the element list is not preceded by an *AssignmentExpression* (i.e., a comma at the beginning or after another comma), the missing array element contributes to the length of the Array and increases the index of subsequent elements. Elided array elements are not defined. If an element is elided at the end of an array, that element does not contribute to the length of the Array.

Syntax

ArrayLiteral :

[*Elision*_{opt}]
[*ElementList*]
[*ElementList* , *Elision*_{opt}]

ElementList :

*Elision*_{opt} *AssignmentExpression*
*Elision*_{opt} *SpreadElement*
ElementList , *Elision*_{opt} *AssignmentExpression*
ElementList , *Elision*_{opt} *SpreadElement*

Elision :

'
Elision ,

Deleted: character

Deleted: A *Literal* is evaluated as described 7.8.

Deleted: *SealedArrayInitialiser* :
ArrayInitialiser
ArrayInitialiser

Deleted: *array initialiser*

Deleted: written in a form of a literal. It is

Deleted: ,

Deleted: ... *AssignmentExpression*

Deleted: ... *AssignmentExpression*

SpreadElement :
... AssignmentExpression

Static Semantics

Static Semantics: Elision Width

Elision : ,

1. Return the numeric value 1.

Elision : Elision ,

1. Let preceding be the Elision Width of Elision.
2. Return preceding+1.

Runtime Semantics

Runtime Semantics: Array Accumulation

With parameters array and nextIndex.

ElementList : Elision_{opt} AssignmentExpression

1. Let padding be the Elision Width of Elision; if Elision is not present, use the numeric value zero.
2. Let initResult be the result of evaluating AssignmentExpression.
3. Let initialValue be GetValue(initResult).
4. ReturnIfAbrupt(initialValue).
5. Call the [[DefineOwnProperty]] internal method of array with arguments
`ToString(ToUint32(nextIndex+padding)), the Property Descriptor { [[Value]]: initialValue, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true }, and false.`
6. Return nextIndex+padding+1.

ElementList : Elision_{opt} SpreadElement

1. Let padding be the Elision Width of Elision; if Elision is not present, use the numeric value zero.
2. Return the result of performing Array Accumulation for SpreadElement with arguments array and nextIndex+padding.

ElementList : ElementList , Elision_{opt} AssignmentExpression

1. Let postIndex be the result of performing Array Accumulation for ElementList with arguments array and nextIndex.
2. ReturnIfAbrupt(postIndex).
3. Let padding be the Elision Width of Elision; if Elision is not present, use the numeric value zero.
4. Let initResult be the result of evaluating AssignmentExpression.
5. Let initialValue be GetValue(initResult).
6. ReturnIfAbrupt(initialValue).
7. Call the [[DefineOwnProperty]] internal method of array with arguments
`ToString(ToUint32((postIndex+padding)) and the Property Descriptor { [[Value]]: initialValue, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true }, and false.`
8. Return postIndex+padding+1.

ElementList : ElementList , Elision_{opt} SpreadElement

1. Let postIndex be the result of performing Array Accumulation for ElementList with arguments array and nextIndex.
2. ReturnIfAbrupt(postIndex).
3. Let padding be the Elision Width of Elision; if Elision is not present, use the numeric value zero.

Deleted: ArrayComprehension : Expression ComprehensionForList Expression ComprehensionForList if (Expression) ComprehensionForList : ComprehensionFor ComprehensionForList ComprehensionFor ComprehensionFor : for (LeftHandSideExpression of Expression)

Deleted: 11.1.4.1

Deleted: Static Semantics: Early Errors
Early Errors

The static semantics of the production
SpreadElementElementList : Elision_{opt} ... AssignmentExpression are:
 ↫ It is a Syntax Error if the source code parsed with this production is not extended code.

Deleted: ElementList : ElementList , Elision_{opt} ... AssignmentExpression
 ↫ It is a Syntax Error if the source code parsed with this production is not extended code.

Deleted: Elision : [empty]
 ↫ Return the numeric value 0.

Deleted: 11.1.4.2

Deleted: opt

Deleted: If initialValue is an abrupt completion, return initialValue

Deleted: opt

Deleted: If postIndex is an abrupt completion, return postIndex

Deleted: opt

Deleted: If initialValue is an abrupt completion, return initialValue

Deleted: If postIndex is an abrupt completion, return postIndex

Deleted: Let pad be the result of evaluating Elision_{opt}; if no present, use the numeric value zero.

4. Return the result of performing Array Accumulation for *SpreadElement* with arguments *array* and *postIndex+padding*.

SpreadElement : ... *AssignmentExpression*

1. Let *spreadRef* be the result of evaluating *AssignmentExpression*.
2. Let *spreadValue* be *GetValue(spreadRef)*.
3. Let *spreadObj* be *ToObject(spreadValue)*.
4. ReturnIfAbrupt(*spreadObj*).
5. Let *lenVal* be the result of calling the **[[Get]]** internal method of *spreadObj* with argument **"length"**.
6. Let *spreadLen* be *ToInt32(lenVal)*.
7. ReturnIfAbrupt(*spreadLen*).
8. Let *n*=0;
9. Repeat, while *n* < *spreadLen*
 - a. Let *exists* be the result of calling the **[[HasProperty]]** internal method of *spreadObj* with *ToString(n)*.
 - b. If *exists* is true then,
 - i. Let *v* be the result of calling the **[[Get]]** internal method of *spreadObj* passing *ToString(n)* as the argument.
 - ii. ReturnIfAbrupt(*v*).
 - iii. Call the **[[DefineOwnProperty]]** internal method of *array* with arguments *ToString(ToInt32(nextIndex))*, **Property Descriptor** **{[[Value]]: *v*, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}**, and false.
 - c. Let *n* = *n*+1.
 - d. Let *nextIndex* = *nextIndex* +1.
10. Return *nextIndex*.

NOTE **[[DefineOwnProperty]]** is used to ensure that own properties are defined for the array even if the standard built-in *Array* prototype object has been modified in a manner that would preclude the creation of new own properties using **[[Put]]**.

Runtime Semantics: Evaluation

ArrayLiteral : [*Elision_{opt}*]

1. Let *array* be the result of the abstract operation *ArrayCreate* (15.4) with argument 0.
2. Let *pad* be the *Elision Width of Elision*; if *Elision* is not present, use the numeric value zero.
3. Call the **[[Put]]** internal method of *array* with arguments "length", *pad*, and false.
4. Return *array*.

ArrayLiteral : [*ElementList*]

1. Let *array* be the result of the abstract operation *ArrayCreate* (15.4) with argument 0.
2. Let *len* be result of performing Array Accumulation for *ElementList* with arguments *array* and 0.
3. ReturnIfAbrupt(*len*).
4. Call the **[[Put]]** internal method of *array* with arguments "length", *len*, and false.
5. Return *array*.

ArrayLiteral : [*ElementList* , *Elision_{opt}*]

1. Let *array* be the result of the abstract operation *ArrayCreate* (15.4) with argument 0.
2. Let *len* be result of performing Array Accumulation for *ElementList* with arguments *array* and 0.
3. ReturnIfAbrupt(*len*).
4. Let *padding* be the *Elision Width of Elision*; if *Elision* is not present, use the numeric value zero.
5. Call the **[[Put]]** internal method of *array* with arguments "length", *ToInt32(padding+len)*, and false.
6. Return *array*.

Comment [AW36]: Note that the value the spread operator is applied to is coerced to an Object.

Deleted: If *spreadObj* is an abrupt completion, return *spreadObj*

Comment [AW37]: Note that indices wrap. For example consider:

[..., ..., { 4294967293: "x", length: Math.pow(2,32)-2}]

Deleted: The production

Deleted: is evaluated as follows:

Deleted: ion

Deleted: the result of creating a new object as in the expression **new Array()** where **Array** the standard built-in constructor with that name

Deleted: result of evaluating

Deleted: opt

Deleted: ; if not present, use the numeric value zero

Deleted: The production

Deleted: is evaluated as follows:

Deleted: ion

Deleted: the result of creating a new object as in the expression **new Array()** where **Array** the standard built-in constructor with that name

Deleted: Return the

Deleted: evaluating

Deleted: If *len* is an abrupt completion, return *len*

Deleted: The production

Deleted: is evaluated as follows:

Deleted: ion

Deleted: the result of creating a new object as in the expression **new Array()** where **Array** the standard built-in constructor with that name

Deleted: <#>Let *array* be the result of evaluating *ElementList*.¶

Deleted: If *len* is an abrupt completion, return *len*

Deleted: Let *padding* be the *Elision Width of result* evaluating *Elision_{opt}*; if not present, use the numeric value zero.

Deleted: <#>Let *len* be the result of calling the **[[Get]]** internal method of *array* with argument "length".¶

11.1.4.2 Array Comprehension

Syntax

ArrayComprehension :

[AssignmentExpression ComprehensionForList]
 [AssignmentExpression ComprehensionForList if Expression]

ComprehensionForList :

ComprehensionFor
 ComprehensionForList ComprehensionFor

ComprehensionFor :

for ForBinding of Expression |

ForBinding :

BindingIdentifier
 BindingPattern ▾

Runtime Semantics

Runtime Semantics: Binding Initialisation

With arguments value and environment.

NOTE undefined is passed for environment to indicate that a PutValue operation should be used to assign the initialisation value. This is the case for var statements formal parameter lists of non-strict functions. In those cases a lexical binding is hosted and preinitialized prior to evaluation of its initializer.

ForBinding : BindingPattern

1. Let obj be ToObject(value).
2. ReturnIfAbrupt(obj).
3. Return the result of performing Binding Initialisation for BindingPattern passing obj and environment as the arguments.

Runtime Semantics: Evaluation

ArrayComprehension : [ElementList]

1. Let array be the result of the abstract operation ArrayCreate (15.4) with argument 0.
2. Let len be result of performing Array Accumulation for ElementList with arguments array and 0.
3. ReturnIfAbrupt(len).
4. Call the [[Put]] internal method of array with arguments "length", len, and false.
5. Return array.

11.1.5 Object Initialiser

NOTE An object initialiser is an expression describing the initialisation of an Object, written in a form resembling a literal. It is a list of zero or more pairs of property names and associated values, enclosed in curly braces. The values need not be literals; they are evaluated each time the object initialiser is evaluated.

Syntax

ObjectLiteral :

{ }
 { PropertyNameDefinitionList }
 { PropertyNameDefinitionList , }

Comment [AWB838]: AssignmentExpression??

Deleted:

Deleted: (

Deleted:)

Comment [AWB839]: AssignmentExpression??

Deleted: (

Deleted: LeftHandSideExpression

Deleted:)

Deleted: Static Semantics¶

Static Semantics: Bound Names¶

ForBinding : BindingIdentifier ¶

<#>Return the Bound Names of BindingIdentifier ¶

ForBinding : BindingPattern ¶

<#>Return the Bound Names of BindingPattern ¶

Deleted: Runtime Semantics: Binding Initialisation

With arguments value and environment. ¶

NOTE undefined is passed for environment to indicate that a PutValue operation should be used to assign the initialisation value. This is the case for var statements formal parameter lists of non-strict functions. In those cases a lexical binding is hosted and preinitialized prior to evaluation of its initializer. ¶

ForBinding : BindingIdentifier ¶

<#>Perform Binding Initialisation for BindingIdentifier passing value and env as the arguments. ¶

ForBinding: BindingPattern ¶

<#>Perform Binding Initialisation for BindingPattern passing value and env as the arguments. ¶

Deleted: Literal

Deleted: ion

Deleted: If len is an abrupt completion, return len

Deleted: The production ElementList : Elision_{opt} AssignmentExpression is evaluated as follows: ¶

<#>Let array be the result of creating a new object as if by the expression new Array() where Array is the standard built-in constructor with that name. ¶

<#>Let firstIndex be the result of evaluating Elision; if not present, use the numeric value zero. ¶

<#>Let initResult be the result of evaluating AssignmentExpression. ¶

<#>Let initValue be GetValue(initResult). ¶

<#>Call the [[DefineOwnProperty]] internal method of array with arguments Tostring(firstIndex), the Property Descriptor [Value]: initValue, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true, and false. ¶

<#>Return array. ¶

The production ElementList : Elision_{opt} ... AssignmentExpression is evaluated as follows: ¶

Let array be the result of creating a new object as if by the expression new Array() where Array is the standard built-in constructor with that name. ¶

Let index be the result of evaluating Elision; if not present, use the numeric value zero. ¶

<#>Let spreadRef be the result of evaluating AssignmentExpression. ¶

<#>Let spreadValue be GetValue(spreadRef). ¶

<#>Let spreadObj be ToObject(spreadValue). ¶

<#>Let lenVal be the result of calling the [[Get]] internal method of spreadObj with argument "length". ¶

<#>Let spreadLen be Uint32(lenVal). ¶

<#>Let n=0; ¶

<#>Repeat, while n < spreadLen ¶

Deleted: PropertyNameAndValueList

Deleted: PropertyNameAndValueList

PropertyDefinitionList :

PropertyDefinition
PropertyDefinitionList , PropertyDefinition

Deleted: PropertyNameAndValueList

Deleted: PropertyAssignment

Deleted: PropertyNameAndValueList

Deleted: PropertyAssignment

Deleted: PropertyAssignment

PropertyDefinition :

IdentifierName
CoverInitialisedName
PropertyName : AssignmentExpression
MethodDefinition

Deleted: PropertyAssignment

PropertyName :

IdentifierName
StringLiteral
NumericLiteral

Deleted:
PropertyName (FormalParameterList) { FunctionBody } ..
 \star PropertyName (FormalParameterList) { FunctionBody }
get PropertyName () { FunctionBody }
set PropertyName (PropertySetParameterList) { FunctionBody }

CoverInitialisedName :

IdentifierName Initialiser

Initialiser :

= AssignmentExpression

NOTE 1 MethodDefinition is defined in 13.3.

NOTE 2 In certain contexts, ObjectLiteral is used as a cover grammar for a more restricted secondary grammar. The CoverInitialisedName production is necessary to fully cover these secondary grammars. However, use of this production results in an early Syntax Error in normal contexts where an actual ObjectLiteral is expected.

Static Semantics

Static Semantics: Early Errors

In addition to describe an actual object initialiser the ObjectLiteral productions are used as a cover grammar for ObjectAssignmentPattern (11.13.1). When ObjectLiteral appears in a context where ObjectAssignmentPattern is required, the following Early Error rules are **not** applied.

ObjectLiteral : { PropertyDefinitionList }

and

ObjectLiteral : { PropertyDefinitionList , }

- It is a Syntax Error if PropertyNameList of PropertyDefinitionList contains any duplicate entries, unless one of the following conditions are true for each duplicate entry:
 1. The source code corresponding to PropertyDefinitionList is not strict code and all occurrences in the list of the duplicated entry were obtained from productions of the form PropertyDefinition : PropertyName : AssignmentExpression.
 2. The duplicated entry occurs exactly twice in the list and one occurrence was obtained from a get accessor MethodDefinition and the other occurrence was obtained from a set accessor MethodDefinition.

Deleted: PropertyNameAndValueList :|
BindingIdentifier
BindingPattern |

Deleted: Identifier |
Semantics |

Deleted: 11.1.5.1

PropertyDefinition : MethodDefinition

- It is a Syntax Error if ReferencesSuper of MethodDefinition is true.

Deleted: PropertyNameAndValueList :
PropertyNameAndValueList , PropertyAssignment

Deleted: a

PropertyDefinition : IdentifierName

- It is a Syntax Error if IdentifierName is a ReservedWord.

Deleted: property definition

Deleted: property definition

Deleted: i

PropertyDefinition : CoverInitialisedName

- Always throw a Syntax Error if this production is present

Comment [AWB840]: The currently prevailing position in TC39 is that use of super should not be allowed in object literals. This restriction is arbitrary in the sense that the runtime semantics would work.

Deleted: i

NOTE This production exists so that *ObjectLiteral* can serve as a cover grammar for *ObjectAssignmentPattern* (11.13.1). It can not occur in an actual object initialiser.

Static Semantics: Contains

With parameter *symbol*.

PropertyDefinition : MethodDefinition

1. If *symbol* is *MethodDefinition*, return **true**.
2. Return **false**.

NOTE Static semantic rules that depend upon substructure generally do not look into function definitions.

PropertyName : IdentifierName

1. If *symbol* is a *ReservedWord*, return **false**.
2. If *symbol* is an *Identifier* and *StringValue* of *symbol* is the same value as the *StringValue* of *IdentifierName*, return **true**.
3. Return **false**.

Static Semantics: IsValidSimpleAssignmentTarget

PrimaryExpression : Literal

1. Return **false**.

Static Semantics: PropName

PropertyDefinition : IdentifierName

1. Return *StringValue* of *IdentifierName*.

PropertyDefinition : PropertyName : AssignmentExpression

1. Return *PropName* of *PropertyName*.

PropertyName : StringLiteral

1. Return a *String* values whose characters are the *SV* of the *StringLiteral*.

PropertyName : NumericLiteral

1. Let *nbr* be the result of forming the value of the *NumericLiteral*.
2. Return *ToString*(*nbr*).

Static Semantics: PropertyNameList

PropertyDefinitionList : PropertyDefinition

1. Return a new List containing *PropName* of *PropertyDefinition*.

PropertyDefinitionList : PropertyDefinitionList , PropertyDefinition

1. Let *list* be *PropertyNameList* of *PropertyDefinitionList*.
2. Append *PropName* of *PropertyDefinition* to the end of *list*.
3. Return *list*.

Deleted: <#>It is a Syntax Error if this production is contained in strict code, *PropertyAssignment* is the production *PropertyAssignment : PropertyName : AssignmentExpression*, and *PropertyDefinitionList(PropName of PropertyAssignment)* of *PropertyNameAndValueList* is not the empty List.
 <#>It is a Syntax Error if *PropertyAssignment* is the production *PropertyAssignment : IdentifierName* and *PropertyDefinitionList(PropName of PropertyAssignment)* of *PropertyNameAndValueList* is not the empty List.
 <#>It is a Syntax Error if *PropertyAssignment* is the production *PropertyAssignment : PropertyName (FormalParameterList) { FunctionBody }* and *PropertyDefinitionList(PropName of PropertyAssignment)* of *PropertyNameAndValueList* is not the empty List.
 <#>It is a Syntax Error if *PropertyAssignment* is the production *PropertyAssignment : * PropertyName (FormalParameterList) { FunctionBody }* and *PropertyDefinitionList(PropName of PropertyAssignment)* of *PropertyNameAndValueList* is not the empty List.
 <#>It is a Syntax Error if *PropertyAssignment* is the production *PropertyAssignment : get PropertyName () { FunctionBody }* and *PropertyDefinitionList(PropName of PropertyAssignment)* of *PropertyNameAndValueList* include a production of the form *PropertyAssignment : PropertyName : AssignmentExpression*.
 <#>It is a Syntax Error if *PropertyAssignment* is the production *PropertyAssignment : set PropertyName (PropertySetParameterList) { FunctionBody }* and *PropertyDefinitionList(PropName of PropertyAssignment)* of *PropertyNameAndValueList* include a production of the form *PropertyAssignment : PropertyName : AssignmentExpression*.
 <#>It is a Syntax Error if *PropertyAssignment* is the production *PropertyAssignment : get PropertyName () { FunctionBody }* and *PropertyDefinitionList(PropName of PropertyAssignment)* of *PropertyNameAndValueList* include a production of the form *PropertyAssignment : PropertyName : AssignmentExpression*.
Deleted: *PropertyDefinition : MethodDefinition ¶*
Deleted:
Deleted:
Deleted: NOTE Static semantic rules that depend upon substructure generally do not look into function definitions.
Deleted: Static Semantics: ExpectedArgumentCount
PropertySetParameterList : BindingIdentifier ¶
 <#>Return 1.
PropertySetParameterList : BindingPattern ¶
Deleted: *PropertyAssignment*
Deleted:
Deleted: *PropertyAssignment*
Deleted: *PropertyDefinition : MethodDefinition ¶*
 <#>Return *PropName* of *MethodDefinition*.
Deleted: *PropertyAssignment : PropertyName (FormalParameterList) { FunctionBody } ¶*
 <#>Return *PropName* of *PropertyName*.
Deleted: *PropertyName : IdentifierName ¶*
 <#>Return *PropName* of *IdentifierName*.
Deleted: the
Comment [AWB1041]: Issue: static semantic rules probably should call *ToString* (a runtime operation).

Runtime Semantics

Runtime Semantics: Evaluation

ObjectLiteral : { }

1. Return a new object created as if by the expression `new Object()` where `Object` is the standard built-in constructor with that name.

ObjectLiteral :

```
{ PropertyNameAndValueList }
{ PropertyNameAndValueList , }
```

1. Let `obj` be the result of the abstract operation `ObjectCreate (15.2)`.
2. Let `status` be the result of performing Property Definition Evaluation of *PropertyNameAndValueList* with argument `obj`.
3. `ReturnIfAbrupt(status)`.
4. Return `obj`.

Runtime Semantics: Property Definition Evaluation

With parameter `object`.

PropertyNameAndValueList : PropertyDefinitionList , PropertyDefinition

1. Let `status` be the result of performing Property Definition Evaluation of *PropertyDefinitionList* with argument `object`.
2. `ReturnIfAbrupt(status)`.
3. Return the result of performing Property Definition Evaluation of *PropertyDefinition* with argument `object`.

PropertyDefinition : IdentifierName

1. Let `propName` be `PropName` of `IdentifierName`.
2. Let `exprValue` be the result of performing Identifier Resolution as specified in 10.3.1 using `IdentifierName`.
3. Let `propValue` be `GetValue(exprValue)`.
4. `ReturnIfAbrupt(propValue)`.
5. Let `desc` be the Property Descriptor `{[[Value]]: propValue, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`.
6. Return the result of calling the `[[DefineOwnProperty]]` internal method of `object` with arguments `propName`, `desc`, and `false`.

PropertyDefinition : PropertyName : AssignmentExpression

1. Let `propName` be `PropName` of `PropertyName`.
2. Let `exprValue` be the result of evaluating `AssignmentExpression`.
3. Let `propValue` be `GetValue(exprValue)`.
4. `ReturnIfAbrupt(propValue)`.
5. Let `desc` be the Property Descriptor `{[[Value]]: propValue, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`.
6. Return the result of calling the `[[DefineOwnProperty]]` internal method of `object` with arguments `propName`, `desc`, and `false`.

11.1.6 Function Defining Expressions

See 13.1 for `PrimaryExpression : FunctionExpression`.

See 13.4 for `PrimaryExpression : GeneratorExpression`.

See 13.5 for `PrimaryExpression : ClassExpression`.

Deleted: 11.1.5.2
Deleted: The production <code>...ObjectLiteral : { }</code>
Deleted: <code>PropertyNameAndValueList...roperty</code>
Deleted: <code>ObjectLiteral : </code>
Deleted: <code>ion</code>
Deleted: creating a new object as if by the
Deleted: <code>P</code>
Deleted: <code>success</code>
Deleted: <code>D</code>
Deleted: <code>PropertyNameAndValueList</code>
Deleted: If <code>successstatus</code> is an abrupt completion
Deleted: the result of evaluating
Deleted: The production
Deleted: The production
Deleted: <code>PropertyNameAndValueList...roperty</code>
Deleted: <code>Deleted:</code>
Deleted: <#>Let <code>obj</code> be the result of evaluating
Deleted: <#>Let <code>previous</code> be the result of calling
Deleted: <code>success</code>
Deleted: P...rforming Property Definition
Deleted: <code>PropertyNameAndValueList</code>
Deleted: Call the <code>[[DefineOwnProperty]]</code> internal
Deleted: If <code>successstatus</code> is an abrupt completion
Deleted: P...rforming Property Definition
Deleted: <code>PropertyAssignment</code>
Deleted: Return <code>obj</code> .
Deleted: <code>¶</code>
Deleted: The production
Deleted: <code>PropertyAssignment</code>
Deleted: is evaluated as follows:
Deleted: (...of <code>IdentifierName</code>)
Deleted: as the <code>Identifier</code>
Deleted: If <code>propValue</code> is an abrupt completion,
Deleted: Call
Deleted: <#>Return Property Identifier
Deleted: The production
Deleted: <code>PropertyAssignment</code>
Deleted: is evaluated as follows:
Deleted: the result of evaluating
Deleted: (...of <code>PropertyName</code>)
Deleted: If <code>propValue</code> is an abrupt completion,
Deleted: Call
Deleted: Return Property Identifier (<code>propName</code>)
Comment [AWB642]: Need a actual
Deleted: <code>PropertyDefinition : MethodDefinition</code>
Deleted: <code>PropertyAssignment : PropertyName</code>

11.1.7 Generator Comprehensions

Syntax

GeneratorComprehension :

(*Expression* *ComprehensionForList*)
 (*Expression* *ComprehensionForList* **if** *Expression*)

Deleted: Runtime Semantics: Evaluation
PrimaryExpression : *FunctionExpression* ¶
 <#> Return the result of evaluating *FunctionExpression*. ¶

11.1.8 Regular Expression Literals

Syntax

See 7.8.5.

Static Semantics

Static Semantics: Early Errors

PrimaryExpression : *RegularExpressionLiteral*

- It is a Syntax Error if *BodyText* of *RegularExpressionLiteral* can not be recognized using the goal symbol *Pattern* of the ECMAScript RegExp grammar specified in 15.10.
- It is a Syntax Error if *FlagText* of *RegularExpressionLiteral* contains any character other than "g", "i", "m", "u", or "y", or if it contains the same character more than once.

Deleted: (
Deleted:)

Runtime Semantics

Runtime Semantics: Evaluation

PrimaryExpression : *RegularExpressionLiteral*

1. A regular expression literal evaluates to a value of the Object type that is an instance of the standard built-in constructor *RegExp*. This value is determined in two steps: first, the characters comprising the regular expression's *RegularExpressionBody* and *RegularExpressionFlags* production expansions are collected uninterpreted into two Strings *Pattern* and *Flags*, respectively. Then each time the literal is evaluated, a new object is created as if by the expression `new RegExp(Pattern, Flags)` where *RegExp* is the standard built-in constructor with that name. The newly constructed object becomes the value of the *RegularExpressionLiteral*.

Comment [AWB843]: Should convert to a multistep algorithm and breakout a static semantic rule for the error

Deleted: Quasi

11.1.9 Template Literals

Syntax

TemplateLiteral :

NoSubstitutionTemplate
 TemplateHead *Expression* [Lexical goal *InputElementTemplateTail*] *TemplateSpans*

Deleted: Quasi

Deleted: FullQuasi

Deleted: Quasi

Deleted: QuasiMiddleList_{opt} [Lexical goal *InputElementQuasiTail*]

Deleted: Quasi

Deleted: Tail

Deleted: Quasi

Deleted: [Lexical goal *InputElementQuasiTail*] Quasi

Deleted: Quasi

Deleted: Quasi

Deleted: Quasi

Deleted: QuasiStrings

TemplateSpans:

TemplateTail
 TemplateMiddleList [Lexical goal *InputElementTemplateTail*] TemplateTail

TemplateMiddleList:

TemplateMiddle *Expression*
 TemplateMiddleList [Lexical goal *InputElementTemplateTail*] TemplateMiddle *Expression*

Static Semantics

Static Semantics: TemplateStrings

With parameter *raw*.

[TemplateLiteral : NoSubstitutionTemplate](#)

1. If `raw` is false, then
 - a. Let `string` be the [TV of NoSubstitutionTemplate](#).
2. Else, Let `string` be the [TRV of NoSubstitutionTemplate](#).
3. Return a List containing the single element, `string`.

Deleted: Quasi...emplateLiteral : FullQuasi

[TemplateLiteral : TemplateHead Expression \[Lexical goal InputElementTemplateTail\] TemplateSpans](#)

1. If `raw` is false, then
 - a. Let `head` be the [TV of TemplateHead](#).
2. Else,
 - a. Let `head` be the [TRV of TemplateHead](#).
3. Let `tail` be [TemplateStrings of TemplateSpans](#) with argument `raw`.
4. Return a List containing `head` followed by the element, in order of `tail`.

Deleted: Quasi...emplateLiteral :

Deleted: QV...V of Quasi

Deleted: <#>Let `tail` be the QV of [QuasiTail](#).

Deleted: QRV...RV of Quasi

Deleted: the QRV ...f Quasi...emplateTail

[TemplateSpans : TemplateTail](#)

1. If `raw` is false, then
 - a. Let `tail` be the [TV of TemplateTail](#).
2. Else,
 - a. Let `tail` be the [TRV of TemplateTail](#).
3. Return a List containing the single element, `tail`.

Deleted: Quasi...emplateLiteral...pans :

[TemplateSpans : TemplateMiddleList \[Lexical goal InputElementTemplateTail\] TemplateTail](#)

1. Let `middle` be [TemplateStrings of TemplateMiddleList](#) with argument `raw`.
2. If `raw` is false, then
 - a. Let `tail` be the [TV of TemplateTail](#).
3. Else,
 - a. Let `tail` be the [TRV of TemplateTail](#).
4. Return a List containing the elements, in order, of `middle` followed by `tail`.

Deleted: <#>Let `head` be the QV of [QuasiHead](#)

Deleted: <#>Let `head` be the QRV of [QuasiHead](#)

Deleted: <#>Let `middle` be QuasiStrings of [QuasiMiddleList](#) with argument `raw`.

Deleted: Quasi...emplateMiddleList : [Lexical

[TemplateMiddleList : TemplateMiddle Expression](#)

1. If `raw` is false, then
 - a. Let `string` be the [TV of TemplateMiddle](#).
2. Else,
 - a. Let `string` be the [TRV of TemplateMiddle](#).
3. Return a List containing the single element, `string`.

Deleted: QV...V of Quasi

Deleted: QRV...RV of Quasi

[TemplateMiddleList : TemplateMiddleList \[Lexical goal InputElementTemplateTail\] TemplateMiddle Expression](#)

1. Let `front` be [TemplateStrings of TemplateMiddleList](#) with argument `raw`.
2. If `raw` is false, then
 - a. Let `last` be the [TV of TemplateMiddle](#).
3. Else,
 - a. Let `last` be the [TRV of TemplateMiddle](#).
4. Append `last` as the last element of the List `front`.
5. Return `front`.

Deleted: Quasi...emplateMiddleList :

Deleted: QuasiStrings...emplateStrings of Qua

Deleted: QV...V of Quasi

Deleted: QRV...RV of Quasi

Runtime Semantics

Runtime Semantics: ArgumentListEvaluation

[TemplateLiteral : NoSubstitutionTemplate](#)

1. Let `siteObj` be the result of the abstraction operation [GetTemplateCallSite](#) passing this [TemplateLiteral](#) production as the argument.
2. Return a List containing the one element which is `siteObj`.

Deleted: Quasi...emplateLiteral : FullQuasi

Deleted: the ...result of the abstraction operation

TemplateLiteral : TemplateHead Expression [Lexical goal InputElementTemplateTail] TemplateSpans

1. Let `siteObj` be the result of the abstraction operation `GetTemplateCallSite` passing this `TemplateLiteral` production as the argument.
2. Let `firstSub` be the result of evaluating `Expression`.
3. ReturnIfAbrupt(`firstSub`).
4. Let `restSub` be SubstitutionEvaluation of `TemplateSpans`.
5. ReturnIfAbrupt(`restSub`).
6. Assert, `restSub` is a List.
7. Return a List whose first element is `siteObj`, whose second elements is `firstSub`, and whose subsequent elements are the elements of `restSub`, in order. `restSub` may contain no elements.

The abstract operation `GetTemplateCallSite` is called with a grammar production, `templateLiteral`, as an argument. It performs the following steps:

1. If a call site object for the source code corresponding to `templateLiteral` has already been created by a previous call to this abstract operation, then return that call site object.
2. Let `cookedStrings` be `TemplateStrings` of `templateLiteral` with argument `false`.
3. Let `rawStrings` be `TemplateStrings` of `templateLiteral` with argument `true`.
4. Let `count` be the number of elements in the List `cookedStrings`.
5. Let `siteObj` be the result of the abstraction operation `ArrayCreate` with argument `count`.
6. Let `rawObj` be the result of the abstraction operation `ArrayCreate` with argument `count`.
7. Let `index` be `0`.
8. Repeat while `index < count`
 - a. Let `prop` be `ToString(index)`.
 - b. Let `cookedValue` be the string value at `0-based position index` of the List `cookedStrings`.
 - c. Call the `[[DefineOwnProperty]]` internal method of `siteObj` with arguments `prop`, `Property Descriptor` `{[[Value]]: cookedValue, [[Writable]]: false, [[Configurable]]: false}`, and `false`.
 - d. Let `rawValue` be the string value at `0-based position index` of the List `rawStrings`.
 - e. Call the `[[DefineOwnProperty]]` internal method of `rawObj` with arguments `prop`, `Property Descriptor` `{[[Value]]: rawValue, [[Writable]]: false, [[Configurable]]: false}`, and `false`.
 - f. Let `index` be `index+1`.
9. Call the `FreezeObject` abstract operation with argument `rawObj`.
10. Call the `[[DefineOwnProperty]]` internal method of `siteObj` with arguments `"raw"`, `Property Descriptor` `{[[Value]]: rawObj, [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false}`, and `false`.
11. Call the `FreezeObject` abstract operation with argument `siteObj`.
12. Remember an association between the source code corresponding to `templateLiteral` and `siteObj` such that `siteObj` can be retrieved in subsequent calls to this abstract operation.
13. Return `siteObj`.

NOTE 1 The creation of a call site object can not result in an abrupt completion.

NOTE 2 Each `TemplateLiteral` in the program code is associated with a unique `Template call site object` that is used in the evaluation of tagged `Templates` (11.2.6). The same call site object is used each time a specific tagged `Template` is evaluated. Whether call site objects are created lazily upon first evaluation of the `TemplateLiteral` or eagerly prior to first evaluation is an implementation choice that is not observable to ECMA Script code.

Runtime Semantics: SubstitutionEvaluation

TemplateSpans : TemplateTail

1. Return an empty List.

TemplateSpans : TemplateMiddleList [Lexical goal InputElementTemplateTail] TemplateTail

1. Return the result of SubstitutionEvaluation of `TemplateMiddleList`.

TemplateMiddleList : TemplateMiddle Expression

1. Let `sub` be the result of evaluating `Expression`.

```

Deleted: QuasiLiteral : QuasiHead Expression [Lexical goal InputElementQuasiTail] QuasiTail
<#>Let siteObj be the the result of the abstraction operation GetQuasiCallSite passing this QuasiLiteral production as the argument.¶
<#>Let firstSub be the result of evaluating Expression. ¶
<#>ReturnIfAbrupt(sub).¶
<#>Return a List whose first element is siteObj, whose second elements is firstSub, and whose subsequent elements are the elements of sub. ¶
Quasi

Deleted: Quasi
Deleted: QuasiMiddleList
Deleted: Quasi
Deleted: Quasi
Deleted: Tail
Deleted: the
Deleted: Quasi
Deleted: Quasi
Deleted: Quasi
Deleted: MiddleList
Deleted: Quasi
Deleted: Quasi
Deleted: quasi
Deleted: quasi
Deleted: QuasiStrings
Deleted: quasi
Deleted: QuasiStrings
Deleted: quasi
Deleted: }
Deleted: value
Deleted: }
Comment [AWB944]: TODO
Deleted: quasi

```

```

Deleted: Quasi
Deleted: Quasi
Deleted: Quasi
Deleted: Quasi
Deleted: Quasi

```

```

Deleted: Quasi
Deleted: [Lexical goal InputElementQuasiTail] Quasi

```

2. [ReturnIfAbrupt\(*sub*\)](#)
3. [Return a List containing only *sub*.](#)

[TemplateMiddleList : TemplateMiddleList \[Lexical goal InputElementTemplateTail\] TemplateMiddle Expression](#)

1. Let *preceding* be the result of SubstitutionEvaluation of [TemplateMiddleList](#).
2. [ReturnIfAbrupt\(*preceding*\)](#)
3. Let *next* be the result of evaluating [Expression](#).
4. [ReturnIfAbrupt\(*next*\)](#)
5. Append *next* as the list element of the List *preceding*.
6. [Return *preceding*.](#)

Runtime Semantics: Evaluation

[TemplateLiteral : NoSubstitutionTemplate](#)

1. [Return the string value whose elements are the TV of *NoSubstitutionTemplate* as defined in 7.8.6.](#)

[TemplateLiteral : TemplateHead Expression \[Lexical goal InputElementTemplateTail\] TemplateSpans](#)

1. Let *head* be the TV of [TemplateHead](#) as defined in 7.8.6.
2. Let *sub* be the result of evaluating [Expression](#).
3. Let *middle* be [ToString\(*sub*\)](#).
4. [ReturnIfAbrupt\(*middle*\)](#)
5. Let *tail* be the result of evaluating [TemplateSpans](#).
6. [ReturnIfAbrupt\(*tail*\)](#)
7. [Return the string value whose elements are the code units of *head* followed by the code units of *tail*.](#)

[TemplateSpan : TemplateTail](#)

1. Let *tail* be the TV of [TemplateTail](#) as defined in 7.8.6.
2. [Return the string whose elements are the code units of *tail*.](#)

[TemplateSpan : TemplateMiddleList \[Lexical goal InputElementTemplateTail\] TemplateTail](#)

1. Let *head* be the result of evaluating [TemplateMiddleList](#).
2. [ReturnIfAbrupt\(*head*\)](#)
3. Let *tail* be the TV of [TemplateTail](#) as defined in 7.8.6.
4. [Return the string whose elements are the code units elements of *head* followed by the code units of *tail*.](#)

[TemplateMiddleList : TemplateMiddle Expression](#)

1. Let *head* be the TV of [TemplateMiddle](#) as defined in 7.8.6.
2. Let *sub* be the result of evaluating [Expression](#).
3. Let *middle* be [ToString\(*sub*\)](#).
4. [ReturnIfAbrupt\(*middle*\)](#)
5. [Return the sequence of characters consisting of the code units of *head* followed by the elements of *middle*.](#)

[TemplateMiddleList : TemplateMiddleList \[Lexical goal InputElementTemplateTail\] TemplateMiddle Expression](#)

1. Let *rest* be the result of evaluating [TemplateMiddleList](#).
2. [ReturnIfAbrupt\(*rest*\)](#)
3. Let *middle* be the TV of [TemplateMiddle](#) as defined in 7.8.6.
4. Let *sub* be the result of evaluating [Expression](#).
5. Let *last* be [ToString\(*sub*\)](#).
6. [ReturnIfAbrupt\(*last*\)](#)
7. [Return the sequence of characters consisting of the elements of *rest* followed by the code units of *middle* followed by the elements of *last*.](#)

Deleted: *middle*

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *FullQuasi*

Deleted: *QV*

Deleted: *FullQuasi*

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *Tail*

Deleted: *QV*

Deleted: *Quasi*

Comment [AWB945]: Note that the conversion semantics are like

Deleted: <#>Let *tail* be the QV of *QuasiTail* as

Deleted: followed by the elements of *middle*

Deleted: *Quasi*

Deleted: *Literal*

Deleted: *QuasiHead Expression*

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *Quasi*

Comment [AWB946]: Note that the

Deleted: <#>Let *head* be the QV of *QuasiHead* as

Deleted: *rest*

Deleted: *QV*

Deleted: *Quasi*

Deleted: followed by the elements of *first*

Deleted: *Quasi*

Deleted: [Lexical goal InputElementQuasiTail]

Deleted: *QV*

Deleted: *Quasi*

Comment [AWB947]: Note that the

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *Quasi*

Deleted: *QV*

Deleted: *Quasi*

Comment [AWB948]: Note that the

11.1.10 The Grouping Operator

Static Semantics: IsValidSimpleAssignmentTarget

PrimaryExpression : CoverParenthesizedExpressionAndArrowParameterList

1. Let *expr* be *CoverParenthesizedExpression* of *CoverParenthesizedExpressionAndArrowParameterList*.
2. Return *IsValidSimpleAssignmentTarge* of *expr*.

ParenthesizedExpression : (Expression)

1. Return *IsValidSimpleAssignmentTarge* of *Expression*.

Runtime Semantics: Evaluation

PrimaryExpression : CoverParenthesizedExpressionAndArrowParameterList

1. Let *expr* be *CoverParenthesizedExpression* of *CoverParenthesizedExpressionAndArrowParameterList*.
2. Return the result of evaluating *expr*.

ParenthesizedExpression : (Expression)

1. Return the result of evaluating *Expression*. This may be of type Reference.

NOTE This algorithm does not apply GetValue to the result of evaluating *Expression*. The principal motivation for this is so that operators such as `delete` and `typeof` may be applied to parenthesised expressions.

11.2 Left-Hand-Side Expressions

Syntax

MemberExpression :
[Lexical goal InputElementRegExp] PrimaryExpression
MemberExpression [Expression]
MemberExpression . IdentifierName
MemberExpression TemplateLiteral
super [Expression]
super . IdentifierName
new MemberExpression Arguments

NewExpression :
MemberExpression
new NewExpression

CallExpression :
MemberExpression Arguments
super Arguments
CallExpression Arguments
CallExpression [Expression]
CallExpression . IdentifierName
CallExpression TemplateLiteral

Arguments :
()
(ArgumentList)

Deleted: *ComprehensionForList :¶ ComprehensionFor ComprehensionForList ComprehensionFor¶ ComprehensionFor :¶ for (LeftHandSideExpression of Expression)¶*

Deleted: The production *PropertyName : IdentifierName* is evaluated as follows:
 ¶Return the String value containing the same sequence of characters as the *IdentifierName*.
 The production *PropertyName : StringLiteral* is evaluated as follows:
 ¶Return the SV of the *StringLiteral*.
 The production *PropertyName : NumericLiteral* is evaluated as follows:
 ¶Let *nbr* be the result of forming the value of the *NumericLiteral*.
 ¶Return *ToString(nbr)*.

Deleted: 6

Deleted: 7

Deleted: 8

Deleted: The production

Deleted: *PrimaryExpression*

Deleted: is evaluated as follows:

Deleted: *FunctionExpression ..*

Deleted: *Quasi*

Deleted: *MemberExpression <| TriangleLiteral*

Comment [AWB849]: Issue: do we also want: new super Arguments ?

Deleted: *MemberExpression <| SealedArrayLiteral .. MemberExpression <| SealedObjectLiteral .. MemberExpression <| FunctionExpression .. MemberExpression <| ValueLiteral*

Deleted: *Quasi*

Deleted: ..

Deleted: *CallExpression <| TriangleLiteral*

ArgumentList :

```

AssignmentExpression
... AssignmentExpression
ArgumentList , AssignmentExpression
ArgumentList , ... AssignmentExpression

```

LeftHandSideExpression :

```

NewExpression
CallExpression

```

Static Semantics

Static Semantics: Contains

With parameter *symbol*.

MemberExpression : MemberExpression . IdentifierName

1. If *MemberExpression* contains *symbol* is **true**, return **true**.
2. If *symbol* is a *ReservedWord*, return **false**.
3. If *symbol* is an *Identifier* and *StringValue* of *symbol* is the same value as the *StringValue* of *IdentifierName*, return **true**.
4. Return **false**.

MemberExpression : super . IdentifierName

1. If *symbol* is the *ReservedWord* **super**, return **true**.
2. If *symbol* is a *ReservedWord*, return **false**.
3. If *symbol* is an *Identifier* and *StringValue* of *symbol* is the same value as the *StringValue* of *IdentifierName*, return **true**.
4. Return **false**.

CallExpression : CallExpression . IdentifierName

1. If *CallExpression* contains *symbol* is **true**, return **true**.
2. If *symbol* is a *ReservedWord*, return **false**.
3. If *symbol* is an *Identifier* and *StringValue* of *symbol* is the same value as the *StringValue* of *IdentifierName*, return **true**.
4. Return **false**.

Static Semantics: IsValidSimpleAssignmentTarget

CallExpression :

```

MemberExpression Arguments
super Arguments
CallExpression Arguments |
CallExpression [ Expression ]
CallExpression . IdentifierName

```

MemberExpression :

```

MemberExpression [ Expression ]
MemberExpression . IdentifierName
super [ Expression ]
super . IdentifierName

```

1. Return **true**.

Deleted: TriangleLiteral ;
SealedArrayLiteral
SealedObjectLiteral ↗
FunctionExpression
ArrowFunction ↗
ValueLiteral ¶

Deleted:

Deleted:

Deleted:

Deleted:

Deleted:

Deleted:

Deleted: Static Semantics:
IsInvalidAssignmentPattern¶
LeftHandSideExpression : NewExpression¶
<#> If the source code corresponding to
NewExpression cannot be parsed as *ArrayLiteral*,
then ¶
<#> If the source code corresponding to
NewExpression cannot be parsed as *ObjectLiteral*,
then return **false**. ¶
<#> If the source code corresponding to
NewExpression cannot be parsed using
AssignmentPattern (11.13.1) as the goal symbol,
return **true**. ¶
<#> Return **false**. ¶
LeftHandSideExpression : CallExpression¶
<#> Return **false**. ¶

Comment [AWB1050]: These would become
false, if we disallow host functions returning
reference values.

CallExpression : CallExpression TemplateLiteral
NewExpression : new NewExpression
MemberExpression : new MemberExpression Arguments

1. Return false.

11.2.1 Property Accessors

Properties are accessed by name, using either the dot notation:

MemberExpression . IdentifierName
CallExpression . IdentifierName

or the bracket notation:

MemberExpression [Expression]
CallExpression [Expression]

The dot notation is explained by the following syntactic conversion:

MemberExpression . IdentifierName

is identical in its behaviour to

MemberExpression [<identifier-name-string>]

and similarly

CallExpression . IdentifierName

is identical in its behaviour to

CallExpression [<identifier-name-string>]

where *<identifier-name-string>* is a string literal containing the same sequence of characters after processing of Unicode escape sequences as the *IdentifierName*.

Runtime Semantics: Evaluation

MemberExpression : MemberExpression [Expression]

1. Let *baseReference* be the result of evaluating *MemberExpression*.
2. Let *baseValue* be *GetValue(baseReference)*.
3. ReturnIfAbrupt(baseValue).
4. Let *propertyNameReference* be the result of evaluating *Expression*.
5. Let *propertyNameValue* be *GetValue(propertyNameReference)*.
6. ReturnIfAbrupt(propertyNameValue).
7. ReturnIfAbrupt(CheckObjectCoercible(baseValue)).
8. Let *propertyNameString* be *ToString(propertyNameValue)*.
9. If the code matched by the syntactic production that is being evaluated is strict mode code, let *strict* be **true**, else let *strict* be **false**.
10. Return a value of type Reference whose base value is *baseValue* and whose referenced name is *propertyNameString*, and whose strict mode flag is *strict*.

CallExpression : CallExpression [Expression]

Is evaluated in exactly the same manner as MemberExpression : MemberExpression [Expression], except that the contained *CallExpression* is evaluated in step 1.

11.2.2 The new Operator

Runtime Semantics: Evaluation

NewExpression : new NewExpression

- Deleted:** The production
- Deleted:** is evaluated as follows:
 - Deleted:** If *baseValue* is an abrupt completion, return *baseValue*
 - Deleted:** If *propertyNameValue* is an abrupt completion, return *propertyNameValue*
 - Deleted:** Call
 - Deleted:** If the result of
 - Deleted:** is an abrupt completion, return that result
 - Deleted:** contained in
 - Deleted:** The production
 - Deleted:** is
 - Deleted:** ,

1. Let *ref* be the result of evaluating *NewExpression*.
2. Let *constructor* be *GetValue(ref)*.
3. [ReturnIfAbrupt\(constructor\)](#)
4. If *Type(constructor)* is not Object, throw a **TypeError** exception.
5. If *constructor* does not implement the **[[Construct]]** internal method, throw a **TypeError** exception.
6. Return the result of calling the **[[Construct]]** internal method on *constructor*, with an empty List as the argument.

MemberExpression : new MemberExpression Arguments

1. Let *ref* be the result of evaluating *MemberExpression*.
2. Let *constructor* be *GetValue(ref)*.
3. [ReturnIfAbrupt\(constructor\)](#)
4. Let *argList* be the result of evaluating *Arguments*, producing an internal List of argument values (11.2.4).
5. [ReturnIfAbrupt\(argList\)](#)
6. If *Type(constructor)* is not Object, throw a **TypeError** exception.
7. If *constructor* does not implement the **[[Construct]]** internal method, throw a **TypeError** exception.
8. Return the result of calling the **[[Construct]]** internal method on *constructor*, passing argList as the argument.

11.2.3 Function Calls

Runtime Semantics: Evaluation

CallExpression : MemberExpression Arguments

1. [Let ref be the result of evaluating MemberExpression](#)
2. [If this CallExpression is in a tail position \(13.7\) then let tailCall be true, otherwise let tailCall be false.](#)
3. [Return the result of the abstract operation EvaluateCall with arguments ref, Arguments, and tailCall.](#)

CallExpression : CallExpression Arguments

1. [Let ref be the result of evaluating CallExpression](#)
2. [If this CallExpression is in a tail position \(13.7\) then let tailCall be true, otherwise let tailCall be false.](#)
3. [Return the result of the abstract operation EvaluateCall with arguments ref, Arguments, and tailCall.](#)

The abstract operation **EvaluateCall** takes as arguments a value *ref*, and a syntactic grammar production *arguments*, and a Boolean argument *tailPosition*. It performs the following steps:

1. Let *func* be *GetValue(ref)*.
2. [ReturnIfAbrupt\(func\)](#)
3. Let *argList* be the result of performing ArgumentListEvaluation of Arguments.
4. [ReturnIfAbrupt\(argList\)](#)
5. If *Type(func)* is not Object, throw a **TypeError** exception.
6. If *IsCallable(func)* is false, throw a **TypeError** exception.
7. If *Type(ref)* is Reference, then
 - a. If *IsPropertyReference(ref)* is true, then
 - i. Let *thisValue* be [GetThisValue\(ref\)](#).
 - b. Else, the base of *ref* is an Environment Record
 - i. Let *thisValue* be the result of calling the [WithBaseObject](#) concrete method of *GetBase(ref)*.
8. Else, *Type(ref)* is not Reference.
 - a. Let *thisValue* be **undefined**.
9. [If tailPosition is true, then](#)
 - a. Let *leafContext* be the running execution context.
 - b. [Suspend leafContext](#).
 - c. [Pop leafContext from the execution context context stack. The execution context now on the top of the stack becomes the running execution context, however it remains in its suspended state.](#)
 - d. [Assert: leafContext has no further use. It will never be activated as the running execution context.](#)
10. Let *result* be the result of calling the **[[Call]]** internal method on *func*, passing thisValue and argList as the argument values.

- Deleted:** If *constructor* is an abrupt completion, return *constructor*
- Deleted:** , providing no arguments (that is,
- Deleted:** list
- Deleted:** of
- Comment [AWB951]:** TODO probably need to do something about new operators in tail position.
- Deleted:** arguments)
- Deleted:** The production
- Deleted:** is evaluated as follows:
- Deleted:** If *constructor* is an abrupt completion, return *constructor*
- Deleted:** list
- Deleted:** If *argList* is an abrupt completion, return *argList*
- Deleted:** providing the list
- Deleted:** values
- Comment [AWB752]:** TODO: tail calls.
- Jan 19 meeting notes: Tentative decision is to support tail calls in strict mode only.
- Deleted:** The production
- Deleted:** is evaluated as follows:
- Deleted:**
- Deleted:** and
- Deleted:**
- Deleted:** and
- Deleted:**
- Deleted:** Reference,
- Deleted:** <#>Let *ref* be the result of evaluating *MemberExpression*.¶
- Deleted:** If *func* is an abrupt completion, return *func*
- Deleted:** evaluating
- Deleted:** , producing an internal list of argument values (see 11.2.4)
- Deleted:** If *argList* is an abrupt completion, return *argList*
- Deleted:** GetBase
- Deleted:** ImplicitThisValue
- Deleted:** <#>Let *leafCallerContext* be *leafContext*'s PreviousContext¶
- Deleted:** Make *leafCallerContext* t
- Comment [AWB953]:** Is this really true. Need to think about whether generators may
- Deleted:** Return
- Deleted:** providing
- Deleted:** as the this value
- Deleted:** providing the list
- Deleted:**

11. Assert: If *tailPosition* is true, the above call will not return here, but instead evaluation will continue with the resumption of *leafCallerContext* as the running execution context.
12. Return result.

A tail position call must either release any transient internal resources associated with the currently executing function execution context before invoking the target function or reuse those resources in support of the target function.

NOTE 1 For example, a tail position call should only grow an implementation's activation record stack by the amount that the size of the target function's activation record exceeds the size of the calling function's activation record. If the target function's activation record is smaller, then the total size of the stack should decrease.

NOTE 2 The returned result will never be of type Reference if *func* is an ordinary object. Whether calling an exotic object can return a value of type Reference is implementation-dependent. If a value of type Reference is returned, it must be a non-strict Property Reference.

11.2.4 The super Keyword

Static Semantics

Static Semantics: Early Errors

MemberExpression :

super [Expression]
super . IdentifierName

- It is a Syntax Error if the source code parsed with this production is global code that is not eval code.
- It is a Syntax Error if the source code parsed with this production is eval code and the source code is not being processed by a direct call to eval that is contained in function code.

CallExpression : super Arguments

- It is a Syntax Error if the source code parsed with this production is global code that is not eval code.
- It is a Syntax Error if the source code parsed with this production is eval code and the source code is not being processed by a direct call to eval that is contained in function code.

Runtime Semantics: Evaluation

MemberExpression : super [Expression]

1. Let *env* be the result of performing the GetThisEnvironment abstract operation.
2. If the result of calling the HasSuperBinding concrete method of *env* is false, then throw ReferenceError.
3. Let *actualThis* be the result of calling the GetThisBinding concrete method of *env*.
4. Let *baseValue* be the result of calling the GetSuperBase concrete method of *env*.
5. Let *propertyNameReference* be the result of evaluating *Expression*.
6. Let *propertyNameValue* be GetValue(*propertyNameReference*).
7. ReturnIfAbrupt(CheckObjectCoercible(*baseValue*)).
8. Let *propertyKey* be ToPropertyKey(*propertyNameValue*).
9. If the code matched by the syntactic production that is being evaluated is strict mode code, let *strict* be true, else let *strict* be false.
10. Return a value of type Reference that is a Super Reference whose base value is *baseValue*, whose referenced name is *propertyKey*, whose *thisValue* is *actualThis*, and whose strict mode flag is *strict*.

MemberExpression : super . IdentifierName

1. Let *env* be the result of performing the GetThisEnvironment abstract operation.
2. If the result of calling the HasSuperBinding concrete method of *env* is false, then throw ReferenceError.
3. Let *actualThis* be the result of calling the GetThisBinding concrete method of *env*.
4. Let *baseValue* be the result of calling the GetSuperBase concrete method of *env*.
5. ReturnIfAbrupt(CheckObjectCoercible(*baseValue*)).

Deleted: a

Comment [AWB954]: Issue: can we eliminate reference returning functions for ES6??

Deleted: The This production *CallExpression : CallExpression Arguments* is evaluated in exactly the same manner, as *CallExpression : MemberExpression Arguments* except that the contained *CallExpression* is evaluated in step 1.¶

Deleted: native

Deleted: ECMAScript

Deleted: host

Deleted: 3

Deleted: code

Deleted: that is also global code

Deleted: <#>It is a Syntax Error if the source code parsed with this production is not extended code.¶

Deleted: code

Deleted: that is also global code

Deleted: <#>It is a Syntax Error if the source code parsed with this production is not extended code.¶

Deleted: HomeObject

Deleted: <#>Let *baseReference* be the result of evaluating *MemberExpression*.¶
 <#>Let *baseValue* be GetValue(*baseReference*).¶

Deleted: Call CheckObjectCoercible(*baseValue*).

Deleted: NameString

Deleted: String

Deleted: and

Deleted: NameString

6. Let *propertyKey* be *StringValue* of *IdentifierName*.
7. If the code matched by the syntactic production that is being evaluated is strict mode code, let *strict* be **true**, else let *strict* be **false**.
8. Return a value of type *Reference* that is a *Super Reference* whose *base value* is *baseValue*, whose referenced name is *propertyKey*, whose *thisValue*.

CallExpression : super Arguments

1. Let *env* be the result of performing the *GetThisEnvironment* abstract operation.
2. If the result of calling the *HasSuperBinding* concrete method of *env* is **false**, then throw *ReferenceError*.
3. Let *actualThis* be the result of calling the *GetThisBinding* concrete method of *env*.
4. Let *baseValue* be the result of calling the *GetSuperBase*, concrete method of *env*.
5. **ReturnIfAbrupt**(*CheckObjectCoercible(baseValue)*).
6. Let *propertyKey* be the result of calling the *GetMethodSimpleName* concrete method of *env*.
7. If the code matched by the syntactic production that is being evaluated is strict mode code, let *strict* be **true**, else let *strict* be **false**.
8. Let *ref* be a value of type *Reference* that is a *Super Reference* whose *base value* is *baseValue*, whose referenced name is *propertyKey*, whose *thisValue*.
9. If this *CallExpression* is in a tail position (13.7) then let *tailCall* be **true**, otherwise let *tailCall* be **false**.
10. Return the result of the abstract operation *EvaluateCall* with arguments *ref*, *Arguments*, and *tailCall*.

11.2.5 Argument Lists

The evaluation of an argument list produces a List of values (see 8.7).

Runtime Semantics

Runtime Semantics: ArgumentListEvaluation

Arguments : ()

1. Return an empty List.

ArgumentList : AssignmentExpression

1. Let *ref* be the result of evaluating *AssignmentExpression*.
2. Let *arg* be *GetValue(ref)*.
3. **ReturnIfAbrupt**(*arg*).
4. Return a List whose sole item is *arg*.

ArgumentList : ... AssignmentExpression

1. Let *list* be an empty List.
2. Let *spreadRef* be the result of evaluating *AssignmentExpression*.
3. Let *spreadValue* be *GetValue(spreadRef)*.
4. Let *spreadObj* be *ToObject(spreadValue)*.
5. **ReturnIfAbrupt**(*spreadObj*).
6. Let *lenVal* be the result of calling the *[[Get]]* internal method of *spreadObj* with argument "**length**".
7. Let *spreadLen* be *ToInt32(lenVal)*.
8. **ReturnIfAbrupt**(*spreadLen*).
9. Let *n* = 0.
10. Repeat, while *n* < *spreadLen*
 - a. Let *nextArg* be the result of calling the *[[Get]]* internal method of *spreadObj* passing *ToString(n)* as the argument.
 - b. **ReturnIfAbrupt**(*nextArg*).
 - c. Append *nextArg* as the last element of *list*.
 - d. Let *n* = *n*+1.
11. Return *list*.

Deleted:

Deleted: HomeObject

Deleted:

Deleted: and

Deleted: 4

Deleted: 8

Deleted: 11.2.45.1 Static Semantics¶
Static Semantics: Early Errors¶

The production *Arguments : ()* is evaluated follows:¶

<#> Return an empty List.¶

The production *Arguments : (ArgumentList)* evaluated as follows:¶

<#> Return the result of evaluating *ArgumentList*.¶

The production *ArgumentList :*

AssignmentExpression is evaluated as follows:¶

<#> Let *ref* be the result of evaluating *AssignmentExpression*.¶

<#> Let *arg* be *GetValue(ref)*.¶

<#> Return a List whose sole item is *arg*.¶

The static semantics of the production *ArgumentList : ... AssignmentExpression are:¶*

<#> It is a Syntax Error if the sourcecode parsed with this production is not extended code.¶

The static semantics of the production *ArgumentList : ArgumentList , ... AssignmentExpression are:¶*

<#> It is a Syntax Error if the sourcecode parsed with this production is not extended code.¶

11.2.45.2

Deleted: Evaluation

Deleted: The production

Deleted: is evaluated as follows:

Deleted: The production *Arguments : (ArgumentList)* is evaluated as follows:¶

<#> Return the result of evaluating *ArgumentList*.¶

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If *arg* is an abrupt completion, return a

Comment [AW55]: Note that the value the spread operator is applied to is coerced to an Object.

Deleted: If *spreadObj* is an abrupt completion, return *spreadObj*

ArgumentList : *ArgumentList* , *AssignmentExpression*

1. Let *precedingArgs* be the result of evaluating *ArgumentList*.
2. [ReturnIfAbrupt\(*precedingArgs*\)](#)
3. Let *ref* be the result of evaluating *AssignmentExpression*.
4. Let *arg* be *GetValue(ref)*.
5. [ReturnIfAbrupt\(*arg*\)](#)
6. Return a List whose length is one greater than the length of *precedingArgs* and whose items are the items of *precedingArgs*, in order, followed at the end by *arg* which is the last item of the new list.

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If *precedingArgs* is an abrupt completion, return *precedingArgs*

Deleted: If *arg* is an abrupt completion, return *arg*

ArgumentList : *ArgumentList* , ... *AssignmentExpression*

1. Let *precedingArgs* be an empty List.
2. Let *spreadRef* be the result of evaluating *AssignmentExpression*.
3. Let *spreadValue* be *GetValue(spreadRef)*.
4. [Let spreadObj be ToObject\(*spreadValue*\)](#)
5. [ReturnIfAbrupt\(*spreadObj*\)](#)
6. Let *lenVal* be the result of calling the [[Get]] internal method of *spreadObj* with argument "length".
7. Let *spreadLen* be *ToUint32(lenVal)*.
8. [ReturnIfAbrupt\(*spreadLen*\)](#).
9. Let *n* = 0.
10. Repeat, while *n* < *spreadLen*
 - a. Let *nextArg* be the result of calling the [[Get]] internal method of *spreadObj* passing *ToString(n)* as the argument.
 - b. [ReturnIfAbrupt\(*nextArg*\)](#).
 - c. Append *nextArg* as the last element of *precedingArgs*.
 - d. Let *n* = *n*+1.
11. [Return *precedingArgs*](#).

Deleted: The production

Deleted: is evaluated as follows:

Comment [AW56]: Note that the value the spread operator is applied to is coerced to an Object.

Deleted: If *spreadObj* is an abrupt completion, return *spreadObj*

11.2.6 Tagged Templates

Runtime Semantics

The runtime semantics of production:

CallExpression : *CallExpression* *TemplateLiteral*

Deleted: Quasi

is identical to that of

MemberExpression : *MemberExpression* *TemplateLiteral*

Deleted: Quasi

but with evaluation of *CallExpression* substituted for the evaluation of *MemberExpression*.

Runtime Semantics: Evaluation

MemberExpression : *MemberExpression* *TemplateLiteral*

Deleted: Quasi

1. Let *tagRef* be the result of evaluating *MemberExpression*.

Deleted: Quasi

2. If this *MemberExpression* is in a tail position (13.7) then let *tailCall* be **true**, otherwise let *tailCall* be **false**.
3. Return the result of the abstract operation *EvaluateCall* with arguments *tagRef*, *TemplateLiteral*, and *tailCall*.

11.3 Postfix Expressions

Syntax

PostfixExpression :

LeftHandSideExpression

LeftHandSideExpression [no LineTerminator here] **++**

LeftHandSideExpression [no LineTerminator here] **--**

Static Semantics

Static Semantics: Early Errors

PostfixExpression :

LeftHandSideExpression

LeftHandSideExpression [no LineTerminator here] ++

LeftHandSideExpression [no LineTerminator here] --

- It is a Syntax Error if the derived LeftHandSideExpression is PrimaryExpression : ObjectLiteral and ContainsNonObjectLiteralProductions of ObjectLiteral is true.
- It is a Syntax Error if the derived LeftHandSideExpression is PrimaryExpression : (Expression) and Expression derived a production that if used in place of LeftHandSideExpression would produce a Syntax Error according to these rules. This rule is recursively applied.

PostfixExpression :

LeftHandSideExpression [no LineTerminator here] ++

LeftHandSideExpression [no LineTerminator here] --

- It is an early Reference Error if IsValidSimpleAssignmentTarget of LeftHandSideExpression is false.

Static Semantics: IsValidSimpleAssignmentTarget

PostfixExpression :

LeftHandSideExpression [no LineTerminator here] ++

LeftHandSideExpression [no LineTerminator here] --

1. Return false.

11.3.1 Postfix Increment Operator

Runtime Semantics: Evaluation

PostfixExpression : LeftHandSideExpression [no LineTerminator here] ++

1. Let lhs be the result of evaluating LeftHandSideExpression.
2. Let oldValue be ToNumber(GetValue(lhs)).
3. ReturnIfAbrupt(oldValue).
4. Let newValue be the result of adding the value 1 to oldValue, using the same rules as for the + operator (see 11.6.3).
5. Let status be PutValue(lhs, newValue).
6. ReturnIfAbrupt(status).
7. Return oldValue.

11.3.2 Postfix Decrement Operator

Runtime Semantics: Evaluation

PostfixExpression : LeftHandSideExpression [no LineTerminator here] --

1. Let lhs be the result of evaluating LeftHandSideExpression.
2. Let oldValue be ToNumber(GetValue(lhs)).
3. Let newValue be the result of subtracting the value 1 from oldValue, using the same rules as for the - operator (11.6.3).
4. Let status be PutValue(lhs, newValue).
5. ReturnIfAbrupt(status).
6. Return oldValue.

Deleted: It is a Syntax Error if the PostfixExpression is contained in strict code and the LeftHandSideExpression is the Identifier eval or the Identifier arguments.

Deleted: ¶

¶ It is a Syntax Error if the AssignmentExpression is contained in extended code and the LeftHandSideExpression is a Identifier or a FunctionExpression. ¶

¶ It is a Syntax Error if the AssignmentExpression is contained in extended code and the LeftHandSideExpression is an Identifier that does not statically resolve to a declarative environment record binding or if the resolved binding is an immutable binding. ¶ It is a Syntax Error if the LeftHandSideExpression is PrimaryExpression : (Expression) and Expression derived a production that if used in place of LeftHandSideExpression that would produce a Syntax Error according to these rules. This rule is recursively applied.

Deleted: The production

Deleted: is evaluated as follows:

Deleted: ¶ Throw a SyntaxError exception if the following conditions are all true: ¶ <#> Type(lhs) is Reference is true ¶ <#> IsStrictReference(lhs) is true ¶ <#> Type(GetBase(lhs)) is Environment Record ¶ <#> GetReferencedName(lhs) is either "eval" or "arguments" ¶

Deleted: If oldValue is an abrupt completion, return oldValue.

Deleted: Call

Deleted: If

Deleted: The production

Deleted: is evaluated as follows:

Deleted: ¶ Throw a SyntaxError exception if the following conditions are all true: ¶ <#> Type(lhs) is Reference is true ¶ <#> IsStrictReference(lhs) is true ¶ <#> Type(GetBase(lhs)) is Environment Record ¶ <#> GetReferencedName(lhs) is either "eval" or "arguments" ¶

Deleted: If Call

11.4 Unary Operators

Syntax

UnaryExpression :
PostfixExpression
delete *UnaryExpression*
void *UnaryExpression*
typeof *UnaryExpression*
++ *UnaryExpression*
-- *UnaryExpression*
+ *UnaryExpression*
- *UnaryExpression*
~ *UnaryExpression*
! *UnaryExpression*

Static Semantics

Static Semantics: Early Errors

UnaryExpression :
delete *UnaryExpression*

- It is a Syntax Error if the *UnaryExpression* is contained in strict code and the derived *UnaryExpression* is the Identifier `eval` or the Identifier `arguments`.
- It is a Syntax Error if the derived *UnaryExpression* is *PrimaryExpression* : `(Expression)` and *Expression* derived a production that if used in place of *UnaryExpression* would produce a Syntax Error according to these rules. This rule is recursively applied.

UnaryExpression :
++ *UnaryExpression*
-- *UnaryExpression*

- It is an early Reference Error if *IsValidSimpleAssignmentTarget* of *UnaryExpression* is `false`.

Static Semantics: *IsValidSimpleAssignmentTarget*

UnaryExpression :
delete *UnaryExpression*
void *UnaryExpression*
typeof *UnaryExpression*
++ *UnaryExpression*
-- *UnaryExpression*
+ *UnaryExpression*
- *UnaryExpression*
~ *UnaryExpression*
! *UnaryExpression*

1. Return `false`.

11.4.1 The **delete** Operator

Static Semantics: Early Errors

UnaryExpression : **delete** *UnaryExpression*

- It is a Syntax Error if the *UnaryExpression* is contained in strict code and the *UnaryExpression* derives an Identifier that statically resolves to a environment record.

Deleted: <#>
++ *UnaryExpression* ..
-- *UnaryExpression*¶

Deleted: <#>It is a Syntax Error if the *UnaryExpression* contained in extended code and the derived *UnaryExpression* is a *Literal* or a *FunctionExpression*.¶
<#>It is a Syntax Error if the *UnaryExpression* is contained in extended code and the derived *UnaryExpression* is an *Identifier* that does not statically resolve to a declarative environment record binding or if the resolved binding is an immutable binding.¶

Deleted: *LeftHandSide*

Runtime Semantics: Evaluation

UnaryExpression : **delete** *UnaryExpression*

1. Let *ref* be the result of evaluating *UnaryExpression*.
- 2. ReturnIfAbrupt(*ref*)**
3. If Type(*ref*) is not Reference, return **true**.
4. If IsUnresolvableReference(*ref*) is **true**, then,
 - a. If IsStrictReference(*ref*) is **true**, throw a **SyntaxError** exception.
 - b. Else, return **true**.
5. If IsPropertyReference(*ref*) is **true**, then
 - a. **If IsSuperReference(*ref*)**, then throw a **ReferenceError** exception.
 - b. Return the result of calling the [[Delete]] internal method on ToObject(GetBase(*ref*)) providing GetReferencedName(*ref*) and IsStrictReference(*ref*) as the arguments.
6. Else, *ref* is a Reference to an Environment Record binding, so
 - a. Let *bindings* be GetBase(*ref*).
 - b. Return the result of calling the DeleteBinding concrete method of *bindings*, providing GetReferencedName(*ref*) as the argument.

NOTE When a **delete** operator occurs within strict mode code, a **SyntaxError** exception is thrown if its *UnaryExpression* is a direct reference to a variable, function argument, or function name. In addition, if a **delete** operator occurs within strict mode code and the property to be deleted has the attribute { [[Configurable]]: **false** }, a **TypeError** exception is thrown.

11.4.2 The **void** Operator

Runtime Semantics: Evaluation

UnaryExpression : **void** *UnaryExpression*

1. Let *expr* be the result of evaluating *UnaryExpression*.
2. Call GetValue(*expr*).
- 3. ReturnIfAbrupt(*expr*)**
4. Return **undefined**.

NOTE GetValue must be called even though its value is not used because it may have observable side-effects.



11.4.3 The **typeof** Operator

Runtime Semantics: Evaluation

UnaryExpression : **typeof** *UnaryExpression*

1. Let *val* be the result of evaluating *UnaryExpression*.
2. If Type(*val*) is Reference, then
 - a. If IsUnresolvableReference(*val*) is **true**, return "**undefined**".
 - b. Let *val* be GetValue(*val*).
- 3. ReturnIfAbrupt(*val*)**
4. Return a String determined by Type(*val*) according to [Table 25](#).

[Table 25](#) — **typeof** Operator Results



Type of val	Result
Undefined	"undefined"
Null	"object"
Boolean	"boolean"
Number	"number"
String	"string"
Object (native and does not implement [[Call]])	"object"
Object (native or host and does implement [[Call]])	"function"
Object (host and does not implement [[Call]])	Implementation-defined except may not be "undefined", "boolean", "number", OR "string".

11.4.4 Prefix Increment Operator

Runtime Semantics: Evaluation

UnaryExpression : ++ UnaryExpression

1. Let *expr* be the result of evaluating *UnaryExpression*.
2. Let *oldValue* be *ToNumber*(*GetValue*(*expr*)).
3. *ReturnIfAbrupt*(*oldValue*).
4. Let *newValue* be the result of adding the value **1** to *oldValue*, using the same rules as for the **+** operator (see 11.6.3).
5. *Let status be PutValue(expr, newValue)*.
6. *ReturnIfAbrupt(status)*.
7. Return *newValue*.

11.4.5 Prefix Decrement Operator

Runtime Semantics: Evaluation

UnaryExpression : -- UnaryExpression

1. Let *expr* be the result of evaluating *UnaryExpression*.
2. Let *oldValue* be *ToNumber*(*GetValue*(*expr*)).
3. *ReturnIfAbrupt*(*oldValue*).
4. Let *newValue* be the result of subtracting the value **1** from *oldValue*, using the same rules as for the **-** operator (see 11.6.3).
5. *Let status be PutValue(expr, newValue)*.
6. *ReturnIfAbrupt(status)*.
7. Return *newValue*.

11.4.6 Unary + Operator

NOTE The unary **+** operator converts its operand to Number type.

Runtime Semantics: Evaluation

UnaryExpression : + UnaryExpression

1. Let *expr* be the result of evaluating *UnaryExpression*.
2. Return *ToNumber*(*GetValue*(*expr*)).

Deleted: The production

Deleted: is evaluated as follows:

Deleted: *<#>* Throw a **SyntaxError** exception if the following conditions are all true:
<#> *Type(expr)* is Reference is **true**
<#> *IsStrictReference(expr)* is **true**
<#> *Type(GetBase(expr))* is Environment Record
<#> *GetReferencedName(expr)* is either "**eval**" or "**arguments**"

Deleted: If *oldValue* is an abrupt completion, return *oldValue*.

Deleted: If

Deleted: Call

Deleted: The production

Deleted: is evaluated as follows:

Deleted: *<#>* Throw a **SyntaxError** exception if the following conditions are all true:
<#> *Type(expr)* is Reference is **true**
<#> *IsStrictReference(expr)* is **true**
<#> *Type(GetBase(expr))* is Environment Record
<#> *GetReferencedName(expr)* is either "**eval**" or "**arguments**"

Deleted: If *oldValue* is an abrupt completion, return *oldValue*.

Deleted: Call

Deleted: If

11.4.7 Unary - Operator

NOTE The unary `-` operator converts its operand to Number type and then negates it. Negating `+0` produces `-0`, and negating `-0` produces `+0`.

Deleted: Note that negating

Runtime Semantics: Evaluation

UnaryExpression : `- UnaryExpression`

1. Let `expr` be the result of evaluating `UnaryExpression`.
2. Let `oldValue` be `ToNumber(GetValue(expr))`.
3. ReturnIfAbrupt(`oldValue`).
4. If `oldValue` is `NaN`, return `NaN`.
5. Return the result of negating `oldValue`; that is, compute a Number with the same magnitude but opposite sign.

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If `oldValue` is an abrupt completion, return `oldValue`.

11.4.8 Bitwise NOT Operator (`~`)

Runtime Semantics: Evaluation

UnaryExpression : `~ UnaryExpression`

1. Let `expr` be the result of evaluating `UnaryExpression`.
2. Let `oldValue` be `ToInt32(GetValue(expr))`.
3. ReturnIfAbrupt(`oldValue`).
4. Return the result of applying bitwise complement to `oldValue`. The result is a signed 32-bit integer.

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If `oldValue` is an abrupt completion, return `oldValue`.

11.4.9 Logical NOT Operator (`!`)

Runtime Semantics: Evaluation

UnaryExpression : `! UnaryExpression`

1. Let `expr` be the result of evaluating `UnaryExpression`.
2. Let `oldValue` be `ToBoolean(GetValue(expr))`.
3. ReturnIfAbrupt(`oldValue`).
4. If `oldValue` is `true`, return `false`.
5. Return `true`.

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If `oldValue` is an abrupt completion, return `oldValue`.

11.5 Multiplicative Operators

Syntax

MultiplicativeExpression :
 UnaryExpression
 MultiplicativeExpression * UnaryExpression
 MultiplicativeExpression / UnaryExpression
 MultiplicativeExpression % UnaryExpression

Static Semantics: IsValidSimpleAssignmentTarget

MultiplicativeExpression :
 MultiplicativeExpression * UnaryExpression
 MultiplicativeExpression / UnaryExpression
 MultiplicativeExpression % UnaryExpression

1. Return false.

Runtime Semantics: Evaluation

The production *MultiplicativeExpression* : *MultiplicativeExpression* @ *UnaryExpression*, where @ stands for one of the operators in the above definitions, is evaluated as follows:

1. Let *left* be the result of evaluating *MultiplicativeExpression*.
2. Let *leftValue* be *GetValue(left)*.
3. *ReturnIfAbrupt(leftValue)*
4. Let *right* be the result of evaluating *UnaryExpression*.
5. Let *rightValue* be *GetValue(right)*.
6. Let *lnum* be *ToNumber(leftValue)*.
7. *ReturnIfAbrupt(lnum)*
8. Let *rnum* be *ToNumber(rightValue)*.
9. *ReturnIfAbrupt(rnum)*
10. Return the result of applying the specified operation (*, /, or %) to *lnum* and *rnum*. See the Notes below
11.5.1, 11.5.2, 11.5.3.

11.5.1 Applying the * Operator

The * operator performs multiplication, producing the product of its operands. Multiplication is commutative. Multiplication is not always associative in ECMAScript, because of finite precision.

The result of a floating-point multiplication is governed by the rules of IEEE 754 binary double-precision arithmetic:

- If either operand is **NaN**, the result is **NaN**.
- The sign of the result is positive if both operands have the same sign, negative if the operands have different signs.
- Multiplication of an infinity by a zero results in **NaN**.
- Multiplication of an infinity by an infinity results in an infinity. The sign is determined by the rule already stated above.
- Multiplication of an infinity by a finite nonzero value results in a signed infinity. The sign is determined by the rule already stated above.
- In the remaining cases, where neither an infinity or NaN is involved, the product is computed and rounded to the nearest representable value using IEEE 754 round-to-nearest mode. If the magnitude is too large to represent, the result is then an infinity of appropriate sign. If the magnitude is too small to represent, the result is then a zero of appropriate sign. The ECMAScript language requires support of gradual underflow as defined by IEEE 754.

11.5.2 Applying the / Operator

The / operator performs division, producing the quotient of its operands. The left operand is the dividend and the right operand is the divisor. ECMAScript does not perform integer division. The operands and result of all division operations are double-precision floating-point numbers. The result of division is determined by the specification of IEEE 754 arithmetic:

- If either operand is **NaN**, the result is **NaN**.
- The sign of the result is positive if both operands have the same sign, negative if the operands have different signs.
- Division of an infinity by an infinity results in **NaN**.
- Division of an infinity by a zero results in an infinity. The sign is determined by the rule already stated above.
- Division of an infinity by a nonzero finite value results in a signed infinity. The sign is determined by the rule already stated above.
- Division of a finite value by an infinity results in zero. The sign is determined by the rule already stated above.
- Division of a zero by a zero results in **NaN**; division of zero by any other finite value results in zero, with the sign determined by the rule already stated above.

Deleted: Semantics¶

Deleted: lval

Deleted: If *leftValue* is an abrupt completion, return *leftValue*.

Deleted: leftNum

Deleted: n

Deleted: If *leftNum* is an abrupt completion, return *leftNum*.

Deleted: rightNum

Deleted: n

Deleted: If *rightNum* is an abrupt completion, return *rightNum*.

Deleted: leftNum

Deleted: rightNum

- Division of a nonzero finite value by a zero results in a signed infinity. The sign is determined by the rule already stated above.
- In the remaining cases, where neither an infinity, nor a zero, nor **NaN** is involved, the quotient is computed and rounded to the nearest representable value using IEEE 754 round-to-nearest mode. If the magnitude is too large to represent, the operation overflows; the result is then an infinity of appropriate sign. If the magnitude is too small to represent, the operation underflows and the result is a zero of the appropriate sign. The ECMAScript language requires support of gradual underflow as defined by IEEE 754.

11.5.3 Applying the % Operator

The % operator yields the remainder of its operands from an implied division; the left operand is the dividend and the right operand is the divisor.

NOTE In C and C++, the remainder operator accepts only integral operands; in ECMAScript, it also accepts floating-point operands.

The result of a floating-point remainder operation as computed by the % operator is not the same as the “remainder” operation defined by IEEE 754. The IEEE 754 “remainder” operation computes the remainder from a rounding division, not a truncating division, and so its behaviour is not analogous to that of the usual integer remainder operator. Instead the ECMAScript language defines % on floating-point operations to behave in a manner analogous to that of the Java integer remainder operator; this may be compared with the C library function fmod.

The result of an ECMAScript floating-point remainder operation is determined by the rules of IEEE arithmetic:

- If either operand is **NaN**, the result is **NaN**.
- The sign of the result equals the sign of the dividend.
- If the dividend is an infinity, or the divisor is a zero, or both, the result is **NaN**.
- If the dividend is finite and the divisor is an infinity, the result equals the dividend.
- If the dividend is a zero and the divisor is nonzero and finite, the result is the same as the dividend.
- In the remaining cases, where neither an infinity, nor a zero, nor **NaN** is involved, the floating-point remainder r from a dividend n and a divisor d is defined by the mathematical relation $r = n - (d \times q)$ where q is an integer that is negative only if n/d is negative and positive only if n/d is positive, and whose magnitude is as large as possible without exceeding the magnitude of the true mathematical quotient of n and d. r is computed and rounded to the nearest representable value using IEEE 754 round-to-nearest mode.

11.6 Additive Operators

Syntax

```
AdditiveExpression :
  MultiplicativeExpression
  AdditiveExpression + MultiplicativeExpression
  AdditiveExpression - MultiplicativeExpression
```

Static Semantics: IsValidSimpleAssignmentTarget

```
AdditiveExpression :
  AdditiveExpression + MultiplicativeExpression
  AdditiveExpression - MultiplicativeExpression
```

1. Return false.

11.6.1 The Addition operator (+)

NOTE The addition operator either performs string concatenation or numeric addition.

Formatted: Font: 9 pt

Runtime Semantics: Evaluation

AdditiveExpression : AdditiveExpression + MultiplicativeExpression

1. Let *lref* be the result of evaluating AdditiveExpression.
2. Let *lval* be GetValue(*lref*).
3. *ReturnIfAbrupt(lval)*
4. Let *rref* be the result of evaluating MultiplicativeExpression.
5. Let *rval* be GetValue(*rref*).
6. *ReturnIfAbrupt(rval)*
7. Let *lprim* be ToPrimitive(*lval*).
8. *ReturnIfAbrupt(lprim)*
9. Let *rprim* be ToPrimitive(*rval*).
10. *ReturnIfAbrupt(rprim)*
11. If Type(*lprim*) is String or Type(*rprim*) is String, then
 - a. Return the String that is the result of concatenating ToString(*lprim*) followed by ToString(*rprim*)
12. Return the result of applying the addition operation to ToNumber(*lprim*) and ToNumber(*rprim*). See the Note below 11.6.3.

NOTE 1 No hint is provided in the calls to ToPrimitive in steps 5 and 6. All native ECMAScript objects except Date objects handle the absence of a hint as if the hint Number were given; Date objects handle the absence of a hint as if the hint String were given. Exotic objects may handle the absence of a hint in some other manner.

NOTE 2 Step 7 differs from step 3 of the comparison algorithm for the relational operators (11.8.1), by using the logical-or operation instead of the logical-and operation.

11.6.2 The Subtraction Operator (-)

Runtime Semantics: Evaluation

AdditiveExpression : AdditiveExpression - MultiplicativeExpression

1. Let *lref* be the result of evaluating AdditiveExpression.
2. Let *lval* be GetValue(*lref*).
3. *ReturnIfAbrupt(lval)*
4. Let *rref* be the result of evaluating MultiplicativeExpression.
5. Let *rval* be GetValue(*rref*).
6. *ReturnIfAbrupt(rval)*
7. Let *lnum* be ToNumber(*lval*).
8. *ReturnIfAbrupt(lnum)*
9. Let *rnum* be ToNumber(*rval*).
10. *ReturnIfAbrupt(rnum)*
11. Return the result of applying the subtraction operation to *lnum* and *rnum*. See the note below 11.6.3.

11.6.3 Applying the Additive Operators to Numbers

The + operator performs addition when applied to two operands of numeric type, producing the sum of the operands. The - operator performs subtraction, producing the difference of two numeric operands.

Addition is a commutative operation, but not always associative.

The result of an addition is determined using the rules of IEEE 754 binary double-precision arithmetic:

- If either operand is **NaN**, the result is **NaN**.
- The sum of two infinities of opposite sign is **NaN**.
- The sum of two infinities of the same sign is the infinity of that sign.
- The sum of an infinity and a finite value is equal to the infinite operand.
- The sum of two negative zeroes is **-0**. The sum of two positive zeroes, or of two zeroes of opposite sign, is **+0**.
- The sum of a zero and a nonzero finite value is equal to the nonzero operand.

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If *lval* is an abrupt completion, return *lval*.

Deleted: If *rval* is an abrupt completion, return *rval*.

Deleted: If *lprim* is an abrupt completion, return *lprim*.

Deleted: If *rprim* is an abrupt completion, return *rprim*.

Deleted: Host

Deleted: 5

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If *lval* is an abrupt completion, return *lval*

Deleted: If *rval* is an abrupt completion, return *rval*.

Deleted: If *lnum* is an abrupt completion, return *lnum*.

Deleted: If *rnum* is an abrupt completion, return *rnum*.

- The sum of two nonzero finite values of the same magnitude and opposite sign is **+0**.
- In the remaining cases, where neither an infinity, nor a zero, nor NaN is involved, and the operands have the same sign or have different magnitudes, the sum is computed and rounded to the nearest representable value using IEEE 754 round-to-nearest mode. If the magnitude is too large to represent, the operation overflows and the result is then an infinity of appropriate sign. The ECMAScript language requires support of gradual underflow as defined by IEEE 754.

The `-` operator performs subtraction when applied to two operands of numeric type, producing the difference of its operands; the left operand is the minuend and the right operand is the subtrahend. Given numeric operands a and b , it is always the case that $a - b$ produces the same result as $a + (-b)$.

11.7 Bitwise Shift Operators

Syntax

```
ShiftExpression :  
  AdditiveExpression  
  ShiftExpression << AdditiveExpression  
  ShiftExpression >> AdditiveExpression  
  ShiftExpression >>> AdditiveExpression
```

Static Semantics: IsValidSimpleAssignmentTarget

```
ShiftExpression :  
  ShiftExpression << AdditiveExpression  
  ShiftExpression >> AdditiveExpression  
  ShiftExpression >>> AdditiveExpression
```

1. [Return false.](#)

11.7.1 The Left Shift Operator (`<<`)

NOTE Performs a bitwise left shift operation on the left operand by the amount specified by the right operand.

Formatted: Font: 9 pt

Runtime Semantics: Evaluation

```
ShiftExpression : ShiftExpression << AdditiveExpression
```

Deleted: The production
Deleted: is evaluated as follows:

1. Let *lref* be the result of evaluating *ShiftExpression*.
2. Let *lval* be GetValue(*lref*).
3. [ReturnIfAbrupt\(*lval*\)](#)
4. Let *rref* be the result of evaluating *AdditiveExpression*.
5. Let *rval* be GetValue(*rref*).
6. [ReturnIfAbrupt\(*rval*\)](#)
7. Let *lnum* be ToInt32(*lval*).
8. [ReturnIfAbrupt\(*lnum*\)](#)
9. Let *rnum* be ToUint32(*rval*).
10. [ReturnIfAbrupt\(*rnum*\)](#)
11. Let *shiftCount* be the result of masking out all but the least significant 5 bits of *rnum*, that is, compute *rnum* & `0x1F`.
12. Return the result of left shifting *lnum* by *shiftCount* bits. The result is a signed 32-bit integer.

Deleted: If *lval* is an abrupt completion, return *lval*.

Deleted: If *rval* is an abrupt completion, return *rval*.

Deleted: *n*

Deleted: If *lnum* is an abrupt completion, return *lnum*.

Deleted: *n*

Deleted: If *rnum* is an abrupt completion, return *rnum*.

11.7.2 The Signed Right Shift Operator (`>>`)

NOTE Performs a sign-filling bitwise right shift operation on the left operand by the amount specified by the right operand.

Formatted: Font: 9 pt

Runtime Semantics: Evaluation

ShiftExpression : ShiftExpression >> AdditiveExpression

1. Let *lref* be the result of evaluating *ShiftExpression*.
2. Let *lval* be *GetValue(lref)*.
- 3. *ReturnIfAbrupt(lval)***
4. Let *rref* be the result of evaluating *AdditiveExpression*.
5. Let *rval* be *GetValue(rref)*.
- 6. *ReturnIfAbrupt(rval)***
7. Let *lnum* be *ToInt32(lval)*.
- 8. *ReturnIfAbrupt(lnum)***
9. Let *rnum* be *ToInt32(rval)*.
- 10. *ReturnIfAbrupt(rnum)***
11. Let *shiftCount* be the result of masking out all but the least significant 5 bits of *rnum*, that is, compute *rnum* & 0x1F.
12. Return the result of performing a sign-extending right shift of *lnum* by *shiftCount* bits. The most significant bit is propagated. The result is a signed 32-bit integer.

11.7.3 The Unsigned Right Shift Operator (>>>)

NOTE Performs a zero-filling bitwise right shift operation on the left operand by the amount specified by the right operand.

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If *lval* is an abrupt completion, return *lval*.

Deleted: If *rval* is an abrupt completion, return *rval*.

Deleted: *n*

Deleted: If *lnum* is an abrupt completion, return *lnum*.

Deleted: *n*

Deleted: If *rnum* is an abrupt completion, return *rnum*.

Runtime Semantics: Evaluation

ShiftExpression : ShiftExpression >>> AdditiveExpression

1. Let *lref* be the result of evaluating *ShiftExpression*.
2. Let *lval* be *GetValue(lref)*.
- 3. *ReturnIfAbrupt(lval)***
4. Let *rref* be the result of evaluating *AdditiveExpression*.
5. Let *rval* be *GetValue(rref)*.
- 6. *ReturnIfAbrupt(rval)***
7. Let *lnum* be *ToInt32(lval)*.
- 8. *ReturnIfAbrupt(lnum)***
9. Let *rnum* be *ToInt32(rval)*.
- 10. *ReturnIfAbrupt(rnum)***
11. Let *shiftCount* be the result of masking out all but the least significant 5 bits of *rnum*, that is, compute *rnum* & 0x1F.
12. Return the result of performing a zero-filling right shift of *lnum* by *shiftCount* bits. Vacated bits are filled with zero. The result is an unsigned 32-bit integer.

11.8 Relational Operators

NOTE The result of evaluating a relational operator is always of type Boolean, reflecting whether the relationship named by the operator holds between its two operands.

Formatted: Font: 9 pt

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If *lval* is an abrupt completion, return *lval*.

Deleted: If *rval* is an abrupt completion, return *rval*.

Deleted: *n*

Deleted: If *lnum* is an abrupt completion, return *lnum*.

Deleted: *n*

Deleted: If *rnum* is an abrupt completion, return *rnum*.

Syntax

```
RelationalExpression :
  ShiftExpression
  RelationalExpression < ShiftExpression
  RelationalExpression > ShiftExpression
  RelationalExpression <= ShiftExpression
  RelationalExpression >= ShiftExpression
  RelationalExpression instanceof ShiftExpression
  RelationalExpression in ShiftExpression
```

Formatted: Font: 9 pt

RelationalExpressionNoIn :

```

ShiftExpression
RelationalExpressionNoIn < ShiftExpression
RelationalExpressionNoIn > ShiftExpression
RelationalExpressionNoIn <= ShiftExpression
RelationalExpressionNoIn >= ShiftExpression
RelationalExpressionNoIn instanceof ShiftExpression

```

The semantics of the *RelationalExpressionNoIn* productions are the same as the *RelationalExpression* productions except that the contained *RelationalExpressionNoIn* is used in place of the contained *RelationalExpression*.

NOTE The “*NoIn*” variants are needed to avoid confusing the *in* operator in a relational expression with the *in* operator in a *for* statement.

Deleted: evaluated in
Deleted: manner
Deleted: evaluated instead

Static Semantics: IsValidSimpleAssignmentTarget

RelationalExpression :

```

RelationalExpression < ShiftExpression
RelationalExpression > ShiftExpression
RelationalExpression <= ShiftExpression
RelationalExpression >= ShiftExpression
RelationalExpression instanceof ShiftExpression
RelationalExpression in ShiftExpression

```

1. Return false.

11.8.1 Runtime Semantics

Runtime Semantics: The Abstract Relational Comparison Algorithm

The comparison $x < y$, where x and y are values, produces **true**, **false**, or **undefined** (which indicates that at least one operand is **NaN**). In addition to x and y the algorithm takes a Boolean flag named *LeftFirst* as a parameter. The flag is used to control the order in which operations with potentially visible side-effects are performed upon x and y . It is necessary because ECMAScript specifies left to right evaluation of expressions. The default value of *LeftFirst* is **true** and indicates that the x parameter corresponds to an expression that occurs to the left of the y parameter’s corresponding expression. If *LeftFirst* is **false**, the reverse is the case and operations must be performed upon y before x . Such a comparison is performed as follows:

Deleted: Semantics¶
The result of evaluating a relational operator always of type Boolean, reflecting whether the relationship named by the operator holds between its two operands.¶
The *RelationalExpressionNoIn* productions are evaluated in the same manner as the *RelationalExpression* productions except that the contained *RelationalExpressionNoIn* is evaluated instead of the contained *RelationalExpression*.

1. ReturnIfAbrupt(x)

Deleted: If x is an abrupt completion, return x .

2. ReturnIfAbrupt(y)

Deleted: If y is an abrupt completion, return y .

3. If the *LeftFirst* flag is **true**, then
 - a. Let px be the result of calling *ToPrimitive*(x , hint Number).
 - b. ReturnIfAbrupt(px)
 - c. Let py be the result of calling *ToPrimitive*(y , hint Number).
 - d. ReturnIfAbrupt(py)
4. Else the order of evaluation needs to be reversed to preserve left to right evaluation
 - a. Let py be the result of calling *ToPrimitive*(y , hint Number).
 - b. ReturnIfAbrupt(py)
 - c. Let px be the result of calling *ToPrimitive*(x , hint Number).
 - d. ReturnIfAbrupt(px)
5. If it is not the case that both *Type(px)* is String and *Type(py)* is String, then
 - a. Let nx be the result of calling *ToNumber*(px). Because px and py are primitive values evaluation order is not important.
 - b. Let ny be the result of calling *ToNumber*(py).
 - c. If nx is **NaN**, return **undefined**.
 - d. If ny is **NaN**, return **undefined**.
 - e. If nx and ny are the same Number value, return **false**.
 - f. If nx is **+0** and ny is **-0**, return **false**.

Deleted: If px is an abrupt completion, return px .

Deleted: If py is an abrupt completion, return py .

Deleted: If py is an abrupt completion, return py .

Deleted: If px is an abrupt completion, return px .

Deleted: If py is an abrupt completion, return py .

- g. If nx is -0 and ny is $+0$, return **false**.
 - h. If nx is $+\infty$, return **false**.
 - i. If ny is $+\infty$, return **true**.
 - j. If ny is $-\infty$, return **false**.
 - k. If nx is $-\infty$, return **true**.
 - l. If the mathematical value of nx is less than the mathematical value of ny —note that these mathematical values are both finite and not both zero—return **true**. Otherwise, return **false**.
6. Else, both px and py are Strings
- a. If py is a prefix of px , return **false**. (A String value p is a prefix of String value q if q can be the result of concatenating p and some other String r . Note that any String is a prefix of itself, because r may be the empty String.)
 - b. If px is a prefix of py , return **true**.
 - c. Let k be the smallest nonnegative integer such that the character at position k within px is different from the character at position k within py . (There must be such a k , for neither String is a prefix of the other.)
 - d. Let m be the integer that is the code unit value for the character at position k within px .
 - e. Let n be the integer that is the code unit value for the character at position k within py .
 - f. If $m < n$, return **true**. Otherwise, return **false**.

NOTE 1 Step 3 differs from step 7 in the algorithm for the addition operator + (11.6.1) in using and instead of or.

NOTE 2 The comparison of Strings uses a simple lexicographic ordering on sequences of code unit values. There is no attempt to use the more complex, semantically oriented definitions of character or string equality and collating order defined in the Unicode specification. Therefore String values that are canonically equal according to the Unicode standard could test as unequal. In effect this algorithm assumes that both Strings are already in normalised form. Also, note that for strings containing supplementary characters, lexicographic ordering on sequences of UTF-16 code unit values differs from that on sequences of code point values.

Formatted: Note

Runtime Semantics: Evaluation

RelationalExpression : RelationalExpression < ShiftExpression

1. Let $lref$ be the result of evaluating *RelationalExpression*.
2. Let $lval$ be *GetValue(lref)*.
3. *ReturnIfAbrupt(lval)*
4. Let $rref$ be the result of evaluating *ShiftExpression*.
5. Let $rval$ be *GetValue(rref)*.
6. Let r be the result of performing abstract relational comparison $lval < rval$. (see 11.8.5)
7. *ReturnIfAbrupt(r)*
8. If r is **undefined**, return **false**. Otherwise, return r .

RelationalExpression : RelationalExpression > ShiftExpression

1. Let $lref$ be the result of evaluating *RelationalExpression*.
2. Let $lval$ be *GetValue(lref)*.
3. *ReturnIfAbrupt(lval)*
4. Let $rref$ be the result of evaluating *ShiftExpression*.
5. Let $rval$ be *GetValue(rref)*.
6. Let r be the result of performing abstract relational comparison $rval < lval$ with *LeftFirst* equal to **false**.
7. *ReturnIfAbrupt(r)*
8. If r is **undefined**, return **false**. Otherwise, return r .

RelationalExpression : RelationalExpression <= ShiftExpression

1. Let $lref$ be the result of evaluating *RelationalExpression*.
2. Let $lval$ be *GetValue(lref)*.
3. *ReturnIfAbrupt(lval)*
4. Let $rref$ be the result of evaluating *ShiftExpression*.
5. Let $rval$ be *GetValue(rref)*.

Deleted: 11.8.1 The Less-than Operator ($<$)
The production

Deleted: is evaluated as follows:

Deleted: If $lval$ is an abrupt completion, return $lval$.

Deleted: 11.8.2 . The Greater-than Operator ($>$)
The production

Deleted: is evaluated as follows:

Deleted: If $lval$ is an abrupt completion, return $lval$.

Deleted: (see 11.8.5)

Deleted: 11.8.3 The Less-than-or-equal Operator (\leq)
The production

Deleted: is evaluated as follows:

Deleted: If $lval$ is an abrupt completion, return $lval$.

6. Let r be the result of performing abstract relational comparison $rval < lval$ with $LeftFirst$ equal to **false**.
7. **ReturnIfAbrupt(r)**
8. If r is **true** or **undefined**, return **false**. Otherwise, return **true**.

Deleted: (see 11.8.5)

RelationalExpression : RelationalExpression \geq ShiftExpression

1. Let $lref$ be the result of evaluating *RelationalExpression*.
2. Let $lval$ be *GetValue(lref)*.
3. **ReturnIfAbrupt(lval)**
4. Let $rref$ be the result of evaluating *ShiftExpression*.
5. Let $rval$ be *GetValue(rref)*.
6. Let r be the result of performing abstract relational comparison $lval < rval$.
7. **ReturnIfAbrupt(r)**
8. If r is **true** or **undefined**, return **false**. Otherwise, return **true**.

Deleted: 11.8.4 The Greater-than-or-equal Operator (\geq)
The production

Deleted: is evaluated as follows:

Deleted: If $lval$ is an abrupt completion, return $lval$.

Deleted: (see 11.8.5)

RelationalExpression : RelationalExpression instanceof ShiftExpression

1. Let $lref$ be the result of evaluating *RelationalExpression*.
2. Let $lval$ be *GetValue(lref)*.
3. **ReturnIfAbrupt(lval)**
4. Let $rref$ be the result of evaluating *ShiftExpression*.
5. Let $rval$ be *GetValue(rref)*.
6. **ReturnIfAbrupt(rval)**
7. If *Type(rval)* is not **Object**, throw a **TypeError** exception.
8. If $rval$ does not have a **[[HasInstance]]** internal method, throw a **TypeError** exception.
9. Return the result of calling the **[[HasInstance]]** internal method of $rval$ with argument $lval$.

Deleted: is evaluated as follows:

Deleted: If $lval$ is an abrupt completion, return $lval$.

Deleted: If $rval$ is an abrupt completion, return $rval$.

RelationalExpression : RelationalExpression in ShiftExpression

1. Let $lref$ be the result of evaluating *RelationalExpression*.
2. Let $lval$ be *GetValue(lref)*.
3. **ReturnIfAbrupt(lval)**
4. Let $rref$ be the result of evaluating *ShiftExpression*.
5. Let $rval$ be *GetValue(rref)*.
6. **ReturnIfAbrupt(rval)**
7. If *Type(rval)* is not **Object**, throw a **TypeError** exception.
8. Return the result of calling the **[[HasProperty]]** internal method of $rval$ with argument *ToString(lval)*.

Deleted: 11.8.7 . The in operator
The production

Deleted: is evaluated as follows:

Deleted: If $lval$ is an abrupt completion, return $lval$.

Deleted: If $rval$ is an abrupt completion, return $rval$.

11.9 Equality Operators

NOTE The result of evaluating an equality operator is always of type Boolean, reflecting whether the relationship named by the operator holds between its two operands.

Formatted: Note

Syntax

EqualityExpression :

```

RelationalExpression
EqualityExpression == RelationalExpression
EqualityExpression != RelationalExpression
EqualityExpression ==== RelationalExpression
EqualityExpression !==== RelationalExpression
EqualityExpression [no LineTerminator here] is RelationalExpression
EqualityExpression [no LineTerminator here] isnt RelationalExpression

```

EqualityExpressionNoIn :

RelationalExpressionNoIn
EqualityExpressionNoIn == RelationalExpressionNoIn
EqualityExpressionNoIn != RelationalExpressionNoIn
EqualityExpressionNoIn === RelationalExpressionNoIn
EqualityExpressionNoIn !== RelationalExpressionNoIn
EqualityExpression [no LineTerminator here] is RelationalExpression
EqualityExpression [no LineTerminator here] isnt RelationalExpression

The semantics of the *EqualityExpressionNoIn* productions are the same as the *EqualityExpression* productions except that the contained *EqualityExpressionNoIn* and *RelationalExpressionNoIn* are used in place of the contained *EqualityExpression* and *RelationalExpression*, respectively.

Static Semantics: IsValidSimpleAssignmentTarget

EqualityExpression :

EqualityExpression == RelationalExpression
EqualityExpression != RelationalExpression
EqualityExpression === RelationalExpression
EqualityExpression !== RelationalExpression
EqualityExpression [no LineTerminator here] is RelationalExpression
EqualityExpression [no LineTerminator here] isnt RelationalExpression

1. Return **false**.

11.9.1 Runtime Semantics

Runtime Semantics: The Abstract Equality Comparison Algorithm

The comparison $x == y$, where x and y are values, produces **true** or **false**. Such a comparison is performed as follows:

1. If $\text{Type}(x)$ is the same as $\text{Type}(y)$, then
 - a. Return the result of performing strict equality comparison algorithm $x === y$.
2. If x is **null** and y is **undefined**, return **true**.
3. If x is **undefined** and y is **null**, return **true**.
4. If $\text{Type}(x)$ is **Number** and $\text{Type}(y)$ is **String**,
return the result of the comparison $x == \text{ToNumber}(y)$.
5. If $\text{Type}(x)$ is **String** and $\text{Type}(y)$ is **Number**,
return the result of the comparison $\text{ToNumber}(x) == y$.
6. If $\text{Type}(x)$ is **Boolean**, return the result of the comparison $\text{ToNumber}(x) == y$.
7. If $\text{Type}(y)$ is **Boolean**, return the result of the comparison $x == \text{ToNumber}(y)$.
8. If $\text{Type}(x)$ is either **String** or **Number** and $\text{Type}(y)$ is **Object**,
return the result of the comparison $x == \text{ToPrimitive}(y)$.
9. If $\text{Type}(x)$ is **Object** and $\text{Type}(y)$ is either **String** or **Number**,
return the result of the comparison $\text{ToPrimitive}(x) == y$.
10. Return **false**.

NOTE 1 Given the above definition of equality:

- String comparison can be forced by: `" " + a == " " + b`.
- Numeric comparison can be forced by: `+a == +b`.
- Boolean comparison can be forced by: `!a == !b`.

NOTE 2 The equality operators maintain the following invariants:

- $A != B$ is equivalent to $!(A == B)$.
- $A == B$ is equivalent to $B == A$, except in the order of evaluation of A and B .

Deleted: Semantics

The result of evaluating an equality operator is always type Boolean, reflecting whether the relationship name by the operator holds between its two operands.¶

Deleted: evaluated in

Deleted: manner

Deleted: evaluated instead

Deleted: 1

Deleted: <#>`ReturnIfAbrupt(x)`. If x is an abrupt completion, return x .¶
<#>`ReturnIfAbrupt(y)`. If y is an abrupt completion, return y .¶

Deleted: <#> If $\text{Type}(x)$ is **Undefined**, return **true**.¶

<#> If $\text{Type}(x)$ is **Null**, return **true**.¶
<#> If $\text{Type}(x)$ is **Number**, then¶
<#> If x is **NaN**, return **false**.¶
<#> If y is **NaN**, return **false**.¶
<#> If x is the same Number value as y , return **true**.¶
<#> If x is **+0** and y is **-0**, return **true**.¶
<#> If x is **-0** and y is **+0**, return **true**.¶
<#> Return **false**.¶
<#> If $\text{Type}(x)$ is **String**, then return **true** if x and y are exactly the same sequence of characters (same length and same characters in corresponding positions). Otherwise, return **false**.¶
<#> If $\text{Type}(x)$ is **Boolean**, return **true** if x and y are both **true** or both **false**. Otherwise, return **false**.¶
<#> Return **true** if x and y refer to the same objectObject value. Otherwise, return **false**.¶

NOTE 3 The equality operator is not always transitive. For example, there might be two distinct String objects, each representing the same String value; each String object would be considered equal to the String value by the `==` operator, but the two String objects would not be equal to each other. For Example:

- `new String("a") == "a"` and `"a" == new String("a")` are both **true**.
- `new String("a") == new String("a")` is **false**.

NOTE 4 Comparison of Strings uses a simple equality test on sequences of code unit values. There is no attempt to use the more complex, semantically oriented definitions of character or string equality and collating order defined in the Unicode specification. Therefore Strings values that are canonically equal according to the Unicode standard could test as unequal. In effect this algorithm assumes that both Strings are already in normalised form.

Runtime Semantics: The Strict Equality Comparison Algorithm

The comparison `x === y`, where `x` and `y` are values, produces **true** or **false**. Such a comparison is performed as follows:

1. If `Type(x)` is different from `Type(y)`, return **false**.
2. If `Type(x)` is **Undefined**, return **true**.
3. If `Type(x)` is **Null**, return **true**.
4. If `Type(x)` is **Number**, then
 - a. If `x` is **NaN**, return **false**.
 - b. If `y` is **NaN**, return **false**.
 - c. If `x` is the same Number value as `y`, return **true**.
 - d. If `x` is **+0** and `y` is **-0**, return **true**.
 - e. If `x` is **-0** and `y` is **+0**, return **true**.
 - f. Return **false**.
5. If `Type(x)` is **String**, then
 - a. If `x` and `y` are exactly the same sequence of characters (same length and same characters in corresponding positions), return **true**.
 - b. Else, return **false**.
6. If `Type(x)` is **Boolean**, then
 - a. If `x` and `y` are both **true** or both **false**, return **true**.
 - b. Else, return **false**.
7. If `x` and `y` are the same **Object** value, return **true**.
8. Return **false**.

NOTE This algorithm differs from the **SameValue Algorithm** (9.12) in its treatment of signed zeroes and NaNs.

Runtime Semantics: Evaluation

EqualityExpression : EqualityExpression == RelationalExpression

1. Let `lref` be the result of evaluating `EqualityExpression`.
2. Let `lval` be `GetValue(lref)`.
3. ReturnIfAbrupt(`lval`).
4. Let `rref` be the result of evaluating `RelationalExpression`.
5. Let `rval` be `GetValue(rref)`.
6. ReturnIfAbrupt(`rval`).
7. Return the result of performing abstract equality comparison algorithm `rval == lval`.

EqualityExpression : EqualityExpression != RelationalExpression

1. Let `lref` be the result of evaluating `EqualityExpression`.
2. Let `lval` be `GetValue(lref)`.
3. ReturnIfAbrupt(`lval`).
4. Let `rref` be the result of evaluating `RelationalExpression`.
5. Let `rval` be `GetValue(rref)`.
6. ReturnIfAbrupt(`rval`).
7. Let `r` be the result of performing abstract equality comparison algorithm `rval == lval`.
8. If `r` is **true**, return **false**. Otherwise, return **true**.

Deleted: <#>`ReturnIfAbrupt(x)`. If `x` is an abrupt completion, return `x`.
 <#>`ReturnIfAbrupt(y)`. If `y` is an abrupt completion, return `y`.

Deleted: `return true` i

Deleted: ; otherwise

Deleted: `return true` i

Deleted: ;

Deleted: otherwise

Deleted: `Return true` i

Deleted: refer to

Deleted: object

Deleted: .

Deleted: Otherwise, r

Deleted: 11.9.1 The Equals Operator (`==`)
 The production

Deleted: is evaluated as follows:

Deleted: If `lval` is an abrupt completion, return `lval`.

Deleted: (see 11.9.3).

Deleted: 11.9.2 . The Does-not-equals Operator (`!=`)
 The production

Deleted: is evaluated as follows:

Deleted: If `lval` is an abrupt completion, return `lval`.

Deleted: If `rval` is an abrupt completion, return `rval`.

Deleted: (see 11.9.3).

EqualityExpression : *EqualityExpression* **====** *RelationalExpression*

1. Let *lref* be the result of evaluating *EqualityExpression*.
2. Let *lval* be *GetValue(lref)*.
- 3. *ReturnIfAbrupt(lval)***
4. Let *rref* be the result of evaluating *RelationalExpression*.
5. Let *rval* be *GetValue(rref)*.
- 6. *ReturnIfAbrupt(rval)***
7. Return the result of performing the strict equality comparison *algorithm rval === lval*.

Deleted: 11.9.4 The Strict Equals Operator (**====**)
The production

Deleted: is evaluated as follows:

Deleted: If *lval* is an abrupt completion, return *lval*.

EqualityExpression : *EqualityExpression* **!==** *RelationalExpression*

1. Let *lref* be the result of evaluating *EqualityExpression*.
2. Let *lval* be *GetValue(lref)*.
- 3. *ReturnIfAbrupt(lval)***
4. Let *rref* be the result of evaluating *RelationalExpression*.
5. Let *rval* be *GetValue(rref)*.
- 6. *ReturnIfAbrupt(r)***
7. Let *r* be the result of performing strict equality comparison *algorithm rval === lval*.
8. If *r* is **true**, return **false**. Otherwise, return **true**.

Deleted: (See 11.9.6)

Deleted: 11.9.5 . The Strict Does-not-equal Operator
(**!==**)
The production

Deleted: is evaluated as follows:

Deleted: If *lval* is an abrupt completion, return *lval*.

EqualityExpression : *EqualityExpression* [*no LineTerminator here*] **is** *RelationalExpression*

1. Let *lref* be the result of evaluating *EqualityExpression*.
2. Let *lval* be *GetValue(lref)*.
- 3. *ReturnIfAbrupt(lval)***
4. Let *rref* be the result of evaluating *RelationalExpression*.
- 5. *Let rval be GetValue(rref)***
6. Return the result of performing *SameValue(rval, lval)*.

Deleted: If *lval* is an abrupt completion, return *lval*.

Deleted: If *rval* is an abrupt completion, return *rval*.

Deleted: **v**

EqualityExpression : *EqualityExpression* [*no LineTerminator here*] **isnt** *RelationalExpression*

1. Let *lref* be the result of evaluating *EqualityExpression*.
2. Let *lval* be *GetValue(lref)*.
- 3. *ReturnIfAbrupt(lval)***
4. Let *rref* be the result of evaluating *RelationalExpression*.
- 5. *Let rval be GetValue(rref)***
6. Let *r* be the result of performing *SameValue(rval, lval)*.
7. *ReturnIfAbrupt(r)*.
8. If *r* is **true**, return **false**. Otherwise, return **true**.

Deleted: If *lval* is an abrupt completion, return *lval*.

Deleted: **v**

11.10 Binary Bitwise Operators

Syntax

BitwiseANDExpression :
EqualityExpression
BitwiseANDExpression **&** *EqualityExpression*

BitwiseANDExpressionNoIn :
EqualityExpressionNoIn
BitwiseANDExpressionNoIn **&** *EqualityExpressionNoIn*

BitwiseXORExpression :
BitwiseANDExpression
BitwiseXORExpression **^** *BitwiseANDExpression*

BitwiseXORExpressionNoIn :
BitwiseANDExpressionNoIn
BitwiseXORExpressionNoIn **^** *BitwiseANDExpressionNoIn*

BitwiseORExpression :
BitwiseXORExpression
BitwiseORExpression | *BitwiseXORExpression*

BitwiseORExpressionNoIn :
BitwiseXORExpressionNoIn
BitwiseORExpressionNoIn | *BitwiseXORExpressionNoIn*

Static Semantics: IsValidSimpleAssignmentTarget

BitwiseANDExpression : *BitwiseANDExpression & EqualityExpression*
BitwiseXORExpression : *BitwiseXORExpression ^ BitwiseANDExpression*
BitwiseORExpression : *BitwiseORExpression | BitwiseXORExpression*

1. Return false.

Runtime Semantics: Evaluation

The production $A : A @ B$, where $@$ is one of the bitwise operators in the productions above, is evaluated as follows:

1. Let $lref$ be the result of evaluating A .
2. Let $lval$ be $\text{GetValue}(lref)$.
3. ReturnIfAbrupt($lval$)
4. Let $rref$ be the result of evaluating B .
5. Let $rval$ be $\text{GetValue}(rref)$.
6. ReturnIfAbrupt($rval$)
7. Let $lnum$ be $\text{ToInt32}(lval)$.
8. ReturnIfAbrupt($lnum$)
9. Let $rnum$ be $\text{ToInt32}(rval)$.
10. ReturnIfAbrupt($rnum$)
11. Return the result of applying the bitwise operator $@$ to $lnum$ and $rnum$. The result is a signed 32 bit integer.

Deleted: Semantics¶

Deleted: If $lval$ is an abrupt completion, return $lval$.

Deleted: If $rval$ is an abrupt completion, return $rval$.

Deleted: If $lnum$ is an abrupt completion, return $lnum$.

Deleted: If $rnum$ is an abrupt completion, return $rnum$.

11.11 Binary Logical Operators

Syntax

LogicalANDExpression :
BitwiseORExpression
LogicalANDExpression && BitwiseORExpression

LogicalANDExpressionNoIn :
BitwiseORExpressionNoIn
LogicalANDExpressionNoIn && BitwiseORExpressionNoIn

LogicalORExpression :
LogicalANDExpression
LogicalORExpression || LogicalANDExpression

LogicalORExpressionNoIn :
LogicalANDExpressionNoIn
LogicalORExpressionNoIn || LogicalANDExpressionNoIn

The semantics of the *LogicalANDExpressionNoIn* and *LogicalORExpressionNoIn* productions are the same manner as the *LogicalANDExpression* and *LogicalORExpression* productions except that the contained *LogicalANDExpressionNoIn*, *BitwiseORExpressionNoIn* and *LogicalORExpressionNoIn* are used in place of the contained *LogicalANDExpression*, *BitwiseORExpression* and *LogicalORExpression*, respectively.

Deleted: evaluated in

Deleted: evaluated instead

NOTE The value produced by a **&&** or **||** operator is not necessarily of type Boolean. The value produced will always be the value of one of the two operand expressions.

Static Semantics: IsValidSimpleAssignmentTarget

LogicalANDExpression : LogicalANDExpression && BitwiseORExpression

LogicalORExpression : LogicalORExpression || LogicalANDExpression

1. Return false.

Runtime Semantics: Evaluation

LogicalANDExpression : LogicalANDExpression && BitwiseORExpression

1. Let *lref* be the result of evaluating *LogicalANDExpression*.
2. Let *lval* be ToBoolean(*GetValue(lref)*).
3. ReturnIfAbrupt(*lval*).
4. If *lval* is false, return *lval*.
5. Let *rref* be the result of evaluating *BitwiseORExpression*.
6. Return *GetValue(rref)*.

LogicalORExpression : LogicalORExpression || LogicalANDExpression

1. Let *lref* be the result of evaluating *LogicalORExpression*.
2. Let *lval* be ToBoolean(*GetValue(lref)*).
3. ReturnIfAbrupt(*lval*).
4. If *lval* is true, return *lval*.
5. Let *rref* be the result of evaluating *LogicalANDExpression*.
6. Return *GetValue(rref)*.

11.12 Conditional Operator (? :)

Syntax

ConditionalExpression :
LogicalORExpression
LogicalORExpression ? AssignmentExpression : AssignmentExpression

ConditionalExpressionNoIn :
LogicalORExpressionNoIn
LogicalORExpressionNoIn ? AssignmentExpression : AssignmentExpressionNoIn

The semantics of the *ConditionalExpressionNoIn* production is the same as the *ConditionalExpression* production except that the contained *LogicalORExpressionNoIn*, *AssignmentExpression* and *AssignmentExpressionNoIn* are used in place of the contained *LogicalORExpression*, first *AssignmentExpression* and second *AssignmentExpression*, respectively.

NOTE The grammar for a *ConditionalExpression* in ECMAScript is a little bit different from that in C and Java, which each allow the second subexpression to be an Expression but restrict the third expression to be a *ConditionalExpression*. The motivation for this difference in ECMAScript is to allow an assignment expression to be governed by either arm of a conditional and to eliminate the confusing and fairly useless case of a comma expression as the centre expression.

Static Semantics: IsValidSimpleAssignmentTarget

ConditionalExpression : LogicalORExpression ? AssignmentExpression : AssignmentExpression

1. Return false.

Runtime Semantics: Evaluation

ConditionalExpression : LogicalORExpression ? AssignmentExpression : AssignmentExpression

1. Let *lref* be the result of evaluating *LogicalORExpression*.

Deleted: Semantics¶
The production

Deleted: is evaluated as follows:

Deleted: If *lval* is an abrupt completion, return *lval*.

Deleted: *ToBoolean(lval)*

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If *lval* is an abrupt completion, return *lval*.

Deleted: *ToBoolean(lval)*

Deleted: The *LogicalANDExpressionNoIn* and *LogicalORExpressionNoIn* productions are evaluated in the same manner as the *LogicalANDExpression* and *LogicalORExpression* productions except that the contained *LogicalANDExpressionNoIn*, *BitwiseORExpressionNoIn* and *LogicalORExpressionNoIn* are evaluated instead of the contained *LogicalANDExpression*, *BitwiseORExpression* and *LogicalORExpression*, respectively.
NOTE The value produced by a **&&** or **||** operator is not necessarily of type Boolean. The value produced will always be the value of one of the two operand expressions.¶

Deleted: evaluated in

Deleted: manner

Deleted: evaluated instead

2. Let *lval* be ToBoolean(GetValue(*lref*)).

3. ReturnIfAbrupt(*lval*).

4. If *lval* is true, then

- a. Let *trueRef* be the result of evaluating the first *AssignmentExpression*.
- b. Return GetValue(*trueRef*).

5. Else

- a. Let *falseRef* be the result of evaluating the second *AssignmentExpression*.
- b. Return GetValue(*falseRef*).

11.13 Assignment Operators

Syntax

AssignmentExpression :

ConditionalExpression

YieldExpression

ArrowFunction

LeftHandSideExpression = *AssignmentExpression*

LeftHandSideExpression *AssignmentOperator* *AssignmentExpression*

AssignmentExpressionNoIn :

ConditionalExpressionNoIn

YieldExpression

ArrowFunction

LeftHandSideExpression = *AssignmentExpressionNoIn*

LeftHandSideExpression *AssignmentOperator* *AssignmentExpressionNoIn*

AssignmentOperator : one of

 *= /= %= += -= <<= >>= >>>= &= ^= |=

The semantics of the *AssignmentExpressionNoIn* productions are the same manner as the *AssignmentExpression* productions except that the contained *ConditionalExpressionNoIn* and *AssignmentExpressionNoIn* are used in place of the contained *ConditionalExpression* and *AssignmentExpression*, respectively.

Static Semantics

Static Semantics: Early Errors

AssignmentExpression : *LeftHandSideExpression* = *AssignmentExpression*

- It is a Syntax Error if *LeftHandSideExpression* is either an *ObjectLiteral* or an *ArrayLiteral* and if the lexical token sequence matched by *LeftHandSideExpression* cannot be parsed with no tokens left over using *AssignmentPattern* as the goal symbol.
- If *LeftHandSideExpression* is either an *ObjectLiteral* or an *ArrayLiteral* and if the lexical token sequence matched by *LeftHandSideExpression* can be parsed with no tokens left over using *AssignmentPattern* as the goal symbol then the following rules are not applied. Instead, the Early Error rules for *AssignmentPattern* are used.
- It is a Syntax Error if the *LeftHandSideExpression* is an *Identifier* that can be statically determined to always resolve to a declarative environment record binding and the resolved binding is an immutable binding.
- It is an early Reference Error if *LeftHandSideExpression* is neither an *ObjectLiteral* nor an *ArrayLiteral* and *IsValidSimpleAssignmentTarget* of *LeftHandSideExpression* is false.

AssignmentExpression : *LeftHandSideExpression* *AssignmentOperator* *AssignmentExpression*

- It is a Syntax Error if the *LeftHandSideExpression* is an *Identifier* that can be statically determined to always resolve to a declarative environment record binding and the resolved binding is an immutable binding.
- It is an early Reference Error if *IsValidSimpleAssignmentTarget* of *LeftHandSideExpression* is false.

Deleted: If *lval* is an abrupt completion, return *lval*.

Deleted: ToBoolean(GetValue(*lref*))

Deleted: Supplemental Syntax¶

In certain circumstances when processing the production *AssignmentExpression* :
LeftHandSideExpression = *AssignmentExpression* the following grammar is used to refine the interpretation of *LeftHandSideExpression*.¶

AssignmentPattern :¶
ObjectAssignmentPattern
ArrayAssignmentPattern ¶
ObjectAssignmentPattern :¶
{ } ..
{ *AssignmentPropertyList* }
{ *AssignmentPropertyList* , } ¶
ArrayAssignmentPattern.¶
[*Elision*_opt *AssignmentRestElement*_opt]
[*AssignmentElementList* , *Elision*_opt]
*AssignmentRestElement*_opt] ¶
AssignmentPropertyList :¶
AssignmentProperty
AssignmentPropertyList ,
AssignmentProperty ¶
AssignmentElementList :¶
*Elision*_opt *AssignmentElement* ..
AssignmentElementList , *Elision*_opt
AssignmentElement ¶
AssignmentProperty :¶
Identifier
PropertyName : *LeftHandSideExpression*
AssignmentElement :¶
LeftHandSideExpression ¶
AssignmentRestElement :¶
... *LeftHandSideExpression* ¶

Deleted: *AssignmentExpression* :¶

LeftHandSideExpression = *AssignmentExpression*
LeftHandSideExpression *AssignmentOperator*
AssignmentExpression ¶

¶#Semantics¶

¶#11.13.1 Simple Assignment (=)¶

¶#The static semantics of *AssignmentExpression* : *LeftHandSideExpression* *AssignmentExpression* are:¶

¶#It is a Syntax Error if the *AssignmentExpression* is contained in strict code and the *LeftHandSideExpression* is the *Identifier* eval or the *Identifier* arguments.¶

¶#It is a Syntax Error if the *AssignmentExpression* is contained in extended code and the *LeftHandSideExpression* is the *Identifier* this or the *Identifier* super.¶

¶#It is a Syntax Error if the *AssignmentExpression* is contained in extended code and the *LeftHandSideExpression* is a *Literal* or a *FunctionExpression*.¶

¶#It is a Syntax Error if the *AssignmentExpression* is contained in extended code and the *LeftHandSideExpression* is an *Identifier* that can be does not statically determine to always resolves to a declarative environment record binding or and the resolved binding is an immutable binding.¶

Deleted: ¶#It is a Syntax Error if the *AssignmentExpression* is contained in extended code and *IsInvalidAssignmentPattern* of the *LeftHandSideExpression* is an *ObjectLiteral* or a *ArrayLiteral* and the source code corresponding *LeftHandSideExpression* cannot be parsed using *AssignmentPattern* as the goal symboltrue.¶

Static Semantics: IsValidSimpleAssignmentTarget

AssignmentExpression :
YieldExpression
ArrowFunction
LeftHandSideExpression = AssignmentExpression
LeftHandSideExpression AssignmentOperator AssignmentExpression

1. Return **false**.

Runtime Semantics

Runtime Semantics: Evaluation

AssignmentExpression : LeftHandSideExpression = AssignmentExpression

1. If LeftHandSideExpression is neither an ObjectLiteral nor an ArrayLiteral then
 - a. Let lref be the result of evaluating LeftHandSideExpression.
 - b. ReturnIfAbrupt(lref).
 - c. Let rref be the result of evaluating AssignmentExpression.
 - d. Let rval be GetValue(rref).
 - e. Let status be PutValue(lref, rval).
 - f. ReturnIfAbrupt(status).
 - g. Return rval.
2. Let AssignmentPattern be the parse of the source code corresponding to LeftHandSideExpression using AssignmentPattern as the goal symbol.
3. Let rref be the result of evaluating AssignmentExpression.
4. Let rval be ToObject(GetValue(rref)).
5. ReturnIfAbrupt(rval).
6. Let status be the result of performing Destructuring Assignment Evaluation of AssignmentPattern using rval as the argument.
7. ReturnIfAbrupt(status).
8. Return rval.

AssignmentExpression : LeftHandSideExpression AssignmentOperator AssignmentExpression

1. Let lref be the result of evaluating LeftHandSideExpression.
2. Let lval be GetValue(lref).
3. ReturnIfAbrupt(lval).
4. Let rref be the result of evaluating AssignmentExpression.
5. Let rval be GetValue(rref).
6. ReturnIfAbrupt(rval).
7. Let operator be the @ where AssignmentOperator is @=.
8. Let r be the result of applying operator @ to lval and rval.
9. Let status be PutValue(lref, r).
10. ReturnIfAbrupt(status).
11. Return r.

NOTE When an assignment occurs within strict mode code, it is an runtime error if lref in step 1.e of the first algorithm or step 9 of the second algorithm is an unresolved reference. If it is, a ReferenceError exception is thrown. The LeftHandSide also may not be a reference to a data property with the attribute value {[[Writable]]:false}, to an accessor property with the attribute value {[[Set]]:undefined}, nor to a non-existent property of an object whose [[Extensible]] internal property has the value false. In these cases a TypeError exception is thrown.

11.13.1 Destructuring Assignment

Supplemental Syntax

In certain circumstances when processing the production AssignmentExpression : LeftHandSideExpression = AssignmentExpression the following grammar is used to refine the interpretation of LeftHandSideExpression.

Deleted: The production
Deleted: is evaluated as follows:
Deleted: If <u>lref</u> is an abrupt completion, return <u>lref</u> .
Deleted: <u><#></u> Throw a <u>SyntaxError</u> exception if the following conditions are all true: <#> Type(<u>lref</u>) is Reference is <u>true</u> <#> IsStrictReference(<u>lref</u>) is <u>true</u> <#> Type(<u>GetBase(lref)</u>) is Environment Record <#> GetReferencedName(<u>lref</u>) is either " <u>eval</u> " or " <u>arguments</u> "
Deleted: Call
Deleted: If the result of
Deleted: <u><#></u> If this is not extended code, throw a <u>ReferenceError</u> exception.
Deleted: If <u>rval</u> is an abrupt completion, return <u>rval</u> .
Deleted: P
Deleted: Evaluate
Deleted: <u>obj</u> parameter
Deleted: If <u>status</u> is an abrupt completion, return <u>rval</u> .
Deleted: where <u>AssignmentOperator</u> is <u>@=</u> and <u>@</u> represents one of the operators indicated above
Deleted: If <u>lval</u> is an abrupt completion, return <u>lval</u> .
Deleted: If <u>rval</u> is an abrupt completion, return <u>rval</u> .
Deleted: <u><#></u> Throw a <u>SyntaxError</u> exception if the following conditions are all true: <#> Type(<u>lref</u>) is Reference is <u>true</u> <#> IsStrictReference(<u>lref</u>) is <u>true</u> <#> Type(<u>GetBase(lref)</u>) is Environment Record <#> GetReferencedName(<u>lref</u>) is either " <u>eval</u> " or " <u>arguments</u> "
Deleted: If the result of
Deleted: Call
Deleted: is an abrupt completion, return that result
Deleted: ¶
Formatted: Note
Deleted: its <u>LeftHandSide</u> must not evaluate to an
Deleted: d
Deleted:
Deleted: must not be
Deleted: an
Deleted: does
Deleted: upon assignment
Deleted: ¶
Deleted: .1

AssignmentPattern :

- ObjectAssignmentPattern
- ArrayAssignmentPattern

ObjectAssignmentPattern :

- {}
- { AssignmentPropertyList }
- { AssignmentPropertyList , }

ArrayAssignmentPattern :

- [Elision_{opt} AssignmentRestElement_{opt}]
- [AssignmentElementList ,]
- [AssignmentElementList , Elision_{opt} AssignmentRestElement_{opt}]

AssignmentPropertyList :

- AssignmentProperty
- AssignmentPropertyList , AssignmentProperty

AssignmentElementList :

- Elision_{opt} AssignmentElement
- AssignmentElementList , Elision_{opt} AssignmentElement

AssignmentProperty :

- Identifier Initialiser_{opt}
- PropertyName : AssignmentElement

AssignmentElement :

- LeftHandSideExpression Initialiser_{opt}

AssignmentRestElement :

- ... LeftHandSideExpression

Static Semantics

Static Semantics: Early Errors

AssignmentProperty : Identifier Initialiser_{opt}

- It is a Syntax Error if Identifier is the Identifier eval or the Identifier arguments.
- It is a Syntax Error if Identifier is the Identifier this or the Identifier super.
- It is a Syntax Error if Identifier does not statically resolve to a declarative environment record binding or if the resolved binding is an immutable binding.

Deleted: LeftHandSideExpression

Deleted: PropertyName

Deleted: :

Deleted: LeftHandSideExpression

Comment [AW57]: This part probably does need to be here if 11.1.2 has this as a static semantic for extended code.

AssignmentElement : LeftHandSideExpression Initialiser_{opt}

- It is a Syntax Error if LeftHandSideExpression is the Identifier eval or the Identifier arguments.
- It is a Syntax Error if LeftHandSideExpression is the Identifier this or the Identifier super.
- It is a Syntax Error if the LeftHandSideExpression is a Literal, a FunctionExpression or a ClassExpression.
- It is a Syntax Error if the LeftHandSideExpression is an Identifier that does not statically resolve to a declarative environment record binding or if the resolved binding is an immutable binding.
- It is a Syntax Error if IsValidAssignmentPattern of LeftHandSideExpression is true.
- It is a Syntax Error if the LeftHandSideExpression is PrimaryExpression : (Expression) and Expression derived a production that would produce a Syntax Error according to these rules. This rule is recursively applied.

Comment [AWB658]: This list need to be updated when the grammer is stable

Comment [AW59]: This part probably does need to be here if 11.1.2 has this as a static semantic for extended code.

Deleted: It is a Syntax Error if the LeftHandSideExpression is an ObjectLiteral or a ArrayLiteral and the source code corresponds to LeftHandSideExpression using cannot be parsed using AssignmentPattern as the goal symbol.

AssignmentRestElement : ... LeftHandSideExpression

- It is a Syntax Error if LeftHandSideExpression is the Identifier eval or the Identifier arguments.

- It is a Syntax Error if *LeftHandSideExpression* is the Identifier *this* or the Identifier *super*.
- It is a Syntax Error if the *LeftHandSideExpression* is a *Literal*, an *ObjectLiteral*, an *ArrayLiteral*, a *FunctionExpression*, or a *ClassExpression*.
- It is a Syntax Error if the *LeftHandSideExpression* is an Identifier that does not statically resolve to a declarative environment record binding or if the resolved binding an immutable binding.
- It is a Syntax Error if the *LeftHandSideExpression* is *PrimaryExpression : (Expression)* and *Expression* derived a production that would produce a Syntax Error according to these rules. This rule is recursively applied.

Runtime Semantics

Runtime Semantics: Destructuring Assignment Evaluation

with parameter *obj*

ObjectAssignmentPattern : { }

and

ArrayAssignmentPattern :

[]
[Elision]

1. Return NormalCompletion(empty).

AssignmentPropertyList : AssignmentPropertyList , AssignmentProperty

1. Let status be the result of performing Destructuring Assignment Evaluation for *AssignmentPropertyList* using *obj* as the argument.
2. ReturnIfAbrupt(status).
3. Return the result of performing Destructuring Assignment Evaluation of *AssignmentProperty* for *AssignmentProperty* using *obj* as the argument.

AssignmentProperty : Identifier Initialiser_{opt}

1. Let P be StringValue of *Identifier*.
2. Let v be the result of calling the [[Get]] internal method of *obj* with argument *P*.
3. ReturnIfAbrupt(v).
4. If *Initialiser_{opt}* is present and v is *undefined*, then
 - a. Let *defaultValue* be the result of evaluating *Initialiser*.
 - b. Let v be ToObject(*defaultValue*).
5. ReturnIfAbrupt(v).
6. Let *ref* be the result of performing Identifier Resolution(10.3.1) with the *IdentifierName* corresponding to *Identifier*.
7. Return PutValue(*ref*, *v*).

AssignmentProperty : PropertyName : AssignmentElement

1. Let name be PropName of *PropertyName*.
2. Return the result of performing Keyed Destructuring Assignment Evaluation of *AssignmentElement* with *obj* and *name* as the arguments.

ArrayAssignmentPattern : [Elision_{opt} AssignmentRestElement]

1. Let skip be the Elision Width of *Elision*; if *Elision* is not present, use the numeric value zero.
2. Return the result of performing Indexed Destructuring Assignment Evaluation of *AssignmentRestElement* with *obj* and *skip* as the arguments.

ArrayAssignmentPattern : [AssignmentElementList]

Comment [AWB660]: This list need to be updated when the grammar is stable

Deleted: The supplemental production
AssignmentPattern : ObjectAssignmentPattern ¶
 is evaluated with the parameter *obj* as follows:
 <#>EvaluatePerformReturn the result of performing Destructuring Assignment Evaluation of *ObjectAssignmentPattern* usingwith *obj* as the *obj* parameterargument.
 <#>¶

Deleted: The supplemental production

Deleted: ,the production *ArrayAssignmentPattern : []*

Deleted: *ObjectAssignmentPattern : ¶*

Deleted: The supplemental production

Deleted: is evaluated with the parameter *obj* as follo

Deleted: Perform

Deleted: of

Deleted: Evaluate

Deleted: with

Deleted: using ...bj as the *obj* parameter

Deleted: If *status* is an abrupt completion,

Deleted: Perform

Deleted: Evaluate

Deleted: with

Deleted: using ...bj as the *obj* ...rgumentparameter

Deleted: The supplemental production

Deleted:

Deleted: <#>Let exists be the result of calling the

Deleted: <#>Else ¶

Deleted: v

Deleted: Else,

Deleted: <#> Let v be *undefined*.¶

Deleted: using

Deleted: Call

Deleted: ¶

Deleted: The static semantics of the supplemental

Deleted: *LeftHandSideExpression*

Deleted: is evaluated with the parameter *obj* as follow

Deleted: the result of evaluating ...ropName of

Deleted: Indexed

Deleted: <#>Let v be the result of calling the [[Get]] inter

Deleted: The supplemental production

Deleted:

Deleted: is evaluated with the parameter *obj* as follow

Deleted: If *Elision* is present, then let *skip* be the result of

Deleted: Perform

Deleted: Evaluate ...ssignmentRestElement with *obj* using

Deleted: 0

Deleted: index ...rgumentsparameter...¶

1. Return the result of performing Indexed Destructuring Assignment Evaluation of *AssignmentElementList* using *obj* and *0* as the arguments.

ArrayAssignmentPattern : [*AssignmentElementList* , *Elision_{opt}* *AssignmentRestElement_{opt}*]

1. Let *lastIndex* be the result of performing Indexed Destructuring Assignment Evaluation of *AssignmentElementList* using *obj* and *0* as the arguments.
2. ReturnIfAbrupt(*lastIndex*).
3. Let *skip* be the Elision Width of *Elision*; if *Elision* is not present, use the numeric value zero.
4. If *AssignmentRestElement* is present, then return the result of performing Indexed Destructuring Assignment Evaluation of *AssignmentRestElement* with *obj* and *lastIndex+skip* as the arguments.
5. Return *lastIndex*.

Runtime Semantics: Indexed Destructuring Assignment Evaluation

with parameters *obj* and *index*

AssignmentElementList : *Elision_{opt}* *AssignmentElement*

1. Let *skip* be the Elision Width of *Elision*; if *Elision* is not present, use the numeric value zero.
2. Let *name* be *ToString(index+skip)*.
3. Let *status* be the result of performing Keyed Destructuring Assignment Evaluation of *AssignmentElement* with *obj* and *name* as the arguments.
4. ReturnIfAbrupt(*status*).
5. Return *index+skip+1*.

AssignmentElementList : *AssignmentElementList* , *Elision_{opt}* *AssignmentElement*

1. Let *listNext* be the result of performing Indexed Destructuring Assignment Evaluation of *AssignmentElementList* using *obj* as the *obj* parameter and *index* as the *index* parameter.
2. Let *skip* be the Elision Width of *Elision*; if *Elision* is not present, use the numeric value zero.
3. ReturnIfAbrupt(*listNext*).
4. Let *name* be *ToString(listNext+skip)*.
5. Let *status* be the result of performing Keyed Destructuring Assignment Evaluation of *AssignmentElement* with *obj* and *name* as the arguments.
6. ReturnIfAbrupt(*status*).
7. Return *listNext+skip+1*.

AssignmentRestElement : ... *LeftHandSideExpression*

1. Let *lref* be the result of evaluating *LeftHandSideExpression*.
2. ReturnIfAbrupt(*lref*).
3. Let *lenVal* be the result of calling the *[[Get]]* internal method of *obj* with argument *"length"*.
4. Let *len* be *ToInt32(lenVal)*.
5. ReturnIfAbrupt(*len*).
6. Let *A* be the result of the abstract operation *ArrayCreate* (15.4) with argument *0*.
7. Let *n=0*.
8. Repeat, while *index < len*
 - a. Let *P* be *ToString(index)*.
 - b. Let *exists* be the result of calling the *[[HasProperty]]* internal method of *obj* with argument *P*.
 - c. If *exists* is *true*, then
 - i. Let *v* be the result of calling the *[[Get]]* internal method of *obj* passing *ToString(index)* as the argument.
 - ii. ReturnIfAbrupt(*len*).
 - iii. Call the *[[DefineOwnProperty]]* internal method of *A* with arguments *ToString(n)*, *Property Descriptor* *{[[Value]]: v, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}*, and *false*.
 - d. Let *n = n+1*.
 - e. Let *index = index+1*.

Deleted: <#>Perform Indexed Destructuring
Deleted: The supplemental production
Deleted: <i>AssignmentPropertyList</i>
Deleted: <i>t</i>
Deleted: <#>is evaluated with the parameters
Deleted: <i>index</i>
Deleted: evaluating ... <i>AssignmentElementList</i>
Deleted: If <i>lastIndex</i> is an abrupt completion,
Deleted: If <i>Elision</i> is present, then let <i>skip</i> be the Elision Width of <i>Elision</i> .
Deleted: perform
Deleted: evaluate ... <i>AssignmentRestElement</i> with <i>obj</i> and <i>lastIndex+skip</i> as the arguments.
Deleted: <i>i</i>
Deleted: <i>index</i> ... <i>argumentsparameter</i> ...¶
Deleted: The supplemental production
Deleted: is evaluated with the parameters <i>obj</i> and <i>index</i> .
Deleted: If <i>Elision</i> is present, then let <i>skip</i> be the Elision Width of <i>Elision</i> .
Deleted: Perform
Deleted: Indexed
Deleted: Evaluate
Deleted: Let <i>index</i> be the result of evaluating ... <i>bj</i> as the <i>obj</i> parameter.
Deleted: <i>index+skip</i>
Deleted: <i>index</i> ... <i>argumentsparameter</i>
Deleted: If <i>status</i> is an abrupt completion, return <i>status</i> .
Deleted: <i>+skip</i>
Deleted: <i>t</i>
Deleted: The supplemental production
Deleted: is evaluated with the parameters <i>obj</i> and <i>index</i> .
Deleted: <i>e...istNextnd</i>
Deleted: evaluating
Deleted: <i>tRes</i>
Deleted: If <i>Elision</i> is present, then let <i>skip</i> be the Elision Width of <i>Elision</i> .
Deleted: If <i>listNext</i> is an abrupt completion, return <i>listNext</i> .
Deleted: Let <i>index</i> be the result of evaluating ... <i>AssignmentElement</i> with <i>obj</i> and <i>index</i> .
Deleted: Perform
Deleted: Indexed
Deleted: Evaluate ... <i>AssignmentElement</i> with <i>obj</i> and <i>index</i> .
Deleted: <i>e</i>
Deleted: <i>listNextnd+ski</i>
Deleted: <i>index</i> ... <i>argumentsparameter</i>
Deleted: If <i>status</i> is an abrupt completion, return <i>status</i> .
Deleted: <i>i...istNextnd</i>
Deleted: <i>t</i>
Deleted: The supplemental production
Deleted: The supplemental production
Deleted: is evaluated with the parameters <i>obj</i> and <i>index</i> .
Deleted: If <i>lref</i> is an abrupt completion, return <i>lref</i> .
Deleted: <i>t</i>
Deleted: If <i>len</i> is an abrupt completion, return <i>len</i> .
Deleted: <i>ion</i>
Deleted: a new array object created as if by the <i>ArrayCreate</i> abstract operation.
Deleted: If <i>v</i> is an abrupt completion, return <i>v</i> .

9. *Return PutValue(*lref.A*)*

Deleted: Call

Deleted: ¶

Runtime Semantics: Keyed Destructuring Assignment Evaluation

with parameters *obj* and *propertyName*

AssignmentElement : LeftHandSideExpression Initialiser_{opt}

1. Let *v* be the result of calling the [[Get]] internal method of *obj* with argument *propertyName*.
2. ReturnIfAbrupt(*v*).
3. If *Initialiser_{opt}* is present and *v* is **undefined**, then
 - a. Let *v* be the result of evaluating *Initialiser*.
4. If *LeftHandSideExpression* is an *ObjectLiteral* or an *ArrayLiteral* then
 - a. Let *AssignmentPattern* be the parse of the source code corresponding to *LeftHandSideExpression* using *AssignmentPattern* as the goal symbol
 - b. Let *vObj* be *ToObject(v)*.
 - c. ReturnIfAbrupt(*vObj*).
 - d. Return the result of performing Destructuring Assignment Evaluation of *AssignmentPattern* with *vObj* as the argument.
5. ReturnIfAbrupt(*v*).
6. Let *lref* be the result of evaluating *LeftHandSideExpression*.
7. Return PutValue(*lref.v*).

11.14 Comma Operator (,)

Syntax

Expression :

 AssignmentExpression
 Expression , AssignmentExpression

ExpressionNoIn :

 AssignmentExpressionNoIn
 ExpressionNoIn , AssignmentExpressionNoIn

The semantics of the *ExpressionNoIn* production is the same manner as the *Expression* production except that the contained *ExpressionNoIn* and *AssignmentExpressionNoIn* are used in place of the contained *Expression* and *AssignmentExpression*, respectively.

Deleted: evaluated in

Deleted: evaluated instead

Static Semantics: IsValidSimpleAssignmentTarget

Expression : Expression , AssignmentExpression

1. Return false.

Runtime Semantics: Evaluation

Expression : Expression , AssignmentExpression

1. Let *lref* be the result of evaluating *Expression*.
2. ReturnIfAbrupt(GetValue(*lref*)).
3. Let *rref* be the result of evaluating *AssignmentExpression*.
4. Return *GetValue(rref)*.

NOTE GetValue must be called even though its value is not used because it may have observable side-effects.

Deleted: Semantics¶
The production

Deleted: is evaluated as follows:

Deleted: Call

Deleted: If the result of

Deleted:

Deleted: is an abrupt completion, return that result

Deleted: .

12 Statements and Declarations

Syntax

Statement :

BlockStatement
VariableStatement
EmptyStatement
ExpressionStatement
IfStatement
BreakableStatement
ContinueStatement
BreakStatement
ReturnStatement
WithStatement
LabelledStatement
ThrowStatement
TryStatement
DebuggerStatement

Declaration :

FunctionDeclaration
GeneratorDeclaration
ClassDeclaration
LexicalDeclaration

BreakableStatement :

IterationStatement
SwitchStatement

Static Semantics

Static Semantics: VarDeclaredNames

Statement :

EmptyStatement
ExpressionStatement
ContinueStatement
BreakStatement
ReturnStatement
ThrowStatement
DebuggerStatement

1. Return a new empty List.

Runtime Semantics

Runtime Semantics: Labelled Evaluation

With argument labelSet.

BreakableStatement : IterationStatement

1. Let *stmtResult* be the result of performing Labelled Evaluation of *IterationStatement* with argument *labelSet*.
2. If *stmtResult.[[type]]* is *break* and *stmtResult.[[target]]* is *empty*, then
 - a. Let *stmtResult* be NormalCompletion(*stmtResult.[[value]]*)
3. Return *stmtResult*.

BreakableStatement : SwitchStatement

Deleted: *IterationStatement*

Deleted:
SwitchStatement

Deleted: *LetDeclaration* ..
Const

Deleted: A Statement can be part of a LabelledStatement, which itself can be part of a LabelledStatement, and so on. The labels introduced this way are collectively referred to as the "current label set" when describing the semantics of individual statements. A LabelledStatement has no semantic meaning other than the introduction of a label to a label set. The label set of an IterationStatement or a SwitchStatement initially contains the single element *empty*. The label set of any other statement is initially empty.¶

Deleted: **Static Semantics: BoundNames**
The BoundNames of the Declaration production are determined as follows:¶

<#> Return the BoundNames of the single non-terminal symbol that is the right hand side of the production.¶

Deleted: The VarDeclaredNames of the productions:

Statement : *EmptyStatement* ..
Statement : *ExpressionStatement* ..
Statement : *ContinueStatement* ..
Statement : *BreakStatement* ..
Statement : *ReturnStatement* ..
Statement : *ThrowStatement* ..
Statement : *DebuggerStatement* ..

is determined as follows:¶

Deleted: *Statement* :¶
BlockStatement ..
VariableStatement ..
IterationStatement ..
WithStatement ..
LabelledStatement ..
SwitchStatement ..
TryStatement ¶

The VarDeclaredNames of the productions:

Statement : *BlockStatement* ..
Statement : *IfStatement* ..
Statement : *IterationStatement* ..
Statement : *WithStatement* ..
Statement : *LabelledStatement* ..
Statement : *SwitchStatement* ..
Statement : *TryStatement* ..

is determined as follows:¶

<#> Return the VarDeclaredNames of the single non-terminal symbol that is the right hand side of the production.¶

The VarDeclaredNames of the production *Statement* : *VariableStatement* is determined as follows:¶

<#> Return the BoundNames of the VariableStatement

3. Let *stmtResult* be the result of evaluating *SwitchStatement*.
4. If *stmtResult*.[[type]] is *break* and *stmtResult*.[[target]] is empty, then
 - a. Let *stmtResult* be *NormalCompletion*(*stmtResult*.[[value]])
5. Return *stmtResult*.

NOTE A *BreakableStatement* is one that can be exited via an unlabelled *BreakStatement*.

Runtime Semantics: Evaluation

BreakableStatement :
 IterationStatement
 SwitchStatement

1. Let *newLabelSet* be a new empty List.
2. Return the result of performing Labelled Evaluation of this *BreakableStatement* with argument *newLabelSet*.

12.1 Block

Syntax

BlockStatement :
 Block

Block :
 { *StatementList*_{opt} }

StatementList :
StatementListItem
StatementList StatementListItem

StatementListItem :
Statement
Declaration

Static Semantics

Static Semantics: Early Errors

Block : { *StatementList* }.

- It is a Syntax Error if the LexicallyDeclaredNames of *StatementList* contains any duplicate entries.
- It is a Syntax Error if any element of the LexicallyDeclaredNames of *StatementList* also occurs in the VarDeclaredNames of *StatementList*.

Static Semantics: LexicalDeclarations

StatementList : *StatementList StatementListItem*

1. Let *declarations* be LexicalDeclarations of *StatementList*.
2. Append to *declarations* the elements of the LexicalDeclarations of *StatementListItem*.
3. Return *declarations*.

StatementListItem : *Statement*

1. Return a new empty List.

StatementListItem : *Declaration*

1. Return a new List containing *Declaration*.

Deleted: s

Comment [AWB 361]: Need to have an evalution semantics in section 13 for *FunctionDeclaration* as follows¶

Deleted: The *Statement* productions are all evaluated as follows¶
 <#>Return the result of evaluating the single non-terminal symbol that is the right hand side of the production.¶
 The *Declaration* productions are all evaluated as follows¶
 <#>Return the result of evaluating the single non-terminal symbol that is the right hand side of the production.¶
 NOTE The result of evaluating a *Statement* or *Declaration* is always a Completion value.¶

Deleted: The BoundNames of the *Declaration* production are determined as follows:¶
 <#>Return the BoundNames of the single non-terminal symbol that is the right hand side of the production.¶
 The *Declaration* productions are all evaluated as follows¶
 <#>Return the result of evaluating the single non-terminal symbol that is the right hand side of the production.¶

Deleted: NOTE .Several widely used implementations of ECMAScript are known to support the use of *FunctionDeclaration* as a *Statement*. However there are significant and irreconcilable variations among the implementations in the semantics applied to such *FunctionDeclarations*. Because of these irreconcilable differences, the use of a *FunctionDeclaration* as a *Statement* results in code that is not reliably portable among implementations. It is recommended that ECMAScript implementations either disallow this usage of *FunctionDeclaration* or issue a warning when such a usage is encountered. Future editions of ECMAScript may define alternative portable means for declaring functions in a *Statement* context.¶

Deleted: <#>It is a Syntax Error if *StatementList* includes a *StatementListItem* : *Declaration* production whose *Declaration* is a *Declaration* : *FunctionDeclaration* production and the source code matching this *Block* production is not contained in extended code.¶

Deleted: i

Deleted: *StatementList* : *StatementListItem* ¶
 <#>Return the LexicalDeclarations of *StatementListItem*.¶

Deleted: names

Deleted: return

Static Semantics: LexicallyDeclaredNames

Block : { }

1. Return a new empty List.

StatementList : StatementList StatementListItem

1. Let *names* be LexicallyDeclaredNames of *StatementList*.
2. Append to *names* the elements of the LexicallyDeclaredNames of *StatementListItem*.
3. Return *names*.

StatementListItem : Statement

1. Return a new empty List.

StatementListItem : Declaration

1. Return the BoundNames of *Declaration*.

Static Semantics: VarDeclaredNames

Block : { }

1. Return a new empty List.

StatementList : StatementList StatementListItem

1. Let *names* be VarDeclaredNames of *StatementList*.
2. Append to *names* the elements of the VarDeclaredNames of *StatementListItem*.
3. Return *names*.

StatementListItem : Declaration

1. Return a new empty List.

Runtime Semantics

Runtime Semantics: Evaluation

Block : { }

1. Return NormalCompletion(empty).

Block : { StatementList }

1. Let *oldEnv* be the running execution context's LexicalEnvironment.
2. Let *blockEnv* be the result of calling NewDeclarativeEnvironment passing *oldEnv* as the argument.
3. Perform Block Declaration Instantiation using *StatementList* and *blockEnv*.
4. Set the running execution context's LexicalEnvironment to *blockEnv*.
5. Let *blockValue* be the result of evaluating *StatementList*.
6. Set the running execution context's LexicalEnvironment to *oldEnv*.
7. Return *blockValue*.

NOTE No matter how control leaves the *Block* the LexicalEnvironment is always restored to its former state.

StatementList : StatementList StatementListItem

1. Let *sL* be the result of evaluating *StatementList*.

Deleted: The VarDeclaredNames of the production *BlockStatement : Block* is determined as follows:
 ↪ Return the VarDeclaredNames of *Block*.
 The production *BlockStatement : Block* is evaluated as follows:
 ↪ Return the result of evaluating *Block*.

Deleted: The LexicallyDeclaredNames of the production

Deleted: is determined as follows:

Deleted: *Block : { StatementList }*
 ↪ Return the LexicallyDeclaredNames of *StatementList*.
StatementList : StatementListItem
 ↪ Return the LexicallyDeclaredNames of *StatementListItem*.

Deleted: *BlockStatement : Block*
 ↪ Return the VarDeclaredNames of *Block*.

Deleted: The VarDeclaredNames of the production

Deleted: is determined as follows:

Deleted: *Block : { StatementList }*
 ↪ Return the VarDeclaredNames of *StatementList*.
StatementList : StatementListItem
 ↪ Return the VarDeclaredNames of *StatementListItem*.

Deleted: *StatementListItem : Statement*
 ↪ Return the VarDeclaredNames of *Statement*.

Deleted: *BlockStatement : Block*
 ↪ Return the result of evaluating *Block*.

Deleted: The production

Deleted: is evaluated as follows:

Deleted: normal,

Deleted: , empty

Deleted: The static semantics of the production *Block : { StatementList }* are:
 ↪ It is a Syntax Error if *StatementList* include *StatementListItem : Declaration* production who *Declaration* is a *Declaration : FunctionDeclaration* production and the source code matching this

Deleted: is evaluated as follows:

Deleted: running

Deleted: current

Deleted: For each element *param*, of *formals*,

Deleted: running

Deleted: current

Deleted: running

Deleted: current

Comment [AW62]: If evaluation of code starts anywhere else other than here (for example at the start of a function body) then the environment is created as if it were the environment of a *FunctionDeclaration* production.

Deleted: The LexicallyDeclaredNames of the production *StatementList : StatementListItem* is evaluated as follows:

Deleted: The LexicallyDeclaredNames of the production *StatementList : StatementList*

Deleted: is evaluated as follows:

2. [ReturnIfAbrupt\(s\)](#)
 3. Let s be the result of evaluating Statement.
 4. If $s.[[type]]$ is throw, [return s](#).
 5. If $s.[[value]]$ is empty, let $V = sl.[[value]]$, otherwise let $V = s.[[value]]$.
 6. Return [Completion](#) {[[type]]: $s.[[type]]$, [[value]]: V , [[target]]: $s.[[target]]$ }.

NOTE Steps 4 and 5 of the above algorithm ensure that the value of a *StatementList* is the value of the last value producing *Statement* in the *StatementList*. For example, the following calls to the `eval` function all return the value 1:

```
eval("1;;;;")  
eval("1;{})")  
eval("1;var a;")
```

12.2 Declarations and the Variable Statement

12.2.1 Let and Const Declarations

NOTE A `let` and `const` declarations define variables that are scoped to the running execution context's LexicalEnvironment. The variables are created when their containing Lexical Environment is instantiated but may not be accessed in any way until the variable's `LexicalBinding` is evaluated. A variable defined by a `LexicalBinding` with an Initialiser is assigned the value of its Initialiser's AssignmentExpression when the `LexicalBinding` is evaluated, not when the variable is created. If a `LexicalBinding` in a `let` declaration does not have an Initialiser the variable is assigned the value `undefined` when the `LexicalBinding` is evaluated.

Syntax

LexicalDeclaration :
LetOrConst BindingList ;

LexicalDeclarationNoIn :
LetOrConst BindingListNoIn

LetOrConst:

BindingList :
LexicalBinding

BindingListNoIn :
LexicalBindingNoIn

LexicalBinding :
BindingIdentifier Initialiser_{opt}

LexicalBindingNoIn :
BindingIdentifier InitialiserNoIn_{opt}
BindingPattern Initialiser NoIn

BindingIdentifier ::

InitialiserNoIn :
— AssignmentExpressionNoIn

The semantics

productions are the

124

Deleted: If <i>s1</i> is an abrupt completion, return <i>s1</i>
Deleted: <i>an exception was thrown, return (</i>
Deleted: <i>V, empty)</i>
Deleted: where
Deleted: <i>V</i> is the exception. (Execution now proceeds as if exception were thrown.)
Deleted: value
Deleted: (
Deleted: type
Deleted:).
Deleted: 5
Deleted: 6
Deleted: The LexicallyDeclaredNames and the LexicalDeclarations of the production <i>StatementListItem Statement</i> are determined as follows: ->#Return a new empty List.
Deleted: The production <i>StatementListItem : Statement</i> is
Deleted: The LexicallyDeclaredNames of the production
Deleted: The production <i>StatementListItem : Declaration</i> is
Deleted: s
Deleted: current
Deleted: Let
Deleted: Let
Deleted: executed
Deleted: LetBinding
Deleted: t
Deleted: executed
Deleted: LetBinding
Deleted: t
Deleted: executed
Deleted: Let
Deleted: let Let
Deleted: Let
Deleted: Let
Deleted: Let
Deleted: Let
Deleted: Let
Deleted: Let
Deleted: Let
Deleted: Initialiser :
Deleted: Let
Deleted: Let
Deleted: Let
Deleted: Let

except that the contained *BindingListNoIn*, *LexicalBindingNoIn*, *InitialiserNoIn* and *AssignmentExpressionNoIn* are used in place of the contained *BindingList*, *LexicalBinding*, *Initialiser* and *AssignmentExpression*, respectively.

Static Semantics

Static Semantics: Early Errors

LexicalBinding : *BindingIdentifier*

- It is a Syntax Error if *IsConstantDeclaration* of the *LexicalDeclaration* containing this production is true.

BindingIdentifier : *Identifier*

- It is a Syntax Error if the *BindingIdentifier* is contained in strict code and if the *Identifier* is *eval* or *arguments*.

Static Semantics: BoundNames

LexicalDeclaration : *LetOrConst BindingList* ;

1. Return the *BoundNames* of *BindingList*.

BindingList : *BindingList* , *LexicalBinding*

1. Let *names* be the *BoundNames* of *BindingList*.
2. Append to *names* the elements of the *BoundNames* of *LexicalBinding*.
3. Return *names*.

LexicalBinding : *BindingIdentifier Initialiser* _{opt}

1. Return the *BoundNames* of *BindingIdentifier*.

LexicalBinding: *BindingPattern Initialiser*

1. Return the *BoundNames* of *BindingPattern*.

BindingIdentifier : *Identifier*

1. Return a new List containing the *StringValue* of *Identifier*.

Static Semantics: IsConstantDeclaration

LexicalDeclaration : *LetOrConst BindingList* ;

1. Return *IsConstantDeclaration* of *LetOrConst*.

LetOrConst : *let*

1. Return false.

LetOrConst : *const*

1. Return true.

Deleted: *Let*

Deleted: *Let*

Deleted: *Let*

Deleted: *Let*

Deleted: NOTE A *let* declaration defines variables that are scoped to the current execution context's LexicalEnvironment. Let variables are created when their containing Lexical Environment is instantiated but may not be accessed in any way until the variable's *LetBinding* is executed. A variable defined by *LetBinding* with an *Initialiser* is assigned the value of its *Initialiser*'s *AssignmentExpression* when the *LetBinding* is executed, not when the variable is created. If a *LetBinding* does not have an *Initialiser* the variable is assigned the value *undefined* when the *LetBinding* is executed. ¶

Deleted: if the *BindingIdentifier*

Comment [AWB863]: Consider disallowing *undefined* as a binding identifier in all new declaration forms.

Deleted: Semantics ¶

Deleted: The static semantics of the production *LetDeclaration* : *let LetBindingList* ;

Deleted: *Bound Names*

Deleted: The *BoundNames* of the production

Deleted: *Let*

Deleted: *let LetBindingList*

Deleted: is determined as follows:

Deleted: *Bound Names*

Deleted: *Let*

Deleted: *LetBindingList* : *LetLexicalBinding* ¶

Deleted: *Let*

Deleted: *Let*

Deleted: *N*

Deleted: *Let*

Deleted: *Let*

Deleted: *Let*

Deleted: *Bound Names*

Deleted: *Let*

Deleted: *Let*

Deleted: *Bound Names*

Deleted: *Let*

Deleted: *Let*

Deleted: *BindingList*

Deleted:

Deleted: *BindingList*

Deleted: *false*

Runtime Semantics

Runtime Semantics: Binding Initialisation

With arguments *value* and *environment*.

NOTE *undefined* is passed for *environment* to indicate that a *PutValue* operation should be used to assign the *initialisation* value. This is the case for *var* statements formal parameter lists of non-strict functions. In those cases a lexical binding is hosted and preinitialized prior to evaluation of its initializer.

BindingIdentifier : Identifier

1. If *environment* is not *undefined*, then
 - a. Let *name* be *StringValue* of *Identifier*.
 - b. Let *env* be the environment record component of *environment*.
 - c. Call the *InitializeBinding* concrete method of *env* passing *name* and *value* as the arguments.
 - d. Return *NormalCompletion(undefined)*.
2. Else
 - a. Let *lhs* be the result of evaluating *Identifier* as described in 11.1.2.
 - b. Return *PutValue(lhs, value)*.

Runtime Semantics: Evaluation

LexicalDeclaration ; LetOrConst BindingList ;

1. Let *next* be the result of evaluating *BindingList*.
2. ReturnIfAbrupt(*next*).
3. Return *NormalCompletion(empty)*.

BindingList : BindingList , LexicalBinding

1. Let *next* be the result of evaluating *BindingList*.
2. ReturnIfAbrupt(*next*).
3. Return the result of evaluating *LexicalBinding*.

LexicalBinding : BindingIdentifier

1. Let *env* be the *running* execution context's *LexicalEnvironment*.
2. Return the result of performing *Binding Initialisation* for *BindingIdentifier* passing *undefined* and *env* as the arguments.

NOTE A static semantics rule ensures that this form of *LexicalBinding* never occurs in a *const* declaration.

LexicalBinding : BindingIdentifier Initialiser

1. Let *rhs* be the result of evaluating *Initialiser*.
2. Let *value* be *GetValue(rhs)*.
3. ReturnIfAbrupt(*value*).
4. Let *env* be the *running* execution context's *LexicalEnvironment*.
5. Return the result of performing *Binding Initialisation* for *BindingIdentifier* passing *value* and *env* as the arguments.

LexicalBinding : BindingPattern Initialiser

1. Let *rhs* be the result of evaluating *Initialiser*.
2. Let *value* be *ToObject(GetValue(rhs))*.
3. ReturnIfAbrupt(*rval*).
4. Let *env* be the *running* execution context's *LexicalEnvironment*.

Deleted: RuntimeStatic Semantics: String Value
BindingIdentifier : *Identifier* ¶
 <#>Return the String Value of *Identifier*.¶

Deleted: Initialization
Deleted: environment

Deleted: initialization
Deleted: the

Deleted: *BindingIdentifier* *BindingIdentifier* : *Identifier*

Deleted: environment

Deleted:

Deleted: environment

Deleted: environment ...assing name *Identifier*

Deleted: Value

Deleted: Call

Deleted: The production

Deleted: *LetDeclaration* ... *LetOrConst* *let* *Let*

Deleted: is evaluated as follows:

Deleted: Evaluate *Let*

Deleted: If *next* is an abrupt completion, return *next*

Deleted: (normal, ...empty, empty)

Deleted: *LetBindingList* : *LetLexicalBinding* is evaluated

Deleted: *Let...indingList* : *Let...indingList* , *Let*

Deleted: is evaluated as follows:

Deleted: Evaluate *Let*

Deleted: If *next* is an abrupt completion, return *next*

Deleted: Evaluate *Let*

Deleted: *Let*

Deleted: is evaluated as follows:

Deleted: running

Deleted: current

Deleted: Perform ...inding Initialization

Deleted: *e*

Deleted: The production

Deleted: *Let*

Deleted: is evaluated as follows:

Deleted: If *value* is an abrupt completion, return *rval*

Deleted: running

Deleted: current

Deleted: Perform ...inding Initialization

Deleted: *Let*

Deleted: is evaluated as follows:

Deleted: *rval*

Deleted: If *rval* is an abrupt completion,

Deleted: running

Deleted: current

5. Return the result of performing *Binding Initialisation* for *BindingPattern* using *value* as the *obj* parameter and *env* as the *environment* parameter.

12.2.2 Variable Statement

NOTE A *var* statement declares variables that are scoped to the *running* execution context's *VariableEnvironment*. *Var* variables are created when their containing *Lexical Environment* is instantiated and are initialised to *undefined* when created. Within the scope of any *VariableEnvironemnt* a common *Identifier* may appear in more than one *VariableDeclaration* but those declarations collective define only one variable. A variable defined by a *VariableDeclaration* with an *Initialiser* is assigned the value of its *Initialiser's AssignmentExpression* when the *VariableDeclaration* is executed, not when the variable is created.

Syntax

VariableStatement :

var *VariableDeclarationList* ;

VariableDeclarationList :

VariableDeclaration
VariableDeclarationList , *VariableDeclaration*

VariableDeclarationListNoIn :

VariableDeclarationNoIn
VariableDeclarationListNoIn , *VariableDeclarationNoIn*

VariableDeclaration :

*BindingIdentifier Initialiser*_{opt}
BindingPattern Initialiser

VariableDeclarationNoIn :

*BindingIdentifier InitialiserNoIn*_{opt}
BindingPattern InitialiserNoIn

The semantics of the *VariableDeclarationListNoIn*, *VariableDeclarationNoIn* and *InitialiserNoIn* productions are the same as the *VariableDeclarationList*, *VariableDeclaration* and *Initialiser* productions except that the contained *VariableDeclarationListNoIn*, *VariableDeclarationNoIn*, *InitialiserNoIn* and *AssignmentExpressionNoIn* are used in of the contained *VariableDeclarationList*, *VariableDeclaration*, *Initialiser* and *AssignmentExpression*, respectively.

Static Semantics

Static Semantics: BoundNames

VariableDeclarationList : *VariableDeclarationList* , *VariableDeclaration*

1. Let *names* be *BoundNames* of *VariableDeclarationList*.
2. Append to *names* the elements of *BoundNames* of *VariableDeclaration*.
3. Return *names*.

VariableDeclaration : *BindingIdentifier Initialiser*_{opt}

1. Return the *BoundNames* of *BindingIdentifier*.

VariableDeclaration : *BindingPattern Initialiser*

1. Return the *BoundNames* of *BindingPattern*.

Deleted: Perform

Deleted: Initialization

Deleted: Evaluate

Deleted: rval

Deleted: *BindingIdentifier* : *Identifier* is evaluated as follows:
Return the result of evaluating *Identifier* as described in 11.1.2.

Deleted: The production *Initialiser* : = *AssignmentExpression* is evaluated as follows:
Return the result of evaluating *AssignmentExpression*.

Deleted: The *LetBindingListNoIn*, *LetBindingNoIn* and *InitialiserNoIn* productions are evaluated in the same manner as the *LetBindingList*, *LetBinding* and *Initialiser* productions except that the contained *LetBindingListNoIn*, *LetBindingNoIn*, *InitialiserNoIn* and *AssignmentExpressionNoIn* are evaluated instead of the contained *LetBindingList*, *LetBinding*, *Initialiser* and *AssignmentExpression*, respectively.

Deleted: 12.2.2 Const Declaration
NOTE A *const* declaration defines read-only variables that are scoped to the current execution context's *LexicalEnvironment*. Constant variables are created when their containing *Lexical Environment* is instantiated but may not be accessed in any way until the variable's *ConstBinding* is executed. A variable defined by a *ConstBinding* is assigned the value of its *Initialiser's AssignmentExpression* when the *ConstBinding* is executed, not when the variable is created.

Syntax

ConstDeclaration :

const *ConstBindingList* ;

ConstBindingList :

ConstBinding

ConstBinding :

ConstBinding List , *ConstBinding*

ConstBinding :

BindingIdentifier Initialiser

BindingPattern Initialiser

NOTE A *const* declaration defines read-only variables that are scoped to the current execution context's *LexicalEnvironment*. Constant variables are created when their containing *Lexical Environment* is instantiated but may not be accessed in any way until the variable's *ConstBinding* is executed. A variable defined by a *ConstBinding* is assigned the value of its *Initialiser's AssignmentExpression* when the *ConstBinding* is executed, not when the variable is created.

Deleted: 3

Deleted: current

Deleted: 1

Deleted: NOTE . A *var* statement declares variables that are scoped to the current execution context's *VariableEnvironment*. *Var* variables are created when their containing

Deleted: Static Semantics: Early Errors
VariableDeclaration : *BindingPattern Initialiser*

Deleted: The *BoundNames* of the production *VariableStatement* : *var* *VariableDeclarationList* is determined as follows:

Runtime Semantics

Runtime Semantics: Binding Initialisation

With arguments *value* and *environment*.

NOTE *undefined* is passed for *environment* to indicate that a *PutValue* operation should be used to assign the initialisation value. This is the case for *var* statements formal parameter lists of non-strict functions. In those cases a lexical binding is hosted and preinitialized prior to evaluation of its initializer.

VariableDeclaration : BindingIdentifier

1. Return the result of performing Binding Initialisation for *BindingIdentifier* passing *value* and *undefined* as the arguments.

VariableDeclaration : BindingIdentifier Initialiser

1. Return the result of performing Binding Initialisation for *BindingIdentifier* passing *value* and *undefined* as the arguments.

VariableDeclaration : BindingPattern Initialiser

1. Return the result of performing Binding Initialisation for *BindingPattern* passing *value* and *undefined* as the arguments.

Runtime Semantics: Evaluation

VariableStatement : var VariableDeclarationList ;

1. Let *next* be the result of evaluating *VariableDeclarationList*.
2. ReturnIfAbrupt(*next*).
3. Return *NormalCompletion(empty)*.

VariableDeclarationList : VariableDeclarationList , VariableDeclaration

1. Let *next* be the result of evaluating *VariableDeclarationList*.
2. ReturnIfAbrupt(*next*).
3. Return the result of evaluating *VariableDeclaration*.

VariableDeclaration : BindingIdentifier

1. Return *NormalCompletion(empty)*.

VariableDeclaration : BindingIdentifier Initialiser

1. Let *rhs* be the result of evaluating *Initialiser*.
2. Let *value* be *GetValue(rhs)*.
3. ReturnIfAbrupt(*value*).
4. Return the result of performing Binding Initialisation for *BindingIdentifier* passing *value* and *undefined* as the arguments.

NOTE If a *VariableDeclaration* is nested within a *with* statement and the *Identifier* in the *VariableDeclaration* is the same as a property name of the binding object of the *with* statement's object environment record, then step 3 will assign *value* to the property instead of to the *VariableEnvironment* binding of the *Identifier*.

VariableDeclaration : BindingPattern Initialiser

2. Let *rhs* be the result of evaluating *Initialiser*.
3. Let *rval* be *ToObject(GetValue(rhs))*.
4. ReturnIfAbrupt(*rval*).

Deleted: the
Deleted: The production
Deleted: is evaluated as follows:
Deleted: Evaluate
Deleted: If <i>next</i> is an abrupt completion, return <i>next</i>
Deleted: (normal,
Deleted: <i>y</i> , empty)
Deleted: The BoundNames of the production <i>VariableDeclarationList : VariableDeclaration</i> is determined as follows: <#>Return BoundNames of <i>VariableDeclaration</i> .¶
Deleted: The production <i>VariableDeclarationList : VariableDeclaration</i> is evaluated as follows: <#>Let <i>names</i> be BoundNames of <i>VariableDeclarationList</i> . <#>Append to <i>names</i> the elements of BoundNames of <i>VariableDeclaration</i> .¶ <#>Return <i>names</i> .¶ The production
Deleted: The BoundNames of the production <i>VariableDeclarationList : VariableDeclarationList , VariableDeclaration</i> is determined as follows: <#>Let <i>names</i> be BoundNames of <i>VariableDeclarationList</i> . <#>Append to <i>names</i> the elements of BoundNames of <i>VariableDeclaration</i> .¶ <#>Return <i>names</i> .¶ The production
Deleted: is evaluated as follows:
Deleted: Evaluate
Deleted: If <i>next</i> is an abrupt completion, return <i>next</i>
Deleted: Evaluate
Deleted: The BoundNames of the production <i>VariableDeclaration : BindingIdentifier Initialiser_{opt}</i> is determined as follows: ¶ <#>Return the BoundNames of <i>BindingIdentifier</i> .¶ The production
Deleted: is evaluated as follows:
Deleted: the String value of <i>BindingIdentifier</i>
Deleted: The production
Deleted: is evaluated as follows:
Deleted: If <i>value</i> is an abrupt completion, return <i>value</i>
Deleted: Perform
Deleted: Initialization
Deleted: NOTE 1 The String value of a <i>VariableDeclaration</i> is used in the evaluation of for-in statements (12.6.4).¶
Deleted: 2
Deleted: 4
Deleted: The static semantics of the production <i>VariableDeclaration : BindingPattern Initialiser</i> are: ¶ <#>It is a Syntax Error if the source code matching this production is not contained in extended code.¶ The BoundNames of the production <i>VariableDeclaration : BindingPattern Initialiser</i> is determined as follows: ¶ <#>Return the BoundNames of <i>BindingPattern</i> .¶
Deleted: is evaluated as follows:
Deleted: <i>ToObject</i> (
Deleted:)
Deleted: If <i>rval</i> is an abrupt completion, return <i>rval</i>

5. Return the result of performing Binding Initialisation for BindingPattern passing rval and undefined as arguments.

12.2.4 Destructuring Binding Patterns

Syntax

BindingPattern :

ObjectBindingPattern
ArrayBindingPattern

ObjectBindingPattern :

{ }
{ BindingPropertyList }
{ BindingPropertyList , }

ArrayBindingPattern :

[Elision_{opt} BindingRestElement_{opt}]
[BindingElementList]
[BindingElementList , Elision_{opt} BindingRestElement_{opt}]

BindingPropertyList :

BindingProperty
BindingPropertyList , BindingProperty

BindingElementList :

Elision_{opt} BindingElement
BindingElementList , Elision_{opt} BindingElement

BindingProperty :

SingleNameBinding
PropertyName : BindingElement

BindingElement :

SingleNameBinding
BindingPattern Initialiser_{opt}

SingleNameBinding :

BindingIdentifier Initialiser_{opt}

BindingRestElement :

... BindingIdentifier

Static Semantics

Static Semantics: Early Errors

BindingPattern : ObjectBindingPattern

- It is a Syntax Error if the BoundNames of ObjectBindingPattern contains the string “eval” or the string “arguments”.

BindingPattern : ObjectBindingPattern

- It is a Syntax Error if the BoundNames of ArrayBindingPattern contains the string “eval” or the string “arguments”.

Static Semantics: BoundNames

Deleted: Perform
Deleted: Initialization
Deleted: Evaluate
Deleted: using
Deleted: as the obj parameter
Deleted: the environment parameter
Deleted: The VariableDeclarationListNoIn, VariableDeclarationNoIn and InitialiserNoIn productions are evaluated in the same manner as the VariableDeclarationList, VariableDeclaration and Initialiser productions except that the contained VariableDeclarationListNoIn, VariableDeclarationNoIn, InitialiserNoIn and AssignmentExpressionNoIn are evaluated instead of the contained VariableDeclarationList, VariableDeclaration, Initialiser and AssignmentExpression, respectively.¶

Deleted: VariableStatement :¶
var VariableDeclarationList ;¶
VariableDeclaration¶
VariableDeclarationList , VariableDeclaration¶
VariableDeclarationListNoIn ;¶
VariableDeclarationNoIn .¶
VariableDeclarationListNoIn ,
VariableDeclarationNoIn¶
VariableDeclarationNoIn ;¶
VariableDeclaration :¶
Identifier Initialiser_{opt}¶
VariableDeclarationNoIn :¶
Identifier InitialiserNoIn_{opt}¶
Initialiser :¶
= AssignmentExpression¶
InitialiserNoIn :¶
= AssignmentExpressionNoIn¶

Comment [AW64]: The destructuring wiki page argues for allowing empty binding patterns. I'm not really convinced.

Comment [AW65]: See above comment about empty binding patterns.

Comment [AW66]: See above comment about empty binding patterns.

Deleted: Identifier

Deleted: PropertyName : SingleNameBinding

Deleted: PropertyName : BindingPattern Initialiser_{opt}

Deleted: Identifier ..

Deleted: Identifier

Deleted: Bound Names

Deleted: Bound Names

Deleted: Bound Names

ObjectBindingPattern : { }

1. Return an empty List.

ArrayBindingPattern : [Elision_{opt}]

1. Return an empty List.

ArrayBindingPattern : [Elision_{opt} BindingRestElement]

1. Return the BoundNames of *BindingElementList*.

ArrayBindingPattern : [BindingElementList , Elision_{opt}]

1. Return the BoundNames of *BindingElementList*.

ArrayBindingPattern : [BindingElementList , Elision_{opt} BindingRestElement]

1. Let *names* be BoundNames of *BindingElementList*.

2. Append to *names* the elements of BoundNames of *BindingRestElement*.

3. Return *names*.

BindingPropertyList : BindingPropertyList , BindingProperty

1. Let *names* be BoundNames of *BindingPropertyList*.

2. Append to *names* the elements of BoundNames of *BindingProperty*.

3. Return *names*.

BindingElementList : Elision_{opt} BindingElement

1. Return BoundNames of *BindingElement*.

BindingElementList : BindingElementList , Elision_{opt} BindingElement

1. Let *names* be BoundNames of *BindingElementList*.

2. Append to *names* the elements of BoundNames of *BindingElement*.

3. Return *names*.

BindingProperty : PropertyName : BindingElement

1. Return the BoundNames of *BindingElement*.

SingleNameBinding : BindingIdentifier Initialiser_{opt}

1. Return the BoundNames of *BindingIdentifier*.

BindingElement : BindingPattern Initialiser_{opt}

1. Return the BoundNames of *BindingPattern*.

Static Semantics: HasInitialiser

BindingElement : BindingPattern

1. Return false.

BindingElement : BindingPattern Initialiser

1. Return true.

Deleted: Semantics¶

Deleted: A variable statement declares variables that are created as defined in 10.5. Variables are initialised *undefined* when created. A variable with an *Initialiser* assigned the value of its *AssignmentExpression* when the *VariableStatement* is executed, not when the variable is created.¶

Semantics¶

The production *VariableStatement* : **var** *VariableDeclarationList* ; is evaluated as follows:¶

<#>Evaluate *VariableDeclarationList*.¶

<#>Return (normal, empty, empty).¶

The production

VariableDeclarationList : *VariableDeclaration* is evaluated as follows:¶

<#>Evaluate *VariableDeclaration*.¶

The production *VariableDeclarationList* : *VariableDeclarationList* , *VariableDeclaration* is evaluated as follows:¶

<#>Evaluate *VariableDeclarationList*.¶

<#>Evaluate *VariableDeclaration*.¶

The production *VariableDeclaration* : *Identifier* is evaluated as follows:¶

<#>Return a String value containing the same sequence of characters as in the *Identifier*.¶

The production *VariableDeclaration* : *Identifier Initialiser* is evaluated as follows:¶

<#>Let *lhs* be the result of evaluating *Identifier* as described 11.1.2.¶

<#>Let *rhs* be the result of evaluating *Initialiser*.¶

<#>Let *value* be *GetValue(rhs)*.¶

<#>Call *PutValue(lhs, value)*.¶

<#>Return a String value containing the same sequence of characters as in the *Identifier*.¶

NOTE 1 The String value of a *VariableDeclaration* is used in the evaluation of for-in statements (12.6.4).¶

NOTE 2 . If a *VariableDeclaration* is nested within a with statement and the *Identifier* in the *VariableDeclaration* is the same as a property name of the binding object of the with statement's object environment record, then step 4 will assign value to the property instead of to the VariableEnvironment binding of the *Identifier*.¶

Deleted: The BoundNames of the production *BindingPattern* : *ObjectBindingPattern* is determined as follows:¶

<#>Return the Bound Names of *ObjectBindingPattern*.¶

BindingPattern : *ArrayBindingPattern* ¶

<#>Return BoundNames of *ArrayBindingPattern*.¶

Comment [AW67]: The restructuring wiki page argues for allowing empty binding patterns. I'm not really convinced.

Deleted: *ObjectBindingPattern* :¶

- { *BindingPropertyList* }
- { *BindingPropertyList* , }¶

<#>Return the BoundNames of *BindingPropertyList*.¶

Deleted: *ArrayBindingPattern* : [*BindingElementList*]¶

<#>Return the BoundNames of *BindingElementList*.¶

Deleted: *BindingPropertyList* : *BindingProperty* ¶

<#>Return BoundNames of *BindingProperty*.¶

Deleted: *BindingProperty* : *SingleNameBinding* ¶

<#>Return the BoundNames of *SingleNameBinding* .¶

Deleted: *BindingElement* : *SingleNameBinding* ¶

<#>Return the BoundNames of *SingleNameBinding* .¶

Deleted: *BindingRestElement* : . . . *BindingIdentifier* ¶

<#>Return the BoundNames of *BindingIdentifier*.¶

Deleted: *BindingElement* : *SingleNameBinding* ¶

<#>Return HasInitializer of *SingleNameBinding* .¶

SingleNameBinding : BindingIdentifier

1. Return false.

SingleNameBinding : BindingIdentifier Initialiser

1. Return true.

Runtime Semantics

Runtime Semantics: Binding Jinitialisation

With parameters *value* and *environment*.

NOTE When **undefined** is passed for *environment* it indicates that a PutValue operation should be used to assign the **initialisation** value. This is the case for formal parameter lists of non-strict functions. In that case the formal parameter bindings are preinitialized in order to deal with the possibility of multiple parameters with the same name.

BindingPattern : ObjectBindingPattern

1. **Assert:** Type(*value*) is Object
2. **Return the result of performing Binding Jinitialisation for ObjectBindingPattern using *obj* and *environment* as arguments.**

BindingPattern : ArrayBindingPattern

1. **Assert:** Type(*value*) is Objec
2. **Return the result of performing Indexed Binding Jinitialisation for ArrayBindingPattern using *array*, *0*, and *environment* as arguments.**

ObjectBindingPattern: {}

1. **Return NormalCompletion(empty).**

BindingPropertyList : BindingPropertyList , BindingProperty

1. **Let *status* be the result of performing Binding Jinitialisation for BindingPropertyList using *value* and *environment* as arguments.**
2. **ReturnIfAbrupt(*status*).**
3. **Return the result of performing Binding Jinitialisation for BindingProperty using *value* and *environment* as arguments.**

BindingProperty : SingleNameBinding

1. **Let *name* be the string that is the only element of BoundNames of SingleNameBinding.**
2. **Return the result of performing Keyed Binding Jinitialisation for SingleNameBinding using *value*, *environment*, and *name* as the arguments.**

BindingProperty : PropertyName : BindingElement

1. **Let *P* be the PropName of PropertyName**
2. **Return the result of performing Keyed Binding Jinitialisation for BindingElement using *value*, *environment*, and *P* as arguments.**

Runtime Semantics: Indexed Binding Jinitialisation

With parameters *array*, *nextIndex*, and *environment*.

Deleted: Initialization
Deleted: enivornment
Deleted: initialization
Deleted: the
Deleted: The production
Deleted: If <i>value</i> is neither of null or undefined then
Deleted: <#>Let <i>obj</i> be ToObject(<i>value</i>).¶ <#>Else, let <i>obj</i> be undefined .¶
Deleted: is evaluated with parameters <i>value</i> and <i>env</i> as follows:¶ Evaluate
Deleted: Perform ...inding Initialization
Deleted: <i>value</i> as the ...bj parameter ...nd <i>env</i> a
Deleted: The BoundNames of the production
Deleted: BindingPattern : ArrayBindingPattern is
Deleted: If <i>value</i> is neither of null or undefined
Deleted: <#>Let <i>array</i> be ToObject(<i>value</i>).¶
Deleted: <#>Let <i>lenValue</i> be the result of calling
Deleted: <#>Else,¶
Deleted: <#>Let <i>arrayLength</i> be 0.¶
Deleted: is evaluated with parameters <i>value</i>
Deleted: Perform ...ndexed Binding Initialization
Deleted: Evaluate ...rrayBindingPattern using
Deleted: <i>arrayLength</i> , undefined
Deleted: as the <i>obj</i> parameter ...nd <i>env</i> as the
Deleted: The BoundNames of the production
Deleted: with parameters <i>value</i> and <i>env</i> as
Deleted: Return
Comment [AW68]: The destructuring wiki
Deleted: ObjectBindingPattern :¶
Deleted: The BoundNames of the production
Deleted: The production BindingPropertyList
Deleted: The BoundNames of the production
Deleted: with parameters <i>obj</i> and <i>env</i> as
Deleted: next
Deleted: Perform ...inding Initialization
Deleted: Evaluate ...indingPropertyList using
Deleted: next
Deleted: If <i>next</i> is an abrupt completion, return
Deleted: Perform ...inding Initialization
Deleted: Evaluate ...indingProperty using
Deleted: Perform ...yed Binding Initialization
Deleted: Perform ...yed Binding Initialization
Deleted: Evaluate
Deleted: Initialization
Deleted: arrayLength,

NOTE When undefined is passed for *environment* it indicates that a PutValue operation should be used to assign the initialisation value. This is the case for formal parameter lists of non-strict functions. In that case the formal parameter bindings are preinitialized in order to deal with the possibility of multiple parameters with the same name.

ArrayBindingPattern : [Elision_{opt}]

1. Return NormalCompletion(empty).

ArrayBindingPattern: [Elision_{opt} BindingRestElement]

1. Let nextIndex be the Elision Width of Elision; if Elision is not present, use the numeric value zero.
2. Return the result of performing Indexed Binding Initialisation for BindingRestElement using array, nextIndex, and environment as arguments.

ArrayBindingPattern: [BindingElementList]

1. Return the result of performing Indexed Binding Initialisation for BindingElementList using array, nextIndex, and environment as arguments.

ArrayBindingPattern: [BindingElementList , Elision_{opt}]

1. Let next be the result of performing Indexed Binding Initialisation for BindingElementList using array, nextIndex, and environment as arguments.
2. ReturnIfAbrupt(next).
3. Let skip be the Elision Width of Elision; if Elision is not present, use the numeric value zero.
4. Return the result of performing Indexed Binding Initialisation for BindingRestElement using array, next+skip , and environment as arguments.

BindingElementList : Elision_{opt} BindingElement

1. Let skip be the Elision Width of Elision; if Elision is not present, use the numeric value zero.
2. Let status be the result of performing Indexed Binding Initialisation for BindingElement using array, nextIndex+skip , and environment as arguments.
3. ReturnIfAbrupt(status).
4. Return nextIndex+skip+1.

BindingElementList : BindingElementList , Elision_{opt} BindingElement

1. Let listNext be the result of performing Indexed Binding Initialisation for BindingElementList using array, nextIndex, and environment as arguments.
2. ReturnIfAbrupt(listNext).
3. Let skip be the Elision Width of Elision; if Elision is not present, use the numeric value zero.
4. Let status be the result of performing Indexed Binding Initialisation for BindingElement using array, listNext+skip , and environment as arguments.
5. ReturnIfAbrupt(status).
6. Return listNext+skip+1.

BindingElement: SingleNameBinding

1. Return the result of performing Keyed Binding Initialisation for SingleNameBinding using array, environment, and ToString(nextIndex) as the arguments.

BindingElement: BindingPattern Initialiser_{opt}

Deleted: initialization
Deleted: the
Deleted: Return
Deleted: If Elision is present, then let nextIndex be the result of performing Indexed Binding Initialisation for BindingRestElement using array, nextIndex, and environment as arguments.
Deleted: Perform ...ndexed Binding Initialization
Deleted: arrayLength,
Deleted: Perform ...ndexed Binding Initialization
Deleted: Perform ...ndexed Binding Initialization
Deleted: 0,
Deleted: index
Deleted: Initialization
Deleted: ,
Deleted: 0
Deleted: index
Deleted: If index is an abrupt completion, return index.
Deleted: If Elision is present, then let skip be the result of performing Indexed Binding Initialisation for BindingRestElement using array, nextIndex+skip , and environment as arguments.
Deleted: Perform ...ndexed Binding Initialization
Deleted: arrayLength,
Deleted: index
Deleted: The BoundNames of the production
Deleted: with the parameters obj, env, and index as arguments.
Deleted: If Elision is present, then let skip be the result of performing Indexed Binding Initialisation for BindingRestElement using array, nextIndex+skip , and environment as arguments.
Deleted: next
Deleted: Perform ...ndexed Binding Initialization
Deleted: Evaluate ...indingElement using obj...rray as the arguments.
Deleted: arrayLength,
Deleted:
Deleted: env as the env parameter, and index+skip ...s the arguments.
Deleted: next
Deleted: If next is an abrupt completion, return next.
Deleted: index
Deleted: The BoundNames of the production
Deleted: is evaluated with the parameters obj, env, and index as arguments.
Deleted: Initialization
Deleted: obj
Deleted: arrayLength,
Deleted: as the obj parameter, env as the env parameter, and index as the index parameter.
Deleted: next
Deleted: If next is an abrupt completion, return next.
Deleted: If Elision is present, then let skip be the result of performing Indexed Binding Initialisation for BindingRestElement using array, listNext+skip , and environment as arguments.
Deleted: Evaluate
Deleted: next
Deleted: Perform ...ndexed Binding Initialization
Deleted: obj...rray as the obj parameter
Deleted: arrayLength,
Deleted: env as the env parameter
Deleted: ,
Deleted: and ...istNext+skip , and environment as the index parameter.
Deleted: listNext
Deleted: If listNext is an abrupt completion, return listNext.
Deleted: listNext
Deleted: ¶
Deleted: The BoundNames of the production
Deleted: <#>If nextIndex ≥ arrayLength, then ¶
Deleted: with the parameters obj, env and index as arguments.

1. Let P be $\text{ToString}(nextIndex)$.
2. Let v be the result of calling the $[[\text{Get}]]$ internal method of $array$ with argument P .
3. **ReturnIfAbrupt(v)**.
4. If $\text{Initialiser}_{\text{opt}}$ is present and v is **undefined**, then
 - a. Let defaultValue be the result of evaluating Initialiser .
 - b. Let v be $\text{ToObject}(\text{defaultValue})$.
5. **ReturnIfAbrupt(v)**.
6. **Return the result of performing Binding Initialisation for BindingPattern passing v and environment as arguments.**

BindingRestElement : ... BindingIdentifier

2. Let A be the result of the abstract operation **ArrayCreate** (15.4) with argument 0 .
3. Let $lenVal$ be the result of calling the $[[\text{Get}]]$ internal method of $array$ with argument **"length"**.
4. Let arrayLength be $\text{ToUint32}(lenVal)$.
5. **ReturnIfAbrupt(arrayLength)**.
6. Let $n=0$.
7. Let $\text{index} = nextIndex$.
8. Repeat, while $\text{index} < \text{arrayLength}$
 - a. Let P be $\text{ToString}(\text{index})$.
 - b. Let exists be the result of calling the $[[\text{HasProperty}]]$ internal method of $array$ with argument P .
 - c. If exists is **true**, then
 - i. Let v be the result of calling the $[[\text{Get}]]$ internal method of $array$ passing P as the argument.
 - ii. **ReturnIfAbrupt(v)**.
 - iii. Call the $[[\text{DefineOwnProperty}]]$ internal method of A with arguments $\text{ToString}(n)$, **Property Descriptor** $\{\text{[[Value]]: } v, \text{[[Writable]]: true}, \text{[[Enumerable]]: true}, \text{[[Configurable]]: true}\}$, and **false**.
 - d. Let $n = n+1$.
 - e. Let $\text{index} = \text{index}+1$.
9. **Return the result of performing Binding Initialisation for BindingIdentifier using A and environment as arguments.**

Runtime Semantics: Keyed Binding Initialisation

With parameters obj , $environment$, and $propertyName$.

NOTE When **undefined** is passed for $environment$ it indicates that a **PutValue** operation should be used to assign the initialisation value. This is the case for formal parameter lists of non-strict functions. In that case the formal parameter bindings are preinitialized in order to deal with the possibility of multiple parameters with the same name.

BindingElement: BindingPattern Initialiser_{opt}

1. Let v be the result of calling the $[[\text{Get}]]$ internal method of obj with argument $propertyName$.
2. **ReturnIfAbrupt(v)**.
3. If $\text{Initialiser}_{\text{opt}}$ is present and v is **undefined**, then
 - a. Let defaultValue be the result of evaluating Initialiser .
 - b. Let v be $\text{ToObject}(\text{defaultValue})$.
4. **ReturnIfAbrupt(v)**.
5. **Return the result of performing Binding Initialisation for BindingPattern passing v and environment as arguments.**

SingleNameBinding : BindingIdentifier Initialiser_{opt}

1. Let v be the result of calling the $[[\text{Get}]]$ internal method of obj passing $propertyName$ as the argument.
2. **ReturnIfAbrupt(v)**.
3. If $\text{Initialiser}_{\text{opt}}$ is present and v is **undefined**, then
 - a. Let v be the result of evaluating Initialiser .
4. **ReturnIfAbrupt(v)**.
5. **Return the result of performing Binding Initialisation for BindingIdentifier passing v and environment as arguments.**

Deleted: $\langle \# \rangle$ If $nextIndex \geq arrayLength$, then $\langle \# \rangle$ Let exists be false . $\langle \# \rangle$ Else ¶
Deleted: $\langle \# \rangle$ Let exists be the result of calling the $[[\text{HasProperty}]]$ internal method of $array$ with argument P . ¶
Deleted: with the parameters obj , env and $index$ as follows. ¶ $\langle \# \rangle$ Let P be $\text{ToString}(index)$. ¶ $\langle \# \rangle$ Let exists be the result of calling the $[[\text{HasProperty}]]$ internal method of obj with argument P . ¶
Deleted: $\langle \# \rangle$ If exists is true , then ¶
Deleted: $\langle \# \rangle$ obj
Deleted: passing P as the argument
Deleted: $\langle \# \rangle$ Else ¶
Deleted: $\langle \# \rangle$ Let v be the result of evaluating Initialiser
Deleted: If v is an abrupt completion, return v .
Deleted: Perform
Deleted: Initialization
Deleted: Evaluate
Deleted: v
Deleted: env
Deleted: ion
Deleted: a new array object created as if by the Object.Create operation
Deleted: If $arrayLength$ is an abrupt completion, return v .
Deleted: If v is an abrupt completion, return v .
Deleted: $\langle \# \rangle$ $.[\text{value}]$
Deleted: Perform
Deleted: Initialization
Deleted: $array$
Deleted: Initialization
Deleted: initialization
Deleted: the
Deleted: $\langle \# \rangle$ $\text{BindingElement: SingleNameBinding}$
Deleted: $\langle \# \rangle$ Let exists be the result of calling the $[[\text{HasProperty}]]$ internal method of obj with argument $propertyName$.
Deleted: $\langle \# \rangle$ Else ¶
Deleted: $\langle \# \rangle$ v
Deleted: $\langle \# \rangle$ Else ¶
Deleted: If v is an abrupt completion, return v .
Deleted: Perform
Deleted: Initialization
Deleted: $\langle \# \rangle$ Let exists be the result of calling the $[[\text{HasProperty}]]$ internal method of obj with argument $propertyName$.
Deleted: $\langle \# \rangle$ Else ¶
Deleted: $\langle \# \rangle$ v
Deleted: $\langle \# \rangle$ Else ¶
Deleted: If v is an abrupt completion, return v .
Deleted: Perform
Deleted: Initialization
Deleted: $\langle \# \rangle$ $enviornment$

12.3 Empty Statement

Syntax

EmptyStatement :
;

Runtime Semantics

Runtime Semantics: Evaluation

EmptyStatement : ;

1. Return NormalCompletion(empty).

12.4 Expression Statement

Syntax

ExpressionStatement :
[lookahead $\notin \{\}$, function, class] *Expression* ;

NOTE An *ExpressionStatement* cannot start with an opening curly brace because that might make it ambiguous with a *Block*. Also, an *ExpressionStatement* cannot start with the function or class keywords because that would make it ambiguous with a *FunctionDeclaration*, a *GeneratorDeclaration*, or a *ClassDeclaration*.

Runtime Semantics

Runtime Semantics: Evaluation

ExpressionStatement : [lookahead $\notin \{\}$, function, class] *Expression* ;

1. Let *exprRef* be the result of evaluating *Expression*.
2. Let *value* be *GetValue(exprRef)*.
3. ReturnIfAbrupt(value).
4. Return NormalCompletion(value).

12.5 The if Statement

Syntax

IfStatement :
if (*Expression*) *Statement* else *Statement*
if (*Expression*) *Statement*

Each *else* for which the choice of associated *if* is ambiguous shall be associated with the nearest possible *if* that would otherwise have no corresponding *else*.

Static Semantics: VarDeclaredNames

IfStatement : if (*Expression*) *Statement* else *Statement* ;

1. Let *names* be *VarDeclaredNames* of the first *Statement*.
2. Append to *names* the elements of the *VarDeclaredNames* of the second *Statement*.
3. Return *names*.

IfStatement : if (*Expression*) *Statement*

1. Return the *VarDeclaredNames* of *Statement*.

Deleted: The *BoundNames* of the production *BindingRestElement* : ... *BindingIdentifier* is determined as follows:
 ↪ Return the *BoundNames* of *BindingIdentifier*.

Deleted: The *BoundNames* of the production *BindingRestElement* : ... *Identifier* is determined as follows:
 ↪ Return *BoundNames* of *Identifier*.

Deleted: The production *BindingRestElement* : ...
BindingIdentifier is evaluated with the parameters *obj*, *env* and *index* as follows:
 ↪ Let *lenVal* be the result of calling the [[Get]] internal method of *obj* with argument "length".
 ↪ Let *len* be *ToUint32(lenVal)*.
 ↪ Let *A* be a new array object created as if by the expression *new Array()* where *Array* is the standard built-in constructor with that name.
 ↪ Let *n* = 0.
 ↪ Repeat, while *index* < *len*:
 ↪ Let *P* be *ToString(index)*.
 ↪ Let *exists* be the result of calling the [[HasProperty]] internal method of *obj* with argument *P*.
 ↪ If *exists* is *true*, then:
 ↪ Let *v* be the result of calling the [[Get]] internal method of *obj* passing *P* as the argument.
 ↪ Call the [[DefineOwnProperty]] internal method of *A* with arguments *ToString(*n*)*, *PropertyDescriptor* {[[Value]]: *v*, [[Writable]]: *true*, [[Enumerable]]: *true*, [[Configurable]]: *true*}, and *false*.
 ↪ Let *n* = *n* + 1.
 ↪ Let *index* = *index* + 1.
 ↪ Perform Binding Initialization for *BindingIdentifier* using *v* as the value and *env* as the environment.

Deleted: Semantics
 The production

Deleted: is evaluated as follows:

Deleted: (normal,

Deleted: , empty).

Deleted: might

Deleted: Semantics
 The production

Deleted: is evaluated as follows:

Deleted: If *value* is an abrupt completion, return *value*

Deleted: (normal, *GetValue(exprRef)*)

Deleted: , empty

Runtime Semantics

Runtime Semantics: Evaluation

IfStatement : if (Expression) Statement else Statement

1. Let exprRef be the result of evaluating Expression.
2. Let exprValue be ToBoolean(GetValue(exprRef)).
3. ReturnIfAbrupt(exprValue).
4. If exprValue is true, then
 - a. Return the result of evaluating the first Statement.
5. Else,
 - a. Return the result of evaluating the second Statement.

IfStatement : if (Expression) Statement

1. Let exprRef be the result of evaluating Expression.
2. Let exprValue be ToBoolean(GetValue(exprRef)).
3. ReturnIfAbrupt(exprValue).
4. If exprValue is false, return NormalCompletion(undefined).
5. Return the result of evaluating Statement.

12.6 Iteration Statements

Syntax

IterationStatement :

- do Statement while (Expression)
- while (Expression) Statement
- for (ExpressionNoIn_{opt}; Expression_{opt} ; Expression_{opt}) Statement
- for (var VariableDeclarationListNoIn ; Expression_{opt} ; Expression_{opt}) Statement
- for (LexicalDeclarationNoIn ; Expression_{opt} ; Expression_{opt}) Statement
- for (LeftHandSideExpression in Expression) Statement
- for (var ForBinding in Expression) Statement
- for (ForDeclaration in Expression) Statement
- for (LeftHandSideExpression of Expression) Statement
- for (var ForBinding of Expression) Statement
- for (ForDeclaration of Expression) Statement

ForDeclaration :

LetOrConst ForBinding

NOTE 1 ForBinding is defined in 11.1.4.2.


NOTE 2 A semicolon is not required after a do-while statement.]

Runtime Semantics

The abstract operation LoopContinues with arguments completion and labelSet is defined by the following step:

1. If completion.[[type]] is normal, then return true.
2. If completion.[[type]] is not continue, then return false.
3. If completion.[[target]] is empty, then return true.
4. If completion.[[target]] is an element of labelSet, then return true.
5. Return false.

NOTE Within the Statement part of an IterationStatement a ContinueStatement may be used to begin a new iteration.



12.6.1 The do-while Statement

Static Semantics: VarDeclaredNames

IterationStatement: `do Statement while (Expression)`

1. Return the VarDeclaredNames of *Statement*.

Runtime Semantics

Runtime Semantics: Labelled Evaluation

With argument *labelSet*.

IterationStatement: `do Statement while (Expression)`

1. Let *V*=undefined.
2. Repeat
 - a. Let *stmt* be the result of evaluating *Statement*.
 - b. If *stmt*.[[value]] is not empty, let *V*=*stmt*.[[value]].
 - c. If *stmt* is an abrupt completion and LoopContinues (stmt,labelSet) is false, return *stmt*.
 - d. Let *exprRef* be the result of evaluating *Expression*.
 - e. Let *exprValue* be ToBooleanGetValue(exprRef).
 - f. If *exprValue* is false, Return NormalCompletion(V).
 - g. Else if *exprValue* is a Completion Record, then
 - i. Assert: *exprValue* is an abrupt completion.
 - ii. If LoopContinues (exprValue,labelSet) is false, return *exprValue*.

12.6.2 The while Statement

Static Semantics: VarDeclaredNames

IterationStatement: `while (Expression) Statement`

1. Return the VarDeclaredNames of *Statement*.

Runtime Semantics

Runtime Semantics: Labelled Evaluation

With argument *labelSet*.

IterationStatement: `while (Expression) Statement`

1. Let *V*=undefined.
2. Repeat
 - a. Let *exprRef* be the result of evaluating *Expression*.
 - b. Let *exprValue* be ToBooleanGetValue(exprRef).
 - c. If *exprValue* is false, return NormalCompletion(V).
 - d. Else if *exprValue* is a Completion Record, then
 - i. Assert: *exprValue* is an abrupt completion.
 - ii. If LoopContinues (exprValue,labelSet) is false, return *exprValue*.
 - e. Let *stmt* be the result of evaluating *Statement*.
 - f. If *stmt*.[[value]] is not empty, let *V*=*stmt*.[[value]].
 - g. If LoopContinues (stmt,labelSet) is false, return *stmt*.

Deleted: The VarDeclaredNames of the production
Deleted: ;
Deleted: is determined as follows:

Deleted: Runtime Semantics: Evaluation¶

Deleted: The production
Deleted: ;
Deleted: is evaluated as follows:
Comment [AWB672]: Breaking change: completion reform
Deleted: empty
Deleted: <#>Let *iterating* be true.¶
Deleted: ,
Deleted: while *iterating* is true
Deleted: <#>If *stmt*.type is not continue or|| *stmt*.target is in the current label set, then¶
<#>If *stmt*.type is break and *stmt*.target is in the current label set, return (normal, *V*, empty).¶
Deleted: loopContinues
Deleted: ToBooleanGetValue(exprRef)
Deleted: set *iterating* to false
Comment [AWB673]: Break/continue/return in the expression works normally (future for do {} or block lambda expressions)
Deleted: loopContinues
Deleted: <#>Return (normal, *V*, empty);¶
Deleted: The VarDeclaredNames of the production
Deleted: *Statement* is determined as follows:
Deleted: Runtime Semantics: Evaluation¶

Deleted: The production
Deleted: is evaluated as follows:
Comment [AWB674]: ES5 breaking change: completion reform
Deleted: empty
Deleted: ToBooleanGetValue(exprRef)
Deleted: (normal,
Deleted: , empty
Comment [AWB675]: Break/continue/return in the expression works normally (future for do {} or block lambda expressions)
Deleted: loopContinues
Deleted: <#>If *stmt*.type is not continue or|| *stmt*.target is in the current label set, then¶
<#>If *stmt*.type is break and *stmt*.target is in the current label set, then¶
<#>Return (normal, *V*, empty).¶
Deleted: *stmt* is an abrupt completion
Deleted: loopContinues

12.6.3 The `for` Statement

Static Semantics

Static Semantics: VarDeclaredNames

IterationStatement : `for` (ExpressionNoIn_{opt} ; Expression_{opt} ; Expression_{opt}) Statement

1. Return the VarDeclaredNames of Statement.

IterationStatement : `for` (`var` VariableDeclarationListNoIn ; Expression_{opt} ; Expression_{opt}) Statement

1. Let names be BoundNames of VariableDeclarationListNoIn.
2. Append to names the elements of the VarDeclaredNames of Statement.
3. Return names.

IterationStatement : `for` (LexicalDeclarationNoIn ; Expression_{opt} ; Expression_{opt}) Statement

1. Return the VarDeclaredNames of Statement.

Runtime Semantics

Runtime Semantics: Labelled Evaluation

With argument *labelSet*.

IterationStatement : `for` (ExpressionNoIn_{opt} ; Expression_{opt} ; Expression_{opt}) Statement

1. If ExpressionNoIn is present, then.
 - a. Let *exprRef* be the result of evaluating ExpressionNoIn.
 - b. Let *exprValue* be GetValue(exprRef). (This value is not used but the call may have side-effects.)
 - c. If LoopContinues(exprValue,labelSet) is false, return exprValue.
2. Return the result of performing For Body Evaluation with the first Expression as the *testExpr* argument, the second Expression as the *incrementExpr* argument and with *labelSet*.

The abstract operation For Body Evaluation with arguments *testExpr*, *incrementExpr*, and *labelSet* is performed as follows:

1. Let *V* = undefined.
2. Repeat
 - a. If *testExpr* is not [empty], then
 - i. Let *testExprRef* be the result of evaluating *testExpr*.
 - ii. Let *testExprValue* be ToBoolean(GetValue(testExprRef))
 - iii. If *testExprValue* is false, return NormalCompletion(V).
 - iv. Else if LoopContinues(testExprValue,labelSet) is false, return *testExprValue*.
 - b. Let *stmt* be the result of evaluating Statement.
 - c. If *stmt.[[value]]* is not empty, let *V* = *stmt.[[value]]*.
 - d. If LoopContinues(stmt,labelSet) is false, return *stmt*.
 - e. If *incrementExpr* is not [empty], then
 - i. Let *incExprRef* be the result of evaluating *incrementExpr*.
 - ii. Let *incExprValue* be GetValue(incExprRef).
 - iii. If LoopContinues(incExprValue,labelSet) is false, return incExprValue.

IterationStatement : `for` (`var` VariableDeclarationListNoIn ; Expression_{opt} ; Expression_{opt}) Statement

1. Let *varDcl* be the result of evaluating VariableDeclarationListNoIn.
2. If LoopContinues(varDcl,labelSet) is false, return *varDcl*.
3. Return the result of performing For Body Evaluation with the first Expression as the *testExpr* argument, the second Expression as the *incrementExpr* argument and with *labelSet*.

Comment [AWB 376]: The lexical scoping for iteration variables still needs to be taken care of

Deleted: The VarDeclaredNames of the production

Deleted: is determined as follows:

Deleted: Runtime Semantics: Evaluation

Deleted: The production

Deleted: is evaluated as follows:

Deleted: Call

Deleted: loopContinues

Deleted: increment

Deleted: testExpr

Deleted: ion

Comment [AWB677]: ES5 breaking change
Completion reform

Deleted: empty

Deleted: the first Expression

Deleted: present

Deleted: the first

Deleted: Expression

Deleted: ToBoolean(GetValue(testExprRef))

Deleted: (normal,

Deleted: , empty

Deleted: loopContinues

Deleted: <#>If stmt.type is break and stmt.target is in the current label set, return (normal, *V*, empty).
<#>If stmt.type is not continue || stmt.target is not in the current label set, then

Deleted: *stmt*

Deleted: is an abrupt completion

Deleted: loopContinues

Deleted: the second

Deleted: Expression

Deleted: present

Deleted: the second

Deleted: Expression

Deleted: Call

Deleted: (This value is not used.)

Deleted: loopContinues

Deleted: loopContinues

Deleted: incrementExpr

Deleted: testExpr

IterationStatement : `for` (*LexicalDeclarationNoIn* ; *Expression_{opt}* ; *Expression_{opt}*) *Statement*

1. Let *oldEnv* be the *running execution context's LexicalEnvironment*.
2. Let *loopEnv* be the result of calling `NewDeclarativeEnvironment` passing *oldEnv* as the argument.
3. Let *isConst* be the result of performing `IsConstantDeclaration` of *d*.
4. For each element *dn* of the *BoundNames* of *LexicalDeclarationNoIn* do
 - a. If *isConst* is `true`, then
 - i. Call *loopEnv*'s `CreateImmutableBinding` concrete method passing *dn* as the argument.
 - b. Else,
 - i. Call *loopEnv*'s `CreateMutableBinding` concrete method passing *dn* and `false` as the arguments.
5. Set the *running execution context's LexicalEnvironment* to *loopEnv*.
6. Let *forDcl* be the result of evaluating *LexicalDeclarationNoIn*.
7. If `LoopContinues`(*forDcl*, *labelSet*) is `false`, then
 - a. Set the *running execution context's LexicalEnvironment* to *oldEnv*.
 - b. Return *forDcl*.
8. Let *bodyResult* be the result of performing `For Body Evaluation` with the first *Expression* as the *testExpr* argument, the second *Expression* as the *incrementExpr* argument and with *labelSet*.
9. Set the *running execution context's LexicalEnvironment* to *oldEnv*.
10. Return *bodyResult*.

12.6.4 The `for-in` and `for-of` Statements

Static Semantics

Static Semantics: Early Errors

IterationStatement :

`for (LeftHandSideExpression in Expression) Statement`
`for (LeftHandSideExpression of Expression) Statement`

- It is a Syntax Error if the *IterationStatement* is contained in strict code and *LeftHandSideExpression* is the *Identifier eval* or the *Identifier arguments*.
- It is a Syntax Error if the *LeftHandSideExpression* is an *Identifier* that statically resolves to a declarative environment record binding and the resolved binding is an immutable binding.
- It is a Syntax Error if the *LeftHandSideExpression* is *PrimaryExpression : (Expression)* and *Expression* derived a production that would produce a Syntax Error according to these rules. This rule is recursively applied.
- It is a Syntax Error if *IsInvalidAssignmentPattern* of *LeftHandSideExpression* is `true`.

IterationStatement :

`for (ForDeclaration in Expression) Statement`
`for (ForDeclaration of Expression) Statement`

- It is a Syntax Error if any element of the *LexicallyDeclaredNames* of *ForDeclaration* also occurs in the *VarDeclaredNames* of *Statement*.

Static Semantics: BoundNames

ForDeclaration : LetOrConst ForBinding

1. Return the *BoundNames* of *ForBinding*.

Static Semantics: VarDeclaredNames

IterationStatement : `for` (*LeftHandSideExpression* **in** *Expression*) *Statement*

1. Return the *VarDeclaredNames* of *Statement*.

Comment [AWB678]: A final decision has not yet been reached on the scoping semantics used for this form of statement. This version uses "loop scoping" a single set of let/const bindings are used for all iterations of the loop. This is the simplest of the semantics under consideration.

Deleted: <#>Evaluate `VariableDeclarationListNoIn`.
<#>Let *V* = empty.
<#>Repeat
<#>If the first *Expression* is present, then
<#>Let *testExprRef* be the result of evaluating the first *Expression*.
<#>If `ToBoolean`(`GetValue`(*testExprRef*)) is `false`, then return (*normal*, *V*, empty).
<#>Let *stmt* be the result of evaluating *Statement*.
<#>If *stmt.type* is `empty`, let *V* = *stmt.value*.
<#>If *stmt.type* is `break` and *stmt.target* is in the current label set, return (*normal*, *V*, empty).
<#>If *stmt.type* is not `continue` || *stmt.target* is not in the current label set, then
<#>If *stmt* is an abrupt completion, return *stmt*.
<#>If the second *Expression* is present, then
<#>Let *incExprRef* be the result of evaluating the second *Expression*.
<#>Call `GetValue`(*incExprRef*). (This value is not used.)

Deleted: *running*

Deleted: *current*

Deleted: *the*

Deleted: *running*

Deleted: *current*

Deleted: *loopContinues*

Deleted: *varDcl*

Deleted: *running*

Deleted: *current*

Deleted: *varDcl*

Deleted: *increment*

Deleted: *testExpr*

Deleted: *running*

Deleted: *current*

Deleted: It is a Syntax Error if the *LeftHandSideExpression* is an *ObjectLiteral* or an *ArrayLiteral* and the source code corresponding to *LeftHandSideExpression* cannot be parsed using *AssignmentPattern* as the goal symbol.

Deleted:

Deleted:

Deleted: *Var Declared Names*

Deleted: *Bound Names*

Deleted: *ForVarDeclaration : BindingPattern*
<#>Return the *Bound Names* of *BindingPattern*.
ForVarDeclaration : VariableDeclarationNoIn

Deleted: *Bound Names*

Deleted: *ForBinding : BindingIdentifier*
<#>Return the *Bound Names* of *BindingIdentifier*.

Deleted: *Var Declared Names*

Deleted: The *VarDeclaredNames* of the production

Deleted: is determined as follows:

Deleted: *Var Declared Names*

IterationStatement : for (var *ForBinding* in *Expression*) *Statement*

1. Let *names* be the *BoundNames* of *ForBinding*.
2. Append to *names* the elements of the *VarDeclaredNames* of *Statement*.
3. Return *names*.

IterationStatement : for (*ForDeclaration* in *Expression*) *Statement*

1. Return the *VarDeclaredNames* of *Statement*.

IterationStatement : for (*LeftHandSideExpression* of *Expression*) *Statement*

1. Return the *VarDeclaredNames* of *Statement*.

IterationStatement : for (var *ForBinding* of *Expression*) *Statement*

1. Let *names* be the *BoundNames* of *ForBinding*.
2. Append to *names* the elements of the *VarDeclaredNames* of *Statement*.
3. Return *names*.

IterationStatement : for (*ForDeclaration* of *Expression*) *Statement*

1. Return the *VarDeclaredNames* of *Statement*.

Runtime Semantics

Runtime Semantics: Binding Instantiation

With arguments *value* and *environment*.

ForDeclaration : LetOrConst *ForBinding*

1. For each element *name* of the *BoundNames* of *ForBinding* do
 - a. If *IsConstantDeclaration* of *LetOrConst* is *false*, then
 - i. Call *environment*'s *CreateMutableBinding* concrete method with argument *name*.
 - b. Else,
 - i. Call *environment*'s *CreateImmutableBinding* concrete method with argument *name*.
2. Return the result of performing Binding Initialisation for *ForBinding* passing *value* and *environment* as the arguments.

Runtime Semantics: Labelled Evaluation

With argument *labelSet*.

IterationStatement : for (*LeftHandSideExpression* in *Expression*) *Statement*

1. Let *keyResult* be the result of performing For In/Of Expression Evaluation with *Statement*, *enumerate*, and *labelSet*.
2. ReturnIfAbrupt(*keyResult*).
3. Return the result of performing For In/Of Body Evaluation with *LeftHandSideExpression*, *Statement*, *keyResult*, *assignment*, and *labelSet*.

IterationStatement : for (var *ForBinding* in *Expression*) *Statement*

1. Let *keyResult* be the result of performing For In/Of Expression Evaluation with *Statement*, *enumerate*, and *labelSet*.
2. ReturnIfAbrupt(*keyResult*).
3. Return the result of performing For In/Of Body Evaluation with *ForBinding*, *Statement*, *keyResult*, *varBinding*, and *labelSet*.

Deleted: *VariableDeclarationNoIn*

Deleted: *BindingIdentifier*

Deleted: *Bound Names*

Deleted: *Variable*

Deleted: *BindingIdentifier*

Deleted: *DeclarationNoIn*

Deleted: *Var Declared Names*

Deleted: *Var Declared Names*

Deleted: *Var Declared Names*

Deleted: *ForVarDeclaration*

Deleted: *Bound Names*

Deleted: *ForVarDeclaration*

Deleted: *Var Declared Names*

Deleted: *Var Declared Names*

Deleted: *Bound Names*

Deleted: Perform

Deleted: Runtime Semantics: Binding Initialisation¶

With arguments *value* and *environment*.¶
NOTE *undefined* is passed for *environment* indicate that a PutValue operation should be used to assign the initialisation value. This is the case for *var* statements formal parameter lists of non-strict functions. In those cases a lexical binding is hosted and preinitialised prior to evaluation of its initialiser.

ForVarDeclaration : BindingPattern ¶

<#> Perform Binding Initialisation for *BindingPattern* passing *value* and *env* as the arguments.¶

ForVarDeclaration : VariableDeclarationNoIn ¶

<#> Perform Binding Initialisation for *VariableDeclarationNoIn* passing *value* and *env* as the arguments.¶

ForBinding : BindingIdentifier ¶

<#> Perform Binding Initialisation for *BindingIdentifier* passing *value* and *env* as the arguments.¶

ForBinding : BindingPattern ¶

<#> Perform Binding Initialisation for *BindingPattern* passing *value* and *env* as the arguments.¶

Deleted: Runtime Semantics: Evaluation¶

Deleted: The production

Deleted: is evaluated as follows:

Deleted: .[[value]]

Deleted: *BindingIdentifier*

Deleted: *BindingIdentifier*

Deleted: .[[value]]

IterationStatement : `for` (*ForDeclaration* `in` *Expression*) Statement

1. Let *keyResult* be the result of performing For In/Of Expression Evaluation with *Statement*, *enumerate*, and *labelSet*.
2. ReturnIfAbrupt(*keyResult*).
3. Return the result of performing For In/Of Body Evaluation with *ForDeclaration*, *Statement*, *keyResult*, *lexicalBinding*, and *labelSet*.

Deleted: .[[value]]

Deleted: ForDeclaration

IterationStatement : `for` (*LeftHandSideExpression* `of` *Expression*) Statement

1. Let *keyResult* be the result of performing For In/Of Expression Evaluation with *Statement*, *iterate*, and *labelSet*.
2. ReturnIfAbrupt(*keyResult*).
3. Return the result of performing For In/Of Body Evaluation with *LeftHandSideExpression*, *Statement*, *keyResult*, *assignment*, and *labelSet*.

Deleted: .[[value]]

Deleted: BindingIdentifier

IterationStatement : `for` (`var` *ForBinding* `of` *Expression*) Statement

1. Let *keyResult* be the result of performing For In/Of Expression Evaluation with *Expression*, *iterate*, and *labelSet*.
2. ReturnIfAbrupt(*keyResult*).
3. Return the result of performing For In/Of Body Evaluation with *ForBinding*, *Statement*, *keyResult*, *varBinding*, and *labelSet*.

Deleted: BindingIdentifier

Deleted: .[[value]]

Deleted: Statement

IterationStatement : `for` (*ForDeclaration* `of` *Expression*) Statement

1. Let *keyResult* be the result of performing For In/Of Expression Evaluation with *Expression*, *iterate*, and *labelSet*.
2. ReturnIfAbrupt(*keyResult*).
3. Return the result of performing For In/Of Body Evaluation with *ForDeclaration*, *Statement*, *keyResult*, *lexicalBinding*, and *labelSet*.

Deleted: Statement

Deleted: .[[value]]

Deleted: ForDeclaration

Deleted: ion

Deleted: is performed as follows:

Deleted: Expression

Deleted: then return

Deleted: loopContinues

Comment [AWB679]: Note a continue in the initialization expression is just like a break

Comment [AWB680]: Completion value reform

Deleted: undefined,

Comment [AWB681]: Completion value reform

Deleted: undefined,

Deleted:

Deleted: .

Deleted: (normal, empty, empty)

Comment [AWB682]: Break/continue in the expression works normally (future for do {} or block lambda expressions)

Deleted: LoopContinues

Comment [AWB683]: Note a continue in the initialization expression is just like a break

Comment [AWB684]: Completion value reform

Deleted: undefined,

Deleted: ion

Deleted: is performed as follows:

Deleted: running

Deleted: current

The abstract operation For In/Of Expression Evaluation is called with arguments *expr*, *iterationKind*, and *labelSet*. The value of *iterationKind* is either *enumerate* or *iterate*.

1. Let *exprRef* be the result of evaluating the production that is *expr*.
2. Let *exprValue* be GetValue(*exprRef*).
3. If *exprValue* is an abrupt completion,
 - a. If *LoopContinues(exprValue,labelSet)* is *false*, then return *exprValue*.
 - b. Else, return Completion {[[type]]: *break*, [[value]]: *empty*, [[target]]: *empty*}.
4. If *exprValue* [[value]] is *null* or *undefined*, return Completion {[[type]]: *break*, [[value]]: *empty*, [[target]]: *empty*}.
5. Let *obj* be ToObject(*exprValue*).
6. If *iterationKind* is *enumerate*, then
 - a. Let *keys* be the result of calling the [[Enumerate]] internal method of *obj* with arguments *true* and *true*.
7. Else,
 - a. Assert *iterationKind* is *iterate*.
 - b. Let *keys* be the result of calling the [[Iterate]] internal method of *obj*.
8. If *keys* is an abrupt completion, then
 - a. If *LoopContinues(exprValue,labelSet)* is *false*, then return *exprValue*.
 - b. Assert: *keys*[[type]] is *continue*.
 - c. Return Completion {[[type]]: *break*, [[value]]: *empty*, [[target]]: *empty*}.
9. Return *keys*.

The abstract operation For In/Of Body Evaluation is called with arguments *lhs*, *stmt*, *keys*, *lhsKind*, and *labelSet*. The value of *lhsKind* is either *assignment*, *varBinding* or *lexicalBinding*.

1. Let *oldEnv* be the running execution context's LexicalEnvironment.

2. Let $V = \text{undefined}$.
3. Repeat
 - a. Let $next$ be the result of performing `Invoke` with arguments `"next"`, $keys$, and an empty arguments `List`.
 - b. If `IteratorComplete(next)` is `true`, then return `NormalCompletion(V)`.
 - c. If `LoopContinues(next,labelSet)` is `false`, then return $next$.
 - d. If $next$ is an abrupt completion, then let $status$ be $next$.
 - e. Else,
 - i. Assert $next.[[type]]$ is `normal`.
 - ii. Let $nextValue$ be $next.[[value]]$.
 - iii. If $lhsKind$ is `assignment`, then
 1. Assert: lhs is a `LeftHandSideExpression`.
 2. If lhs is neither an `ObjectLiteral` nor an `ArrayLiteral` then
 - a. Let $lhsRef$ be the result of evaluating lhs (it may be evaluated repeatedly).
 - b. Let $status$ be the result of performing `PutValue(lhsRef, nextValue)`.
 3. Else
 - a. Let `AssignmentPattern` be the parse of the source code corresponding to lhs using `AssignmentPattern` as the goal symbol.
 - b. Let $rval$ be `ToObject(nextValue).`
 - c. If $rval$ is an abrupt completion, then let $status$ be $rval$.
 - d. Else, let $status$ be the result of performing `DestructuringAssignmentEvaluation` of `AssignmentPattern` using $rval$ as the argument.
 - iv. Else if $lhsKind$ is `varBinding`, then
 1. Assert: lhs is a `ForBinding`.
 2. Let $status$ be the result of performing `BindingInitialisation` for lhs passing $nextValue$ and `undefined` as the arguments.
 - v. Else,
 1. Assert $lhsKind$ is `lexicalBinding`.
 2. Assert: lhs is a `ForDeclaration`.
 3. Let $iterationEnv$ be the result of calling `NewDeclarativeEnvironment` passing $oldEnv$ as the argument.
 4. Perform `BindingInstantiation` for lhs passing $nextValue$ and $iterationEnv$ as arguments.
 5. Let $status$ be `NormalCompletion(empty)`.
 6. Set the `running execution context's LexicalEnvironment` to $iterationEnv$.
 - vi. If $status.[[type]]$ is `normal`, then
 1. Let $status$ be the result of evaluating $stmt$.
 2. If $status.[[type]]$ is `normal` and $status.[[value]]$ is not empty, then
 - a. Let $V = status.[[value]]$.
 - vii. Set the `running execution context's LexicalEnvironment` to $oldEnv$.
 - viii. If $status$ is an abrupt completion and `LoopContinues(status,labelSet)` is `false`, then return $status$.

12.7 The `continue` Statement

Syntax

`ContinueStatement :`
 `continue ;`
 `continue [no LineTerminator here] Identifier ;`

Static Semantics

Static Semantics: Early Errors

`ContinueStatement : continue ;`

- It is a Syntax Error if `this production` is not nested, directly or indirectly (but not crossing function boundaries), within an `IterationStatement`.

Comment [AWB685]: Completion value reform

Deleted: `)`

Deleted: empty

Comment [AWB786]: TODO: need to define

Deleted: `loopContinues`

Deleted: `<#>Let P be the name of the next property of obj whose [[Enumerable]] attribute is true. If there is no such property, return (normal, empty).¶`

Deleted: `the LeftHandSideExpression`

Deleted: `Call`

Deleted: `P`

Comment [AWB687]: ToDo, update this to return a completion value

Deleted: `ForDeclaration`

Deleted: `running`

Deleted: `current`

Deleted: `stmt`

Deleted: `Statement`

Deleted: `If stmt.value is not empty, !`

Deleted: `stmt`

Deleted: `running`

Deleted: `current`

Deleted: `loopContinues`

Deleted: `<#>If stmt.type is break and stmt.target is in the current label set, return (normal, V, empty).¶`

`<#>If stmt.type is not continue or|| stmt.target is in the current label set, then¶`

`<#>If stmt is an abrupt completion, return stmt.¶`

Deleted: The `VarDeclaredNames` of the production

```
for ( var VariableDeclarationNoIn in Expression ) Statement .
is determined as follows:¶
<#>Let names be BoundNames of VariableDeclarationNoIn.¶
<#>Append to names the elements of the VarDeclaredNames of Statement.¶
<#>Return names.¶
```

Deleted: The production `IterationStatement : for (var VariableDeclarationNoIn in Expression) Statement .`

is evaluated as follows:¶

`<#>Let varName be the result of evaluating VariableDeclarationNoIn.¶`

`<#>Let exprRef be the result of evaluating the Expression.¶`

`<#>Let exprValue be GetValue(exprRef).¶`

`<#>If exprValue is null or undefined, return (normal, empty, empty).¶`

`<#>Let obj be ToObject(exprValue).¶`

Deleted: Semantics¶

Deleted: A program is considered syntactically incorrect if either of the following is true:¶

Deleted: The program contains a `continue` statement without the optional `Identifier`, which

ContinueStatement : continue [no LineTerminator here] Identifier ;

- It is a Syntax Error if Identifier does not appear in the CurrentLabelSet of an enclosing (but not crossing function boundaries) IterationStatement.

Deleted: The program contains a continue statement with the optional Identifier, where

Deleted: label set

Runtime Semantics

Runtime Semantics: Evaluation

ContinueStatement : continue ;

1. Return Completion {[[type]]: continue, [[value]]: empty, [[target]]: empty}.

Deleted: A ContinueStatement without an Identifier is evaluated as follows:
¶

Deleted: (

Deleted:).

Deleted: A ContinueStatement with the optional Identifier evaluated as follows:
¶

Deleted: (

Deleted:).

12.8 The break Statement

Syntax

BreakStatement :

```
break ;
break [no LineTerminator here] Identifier ;
```

Static Semantics

Static Semantics: Early Errors

BreakStatement : break ;

- It is a Syntax Error if this production, not nested, directly or indirectly (but not crossing function boundaries), within an IterationStatement or a SwitchStatement.

Deleted: Semantics
A program is considered syntactically incorrect if either the following is true:
¶

Deleted: The program contains a break statement without the optional Identifier, which is

Deleted: The program contains a break statement with the optional Identifier, where

Deleted: label set

Runtime Semantics

Runtime Semantics: Evaluation

BreakStatement : break ;

1. Return Completion {[[type]]: break, [[value]]: empty, [[target]]: empty}.

Deleted: A BreakStatement without an Identifier is evaluated as follows:
¶

Deleted: (

Deleted:).

Deleted: A BreakStatement with an Identifier is evaluated as follows:
¶

Deleted: (

Deleted:).

12.9 The return Statement

Syntax

ReturnStatement :

```
return ;
return [no LineTerminator here] Expression ;
```

NOTE A `return` statement causes a function to cease execution and return a value to the caller. If `Expression` is omitted, the return value is `undefined`. Otherwise, the return value is the value of `Expression`.

Static Semantics

Static Semantics: Early Errors

- It is a Syntax Error if a `return` statement is not within a `FunctionBody`.

Runtime Semantics

Runtime Semantics: Evaluation

`ReturnStatement : return ;`

1. Return Completion {[[type]]: return, [[value]]: `undefined`, [[target]]: empty}.

`ReturnStatement : return [no LineTerminator here] Expression ;`

1. Let `exprRef` be the result of evaluating `Expression`.

2. Let `exprValue` be `GetValue(exprRef)`.

3. ReturnIfAbrupt(exprValue).

4. Return Completion {[[type]]: return, [[value]]: `exprValue`, [[target]]: empty}.

12.10 The `with` Statement

Syntax

`WithStatement :`

`with (Expression) Statement`

NOTE The `with` statement adds an object environment record for a computed object to the lexical environment of the running execution context. It then executes a statement using this augmented lexical environment. Finally, it restores the original lexical environment.

Static Semantics

Static Semantics: Early Errors

`WithStatement : with (Expression) Statement`

- It is a Syntax Error if the code that matches this production is contained in `strict` code.

Static Semantics: VarDeclaredNames

`WithStatement : with (Expression) Statement`

1. Return the `VarDeclaredNames` of `Statement`.

Runtime Semantics

Runtime Semantics: Evaluation

`WithStatement : with (Expression) Statement`

1. Let `val` be the result of evaluating `Expression`.

2. Let `obj` be `ToObject(GetValue(val))`.

3. ReturnIfAbrupt(obj).

4. Let `oldEnv` be the running execution context's `LexicalEnvironment`.

Deleted: <#>Semantics¶

Deleted: A ECMAScript program is considered syntactically incorrect if it contains

Deleted: that

Deleted: A `return` statement causes a function to cease execution and return a value to the caller. If `Expression` is omitted, the return value is `undefined`. Otherwise, the return value is the value of `Expression`.

Deleted: A `ReturnStatement` is evaluated as follows:¶ If the `Expression` is not present, r

Deleted: (

Deleted:).

Comment [AWB988]: TODO If `exprRef` is Reference that invokes a getter we probably should find a way to specify that the get call is handled as a tail call.

Deleted: If `exprValue` is an abrupt completion, return `exprValue`

Deleted: (

Deleted: `GetValue(`

Deleted: `exprRef`)

Deleted:).

Deleted: current

Deleted: Semantics¶ The static semantics of the production

Deleted: are:

Deleted: static

Deleted: The `VarDeclaredNames` of the production

Deleted: is determined as follows:

Deleted: The production

Deleted: is evaluated as follows:

Deleted: If `obj` is an abrupt completion, return a

Deleted: running

Deleted: current

5. Let *newEnv* be the result of calling `NewObjectEnvironment` passing *obj* and *oldEnv* as the arguments.
6. Set the *withEnvironment* flag of *newEnv* to **true**.
7. Set the *running* execution context's `LexicalEnvironment` to *newEnv*.
8. Let *C* be the result of evaluating *Statement*.
9. Set the *running* execution context's `LexicalEnvironment` to *oldEnv*.
10. Return *C*.

NOTE No matter how control leaves the embedded *Statement*, whether normally or by some form of abrupt completion or exception, the `LexicalEnvironment` is always restored to its former state.

12.11 The `switch` Statement

Syntax

`SwitchStatement` :
`switch (Expression) CaseBlock`

`CaseBlock` :
`{ CaseClausesopt }`
`{ CaseClausesopt DefaultClause CaseClausesopt }`

`CaseClauses` :
`CaseClause`
`CaseClauses CaseClause`

`CaseClause` :
`case Expression : StatementListopt`

`DefaultClause` :
`default : StatementListopt`

Static Semantics

Static Semantics: Early Errors

`CaseBlock : { CaseClauses }`

Deleted: *provideThis*

Deleted: running

Deleted: current

Deleted: but if an exception is thrown during the evaluation let *C* be (`throw, V, empty`), where *V* is the exception. (Execution now proceeds as if no exception were thrown.)

Deleted: running

Deleted: current

Deleted: 12.10.1 Strict Mode Restrictions¶

Strict mode code may not include a `WithStatement`. The occurrence of a `WithStatement` in such a context is treated as a `SyntaxError`.¶

Static Semantics: LexicalDeclarations

`CaseBlock : {}`

1. Return a new empty List.

`CaseBlock : { CaseClausesopt DefaultClause CaseClausesopt }`

Deleted: are:

Deleted: i

1. If the first *CaseClauses* is present, let *declarations* be the `LexicalDeclarations` of the first *CaseClauses*.
2. Else let *declarations* be a new empty List.
3. Append to *declarations* the elements of the `LexicalDeclarations` of the *DefaultClause*.
4. If the second *CaseClauses* is not present, return *declarations*.
5. Else return the result of appending to *declarations* the elements of the `LexicalDeclarations` of the second *CaseClauses*.

Deleted: `CaseClause : case Expression : StatementList`
`<#> It is a Syntax Error if StatementList includes a StatementListItem : FunctionDeclaration production and no source code matching this CaseClause production is not contained in extended code.¶`

`CaseClauses : CaseClauses CaseClause`

1. Let *declarations* be `LexicalDeclarations` of *CaseClauses*.
2. Append to *declarations* the elements of the `LexicalDeclarations` of *CaseClause*.

Deleted: `CaseBlock : { CaseClauses }` ¶
`<#> Return the LexicalDeclarations of CaseClauses.¶`

Deleted: `LexicallyDeclaredNames`

Deleted: `names`

Deleted: `names`

Deleted: the

Deleted: `lyDeclaredNames`

Deleted: `CaseClauses : CaseClause` ¶
`<#> Return the LexicalDeclarations of CaseClause.¶`

Deleted: `names`

3. Return declarations.

CaseClause : case Expression : StatementList_{opt}

1. If the StatementList is present, return the LexicalDeclarations of StatementList.
2. Else return a new empty List.

DefaultClause : default : StatementList_{opt}

1. If the StatementList is present, return the LexicalDeclarations of StatementList.
2. Else return a new empty List.

Static Semantics: LexicallyDeclaredNames

CaseBlock : { }

1. Return a new empty List.

CaseBlock : { CaseClauses_{opt} DefaultClause CaseClauses_{opt} }

1. If the first CaseClauses is present, let names be the LexicallyDeclaredNames of the first CaseClauses.
2. Else let names be a new empty List.
3. Append to names the elements of the LexicallyDeclaredNames of the DefaultClause.
4. If the second CaseClauses is not present, return names.
5. Else return the result of appending to names the elements of the LexicallyDeclaredNames of the second CaseClauses.

CaseClauses : CaseClauses CaseClause

1. Let names be LexicallyDeclaredNames of CaseClauses.
2. Append to names the elements of the LexicallyDeclaredNames of CaseClause.
3. Return names.

CaseClause : case Expression : StatementList_{opt}

1. If the StatementList is present, return the LexicallyDeclaredNames of StatementList.
2. Else return a new empty List.

DefaultClause : default : StatementList_{opt}

1. If the StatementList is present, return the LexicallyDeclaredNames of StatementList.
2. Else return a new empty List.

Static Semantics: VarDeclaredNames

SwitchStatement : switch (Expression) CaseBlock

1. Return the VarDeclaredNames of CaseBlock.

CaseBlock : { }

1. Return a new empty List.

CaseBlock : { CaseClauses_{opt} DefaultClause CaseClauses_{opt} }

1. If the first CaseClauses is present, let names be the VarDeclaredNames of the first CaseClauses.
2. Else let names be a new empty List.
3. Append to names the elements of the VarDeclaredNames of the DefaultClause.
4. If the second CaseClauses is not present, return names.

Deleted: CaseBlock : { CaseClauses } ¶
 ↳ Return the LexicallyDeclaredNames of CaseClauses. ¶

Deleted: the

Deleted: CaseClauses : CaseClause ¶
 ↳ Return the LexicallyDeclaredNames of CaseClause. ¶

Deleted: Semantics ¶
 The VarDeclaredNames of the production
Deleted: is determined as follows:

Deleted: CaseBlock : { CaseClauses } ¶
 ↳ Return the VarDeclaredNames of CaseClauses

5. Else return the result of appending to *names* the elements of the VarDeclaredNames of the second *CaseClauses*.

Deleted: the

CaseClauses : CaseClauses CaseClause

Deleted: *CaseClauses* : *CaseClause* ¶
 <#>Return the VarDeclaredNames of *CaseClause*.¶

1. Let *names* be VarDeclaredNames of *CaseClauses*.

2. Append to *names* the elements of the VarDeclaredNames of *CaseClause*.

3. Return *names*.

CaseClause : case Expression : StatementList_{opt}

1. If the *StatementList* is present, return the VarDeclaredNames of *StatementList*.

2. Else return a new empty List.

DefaultClause : default : StatementList_{opt}

1. If the *StatementList* is present, return the VarDeclaredNames of *StatementList*.

2. Else return a new empty List.

Runtime Semantics

Runtime Semantics: Case Block Evaluation

With argument *input*.

CaseBlock : { CaseClauses_{opt} }

1. Let *V*=undefined.
2. Let *A* be the list of *CaseClause* items in source text order.
3. Let *searching* be **true**.
4. Repeat, while *searching* is **true**
 - a. Let *C* be the next *CaseClause* in *A*. If there is no such *CaseClause*, return NormalCompletion(*V*).
 - b. Let *clauseSelector* be the result of evaluating *C*.
 - c. ReturnIfAbrupt(*clauseSelector*).
 - d. If *input* is equal to *clauseSelector* as defined by the Strict Equality Comparison Algorithm (11.9.1), then
 - i. Set *searching* to **false**.
 - ii. If *C* has a *StatementList*, then
 1. Evaluate *C*'s *StatementList* and let *R* be the result.
 2. ReturnIfAbrupt(*r*).
 3. Let *V*=*R*[[value]].
5. Repeat
 - a. Let *C* be the next *CaseClause* in *A*. If there is no such *CaseClause*, return NormalCompletion(*V*).
 - b. If *C* has a *StatementList*, then
 - i. Evaluate *C*'s *StatementList* and let *R* be the result.
 - ii. If *R*[[value]] is not empty, then let *V*=*R*[[value]].
 - iii. If *R* is an abrupt completion, then return Completion {[[type]]: *R*[[type]], [[value]]: *V*, [[target]]: *R*[[target]]}.

CaseBlock : { CaseClauses_{opt} DefaultClause CaseClauses_{opt} }

1. Let *V*=undefined.
2. Let *A* be the list of *CaseClause* items in the first *CaseClauses*, in source text order.
3. Let *found* be **false**.
4. Repeat letting *C* be in order each *CaseClause* in *A*
 - a. If *found* is **false**, then
 - i. Let *clauseSelector* be the result of Case Selector Evaluation of C.
 - ii. If *clauseSelector* is an abrupt completion, then
 1. If *clauseSelector*[[value]] is empty, then return Completion {[[type]]: *clauseSelector*[[type]], [[value]]: undefined, [[target]]: *clauseSelector*[[target]]}.

Deleted: Runtime Semantics: Evaluation¶
 The production *SwitchStatement* : **switch** (*Expression*) *CaseBlock* is evaluated as follows:¶
 <#>Let *exprRef* be the result of evaluating *Expression*.¶
 <#>Let *oldEnv* be the running execution context's LexicalEnvironment.¶
 <#>Let *blockEnv* be the result of calling NewDeclarativeEnvironment passing *oldEnv* as the argument.¶
 <#>Perform Block Declaration Instantiation using *CaseBlock* and *blockEnv*.¶
 <#>Let *R* be the result of evaluating *CaseBlock*, passing it *GetValue(exprRef)* as a parameter.¶
 <#>Set the running execution context's LexicalEnvironment to *oldEnv*.¶
 <#>If *R*.type is **break** and *R*.target is in the current label set, return (normal, *R*.value, empty).¶
 <#>Return *R*.¶
 NOTE: No matter how control leaves the *SwitchStatement*, the LexicalEnvironment is always restored to its former state.¶

Deleted: The production

Deleted: is given an input parameter, *input*, and is evaluated as follows:

Comment [AWB689]: ES5 breaking change: completion reform

Deleted: empty

Deleted: (normal,

Deleted: , empty

Deleted: If *clauseSelector* is an abrupt completion, return *clauseSelector*

Deleted: 6

Deleted: === operator

Deleted: If *R* is an abrupt completion, then return *R*

Deleted: (normal,

Deleted: , empty

Deleted: (

Deleted:).

Deleted: The production

Deleted: is given an input parameter, *input*, and is evaluated as follows:

Comment [AWB690]: ES5 breaking change: completion reform

Deleted: empty

Deleted: <#>Let *B* be the list of *CaseClause* items in the second *CaseClauses*, in source text order.¶

Deleted: evaluating

2. Else, return clauseSelector.
- If input is equal to clauseSelector as defined by the Strict Equality Comparison Algorithm (11.9.1), then set found to true.
 - If found is true, then
 - Evaluate CaseClause C and let R be the result.
 - If R.[[value]] is not empty, then let V = R.[[value]].
 - If R is an abrupt completion, then return Completion {[[type]]: R.[[type]], [[value]]: V, [[target]]: R.[[target]]}.
5. Let foundInB be false.
6. If found is false, then
 - Let B be a new list of the CaseClause items in the second CaseClauses, in source text order.
 - Repeat, letting C be in order each CaseClause in B.
 - If foundInB is false, then
 - Let clauseSelector be the result of Case Selector Evaluation of C.
 - If clauseSelector is an abrupt completion, then
 - If clauseSelector.[[value]] is empty, then return Completion {[[type]]: clauseSelector.[[type]], [[value]]: undefined, [[target]]: clauseSelector.[[target]]}.
 - Else, return clauseSelector.
 - If input is equal to clauseSelector as defined by the Strict Equality Comparison Algorithm (11.9.1), then set foundInB to true.
 - If foundInB is true, then
 - Evaluate CaseClause C and let R be the result.
 - If R.[[value]] is not empty, then let V = R.[[value]].
 - If R is an abrupt completion, then return Completion {[[type]]: R.[[type]], [[value]]: V, [[target]]: R.[[target]]}.

7. If foundInB is true, then return NormalCompletion(V).

8. Evaluate DefaultClause and let R be the result.

9. If R.[[value]] is not empty, then let V = R.[[value]].

10. If R is an abrupt completion, then return Completion {[[type]]: R.[[type]], [[value]]: V, [[target]]: R.[[target]]}.

11. Let B be a new list of the CaseClause items in the second CaseClauses, in source text order.

12. Repeat, letting C be in order each CaseClause in B (NOTE this is another complete iteration of the second CaseClauses)

 - Evaluate CaseClause C and let R be the result.
 - If R.[[value]] is not empty, then let V = R.[[value]].
 - If R is an abrupt completion, then return Completion {[[type]]: R.[[type]], [[value]]: V, [[target]]: R.[[target]]}.

13. Return NormalCompletion(V).

Runtime Semantics: Case Selector Evaluation

CaseClause : case Expression : StatementList_{opt}

- Let exprRef be the result of evaluating Expression.
- Return GetValue(exprRef).

NOTE Case Selector Evaluation does not execute the associated StatementList. It simply evaluates the Expression and returns the value, which the CaseBlock algorithm uses to determine which StatementList to start executing.

Runtime Semantics: Evaluation

SwitchStatement : switch (Expression) CaseBlock

- Let exprRef be the result of evaluating Expression.
- Let switchValue be GetValue(exprRef).
- ReturnIfAbrupt(switchValue).
- Let oldEnv be the running execution context's LexicalEnvironment.
- Let blockEnv be the result of calling NewDeclarativeEnvironment passing oldEnv as the argument.
- Perform Block Declaration Instantiation using CaseBlock and blockEnv.
- Let R be the result of performing Case Block Evaluation of CaseBlock with argument switchValue.
- Set the running execution context's LexicalEnvironment to oldEnv.

Deleted: 6
Deleted: === operator
Deleted: <#>If C has a StatementList, then
Deleted: 's StatementList
Deleted: ()
Deleted:).

Deleted: while foundInB is false and all elements of B have not been processed
Deleted: <#>Let C be the next CaseClause in B
Deleted: evaluating

Deleted: 6
Deleted: === operator
Deleted: ¶ S
Deleted: If C has a StatementList,
Deleted: C's StatementList
Deleted: ()
Deleted:).

Deleted: <#>If foundInB is false and the DefaultClause has a StatementList, then
Deleted: the
Deleted: 's StatementList
Deleted: (R.type, V, R.target)
Deleted: Note
Deleted: that if step 7.a.i has been performed the loop does not start at the beginning of B
Deleted: <#>Let C be the next CaseClause in B there is no such CaseClause, return NormalCompletion(normal, V, empty). ¶
<#>If C has a StatementList, then ¶
Deleted: 's StatementList
Deleted: return (R.type, V, R.target)
Deleted: Evaluating
Deleted: CaseClause

Deleted: If switchValue is an abrupt completion return switchValue
Deleted: running
Deleted: current
Deleted: running
Deleted: current

9. Return R .

NOTE No matter how control leaves the *SwitchStatement* the *LexicalEnvironment* is always restored to its former state.

CaseClause : **case** *Expression* : [empty]

1. Return NormalCompletion(empty).

CaseClause : **case** *Expression* : *StatementList*

1. Return the result of evaluating *StatementList*.

DefaultClause : **default**: [empty]

1. Return NormalCompletion(empty).

DefaultClause : **default**: *StatementList*

1. Return the result of evaluating *StatementList*.

12.12 Labelled Statements

Syntax

LabelledStatement :
 Identifier : *Statement*

NOTE A *Statement* may be prefixed by a label. Labelled statements are only used in conjunction with labelled **break** and **continue** statements. ECMAScript has no **goto** statement. A *Statement* can be part of a *LabelledStatement*, which itself can be part of a *LabelledStatement*, and so on. The labels introduced this way are collectively referred to as the "current label set" when describing the semantics of individual statements. A *LabelledStatement* has no semantic meaning other than the introduction of a label to a label set. The label set of an *IterationStatement* or a *SwitchStatement* initially contains the single element **empty**. The label set of any other statement is initially empty.

Static Semantics

Static Semantics: Early Errors

- It is a Syntax Error if a *LabelledStatement* is enclosed by a *LabelledStatement* with the same *Identifier* as label. This does not apply to labels appearing within the body of a *FunctionDeclaration* that is nested, directly or indirectly, within a labelled statement.

Static Semantics: VarDeclaredNames

LabelledStatement : *Identifier* : *Statement*

1. Return the VarDeclaredNames of *Statement*.

Runtime Semantics

Runtime Semantics: Labelled Evaluation

With argument *labelSet*.

LabelledStatement : *Identifier* : *Statement*

1. Let *label* be the StringValue of *Identifier*.

Deleted: <#>If $R.[[type]]$ is **break** and $R.[[target]]$ is in *CurrentLabelSet*, return NormalCompletion($R.[[value]]$).¶

Deleted: The production

Deleted: opt

Deleted: is evaluated as follows:

Deleted: <#>Let *exprRef* be the result of evaluating *Expression*.¶
<#>Return GetValue(*exprRef*).¶
NOTE Evaluating *CaseClause* does not execute the associated *StatementList*. It simply evaluates the *Expression* and returns the value, which the *CaseBlock* algorithm uses to determine which *StatementList* to start executing.¶

Deleted: Semantics¶

Deleted: An ECMAScript program is considered syntactically incorrect if it contains

Deleted: that

Deleted: The VarDeclaredNames of the production *DefaultCase*

Deleted: *t* is determined as follows:

2. Let `newLabelSet` be a new List containing `label` and the elements of `labelSet`.
3. If Statement is either `LabelledStatement` or `BreakableStatement`, then
 - a. Let `stmtResult` be the result of performing Labelled Evaluation of `Statement` with argument `newLabelSet`.
4. Else,
 - a. Let `stmtResult` be the result of evaluating `Statement`.
5. If `stmtResult.[[type]]` is `break` and `stmtResult.[[target]]` is the same value as `label`, then
 - a. Let `result` be `NormalCompletion(stmtResult.[[value]])`.
6. Else, let `result` be `stmtResult`.
7. Return `result`.

Runtime Semantics: Evaluation

`LabelledStatement : Identifier : Statement`

3. Let `newLabelSet` be a new empty List.
4. Return the result of performing Labelled Evaluation of this `LabelledStatement` with argument `newLabelSet`.

12.13 The `throw` Statement

Syntax

`ThrowStatement :`
`throw [no LineTerminator here] Expression ;`

Runtime Semantics: Evaluation

The production `ThrowStatement : throw [no LineTerminator here] Expression ;` is evaluated as follows:

1. Let `exprRef` be the result of evaluating `Expression`.
2. Let `exprValue` be `GetValue(exprRef)`.
3. Return `IfAbrupt(exprValue)`.
4. Return `Completion {[[type]]: throw, [[value]]: GetValue(exprRef), [[target]]: empty}`.

12.14 The `try` Statement

Syntax

`TryStatement :`
`try Block Catch`
`try Block Finally`
`try Block Catch Finally`

`Catch :`
`catch (CatchParameter) Block`

`Finally :`
`finally Block`

`CatchParameter :`
`BindingIdentifier`
`BindingPattern`

NOTE The `try` statement encloses a block of code in which an exceptional condition can occur, such as a runtime error or a `throw` statement. The `catch` clause provides the exception-handling code. When a catch clause catches an exception, its `Identifier` is bound to that exception.

Deleted: The production `Identifier : Statement` is evaluated by adding `Identifier` to the label set of `Statement` and then evaluating `Statement`. If the `LabelledStatement` itself has a non-empty label set, these labels are also added to the label set of `Statement` before evaluating it. If the result of evaluating `Statement` is `(break, V, L)` where `L` is equal to `Identifier`, the production results in `(normal, V, empty)`.¶

Deleted: Prior to the evaluation of a `LabelledStatement`, the contained `Statement` is regarded as possessing an empty label set, unless it is an `IterationStatement` or a `SwitchStatement`, in which case it is regarded as possessing a label set consisting of the single element, `empty`.¶

Deleted: Semantics¶

Deleted: `Identifier`

Formatted: Note

Catch : catch (CatchParameter) Block

- It is a Syntax Error if any element of the BoundNames of *CatchParameter* also occurs in the *LexicallyDeclaredNames of Block*.
- It is a Syntax Error if any element of the BoundNames of *CatchParameter* also occurs in the *VarDeclaredNames of Block*.

Deleted: the code that matches this production is contained in extended code and

Comment [AWB91]: Note that this is a new restriction that does not exist in ES5

Static Semantics: VarDeclaredNames

TryStatement : try Block Catch

1. Let *names* be *VarDeclaredNames of Block*.
2. Append to *names* the elements of the *VarDeclaredNames of Catch*.
3. Return *names*.

Deleted: Static Semantics: *BoundNames*
CatchParameter: *BindingIdentifier* ¶
 <#>Return the BoundNames of *BindingIdentifier*.¶
CatchParameter: *BindingPattern* ¶
 <#>Return the BoundNames of *BindingPattern*.¶

Deleted: Semantics¶
 The *VarDeclaredNames* of the production

Deleted: is determined as follows:

TryStatement : try Block Finally

1. Let *names* be *VarDeclaredNames of Block*.
2. Append to *names* the elements of the *VarDeclaredNames of Finally*.
3. Return *names*.

TryStatement : try Block Catch Finally

1. Let *names* be *VarDeclaredNames of Block*.
2. Append to *names* the elements of the *VarDeclaredNames of Catch*.
3. Append to *names* the elements of the *VarDeclaredNames of Finally*.
4. Return *names*.

Catch : catch (CatchParameter) Block

1. Return the *VarDeclaredNames of Block*.

Deleted: *Finally* : *finally Block* ¶
 <#>Return the *VarDeclaredNames of Block*.¶

Deleted: Initialization

Deleted: environment

Runtime Semantics

Runtime Semantics: Binding Initialisation

With arguments *value* and *environment*.

NOTE *undefined* is passed for *environment* to indicate that a *PutValue* operation should be used to assign the *initialisation* value. This is the case for *var* statements formal parameter lists of non-strict functions. In those cases a lexical binding is hosted and preinitialized prior to evaluation of its initializer.

Deleted: initialization

Deleted: the

Deleted: *CatchParameter*: *BindingIdentifier* ¶
 <#>PerformReturn the result of performing Binding
 InitialisationInitialisation for *BindingIdentifier* passing *value* and *environment* as the arguments.¶

Comment [AWB1092]: Catching a thrown null or undefined with a destructuring parameter rethrows a *TypeError*. Does this make sense?

Deleted: Perform

Deleted: Initialization

Deleted: environment

Runtime Semantics: Catch Clause Evaluation

with parameter *thrownValue*

Catch : catch (CatchParameter) Block

1. Let *oldEnv* be the *running* execution context's *LexicalEnvironment*.
2. Let *catchEnv* be the result of calling *NewDeclarativeEnvironment* passing *oldEnv* as the argument.
3. For each element *argName* of the *BoundNames* of *CatchParameter*, do
 - a. Call the *CreateMutableBinding* concrete method of *catchEnv* passing *argName* as the argument.

Deleted: running

Deleted: current

4. Let *status* be the result of performing *BindingInitialisation* for *CatchParameter* passing *thrownValue* and *catchEnv* as arguments.
5. ReturnIfAbrupt(*status*).
6. Set the *running execution context's LexicalEnvironment* to *catchEnv*.
7. Let *B* be the result of evaluating *Block*.
8. Set the *running execution context's LexicalEnvironment* to *oldEnv*.
9. Return *B*.

NOTE No matter how control leaves the *Block* the *LexicalEnvironment* is always restored to its former state.

Runtime Semantics: Evaluation

TryStatement : try Block Catch

1. Let *B* be the result of evaluating *Block*.
2. If *B*[[type]] is not *throw*, return *B*.
3. Return the result of *performing Catch Clause Evaluation of Catch* with parameter *B*.[[value]].

TryStatement : try Block Finally

1. Let *B* be the result of evaluating *Block*.
2. Let *F* be the result of evaluating *Finally*.
3. If *F*[[type]] is *normal*, return *B*.
4. Return *F*.

TryStatement : try Block Catch Finally

1. Let *B* be the result of evaluating *Block*.
2. If *B*[[type]] is *throw*, then
 - a. Let *C* be the result of *performing Catch Clause Evaluation of Catch* with parameter *B*.value.
3. Else, *B*[[type]] is not *throw*,
 - a. Let *C* be *B*.
4. Let *F* be the result of evaluating *Finally*.
5. If *F*[[type]] is *normal*, return *C*.
6. Return *F*.

12.15 The debugger statement

Syntax

DebuggerStatement :
 debugger ;

Runtime Semantics: Evaluation

NOTE Evaluating the *DebuggerStatement* production may allow an implementation to cause a breakpoint when run under a debugger. If a debugger is not present or active this statement has no observable effect.

The production *DebuggerStatement : debugger ;* is evaluated as follows:

1. If an implementation defined debugging facility is available and enabled, then
 - a. Perform an implementation defined debugging action.
 - b. Let *result* be an implementation defined Completion value.
2. Else
 - a. Let *result* be *NormalCompletion*(*empty*).
3. Return *result*.

Deleted: Perform
Deleted: Initialization
Deleted: <i>g</i>
Deleted: If an exception was thrown in the preceding step, return (<i>throw</i> , <i>V</i> , <i>empty</i>) where <i>V</i> is the exception. (Execution now proceeds as if no exception were thrown.) <i>status</i> is an abrupt completion, then return <i>status</i>
Deleted: <i>running</i>
Deleted: <i>current</i>
Deleted: <i>running</i>
Deleted: <i>current</i>
Deleted: The production
Deleted: is evaluated as follows:
Deleted: evaluating
Deleted: The production
Deleted: is evaluated as follows:
Deleted: The production
Deleted: is evaluated as follows:
Deleted: evaluating
Deleted: The production
Deleted: is evaluated as follows:
Deleted: evaluating
Deleted: The production <i>Catch : catch</i> (<i>IdentifierCatchParameter</i>) <i>Block</i> is evaluated with parameter <i>C</i> as follows: <i><#></i> Let <i>C</i> be the parameter that has been passed to this production. <i><#></i> Let <i>oldEnv</i> be the running execution context's LexicalEnvironment. <i><#></i> Let <i>catchEnv</i> be the result of calling NewDeclarativeEnvironment passing <i>oldEnv</i> as the argument. <i><#></i> For each element <i>argName</i> of the BoundNames of <i>CatchParameter</i> , do <i><#></i> Call the CreateMutableBinding concrete method of <i>catchEnv</i> passing <i>argName</i> the <i>Identifier</i> String value as the argument. <i><#></i> Call the Evaluate <i>CatchParameter</i> SetMutableBinding using concrete method of <i>catchEnv</i> passing the <i>Identifier</i> , <i>C</i> and <i>catEnv</i> , and <i>false</i> as arguments. Note that the last argument is immaterial in this situation. <i><#></i> If an exception was thrown in the preceding step, return (<i>throw</i> , <i>V</i> , <i>empty</i>) where <i>V</i> is the exception. (Execution now proceeds as if no exception were thrown.) <i><#></i> Set the running execution context's LexicalEnvironment to <i>catchEnv</i> . <i><#></i> Let <i>B</i> be the result of evaluating <i>Block</i> . <i><#></i> Set the running execution context's LexicalEnvironment to <i>oldEnv</i> . <i><#></i> Return <i>B</i> .
Deleted: The production <i>Finally : finally</i> <i>Block</i> is evaluated as follows: <i><#></i> The BoundNames of the production <i>CatchParameter : BindingIdentifier</i> is determined.
Deleted: Semantics
Deleted: Runtime Semantics: Evaluation
Deleted: (normal,
Deleted: , empty

13 Functions and Generators

13.1 Function Definitions

Syntax

FunctionDeclaration :

`function BindingIdentifier (FormalParameterList) { FunctionBody }`

Deleted: opt

FunctionExpression :

`function BindingIdentifieropt (FormalParameterList) { FunctionBody }`

Deleted: opt

FormalParameterList :

`[empty]
FunctionRestParameter
FormalsList
FormalsList , FunctionRestParameter`

Deleted: ... Identifier

Deleted: ... Identifier

Deleted: FormalParameterList

Deleted: Identifier

Deleted: FormalParameterList

Deleted: Identifier

Deleted: BindingIdentifier Initialiser_{opt}

Deleted: Pattern

Deleted: Initialiser_{opt}

Deleted: SourceElements_{opt}

Deleted: NOTE . The identifier of a rest parameter is specified as an *Identifier* rather than a *BindingIdentifier* because it may be the identifier `arguments..`¶

Deleted: Semantics¶

Deleted: <#> It is a Syntax Error if the source code matching this production is extended code and the *BoundNames* of *BindingIdentifier* also occurs in the *VarDeclaredNames* of *FunctionBody*.¶
<#> It is a Syntax Error if the source code matching this production is extended code and the *BoundNames* of *BindingIdentifier* also occurs in the *LexicallyDeclaredNames* of *FunctionBody*.¶

Deleted: <#> It is a Syntax Error if the source code matching this production is extended code and any element of the *LexicallyDeclaredNames* of *FormalParameterList* also occurs in the *VarDeclaredNames* of *FunctionBody*.¶

Deleted: the source code matching this production is extended code and

Comment [AWB693]: There is an issue that function declarations have "lexically declared names" and in ES<5 nested functions are allowed to have the same name as vars or formal parameters. We either need to take this a breaking change or adjust this rule to only apply to function declarations nested within blocks.

Deleted: the source code matching this production is extended code and

Deleted: *BoundNames*

Deleted: *i*

Deleted: the source code matching this production is extended code and

Comment [AWB694]: Similar function declaration ES compat issues.

FunctionBody :

`StatementListopt`

Static Semantics

Static Semantics: Early Errors

FunctionDeclaration : function BindingIdentifier (FormalParameterList) { FunctionBody }

and

FunctionExpression : function BindingIdentifier_{opt} (FormalParameterList) { FunctionBody }

- It is a Syntax Error if any element of the *BoundNames* of *FormalParameterList* also occurs in the *LexicallyDeclaredNames* of *FunctionBody*.
- It is a Syntax Error if *FunctionBody* Contains *YieldExpression*.

FunctionBody : StatementList

- It is a Syntax Error if the *LexicallyDeclaredNames* of *StatementList* contains any duplicate entries.
- It is a Syntax Error if any element of the *LexicallyDeclaredNames* of *StatementList* also occurs in the *VarDeclaredNames* of *StatementList*.

FormalParameterList : FormalsList

- It is a Syntax Error if *FormalParameterList* Contains *YieldExpression*.
- It is a Syntax Error if *BoundNames* of *FormalsList* contains any duplicate elements and either *FormalsList* Contains *BindingPattern* or *FormalsList* Contains *Initialiser*.
- It is a Syntax Error if *BoundNames* of *FormalsList* contains either "eval" or "arguments" and either *FormalsList* Contains *BindingPattern* or *FormalsList* Contains *Initialiser*.

FormalParameterList : FormalsList , FunctionRestParameter

- It is a Syntax Error if *BoundNames* of *FormalsList* contains any duplicate elements.
- It is a Syntax Error if *BoundNames* of *FormalsList* contains any element of the *BoundNames* of *FunctionRestParameter*.

FormalsList : *FormalsList* , *FormalParameter*

- It is a Syntax Error if the source code matching this production is strict code and *BoundNames* of *FormalsList* contains any element which is also contained in *BoundNames* of *FormalParameter*.

FunctionRestParameter : ... *BindingIdentifier*

- It is a Syntax Error if the StringValue of the sole element of *BindingIdentifier* is eval or arguments.

FormalParameter : *BindingElement*

- It is a Syntax Error if *BoundNames* of *BindingElement* contains any duplicate elements.

Static Semantics: BoundNames

FunctionDeclaration : function *BindingIdentifier* (*FormalParameterList*) { *FunctionBody* }

1. Return the *BoundNames* of *BindingIdentifier*.

FormalParameterList : [empty]

1. Return an empty List.

FormalParameterList : *FormalsList* , *FunctionRestParameter*

1. Let *names* be *BoundNames* of *FormalsList*.
2. Append to *names* the *BoundNames* of *FunctionRestParameter*.
3. Return *names*.

FormalsList : *FormalsList* , *FormalParameter*

1. Let *names* be *BoundNames* of *FormalsList*.
2. Append to *names* the elements of *BoundNames* of *FormalParameter*.
3. Return *names*.

Static Semantics: Contains

With parameter symbol.

FunctionDeclaration : function *BindingIdentifier* (*FormalParameterList*) { *FunctionBody* }

1. Return false.

FunctionExpression : function *BindingIdentifier*_{opt} (*FormalParameterList*) { *FunctionBody* }

3. Return false.

NOTE Static semantic rules that depend upon substructure generally do not look into function definitions.

Static Semantics: ExpectedArgumentCount

FormalParameterList :

- [empty]
- FunctionRestParameter*

Deleted:
Deleted: the
Deleted: String Value
Deleted: Identifier

Deleted:

Deleted: <#>It is a Syntax Error if the source code parsed with this production is not extended code.¶
 <#>It is a Syntax Error if Identifier is "eval" or arguments.

Deleted: <#>It is a Syntax Error if the derivation of *BindingElement* is *BindingIdentifier* Initialiser and the source code matching this production is not extended code.¶
 <#>It is a Syntax Error if the derivation of *BindingElement* is *BindingPattern* Initialiser_{opt} and the source code parsed with this production is not extended code.¶

Deleted: *FormalParameterList* :
FunctionRestParameter¶
 <#>Return the *BoundNames* of *FunctionRestParameter*.¶
FormalParameterList : *FormalsList*¶
 <#>Return the *BoundNames* of *FormalsList*.¶

Deleted: *FormalParameterList* : ...
BindingIdentifier¶
 <#>Return the *BoundNames* String Value of *BindingIdentifier*.¶
FormalParameter : *BindingElement* ¶
 <#>Return the *BoundNames* of *BindingElement*.

1. Return 0.

FormalParameterList :
FormalsList , FunctionRestParameter

Deleted: *FormalsList*

1. Return the ExpectedArgumentCount of *FormalsList*.

NOTE The *ExpectedArgumentCount* of a *FormalParameterList* is the number of *FormalParameters* to the left of either the rest parameter or the first *FormalParameter* with an Initialiser. A *FormalParameter* without an initialiser is allowed after the first parameter with an initializer but such parameters are considered to be optional with *undefined* as their default value.

Deleted: are

FormalsList : FormalParameter

1. If HasInitialiser of *FormalParameter* is false return 0
2. Return 1.

FormalsList : FormalsList , FormalParameter

1. Let *count* be the *ExpectedArgumentCount* of *FormalsList*.
2. If HasInitialiser of *FormalsList* is true or HasInitialiser of *FormalParameter* is true, then return *count*.
3. Return *count*+1.

Static Semantics: HasInitialiser

FormalsList : FormalsList , FormalParameter

Deleted: *FormalsList : FormalParameter* ¶
 <#>Return HasInitialiser of *FormalParameter*.¶

1. If HasInitialiser of *FormalsList* is true, then return true.
2. Return HasInitialiser of *FormalParameter*.

Static Semantics: IsConstantDeclaration

FunctionDeclaration : function BindingIdentifier (FormalParameterList) { FunctionBody }

1. Return false.

Static Semantics: IsStrict

FunctionBody : StatementList_{opt}

1. If this *FunctionBody* is contained in strict code or if *StatementList* is strict code, then return true.
Otherwise, return false.

Comment [AWB1095]: Need a better definition

Static Semantics: LexicallyDeclaredNames

FunctionDeclaration : function BindingIdentifier (FormalParameterList) { FunctionBody }

1. Return the BoundNames of *BindingIdentifier*.

FunctionBody : [empty]

1. Return an empty List.

Static Semantics: VarDeclaredNames

FunctionDeclaration : function BindingIdentifier (FormalParameterList) { FunctionBody }

1. Return an empty List.

Deleted: *FunctionBody : StatementList* ¶
 <#>Return the LexicallyDeclaredNames of *StatementList*.¶

FunctionBody : [empty]

1. Return an empty List.

Runtime Semantics

Runtime Semantics: Binding Initialisation

With parameters value and environment and optional parameter index.

NOTE When undefined is passed for environment it indicates that a PutValue operation should be used to assign the initialisation value. This is the case for formal parameter lists of non-strict functions. In that case the formal parameter bindings are preinitialized in order to deal with the possibility of multiple parameters with the same name.

FormalParameterList : [empty]

1. Return NormalCompletion(empty).

FormalParameterList : FunctionRestParameter

1. Return the result of performing Indexed Binding Initialisation for FunctionRestParameter using value, 0, and environment as the arguments.

FormalParameterList : FormalsList

1. Return the result of performing Indexed Binding Initialisation for FormalsList using value, 0, and environment as the arguments.

FormalParameterList : FormalsList , FunctionRestParameter

1. Let restIndex be the result of performing Indexed Binding Initialisation for FormalsList using value, 0, and environment as the arguments.
2. ReturnIfAbrupt(restIndex).
3. Return the result of performing Indexed Binding Initialisation for FunctionRestParameter using value, restIndex, and environment as the arguments.

Runtime Semantics: Indexed Binding Initialisation

With parameters array, nextIndex, and environment.

FormalsList : FormalParameter

1. Let status be the result of performing Indexed Binding Initialisation for FormalParameter using array, nextIndex, and environment as the arguments.
2. ReturnIfAbrupt(status).
3. Return nextIndex + 1.

FormalsList : FormalsList , FormalParameter

1. Let lastIndex be the result of performing Indexed Binding Initialisation for FormalsList using array, nextIndex, and environment as the arguments.
2. ReturnIfAbrupt(lastIndex).
3. Let status be the result of performing Indexed Binding Initialisation for FormalParameter using array, lastIndex, and environment as the arguments.
4. ReturnIfAbrupt(status).
5. Return lastIndex + 1.

Deleted: <u>FunctionBody</u> : <u>StatementList</u> ¶
<#>Return the VarDeclaredNames of <u>StatementList</u>
Deleted: Initialization
Deleted: <u>enviornment</u>
Deleted: initialization
Deleted: the
Deleted: Perform
Deleted: Initialization
Deleted: <u>lenValue</u> ,
Deleted: ¶
Return
Deleted: <#>Asset: <u>value</u> is a new created arguments object and hence it has a valid integer valued "length" property.¶
<#>Let <u>lenValue</u> be the result of calling the [[Get] internal method of <u>value</u> with argument "length".
Deleted: Perform
Deleted: Initialization
Deleted: <u>lenValue</u> ,
Deleted: <#>Return.¶
Deleted: Initialization
Deleted: <u>lenValue</u> ,
Deleted: Perform
Deleted: Initialization
Deleted: <u>lenValue</u> ,
Deleted: <#>Return.¶
Deleted: Initialization
Deleted: <u>lenValue</u> ,
Deleted: .[[value]]
Deleted: <#>Return.¶
Deleted: Initialization
Deleted: <u>arrayLength</u> ,
Deleted: Perform
Deleted: Initialization
Deleted: <u>value</u>
Deleted: <u>env</u> , and
Deleted: <u>i</u>
Deleted: <u>i</u>
Deleted: Initialization
Deleted: <u>value</u>
Deleted: <u>lenValue</u> ,
Deleted: Perform
Deleted: Initialization
Deleted: <u>value</u>
Deleted: <u>lenValue</u> ,

FunctionRestParameter : . . . BindingIdentifier

1. Assert: array is a well formed arguments object and hence it has a valid integer valued "length" property.
2. Let status be the result of calling the [[Get]] internal method of array with argument "length".
3. Let argumentsLength be status.[[value]].
4. Let A be the result of the abstract operation ArrayCreate (15.4) with argument 0.
5. Let n=0;
6. Repeat, while nextIndex < argumentsLength,
 - a. Let P be ToString(nextIndex).
 - b. Assert: array is a well formed arguments object, hence it must have a property P.
 - c. Let v be the result of calling the [[Get]] internal method of array passing P as the argument.
 - d. Call the [[DefineOwnProperty]] internal method of A with arguments ToString(n), Property Descriptor {[[Value]]: v.[[value]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}, and false.
 - e. Let n = n+1.
 - f. Let nextIndex = nextIndex + 1.
7. Return the result of performing BindingInitialization for BindingIdentifier using A and environment as arguments.

Runtime Semantics: Instantiate Function Declaration

FunctionDeclaration : function BindingIdentifier (FormalParameterList) { FunctionBody }

1. If the FunctionDeclaration is contained in strict code or if its FunctionBody is strict code, then let strict be true. Otherwise let strict be false.
2. Let scope be the LexicalEnvironment of the running execution context.
3. Let F be the result of performing the FunctionCreate abstract operation with arguments Normal, FormalParameterList, FunctionBody, scope, and strict.
4. Perform the abstract operation MakeConstructor with argument F.
5. Return F.

Runtime Semantics: Evaluation

FunctionDeclaration : function BindingIdentifier (FormalParameterList) { FunctionBody }

1. Return (normal, empty, empty).

FunctionExpression : function (FormalParameterList) { FunctionBody }

1. If the FunctionExpression is contained in strict code or if its FunctionBody is strict code, then let strict be true. Otherwise let strict be false.
2. Let scope be the LexicalEnvironment of the running execution context.
3. Let closure be the result of performing the FunctionCreate abstract operation with arguments Normal, FormalParameterList, FunctionBody, scope, and strict.
4. Perform the abstract operation MakeConstructor with argument closure.
5. Return closure.

FunctionExpression : function BindingIdentifier (FormalParameterList) { FunctionBody }

1. If the FunctionExpression is contained in strict code or if its FunctionBody is strict code, then let strict be true. Otherwise let strict be false.
2. Let funcEnv be the result of calling NewDeclarativeEnvironment passing the running execution context's Lexical Environment as the argument
3. Let envRec be funcEnv's environment record.
4. Let name be StringValue of BindingIdentifier.
5. Call the CreateImmutableBinding concrete method of envRec passing name as the argument.
6. Let closure be the result of performing the FunctionCreate abstract operation with arguments Normal, FormalParameterList, FunctionBody, funcEnv, and strict.
7. Perform the abstract operation MakeConstructor with argument closure.

Deleted: argumentsLength
Deleted: value
Deleted: argumentsLength
Deleted: ion
Deleted: a new array object created as if by the expression new Array() where Array is the standard built-in constructor with that name
Deleted: arrayLength
Deleted: Perform
Deleted: Initialization
Deleted: FormalParameter : BindingElement ¶ ->#>Return the result of performing PerformIndexedBindInitializationInitialization for BindingElement using array, arrayLength, nextIndex, and environment as the arguments.
Deleted: current
Deleted: ing
Deleted: The production
Deleted: opt
Deleted: .. is instantiated as follows during Declaration Binding instantiation (10.5):
Deleted: Return the result of creating a new Function object as specified in 13.2 with parameters specified by FormalParameterList _{opt} and body specified by FunctionBody. Pass in the VariableEnvironment of the running execution context as the Scope. Pass in true as the Strict flag if the FunctionDeclaration is contained in strict code or if its FunctionBody is strict code.
Deleted: The production
Deleted: opt
Deleted: .. is evaluated as follows:
Deleted: current
Deleted: ing
Deleted: the result of creating a new Function object as specified in 13.2 with parameters specified by FormalParameterList _{opt} and body specified by FunctionBody. Pass in the LexicalEnvironment of the running execution context as the Scope. Pass in true as the Strict flag if the FunctionExpression is contained in strict code or if its FunctionBody is strict code
Deleted: opt
Deleted: running
Deleted: current
Deleted:
Deleted: the String value of BindingIdentifier
Deleted: <#>Let closure be the result of creating a new Function object as specified in 13.2 with parameters specified by FormalParameterList _{opt} and body specified by FunctionBody. Pass in funcEnv as the Scope. Pass in true as the Strict flag if the FunctionExpression is contained in strict code or if its FunctionBody is strict code.¶
Deleted: ing

8. Call the `InitializeBinding` concrete method of `envRec` passing `name` and `closure` as the arguments.
 9. Return `NormalCompletion(closure)`.

NOTE 1 The `BindingIdentifier` in a `FunctionExpression` can be referenced from inside the `FunctionExpression`'s `FunctionBody` to allow the function to call itself recursively. However, unlike in a `FunctionDeclaration`, the `BindingIdentifier` in a `FunctionExpression` cannot be referenced from and does not affect the scope enclosing the `FunctionExpression`.

NOTE 2 A `prototype` property is automatically created for every function defined using a `FunctionDeclaration` or `FunctionExpression`, to allow for the possibility that the function will be used as a constructor.

`FunctionBody` : `StatementListopt`

1. The code of this `FunctionBody` is strict mode code if it is contained in strict mode code or if the Directive Prologue (14.1) of its `StatementList` contains a Use Strict Directive or if any of the conditions in 10.1.1 apply. If the code of this `FunctionBody` is strict mode code, `StatementList` is evaluated in the following steps as strict mode code. Otherwise, `StatementList` is evaluated in the following steps as non-strict mode code.
2. If `StatementList` is present return the result of evaluating `StatementList`.
3. Else return `NormalCompletion(undefined)`.

13.2 Arrow Function Definitions

Syntax

`ArrowFunction` :
`ArrowParameters => ConciseBody`

`ArrowParameters` :
`BindingIdentifier`
`CoverParenthesizedExpressionAndArrowParameterList`

`ConciseBody` :
`[lookahead $\notin \{, \}\}$` `AssignmentExpression`
`{ FunctionBody }`

Supplemental Syntax

When processing the production `ArrowParameters` : `CoverParenthesizedExpressionAndArrowParameterList` the following grammar is used to refine the interpretation of `CoverParenthesizedExpressionAndArrowParameterList`.

`ArrowFormalParameterList` :
`(FormalParameterList)`

Static Semantics

Static Semantics: Early Errors

`ArrowFunction` : `ArrowParameters => ConciseBody`

- It is a Syntax Error if any element of the `LexicallyDeclaredNames` of `ConciseBody` also occurs in the `VarDeclaredNames` of `ConciseBody`.
- It is a Syntax Error if any element of the `BoundNames` of `ArrowParameters` also occurs in the `LexicallyDeclaredNames` of `ConciseBody`.
- It is a Syntax Error if `ConciseBody` Contains `YieldExpression`.

`ArrowParameters` : `BindingIdentifier`

- It is a Syntax Error if the StringValue of the sole element of the `BoundNames` of `BindingIdentifier` is `eval` or `arguments`.

Deleted: Immutable
Deleted: the String value of `Identifier`
Deleted: Value

Deleted: The production
Deleted: Source
Deleted: Elements
Deleted: is evaluated as follows:
Deleted: part of a `FunctionDeclaration` or `FunctionExpression` that is
Deleted: SourceElements
Deleted: SourceElements
Deleted: Source
Deleted: Elements
Deleted: SourceElements
Deleted: normal,
Deleted: , empty
Deleted: (`ArrowFormalParameterList`)
Deleted: `ArrowFormalParameterList` :
`[empty]`
`FunctionRestParameter` ,
`CoverFormalsList`
`CoverFormalsList` , `FunctionRestParameter` ,

Deleted: `CoverFormalsList` :
`Expression`
Supplemental Syntax
 When processing the production `CoverFormalsList` : `Expression` the `FormalsList` production is used to further restrict the source code that matches `Expression`.
`ArrowFormalParameterList` :
`FormalParameterList`
Deleted: `ConciseBody`
Deleted: `ConciseBody`
Deleted: `ConciseBody`
Deleted: `ConciseBody`
Deleted: `ConciseBody`

ArrowParameters : CoverParenthesizedExpressionAndArrowParameterList

- It is a Syntax Error if the lexical token sequence matched by CoverParenthesizedExpressionAndArrowParameterList cannot be parsed with no tokens left over using ArrowFormalParameterList as the goal symbol.
- All Early Errors rules for FormalParameterList and its derived productions, also apply to the CoveredFormalsList of CoverParenthesizedExpressionAndArrowParameterList.

Static Semantics: BoundNames

ArrowParameters : CoverParenthesizedExpressionAndArrowParameterList

1. Let formals be CoveredFormalsList of CoverParenthesizedExpressionAndArrowParameterList.
2. Return the BoundNames of formals.

Static Semantics: Contains

With parameter symbol.

ArrowFunction : ArrowParameters => ConciseBody

1. If ArrowParameters Contains symbol is true, return true;
2. Return ConciseBody Contains symbol.

ArrowParameters : CoverParenthesizedExpressionAndArrowParameterList

1. Let formals be CoveredFormalsList of CoverParenthesizedExpressionAndArrowParameterList.
2. Return formals Contains symbol.

NOTE Contains is used to detect yield and super usage within an ArrowFunction.

Static Semantics: CoveredFormalsList

CoverParenthesizedExpressionAndArrowParameters:

- (Expression)
- ()
- (... Identifier)
- (Expression , ... Identifier)

1. Return the result of parsing the lexical token stream matched by CoverParenthesizedExpressionAndArrowParameters using ArrowFormalParameterList as the goal symbol.

Static Semantics: ExpectedArgumentCount

ArrowParameters : BindingIdentifier

1. Return 1.

ArrowParameters : CoverParenthesizedExpressionAndArrowParameterList

1. Let formals be CoveredFormalsList of CoverParenthesizedExpressionAndArrowParameterList.
2. Return the ExpectedArgumentCount of formals.

Static Semantics: LexicallyDeclaredNames

ConciseBody : lookahead & { { } } AssignmentExpression

1. Return an empty List.

Deleted: ArrowFormalParameterList : CoverFormalsList
Deleted: FunctionRestParameter¶
<#>It is a Syntax Error if <u>BoundNames</u> of <u>CoverFormalsList</u> contains any element which is also contained in <u>BoundNames</u> of <u>FunctionRestParameter</u> .¶
Deleted: CoverFormalsList
Deleted: Expression
Deleted: source code
Deleted: corresponding to
Deleted: Expression
Deleted: FormalsList
Deleted: FormalsList
Deleted:
Deleted: Expression
Deleted: ArrowParameters : BindingIdentifier¶
<#>Return the <u>BoundNames</u> of <u>BindingIdentifier</u> .¶
Deleted: ArrowParameters : (ArrowFormalParameterList)¶
<#>Return the <u>BoundNames</u> of <u>ArrowFormalParameterList</u> .¶
Deleted: ArrowFormalParameterList : [empty]¶
<#>Return an empty List.¶
Deleted: ArrowFormalParameterList : FunctionRestParameter¶
<#>Return the <u>BoundNames</u> of <u>FunctionRestParameter</u> .¶
Deleted: ArrowFormalParameterList : CoverFormalsList¶
<#>Return the <u>BoundNames</u> of <u>CoverFormalsList</u> .¶
Deleted: ArrowFormalParameterList : CoverFormalsList ,
Deleted: FunctionRestParameter¶
<#>Let <u>names</u> be <u>BoundNames</u> of <u>CoverFormalsList</u> .¶
<#>Append to <u>names</u> the <u>BoundNames</u> of <u>FunctionRestParameter</u> .¶
<#>Return <u>names</u> .¶
Deleted: CoverFormalsList : Expression ¶
<#>Return the <u>BoundNames</u> of <u>CoveredFormalsList</u> of <u>Expression</u> .¶
Deleted: ConciseBody
Deleted: s
Deleted: s
Deleted: Static semantic rules that depend upon substructure generally do not look into function definitions
Deleted: This
Deleted:
Deleted: CoverFormalsList : Expression¶
Deleted: source code
Deleted: corresponding to
Deleted: Expression
Deleted: FormalsList
Deleted: ArrowParameters : (ArrowFormalParameterList)¶
<#>Return the <u>ExpectedArgumentCount</u> of <u>ArrowFormalParameterList</u> .¶
Deleted: ArrowFormalParameterList : ¶
[empty]
Deleted: FunctionRestParameter¶
<#>Return 0.¶
Deleted: CoveredCFormalsList of <u>CoverFormalsList</u>
Deleted: ConciseBody

Runtime Semantics

Runtime Semantics: Binding Initialisation

With parameters *value* and *environment* and optional parameter *index*.

NOTE When **undefined** is passed for *environment* it indicates that a *PutValue* operation should be used to assign the initialisation value. This is the case for formal parameter lists of non-strict functions. In that case the formal parameter bindings are preinitialized in order to deal with the possibility of multiple parameters with the same name.

ArrowParameters : BindingIdentifier

1. Return the result of performing Indexed Binding Initialisation for *BindingIdentifier* using *value*, 0, and *environment* as the arguments.

ArrowParameters : CoverParenthesizedExpressionAndArrowParameterList

1. Let *formals* be *CoveredFormalsList* of *CoverParenthesizedExpressionAndArrowParameterList*.
2. Return the result of performing Binding initialization of *formals* with arguments *value* and *environment* and optional argument *index*, if *index* was passed to this routine.

Runtime Semantics: Evaluation

ArrowFunction : ArrowParameters => ConciseBody

1. Let *strict* be **true**.
2. Let *scope* be the *LexicalEnvironment* of the running *execution context*.
3. Let *closure* be the result of performing the *FunctionCreate* abstract operation with arguments *Arrow*, *ArrowParameters*, *ConciseBody*, *scope*, and *strict*.
4. Return *closure*.

ConciseBody : [lookahead ≠ { }] AssignmentExpression

1. The code of this *ConciseBody* is strict mode code if it is contained in strict mode code or if any of the conditions in 10.1.1 apply. If the code of this *ConciseBody* is strict mode code, *AssignmentExpression* is evaluated in the following steps as strict mode code. Otherwise, *AssignmentExpression* is evaluated in the following steps as non-strict mode code.
 2. Let *exprRef* be the result of evaluating *AssignmentExpression*.
 3. Let *exprValue* be *GetValue(exprRef)*.
 4. ReturnIfAbrupt(*exprValue*).
 5. Return Completion {[[type]]: return, [[value]]: *exprValue*, [[target]]: empty}.

13.3 Method Definitions

Syntax

MethodDefinition :

```

  PropertyName ( FormalParameterList ) { FunctionBody }
  * PropertyName ( FormalParameterList ) { FunctionBody }
  get PropertyName ( ) { FunctionBody }
  set PropertyName ( PropertySetParameterList ) { FunctionBody }
```

PropertySetParameterList :

```

  BindingIdentifier
  BindingPattern
```

Static Semantics

Early Errors

Deleted: *ConciseBody* : { *FunctionBody* }
 <#>Return the LexicallyDeclaredNames of *FunctionBody*.
Static Semantics: *VarDeclaredNames*
ConciseBody : [lookahead ≠ { }]
AssignmentExpression ¶
 <#>Return the VarDeclaredNames of *AssignmentExpression*.¶
ConciseBody : { *FunctionBody* }¶
 <#>Return the VarDeclaredNames of *FunctionBody*.

Deleted: , *lenValue*

Deleted: *ArrowParameters* : (*ArrowFormalParameterList*)¶
 <#>Return the result of performing Binding Initialisation for *ArrowFormalParameterList* using *value*, *environment* as the arguments. Also pass the optional argument *index* if it is present.¶

Deleted: *ArrowFormalParameterList* : [empty]
 <#>Return NormalCompletion(empty).¶
ArrowFormalParameterList : *FunctionRestParameter*¶
 <#>Return the result of performing Indexed Bind Initialisation for *FunctionRestParameter* using *value*, *lenValue*, 0, and *environment* as the arguments.¶
ArrowFormalParameterList : *CoverFormalsList*
 <#>Return the result of performing Indexed Bind Initialisation for *CoveredCFormalsList* of *CoverFormalsList* using *value*, *lenValue*, 0, and *environment* as the arguments.¶
ArrowFormalParameterList : *CoverFormalsList*
FunctionRestParameter ¶
 <#>Let *restIndex* be the result of performing Indexed Bind Initialisation for *CoveredCFormalsList* o

Deleted: *ConciseBody*

Comment [AWB796]: Confirm: concise methods are always strict code.

Deleted: *current*

Deleted: *List*

Deleted: *ConciseBody*

Deleted: *Arrow*

Deleted: *Arrow*

Comment [AWB797]: TODO, need to resolve whether or not ArrowBodies are always strict

Comment [AWB998]: TODO If *exprRef* is a Reference that invokes a getter we probably

Deleted: If *exprValue* is an abrupt completion, return *exprValue*

Deleted: *ConciseBody* : { *FunctionBody* }¶
 <#>Return the result of evaluating *FunctionBody*.

Deleted: *ConciseBody*

Deleted: *ConciseBody*

Deleted: {

Deleted: *ConciseBody*

Deleted: *FunctionBody* }

Deleted:

Deleted: {

Deleted: *ConciseBody*

Deleted: *FunctionBody* }

MethodDefinition : PropertyName (FormalParameterList) { FunctionBody }

and

MethodDefinition : * PropertyName (FormalParameterList) { FunctionBody }

Deleted: ConciseBody

- It is a Syntax Error if any element of the LexicallyDeclaredNames of FormalParameterList also occurs in the VarDeclaredNames of FunctionBody.
- It is a Syntax Error if any element of the BoundNames of FormalParameterList also occurs in the LexicallyDeclaredNames of FunctionBody.

Deleted: ConciseBody

Deleted:

Deleted: Concise

Deleted: Concise

MethodDefinition : PropertyName (FormalParameterList) { FunctionBody }

- It is a Syntax Error if FunctionBody Contains YieldExpression.

Deleted: ConciseBody

Deleted:

Deleted: ConciseBody

Deleted:

MethodDefinition : * PropertyName (FormalParameterList) { FunctionBody }

- It is a Syntax Error if FunctionBody Contains YieldExpression is false.

MethodDefinition : get PropertyName () { FunctionBody }

- It is a Syntax Error if FunctionBody Contains YieldExpression.

Deleted: ConciseBody

Deleted:

Deleted: ConciseBody

Deleted:

MethodDefinition : set PropertyName (PropertySetParameterList) { FunctionBody }

- It is a Syntax Error if any element of the BoundNames of PropertySetParameterList also occurs in the LexicallyDeclaredNames of FunctionBody.
- It is a Syntax Error if PropertySetParameterList Contains YieldExpression.
- It is a Syntax Error if FunctionBody Contains YieldExpression.

Deleted: ConciseBody

Deleted:

Deleted: ConciseBody

Deleted:

PropertySetParameterList : BindingPattern

- It is a Syntax Error if BoundNames of BindingPattern contains any duplicate elements.

Deleted: ConciseBody

Deleted:

Static Semantics: ExpectedArgumentCount

PropertySetParameterList : BindingIdentifier

1. Return 1.

PropertySetParameterList : BindingPattern

1. Return 1.

Static Semantics: PropName

MethodDefinition :

```
PropertyName ( FormalParameterList ) { FunctionBody }
* PropertyName ( FormalParameterList ) { FunctionBody }
get PropertyName ( ) { FunctionBody }
set PropertyName ( PropertySetParameterList ) { FunctionBody }
```

1. Return PropName of PropertyName.

Deleted: Static Semantics: BoundNames¶
 PropertySetParameterList : BindingIdentifier ¶
 <#>Return BoundNames of BindingIdentifier ¶
 PropertySetParameterList: BindingPattern ¶
 <#>Return BoundNames of BindingPattern ¶

Deleted: MethodDefinition : PropertyName
 (FormalParameterList) ConciseBody ¶

Deleted: MethodDefinition : * PropertyName
 (FormalParameterList) ConciseBody ¶
 <#>Return PropName of PropertyName.¶
 MethodDefinition : get PropertyName () ConciseBody
 <#>Return PropName of PropertyName.¶
 MethodDefinition : set PropertyName
 (PropertySetParameterList) ConciseBody ¶
 <#>Return PropName of PropertyName.¶

MethodDefinition :

```
PropertyName ( FormalParameterList ) { FunctionBody }
* PropertyName ( FormalParameterList ) { FunctionBody }
get PropertyName ( ) { FunctionBody }
set PropertyName ( PropertySetParameterList ) { FunctionBody }
```

1. Return FunctionBody Contains super.

Static Semantics: SpecialMethodMethodDefinition : PropertyName (FormalParameterList) { FunctionBody }

1. Return false.

MethodDefinition :

```
* PropertyName ( FormalParameterList ) { FunctionBody }
get PropertyName ( ) { FunctionBody }
set PropertyName ( PropertySetParameterList ) { FunctionBody }
```

1. Return true.

Runtime SemanticsRuntime Semantics: Property Definition EvaluationWith parameter object.MethodDefinition : PropertyName (FormalParameterList) { FunctionBody }

1. Let propName be PropName of PropertyName.
2. Let strict be IsStrict of FunctionBody.
3. Let scope be the running execution context's LexicalEnvironment.
4. Let needsSuperBinding be the result of FunctionBody Contains super.
5. If needsSuperBinding is false, then let needsSuperBinding be the result of FormalParameterList Contains super.
6. If needsSuperBinding, then
 - a. Let closure be the result of performing the FunctionCreate abstract operation with arguments Method, FormalParameterList, FunctionBody, scope, and strict and with object as the homeObject optional argument and propName as the methodName optional argument.
7. Else
 - a. Let closure be the result of performing the FunctionCreate abstract operation with arguments Method, FormalParameterList, FunctionBody, scope, and strict.
8. Let desc be the Property Descriptor {[[Value]]: closure, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}.
9. Let status be the result of calling the [[DefineOwnProperty]] internal method of object with arguments propName, desc, and false.
10. ReturnIfAbrupt(status).
11. NormalCompletion(closure).

Deleted: ConciseBody**Deleted:****Deleted:** true**Deleted:** current**Comment [AWB899]:** A default value expression could reference super**Deleted:** ConciseBody**Comment [AWB10100]:** At its sept 2012 meeting TC39 decided that it wants methods be enumerable.**Deleted:** true,**Deleted:** false**Deleted:** false**Deleted:** Return**Deleted:** ConciseBody**Deleted:****Deleted:** true**Deleted:** current**Comment [AWB8101]:** A default value expression could reference superMethodDefinition : * PropertyName (FormalParameterList) { FunctionBody }

1. Let propName be PropName of PropertyName.
2. Let strict be IsStrict of FunctionBody.
3. Let scope be the running execution context's LexicalEnvironment.
4. Let needsSuperBinding be the result of FunctionBody Contains super.
5. If needsSuperBinding is false, then let needsSuperBinding be the result of FormalParameterList Contains super.
6. If needsSuperBinding, then
 - a. Let closure be the result of performing the FunctionCreate abstract operation with arguments Method, FormalParameterList, FunctionBody, scope, and strict and with object as the homeObject optional argument and propName as the methodName optional argument.

7. Else

a. Let *closure* be the result of performing the *FunctionCreate* abstract operation with arguments *Method*, *FormalParameterList*, *FunctionBody*, *scope*, and *strict*.

8. Let *desc* be the *Property Descriptor* $\{[\text{Value}]: \text{closure}, [\text{Writable}]: \text{true}, [\text{Enumerable}]: \text{true}, [\text{Configurable}]: \text{true}\}$.

9. Let *status* be the result of calling the *[[DefineOwnProperty]]* internal method of *object* with arguments *propName*, *desc*, and *false*.

10. *ReturnIfAbrupt(status)*.

11. *NormalCompletion(closure)*.

MethodDefinition : get *PropertyName* () { *FunctionBody* }

1. Let *propName* be *PropName* of *PropertyName*.

2. Let *strict* be *IsStrict* of *FunctionBody*.

3. Let *scope* be the running execution context's *LexicalEnvironment*.

4. Let *formalParameterList* be the production *FormalParameterList* : *empty*.

5. Let *needsSuperBinding* be the result of *FunctionBody Contains super*.

6. If *needsSuperBinding*, then

a. Let *closure* be the result of performing the *FunctionCreate* abstract operation with arguments *Method*, *formalParameterList*, *FunctionBody*, *scope*, and *strict* and with *object* as the *homeObject* optional argument and *propName* as the *methodName* optional argument.

7. Else

a. Let *closure* be the result of performing the *FunctionCreate* abstract operation with arguments *Method*, *formalParameterList*, *FunctionBody*, *scope*, and *strict*.

8. Let *desc* be the *Property Descriptor* $\{[\text{Get}]: \text{closure}, [\text{Enumerable}]: \text{true}, [\text{Configurable}]: \text{true}\}$.

9. Let *status* be the result of calling the *[[DefineOwnProperty]]* internal method of *object* with arguments *propName*, *desc*, and *false*.

10. *ReturnIfAbrupt(status)*.

11. *NormalCompletion(closure)*.

MethodDefinition : set *PropertyName* (*PropertySetParameterList*) { *FunctionBody* }

1. Let *propName* be *PropName* of *PropertyName*.

2. Let *strict* be *IsStrict* of *FunctionBody*.

3. Let *scope* be the running execution context's *LexicalEnvironment*.

4. Let *needsSuperBinding* be the result of *FunctionBody Contains super*.

5. If *needsSuperBinding* is *false*, then let *needsSuperBinding* be the result of *PropertySetParameterList contains super*.

6. If *needsSuperBinding*, then

a. Let *closure* be the result of performing the *FunctionCreate* abstract operation with arguments *Method*, *PropertySetParameterList*, *FunctionBody*, *scope*, and *strict* and with *object* as the *homeObject* optional argument and *propName* as the *methodName* optional argument.

7. Else

a. Let *closure* be the result of performing the *FunctionCreate* abstract operation with arguments *Method*, *PropertySetParameterList*, *FunctionBody*, *scope*, and *strict*.

8. Let *desc* be the *Property Descriptor* $\{[\text{Set}]: \text{closure}, [\text{Enumerable}]: \text{true}, [\text{Configurable}]: \text{true}\}$.

9. Let *status* be the result of calling the *[[DefineOwnProperty]]* internal method of *object* with arguments *propName*, *desc*, and *false*.

10. *ReturnIfAbrupt(status)*.

11. *NormalCompletion(closure)*.

f13.4 Generator Definitions

Syntax

GeneratorDeclaration :

function * *BindingIdentifier* (*FormalParameterList*) { *FunctionBody* }

GeneratorExpression :

function * *BindingIdentifier*_{opt} (*FormalParameterList*) { *FunctionBody* }

Comment [AWB8102]: TODO: need to replace with creation of a generator object

Deleted: <#>Let *closure* be the result of performing the *FunctionCreate* abstract operation with arguments *Method*, *FormalParameterList*, *ConciseBody*, *scope*, and *strict* and with *object* as the *homeObject* optional argument and *propName* as the *methodName* optional argument.¶

Deleted: *true*,

Deleted: *false*

Deleted: *false*

Deleted: *Return*

Deleted: *ConciseBody*

Deleted: { *FunctionBody* }

Deleted: If this *MethodDefinition* is contained in strict code or if *FunctionBody ConciseBody* is strict code, then let *strict* be *true*. Otherwise, let *strict* be *false*.

Deleted: *current*

Deleted: <#>Let *closure* be the result of performing the *FunctionCreate* abstract operation with arguments *Method*, *formalParameterList*, *ConciseBody*, *scope*, and *strict* and with *object* as the *homeObject* optional argument and *propName* as the *methodName* optional argument.¶

Deleted: <#>TODO: Make closure a constructor, for ESS compat¶

Deleted: *Return*

Deleted: *o*

Deleted: *ConciseBody*

Deleted: { *FunctionBody* }

Deleted: If this *MethodDefinition* is contained in strict code or if *FunctionBody ConciseBody* is strict code, then let *strict* be *true*. Otherwise, let *strict* be *false*.

Deleted: *current*

Deleted: *o*

Deleted: *o*

Deleted: <#>Let *closure* be the result of performing the *FunctionCreate* abstract operation with arguments *Method*, *PropertySetParameterList*, *ConciseBody*, *scope*, and *strict* and with *object* as the *homeObject* optional argument and *propName* as the *methodName* optional argument.¶

Deleted: <#>TODO: Make closure a constructor, for ESS compat¶

Deleted: *Return*

Deleted: NOTE The strictness and property attribute for *set* and *get* *MethodDefinition* productions differ from the other *MethodDefinition* productions in order to maintain compatibility with previous editions of this specification.

YieldExpression :
yield YieldDelegator_{opt} [Lexical goal InputElementRegExp] AssignmentExpression

YieldDelegator :

Static Semantics

Static Semantics: Early Errors

*GeneratorDeclaration : function * BindingIdentifier (FormalParameterList) { FunctionBody }*
and
*GeneratorExpression : function * BindingIdentifier_{opt} (FormalParameterList) { FunctionBody }*

- *It is a Syntax Error if any element of the BoundNames of FormalParameterList also occurs in the LexicallyDeclaredNames of FunctionBody.*
- *It is a Syntax Error if FunctionBody Contains YieldExpression is false.*

YieldExpression : yield YieldDelegator_{opt} AssignmentExpression

- *It is a Syntax Error if any AssignmentExpression Contains YieldExpression.*

Static Semantics: BoundNames

*GeneratorDeclaration : function * BindingIdentifier (FormalParameterList) { FunctionBody }*

1. *Return the BoundNames of BindingIdentifier.*

Static Semantics: Contains

With parameter symbol.

*GeneratorDeclaration ; function * BindingIdentifier (FormalParameterList) { FunctionBody }*

1. *Return false.*

*GeneratorExpression : function * BindingIdentifier_{opt} (FormalParameterList) { FunctionBody }*

1. *Return false.*

NOTE *Static semantic rules that depend upon substructure generally do not look into function definitions.*

Static Semantics: IsConstantDeclaration

*GeneratorDeclaration : function * BindingIdentifier (FormalParameterList) { FunctionBody }*

1. *Return false.*

Static Semantics: LexicallyDeclaredNames

*GeneratorDeclaration : function * BindingIdentifier (FormalParameterList) { FunctionBody }*

1. *Return the BoundNames of BindingIdentifier.*

Static Semantics: VarDeclaredNames

*GeneratorDeclaration : function * BindingIdentifier (FormalParameterList) { FunctionBody }*

1. *Return an empty List.*

Comment [AWB10103]: This actually does accomplish anything because a similar annotation within MemberExpression takes care of the possibility of a leading RegExp here.

Deleted: Function

Deleted: Function

Comment [AWB6104]: There is an issue that function declarations have "lexically declared names" and in ES<=5 nested functions are allowed to have the same name as vars or formal parameters. We either need to take this a breaking change or adjust this rule to only apply to function declarations nested within blocks. Generators are new so this isn't really a backwards compat issue for them. But there is a consistency issue WRT to functions and generators.

Deleted:)

Deleted: FunctionDeclaration

Deleted: Function

Runtime Semantics

13.5 Class Definitions

Syntax

ClassDeclaration:

class BindingIdentifier ClassTail

ClassExpression:

class BindingIdentifier_{opt} ClassTail

ClassTail:

ClassHeritage_{opt} { ClassBody_{opt} }

ClassHeritage:

extends AssignmentExpression

ClassBody:

ClassElementList

ClassElementList:

ClassElement

ClassElementList ClassElement

ClassElement:

MethodDefinition

⋮

Static Semantics

Static Semantics: Early Errors

ClassDeclaration : class BindingIdentifier ClassTail

and

ClassExpression : class BindingIdentifier ClassTail

- It is a Syntax Error if BindNames of BindingIdentifier contains either "eval" or "arguments"

ClassBody : ClassElementList

- It is a Syntax Error if PropertyNameList of ClassElementList contains any duplicate entries, unless the following condition is true for each duplicate entry: The duplicated entry occurs exactly twice in the list and one occurrence was obtained from a get accessor MethodDefinition and the other occurrence was obtained from a set accessor MethodDefinition.

Comment [AWB8105]: Class definitions have not yet been achieved final acceptance by TC39 for ES6 hence this section could disappear in a future draft.

ClassElement : MethodDefinition

- It is a Syntax Error if PropName of MethodDefinition is "constructor" and SpecialMethod of MethodDefinition is true.

Static Semantics: BoundNames

ClassDeclaration: class BindingIdentifier ClassTail

1. Return the BindNames of BindingIdentifier.

Static Semantics: ConstructorMethod

Deleted: {

Deleted: }

Deleted: Method

Deleted: ClassHeritage : extends AssignmentExpression
 <#>It is a Syntax Error if AssignmentExpression Contains YieldExpression.¶

ClassBody : *ClassElementList*

1. Let *list* be MethodDefinitions of *ClassElementList*.
2. For each *MethodDefinition m* in *list*, do
 - a. If PropName of *m* is "constructor", return *m*.
3. Return empty.

NOTE Early Error rules ensure that there is only one method definition named "constructor" and that it isn't an accessor property or generator definition.

Static Semantics: Contains

With parameter *symbol*.

ClassTail : *ClassHeritage*_{opt} { *ClassBody* }

1. If *symbol* is *ClassBody*, return true.
2. If *ClassHeritage* is not present, return false.
3. If *symbol* is *ClassHeritage*, return true.
4. Return the result of Contains for *ClassHeritage* with argument *symbol*.

NOTE Static semantic rules that depend upon substructure generally do not look into class bodies.

Static Semantics: IsConstantDeclaration

ClassDeclaration: **class** *BindingIdentifier* *ClassTail*

1. Return false.

Deleted: true

Static Semantics: LexicallyDeclaredNames

ClassDeclaration: **class** *BindingIdentifier* *ClassTail*

1. Return the BoundNames of *BindingIdentifier*.

Static Semantics: MethodDefinitions

ClassElementList : *ClassElement*

1. If PropName of *ClassElement* is empty, return a new empty List.
2. Return a List containing *ClassElement*.

ClassElementList : *ClassElementList* *ClassElement*

5. Let *list* be MethodDefinitions of *ClassElementList*.
6. If PropName of *ClassElement* is empty, return *list*.
7. Append *ClassElement* to the end of *list*.
8. Return *list*.

Static Semantics: PropName

ClassElement : ;

1. Return empty.

Static Semantics: PropertyNameList

ClassElementList : *ClassElement*

1. If PropName of ClassElement is empty, return a new empty List.
2. Return a List containing PropName of ClassElement.

ClassElementList : ClassElementList ClassElement

1. Let list be PropertyNameList of ClassElementList.
2. If PropName of ClassElement is empty, return list.
3. Append PropName of ClassElement to the end of list.
4. Return list.

Static Semantics: VarDeclaredNames

ClassDeclaration: class BindingIdentifier ClassTail

1. Return an empty List.

Runtime Semantics

Runtime Semantics: ClassDefinitionEvaluation

With parameter *className*.

ClassTail : ClassHeritage_{opt} { ClassBody }

1. If ClassHeritage_{opt} is not present, then
 - a. let protoParent be the intrinsic object %ObjectPrototype%.
 - b. Let constructorParent be the intrinsic object %FunctionPrototype%.
2. Else
 - a. Let superclass be the result of evaluating ClassHeritage.
 - b. ReturnIfAbrupt(superclass).
 - c. If superclass is null, then
 - i. Let protoParent be null.
 - ii. Let constructorParent be the intrinsic object %FunctionPrototype%.
 - d. Else if Type(superclass) is not Object, throw a TypeError exception.
 - e. Else if superclass does not have a [[Construct]] internal property, then
 - i. Let protoParent be superclass.
 - ii. Let constructorParent be the intrinsic object %FunctionPrototype%.
 - f. Else
 - i. Let protoParent be the result of calling the [[Get]] internal method of superclass passing "prototype" as the argument.
 - ii. ReturnIfAbrupt(protoParent).
 - iii. If Type(protoParent) is neither Object or Null, throw a TypeError exception.
 - iv. Let constructorParent be superclass.
3. Let proto be the result of the abstract operation ObjectCreate with argument *protoParent*.
4. Let lex be the LexicalEnvironment of the running execution context.
5. If className is not undefined, then
 - a. Let scope be the result of calling NewDeclarativeEnvironment passing lex as the argument.
 - b. Let envRec be scope's environment record.
 - c. Call the CreateImmutableBinding concrete method of envRec passing className as the argument.
 - d. Set the running execution context's LexicalEnvironment to scope.
6. Let constructor be ConstructorMethod of ClassBody.
7. If constructor is empty, then
 - a. Let constructor be the result of parsing the String "**constructor(... args) {super.constructor(...args);}**" using the syntactic grammar with the goal symbol MethodDefinition.
8. If the ClassTail is contained in strict code or if constructor is strict code, then let strict be true. Otherwise let strict be false.
9. Let F be the result of performing Property Definition Evaluation for constructor with argument proto.

Deleted: proto

Deleted: <#> If the ClassTail is contained in strict code or its FunctionBody is strict code, then let strict be true. Otherwise let strict be false.¶

Comment [AWB9106]: Note that this variable currently isn't used in this algorithm

Comment [AWB8107]: As it now stands, this will never be an abrupt completion

10. Perform the abstract operation `MakeConstructor` with argument `F` and `false` as the optional `writablePrototype` argument and `proto` as the optional `prototype` argument.
11. Let `desc` be the Property Descriptor `{[[Enumerable]]: false, [[Writable]]: true, [[Configurable]]: true}`.
12. Call the `[[DefineOwnProperty]]` internal method of `proto` with arguments `"constructor"`, `desc`, and `false`.
13. Let `methods` be `MethodDefinitions` of `ClassBody`.
14. For each `MethodDefinition m` in `order` from `methods`
 - a. Perform `PropertyDefinitionEvaluation` for `m` with argument `proto`.
15. Set the running execution context's `LexicalEnvironment` to `lex`.
16. Return `F`.

Runtime Semantics: Evaluation

ClassDeclaration: class BindingIdentifier ClassTail

1. Let `value` be the result of `ClassDefinitionEvaluation` of `ClassTail` with argument `undefined`.
2. `ReturnIfAbrupt(value)`.
3. Let `env` be the running execution context's `LexicalEnvironment`.
4. Let `status` be the result of performing `BindingInitialisation` for `BindingIdentifier` passing `value` and `env` as the arguments.
5. `ReturnIfAbrupt(status)`.
6. Return `NormalCompletion(empty)`.

NOTE The argument to `ClassDefinitionEvaluation` controls whether or not the class that is defined with a `BindingIdentifier` has a local binding to the identifier. Only a `ClassExpression` gets a local name binding of its name. A `ClassDeclaration` never has such a binding. This maintains the parallel with `FunctionExpression` and `FunctionDeclaration`.

ClassExpression: class BindingIdentifier_{opt} ClassTail

1. If `BindingIdentifieropt` is not present, then let `className` be `undefined`.
2. Else, let `className` be `StringValue` of `BindingIdentifier`.
3. Let `value` be the result of `ClassDefinitionEvaluation` of `ClassTail` with argument `className`.
4. `ReturnIfAbrupt(value)`.
5. Return `NormalCompletion(value)`.

13.6 Creating Function Objects and Constructors

The abstract operation `FunctionCreate` requires the arguments: `kind` which is one of `(Normal, Method, Arrow)`, a parameter list specified by `FormalParameterList`, a body specified by `FunctionBody`, a Lexical Environment specified by `Scope`, a Boolean flag `Strict`, and optionally, an object `functionPrototype`, an object `homeObject` and a string `methodName`. `FunctionCreate` performs the following steps:

1. Create a new native ECMAScript object and let `F` be that object.
2. Set all the internal methods, except for `[[GetProperty]]`, of `F` as described in 8.12.
3. Add the `[[NativeBrand]]` internal property with value `NativeFunction` to `F`.
4. If the `functionPrototype` argument was not provided, then
 - a. Let `functionPrototype` be the intrinsic object `%FunctionPrototype%`.
5. Set the `[[Prototype]]` internal property of `F` to `functionPrototype`.
6. Set the `[[GetProperty]]` internal property of `F` as described in 15.3.5.4.
7. Set the `[[Call]]` internal property of `F` as described in 13.5.1.
8. Set the `[[Scope]]` internal property of `F` to the value of `Scope`.
9. Set the `[[FormalParameters]]` internal property of `F` to `FormalParameterList`.
10. Set the `[[Code]]` internal property of `F` to `FunctionBody`.
11. Set the `[[Extensible]]` internal property of `F` to `true`.
12. Set the `[[Realm]]` internal property of `F` to the running execution context's `Realm`.
13. If the `homeObject` argument was provided, set the `[[Home]]` internal property of `F` to `homeObject`.
14. If the `methodName` argument was provided, set the `[[MethodName]]` internal property of `F` to `methodName`.
15. If `kind` is `Arrow`, then set the `[[ThisMode]]` internal property of `F` to `lexical`.
16. Else if `Strict` is `true`, then set the `[[ThisMode]]` internal property of `F` to `strict`.
17. Else set the `[[ThisMode]]` internal property of `F` to `global`.
18. Let `len` be the `ExpectedArgumentCount` of `FormalParameterList`.

Deleted: <code>ing</code>
Deleted: <code>false</code>
Deleted: <code>false</code>
Deleted: <code>object</code>
Deleted: <code><#>Let className be String Value of BindingIdentifier.¶</code>
Deleted: <code>className</code>
Deleted: If <code>value</code> is an abrupt completion, return <code>value</code>
Deleted:
Deleted: <code>Value</code>
Deleted: 13.1 Strict Mode Restrictions¶ It is a <code>SyntaxError</code> if any <code>Identifier</code> value occurs more than once within a <code>FormalParameterList</code> of a strict mode <code>FunctionDeclaration</code> or <code>FunctionExpression</code> .¶ It is a <code>SyntaxError</code> if the <code>Identifier "eval"</code> or the <code>Identifier "arguments"</code> occurs within a <code>FormalParameterList</code> of a strict mode <code>FunctionDeclaration</code> or <code>FunctionExpression</code> .¶ It is a <code>SyntaxError</code> if the <code>Identifier "eval"</code> or the <code>Identifier "arguments"</code> occurs as the <code>Identifier</code> of a strict mode <code>FunctionDeclaration</code> or <code>FunctionExpression</code> .¶
Deleted: 2
Deleted: 1.1
Deleted: 5
Deleted: A Function object is constructed as follows Given given
Deleted: optional
Deleted: and
Deleted: a Function object is constructed as follows
Deleted: Set
Deleted: Class
Deleted: IsFunction
Deleted: of
Deleted: to "Function"
Deleted: the
Deleted: standard built-in Function prototype object as specified in 15.3.3.1
Deleted: 2
Deleted: <#>Set the <code>[[Construct]]</code> internal property of <code>F</code> as described in 13.2.2.¶ <#>Set the <code>[[HasInstance]]</code> internal property of <code>F</code> as described in 15.3.5.3.¶
Deleted: <#>Let <code>names</code> be a List containing, in right textual order, the Strings corresponding to
Deleted: <code>names</code>
Deleted: current
Deleted: number of formal parameters specified
Deleted: .
Deleted: If no parameters are specified, let <code>len</code>

19. Call the `[[DefineOwnProperty]]` internal method of F with arguments `"length"`, Property Descriptor `{[[Value]]: len , [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false}`, and `false`.
20. If `kind` is Normal and `Strict` is true, then
 - a. Let `thrower` be the `[[ThrowTypeError]]` function Object (13.5.3).
 - b. Call the `[[DefineOwnProperty]]` internal method of F with arguments `"caller"`, PropertyDescriptor `{[[Get]]: thrower, [[Set]]: thrower, [[Enumerable]]: false, [[Configurable]]: false}`, and `false`.
 - c. Call the `[[DefineOwnProperty]]` internal method of F with arguments `"arguments"`, PropertyDescriptor `{[[Get]]: thrower, [[Set]]: thrower, [[Enumerable]]: false, [[Configurable]]: false}`, and `false`.
21. Set the `[[Strict]]` internal property of F to `Strict`.
22. Return F .

The abstract operation `MakeConstructor` requires a Function argument F and optionally, a Boolean `writablePrototype` and an object `prototype`. If `prototype` is provided it is assumed to already contain a `"constructor"` whose value is F . It converts F into a constructor by performing the following steps:

1. Let `installNeeded` be `false`.
2. If the `prototype` argument was not provided, then
 - a. Let `installNeeded` be `true`.
 - b. Let `prototype` be the result of the abstract operation `ObjectCreate` (15.2).
3. If the `writablePrototype` argument was not provided, then
 - a. Let `writablePrototype` be `true`.
4. Set the `[[Construct]]` internal property of F as described in 13.5.2.
5. Set the `[[HasInstance]]` internal property of F as described in 15.3.5.3.
6. If `installNeeded`, then
 - a. Call the `[[DefineOwnProperty]]` internal method of `prototype` with arguments `"constructor"`, Property Descriptor `{[[Value]]: F , [[Writable]]: writablePrototype, [[Enumerable]]: false, [[Configurable]]: writablePrototype}`, and `false`.
7. Call the `[[DefineOwnProperty]]` internal method of F with arguments `"prototype"`, Property Descriptor `{[[Value]]: prototype, [[Writable]]: writablePrototype, [[Enumerable]]: false, [[Configurable]]: false}`, and `false`.
8. Return F .

13.6.1 `[[Call]]`

The `[[Call]]` internal method for a Function object F is called with parameters `thisArgument` and `argumentsList`, a List of ECMAScript values. The following steps are taken:

1. Let `callerContext` be the running execution context.
2. If `callerContext` is not already suspended, then Suspend `callerContext`.
3. Let `calleeContext` be a new ECMAScript Code execution context.
4. Set `calleeContext`'s Realm to the value of F 's `[[Realm]]` internal property.
5. Let `thisMode` be the value of F 's `[[ThisMode]]` internal property.
6. If `thisMode` is lexical, then
 - a. Let `localEnv` be the result of calling `NewDeclarativeEnvironment` passing the value of the `[[Scope]]` internal property of F as the argument.
7. Else,
 - a. If `thisMode` is strict, set `thisValue` to `thisArgument`.
 - b. Else
 - i. if `thisArgument` is `null` or `undefined`, set `thisValue` to `%GlobalObject%`.
 - ii. Else if `Type(thisArgument)` is not Object, set the `thisValue` to `ToObject(thisArgument)`.
 - iii. Else set the `thisValue` to `thisArgument`.
 - c. Let `localEnv` be the result of calling `NewMethodEnvironment` passing F and `thisValue` as the arguments.
8. Set the LexicalEnvironment of `calleeContext` to `localEnv`.
9. Set the VariableEnvironment of `calleeContext` to `localEnv`.
10. Push `calleeContext` on to the execution context stack; `calleeContext` is now the running execution context.
11. Let `status` be the result of performing Function Declaration Binding Instantiation using the function F , `argumentsList`, and `localEnv` as described in 10.5.3.
12. If `status` is an abrupt completion, then

Deleted: 2
Deleted:
Deleted: ion
Deleted: 1
Deleted: <#> Set the <code>[[Home]]</code> internal property of F to <code>prototype</code> . <#> Set the <code>[[MethodName]]</code> internal property of F to <code>"constructor"</code> . Deleted: <#> Let <code>proto</code> be the result of creating a new object as would be constructed by the expression <code>new Object()</code> where <code>Object</code> is the standard built-in construct with that name. Deleted: {
Deleted:
Deleted:
Deleted: true
Deleted: true
Deleted: proto
Deleted: {
Deleted: true
Deleted: <#> If <code>Strict</code> is true, then Let <code>thrower</code> be the <code>[[ThrowTypeError]]</code> function Object (13.2.3). Call the <code>[[DefineOwnProperty]]</code> internal method of F with arguments <code>"caller"</code> , PropertyDescriptor <code>{[[Get]]: <code>thrower</code>, [[Set]]: <code>thrower</code>, [[Enumerable]]: <code>false</code>, [[Configurable]]: <code>false</code>}</code> , and <code>false</code> . Call the <code>[[DefineOwnProperty]]</code> internal method of F with arguments <code>"arguments"</code> , PropertyDescriptor <code>{[[Get]]: <code>thrower</code>, [[Set]]: <code>thrower</code>, [[Enumerable]]: <code>false</code>, [[Configurable]]: <code>false</code>}</code> , and <code>false</code> . Set the <code>[[Strict]]</code> internal property of F to <code>Strict</code> . Deleted: F
Deleted: NOTE A <code>prototype</code> property is automatically
Deleted: 2
Deleted: 1
Deleted: 5
Deleted: .1
Deleted: When t
Deleted: a
Deleted: value
Deleted: list
Deleted: arguments
Deleted: ,
Deleted: the
Deleted: current
Deleted: Let <code>funcCtx status</code> be the result of establishing a
Deleted: <#> Set <code>calleeContext</code> 's PreviousContext to
Deleted:
Deleted: thisArg
Deleted: Make
Deleted: current
Comment [AWB 3108]: May need to update section

- a. Remove calleeContext from the execution context stack and restore callerContext as the running execution context.
- b. Return status.
13. Let *result* be the result of evaluating the *FunctionBody* that is the value of *F*'s [[Code]] internal property.
14. Remove calleeContext from the execution context stack and restore callerContext as the running execution context.
15. If *result.type* is return then return *NormalCompletion(result.[[value]])*.
16. Return *result*.

13.6.2 [[Construct]]

The [[Construct]] internal method for a Function object *F* is called with a single parameter *argumentsList* which is a possibly empty List of ECMAScript values. The following steps are taken:

1. Let *proto* be the value of calling the [[Get]] internal property of *F* with argument "prototype".
2. ReturnIfAbrupt(*proto*).
3. If Type(*proto*) is Object, let *obj* be the result of the abstract operation ObjectCreate with argument *proto*.
4. Else, let *obj* be the result of the abstract operation ObjectCreate.
5. Let *result* be the result of calling the [[Call]] internal property of *F*, providing *obj* as the this value and providing the argument list passed into [[Construct]] as args.
6. ReturnIfAbrupt(*result*).
7. If Type(*result*) is Object then return *result*.
8. Return *NormalCompletion(obj)*.

13.6.3 The [[ThrowTypeError]] Function Object

The [[ThrowTypeError]] object is a unique function object that is defined once as follows:

1. Create a new native ECMAScript object and let *F* be that object.
2. Set all the internal methods of *F* as described in 8.12.
3. Add the [[NativeBrand]] internal property with value NativeFunction to *F*.
4. Set the [[Prototype]] internal property of *F* to the standard built-in Function prototype object as specified in 15.3.3.1.
5. Set the [[Call]] internal property of *F* as described in 13.6.1.
6. Set the [[Scope]] internal property of *F* to the Global Environment.
7. Set the [[FormalParameters]] internal property of *F* to the FormalParameterList : [empty] production.
8. Set the [[Code]] internal property of *F* to be a FunctionBody that unconditionally throws a **TypeError** exception and performs no other action.
9. Call the [[DefineOwnProperty]] internal method of *F* with arguments "length", Property Descriptor {[[Value]]: 0, [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false}, and false.
10. Set the [[Extensible]] internal property of *F* to false.
11. Let [[ThrowTypeError]] be *F*.

13.7 Tail Position Calls

14 Programs and Modules

Syntax

Program :

*ProgramBody*_{opt}

ProgramBody :

StatementList

Static Semantics: Early Errors

ProgramBody : *StatementList*

- It is a Syntax Error if *StatementList* Contains *super*.
- It is a Syntax Error if *StatementList* Contains *YieldExpression*.

Deleted: Remove calleeContext from the execution context stack and restore callerContext as the running execution context.
Deleted: current
Comment [AWB109]: Exceptions could occur during evaluation of parameter default value expressions.
Deleted: If an exception was thrown in the previous step, return (throw, <i>V</i> , empty) where <i>V</i> is the exception. (Execution now proceeds as if no exception were thrown.)
Deleted: <#> If <i>F</i> does not have a [[Code]] internal property or if its value is an empty FunctionBody, then ¶ <#> Let <i>result</i> be (normal,NormalCompletion(undefined, empty,)).¶ <#> Else, ¶
Deleted: R
Deleted: current
Deleted: Exit the execution context <i>funcCtx</i> , restoring the previous execution context.
Deleted: <#> If <i>result.type</i> is throw then throw
Deleted: Otherwise <i>result.type</i> must be normal
Deleted: 2
Deleted: 1
Deleted: 5
Deleted: .21
Deleted: When t...he [[Construct]] internal
Deleted: <#> Let <i>obj</i> be a newly created native
Deleted: Set ...et the [[Prototype]] internal
Deleted: ion
Deleted: to proto
Deleted: If Type(<i>proto</i>) is not Object
Deleted: set ...et the [[Prototype]] internal
Deleted: ion
Deleted: to the standard built-in Object prototyp
Deleted: proto
Deleted: .[[value]]
Deleted: 2
Deleted: 1
Deleted: 5
Deleted: .1
Deleted: Set ...dd the [[Class]
Deleted: IsFunction
Deleted: of ...o <i>F</i> to "Function"
Deleted: 2
Deleted: an empty List
Comment [AWB9110]: TODO: Need to
Deleted: 13.2 Generator Definitions¶
Deleted: SourceElements _{opt}
Deleted: SourceElements
Deleted: SourceElement .

Runtime Semantics

Runtime Semantics: Program Evaluation

With argument *realm*.

Program : *ProgramBody*_{opt} ↴

1. The code of this *Program* is strict mode code if the Directive Prologue (14.1) of its *ProgramBody* contains a Use Strict Directive or if any of the conditions of 10.1.1 apply. If the code of this *Program* is strict mode code, *ProgramBody* is evaluated in the following steps as strict mode code. Otherwise *ProgramBody* is evaluated in the following steps as non-strict mode code.
2. If *ProgramBody* is not present, return *NormalCompletion*(empty).
3. Let *progCxt* be a new execution context.
4. Set the *progCxt*'s Realm to *realm*.
5. Set the *progCxt*'s VariableEnvironment to *realm*._{[[globalEnv]]}
6. Set the *progCxt*'s LexicalEnvironment to *realm*._{[[globalEnv]]}
7. Push *progCxt* on to the execution context stack; *progCxt* is now the running execution context.
8. If *ProgramBody* is present, then
 - a. Perform Global Binding Instantiation as described in 10.5.x using the global code.
9. Let *result* be the result of evaluating *ProgramBody*.
10. Suspend *progCxt* and remove it from the execution context stack. *The stack is now empty and there is no running execution context.*
11. Return *result*.

NOTE The processes for initiating the evaluation of a *Program* and for dealing with the result of such an evaluation are defined by an ECMAScript implementation and not by this specification.

14.1 Directive Prologues and the Use Strict Directive

A Directive Prologue is the longest sequence of *ExpressionStatement* productions occurring as the initial *StatementList* item productions of a *ProgramBody* or *FunctionBody* and where each *ExpressionStatement* in the sequence consists entirely of a *StringLiteral* token followed a semicolon. The semicolon may appear explicitly or may be inserted by automatic semicolon insertion. A Directive Prologue may be an empty sequence.

A Use Strict Directive is an *ExpressionStatement* in a Directive Prologue whose *StringLiteral* is either the exact character sequences "use strict" or 'use strict'. A Use Strict Directive may not contain an *EscapeSequence* or *LineContinuation*.

A Directive Prologue may contain more than one Use Strict Directive. However, an implementation may issue a warning if this occurs.

NOTE The *ExpressionStatement* productions of a Directive Prologue are evaluated normally during evaluation of the containing production. Implementations may define implementation specific meanings for *ExpressionStatement* productions which are not a Use Strict Directive and which occur in a Directive Prologue. If an appropriate notification mechanism exists, an implementation should issue a warning if it encounters in a Directive Prologue an *ExpressionStatement* that is not a Use Strict Directive or which does not have a meaning defined by the implementation.

15 Standard Built-in ECMAScript Objects

There are certain built-in objects available whenever an ECMAScript program begins execution. One, the global object, is part of the lexical environment of the executing program. Others are accessible as initial properties of the global object.

Unless specified otherwise, a built-in object has the *[[NativeBrand]]* internal property with value *NativeFunction* if that built-in object has a *[[Call]]* internal property. Unless specified otherwise, the *[[Extensible]]* internal property of a built-in object initially has the value *true*.

Deleted: *SourceElement* : Statement
FunctionDeclaration

Deleted: Semantics
The production

Deleted: *SourceElements*_{opt}

Deleted: is evaluated as follows:

Deleted: *SourceElements*

Deleted: *SourceElements*

Deleted: *SourceElements*

Deleted: *SourceElements*

Deleted: (normal,

Deleted:

Deleted: , empty

Deleted: for global code as described in 10.4.1

Deleted: <#> Set the *progCxt*'s PreviousContext to empty

Deleted: 's

Deleted: G

Deleted:

Deleted: ironment

Deleted: 's Global Environment

Comment [AWB7111]: fix

Deleted: *SourceElements*

Comment [AWB6112]: This is where we could put something about what to do with unhandled exceptions

Deleted: Exit the execution context *progCxt*.

Deleted: running current execution context to empty

Deleted: The production *SourceElements* *ProgramBody*
SourceElements *SourceElementStatementList* is evaluated follows:
<#> Let *headResult* be the result of evaluating *SourceElement*

<#> If *headResult* is an abrupt completion, return *headResult*

<#> Let *tailResult* be the result of evaluating *SourceElement*

<#> If *tailResult*.value is empty, let *V* = *headResult*.value, otherwise, let *V* = *tailResult*.value

<#> Return (*tailResult*.type, *V*, *tailResult*.target) the result of evaluating *StatementList*.

Deleted: The production *SourceElement* : Statement is evaluated as follows:
<#> Return the result of evaluating *Statement*.
The production *SourceElement* : FunctionDeclaration is evaluated as follows:
<#> Return (normal, empty, empty).

Deleted: as the initial *SourceElement* productions of *Program* or

Deleted: *SourceElements*

Deleted: the

Deleted: [[Class]] internal property of

Deleted: is "Function"

Deleted: IsFunction

Deleted: , or "Object" if that built-in object does not have a [[Call]] internal property

Many built-in objects are functions: they can be invoked with arguments. Some of them furthermore are constructors: they are functions intended for use with the `new` operator. For each built-in function, this specification describes the arguments required by that function and properties of the Function object. For each built-in constructor, this specification furthermore describes properties of the prototype object of that constructor and properties of specific object instances returned by a `new` expression that invokes that constructor.

Unless otherwise specified in the description of a particular function, if a function or constructor described in this clause is given fewer arguments than the function is specified to require, the function or constructor shall behave exactly as if it had been given sufficient additional arguments, each such argument being the `undefined` value.

Unless otherwise specified in the description of a particular function, if a function or constructor described in this clause is given more arguments than the function is specified to allow, the extra arguments are evaluated by the call and then ignored by the function. However, an implementation may define implementation specific behaviour relating to such arguments as long as the behaviour is not the throwing of a **TypeError** exception that is predicated simply on the presence of an extra argument.

NOTE Implementations that add additional capabilities to the set of built-in functions are encouraged to do so by adding new functions rather than adding new parameters to existing functions.

Every built-in function and every built-in constructor has the Function prototype object, which is the initial value of the expression `Function.prototype` (15.3.4), as the value of its `[[Prototype]]` internal property.

Unless otherwise specified every built-in prototype object has the Object prototype object, which is the initial value of the expression `Object.prototype` (15.2.4), as the value of its `[[Prototype]]` internal property, except the Object prototype object itself.

None of the built-in functions described in this clause that are not constructors shall implement the `[[Construct]]` internal method unless otherwise specified in the description of a particular function. The behavior specified in this clause for each built-in function is the specification of the `[[Call]]` internal method behavior for that function. None of the built-in functions described in this clause shall have a `prototype` property unless otherwise specified in the description of a particular function.

Comment [AW113]: https://bugs.ecmascript.org/show_bug.cgi?id=155

This clause generally describes distinct behaviours for when a constructor is “called as a function” and for when it is “called as part of a `new` expression”. The “called as a function” behaviour corresponds to the invocation of the constructor’s `[[Call]]` internal method and the “called as part of a new expression” behaviour corresponds to the invocation of the constructor’s `[[Construct]]` internal method.

Every built-in Function object described in this clause—whether as a constructor, an ordinary function, or both—has a `length` property whose value is an integer. Unless otherwise specified, this value is equal to the largest number of named arguments shown in the subclause headings for the function description, including optional parameters.

NOTE For example, the Function object that is the initial value of the `slice` property of the String prototype object is described under the subclause heading “`String.prototype.slice (start, end)`” which shows the two named arguments `start` and `end`; therefore the value of the `length` property of that Function object is 2.

In every case, the `length` property of a built-in Function object described in this clause has the attributes `{ [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }`. Every other property described in this clause has the attributes `{ [[Writable]]: true, [[Enumerable]]: false, [[Configurable]]: true }` unless otherwise specified.

15.1 The Global Object

The unique *global object* is created before control enters any execution context.

Unless otherwise specified, the standard built-in properties of the global object have attributes {`[[Writable]]: true, [[Enumerable]]: false, [[Configurable]]: true`}.

The global object does not have a `[[Construct]]` internal property; it is not possible to use the global object as a constructor with the `new` operator.

The global object does not have a `[[Call]]` internal property; it is not possible to invoke the global object as a function.

The value of the `[[Prototype]]` internal property of the global object is implementation-dependent.

In addition to the properties defined in this specification the global object may have additional host defined properties. This may include a property whose value is the global object itself; for example, in the HTML document object model the `window` property of the global object is the global object itself.

Deleted: s
Deleted: and `[[Class]]`
Deleted: ies
Deleted: are

15.1.1 Value Properties of the Global Object

15.1.1.1 NaN

The value of `NaN` is `NaN` (see 8.5). This property has the attributes {`[[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false`}.

15.1.1.2 Infinity

The value of `Infinity` is `+∞` (see 8.5). This property has the attributes {`[[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false`}.

15.1.1.3 undefined

The value of `undefined` is `undefined` (see 8.1). This property has the attributes {`[[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false`}.

15.1.2 Function Properties of the Global Object

15.1.2.1 eval (x)

When the `eval` function is called with one argument `x`, the following steps are taken:

1. If `Type(x)` is not `String`, return `x`.
2. Let `prog` be the ECMAScript code that is the result of parsing `x`, interpreted as UTF-16 encoded Unicode text as described in 8.4, for the goal symbol `Program`. If the parse fails or any early errors are detected, throw a `SyntaxError` exception (but see also clause 16).
3. Let `evalCtx` be the result of establishing a new execution context (10.4.2) for the eval code `prog`.
4. If there is no calling context or if the eval code is not being evaluated by a direct call (15.1.2.1.1) to the eval function then,
 - a. Initialise the execution context as if it was a global execution context using the eval code as `C` as described in 10.4.1.1.
5. Else,
 - a. Set the `ThisBinding` to the same value as the `ThisBinding` of the calling execution context.
 - b. Set the `LexicalEnvironment` to the same value as the `LexicalEnvironment` of the calling execution context.
 - c. Set the `VariableEnvironment` to the same value as the `VariableEnvironment` of the calling execution context.
6. If the eval code is strict code, then
 - a. Let `strictVarEnv` be the result of calling `NewDeclarativeEnvironment` passing the `LexicalEnvironment` as the argument.
 - b. Set the `LexicalEnvironment` to `strictVarEnv`.
 - c. Set the `VariableEnvironment` to `strictVarEnv`.
7. Perform Declaration Binding Instantiation as described in 10.5 using the eval code.

Deleted: as a

8. Let *result* be the result of evaluating the program *prog*.
9. Exit the running execution context *evalCtx*, restoring the previous execution context.
10. If *result.type* is **normal** and its completion value is a value *V*, then return the value *V*.
11. If *result.type* is **normal** and its completion value is **empty**, then return the value **undefined**.
12. Otherwise, *result.type* must be **throw**. Throw *result.value* as an exception.

NOTE *The eval code cannot instantiate variable or function bindings in the variable environment of the calling context that invoked the eval if either the code of the calling context or the eval code is strict code. Instead such bindings are instantiated in a new VariableEnvironment that is only accessible to the eval code.*

Comment [AWB7114]: TODO: need to finish refactoring after completing global scope instantiation work.

15.1.2.1.1 Direct Call to Eval

A direct call to the eval function is one that is expressed as a *CallExpression* that meets the following two conditions:

The Reference that is the result of evaluating the *MemberExpression* in the *CallExpression* has an environment record as its base value and its reference name is "**eval**".

The result of calling the abstract operation *GetValue* with that Reference as the argument is the standard built-in function defined in 15.1.2.1.

15.1.2.2 parseInt (string , radix)

The **parseInt** function produces an integer value dictated by interpretation of the contents of the *string* argument according to the specified *radix*. Leading white space in *string* is ignored. If *radix* is **undefined** or 0, it is assumed to be 10 except when the number begins with the character pairs **0x** or **0X**, in which case a radix of 16 is assumed. If *radix* is 16, the number may also optionally begin with the character pairs **0x** or **0X**.

When the **parseInt** function is called, the following steps are taken:

1. Let *inputString* be *ToString(string)*.
2. **ReturnIfAbrupt(string)**.
3. Let *S* be a newly created substring of *inputString* consisting of the first character that is not a *StrWhiteSpaceChar* and all characters following that character. (In other words, remove leading white space.) If *inputString* does not contain any such characters, let *S* be the empty string.
4. Let *sign* be 1.
5. If *S* is not empty and the first character of *S* is a minus sign **-**, let *sign* be **-1**.
6. If *S* is not empty and the first character of *S* is a plus sign **+** or a minus sign **-**, then remove the first character from *S*.
7. Let *R* = *ToInt32(radix)*.
8. **ReturnIfAbrupt(R)**.
9. Let *stripPrefix* be **true**.
10. If *R* \neq 0, then
 - a. If *R* < 2 or *R* > 36, then return **NaN**.
 - b. If *R* \neq 16, let *stripPrefix* be **false**.
11. Else, *R* = 0
 - a. Let *R* = 10.
12. If *stripPrefix* is **true**, then
 - a. If the length of *S* is at least 2 and the first two characters of *S* are either "**0x**" or "**0X**", then remove the first two characters from *S* and let *R* = 16.
13. If *S* contains any character that is not a radix-*R* digit, then let *Z* be the substring of *S* consisting of all characters before the first such character; otherwise, let *Z* be *S*.
14. If *Z* is empty, return **NaN**.
15. Let *mathInt* be the mathematical integer value that is represented by *Z* in radix-*R* notation, using the letters **A-Z** and **a-z** for digits with values 10 through 35. (However, if *R* is 10 and *Z* contains more than 20 significant digits, every significant digit after the 20th may be replaced by a **0** digit, at the option of the implementation; and if *R* is not 2, 4, 8, 10, 16, or 32, then *mathInt* may be an implementation-dependent approximation to the mathematical integer value that is represented by *Z* in radix-*R* notation.)
16. Let *number* be the Number value for *mathInt*.

17. Return $\text{sign} \times \text{number}$.

NOTE `parseInt` may interpret only a leading portion of *string* as an integer value; it ignores any characters that cannot be interpreted as part of the notation of an integer, and no indication is given that any such characters were ignored.

15.1.2.3 `parseFloat (string)`

The `parseFloat` function produces a Number value dictated by interpretation of the contents of the *string* argument as a decimal literal.

When the `parseFloat` function is called, the following steps are taken:

1. Let *inputString* be `ToString(string)`.
2. `ReturnIfAbrupt(string)`.
3. Let *trimmedString* be a substring of *inputString* consisting of the leftmost character that is not a *StrWhiteSpaceChar* and all characters to the right of that character. (In other words, remove leading white space.) If *inputString* does not contain any such characters, let *trimmedString* be the empty string.
4. If neither *trimmedString* nor any prefix of *trimmedString* satisfies the syntax of a *StrDecimalLiteral* (see 9.3.1), return **NaN**.
5. Let *numberString* be the longest prefix of *trimmedString*, which might be *trimmedString* itself, that satisfies the syntax of a *StrDecimalLiteral*.
6. Return the Number value for the MV of *numberString*.

NOTE `parseFloat` may interpret only a leading portion of *string* as a Number value; it ignores any characters that cannot be interpreted as part of the notation of an decimal literal, and no indication is given that any such characters were ignored.

15.1.2.4 `isNaN (number)`

Returns **true** if the argument coerces to **NaN**, and otherwise returns **false**.

1. `Let num be ToNumber(number)`.
2. `ReturnIfAbrupt(num)`.
3. If *num* is **NaN**, return **true**.
4. Otherwise, return **false**.

Deleted: `ToNumber(number)`

NOTE A reliable way for ECMAScript code to test if a value *x* is a **NaN** is an expression of the form *x* \neq *x*. The result will be **true** if and only if *x* is a **NaN**.

15.1.2.5 `isFinite (number)`

Returns **false** if the argument coerces to **NaN**, $+\infty$, or $-\infty$, and otherwise returns **true**.

1. `Let num be ToNumber(number)`.
2. `ReturnIfAbrupt(num)`.
3. If `ToNumber(num)` is **NaN**, $+\infty$, or $-\infty$, return **false**.
4. Otherwise, return **true**.

Deleted: `ber`

15.1.3 URI Handling Function Properties

Uniform Resource Identifiers, or URIs, are Strings that identify resources (e.g. web pages or files) and transport protocols by which to access them (e.g. HTTP or FTP) on the Internet. The ECMAScript language itself does not provide any support for using URIs except for functions that encode and decode URIs as described in 15.1.3.1, 15.1.3.2, 15.1.3.3 and 15.1.3.4.

NOTE Many implementations of ECMAScript provide additional functions and methods that manipulate web pages; these functions are beyond the scope of this standard.

A URI is composed of a sequence of components separated by component separators. The general form is:

Scheme : First / Second ; Third ? Fourth

where the italicised names represent components and “:”, “/”, “;” and “?” are reserved characters used as separators. The `encodeURI` and `decodeURI` functions are intended to work with complete URIs; they assume that any reserved characters in the URI are intended to have special meaning and so are not encoded. The `encodeURIComponent` and `decodeURIComponent` functions are intended to work with the individual component parts of a URI; they assume that any reserved characters represent text and so must be encoded so that they are not interpreted as reserved characters when the component is part of a complete URI.

The following lexical grammar specifies the form of encoded URIs.

Syntax

uri ::=

 *uriCharacters*_{opt}

uriCharacters ::=

 uriCharacter *uriCharacters*_{opt}

uriCharacter ::=

 uriReserved

 uriUnescaped

 uriEscaped

uriReserved ::=
 one of

 ; / ? : @ & = + \$,

uriUnescaped ::=

 uriAlpha

 DecimalDigit

 uriMark

uriEscaped ::=

 % *HexDigit* *HexDigit*

uriAlpha ::=
 one of

 a b c d e f g h i j k l m n o p q r s t u v w x y z

 A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

uriMark ::=
 one of

 - _ . ! ~ * ' ()

NOTE The above syntax is based upon RFC 2396 and does not reflect changes introduced by the more recent RFC 3986.

Runtime Semantics

When a character to be included in a URI is not listed above or is not intended to have the special meaning sometimes given to the reserved characters, that character must be encoded. The character is transformed into its UTF-8 encoding, with surrogate pairs first converted from UTF-16 to the corresponding code point value. (Note that for code units in the range [0,127] this results in a single octet with the same value.) The resulting sequence of octets is then transformed into a String with each octet represented by an escape sequence of the form "%xx".

The encoding and escaping process is described by the abstract operation `Encode` taking two String arguments *string* and *unescapeSet*.

1. Let *strLen* be the number of characters in *string*.
2. Let *R* be the empty String.

3. Let k be 0.
4. Repeat
 - a. If k equals $strLen$, return R .
 - b. Let C be the character at position k within $string$.
 - c. If C is in $unescapeSet$, then
 - i. Let S be a String containing only the character C .
 - ii. Let R be a new String value computed by concatenating the previous value of R and S .
 - d. Else, C is not in $unescapeSet$
 - i. If the code unit value of C is not less than 0xDC00 and not greater than 0xDFFF, throw a **URIError** exception.
 - ii. If the code unit value of C is less than 0xD800 or greater than 0xDBFF, then
 1. Let V be the code unit value of C .
 - iii. Else,
 1. Increase k by 1.
 2. If k equals $strLen$, throw a **URIError** exception.
 3. Let $kChar$ be the code unit value of the character at position k within $string$.
 4. If $kChar$ is less than 0xDC00 or greater than 0xDFFF, throw a **URIError** exception.
 5. Let V be $((\text{the code unit value of } C) - 0xD800) \times 0x400 + (kChar - 0xDC00) + 0x10000$.
 - iv. Let $Octets$ be the array of octets resulting by applying the UTF-8 transformation to V , and let L be the array size.
 - v. Let j be 0.
 - vi. Repeat, while $j < L$
 1. Let $jOctet$ be the value at position j within $Octets$.
 2. Let S be a String containing three characters "%XY" where XY are two uppercase hexadecimal digits encoding the value of $jOctet$.
 3. Let R be a new String value computed by concatenating the previous value of R and S .
 4. Increase j by 1.
 - e. Increase k by 1.

The unescaping and decoding process is described by the abstract operation `Decode` taking two String arguments `string` and `reservedSet`.

1. Let $strLen$ be the number of characters in $string$.
2. Let R be the empty String.
3. Let k be 0.
4. Repeat
 - a. If k equals $strLen$, return R .
 - b. Let C be the character at position k within $string$.
 - c. If C is not '%', then
 - i. Let S be the String containing only the character C .
 - d. Else, C is '%'
 - i. Let $start$ be k .
 - ii. If $k + 2$ is greater than or equal to $strLen$, throw a **URIError** exception.
 - iii. If the characters at position $(k+1)$ and $(k + 2)$ within $string$ do not represent hexadecimal digits, throw a **URIError** exception.
 - iv. Let B be the 8-bit value represented by the two hexadecimal digits at position $(k + 1)$ and $(k + 2)$.
 - v. Increment k by 2.
 - vi. If the most significant bit in B is 0, then
 1. Let C' be the character with code unit value B .
 2. If C' is not in `reservedSet`, then
 - a. Let S be the String containing only the character C' .
 3. Else, C' is in `reservedSet`
 - a. Let S be the substring of $string$ from position $start$ to position k included.
 - vii. Else, the most significant bit in B is 1
 1. Let n be the smallest non-negative number such that $(B \ll n) \& 0x80$ is equal to 0.
 2. If n equals 1 or n is greater than 4, throw a **URIError** exception.

3. Let *Octets* be an array of 8-bit integers of size *n*.
4. Put *B* into *Octets* at position 0.
5. If $k + (3 \times (n - 1))$ is greater than or equal to *strLen*, throw a **URIError** exception.
6. Let *j* be 1.
7. Repeat, while $j < n$
 - a. Increment *k* by 1.
 - b. If the character at position *k* is not ‘%’, throw a **URIError** exception.
 - c. If the characters at position (*k* + 1) and (*k* + 2) within *string* do not represent hexadecimal digits, throw a **URIError** exception.
 - d. Let *B* be the 8-bit value represented by the two hexadecimal digits at position (*k* + 1) and (*k* + 2).
 - e. If the two most significant bits in *B* are not 10, throw a **URIError** exception.
 - f. Increment *k* by 2.
 - g. Put *B* into *Octets* at position *j*.
 - h. Increment *j* by 1.
8. Let *V* be the value obtained by applying the UTF-8 transformation to *Octets*, that is, from an array of octets into a 21-bit value. If *Octets* does not contain a valid UTF-8 encoding of a Unicode code point throw an **URIError** exception.
9. If *V* is less than 0x10000, then
 - a. Let *C* be the character with code unit value *V*.
 - b. If *C* is not in *reservedSet*, then
 - i. Let *S* be the String containing only the character *C*.
 - c. Else, *C* is in *reservedSet*
 - i. Let *S* be the substring of *string* from position *start* to position *k* included.
10. Else, *V* is $\geq 0x10000$
 - a. Let *L* be $((V - 0x10000) \& 0x3FF) + 0xDC00$.
 - b. Let *H* be $((((V - 0x10000) \gg 10) \& 0x3FF) + 0xD800$.
 - c. Let *S* be the String containing the two characters with code unit values *H* and *L*.
 - e. Let *R* be a new String value computed by concatenating the previous value of *R* and *S*.
 - f. Increase *k* by 1.

NOTE This syntax of Uniform Resource Identifiers is based upon RFC 2396 and does not reflect the more recent RFC 3986 which replaces RFC 2396. A formal description and implementation of UTF-8 is given in RFC 3629.

In UTF-8, characters are encoded using sequences of 1 to 6 octets. The only octet of a “sequence” of one has the higher-order bit set to 0, the remaining 7 bits being used to encode the character value. In a sequence of *n* octets, *n*>1, the initial octet has the *n* higher-order bits set to 1, followed by a bit set to 0. The remaining bits of that octet contain bits from the value of the character to be encoded. The following octets all have the higher-order bit set to 1 and the following bit set to 0, leaving 6 bits in each to contain bits from the character to be encoded. The possible UTF-8 encodings of ECMAScript characters are specified in [Table 26](#).

Table 26 — UTF-8 Encodings

Code Unit Value	Representation	1st Octet	2nd Octet	3rd Octet	4th Octet
0x0000 – 0x007F	00000000_0zzzzzzz	0zzzzzzz			
0x0080 – 0x07FF	00000yyy_yyzzzzzz	110yyyyy	10zzzzzz		
0x0800 – 0xD7FF	xxxxyyyy_yyzzzzzz	1110xxxx	10yyyyyy	10zzzzzz	
0xD800 – 0xDBFF followed by 0xDC00 – 0xFFFF	110110vv_vvvwwwxx followed by 110111yy_yyzzzzzz	11110uuu	10uuwwww	10xxxxyy	10zzzzzz
0xDB800 – 0xDBFF not followed by 0xDC00 – 0xFFFF	causes URIerror				
0xDC00 – 0xFFFF	causes URIerror				
0xE000 – 0xFFFF	xxxxyyyy_yyzzzzzz	1110xxxx	10yyyyyy	10zzzzzz	

Where

$uuuuu = vvvv + 1$

to account for the addition of 0x10000 as in Surrogates, section 3.7, of the Unicode Standard.

The range of code unit values 0xD800-0xDFFF is used to encode surrogate pairs; the above transformation combines a UTF-16 surrogate pair into a UTF-32 representation and encodes the resulting 21-bit value in UTF-8. Decoding reconstructs the surrogate pair.

RFC 3629 prohibits the decoding of invalid UTF-8 octet sequences. For example, the invalid sequence C0 80 must not decode into the character U+0000. Implementations of the Decode algorithm are required to throw a **URIError** when encountering such invalid sequences.

15.1.3.1 decodeURI (*encodedURI*)

The **decodeURI** function computes a new version of a URI in which each escape sequence and UTF-8 encoding of the sort that might be introduced by the **encodeURI** function is replaced with the character that it represents. Escape sequences that could not have been introduced by **encodeURI** are not replaced.

When the **decodeURI** function is called with one argument *encodedURI*, the following steps are taken:

1. Let *uriString* be `ToString(encodedURI)`.
2. [ReturnIfAbrupt\(uriString\)](#).
3. Let *reservedURISet* be a String containing one instance of each character valid in *uriReserved* plus “#”.
4. Return the result of calling `Decode(uriString, reservedURISet)`

NOTE The character “#” is not decoded from escape sequences even though it is not a reserved URI character.

15.1.3.2 decodeURIComponent (*encodedURIComponent*)

The **decodeURIComponent** function computes a new version of a URI in which each escape sequence and UTF-8 encoding of the sort that might be introduced by the **encodeURIComponent** function is replaced with the character that it represents.

When the **decodeURIComponent** function is called with one argument *encodedURIComponent*, the following steps are taken:

1. Let *componentString* be `ToString(encodedURIComponent)`.
2. [ReturnIfAbrupt\(componentString\)](#).
3. Let *reservedURIComponentSet* be the empty String.
4. Return the result of calling `Decode(componentString, reservedURIComponentSet)`

15.1.3.3 encodeURI (*uri*)

The **encodeURI** function computes a new version of a URI in which each instance of certain characters is replaced by one, two, three, or four escape sequences representing the UTF-8 encoding of the character.

When the **encodeURI** function is called with one argument *uri*, the following steps are taken:

1. Let *uriString* be `ToString(uri)`.
2. [ReturnIfAbrupt\(uriString\)](#).
3. Let *unescapeURISet* be a String containing one instance of each character valid in *uriReserved* and *uriUnescaped* plus “#”.
4. Return the result of calling `Encode(uriString, unescapeURISet)`

NOTE The character “#” is not encoded to an escape sequence even though it is not a reserved or unescaped URI character.

15.1.3.4 encodeURIComponent (*uriComponent*)

The `encodeURIComponent` function computes a new version of a URI in which each instance of certain characters is replaced by one, two, three, or four escape sequences representing the UTF-8 encoding of the character.

When the `encodeURIComponent` function is called with one argument *uriComponent*, the following steps are taken:

1. Let *componentString* be `ToString(uriComponent)`.
2. ReturnIfAbrupt(*componentString*).
3. Let *unescapeURIComponentSet* be a String containing one instance of each character valid in *uriUnescaped*.
4. Return the result of calling `Encode(componentString, unescapeURIComponentSet)`

15.1.4 Constructor Properties of the Global Object

15.1.4.1 Object (...)

See 15.2.1 and 15.2.2.

15.1.4.2 Function (...)

See 15.3.1 and 15.3.2.

15.1.4.3 Array (...)

See 15.4.1 and 15.4.2.

15.1.4.4 String (...)

See 15.5.1 and 15.5.2.

15.1.4.5 Boolean (...)

See 15.6.1 and 15.6.2.

15.1.4.6 Number (...)

See 15.7.1 and 15.7.2.

15.1.4.7 Date (...)

See 15.9.2.

15.1.4.8 RegExp (...)

See 15.10.3 and 15.10.4.

15.1.4.9 Error (...)

See 15.11.1 and 15.11.2.

15.1.4.10 EvalError (...)

See 15.11.6.1.

15.1.4.11 RangeError (. . .)

See 15.11.6.2.

15.1.4.12 ReferenceError (. . .)

See 15.11.6.3.

15.1.4.13 SyntaxError (. . .)

See 15.11.6.4.

15.1.4.14 TypeError (. . .)

See 15.11.6.5.

15.1.4.15 URIError (. . .)

See 15.11.6.6.

15.1.5 Other Properties of the Global Object

15.1.5.1 Math

See 15.8.

15.1.5.2 JSON

See 15.12.

15.2 Object Objects

The abstract operation `ObjectCreate` with optional argument `proto` (an object or null) is used to specify the creation of new `Object` objects. It performs the following steps:

1. If `proto` was not provided, let `proto` be the intrinsic `%ObjectPrototype%`.
2. Let `obj` be a newly created ECMAScript object.
3. Set the `[[Prototype]]` internal property of `obj` to `proto`.
4. Set `obj`'s common internal methods to the default definitions specified in 8.12.
5. Set the `[[Extensible]]` internal property of `obj` to `true`.
6. Return `obj`.

15.2.1 The Object Constructor Called as a Function

When `Object` is called as a function rather than as a constructor, it performs a type conversion.

15.2.1.1 `Object ([value])`

When the `Object` function is called with no arguments or with one argument `value`, the following steps are taken:

1. If `value` is `null`, `undefined` or not supplied, return the result of the abstract operation `ObjectCreate`.
2. Return `ToObject(value)`.

15.2.2 The Object Constructor

When `Object` is called as part of a `new` expression, it is a constructor that may create an object.

Deleted: create and

Deleted: ion

Deleted: a new `Object` object exactly as if the standard built-in `Object` constructor had been called with the same arguments (15.2.2.1)

15.2.2.1 new Object ([value])

When the `Object` constructor is called with no arguments or with one argument `value`, the following steps are taken:

1. If `value` is supplied, then
 - a. If `Type(value)` is `Object`, then return `value`.
 - b. If `Type(value)` is `String`, return `ToObject(value)`.
 - c. If `Type(value)` is `Boolean`, return `ToObject(value)`.
 - d. If `Type(value)` is `Number`, return `ToObject(value)`.
2. Assert: The argument `value` was not supplied or its type was `Null` or `Undefined`.
3. Return [the result of the abstract operation ObjectCreate](#).

Deleted: ¶
If the `value` is a native ECMAScript object, do not create a new object but simply
Deleted: <#> If the `value` is a host object, then actions are taken and a result is returned in an implementation-dependent manner that may depend on the host object.¶

15.2.3 Properties of the Object Constructor

The value of the `[[Prototype]]` internal property of the `Object` constructor is the standard built-in `Function` prototype object.

Besides the internal properties and the `length` property (whose value is `1`), the `Object` constructor has the following properties:

15.2.3.1 Object.prototype

The initial value of `Object.prototype` is the standard built-in `Object` prototype object (15.2.4).

This property has the attributes `{[[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }`.

Deleted: <#> Let `obj` be a newly created native ECMAScript object.¶
<#> Set the `[[Prototype]]` internal property of `obj` to the standard built-in `Object` prototype object (15.2.4).¶
<#> Set the `[[Class]]` internal property of `obj` to "Object".¶
<#> Set the `[[Extensible]]` internal property of `obj` to `true`.¶
<#> Set all the internal methods of `obj` as specified 8.12.¶

Deleted: `obj`

Deleted: `ion`

15.2.3.2 Object.getPrototypeOf (O)

When the `getPrototypeOf` function is called with argument `O`, the following steps are taken:

1. If `Type(O)` is not `Object` throw a `TypeError` exception.
2. Return the value of the `[[Prototype]]` internal property of `O`.

15.2.3.3 Object.getOwnPropertyDescriptor (O, P)

When the `getOwnPropertyDescriptor` function is called, the following steps are taken:

1. If `Type(O)` is not `Object` throw a `TypeError` exception.
2. Let `name` be `ToString(P)`.
3. [ReturnIfAbrupt\(name\)](#).
4. Let `desc` be the result of calling the `[[GetOwnProperty]]` internal method of `O` with argument `name`.
5. Return the result of calling `FromPropertyDescriptor(desc)` (8.10.4).

Deleted: abstraction operation

Deleted: the result of creating a new object as if the expression `new Array ()` where `Array` is the standard built-in constructor with that name

15.2.3.4 Object.getOwnPropertyNames (O)

When the `getOwnPropertyNames` function is called, the following steps are taken:

1. If `Type(O)` is not `Object` throw a `TypeError` exception.
2. Let `array` be [the result of the abstract operation ArrayCreate \(15.4\) with argument 0](#).
3. Let `n` be `0`.
4. For each named own property `P` of `O`
 - a. Let `name` be the String value that is the name of `P`.
 - b. Call the `[[DefineOwnProperty]]` internal method of `array` with arguments `ToString(n)`, the `PropertyDescriptor {[[Value]]: name, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}, and false.`
 - c. Increment `n` by 1.
5. Return `array`.

NOTE If `O` is a `String` instance, the set of own properties processed in step 4 includes the implicit properties defined in 15.5.5.2 that correspond to character positions within the object's `[[PrimitiveValue]]` `String`.

15.2.3.5 Object.create (O [, Properties])

The **create** function creates a new object with a specified prototype. When the **create** function is called, the following steps are taken:

1. If Type(*O*) is not Object or Null throw a **TypeError** exception.
2. Let *obj* be the result of the abstract operation ObjectCreate with argument *O*.
3. If the argument *Properties* is present and not **undefined**, then
 - a. Return the result of the abstract operation ObjectDefineProperties with arguments *obj* and *Properties*.
4. Return *obj*.

15.2.3.6 Object.defineProperty (O, P, Attributes)

The **defineProperty** function is used to add an own property and/or update the attributes of an existing own property of an object. When the **defineProperty** function is called, the following steps are taken:

1. If Type(*O*) is not Object throw a **TypeError** exception.
2. Let *name* be ToString(*P*).
3. ReturnIfAbrupt(*name*).
4. Let *desc* be the result of calling ToPropertyDescriptor with *Attributes* as the argument.
5. Call the **[[DefineOwnProperty]]** internal method of *O* with arguments *name*, *desc*, and **true**.
6. Return *O*.

15.2.3.7 Object.defineProperties (O, Properties)

The **defineProperties** function is used to add own properties and/or update the attributes of existing own properties of an object. When the **defineProperties** function is called, the following steps are taken:

1. Return the result of the abstract operation ObjectDefineProperties with arguments *O* and *Properties*.

The abstract operation ObjectDefineProperties with arguments *O* and *Properties* performs the following steps:

1. If Type(*O*) is not Object throw a **TypeError** exception.
2. Let *props* be **ToObject(*Properties*)**.
3. Let *names* be an internal list containing the names of each enumerable own property of *props*.
4. Let *descriptors* be an empty internal List.
5. For each element *P* of *names* in list order,
 - a. Let *descObj* be the result of calling the **[[Get]]** internal method of *props* with *P* as the argument.
 - b. ReturnIfAbrupt(*descObj*).
 - c. Let *desc* be the result of calling **ToPropertyDescriptor** with *descObj* as the argument.
 - d. ReturnIfAbrupt(*desc*).
 - e. Append the pair (a two element List) consisting of *P* and *desc* to the end of *descriptors*.
6. For each *pair* from *descriptors* in list order,
 - a. Let *P* be the first element of *pair*.
 - b. Let *desc* be the second element of *pair*.
 - c. Let *status* be the result of calling the **[[DefineOwnProperty]]** internal method of *O* with arguments *P*, *desc*, and **true**.
 - d. ReturnIfAbrupt(*status*).
7. Return *O*.

If an implementation defines a specific order of enumeration for the **for-in** statement, that same enumeration order must be used to order the list elements in step 3 of this algorithm.

15.2.3.8 Object.seal (O)

When the **seal** function is called, the following steps are taken:

1. If Type(*O*) is not Object throw a **TypeError** exception.

Deleted: abstraction operation

Deleted: the result of creating a new object as if by the expression **new Object()** where **Object** is the standard built-in constructor with that name

Deleted: <#> Set the **[[Prototype]]** internal property of *obj* to *O*.

Deleted: add own properties to *obj* as if by calling the standard built-in function

Deleted: **Object.defineProperties**

Deleted: em

Deleted: s

Deleted: Call

2. For each named own property name P of O ,
 - a. Let $desc$ be the result of calling the $[[GetOwnProperty]]$ internal method of O with P .
 - b. If $desc.[[Configurable]]$ is **true**, set $desc.[[Configurable]]$ to **false**.
 - c. Let $status$ be the result of calling the $[[DefineOwnProperty]]$ internal method of O with P , $desc$, and **true** as arguments.
 - d. $\text{ReturnIfAbrupt}(status)$.
3. Set the $[[Extensible]]$ internal property of O to **false**.
4. Return O .

Deleted: Call

15.2.3.9 Object.freeze (O)

When the **freeze** function is called, the following steps are taken:

1. If $\text{Type}(O)$ is not **Object** throw a **TypeError** exception.
2. For each named own property name P of O ,
 - a. Let $desc$ be the result of calling the $[[GetOwnProperty]]$ internal method of O with P .
 - b. If $\text{IsDataDescriptor}(desc)$ is **true**, then
 - i. If $desc.[[Writable]]$ is **true**, set $desc.[[Writable]]$ to **false**.
 - c. If $desc.[[Configurable]]$ is **true**, set $desc.[[Configurable]]$ to **false**.
 - d. Let $status$ be the result of calling the $[[DefineOwnProperty]]$ internal method of O with P , $desc$, and **true** as arguments.
 - e. $\text{ReturnIfAbrupt}(status)$.
3. Set the $[[Extensible]]$ internal property of O to **false**.
4. Return O .

Deleted: Call

15.2.3.10 Object.preventExtensions (O)

When the **preventExtensions** function is called, the following steps are taken:

1. If $\text{Type}(O)$ is not **Object** throw a **TypeError** exception.
2. Set the $[[Extensible]]$ internal property of O to **false**.
3. Return O .

15.2.3.11 Object.isSealed (O)

When the **isSealed** function is called with argument O , the following steps are taken:

1. If $\text{Type}(O)$ is not **Object** throw a **TypeError** exception.
2. For each named own property name P of O ,
 - a. Let $desc$ be the result of calling the $[[GetOwnProperty]]$ internal method of O with P .
 - b. If $desc.[[Configurable]]$ is **true**, then return **false**.
3. If the $[[Extensible]]$ internal property of O is **false**, then return **true**.
4. Otherwise, return **false**.

15.2.3.12 Object.isFrozen (O)

When the **isFrozen** function is called with argument O , the following steps are taken:

1. If $\text{Type}(O)$ is not **Object** throw a **TypeError** exception.
2. For each named own property name P of O ,
 - a. Let $desc$ be the result of calling the $[[GetOwnProperty]]$ internal method of O with P .
 - b. If $\text{IsDataDescriptor}(desc)$ is **true** then
 - i. If $desc.[[Writable]]$ is **true**, return **false**.
 - c. If $desc.[[Configurable]]$ is **true**, then return **false**.
3. If the $[[Extensible]]$ internal property of O is **false**, then return **true**.
4. Otherwise, return **false**.

15.2.3.13 Object.isExtensible (O)

When the **isExtensible** function is called with argument O , the following steps are taken:

1. If `Type(O)` is not `Object` throw a `TypeError` exception.
2. Return the Boolean value of the `[[Extensible]]` internal property of `O`.

15.2.3.14 `Object.keys (O)`

When the `keys` function is called with argument `O`, the following steps are taken:

1. If the `Type(O)` is not `Object`, throw a `TypeError` exception.
2. Let `n` be the number of own enumerable properties of `O`
3. Let `array` be the result of the abstract operation `ArrayCreate (15.4)` with argument `n`
4. Let `index` be 0.
5. For each own enumerable property of `O` whose name String is `P`
 - a. Call the `[[DefineOwnProperty]]` internal method of `array` with arguments `ToString(index)`, the `PropertyDescriptor {[[Value]]: P, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `false`.
 - b. Increment `index` by 1.
6. Return `array`.

If an implementation defines a specific order of enumeration for the `for-in` statement, that same enumeration order must be used in step 5 of this algorithm.

15.2.4 Properties of the Object Prototype Object

The value of the `[[Prototype]]` internal property of the Object prototype object is `null`, and the initial value of the `[[Extensible]]` internal property is `true`.

15.2.4.1 `Object.prototype.constructor`

The initial value of `Object.prototype.constructor` is the standard built-in `Object` constructor.

15.2.4.2 `Object.prototype.toString ()`

When the `toString` method is called, the following steps are taken:

1. If the `this` value is `undefined`, return "`[object Undefined]`".
2. If the `this` value is `null`, return "`[object Null]`".
3. Let `O` be the result of calling `ToObject` passing the `this` value as the argument.
4. If `O` has a `[[NativeBrand]]` internal property, let `tag` be the corresponding value from the `Table 27`.
 5. Table 27.
 6. Else
 - a. Let `hasTag` be the result of calling the `[[HasProperty]]` internal method of `O` with argument `@@toStringTag`.
 - b. If `hasTag` is `false`, let `tag` be "`Object`".
 - c. Else,
 - i. Let `tag` be the result of calling the `[[Get]]` internal method of `O` with argument `@@toStringTag`.
 - ii. If `tag` is an abrupt completion, let `tag` be `NormalCompletion("????")`.
 - iii. Let `tag` be `tag.[[value]]`.
 - iv. If `Type(tag)` is not `String`, let `tag` be "`????`".
 - v. If `tag` is any of `"Arguments"`, `"Array"`, `"Boolean"`, `"Date"`, `"Error"`, `"Function"`, `"JSON"`, `"Math"`, `"Number"`, `"Object"`, `"RegExp"`, or `"String"`, then let `tag` be the string value "`~`" concatenated with the current value of `tag`.
 7. Return the String value that is the result of concatenating the three Strings "`[object`", `tag`, and `"]"`.

Table 27 — Tags for Classified Native Objects

<code>[[NativeBrand]] Value</code>	<code>tag Value</code>
<code>NativeFunction</code>	<code>"Function"</code>

Deleted: abstraction operation

Deleted: the result of creating a new Object as if by the expression `new Array(n)` where `Array` is the standard built-in constructor with that name

Deleted: 15.2.3.15 `Object.isObject (O)`

When the `isObject` function is called with argument `O`, the following steps are taken:
`<#>If Type(O) is Object return true.
<#>Return false.`

Deleted: , the value of the `[[Class]]` internal property is `"Object"`,

Deleted: one of the internal properties

Deleted: listed in Table 23

Deleted: `t`

Deleted: Table 27

Deleted: `i`

Deleted: `O`

Deleted: a host object, let `tag` be an implementation defined string value. This value may not be

Deleted: .

Deleted: `<#>Else, Let let class tag be the string value "Object" of the [[Class]] internal property of O.`

Deleted: class

Deleted: `¶`

NativeArray	" Array "
StringWrapper	" String "
BooleanWrapper	" Boolean "
NumberWrapper	" Number "
NativeMath	" Math "
NativeDate	" Date "
NativeRegExp	" RegExp "
NativeError	" Error "
NativeJSON	" JSON "
NativeArguments	" Arguments "

NOTE Historically, this function was occasionally used to access the string value of the [[Class]] internal property that was used in previous editions of this specification as a nominal type tag for various built-in objects. This definition of `toString` preserves the ability to use it as a reliable test for those specific kinds of built-in objects but it does not provide a reliable type testing mechanism for other kinds of built-in or program defined objects.

15.2.4.3 Object.prototype.toLocaleString()

When the `toLocaleString` method is called, the following steps are taken:

1. Let O be the `this` value.
2. ReturnIfAbrupt(O).
3. Return the result of the abstract operation `Invoke` with arguments "`toString`", O , and an empty arguments List.

NOTE 1 This function is provided to give all Objects a generic `toLocaleString` interface, even though not all may use it. Currently, `Array`, `Number`, and `Date` provide their own locale-sensitive `toLocaleString` methods.

NOTE 2 The first parameter to this function is likely to be used in a future version of this standard; it is recommended that implementations do not use this parameter position for anything else.

15.2.4.4 Object.prototype.valueOf()

When the `valueOf` method is called, the following steps are taken:

1. Let O be the result of calling `ToObject` passing the `this` value as the argument.
2. Return O .

15.2.4.5 Object.prototype.hasOwnProperty(V)

When the `hasOwnProperty` method is called with argument V , the following steps are taken:

1. Let P be `ToString(V)`.
2. ReturnIfAbrupt(P).
3. Let O be the result of calling `ToObject` passing the `this` value as the argument.
4. ReturnIfAbrupt(O).
5. Let $desc$ be the result of calling the [[GetOwnProperty]] internal method of O passing P as the argument.
6. If $desc$ is `undefined`, return `false`.
7. Return `true`.

NOTE 1 Unlike [[HasProperty]] (8.12.6), this method does not consider objects in the prototype chain.

NOTE 2 The ordering of steps 1 and 2 is chosen to ensure that any exception that would have been thrown by step 1 in previous editions of this specification will continue to be thrown even if the `this` value is `undefined` or `null`.

15.2.4.6 Object.prototype.isPrototypeOf(V)

When the `isPrototypeOf` method is called with argument V , the following steps are taken:

- Deleted:** result of calling `ToObject` passing the `this` value
- Deleted:** as the argument
- Deleted:** <#>Let `toString` be the result of calling the [[Get]] internal method of O passing "`toString`" as the argument.
<#>If `IsCallable(toString)` is false, throw a `TypeError` exception.
- Deleted:** calling
- Deleted:** the
- Deleted:** [[Call]] internal method of O
- Deleted:** `toString` passing
- Deleted:** as the `this` value
- Deleted:** no
- Deleted:** <#>If O is the result of calling the `Object` constructor with a host object (15.2.2.1), then
<#>Return either O or another value such as the host object originally passed to the constructor. The specific result that is returned is implementation-defined.

1. If V is not an object, return **false**.
2. Let O be the result of calling `ToObject` passing the `this` value as the argument.
- 3. ReturnIfAbrupt(O)**.
4. Repeat
 - a. Let V be the value of the `[[Prototype]]` internal property of V .
 - b. if V is **null**, return **false**
 - c. If O and V refer to the same object, return **true**.

NOTE The ordering of steps 1 and 2 is chosen to preserve the behaviour specified by previous editions of this specification for the case where V is not an object and the `this` value is `undefined` or `null`.

15.2.4.7 `Object.prototype.propertyIsEnumerable(V)`

When the `propertyIsEnumerable` method is called with argument V , the following steps are taken:

1. Let P be `ToString(V)`.
- 2. ReturnIfAbrupt(P)**.
3. Let O be the result of calling `ToObject` passing the `this` value as the argument.
- 4. ReturnIfAbrupt(O)**.
5. Let $desc$ be the result of calling the `[[GetOwnProperty]]` internal method of O passing P as the argument.
6. If $desc$ is **undefined**, return **false**.
7. Return the value of $desc.[[Enumerable]]$.

NOTE 1 This method does not consider objects in the prototype chain.

NOTE 2 The ordering of steps 1 and 2 is chosen to ensure that any exception that would have been thrown by step 1 in previous editions of this specification will continue to be thrown even if the `this` value is `undefined` or `null`.

15.2.5 Properties of Object Instances

Object instances have no special properties beyond those inherited from the `Object` prototype object.

15.3 Function Objects

15.3.1 The Function Constructor Called as a Function

When `Function` is called as a function rather than as a constructor, it creates and initialises a new `Function` object. Thus the function call `Function(...)` is equivalent to the object creation expression `new Function(...)` with the same arguments.

15.3.1.1 `Function(p1, p2, ..., pn, body)`

When the `Function` function is called with some arguments $p1, p2, \dots, pn, body$ (where n might be 0, that is, there are no “ p ” arguments, and where $body$ might also not be provided), the following steps are taken:

1. Create and return a new `Function` object as if the standard built-in constructor `Function` was used in a `new` expression with the same arguments (15.3.2.1).

15.3.2 The Function Constructor

When `Function` is called as part of a `new` expression, it is a constructor: it initialises the newly created object.

15.3.2.1 `new Function(p1, p2, ..., pn, body)`

The last argument specifies the body (executable code) of a function; any preceding arguments specify formal parameters.

When the `Function` constructor is called with some arguments $p1, p2, \dots, pn, body$ (where n might be 0, that is, there are no “ p ” arguments, and where $body$ might also not be provided), the following steps are taken:

1. Let `argCount` be the total number of arguments passed to this function invocation.
2. Let `P` be the empty String.
3. If `argCount = 0`, let `bodyText` be the empty String.
4. Else if `argCount = 1`, let `bodyText` be that argument.
5. Else, `argCount > 1`
 - a. Let `firstArg` be the first argument.
 - b. Let `P` be `ToString(firstArg)`.
 - c. `ReturnIfAbrupt(P)`.
 - d. Let `k` be 2.
 - e. Repeat, while `k < argCount`
 - i. Let `nextArg` be the `k`'th argument.
 - ii. `Let nextArgString be ToString(nextArg)`.
 - iii. `ReturnIfAbrupt(nextArgString)`.
 - iv. Let `P` be the result of concatenating the previous value of `P`, the String `,`, and `nextArgString`.
 - v. Increase `k` by 1.
 - f. Let `bodyText` be the `k`'th argument.
6. Let `bodyText` be `ToString(bodyText)`.
7. `ReturnIfAbrupt(bodyText)`.
8. Let `parameters` be the result of parsing `P`, interpreted as UTF-16 encoded Unicode text as described in 8.4, using `FormalParameterList` as the goal symbol. Throw a `SyntaxError` exception if the parse fails.
9. Let `body` be the result of parsing `bodyText`, interpreted as UTF-16 encoded Unicode text as described in 8.4, using `FunctionBody` as the goal symbol. Throw a `SyntaxError` exception if the parse fails or if any static semantics errors are detected.
10. If `bodyText` is strict mode code (see 10.1.1) then let `strict` be `true`, else let `strict` be `false`.
11. Return a new Function object created as specified in 13.6 passing `parameters` as the `FormalParameterList`, and `body` as the `FunctionBody`. Pass in the Global Environment as the `Scope` parameter and `strict` as the `Strict` flag.

A `prototype` property is automatically created for every function, to provide for the possibility that the function will be used as a constructor.

NOTE It is permissible but not necessary to have one argument for each formal parameter to be specified. For example, all three of the following expressions produce the same result:

```
new Function("a", "b", "c", "return a+b+c")
new Function("a, b, c", "return a+b+c")
new Function("a,b", "c", "return a+b+c")
```

15.3.3 Properties of the Function Constructor

The Function constructor is itself a Function object and has a `[[NativeBrand]]` internal property whose value is `NativeFunction`. The value of the `[[Prototype]]` internal property of the Function constructor is the standard built-in Function prototype object (15.3.4).


The value of the `[[Extensible]]` internal property of the Function constructor is `true`.

The Function constructor has the following properties:

15.3.3.1 Function.prototype

The initial value of `Function.prototype` is the standard built-in Function prototype object (15.3.4).

This property has the attributes `{ [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }`.



15.3.3.2 Function.length

This is a data property with a value of 1. This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.3.4 Properties of the Function Prototype Object

The Function prototype object is itself a Function object and has a [[NativeBrand]] internal property whose value is NativeFunction. When invoked, it accepts any arguments and returns **undefined**.

The value of the [[Prototype]] internal property of the Function prototype object is the standard built-in Object prototype object (15.2.4). The initial value of the [[Extensible]] internal property of the Function prototype object is **true**.

The Function prototype object does not have a **valueOf** property of its own; however, it inherits the **valueOf** property from the Object prototype Object.

The **length** property of the Function prototype object is **0**.

15.3.4.1 Function.prototype.constructor

The initial value of **Function.prototype.constructor** is the built-in **Function** constructor.

15.3.4.2 Function.prototype.toString()

An implementation-dependent representation of the function is returned. This representation has the syntax of a *FunctionDeclaration*. Note in particular that the use and placement of white space, line terminators, and semicolons within the representation String is implementation-dependent.

The **toString** function is not generic; it throws a **TypeError** exception if its **this** value is not a Function object. Therefore, it cannot be transferred to other kinds of objects for use as a method.

15.3.4.3 Function.prototype.apply(thisArg, argArray)

When the **apply** method is called on an object *func* with arguments *thisArg* and *argArray*, the following steps are taken:

1. If **IsCallable(func)** is **false**, then throw a **TypeError** exception.
2. If *argArray* is **null** or **undefined**, then
 - a. Return the result of calling the [[Call]] internal method of *func*, providing *thisArg* as the **this** value and an empty list of arguments.
3. If **Type(argArray)** is not **Object**, then throw a **TypeError** exception.
4. Let *len* be the result of calling the [[Get]] internal method of *argArray* with argument "**length**".
5. Let *n* be **ToUint32(len)**.
6. [ReturnIfAbrupt\(n\)](#).
7. Let *argList* be an empty List.
8. Let *index* be 0.
9. Repeat while *index < n*
 - a. Let *indexName* be **ToString(index)**.
 - b. Let *nextArg* be the result of calling the [[Get]] internal method of *argArray* with *indexName* as the argument.
 - c. [ReturnIfAbrupt\(nextArg\)](#).
 - d. Append *nextArg* as the last element of *argList*.
 - e. Set *index* to *index + 1*.
10. Return the result of calling the [[Call]] internal method of *func*, providing *thisArg* as the **this** value and *argList* as the list of arguments.

The **length** property of the **apply** method is **2**.

Deleted: IsFunction

Deleted: (its [[Class]] is "Function") that,

Deleted: when

NOTE The `thisArg` value is passed without modification as the `this` value. This is a change from Edition 3, where a `undefined` or `null` `thisArg` is replaced with the global object and `ToObject` is applied to all other values and that result is passed as the `this` value.

15.3.4.4 Function.prototype.call (thisArg [, arg1 [, arg2, ...]])

When the `call` method is called on an object `func` with argument `thisArg` and optional arguments `arg1`, `arg2` etc, the following steps are taken:

1. If `IsCallable(func)` is `false`, then throw a `TypeError` exception.
2. Let `argList` be an empty List.
3. If this method was called with more than one argument then in left to right order starting with `arg1` append each argument as the last element of `argList`
4. Return the result of calling the `[[Call]]` internal method of `func`, providing `thisArg` as the `this` value and `argList` as the list of arguments.

The `length` property of the `call` method is 1.

NOTE The `thisArg` value is passed without modification as the `this` value. This is a change from Edition 3, where a `undefined` or `null` `thisArg` is replaced with the global object and `ToObject` is applied to all other values and that result is passed as the `this` value.

15.3.4.5 Function.prototype.bind (thisArg [, arg1 [, arg2, ...]])

The `bind` method takes one or more arguments, `thisArg` and (optionally) `arg1`, `arg2`, etc, and returns a new function object by performing the following steps:

1. Let `Target` be the `this` value.
2. If `IsCallable(Target)` is `false`, throw a `TypeError` exception.
3. Let `A` be a new (possibly empty) internal list consisting of all of the argument values provided after `thisArg` (`arg1`, `arg2` etc), in order.
4. Let `F` be a new native ECMAScript object .
5. Set all the internal methods of `F` as specified in 8.12.
6. Set the `[[Extensible]` internal property of `F` to `true`.
7. Set the `[[TargetFunction]` internal property of `F` to `Target`.
8. Set the `[[BoundThis]]` internal property of `F` to the value of `thisArg`.
9. Set the `[[BoundArgs]]` internal property of `F` to `A`.
10. Add the `[[NativeBrand]` internal property with value `NativeFunction` to `F`.
11. Set the `[[Prototype]]` internal property of `F` to the intrinsic %FunctionPrototype%.
12. Set the `[[Call]]` internal property of `F` as described in 15.3.4.5.1.
13. Set the `[[Construct]]` internal property of `F` as described in 15.3.4.5.2.
14. Set the `[[HasInstance]]` internal property of `F` as described in 15.3.4.5.3.
15. If `Target` has the `[[NativeBrand]` internal property with value `NativeFunction`, then
 - a. Let `targetLen` be the result of calling the `[[Get]]` internal method of `Target` with argument `"length"`.
 - b. ReturnIfAbrupt(`targetLen`).
 - c. Let `L` be the larger of 0 and the result of `targetLen` minus the number of elements of `A`.
16. Else let `L` be 0.
17. Call the `[[DefineOwnProperty]]` internal method of `F` with arguments `"length"`, `PropertyDescriptor` `{[[value]]: L, [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false}`, and `false`.
18. Let `thrower` be the `[[ThrowTypeError]]` function Object (13.5.3).
19. Call the `[[DefineOwnProperty]]` internal method of `F` with arguments `"caller"`, `PropertyDescriptor` `{[[Get]]: thrower, [[Set]]: thrower, [[Enumerable]]: false, [[Configurable]]: false}`, and `false`.
20. Call the `[[DefineOwnProperty]]` internal method of `F` with arguments `"arguments"`, `PropertyDescriptor` `{[[Get]]: thrower, [[Set]]: thrower, [[Enumerable]]: false, [[Configurable]]: false}`, and `false`.
21. Return `F`.

The `length` property of the `bind` method is 1.

NOTE Function objects created using `Function.prototype.bind` do not have a `prototype` property or the `[[Code]]`, `[[FormalParameters]]`, and `[[Scope]]` internal properties.

Deleted: , except for <code>[[Get]]</code> ,
Deleted: <#> Set the <code>[[Get]]</code> internal property of <code>F</code> as specified in 15.3.5.4.¶
Deleted: Set
Deleted: Class
Deleted: <code>isFunction</code>
Deleted: <code>of</code>
Deleted: <code>to</code>
Deleted: "Function"
Deleted: standard built-in Function prototype object as specified in 15.3.3.1
Deleted: the <code>[[Class]]</code> internal property of <code>F</code>
Deleted: <code>is "Function"</code>
Deleted: <code>isFunction</code>
Deleted: the <code>length</code> property of <code>Target</code>
Deleted: <code>length</code>
Deleted: <#> Set the <code>length</code> own property of <code>F</code> either 0 or <code>L</code> , whichever is larger. ¶
Deleted: <code>set</code>
Deleted: the <code>length</code> own property of <code>F</code>
Deleted: <#> Set the attributes of the <code>length</code> own property of <code>F</code> to the values specified in 15.3.5.1.¶
Deleted: <#> Set the <code>[[Extensible]]</code> internal property of <code>F</code> to <code>true</code> .¶
Deleted: 2

15.3.4.5.1 [[Call]]

When the [[Call]] internal method of a function object, *F*, which was created using the bind function is called with a **this** value and a list of arguments *ExtraArgs*, the following steps are taken:

1. Let *boundArgs* be the value of *F*'s [[BoundArgs]] internal property.
2. Let *boundThis* be the value of *F*'s [[BoundThis]] internal property.
3. Let *target* be the value of *F*'s [[TargetFunction]] internal property.
4. Let *args* be a new list containing the same values as the list *boundArgs* in the same order followed by the same values as the list *ExtraArgs* in the same order.
5. Return the result of calling the [[Call]] internal method of *target* providing *boundThis* as the **this** value and providing *args* as the arguments.

15.3.4.5.2 [[Construct]]

When the [[Construct]] internal method of a function object, *F* that was created using the bind function is called with a list of arguments *ExtraArgs*, the following steps are taken:

1. Let *target* be the value of *F*'s [[TargetFunction]] internal property.
2. If *target* has no [[Construct]] internal method, a **TypeError** exception is thrown.
3. Let *boundArgs* be the value of *F*'s [[BoundArgs]] internal property.
4. Let *args* be a new list containing the same values as the list *boundArgs* in the same order followed by the same values as the list *ExtraArgs* in the same order.
5. Return the result of calling the [[Construct]] internal method of *target* providing *args* as the arguments.

15.3.4.5.3 [[HasInstance]] (V)

When the [[HasInstance]] internal method of a function object *F*, that was created using the bind function is called with argument *V*, the following steps are taken:

1. Let *target* be the value of *F*'s [[TargetFunction]] internal property.
2. If *target* has no [[HasInstance]] internal method, a **TypeError** exception is thrown.
3. Return the result of calling the [[HasInstance]] internal method of *target* providing *V* as the argument.

15.3.5 Properties of Function Instances

In addition to the required internal properties, every function instance has a [[Call]] internal property and in most cases uses a different version of the [[Get]] internal property. Depending on how they are created (see 8.6.2, 13.6, 15, and 15.3.4.5), function instances may have a [[HasInstance]] internal property, a [[Scope]] internal property, a [[Construct]] internal property, a [[FormalParameters]] internal property, a [[Code]] internal property, a [[TargetFunction]] internal property, a [[BoundThis]] internal property, and a [[BoundArgs]] internal property.

Deleted: 2

Every function instance has a [[NativeBrand]] internal property whose value is NativeFunction.

Function instances that correspond to strict mode functions (13.6) and function instances created using the **Function.prototype.bind** method (15.3.4.5) have properties named "caller" and "arguments" that throw a **TypeError** exception. An ECMAScript implementation must not associate any implementation specific behaviour with accesses of these properties from strict mode function code.

Deleted: The value of the [[Class]] internal property is "Function".

Deleted: IsFunction

Deleted: 2

15.3.5.1 length

The value of the **length** property is an integer that indicates the "typical" number of arguments expected by the function. However, the language permits the function to be invoked with some other number of arguments. The behaviour of a function when invoked on a number of arguments other than the number specified by its **length** property depends on the function. This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.3.5.2 `prototype`

The value of the `prototype` property is used to initialise the `[[Prototype]]` internal property of a newly created object before the Function object is invoked as a constructor for that newly created object. This property has the attribute `{ [[Writable]]: true, [[Enumerable]]: false, [[Configurable]]: false }`.

NOTE Function objects created using `Function.prototype.bind` do not have a `prototype` property.

15.3.5.3 `[[HasInstance]] (V)`

Assume F is a Function object.

When the `[[HasInstance]]` internal method of F is called with value V , the following steps are taken:

1. If V is not an object, return `false`.
2. Let O be the result of calling the `[[Get]]` internal method of F with property name `"prototype"`.
3. `ReturnIfAbrupt(O)`.
4. If `Type(O)` is not Object, throw a `TypeError` exception.
5. Repeat
 - a. Let V be the value of the `[[Prototype]]` internal property of V .
 - b. If V is `null`, return `false`.
 - c. If O and V refer to the same object, return `true`.

NOTE Function objects created using `Function.prototype.bind` have a different implementation of `[[HasInstance]]` defined in 15.3.4.5.3.

15.3.5.4 `[[Get]] (P)`

Function objects use a variation of the `[[Get]]` internal method used for other native ECMAScript objects (8.12.3).

Assume F is a Function object. When the `[[Get]]` internal method of F is called with property name P , the following steps are taken:

1. Let v be the result of calling the default `[[Get]]` internal method (8.12.3) on F passing P as the property name argument.
2. If P is `"caller"` and v is a strict mode Function object, throw a `TypeError` exception.
3. Return v .

NOTE Function objects created using `Function.prototype.bind` use the default `[[Get]]` internal method.

15.4 Array Objects

Array objects give special treatment to a certain class of property names. A property name P (in the form of a String value) is an *array index* if and only if `ToString(ToUint32(P))` is equal to P and `ToUint32(P)` is not equal to $2^{32}-1$. A property whose property name is an array index is also called an *element*. Every Array object has a `length` property whose value is always a nonnegative integer less than 2^{32} . The value of the `length` property is numerically greater than the name of every property whose name is an array index; whenever a property of an Array object is created or changed, other properties are adjusted as necessary to maintain this invariant. Specifically, whenever a property is added whose name is an array index, the `length` property is changed, if necessary, to be one more than the numeric value of that array index; and whenever the `length` property is changed, every property whose name is an array index whose value is not smaller than the new length is automatically deleted. This constraint applies only to own properties of an Array object and is unaffected by `length` or array index properties that may be inherited from its prototypes.

An object, O , is said to be *sparse* if the following algorithm returns `true`:

1. Let len be the result of calling the `[[Get]]` internal method of O with argument `"length"`.
2. For each integer i in the range $0 \leq i < \text{ToUint32}(len)$

- a. Let *elem* be the result of calling the [[GetOwnProperty]] internal method of *O* with argument *ToString(i)*.
- b. If *elem* is **undefined**, return **true**.
3. Return **false**.

The abstract operation `ArrayCreate` with argument `length` (a positive integer) is used to specify the creation of new Array objects. It performs the following steps:

1. Let *A* be a newly created ECMAScript object.
2. Set the [[Prototype]] internal property of *A* to the intrinsic object %ArrayPrototype%.
3. Set *A*'s common internal methods except for [[DefineOwnProperty]] to the default definitions specified in 8.12.
4. Set *A*'s [[DefineOwnProperty]] internal method to the definition given in 15.4.5.1.
5. Set the [[NativeBrand]] internal property of *A* to the value NativeArray.
6. Set the [[Extensible]] internal property of *A* to **true**.
7. Call the default [[DefineOwnProperty]] internal method (8.12.9) on *A* with arguments "`length`", Property Descriptor {[[Value]]: *length*, [[Writable]]: **true**, [[Enumerable]]: **false**, [[Configurable]]: **false**}, and **false**.
8. Return *A*.

15.4.1 The Array Constructor Called as a Function

NOTE When `Array` is called as a function rather than as a constructor, it creates and initialises a new Array object. Thus the function call `Array(...)` is equivalent to the object creation expression `new Array(...)` with the same arguments.

Deleted: s

Deleted: of

Formatted: Note

15.4.1.1 `Array([item1[, item2[, ...]]])`

When the `Array` function is called the following steps are taken:

1. Return the result that would be obtained if this functions had been called with the same arguments, as constructor. This result is defined by 15.4.2.1 or 15.4.2.2 depending upon the actual number of arguments.

Deleted: Create and return a new Array object exactly as if the standard built-in constructor `Array` was used in a `new` expression with the same arguments (15.4.2).

15.4.2 The Array Constructor

NOTE When `Array` is called as part of a `new` expression, it is a constructor: it initialises the newly created object.

Deleted: Note

15.4.2.1 `new Array([item0[, item1[, ...]])`

This description applies if and only if the Array constructor is given no arguments or at least two arguments.

1. Let *len* be the number of arguments passed to this constructor call.
2. Let *array* be the result of the abstract operation `ArrayCreate` (15.4) with argument *len*.
3. ReturnIfAbrupt(*array*).
4. Let *k* be 0.
5. Let *items* be a zero-originated List contain the argument items in order.
6. Repeat, while *k* < *len*
 - a. Let *Pk* be `ToString(k)`.
 - b. Let *itemK* be *k*th element of *items*.
 - c. Let *defineStatus* be the result of calling the [[DefineOwnProperty]] internal method of *array* with arguments *Pk*, Property Descriptor {[[Value]]: *itemK*, [[Writable]]: **true**, [[Enumerable]]: **true**, [[Configurable]]: **true**}, and **true**.
 - d. ReturnIfAbrupt(*defineStatus*).
 - e. Increase *k* by 1.
7. Let *putStatus* be the result of calling the [[Put]] internal method of *array* with arguments "`length`", *len*, and **true**.
8. ReturnIfAbrupt(*putStatus*).
9. Return *array*.

Deleted: of

Deleted: abstraction operation

15.4.2.2 new Array (len)

This description applies if and only if the `Array` constructor is given exactly one argument.

1. If `Type(len)` is not `Number`, then
 - a. Let `array` be the result of the abstract operation `ArrayCreate` (15.4) with argument 1.
 - b. `ReturnIfAbrupt(array).`
 - c. Let `defineStatus` be the result of calling the `[[DefineOwnProperty]]` internal method of `array` with arguments `"0"`, Property Descriptor `{[[Value]]: len, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `true`.
 - d. `ReturnIfAbrupt(defineStatus).`
 - e. `Return array.`
2. Let `intLen` be `ToUint32(len)`.
3. If `intLen ≠ len`, then throw a `RangeError` exception.
4. Let `array` be the result of the abstract operation `ArrayCreate` (15.4) with argument `intLen`.
5. `Return array.`

15.4.3 Properties of the Array Constructor

The value of the `[[Prototype]]` internal property of the `Array` constructor is the Function prototype object (15.3.4).

Besides the internal properties and the `length` property (whose value is `1`), the `Array` constructor has the following properties:

15.4.3.1 `Array.prototype`

The initial value of `Array.prototype` is the `Array` prototype object (15.4.4).

This property has the attributes `{ [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }`.

15.4.3.2 `Array.isArray (arg)`

The `isArray` function takes one argument `arg`, and returns the Boolean value `true` if the argument is an object whose class internal property is `"Array"`; otherwise it returns `false`. The following steps are taken:

1. If `Type(arg)` is not `Object`, return `false`.
2. If `arg` has the `[[NativeBrand]]` internal property with value `NativeArray`, then return `true`.
3. Return `false`.

15.4.3.3 `Array.of (...items)`

When the `of` method is called with any number of arguments, the following steps are taken:

1. Let `lenValue` be the result of calling the `[[Get]]` internal method of `items` with the argument `"length"`.
2. Let `len` be `ToInteger(lenValue)`.
3. Let `C` be the `this` value.
4. If `isConstructor(C)` is `true`, then
 - a. Let `newObj` be the result of calling the `[[Construct]]` internal method of `C` with an argument list containing the single item `len`.
 - b. Let `A` be `ToObject(newObj)`.
5. Else,
 - a. Let `A` be the result of the abstract operation `ArrayCreate` (15.4) with argument `len`.
6. `ReturnIfAbrupt(A).`
7. Let `k` be `0`.
8. Repeat, while `k < len`
 - a. Let `Pk` be `ToString(k)`.
 - b. Let `kValue` be the result of calling the `[[Get]]` internal method of `items` with argument `Pk`.

Deleted: The `[[Prototype]]` internal property of the newly constructed object is set to the original `Array` prototype object, the one that is the initial value of `Array.prototype` (15.4.3.1).
 The `[[Class]]` internal property of the newly constructed object is set to `"Array"` has the `[[IsArrayNativeBrand]]` internal property with value `NativeArray`.
 The `[[Extensible]]` internal property of the newly constructed object is set to `true`.
 The `length` property of the newly constructed object is set to the number of arguments.
 The `0` property of the newly constructed object is set to `item0` (if supplied); the `1` property of the newly constructed object is set to `item1` (if supplied); and, in general, for as many arguments as there are, the `k` property of the newly constructed object is set to argument `k` where the first argument is considered to be argument number `0`. These properties all have the attributes `{ [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true }`.

Deleted: The `[[Prototype]]` internal property of the newly constructed object is set to the original `Array` prototype object, the one that is the initial value of `Array.prototype` (15.4.3.1). The newly constructed object has the `[[IsArrayNativeBrand]]` internal property with value `NativeArray`. The `[[Class]]` internal property of the newly constructed object is set to `"Array"`. The `[[Extensible]]` internal property of the newly constructed object is set to `true`. If the argument `len` is a `Number` and `ToUint32(len)` is equal to `len`, then the `length` property of the newly constructed object is set to `ToUint32(len)`. If the argument `len` is a `Number` and `ToUint32(len)` is not equal to `len`, a `RangeError` exception is thrown.
 If the argument `len` is not a `Number`, then the `length` property of the newly constructed object is set to `1` and the `0` property of the newly constructed object is set to `len` with attributes `{ [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true }`.

Deleted: of

Deleted: abstraction operation

Deleted: of

Deleted: abstraction operation

Deleted: the value of the `[[Class]]` internal property of

Deleted: is `"Array"`

Deleted: isArray

Comment [AWB7115]: It would be nice to have a more explicit way to create a collection with a pre-specified number of elements.

Deleted: abstraction operation

- c. Let `defineStatus` be the result of calling the `[[DefineOwnProperty]]` internal method of `A` with arguments `Pk`, Property Descriptor `{[[Value]]: kValue.[[value]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `true`.
- d. `ReturnIfAbrupt(defineStatus)`.
- e. Increase `k` by 1.
9. Let `putStatus` be the result of calling the `[[Put]]` internal method of `A` with arguments `"length"`, `len`, and `true`.
10. `ReturnIfAbrupt(putStatus)`.
11. Return `A`.

The `length` property of the `of` method is `0`.

NOTE 1 The `items` argument is assumed to be a well-formed rest argument value.

NOTE 2 The `of` function is an intentionally generic factory method; it does not require that its `this` value be the `Array` constructor. Therefore it can be transferred to or inherited by other constructors that may be called with a single numeric argument.

15.4.3.4 Array.from (arrayLike)

When the `from` method is called with argument `arrayLike`, the following steps are taken:

1. Let `items` be `ToObject(arrayLike)`.
2. `ReturnIfAbrupt(items)`.
3. Let `lenValue` be the result of calling the `[[Get]]` internal method of `items` with the argument `"length"`.
4. Let `len` be `ToInteger(lenValue)`.
5. `ReturnIfAbrupt(len)`.
6. Let `C` be the `this` value.
7. If `isConstructor(C)` is `true`, then
 - a. Let `newObj` be the result of calling the `[[Construct]]` internal method of `C` with an argument list containing the single item `len`.
 - b. Let `A` be `ToObject(newObj)`.
8. Else,
 - a. Let `A` be the result of the abstract operation `ArrayCreate` (15.4) with argument `len`.
9. `ReturnIfAbrupt(A)`.
10. Let `k` be `0`.
11. Repeat, while `k < len`
 - a. Let `Pk` be `ToString(k)`.
 - b. Let `kPresent` be the result of calling the `[[HasProperty]]` internal method of `items` with argument `Pk`.
 - c. If `kPresent` is `true`, then
 - i. Let `kValue` be the result of calling the `[[Get]]` internal method of `items` with argument `Pk`.
 - ii. `ReturnIfAbrupt(kValue)`.
 - iii. Let `defineStatus` be the result of calling the `[[DefineOwnProperty]]` internal method of `A` with arguments `Pk`, Property Descriptor `{[[Value]]: kValue.[[value]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `true`.
 - iv. `ReturnIfAbrupt(defineStatus)`.
 - d. Increase `k` by 1.
12. Let `putStatus` be the result of calling the `[[Put]]` internal method of `A` with arguments `"length"`, `len`, and `true`.
13. `ReturnIfAbrupt(putStatus)`.
14. Return `A`.

NOTE The `from` function is an intentionally generic factory method; it does not require that its `this` value be the `Array` constructor. Therefore it can be transferred to or inherited by any other constructors that may be called with a single numeric argument.

15.4.4 Properties of the Array Prototype Object

The value of the `[[Prototype]]` internal property of the `Array` prototype object is the standard built-in `Object` prototype object (15.2.4).

Deleted: 3

Deleted: any number of

Deleted: s

Comment [AWB7116]: It would be nice to have a more explicit way to create a collection with a pre-specified number of elements.

Deleted: abstraction operation

The Array prototype object is itself an array; it has an `[[NativeBrand]]` internal property with value `NativeArray`, and it has a `length` property (whose initial value is `+0`) and the special `[[DefineOwnProperty]]` internal method described in 15.4.5.1.

Deleted: its `[[Class]]` is "Array"

Deleted: isArray

In following descriptions of functions that are properties of the Array prototype object, the phrase "this object" refers to the object that is the `this` value for the invocation of the function. It is permitted for the `this` to be an object which does not have an `[[NativeBrand]]` internal property with value `NativeArray`.

NOTE The Array prototype object does not have a `valueOf` property of its own; however, it inherits the `valueOf` property from the standard built-in Object prototype Object.

Deleted: for

Deleted: the value of the `[[Class]]` internal property is not "Array"

Deleted: isArray

15.4.4.1 Array.prototype.constructor

The initial value of `Array.prototype.constructor` is the standard built-in `Array` constructor.

15.4.4.2 Array.prototype.toString ()

When the `toString` method is called, the following steps are taken:

6. Let `array` be the result of calling `ToObject` on the `this` value.
7. `ReturnIfAbrupt(array)`
8. Let `func` be the result of calling the `[[Get]]` internal method of `array` with argument `"join"`.
9. `ReturnIfAbrupt(func)`
10. If `IsCallable(func)` is `false`, then let `func` be the standard built-in method `Object.prototype.toString` (15.2.4.2).
11. Return the result of calling the `[[Call]]` internal method of `func` providing `array` as the `this` value and an empty arguments list.

Deleted: If `array` is an abrupt completion, return `array`.

Deleted: If `func` is an abrupt completion, return `func`.

NOTE The `toString` function is intentionally generic; it does not require that its `this` value be an `Array` object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `toString` function can be applied successfully to an exotic object that is not an `Array` is implementation-dependent.

Deleted: host

15.4.4.3 Array.prototype.toLocaleString ()

The elements of the array are converted to Strings using their `toLocaleString` methods, and these Strings are then concatenated, separated by occurrences of a separator String that has been derived in an implementation-defined locale-specific way. The result of calling this function is intended to be analogous to the result of `toString`, except that the result of this function is intended to be locale-specific.

The result is calculated as follows:

1. Let `array` be the result of calling `ToObject` passing the `this` value as the argument.
2. `ReturnIfAbrupt(array)`
3. Let `arrayLen` be the result of calling the `[[Get]]` internal method of `array` with argument `"length"`.
4. Let `len` be `ToInt32(arrayLen)`.
5. `ReturnIfAbrupt(len)`
6. Let `separator` be the String value for the list-separator String appropriate for the host environment's current locale (this is derived in an implementation-defined way).
7. If `len` is zero, return the empty String.
8. Let `firstElement` be the result of calling the `[[Get]]` internal method of `array` with argument `"0"`.
9. `ReturnIfAbrupt(firstElement)`
10. If `firstElement` is `undefined` or `null`, then
 - a. Let `R` be the empty String.
11. Else
 - a. Let `R` be the result of calling `Invoke` with arguments `"toLocaleString"`, `firstElement`, and an empty arguments List.
 - b. Let `R` be `ToString(R)`.
 - c. ReturnIfAbrupt(R)
12. Let `k` be `1`.
13. Repeat, while `k < len`

Deleted: <#> Let `elementObj` be `ToObject(firstElement)`.
 <#> Let `func` be the result of calling the `[[Get]]` internal method of `elementObj` with argument `"toLocaleString"`.
 <#> If `IsCallable(func)` is `false`, throw a `TypeError` exception.

Comment [AWB7117]: This step was missing in ES<=5.1

Deleted: If `R` is an abrupt completion, return `R`.

Deleted: Let `R` be the result of calling the `[[Call]]` internal method of `func` providing `elementObj` as the `this` value and an empty arguments list.

- a. Let S be a String value produced by concatenating R and $separator$.
- b. Let $nextElement$ be the result of calling the [[Get]] internal method of $array$ with argument $\text{ToString}(k)$.
- c. [ReturnIfAbrupt\(nextElement\)](#)
- d. If $nextElement$ is **undefined** or **null**, then
 - i. Let R be the empty String.
- e. Else
 - i. Let R be the result of calling [Invoke](#) with arguments "toLocaleString", $nextElement$, and an empty arguments List.
 - ii. Let R be [ToString\(R\)](#).
 - iii. ReturnIfAbrupt(R)
- f. Let R be a String value produced by concatenating S and R .
- g. Increase k by 1.

14. Return R .

NOTE 1 The first parameter to this function is likely to be used in a future version of this standard; it is recommended that implementations do not use this parameter position for anything else.

NOTE 2 The `toLocaleString` function is intentionally generic; it does not require that its **this** value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `toLocaleString` function can be applied successfully to an [exotic object that is not an Array](#) is implementation-dependent.

15.4.4.4 `Array.prototype.concat ([item1 [, item2 [, ...]]])`

When the `concat` method is called with zero or more arguments $item1$, $item2$, etc., it returns an array containing the array elements of the object followed by the array elements of each argument in order.

The following steps are taken:

1. Let O be the result of calling `ToObject` passing the **this** value as the argument.
2. [ReturnIfAbrupt\(O\)](#)
3. Let A be [the result of the abstract operation `ArrayCreate` \(15.4\) with argument 0](#).
4. Let n be 0.
5. Let $items$ be an internal List whose first element is O and whose subsequent elements are, in left to right order, the arguments that were passed to this function invocation.
6. Repeat, while $items$ is not empty
 - a. Remove the first element from $items$ and let E be the value of the element.
 - b. If E has the `[NativeBrand]` internal property with value `NativeArray`, then
 - i. Let k be 0.
 - ii. Let len be the result of calling the [[Get]] internal method of E with argument "`length`".
 - iii. [ReturnIfAbrupt\(len\)](#).
 - iv. Repeat, while $k < len$
 1. Let P be `ToString(k).`
 2. Let $exists$ be the result of calling the [[HasProperty]] internal method of E with P .
 3. If $exists$ is **true**, then
 - a. Let $subElement$ be the result of calling the [[Get]] internal method of E with argument P .
 - b. Call the [[DefineOwnProperty]] internal method of A with arguments `ToString(n)`, Property Descriptor {{[[Value]]: $subElement$, [[Writable]]: **true**, [[Enumerable]]: **true**, [[Configurable]]: **true**}, and **false**.
 4. Increase n by 1.
 5. Increase k by 1.
 - c. Else, E is not an Array
 - i. Call the [[DefineOwnProperty]] internal method of A with arguments `ToString(n)`, Property Descriptor {{[[Value]]: E , [[Writable]]: **true**, [[Enumerable]]: **true**, [[Configurable]]: **true**}, and **false**.
 - ii. Increase n by 1.
7. [Let \$putStatus\$ be the result of calling the \[\[Put\]\] internal method of \$A\$ with arguments "`length`", \$n\$, and **true**.](#)
8. [ReturnIfAbrupt\(putStatus\)](#).

Deleted: <#>Let $elementObj$ be `ToObject(nextElement)`. ¶

Comment [AWB7118]: This step was missing in ES<=5.1

Deleted: If R is an abrupt completion, return R .

Deleted: <#>Let $func$ be the result of calling the [[Get]] internal method of $elementObj$ with argument "`toLocaleString`". ¶

<#>If `IsCallable(func)` is **false**, throw a `TypeError` exception.
<#>Let R be the result of calling the [[Call]] internal method $func$ providing $elementObj$ as the **this** value and an empty arguments list. ¶

Deleted: host

Formatted: Font: 9 pt

Deleted: abstraction operation

Deleted: a new array created as if by the expression `new Array()` where `Array` is the standard built-in constructor with that name

Deleted: the value of the [[Class]] internal property of

Deleted: is "`Array`"

Deleted: `isArray`

Deleted: Call

Deleted: If $putStatus$ is an abrupt completion, return $putStatus$.

9. Return *A*.

The `length` property of the `concat` method is **1**.

NOTE 1 The explicit setting of the `length` property in step 7 is necessary to ensure that its value is correct in situations where the trailing elements of the result Array are not present.

NOTE 2 The `concat` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `concat` function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

Deleted: host

15.4.4.5 Array.prototype.join (separator)

The elements of the array are converted to Strings, and these Strings are then concatenated, separated by occurrences of the *separator*. If no separator is provided, a single comma is used as the separator.

The `join` method takes one argument, *separator*, and performs the following steps:

1. Let *O* be the result of calling `ToObject` passing the `this` value as the argument.
2. `ReturnIfAbrupt(O)`
3. Let *lenVal* be the result of calling the `[[Get]]` internal method of *O* with argument `"length"`.
4. Let *len* be `ToUint32(lenVal)`.
5. `ReturnIfAbrupt(len)`
6. If *separator* is **undefined**, let *separator* be the single-character String `,`.
7. Let *sep* be `ToString(separator)`.
8. If *len* is zero, return the empty String.
9. Let *element0* be the result of calling the `[[Get]]` internal method of *O* with argument `"0"`.
10. If *element0* is **undefined** or **null**, let *R* be the empty String; otherwise, Let *R* be `ToString(element0)`.
11. `ReturnIfAbrupt(R)`
12. Let *k* be **1**.
13. Repeat, while *k* < *len*
 - a. Let *S* be the String value produced by concatenating *R* and *sep*.
 - b. Let *element* be the result of calling the `[[Get]]` internal method of *O* with argument `ToString(k)`.
 - c. If *element* is **undefined** or **null**, Let *next* be the empty String; otherwise, let *next* be `ToString(element)`.
d. `ReturnIfAbrupt(next)`
 - e. Let *R* be a String value produced by concatenating *S* and *next*.
 - f. Increase *k* by 1.
14. Return *R*.

Deleted: If *R* is an abrupt completion, return *R*.

Deleted: If *next* is an abrupt completion, return *next*.

The `length` property of the `join` method is **1**.

NOTE The `join` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore, it can be transferred to other kinds of objects for use as a method. Whether the `join` function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

Deleted: host

15.4.4.6 Array.prototype.pop ()

The last element of the array is removed from the array and returned.

1. Let *O* be the result of calling `ToObject` passing the `this` value as the argument.
2. `ReturnIfAbrupt(O)`
3. Let *lenVal* be the result of calling the `[[Get]]` internal method of *O* with argument `"length"`.
4. Let *len* be `ToUint32(lenVal)`.
5. `ReturnIfAbrupt(len)`
6. If *len* is zero,
 - a. Let *putStatus* be the result of calling the `[[Put]]` internal method of *O* with arguments `"length"`, **0**, and **true**.
b. `ReturnIfAbrupt(putStatus)`

Deleted: Call

Deleted: If *putStatus* is an abrupt completion, return *putStatus*.

- c. Return ***undefined***.
7. Else, *len* > 0
- Let *newLen* be *len*-1.
 - Let *idx* be *ToString(newLen)*.
 - Let *element* be the result of calling the [[Get]] internal method of *O* with argument *idx*.
 - ReturnIfAbrupt(element).
 - Let *deleteStatus* be the result of calling the [[Delete]] internal method of *O* with arguments *idx* and true.
 - f. ReturnIfAbrupt(deleteStatus).
 - Let *putStatus* be the result of calling the [[Put]] internal method of *O* with arguments "length", *newLen*, and true.
 - h. ReturnIfAbrupt(putStatus).
 - Return *element*.

NOTE The **pop** function is intentionally generic; it does not require that its **this** value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the **pop** function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

15.4.4.7 Array.prototype.push ([*item1* [, *item2* [, ...]]])

The arguments are appended to the end of the array, in the order in which they appear. The new length of the array is returned as the result of the call.

When the **push** method is called with zero or more arguments *item1*, *item2*, etc., the following steps are taken:

- Let *O* be the result of calling **ToObject** passing the **this** value as the argument.
- ReturnIfAbrupt(*O*).
- Let *lenVal* be the result of calling the [[Get]] internal method of *O* with argument "length".
- Let *n* be **ToInt32**(*lenVal*).
- ReturnIfAbrupt(*n*).
- Let *items* be an internal List whose elements are, in left to right order, the arguments that were passed to this function invocation.
- Repeat, while *items* is not empty
 - Remove the first element from *items* and let *E* be the value of the element.
 - Let *putStatus* be the result of calling the [[Put]] internal method of *O* with arguments *ToString(n)*, *E*, and true.
 - c. ReturnIfAbrupt(putStatus).
 - Increase *n* by 1.
- Let *putStatus* be the result of calling the [[Put]] internal method of *O* with arguments "length", *n*, and true.
- ReturnIfAbrupt(putStatus).
- Return *n*.

The **length** property of the **push** method is 1.

NOTE The **push** function is intentionally generic; it does not require that its **this** value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the **push** function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

15.4.4.8 Array.prototype.reverse ()

The elements of the array are rearranged so as to reverse their order. The object is returned as the result of the call.

- Let *O* be the result of calling **ToObject** passing the **this** value as the argument.
- ReturnIfAbrupt(*O*).
- Let *lenVal* be the result of calling the [[Get]] internal method of *O* with argument "length".
- Let *len* be **ToInt32**(*lenVal*).
- ReturnIfAbrupt(*len*).

- Deleted:** *idx*
- Deleted:** *ToString*
- Deleted:**)
- Deleted:** If *element* is an abrupt completion, return *element*.
- Deleted:** Call
- Deleted:** If *deleteStatus* is an abrupt completion, return *deleteStatus*.
- Deleted:** Call
- Deleted:** *idx*
- Deleted:** If *putStatus* is an abrupt completion, return *putStatus*.
- Deleted:** host

6. Let *middle* be $\text{floor}(len/2)$.
7. Let *lower* be **0**.
8. Repeat, while *lower* \neq *middle*
 - a. Let *upper* be $len - lower - 1$.
 - b. Let *upperP* be `ToString(upper)`.
 - c. Let *lowerP* be `ToString(lower)`.
 - d. Let *lowerValue* be the result of calling the `[[Get]]` internal method of *O* with argument *lowerP*.
 - e. `ReturnIfAbrupt(lowerValue)`
 - f. Let *upperValue* be the result of calling the `[[Get]]` internal method of *O* with argument *upperP*.
 - g. `ReturnIfAbrupt(upperValue)`
 - h. Let *lowerExists* be the result of calling the `[[HasProperty]]` internal method of *O* with argument *lowerP*.
 - i. Let *upperExists* be the result of calling the `[[HasProperty]]` internal method of *O* with argument *upperP*.
 - j. If *lowerExists* is **true** and *upperExists* is **true**, then
 - i. `Let putStatus be the result of calling the [[Put]] internal method of O with arguments lowerP, upperValue, and true .`
 - ii. `ReturnIfAbrupt(putStatus)`
 - iii. `Let putStatus be the result of calling the [[Put]] internal method of O with arguments upperP, lowerValue, and true .`
 - iv. `ReturnIfAbrupt(putStatus)`
 - k. Else if *lowerExists* is **false** and *upperExists* is **true**, then
 - i. `Let putStatus be the result of calling the [[Put]] internal method of O with arguments lowerP, upperValue, and true .`
 - ii. `ReturnIfAbrupt(putStatus)`
 - iii. `Let deleteStatus be the result of calling the [[Delete]] internal method of O, with arguments upperP and true.`
 - iv. `ReturnIfAbrupt(deleteStatus)`
 - l. Else if *lowerExists* is **true** and *upperExists* is **false**, then
 - i. `Let deleteStatus be the result of calling the [[Delete]] internal method of O, with arguments lowerP and true .`
 - ii. `ReturnIfAbrupt(deleteStatus)`
 - iii. `Let putStatus be the result of calling the [[Put]] internal method of O with arguments upperP, lowerValue, and true .`
 - iv. `ReturnIfAbrupt(putStatus)`
 - m. Else, both *lowerExists* and *upperExists* are **false**
 - i. No action is required.
 - n. Increase *lower* by 1.
9. Return *O*.

NOTE The `reverse` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore, it can be transferred to other kinds of objects for use as a method. Whether the `reverse` function can be applied successfully to an [exotic object that is not an Array](#) is implementation-dependent.

Deleted: If *lowerValue* is an abrupt completion, return *lowerValue*

Deleted: If *upperValue* is an abrupt completion, return *upperValue*

Deleted: Call

Deleted: If *putStatus* is an abrupt completion, return *putStatus*

Deleted: Call

Deleted: If *putStatus* is an abrupt completion, return *putStatus*

Deleted: Call

Deleted: If *putStatus* is an abrupt completion, return *putStatus*

Deleted: Call

Deleted: If *putStatus* is an abrupt completion, return *putStatus*

Deleted: Call

Deleted: If *putStatus* is an abrupt completion, return *putStatus*

Deleted: Call

Deleted: If *putStatus* is an abrupt completion, return *putStatus*

Deleted: Call

Deleted: If *putStatus* is an abrupt completion, return *putStatus*

Deleted: Call

Deleted: host

15.4.4.9 `Array.prototype.shift()`

The first element of the array is removed from the array and returned.

1. Let *O* be the result of calling `ToObject` passing the `this` value as the argument.
2. `ReturnIfAbrupt(O)`
3. Let *lenVal* be the result of calling the `[[Get]]` internal method of *O* with argument `"length"`.
4. Let *len* be `ToUint32(lenVal)`.
5. `ReturnIfAbrupt(len)`
6. If *len* is zero, then
 - a. `Let putStatus be the result of calling the [[Put]] internal method of O with arguments "length", 0, and true .`
 - b. `ReturnIfAbrupt(putStatus)`
 - c. Return `undefined`.
7. Let *first* be the result of calling the `[[Get]]` internal method of *O* with argument `"0"`.
8. `ReturnIfAbrupt(first)`

Deleted: Call

Deleted: If *putStatus* is an abrupt completion, return *putStatus*

Deleted: If *first* is an abrupt completion, return *first*

9. Let k be 1.
10. Repeat, while $k < len$
 - a. Let $from$ be $\text{ToString}(k)$.
 - b. Let to be $\text{ToString}(k-1)$.
 - c. Let $fromPresent$ be the result of calling the $[[\text{HasProperty}]]$ internal method of O with argument $from$.
 - d. If $fromPresent$ is **true**, then
 - i. Let $fromVal$ be the result of calling the $[[\text{Get}]]$ internal method of O with argument $from$.
 - ii. [ReturnIfAbrupt\(fromVal\)](#)
 - iii. [Let putStatus be the result of calling the \[\[Put\]\] internal method of O with arguments to, fromVal, and true.](#)
 - iv. [ReturnIfAbrupt\(putStatus\)](#)
 - e. Else, $fromPresent$ is **false**
 - i. [Let deleteStatus be the result of calling the \[\[Delete\]\] internal method of O with arguments to and true.](#)
 - ii. [ReturnIfAbrupt\(deleteStatus\)](#)
 - f. Increase k by 1.
11. [Let deleteStatus be the result of calling the \[\[Delete\]\] internal method of O with arguments \$\text{ToString}\(len-1\)\$ and true.](#)
12. [ReturnIfAbrupt\(deleteStatus\)](#)
13. [Let putStatus be the result of calling the \[\[Put\]\] internal method of O with arguments "**length**", \$\(len-1\)\$, and true.](#)
14. [ReturnIfAbrupt\(putStatus\)](#)
15. Return $first$.

NOTE The **shift** function is intentionally generic; it does not require that its **this** value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the **shift** function can be applied successfully to an [exotic object that is not an Array](#) is implementation-dependent.

15.4.4.10 Array.prototype.slice (start, end)

The **slice** method takes two arguments, $start$ and end , and returns an array containing the elements of the array from element $start$ up to, but not including, element end (or through the end of the array if end is **undefined**). If $start$ is negative, it is treated as $length+start$ where $length$ is the length of the array. If end is negative, it is treated as $length+end$ where $length$ is the length of the array. The following steps are taken:

1. Let O be the result of calling **ToObject** passing the **this** value as the argument.
2. [ReturnIfAbrupt\(O\)](#)
3. Let A be [the result of the abstract operation **ArrayCreate** \(15.4\) with argument 0](#).
4. Let $lenVal$ be the result of calling the $[[\text{Get}]]$ internal method of O with argument "**length**".
5. Let len be $\text{ToInt32}(lenVal)$.
6. [ReturnIfAbrupt\(len\)](#).
7. Let $relativeStart$ be $\text{ToInteger}(start)$.
8. [ReturnIfAbrupt\(relativeStart\)](#).
9. If $relativeStart$ is negative, let k be $\max((len + relativeStart), 0)$; else let k be $\min(relativeStart, len)$.
10. If end is **undefined**, let $relativeEnd$ be len ; else let $relativeEnd$ be $\text{ToInteger}(end)$.
11. [ReturnIfAbrupt\(relativeEnd\)](#).
12. If $relativeEnd$ is negative, let $final$ be $\max((len + relativeEnd), 0)$; else let $final$ be $\min(relativeEnd, len)$.
13. Let n be 0.
14. Repeat, while $k < final$
 - a. Let P_k be $\text{ToString}(k)$.
 - b. Let $kPresent$ be the result of calling the $[[\text{HasProperty}]]$ internal method of O with argument P_k .
 - c. If $kPresent$ is **true**, then
 - i. Let $kValue$ be the result of calling the $[[\text{Get}]]$ internal method of O with argument P_k .
 - ii. [ReturnIfAbrupt\(kValue\)](#)
 - iii. Call the $[[\text{DefineOwnProperty}]]$ internal method of A with arguments $\text{ToString}(n)$, Property Descriptor $\{[[\text{Value}]]: kValue, [[\text{Writable}]]: \text{true}, [[\text{Enumerable}]]: \text{true}, [[\text{Configurable}]]: \text{true}\}$, and **false**.
 - d. Increase k by 1.
 - e. Increase n by 1.

- Deleted:** If $fromVal$ is an abrupt completion, return $fromVal$
- Deleted:** Call
- Deleted:** If $putStatus$ is an abrupt completion, return $putStatus$
- Deleted:** Call
- Deleted:** If $deleteStatus$ is an abrupt completion, return $deleteStatus$
- Deleted:** Call
- Deleted:** If $deleteStatus$ is an abrupt completion, return $deleteStatus$
- Deleted:** Call
- Deleted:** If $putStatus$ is an abrupt completion, return $putStatus$
- Deleted:** Call
- Deleted:** If $putStatus$ is an abrupt completion, return $putStatus$

Deleted: host

- Deleted:** abstraction operation
- Deleted:** a new array created as if by the expression **new Array()** where **Array** is the standard built-in constructor with that name
- Deleted:** If $relativeStart$ is an abrupt completion, return $relativeStart$
- Deleted:** If $relativeEnd$ is an abrupt completion, return $relativeEnd$
- Deleted:** If $kValue$ is an abrupt completion, return $kValue$

15. Let `putStatus` be the result of calling the `[[Put]]` internal method of `A` with arguments `"length"`, `final`, and `true`.

16. `ReturnIfAbrupt(putStatus)`.

17. Return `A`.

Comment [AWB9119]: Fix for ES5 bug
https://bugs.ecmascript.org/show_bug.cgi?id=17

The `length` property of the `slice` method is **2**.

NOTE 1 The explicit setting of the `length` property of the result Array in step 15 is necessary to ensure that its value is correct in situations where the trailing elements of the result Array are not present.

NOTE 2 The `slice` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `slice` function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

Deleted: host

15.4.4.11 Array.prototype.sort (comparefn)

The elements of this array are sorted. The sort is not necessarily stable (that is, elements that compare equal do not necessarily remain in their original order). If `comparefn` is not `undefined`, it should be a function that accepts two arguments `x` and `y` and returns a negative value if `x < y`, zero if `x = y`, or a positive value if `x > y`.

Let `obj` be the result of calling `ToObject` passing the `this` value as the argument.

Let `len` be the result of applying `Uint32` to the result of calling the `[[Get]]` internal method of `obj` with argument `"length"`.

Comment [AWB7120]: TODO: take completion values into account.

If `comparefn` is not `undefined` and is not a consistent comparison function for the elements of this array (see below), the behaviour of `sort` is implementation-defined.

Let `proto` be the value of the `[[Prototype]]` internal property of `obj`. If `proto` is not `null` and there exists an integer `j` such that all of the conditions below are satisfied then the behaviour of `sort` is implementation-defined:

- `obj` is sparse (15.4)
- $0 \leq j < len$
- The result of calling the `[[HasProperty]]` internal method of `proto` with argument `ToString(j)` is `true`.

The behaviour of `sort` is also implementation defined if `obj` is sparse and any of the following conditions are true:

- The `[[Extensible]]` internal property of `obj` is `false`.
- Any array index property of `obj` whose name is a nonnegative integer less than `len` is a data property whose `[[Configurable]]` attribute is `false`.

The behaviour of `sort` is also implementation defined if any array index property of `obj` whose name is a nonnegative integer less than `len` is an accessor property or is a data property whose `[[Writable]]` attribute is `false`.

Otherwise, the following steps are taken.

1. Perform an implementation-dependent sequence of calls to the `[[Get]]`, `[[Put]]`, and `[[Delete]]` internal methods of `obj` and to `SortCompare` (described below), where the first argument for each call to `[[Get]]`, `[[Put]]`, or `[[Delete]]` is a nonnegative integer less than `len` and where the arguments for calls to `SortCompare` are results of previous calls to the `[[Get]]` internal method. The throw argument to the `[[Put]]` and `[[Delete]]` internal methods will be the value `true`. If `obj` is not sparse then `[[Delete]]` must not be called. **If an abrupt completion is returned from any of these operations, it is immediately returned as the value of this function.**
2. Return `obj`.

The returned object must have the following two properties.

- There must be some mathematical permutation π of the nonnegative integers less than len , such that for every nonnegative integer j less than len , if property $old[j]$ existed, then $new[\pi(j)]$ is exactly the same value as $old[j]$. But if property $old[j]$ did not exist, then $new[\pi(j)]$ does not exist.
- Then for all nonnegative integers j and k , each less than len , if $SortCompare(j,k) < 0$ (see *SortCompare* below), then $\pi(j) < \pi(k)$.

Here the notation $old[j]$ is used to refer to the hypothetical result of calling the **[[Get]]** internal method of obj with argument j before this function is executed, and the notation $new[j]$ to refer to the hypothetical result of calling the **[[Get]]** internal method of obj with argument j after this function has been executed.

A function $comparefn$ is a consistent comparison function for a set of values S if all of the requirements below are met for all values a , b , and c (possibly the same value) in the set S : The notation $a <_{CF} b$ means $comparefn(a,b) < 0$; $a =_{CF} b$ means $comparefn(a,b) = 0$ (of either sign); and $a >_{CF} b$ means $comparefn(a,b) > 0$.

- Calling $comparefn(a,b)$ always returns the same value v when given a specific pair of values a and b as its two arguments. Furthermore, $Type(v)$ is Number, and v is not NaN. Note that this implies that exactly one of $a <_{CF} b$, $a =_{CF} b$, and $a >_{CF} b$ will be true for a given pair of a and b .
- Calling $comparefn(a,b)$ does not modify the **this** object.
- $a =_{CF} a$ (reflexivity)
- If $a =_{CF} b$, then $b =_{CF} a$ (symmetry)
- If $a =_{CF} b$ and $b =_{CF} c$, then $a =_{CF} c$ (transitivity of $=_{CF}$)
- If $a <_{CF} b$ and $b <_{CF} c$, then $a <_{CF} c$ (transitivity of $<_{CF}$)
- If $a >_{CF} b$ and $b >_{CF} c$, then $a >_{CF} c$ (transitivity of $>_{CF}$)

NOTE The above conditions are necessary and sufficient to ensure that $comparefn$ divides the set S into equivalence classes and that these equivalence classes are totally ordered.

When the *SortCompare* abstract operation is called with two arguments j and k , the following steps are taken:

1. Let $jString$ be $ToString(j)$.
2. Let $kString$ be $ToString(k)$.
3. Let $hasj$ be the result of calling the **[[HasProperty]]** internal method of obj with argument $jString$.
4. Let $hask$ be the result of calling the **[[HasProperty]]** internal method of obj with argument $kString$.
5. If $hasj$ and $hask$ are both **false**, then return **+0**.
6. If $hasj$ is **false**, then return 1.
7. If $hask$ is **false**, then return -1.
8. Let x be the result of calling the **[[Get]]** internal method of obj with argument $jString$.
9. [ReturnIfAbrupt\(x\)](#).
10. Let y be the result of calling the **[[Get]]** internal method of obj with argument $kString$.
11. [ReturnIfAbrupt\(y\)](#).
12. If x and y are both **undefined**, return **+0**.
13. If x is **undefined**, return 1.
14. If y is **undefined**, return -1.
15. If the argument $comparefn$ is not **undefined**, then
 - a. If **IsCallable(comparefn)** is **false**, throw a **TypeError** exception.
 - b. Return the result of calling the **[[Call]]** internal method of $comparefn$ passing **undefined** as the **this** value and with arguments x and y .
16. Let $xString$ be $ToString(x)$.
17. [ReturnIfAbrupt\(xString\)](#).
18. Let $yString$ be $ToString(y)$.
19. [ReturnIfAbrupt\(yString\)](#).
20. If $xString < yString$, return -1.
21. If $xString > yString$, return 1.
22. Return **+0**.

NOTE 1 Because non-existent property values always compare greater than **undefined** property values, and **undefined** always compares greater than any other value, undefined property values always sort to the end of the result, followed by non-existent property values.

NOTE 2 The `sort` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore, it can be transferred to other kinds of objects for use as a method. Whether the `sort` function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

Deleted: host

15.4.4.12 Array.prototype.splice (start, deleteCount [, item1 [, item2 [, ...]]])

When the `splice` method is called with two or more arguments `start`, `deleteCount` and (optionally) `item1`, `item2`, etc., the `deleteCount` elements of the array starting at array index `start` are replaced by the arguments `item1`, `item2`, etc. An Array object containing the deleted elements (if any) is returned. The following steps are taken:

1. Let `O` be the result of calling `ToObject` passing the `this` value as the argument.
- 2. ReturnIfAbrupt(O).**
3. Let `A` be the result of the abstract operation `ArrayCreate` (15.4) with argument 0.
4. Let `lenVal` be the result of calling the `[[Get]]` internal method of `O` with argument `"length"`.
5. Let `len` be `ToUint32(lenVal)`.
- 6. ReturnIfAbrupt(len).**
7. Let `relativeStart` be `ToInteger(start)`.
- 8. ReturnIfAbrupt(relativeStart).**
9. If `relativeStart` is negative, let `actualStart` be `max((len + relativeStart), 0)`; else let `actualStart` be `min(relativeStart, len)`.
10. Let `actualDeleteCount` be `min(max(ToInteger(deleteCount), 0), len - actualStart)`.
11. Let `k` be 0.
12. Repeat, while `k < actualDeleteCount`
 - a. Let `from` be `ToString(actualStart + k)`.
 - b. Let `fromPresent` be the result of calling the `[[HasProperty]]` internal method of `O` with argument `from`.
 - c. If `fromPresent` is `true`, then
 - i. Let `fromValue` be the result of calling the `[[Get]]` internal method of `O` with argument `from`.
 - ii. ReturnIfAbrupt(fromValue).**
 - iii. Call the `[[DefineOwnProperty]]` internal method of `A` with arguments `ToString(k)`, `PropertyDescriptor {[[Value]]: fromValue, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `false`.
 - d. Increment `k` by 1.
- 13. Let `putStatus` be the result of calling the `[[Put]]` internal method of `A` with arguments `"length"`, `actualDeleteCount`, and `true`.**
- 14. ReturnIfAbrupt(putStatus).**
15. Let `items` be an internal List whose elements are, in left to right order, the portion of the actual argument list starting with `item1`. The list will be empty if no such items are present.
16. Let `itemCount` be the number of elements in `items`.
17. If `itemCount < actualDeleteCount`, then
 - a. Let `k` be `actualStart`.
 - b. Repeat, while `k < (len - actualDeleteCount)`
 - i. Let `from` be `ToString(k + actualDeleteCount)`.
 - ii. Let `to` be `ToString(k + itemCount)`.
 - iii. Let `fromPresent` be the result of calling the `[[HasProperty]]` internal method of `O` with argument `from`.
 - iv. If `fromPresent` is `true`, then
 1. Let `fromValue` be the result of calling the `[[Get]]` internal method of `O` with argument `from`.
 - 2. ReturnIfAbrupt(fromValue).**
 3. Let `putStatus` be the result of calling the `[[Put]]` internal method of `O` with arguments `to`, `fromValue`, and `true`.
 - 4. ReturnIfAbrupt(putStatus).**
 - v. Else, `fromPresent` is `false`
 1. Let `deleteStatus` be the result of calling the `[[Delete]]` internal method of `O` with arguments `to` and `true`.
 - 2. ReturnIfAbrupt(deleteStatus).**
 - vi. Increase `k` by 1.
 - c. Let `k` be `len`.
 - d. Repeat, while `k > (len - actualDeleteCount + itemCount)`

Deleted: abstraction operation

Deleted: a new array created as if by the expression `new Array()` where `Array` is the standard built-in constructor with that name

- i. Let *deleteStatus* be the result of calling the [[Delete]] internal method of *O* with arguments *ToString(k-1)* and **true**.
Deleted: Call
 - ii. [ReturnIfAbrupt\(deleteStatus\)](#).
 - iii. Decrease *k* by 1.
18. Else if *itemCount* > *actualDeleteCount*, then
- a. Let *k* be *(len - actualDeleteCount)*.
 - b. Repeat, while *k* > *actualStart*
 - i. Let *from* be *ToString(k + actualDeleteCount - 1)*.
 - ii. Let *to* be *ToString(k + itemCount - 1)*
 - iii. Let *fromPresent* be the result of calling the [[HasProperty]] internal method of *O* with argument *from*.
 - iv. If *fromPresent* is **true**, then
 - 1. Let *fromValue* be the result of calling the [[Get]] internal method of *O* with argument *from*.
 - [2. ReturnIfAbrupt\(fromValue\)](#).
 - 3. Let *putStatus* be the result of calling the [[Put]] internal method of *O* with arguments *to*, *fromValue*, and **true**.
 - [4. ReturnIfAbrupt\(putStatus\)](#).
 - v. Else, *fromPresent* is **false**
 - 1. Let *deleteStatus* be the result of calling the [[Delete]] internal method of *O* with argument *to* and **true**.
 - [2. ReturnIfAbrupt\(deleteStatus\)](#).
 - vi. Decrease *k* by 1.
19. Let *k* be *actualStart*.
20. Repeat, while *items* is not empty
- a. Remove the first element from *items* and let *E* be the value of that element.
 - b. Let *putStatus* be the result of calling the [[Put]] internal method of *O* with arguments *ToString(k)*, *E*, and **true**.
Deleted: Call
 - c. [ReturnIfAbrupt\(putStatus\)](#).
 - d. Increase *k* by 1.
21. Let *putStatus* be the result of calling the [[Put]] internal method of *O* with arguments "**length**", *(len - actualDeleteCount + itemCount)*, and **true**.
Deleted: Call
- [22. ReturnIfAbrupt\(putStatus\)](#).
23. Return *A*.

The **length** property of the **splice** method is **2**.

NOTE 1 The explicit setting of the **length** property of the result Array in step 13 is necessary to ensure that its value is correct in situations where its trailing elements are not present.

NOTE 2 The **splice** function is intentionally generic; it does not require that its **this** value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the **splice** function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

Deleted: host

15.4.4.13 Array.prototype.unshift ([*item1* [, *item2* [, ...]]])

The arguments are prepended to the start of the array, such that their order within the array is the same as the order in which they appear in the argument list.

When the **unshift** method is called with zero or more arguments *item1*, *item2*, etc., the following steps are taken:

1. Let *O* be the result of calling **ToObject** passing the **this** value as the argument.
- [2. ReturnIfAbrupt\(*O*\)](#).
3. Let *lenVal* be the result of calling the [[Get]] internal method of *O* with argument "**length**".
4. Let *len* be **ToInt32**(*lenVal*).
Deleted: host
- [5. ReturnIfAbrupt\(*len*\)](#).
6. Let *argCount* be the number of actual arguments.
7. Let *k* be *len*.
8. Repeat, while *k* > 0,

- a. Let *from* be `ToString(k-1)`.
 - b. Let *to* be `ToString(k+argCount-1)`.
 - c. Let *fromPresent* be the result of calling the `[[HasProperty]]` internal method of *O* with argument *from*.
 - d. If *fromPresent* is `true`, then
 - i. Let *fromValue* be the result of calling the `[[Get]]` internal method of *O* with argument *from*.
 - ii. `ReturnIfAbrupt(fromValue)`.
 - iii. `Let putStatus be the result of calling the [[Put]] internal method of O with arguments to, fromValue, and true.`
 - iv. `ReturnIfAbrupt(putStatus)`.
 - e. Else, *fromPresent* is `false`
 - i. `Let deleteStatus be the result of calling the [[Delete]] internal method of O with arguments to, and true.`
 - ii. `ReturnIfAbrupt(deleteStatus)`.
 - f. Decrease *k* by 1.
9. Let *j* be 0.
10. Let *items* be an internal List whose elements are, in left to right order, the arguments that were passed to this function invocation.
11. Repeat, while *items* is not empty
 - a. Remove the first element from *items* and let *E* be the value of that element.
 - b. `Let putStatus be the result of calling the [[Put]] internal method of O with arguments ToString(j), E, and true.`
 - c. `ReturnIfAbrupt(putStatus)`.
 - d. Increase *j* by 1.
12. `Let putStatus be the result of calling the [[Put]] internal method of O with arguments "length", len+argCount, and true.`
13. `ReturnIfAbrupt(putStatus)`.
14. Return *len+argCount*.

The `length` property of the `unshift` method is 1.

NOTE The `unshift` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `unshift` function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

Deleted: Call

Deleted: Call

Deleted: Call

Deleted: Call

Deleted: host

15.4.4.14 Array.prototype.indexOf (*searchElement* [, *fromIndex*])

`indexOf` compares *searchElement* to the elements of the array, in ascending order, using the internal Strict Equality Comparison Algorithm (11.9.1), and if found at one or more positions, returns the index of the first such position; otherwise, -1 is returned.

Deleted: 6

The optional second argument *fromIndex* defaults to 0 (i.e. the whole array is searched). If it is greater than or equal to the length of the array, -1 is returned, i.e. the array will not be searched. If it is negative, it is used as the offset from the end of the array to compute *fromIndex*. If the computed index is less than 0, the whole array will be searched.

When the `indexOf` method is called with one or two arguments, the following steps are taken:

1. Let *O* be the result of calling `ToObject` passing the `this` value as the argument.
2. `ReturnIfAbrupt(O)`.
3. Let *lenValue* be the result of calling the `[[Get]]` internal method of *O* with the argument "`length`".
4. Let *len* be `ToInt32(lenValue)`.
5. `ReturnIfAbrupt(len)`.
6. If *len* is 0, return -1.
7. If argument *fromIndex* was passed let *n* be `ToInteger(fromIndex)`; else let *n* be 0.
8. `ReturnIfAbrupt(n)`.
9. If *n* \geq *len*, return -1.
10. If *n* \geq 0, then
 - a. Let *k* be *n*.

Deleted: If *n* is an abrupt completion, return *n*.

11. Else, $n < 0$
 - a. Let k be $\text{len} - \text{abs}(n)$.
 - b. If $k \leq 0$, then let k be 0.
12. Repeat, while $k < \text{len}$
 - a. Let $k\text{Present}$ be the result of calling the `[[HasProperty]]` internal method of O with argument `ToString(k)`.
 - b. If $k\text{Present}$ is `true`, then
 - i. Let element_K be the result of calling the `[[Get]]` internal method of O with the argument `ToString(k)`.
 - ii. [ReturnIfAbrupt\(element_K\)](#)
 - iii. Let same be the result of performing the Strict Equality Comparison Algorithm $\text{searchElement} \equiv \text{element}_K$.
 - iv. If same is `true`, return k .
 - c. Increase k by 1.
13. Return -1.

The `length` property of the `indexOf` method is 1.

NOTE The `indexOf` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `indexOf` function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

15.4.4.15 Array.prototype.lastIndexOf (*searchElement* [, *fromIndex*])

`lastIndexOf` compares *searchElement* to the elements of the array in descending order using the internal Strict Equality Comparison Algorithm (11.9.1), and if found at one or more positions, returns the index of the last such position; otherwise, -1 is returned.

The optional second argument *fromIndex* defaults to the array's length minus one (i.e. the whole array is searched). If it is greater than or equal to the length of the array, the whole array will be searched. If it is negative, it is used as the offset from the end of the array to compute *fromIndex*. If the computed index is less than 0, -1 is returned.

When the `lastIndexOf` method is called with one or two arguments, the following steps are taken:

1. Let O be the result of calling `ToObject` passing the `this` value as the argument.
2. [ReturnIfAbrupt\(O\)](#).
3. Let lenValue be the result of calling the `[[Get]]` internal method of O with the argument "`length`".
4. Let len be `ToUint32(lenValue)`.
5. [ReturnIfAbrupt\(len\)](#).
6. If len is 0, return -1.
7. If argument *fromIndex* was passed let n be `ToInteger(fromIndex)`; else let n be $\text{len}-1$.
8. [ReturnIfAbrupt\(n\)](#).
9. If $n \geq 0$, then let k be $\min(n, \text{len} - 1)$.
10. Else, $n < 0$
 - a. Let k be $\text{len} - \text{abs}(n)$.
11. Repeat, while $k \geq 0$
 - a. Let $k\text{Present}$ be the result of calling the `[[HasProperty]]` internal method of O with argument `ToString(k)`.
 - b. If $k\text{Present}$ is `true`, then
 - i. Let element_K be the result of calling the `[[Get]]` internal method of O with the argument `ToString(k)`.
 - ii. [ReturnIfAbrupt\(element_K\)](#)
 - iii. Let same be the result of performing Strict Equality Comparison Algorithm $\text{searchElement} \equiv \text{element}_K$.
 - iv. If same is `true`, return k .
 - c. Decrease k by 1.
12. Return -1.

The `length` property of the `lastIndexOf` method is 1.

Deleted: is less than

Deleted: If element_K is an abrupt completion, return element_K .

Deleted: applying

Deleted: to

Deleted: and

Deleted: host

Deleted: 6

Deleted: If n is an abrupt completion, return n .

Deleted: If element_K is an abrupt completion, return element_K .

Deleted: applying

Deleted: the

Deleted: Algorithm

Deleted: to

Deleted: and

NOTE The `lastIndexOf` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `lastIndexOf` function can be applied successfully to an [exotic object that is not an Array](#) is implementation-dependent.

Deleted: host

15.4.4.16 Array.prototype.every (callbackfn [, thisArg])

`callbackfn` should be a function that accepts three arguments and returns a value that is coercible to the Boolean value `true` or `false`. `every` calls `callbackfn` once for each element present in the array, in ascending order, until it finds one where `callbackfn` returns `false`. If such an element is found, `every` immediately returns `false`. Otherwise, if `callbackfn` returned `true` for all elements, `every` will return `true`. `callbackfn` is called only for elements of the array which actually exist; it is not called for missing elements of the array.

If a `thisArg` parameter is provided, it will be used as the `this` value for each invocation of `callbackfn`. If it is not provided, `undefined` is used instead.

`callbackfn` is called with three arguments: the value of the element, the index of the element, and the object being traversed.

`every` does not directly mutate the object on which it is called but the object may be mutated by the calls to `callbackfn`.

The range of elements processed by `every` is set before the first call to `callbackfn`. Elements which are appended to the array after the call to `every` begins will not be visited by `callbackfn`. If existing elements of the array are changed, their value as passed to `callbackfn` will be the value at the time `every` visits them; elements that are deleted after the call to `every` begins and before being visited are not visited. `every` acts like the "for all" quantifier in mathematics. In particular, for an empty array, it returns `true`.

When the `every` method is called with one or two arguments, the following steps are taken:

1. Let `O` be the result of calling `ToObject` passing the `this` value as the argument.
 2. [ReturnIfAbrupt\(O\)](#).
 3. Let `lenValue` be the result of calling the `[[Get]]` internal method of `O` with the argument `"length"`.
 4. Let `len` be `ToInt32(lenValue)`.
 5. [ReturnIfAbrupt\(len\)](#).
 6. If `IsCallable(callbackfn)` is `false`, throw a `TypeError` exception.
 7. If `thisArg` was supplied, let `T` be `thisArg`; else let `T` be `undefined`.
 8. Let `k` be `0`.
 9. Repeat, while `k < len`
 - a. Let `Pk` be `ToString(k)`.
 - b. Let `kPresent` be the result of calling the `[[HasProperty]]` internal method of `O` with argument `Pk`.
 - c. If `kPresent` is `true`, then
 - i. Let `kValue` be the result of calling the `[[Get]]` internal method of `O` with argument `Pk`.
 - ii. [ReturnIfAbrupt\(kValue\)](#).
 - iii. Let `testResult` be the result of calling the `[[Call]]` internal method of `callbackfn` with `T` as the `this` value and argument list containing `kValue`, `k`, and `O`.
 - iv. [ReturnIfAbrupt\(testResult\)](#).
 - v. If `ToBoolean(testResult)` is `false`, return `false`.
 - d. Increase `k` by 1.
10. Return `true`.

The `length` property of the `every` method is `1`.

NOTE The `every` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `every` function can be applied successfully to an [exotic object that is not an Array](#) is implementation-dependent.

Deleted: If `kValue` is an abrupt completion, return `kValue`.

Deleted: If `testResult` is an abrupt completion, return `testResult`.

Deleted: host

15.4.4.17 Array.prototype.some (callbackfn [, thisArg])

`callbackfn` should be a function that accepts three arguments and returns a value that is coercible to the Boolean value `true` or `false`. `some` calls `callbackfn` once for each element present in the array, in ascending

order, until it finds one where *callbackfn* returns **true**. If such an element is found, **some** immediately returns **true**. Otherwise, **some** returns **false**. *callbackfn* is called only for elements of the array which actually exist; it is not called for missing elements of the array.

If a *thisArg* parameter is provided, it will be used as the **this** value for each invocation of *callbackfn*. If it is not provided, **undefined** is used instead.

callbackfn is called with three arguments: the value of the element, the index of the element, and the object being traversed.

some does not directly mutate the object on which it is called but the object may be mutated by the calls to *callbackfn*.

The range of elements processed by **some** is set before the first call to *callbackfn*. Elements that are appended to the array after the call to **some** begins will not be visited by *callbackfn*. If existing elements of the array are changed, their value as passed to *callbackfn* will be the value at the time that **some** visits them; elements that are deleted after the call to **some** begins and before being visited are not visited. **some** acts like the "exists" quantifier in mathematics. In particular, for an empty array, it returns **false**.

When the **some** method is called with one or two arguments, the following steps are taken:

1. Let *O* be the result of calling `ToObject` passing the **this** value as the argument.
2. **ReturnIfAbrupt(*O*)**.
3. Let *lenValue* be the result of calling the `[[Get]]` internal method of *O* with the argument "`length`".
4. Let *len* be `ToInt32(lenValue)`.
5. **ReturnIfAbrupt(*len*)**.
6. If `IsCallable(callbackfn)` is **false**, throw a **TypeError** exception.
7. If *thisArg* was supplied, let *T* be *thisArg*; else let *T* be **undefined**.
8. Let *k* be 0.
9. Repeat, while *k* < *len*
 - a. Let *Pk* be `ToString(k)`.
 - b. Let *kPresent* be the result of calling the `[[HasProperty]]` internal method of *O* with argument *Pk*.
 - c. If *kPresent* is **true**, then
 - i. Let *kValue* be the result of calling the `[[Get]]` internal method of *O* with argument *Pk*.
 - ii. **ReturnIfAbrupt(*kValue*)**.
 - iii. Let *testResult* be the result of calling the `[[Call]]` internal method of *callbackfn* with *T* as the **this** value and argument list containing *kValue*, *k*, and *O*.
 - iv. **ReturnIfAbrupt(*testResult*)**.
 - v. If `ToBoolean(testResult)` is **true**, return **true**.
 - d. Increase *k* by 1.
10. Return **false**.

The **length** property of the **some** method is **1**.

NOTE The **some** function is intentionally generic; it does not require that its **this** value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the **some** function can be applied successfully to an [exotic object](#) [that is not an Array](#) is implementation-dependent.

Deleted: If *kValue* is an abrupt completion, return *kValue*.

Deleted: If *testResult* is an abrupt completion, return *testResult*.

Deleted: host

15.4.4.18 `Array.prototype.forEach (callbackfn [, thisArg])`

callbackfn should be a function that accepts three arguments. `forEach` calls *callbackfn* once for each element present in the array, in ascending order. *callbackfn* is called only for elements of the array which actually exist; it is not called for missing elements of the array.

If a *thisArg* parameter is provided, it will be used as the **this** value for each invocation of *callbackfn*. If it is not provided, **undefined** is used instead.

callbackfn is called with three arguments: the value of the element, the index of the element, and the object being traversed.

`forEach` does not directly mutate the object on which it is called but the object may be mutated by the calls to `callbackfn`.

The range of elements processed by `forEach` is set before the first call to `callbackfn`. Elements which are appended to the array after the call to `forEach` begins will not be visited by `callbackfn`. If existing elements of the array are changed, their value as passed to `callbackfn` will be the value at the time `forEach` visits them; elements that are deleted after the call to `forEach` begins and before being visited are not visited.

When the `forEach` method is called with one or two arguments, the following steps are taken:

1. Let O be the result of calling `ToObject` passing the `this` value as the argument.
2. `ReturnIfAbrupt(O)`
3. Let $lenValue$ be the result of calling the `[[Get]]` internal method of O with the argument `"length"`.
4. Let len be `ToUint32(lenValue)`.
5. `ReturnIfAbrupt(len)`
6. If `IsCallable(callbackfn)` is `false`, throw a `TypeError` exception.
7. If `thisArg` was supplied, let T be `thisArg`; else let T be `undefined`.
8. Let k be 0.
9. Repeat, while $k < len$
 - a. Let P_k be `ToString(k)`.
 - b. Let $kPresent$ be the result of calling the `[[HasProperty]]` internal method of O with argument P_k .
 - c. If $kPresent$ is `true`, then
 - i. Let $kValue$ be the result of calling the `[[Get]]` internal method of O with argument P_k .
 - ii. `ReturnIfAbrupt(kValue)`
 - iii. Let `funcResult` be the result of calling the `[[Call]]` internal method of `callbackfn` with T as the `this` value and argument list containing $kValue$, k , and O .
 - iv. `ReturnIfAbrupt(funcResult)`
 - d. Increase k by 1.
10. Return `undefined`.

The `length` property of the `forEach` method is 1.

NOTE The `forEach` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `forEach` function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

Deleted: If $kValue$ is an abrupt completion, return $kValue$.
Deleted: Call
Deleted: If $funcResult$ is an abrupt completion, return $funcResult$.

Deleted: host

15.4.4.19 `Array.prototype.map (callbackfn [, thisArg])`

`callbackfn` should be a function that accepts three arguments. `map` calls `callbackfn` once for each element in the array, in ascending order, and constructs a new Array from the results. `callbackfn` is called only for elements of the array which actually exist; it is not called for missing elements of the array.

If a `thisArg` parameter is provided, it will be used as the `this` value for each invocation of `callbackfn`. If it is not provided, `undefined` is used instead.

`callbackfn` is called with three arguments: the value of the element, the index of the element, and the object being traversed.

`map` does not directly mutate the object on which it is called but the object may be mutated by the calls to `callbackfn`.

The range of elements processed by `map` is set before the first call to `callbackfn`. Elements which are appended to the array after the call to `map` begins will not be visited by `callbackfn`. If existing elements of the array are changed, their value as passed to `callbackfn` will be the value at the time `map` visits them; elements that are deleted after the call to `map` begins and before being visited are not visited.

When the `map` method is called with one or two arguments, the following steps are taken:

1. Let O be the result of calling `ToObject` passing the `this` value as the argument.

2. `ReturnIfAbrupt(O)`
3. Let `lenValue` be the result of calling the `[[Get]]` internal method of *O* with the argument `"length"`.
4. Let `len` be `ToUint32(lenValue)`.
5. `ReturnIfAbrupt(len)`
6. If `IsCallable(callbackfn)` is `false`, throw a `TypeError` exception.
7. If `thisArg` was supplied, let *T* be `thisArg`; else let *T* be `undefined`.
8. Let *A* be the result of the abstract operation `ArrayCreate (15.4)` with argument `len`.
9. Let `k` be `0`.
10. Repeat, while `k < len`
 - a. Let `Pk` be `ToString(k)`.
 - b. Let `kPresent` be the result of calling the `[[HasProperty]]` internal method of *O* with argument `Pk`.
 - c. If `kPresent` is `true`, then
 - i. Let `kValue` be the result of calling the `[[Get]]` internal method of *O* with argument `Pk`.
 - ii. `ReturnIfAbrupt(kValue)`.
 - iii. Let `mappedValue` be the result of calling the `[[Call]]` internal method of `callbackfn` with *T* as the `this` value and argument `List` containing `kValue`, `k`, and *O*.
 - iv. `ReturnIfAbrupt(mappedValue)`.
 - v. Let `defineStatus` be the result of calling the `[[DefineOwnProperty]]` internal method of *A* with arguments `Pk`, Property Descriptor `{[[Value]]: mappedValue, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `false`.
 - vi. `ReturnIfAbrupt(defineStatus)`.
 - d. Increase `k` by `1`.
11. Return *A*.

The `length` property of the `map` method is `1`.

NOTE The `map` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `map` function can be applied successfully to an exotic object that is not an Array is implementation-dependent.

15.4.4.20 `Array.prototype.filter (callbackfn [,thisArg])`

`callbackfn` should be a function that accepts three arguments and returns a value that is coercible to the Boolean value `true` or `false`. `filter` calls `callbackfn` once for each element in the array, in ascending order, and constructs a new array of all the values for which `callbackfn` returns `true`. `callbackfn` is called only for elements of the array which actually exist; it is not called for missing elements of the array.

If a `thisArg` parameter is provided, it will be used as the `this` value for each invocation of `callbackfn`. If it is not provided, `undefined` is used instead.

`callbackfn` is called with three arguments: the value of the element, the index of the element, and the object being traversed.

`filter` does not directly mutate the object on which it is called but the object may be mutated by the calls to `callbackfn`.

The range of elements processed by `filter` is set before the first call to `callbackfn`. Elements which are appended to the array after the call to `filter` begins will not be visited by `callbackfn`. If existing elements of the array are changed their value as passed to `callbackfn` will be the value at the time `filter` visits them; elements that are deleted after the call to `filter` begins and before being visited are not visited.

When the `filter` method is called with one or two arguments, the following steps are taken:

1. Let *O* be the result of calling `ToObject` passing the `this` value as the argument.
2. `ReturnIfAbrupt(O)`.
3. Let `lenValue` be the result of calling the `[[Get]]` internal method of *O* with the argument `"length"`.
4. Let `len` be `ToUint32(lenValue)`.
5. `ReturnIfAbrupt(len)`.
6. If `IsCallable(callbackfn)` is `false`, throw a `TypeError` exception.
7. If `thisArg` was supplied, let *T* be `thisArg`; else let *T* be `undefined`.

Deleted: abstraction operation

Deleted: a new array created as if by the expression `new Array(len)` where `Array` is the standard built-in constructor with that name and `len` is the value of

Deleted: list

Deleted: Call

Deleted: `defineResult`

Deleted: `defineResult`

Deleted: host

8. Let A be [the result of the abstract operation `ArrayCreate` \(15.4\) with argument `0`](#).
9. Let k be `0`.
10. Let to be `0`.
11. Repeat, while $k < len$
 - a. Let P_k be `ToString(k)`.
 - b. Let $kPresent$ be the result of calling the `[[HasProperty]]` internal method of O with argument P_k .
 - c. If $kPresent$ is `true`, then
 - i. Let $kValue$ be the result of calling the `[[Get]]` internal method of O with argument P_k .
 - ii. [`ReturnIfAbrupt\(kValue\)`](#).
 - iii. Let $selected$ be the result of calling the `[[Call]]` internal method of $callbackfn$ with T as the `this` value and argument list containing $kValue$, k , and O .
 - iv. [`ReturnIfAbrupt\(selected\)`](#).
 - v. If `ToBoolean(selected)` is `true`, then
 1. [`Let defineStatus be the result of calling the \[\[DefineOwnProperty\]\] internal method of A with arguments ToString\(to\), Property Descriptor {\[\[Value\]\]: kValue, \[\[Writable\]\]: true, \[\[Enumerable\]\]: true, \[\[Configurable\]\]: true}, and false.`](#)
 2. [`ReturnIfAbrupt\(defineStatus\)`](#).
 3. Increase to by `1`.
 - d. Increase k by `1`.
12. Return A .

The `length` property of the `filter` method is `1`.

NOTE The `filter` function is intentionally generic; it does not require that its `this` value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the `filter` function can be applied successfully to an [exotic object that is not an Array](#) is implementation-dependent.

Deleted: abstraction operation

Deleted: a new array created as if by the expression `new Array()` where `Array` is the standard built-in constructor with that name

Deleted: If $kValue$ is an abrupt completion, return $kValue$

Deleted: If $selected$ is an abrupt completion, return $selected$.

Deleted: Call

Deleted: host

15.4.4.21 `Array.prototype.reduce (callbackfn [, initialValue])`

`callbackfn` should be a function that takes four arguments. `reduce` calls the callback, as a function, once for each element present in the array, in ascending order.

`callbackfn` is called with four arguments: the `previousValue` (or value from the previous call to `callbackfn`), the `currentValue` (value of the current element), the `currentIndex`, and the object being traversed. The first time that callback is called, the `previousValue` and `currentValue` can be one of two values. If an `initialValue` was provided in the call to `reduce`, then `previousValue` will be equal to `initialValue` and `currentValue` will be equal to the first value in the array. If no `initialValue` was provided, then `previousValue` will be equal to the first value in the array and `currentValue` will be equal to the second. It is a **TypeError** if the array contains no elements and `initialValue` is not provided.

`reduce` does not directly mutate the object on which it is called but the object may be mutated by the calls to `callbackfn`.

The range of elements processed by `reduce` is set before the first call to `callbackfn`. Elements that are appended to the array after the call to `reduce` begins will not be visited by `callbackfn`. If existing elements of the array are changed, their value as passed to `callbackfn` will be the value at the time `reduce` visits them; elements that are deleted after the call to `reduce` begins and before being visited are not visited.

When the `reduce` method is called with one or two arguments, the following steps are taken:

1. Let O be the result of calling `ToObject` passing the `this` value as the argument.
2. [`ReturnIfAbrupt\(O\)`](#).
3. Let $lenValue$ be the result of calling the `[[Get]]` internal method of O with the argument `"length"`.
4. Let len be `ToInt32(lenValue)`.
5. [`ReturnIfAbrupt\(len\)`](#).
6. If `IsCallable(callbackfn)` is `false`, throw a **TypeError** exception.
7. If len is `0` and `initialValue` is not present, throw a **TypeError** exception.
8. Let k be `0`.
9. If `initialValue` is present, then
 - a. Set `accumulator` to `initialValue`.

10. Else, *initialValue* is not present
 - a. Let *kPresent* be **false**.
 - b. Repeat, while *kPresent* is **false** and *k* < *len*
 - i. Let *Pk* be *ToString(k)*.
 - ii. Let *kPresent* be the result of calling the **[[HasProperty]]** internal method of *O* with argument *Pk*.
 - iii. If *kPresent* is **true**, then
 1. Let *accumulator* be the result of calling the **[[Get]]** internal method of *O* with argument *Pk*.
 2. [ReturnIfAbrupt\(accumulator\)](#)
 - iv. Increase *k* by 1.
 - c. If *kPresent* is **false**, throw a **TypeError** exception.
 11. Repeat, while *k* < *len*
 - a. Let *Pk* be *ToString(k)*.
 - b. Let *kPresent* be the result of calling the **[[HasProperty]]** internal method of *O* with argument *Pk*.
 - c. If *kPresent* is **true**, then
 - i. Let *kValue* be the result of calling the **[[Get]]** internal method of *O* with argument *Pk*.
 - ii. [ReturnIfAbrupt\(kValue\)](#)
 - iii. Let *accumulator* be the result of calling the **[[Call]]** internal method of *callbackfn* with **undefined** as the **this** value and argument list containing *accumulator*, *kValue*, *k*, and *O*.
 - iv. [ReturnIfAbrupt\(accumulator\)](#)
 - d. Increase *k* by 1.
 12. Return *accumulator*.

The **length** property of the **reduce** method is **1**.

NOTE The **reduce** function is intentionally generic; it does not require that its **this** value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the **reduce** function can be applied successfully to [an exotic object that is not an Array](#) is implementation-dependent.

15.4.4.22 Array.prototype.reduceRight (*callbackfn* [, *initialValue*])

callbackfn should be a function that takes four arguments. **reduceRight** calls the callback, as a function, once for each element present in the array, in descending order.

callbackfn is called with four arguments: the *previousValue* (or value from the previous call to *callbackfn*), the *currentValue* (value of the current element), the *currentIndex*, and the object being traversed. The first time the function is called, the *previousValue* and *currentValue* can be one of two values. If an *initialValue* was provided in the call to **reduceRight**, then *previousValue* will be equal to *initialValue* and *currentValue* will be equal to the last value in the array. If no *initialValue* was provided, then *previousValue* will be equal to the last value in the array and *currentValue* will be equal to the second-to-last value. It is a **TypeError** if the array contains no elements and *initialValue* is not provided.

reduceRight does not directly mutate the object on which it is called but the object may be mutated by the calls to *callbackfn*.

The range of elements processed by **reduceRight** is set before the first call to *callbackfn*. Elements that are appended to the array after the call to **reduceRight** begins will not be visited by *callbackfn*. If existing elements of the array are changed by *callbackfn*, their value as passed to *callbackfn* will be the value at the time **reduceRight** visits them; elements that are deleted after the call to **reduceRight** begins and before being visited are not visited.

When the **reduceRight** method is called with one or two arguments, the following steps are taken:

1. Let *O* be the result of calling **ToObject** passing the **this** value as the argument.
2. [ReturnIfAbrupt\(O\)](#).
3. Let *lenValue* be the result of calling the **[[Get]]** internal method of *O* with the argument "**length**".
4. Let *len* be **ToInt32(lenValue)**.
5. [ReturnIfAbrupt\(len\)](#).
6. If **IsCallable(callbackfn)** is **false**, throw a **TypeError** exception.

Deleted: If *accumulator* is an abrupt completion, return *accumulator*.

Deleted: If *kValue* is an abrupt completion, return *kValue*

Deleted: If *accumulator* is an abrupt completion, return *accumulator*

Deleted: host

7. If *len* is 0 and *initialValue* is not present, throw a **TypeError** exception.
8. Let *k* be *len*-1.
9. If *initialValue* is present, then
 - a. Set *accumulator* to *initialValue*.
10. Else, *initialValue* is not present
 - a. Let *kPresent* be **false**.
 - b. Repeat, while *kPresent* is **false** and *k* \geq 0
 - i. Let *Pk* be *ToString(k)*.
 - ii. Let *kPresent* be the result of calling the **[[HasProperty]]** internal method of *O* with argument *Pk*.
 - iii. If *kPresent* is **true**, then
 1. Let *accumulator* be the result of calling the **[[Get]]** internal method of *O* with argument *Pk*.
 2. **ReturnIfAbrupt(accumulator)**
 - iv. Decrease *k* by 1.
 - c. If *kPresent* is **false**, throw a **TypeError** exception.
 11. Repeat, while *k* \geq 0
 - a. Let *Pk* be *ToString(k)*.
 - b. Let *kPresent* be the result of calling the **[[HasProperty]]** internal method of *O* with argument *Pk*.
 - c. If *kPresent* is **true**, then
 - i. Let *kValue* be the result of calling the **[[Get]]** internal method of *O* with argument *Pk*.
 - ii. **ReturnIfAbrupt(kValue)**
 - iii. Let *accumulator* be the result of calling the **[[Call]]** internal method of *callbackfn* with **undefined** as the **this** value and argument list containing *accumulator*, *kValue*, *k*, and *O*.
 - iv. **ReturnIfAbrupt(accumulator)**
 - d. Decrease *k* by 1.
 12. Return *accumulator*.

The **length** property of the **reduceRight** method is **1**.

NOTE The **reduceRight** function is intentionally generic; it does not require that its **this** value be an Array object. Therefore it can be transferred to other kinds of objects for use as a method. Whether the **reduceRight** function can be applied successfully to an [exotic object that is not an Array](#) is implementation-dependent.

Deleted: If *accumulator* is an abrupt completion, return *accumulator*

Deleted: If *kValue* is an abrupt completion, return *kValue*

Deleted: If *accumulator* is an abrupt completion, return *accumulator*

Deleted: host

15.4.5 Properties of Array Instances

Array instances inherit properties from the Array prototype object and [have the **\[\[NativeBrand\]\]** internal property with value **NativeArray**](#). Array instances also have the following properties.

Deleted: their **[[Class]]**

Deleted: **isArray**

Deleted: value is "Array"

15.4.5.1 **[[DefineOwnProperty]] (*P*, *Desc*, *Throw*)**

Array objects use a variation of the **[[DefineOwnProperty]]** internal method used for other native ECMAScript objects (8.12.9).

Assume *A* is an Array object, *Desc* is a Property Descriptor, and *Throw* is a Boolean flag.

In the following algorithm, the term “Reject” means “If *Throw* is **true**, then throw a **TypeError** exception, otherwise return **false**.”

When the **[[DefineOwnProperty]]** internal method of *A* is called with property *P*, Property Descriptor *Desc*, and Boolean flag *Throw*, the following steps are taken:

1. Let *oldLenDesc* be the result of calling the **[[GetOwnProperty]]** internal method of *A* passing "**length**" as the argument. The result will never be **undefined** or an accessor descriptor because Array objects are created with a length data property that cannot be deleted or reconfigured.
2. Let *oldLen* be *oldLenDesc.[[Value]]*.
3. If *P* is "**length**", then
 - a. If the **[[Value]]** field of *Desc* is absent, then
 - i. Return the result of calling the default **[[DefineOwnProperty]]** internal method (8.12.9) on *A* passing "**length**", *Desc*, and *Throw* as arguments.

Deleted: <#>**ReturnIfAbrupt(A)**</#>

- b. Let *newLenDesc* be a copy of *Desc*.
- c. Let *newLen* be `ToUint32(Desc.[[Value]])`.
- d. If *newLen* is not equal to `ToNumber(Desc.[[Value]])`, throw a **RangeError** exception.
- e. Set *newLenDesc*.[[Value]] to *newLen*.
- f. If *newLen* \geq *oldLen*, then
 - i. Return the result of calling the default [[DefineOwnProperty]] internal method (8.12.9) on *A* passing "**length**", *newLenDesc*, and *Throw* as arguments.
- g. Reject if *oldLenDesc*.[[Writable]] is **false**.
- h. If *newLenDesc*.[[Writable]] is absent or has the value **true**, let *newWritable* be **true**.
- i. Else,
 - i. Need to defer setting the [[Writable]] attribute to **false** in case any elements cannot be deleted.
 - ii. Let *newWritable* be **false**.
 - iii. Set *newLenDesc*.[[Writable]] to **true**.
- j. Let *succeeded* be the result of calling the default [[DefineOwnProperty]] internal method (8.12.9) on *A* passing "**length**", *newLenDesc*, and *Throw* as arguments.
- k. If *succeeded* is **false**, return **false**.
- l. While *newLen* $<$ *oldLen* repeat,
 - i. Set *oldLen* to *oldLen* - 1.
 - ii. Let *deleteSucceeded* be the result of calling the [[Delete]] internal method of *A* passing `ToString(oldLen)` and **false** as arguments.
 - iii. If *deleteSucceeded* is **false**, then
 - 1. Set *newLenDesc*.[[Value]] to *oldLen* + 1.
 - 2. If *newWritable* is **false**, set *newLenDesc*.[[Writable]] to **false**.
 - 3. Call the default [[DefineOwnProperty]] internal method (8.12.9) on *A* passing "**length**", *newLenDesc*, and **false** as arguments.
 - 4. Reject.
 - m. If *newWritable* is **false**, then
 - i. Call the default [[DefineOwnProperty]] internal method (8.12.9) on *A* passing "**length**", Property Descriptor {[[Writable]]: **false**}, and **false** as arguments. This call will always return **true**.
 - n. Return **true**.
- 4. Else if *P* is an array index (15.4), then
 - a. Let *index* be `ToUint32(P)`.
 - b. [ReturnIfAbrupt\(*index*\)](#).
 - c. Reject if *index* \geq *oldLen* and *oldLenDesc*.[[Writable]] is **false**.
 - d. Let *succeeded* be the result of calling the default [[DefineOwnProperty]] internal method (8.12.9) on *A* passing *P*, *Desc*, and **false** as arguments.
 - e. Reject if *succeeded* is **false**.
 - f. If *index* \geq *oldLen*
 - i. Set *oldLenDesc*.[[Value]] to *index* + 1.
 - ii. Call the default [[DefineOwnProperty]] internal method (8.12.9) on *A* passing "**length**", *oldLenDesc*, and **false** as arguments. This call will always return **true**.
 - g. Return **true**.
- 5. Return the result of calling the default [[DefineOwnProperty]] internal method (8.12.9) on *A* passing *P*, *Desc*, and *Throw* as arguments.

15.4.5.2 **length**

The **length** property of this Array object is a data property whose value is always numerically greater than the name of every deletable property whose name is an array index.

The **length** property initially has the attributes { [[Writable]]: **true**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

NOTE Attempting to set the **length** property of an Array object to a value that is numerically less than or equal to the largest numeric property name of an existing array indexed non-deletable property of the array will result in the **length** being set to a numeric value that is one greater than that largest numeric property name. See 15.4.5.1.

15.5 String Objects

15.5.1 The String Constructor Called as a Function

When `string` is called as a function rather than as a constructor, it performs a type conversion.

15.5.1.1 `String ([value])`

Returns a String value (not a String object) computed by `ToString(value)`. If `value` is not supplied, the empty String "" is returned.

15.5.2 The String Constructor

When `string` is called as part of a `new` expression, it is a constructor: it initialises the newly created object.

15.5.2.1 `new String ([value])`

The `[[Prototype]]` internal property of the newly constructed object is set to the standard built-in String prototype object that is the initial value of `String.prototype` (15.5.3.1).

The newly constructed object has the `[[NativeBrand]]` internal property with value `StringWrapper`.

The `[[Extensible]]` internal property of the newly constructed object is set to `true`.

The `[[PrimitiveValue]]` internal property of the newly constructed object is set to `ToString(value)`, or to the empty String if `value` is not supplied.

Deleted: `[[Class]]` internal property of the
Deleted: is set to "String"
Deleted: `IsString`

15.5.3 Properties of the String Constructor

The value of the `[[Prototype]]` internal property of the String constructor is the standard built-in Function prototype object (15.3.4).

Besides the internal properties and the `length` property (whose value is `1`), the String constructor has the following properties:

15.5.3.1 `String.prototype`

The initial value of `String.prototype` is the standard built-in String prototype object (15.5.4).

This property has the attributes `{ [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }`.

15.5.3.2 `String.fromCharCode (...codeUnits)`

The `String.fromCharCode` function may be called with a variable number of arguments which form the rest parameter `codeUnits`. The following steps are taken:

1. Assert: `codeUnits` is a well-formed rest parameter object.
2. Let `length` be the result of calling the `[[Get]]` internal method of `codeUnits` with argument `"length"`.
3. Let `elements` be a new List.
4. Let `nextIndex` be `0`.
5. Repeat while `nextIndex < length`
 - a. Let `next` be the result of calling the `[[Get]]` internal method of `codeUnits` with argument `ToString(nextIndex)`.
 - b. Let `nextCU` be `ToUint16(next)`.
 - c. ReturnIfAbrupt(`nextCU`).
 - d. Append `nextCU` to the end of `elements`.
 - e. Let `nextIndex` be `nextIndex + 1`.

Comment [AWB9121]: Should we provide fromCodeUnit as an alias for this property and remove fromCharCode as obsolete.

Deleted: [
Deleted: `char0 [, char1 [, ...]]`]

Deleted: Returns a String value containing as many characters as the number of arguments. Each argument specifies one character of the resulting String, with the first argument specifying the first character, and so on, from left to right. An argument is converted to a character by applying the operation `ToUint16` (9.7) and regarding the resulting 16-bit integer as the code unit value of a character. If no arguments are supplied, the result is the empty String.||

Deleted: `ing`

6. Return the string value whose elements are, in order, the elements in the List *elements*. If *length* is 0, the empty string is returned.

The **length** property of the **fromCharCode** function is 1.

15.5.3.3 String.fromCodePoint (...codePoints)

The **String.fromCodePoint** function may be called with a variable number of arguments which form the rest parameter *codePoints*. The following steps are taken:

1. Assert: *codePoints* is a well-formed rest parameter object.
2. Let *length* be the result of calling the [[Get]] internal method of *codePoints* with argument "**length**".
3. Let *elements* be a new List.
4. Let *nextIndex* be 0.
5. Repeat while *nextIndex* < *length*
 - a. Let *next* be the result of calling the [[Get]] internal method of *codePoints* with argument `ToString(nextIndex)`.
 - b. Let *nextCP* be `ToNumber(next)`.
 - c. ReturnIfAbrupt(*nextCP*).
 - d. If `SameValue(nextCP, Tolnteger(nextCP))` is false, then throw a **RangeError** exception.
 - e. If *nextCP* < 0 or *nextCP* > 0x10FFFF, then throw a **RangeError** exception.
 - f. Append the elements of the UTF-16 Encoding (clause 6) of *nextCP* to the end of *elements*.
 - g. Let *nextIndex* be *nextIndex* + 1.
6. Return the string value whose elements are, in order, the elements in the List *elements*. If *length* is 0, the empty string is returned.

The **length** property of the **fromCodePoint** function is 0.

15.5.3.4 String.raw (callSite, ...substitutions)

The **String.raw** function may be called with a variable number of arguments. The first argument is *callSite* and the remainder of the arguments form the rest parameter *substitutions*. The following steps are taken:

1. Assert: *substitutions* is a well-formed rest parameter object.
2. Let *cooked* be `ToObject(callSite)`.
3. ReturnIfAbrupt(*cooked*).
4. Let *rawValue* be the result of calling the [[Get]] internal method of *cooked* with argument "**raw**".
5. Let *raw* be `ToObject(rawValue)`.
6. ReturnIfAbrupt(*raw*).
7. Let *len* be the result of calling the [[Get]] internal method of *raw* with argument "**length**".
8. Let *literalSegments* be `ToUint(len)`.
9. ReturnIfAbrupt(*literalSegments*).
10. If *literalSegments* = 0, then return the empty string.
11. Let *stringElements* be a new List.
12. Let *nextIndex* be 0.
13. Repeat while *nextIndex* < *literalSegments*
 - a. Let *nextKey* be `ToString(nextIndex)`.
 - b. Let *next* be the result of calling the [[Get]] internal method of *raw* with argument *nextKey*.
 - c. Let *nextSeg* be `ToString(next)`.
 - d. ReturnIfAbrupt(*nextSeg*).
 - e. Append in order the code unit elements of *nextSeg* to the end of *stringElements*.
 - f. If *nextIndex* + 1 = *literalSegments*, then
 - i. Return the string value whose elements are, in order, the elements in the List *stringElements*. If *length* is 0, the empty string is returned.
 - g. Let *next* be the result of calling the [[Get]] internal method of *substitutions* with argument *nextKey*.
 - h. Let *nextSub* be `ToString(next)`.
 - i. ReturnIfAbrupt(*nextSub*).
 - j. Append in order the code unit elements of *nextSub* to the end of *stringElements*.
 - k. Let *nextIndex* be *nextIndex* + 1.

Deleted: CharCode

Deleted: Units

Deleted: ing

Deleted: Units

Deleted: v

Deleted: V

Comment [AWB9122]: Note this follows the ES6 convention for rest parameters rather than the precedent established by fromCharCode

Deleted: ing

Deleted: ing

Comment [AWB10123]: TODO: this is something we probably need if we are going to eliminate array usage ToUint32

Deleted: elements

Deleted: elements

Deleted: elements

The `length` property of the `raw` function is 1.

NOTE `String.raw` is intended for use as a tag function of a Tagged Template String (11.2.6). When called as such the first argument will be a well formed template call site object and the rest parameter will contain the substitution values.

Deleted: Quasi

Deleted: quasi

15.5.4 Properties of the String Prototype Object

The String prototype object is itself a String object whose value is an empty String. **The String prototype object has the `[[NativeBrand]]` internal property** with value `StringWrapper`.

Deleted: (its `[[Class]]` is "String")

Deleted: IsString

The value of the `[[Prototype]]` internal property of the String prototype object is the standard built-in Object prototype object (15.2.4).

15.5.4.1 `String.prototype.constructor`

The initial value of `String.prototype.constructor` is the built-in `String` constructor.

15.5.4.2 `String.prototype.toString()`

Returns this String value. (Note that, for a String object, the `toString` method happens to return the same thing as the `valueOf` method.)

The `toString` function is not generic; it throws a **TypeError** exception if its `this` value is not a String or a String object. Therefore, it cannot be transferred to other kinds of objects for use as a method.

15.5.4.3 `String.prototype.valueOf()`

Returns this String value.

The `valueOf` function is not generic; it throws a **TypeError** exception if its `this` value is not a String or String object. Therefore, it cannot be transferred to other kinds of objects for use as a method.

15.5.4.4 `String.prototype.charAt(pos)`

NOTE Returns a `single element` String containing the `code unit at element position pos` in the `String value` resulting from converting this object to a String. If there is no `element` at that position, the result is the empty String. The result is a String value, not a String object.

Comment [AWB9124]: Perhaps `BMPChar` should be provided as an alias for this method and `charAt` should be marked as obsolete.

Formatted: Note

Deleted: character

Deleted: String

Deleted: character

If `pos` is a value of Number type that is an integer, then the result of `x.charAt(pos)` is equal to the result of `x.substring(pos, pos+1)`.

When the `charAt` method is called with one argument `pos`, the following steps are taken:

1. `ReturnIfAbrupt(CheckObjectCoercible(this value))`.
2. Let `S` be the result of calling `ToString`, giving it the `this` value as its argument.
3. `ReturnIfAbrupt(S)`.
4. Let `position` be `ToInteger(pos)`.
5. `ReturnIfAbrupt(position)`.
6. Let `size` be the number of `elements` in `S`.
7. If `position < 0` or `position ≥ size`, return the empty String.
8. Return a String of length 1, containing one `code unit` from `S`, namely the `code unit` at position `position`, where the first (leftmost) `code unit` in `S` is considered to be at position 0, the next one at position 1, and so on.

Deleted: Call

Deleted: passing the

Deleted: as its argument

Deleted: s

Deleted: characters

Deleted: character

Deleted: character

Deleted: character

NOTE The `charAt` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.5 String.prototype.charCodeAt(pos)

NOTE Returns a Number (a nonnegative integer less than 2^{16}) **that is** the code unit value of the **string element** at position **pos** in the String resulting from converting this object to a String. If there is no **element** at that position, the result is **NaN**.

When the **charCodeAt** method is called with one argument **pos**, the following steps are taken:

1. ReturnIfAbrupt(CheckObjectCoercible(this value)).
2. Let **S** be the result of calling **ToString**, giving it the **this** value as its argument.
3. ReturnIfAbrupt(S).
4. Let **position** be **ToInteger(pos)**.
5. ReturnIfAbrupt(position).
6. Let **size** be the number of **elements** in **S**.
7. If **position < 0** or **position ≥ size**, return **NaN**.
8. Return a value of Number type, whose value is the code unit value of the **element** at position **position** in the String **S**, where the first (leftmost) **element** in **S** is considered to be at position 0, the next one at position 1, and so on.

NOTE The **charCodeAt** function is intentionally generic; it does not require that its **this** value be a String object. Therefore it can be transferred to other kinds of objects for use as a method.

15.5.4.6 String.prototype.concat(...args)

NOTE When the **concat** method is called with zero or more arguments, it returns a String consisting of the **string elements** of this object (converted to a String) followed by the **string elements** of each of **the arguments** converted to a String. The result is a String value, not a String object.

The following steps are taken:

1. Assert: args is a well-formed rest parameter object.
2. ReturnIfAbrupt(CheckObjectCoercible(this value)).
3. Let **S** be the result of calling **ToString**, giving it the **this** value as its argument.
4. ReturnIfAbrupt(S).
5. Let **args** be an internal list that is a copy of the argument list passed to this function.
6. Let **R** be **S**.
7. Repeat, while **args** is not empty
 - a. Remove the first element from **args** and let **next** be the value of that element.
 - b. Let nextString be ToString(next).
 - c. ReturnIfAbrupt(nextString).
 - d. Let **R** be the String value consisting of the **string elements** in the previous value of **R** followed by the **string elements** of **nextString**.
8. Return **R**.

The **length** property of the **concat** method is **1**.

NOTE The **concat** function is intentionally generic; it does not require that its **this** value be a String object. Therefore it can be transferred to other kinds of objects for use as a method.

15.5.4.7 String.prototype.indexOf(searchString, position)

If **searchString** appears as a substring of the result of converting this object to a String, at one or more positions that are greater than or equal to **position**, then the index of the smallest such position is returned; otherwise, **-1** is returned. If **position** is **undefined**, **0** is assumed, so as to search all of the String.

The **indexOf** method takes two arguments, **searchString** and **position**, and performs the following steps:

1. ReturnIfAbrupt(CheckObjectCoercible(this value)).
2. Let **S** be the result of calling **ToString**, giving it the **this** value as its argument.
3. ReturnIfAbrupt(S).

Deleted: representing

Deleted: character

Formatted: Note

Deleted: character

Deleted: Call CheckObjectCoercible passing the **this** value its argument.

Deleted: characters

Deleted: character

Deleted: character

Deleted: [string1 [, string2 [, ...]]]

Formatted: Note

Deleted: string1, string2, etc.

Deleted: characters

Deleted: characters

Deleted: string1, string2, etc. (where each argument is

Deleted:)

Deleted: .

Deleted: strings

Deleted: Call CheckObjectCoercible passing the **this** value its argument.

Deleted: characters

Deleted: characters

Deleted: ToString

Deleted:)

4. Let `searchStr` be `ToString(searchString)`.
- ~~5. `ReturnIfAbrupt(searchString)`.~~
6. Let `pos` be `ToInteger(position)`. (If `position` is `undefined`, this step produces the value `0`).
- ~~7. `ReturnIfAbrupt(pos)`.~~
8. Let `len` be the number of `elements` in `S`.
9. Let `start` be `min(max(pos, 0), len)`.
10. Let `searchLen` be the number of `elements` in `searchStr`.
11. Return the smallest possible integer `k` not smaller than `start` such that `k + searchLen` is not greater than `len`, and for all nonnegative integers `j` less than `searchLen`, the `code unit` at position `k+j` of `S` is the same as the `code unit` at position `j` of `searchStr`; but if there is no such integer `k`, then return the value `-1`.

Deleted: characters
Deleted: characters
Deleted: character
Deleted: character

The `length` property of the `indexOf` method is `1`.

NOTE The `indexOf` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.8 `String.prototype.lastIndexOf (searchString, position)`

If `searchString` appears as a substring of the result of converting this object to a String at one or more positions that are smaller than or equal to `position`, then the index of the greatest such position is returned; otherwise, `-1` is returned. If `position` is `undefined`, the length of the String value is assumed, so as to search all of the String.

The `lastIndexOf` method takes two arguments, `searchString` and `position`, and performs the following steps:

- ~~1. `ReturnIfAbrupt(CheckObjectCoercible(this value))`.~~
2. Let `S` be the result of calling `ToString`, giving it the `this` value as its argument.
- ~~3. `ReturnIfAbrupt(S)`.~~
4. Let `searchStr` be `ToString(searchString)`.
- ~~5. `ReturnIfAbrupt(searchString)`.~~
6. Let `numPos` be `ToNumber(position)`. (If `position` is `undefined`, this step produces the value `NaN`).
- ~~7. `ReturnIfAbrupt(numPos)`.~~
8. If `numPos` is `NaN`, let `pos` be `+∞`; otherwise, let `pos` be `ToInteger(numPos)`.
9. Let `len` be the number of `elements` in `S`.
10. Let `start` be `min(max(pos, 0), len)`.
11. Let `searchLen` be the number of `elements` in `searchStr`.
12. Return the largest possible nonnegative integer `k` not larger than `start` such that `k + searchLen` is not greater than `len`, and for all nonnegative integers `j` less than `searchLen`, the `code unit` at position `k+j` of `S` is the same as the `code unit` at position `j` of `searchStr`; but if there is no such integer `k`, then return the value `-1`.

Deleted: Call `CheckObjectCoercible` passing the `this` value as its argument.
Deleted: characters
Deleted: characters
Deleted: character
Deleted: character

The `length` property of the `lastIndexOf` method is `1`.

NOTE The `lastIndexOf` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.9 `String.prototype.localeCompare (that)`

When the `localeCompare` method is called with one argument `that`, it returns a Number other than `NaN` that represents the result of a locale-sensitive String comparison of the `this` value (converted to a String) with `that` (converted to a String). The two Strings are `S` and `That`. The two Strings are compared in an implementation-defined fashion. The result is intended to order String values in the sort order specified by the system default locale, and will be negative, zero, or positive, depending on whether `S` comes before `That` in the sort order, the Strings are equal, or `S` comes after `That` in the sort order, respectively.

Before perform the comparisons the following steps are performed to prepare the Strings:

- ~~1. `ReturnIfAbrupt(CheckObjectCoercible(this value))`.~~
2. Let `S` be the result of calling `ToString`, giving it the `this` value as its argument.
- ~~3. `ReturnIfAbrupt(S)`.~~

Deleted: Call `CheckObjectCoercible` passing the `this` value as its argument.

4. Let *That* be `ToString(that)`.
5. `ReturnIfAbrupt(That)`.

The `localeCompare` method, if considered as a function of two arguments `this` and `that`, is a consistent comparison function (as defined in 15.4.4.11) on the set of all Strings.

The actual return values are implementation-defined to permit implementers to encode additional information in the value, but the function is required to define a total ordering on all Strings and to return 0 when comparing Strings that are considered canonically equivalent by the Unicode standard.

If no language-sensitive comparison at all is available from the host environment, this function may perform a bitwise comparison.

NOTE 1 The `localeCompare` method itself is not directly suitable as an argument to `Array.prototype.sort` because the latter requires a function of two arguments.

NOTE 2 This function is intended to rely on whatever language-sensitive comparison functionality is available to the ECMAScript environment from the host environment, and to compare according to the rules of the host environment's current locale. It is strongly recommended that this function treat Strings that are canonically equivalent according to the Unicode standard as identical (in other words, compare the Strings as if they had both been converted to Normalised Form C or D first). It is also recommended that this function not honour Unicode compatibility equivalences or decompositions.

NOTE 3 The second parameter to this function is likely to be used in a future version of this standard; it is recommended that implementations do not use this parameter position for anything else.

NOTE 4 The `localeCompare` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.10 `String.prototype.match (regexp)`

When the `match` method is called with argument `regexp`, the following steps are taken:

1. `ReturnIfAbrupt(CheckObjectCoercible(this value))`.
2. Let *S* be the result of calling `ToString`, giving it the `this` value as its argument.
3. `ReturnIfAbrupt(S)`.
4. If Type(`regexp`) is Object and `regexp` has a `[[NativeBrand]]` internal property whose value is `NativeRegExp`, then let *rx* be `regexp`;
5. Else, let *rx* be the result of the abstract operation `RegExpCreate` (15.10.4.1) with arguments `regexp` and `undefined`,
6. `ReturnIfAbrupt(rx)`.
7. Let *global* be the result of calling the `[[Get]` internal method of *rx* with argument `"global"`.
8. `ReturnIfAbrupt(global)`.
9. If *global* is not `true`, then
 - a. Return the result of calling the abstract operation `RegExpExec` (see 15.10.6.2) with arguments `rx` and `S`.
10. Else, *global* is `true`
 - a. Let `putStatus` be the result of calling the `[[Put]` internal method of *rx* with arguments `"lastIndex"`, `0`, and `true`.
 - b. `ReturnIfAbrupt(putStatus)`.
 - c. Let *A* be the result of the abstract operation `ArrayCreate` (15.4) with argument `0`.
 - d. Let *previousLastIndex* be 0.
 - e. Let *n* be 0.
 - f. Let *lastMatch* be `true`.
 - g. Repeat, while *lastMatch* is `true`
 - i. Let *result* be the result of calling the abstract operation `RegExpExec` (see 15.10.6.2) with arguments `rx` and `S`.
 - ii. `ReturnIfAbrupt(result)`.
 - iii. If *result* is `null`, then set *lastMatch* to `false`.
 - iv. Else, *result* is not `null`

Deleted: Call <code>CheckObjectCoercible</code> passing the <code>this</code> value as its argument.
Deleted: the value of the <code>[[Class]]</code> internal property of <code>regexp</code>
Deleted: is <code>"RegExp"</code>
Deleted: the <code>[[NativeBrand]]</code> internal property of <code>regexp</code>
Deleted: <code>IsRegExp</code>
Deleted: abstraction operation
Deleted: a new <code>RegExp</code> object created as if by the expression <code>new RegExp (regexp)</code> where <code>RegExp</code> is the standard built-in constructor with that name.
Deleted: <code><#>Let exec be the standard built-in function <code>RegExp.prototype.exec</code> (see 15.10.6.2)</code>
Deleted: <code>[[Call]]</code> internal method of <code>exec</code>
Deleted: as
Deleted: the <code>this</code> value and argument list containing the <code>[[Call]]</code> internal method of <code>exec</code>
Deleted: <code>Call</code>
Deleted: and
Deleted: a new array created as if by the expression <code>new Array ()</code> where <code>Array</code> is the standard built-in constructor with that name
Deleted: abstraction operation
Deleted: <code>[[Call]]</code> internal method of <code>exec</code>
Deleted: as the <code>this</code> value and argument list containing the <code>[[Call]]</code> internal method of <code>exec</code>

1. Let *thisIndex* be the result of calling the [[Get]] internal method of *rx* with argument "lastIndex".
2. ReturnIfAbrupt(*thisIndex*)
3. If *thisIndex* = *previousLastIndex* then
 - a Let *putStatus* be the result of calling the [[Put]] internal method of *rx* with arguments "lastIndex", *thisIndex+1*, and true.
 - b ReturnIfAbrupt(*putStatus*).
 - c Set *previousLastIndex* to *thisIndex+1*.
4. Else, set *previousLastIndex* to *thisIndex*.
5. Let *matchStr* be the result of calling the [[Get]] internal method of *result* with argument "0".
6. ReturnIfAbrupt(*matchStr*)
7. Let *defineStatus* be the result of calling the [[DefineOwnProperty]] internal method of *A* with arguments *ToString(n)*, the Property Descriptor {[[Value]]: *matchStr*, [[Writable]]: true, [[Enumerable]]: true, [[configurable]]: true}, and false.
8. ReturnIfAbrupt(*defineStatus*).
9. Increment *n*.
 - h. If *n* = 0, then return null.
 - i. Return *A*.

NOTE The *match* function is intentionally generic; it does not require that its *this* value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.11 String.prototype.replace (searchValue, replaceValue)

First set *string* according to the following steps:

1. ReturnIfAbrupt(CheckObjectCoercible(*this value*))
2. Let *string* be the result of calling *ToString*, giving it the *this* value as its argument.
3. ReturnIfAbrupt(*string*).

If *searchValue* is a regular expression (an object that has a [[NativeBrand]] internal property whose value is NativeRegExp), do the following: If *searchValue.global* is false, then search *string* for the first match of the regular expression *searchValue*. If *searchValue.global* is true, then search *string* for all matches of the regular expression *searchValue*. Do the search in the same manner as in *String.prototype.match*, including the update of *searchValue.lastIndex*. Let *m* be the number of left capturing parentheses in *searchValue* (using *NcapturingParens* as specified in 15.10.2.1).

If *searchValue* is not a regular expression, let *searchString* be *ToString(searchValue)* and search *string* for the first occurrence of *searchString*. Let *m* be 0.

If *replaceValue* is a function, then for each matched substring, call the function with the following *m* + 3 arguments. Argument 1 is the substring that matched. If *searchValue* is a regular expression, the next *m* arguments are all of the captures in the MatchResult (see 15.10.2.1). Argument *m* + 2 is the offset within *string* where the match occurred, and argument *m* + 3 is *string*. The result is a String value derived from the original input by replacing each matched substring with the corresponding return value of the function call, converted to a String if need be.

Otherwise, let *newstring* denote the result of converting *replaceValue* to a String. The result is a String value derived from the original input String by replacing each matched substring with a String derived from *newstring* by replacing elements in *newstring* by replacement text as specified in Table 28. These \$ replacements are done left-to-right, and, once such a replacement is performed, the new replacement text is not subject to further replacements. For example, "\$1,\$2".replace(/(\\$(\d))/g, "\$\$1-\$1\$2") returns "\$1-\$11,\$1-\$22". A \$ in *newstring* that does not match any of the forms below is left as is.

Table 28 — Replacement Text Symbol Substitutions

Code unit	Unicode Characters	Replacement text
-----------	--------------------	------------------

Deleted: Call
Deleted: and

Deleted: Call

Deleted: Call CheckObjectCoercible passing the *this* value as its argument.

Deleted: whose [[Class]]
Deleted: the
Deleted: IsRegExp
Deleted: is "RegExp"

Deleted: characters

Comment [AWB7125]: Needs an real algorithm and also completion record checks

Formatted Table

0x0024, 0x0024	<code>\$\$</code>	<code>\$</code>
0x0024, 0x0026	<code>\$&</code>	The matched substring.
0x0024, 0x0060	<code>\$`</code>	The portion of <i>string</i> that precedes the matched substring.
0x0024, 0x0027	<code>\$'</code>	The portion of <i>string</i> that follows the matched substring.
0x0024, N where 0x0030 ≤ N ≤ 0x0039	<code>\$n where n is one of 0 1 2 3 4 5 6 7 8 9</code>	The <i>n</i> th capture, where <i>n</i> is a single digit in the range 1 to 9 and <code>\$n</code> is not followed by a decimal digit. If <i>n</i> ≤ <i>m</i> and the <i>n</i> th capture is <code>undefined</code> , use the empty String instead. If <i>n</i> > <i>m</i> , the result is implementation-defined.
0x0024, N, N where 0x0030 ≤ N ≤ 0x0039	<code>\$nn where n is one of 0 1 2 3 4 5 6 7 8 9</code>	The <i>nn</i> th capture, where <i>nn</i> is a two-digit decimal number in the range 01 to 99. If <i>nn</i> ≤ <i>m</i> and the <i>nn</i> th capture is <code>undefined</code> , use the empty String instead. If <i>nn</i> > <i>m</i> , the result is implementation-defined.

Deleted: `$``

Deleted: `'`

NOTE The `replace` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.12 String.prototype.search (regexp)

When the search method is called with argument *regexp*, the following steps are taken:

1. `ReturnIfAbrupt(CheckObjectCoercible(this value))`.
2. Let *string* be the result of calling `ToString`, giving it the `this` value as its argument.
3. `ReturnIfAbrupt(string)`.
4. If `Type(regexp)` is Object and *regexp* has a `[[NativeBrand]]` internal property whose value is `NativeRegExp`, then let *rx* be *regexp*;
5. Else, let *rx* be the result of the abstraction operation `RegExpCreate` (15.10.4.1) with arguments *regexp* and `undefined`.
6. `ReturnIfAbrupt(rx)`.
7. Search the value *string* from its beginning for an occurrence of the regular expression pattern *rx*. Let *result* be a Number indicating the offset within *string* where the pattern matched, or `-1` if there was no match. If an abrupt completion occurs during the search, *result* is that Completion Record. The `lastIndex` and `global` properties of *regexp* are ignored when performing the search. The `lastIndex` property of *regexp* is left unchanged.
8. Return *result*.

Deleted: Call `CheckObjectCoercible` passing the `this` value as its argument.

Deleted: `S`

Deleted: the value of the `[[Class]]` internal property of *regexp*

Deleted: the

Deleted: `IsRegExp`

Deleted: `"RegExp"`

Deleted: abstraction operation

Deleted: a new `RegExp` object created as if by the expression `new RegExp(regexp)` where `RegExp` is the standard built-in constructor with that name

Comment [AWB7126]: Needs better spec language

NOTE The `search` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.13 String.prototype.slice (start, end)

The `slice` method takes two arguments, *start* and *end*, and returns a substring of the result of converting this object to a String, starting from `element` position *start* and running to, but not including, `element` position *end* (or through the end of the String if *end* is `undefined`). If *start* is negative, it is treated as `sourceLength+start` where `sourceLength` is the length of the String. If *end* is negative, it is treated as `sourceLength+end` where `sourceLength` is the length of the String. The result is a String value, not a String object. The following steps are taken:

1. `ReturnIfAbrupt(CheckObjectCoercible(this value))`.
2. Let *S* be the result of calling `ToString`, giving it the `this` value as its argument.
3. `ReturnIfAbrupt(S)`.
4. Let *len* be the number of `elements` in *S*.
5. Let *intStart* be `TolInteger(start)`.
6. If *end* is `undefined`, let *intEnd* be *len*; else let *intEnd* be `TolInteger(end)`.
7. If *intStart* is negative, let *from* be `max(len + intStart, 0)`; else let *from* be `min(intStart, len)`.
8. If *intEnd* is negative, let *to* be `max(len + intEnd, 0)`; else let *to* be `min(intEnd, len)`.
9. Let *span* be `max(to - from, 0)`.
10. Return a String `value` containing *span* consecutive `elements` from *S* beginning with the `element` at position *from*.

Deleted: character

Deleted: character

Deleted: Call `CheckObjectCoercible` passing the `this` value as its argument.

Deleted: characters

Deleted: characters

Deleted: character

The `length` property of the `slice` method is **2**.

NOTE The `slice` function is intentionally generic; it does not require that its `this` value be a String object. Therefore it can be transferred to other kinds of objects for use as a method.

15.5.4.14 String.prototype.split (separator, limit)

Returns an Array object into which substrings of the result of converting this object to a String have been stored. The substrings are determined by searching from left to right for occurrences of `separator`; these occurrences are not part of any substring in the returned array, but serve to divide up the String value. The value of `separator` may be a String of any length or it may be a RegExp object (i.e., an object with a `[[NativeBrand]] internal property` whose value is `NativeRegExp`; see 15.10).

The value of `separator` may be an empty String, an empty regular expression, or a regular expression that can match an empty String. In this case, `separator` does not match the empty substring at the beginning or end of the input String, nor does it match the empty substring at the end of the previous separator match. (For example, if `separator` is the empty String, the String is split up into individual `code unit elements`; the length of the result array equals the length of the String, and each substring contains one `code unit`.) If `separator` is a regular expression, only the first match at a given position of the `this` String is considered, even if backtracking could yield a non-empty-substring match at that position. (For example, `"ab".split(/a*/)` evaluates to the array `["a", "b"]`, while `"ab".split(/a*/)` evaluates to the array `["", "b"]`.)

If the `this` object is (or converts to) the empty String, the result depends on whether `separator` can match the empty String. If it can, the result array contains no elements. Otherwise, the result array contains one element, which is the empty String.

If `separator` is a regular expression that contains capturing parentheses, then each time `separator` is matched the results (including any `undefined` results) of the capturing parentheses are spliced into the output array. For example,

```
"A<B>bold</B>and<CODE>coded</CODE>".split(/<(\w)?([^\w]+)>/)
```

evaluates to the array

```
["A", undefined, "B", "bold", "/", "B", "and", undefined,
 "CODE", "coded", "/", "CODE", ""]
```

If `separator` is `undefined`, then the result array contains just one String, which is the `this` value (converted to a String). If `limit` is not `undefined`, then the output array is truncated so that it contains no more than `limit` elements.

When the `split` method is called, the following steps are taken:

1. `ReturnIfAbrupt(CheckObjectCoercible(this value))`.
Deleted: Call `CheckObjectCoercible` passing the `this` value as its argument.
2. Let `S` be the result of calling `ToString`, giving it the `this` value as its argument.
Deleted: a new array created as if by the expression `new Array()` where `Array` is the standard built-in constructor with that name
3. `ReturnIfAbrupt(S)`.
Deleted: characters
4. Let `A` be the result of the abstract operation `ArrayCreate` with argument 0.
Deleted: the
5. Let `lengthA` be 0.
Deleted: IsRegExp
6. If `limit` is `undefined`, let `lim = 232-1`; else let `lim = ToUint32(limit)`.
Deleted: is a RegExp object (its [[Class]] is "RegExp")
7. Let `s` be the number of `elements` in `S`.
Deleted: =
8. Let `p = 0`.
Deleted: =
9. If `separator` has a `[[NativeBrand]] internal property` whose value is `NativeRegExp`, let `R` be `separator`; otherwise let `R` be `ToString(separator)`.
Deleted: e
10. `ReturnIfAbrupt(separator)`.
Deleted: =
11. If `lim = 0`, return `A`.
Deleted: =
12. If `separator` is `undefined`, then
 - a. Call the `[[DefineOwnProperty]]` internal method of `A` with arguments `"0"`, Property Descriptor `{[[Value]]: S, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `false`.
Deleted: =
 - b. `Assert: the previous step will never result in an abrupt completion`.
Deleted: =
 - c. Return `A`.
Deleted: =
13. If `s = 0`, then
Deleted: =

- a. Call *SplitMatch*(*S*, 0, *R*) and let *z* be its MatchResult result.
- b. If *z* is not **failure**, return *A*.
- c. Call the **[[DefineOwnProperty]]** internal method of *A* with arguments "0", Property Descriptor **{[[Value]]: *S*, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}**, and **false**.
- d. Assert: the previous step will never result in an abrupt completion.**
- e. Return *A*.

14. Let *q* = *p*.
15. Repeat, while *q* ≠ *s*
 - a. Call *SplitMatch*(*S*, *q*, *R*) and let *z* be its MatchResult result.
 - b. If *z* is **failure**, then let *q* = *q*+1.
 - c. Else, *z* is not **failure**
 - i. *z* must be a State. Let *e* be *z*'s *endIndex* and let *cap* be *z*'s *captures* array.
 - ii. If *e* = *p*, then let *q* = *q*+1.
 - iii. Else, *e* ≠ *p*
 1. Let *T* be a String value equal to the substring of *S* consisting of the **elements** at positions *p* (inclusive) through *q* (exclusive).
 2. Call the **[[DefineOwnProperty]]** internal method of *A* with arguments **ToString(*lengthA*)**, Property Descriptor **{[[Value]]: *T*, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}**, and **false**.
 - 3. Assert: the previous step will never result in an abrupt completion.**
 4. Increment *lengthA* by 1.
 5. If *lengthA* = *lim*, return *A*.
 6. Let *p* = *e*.
 7. Let *i* = 0.
 8. Repeat, while *i* is not equal to the number of elements in *cap*.
 - a. Let *i* = *i*+1.
 - b. Call the **[[DefineOwnProperty]]** internal method of *A* with arguments **ToString(*lengthA*)**, Property Descriptor **{[[Value]]: *cap*[*i*], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}**, and **false**.
 - c. Assert: the previous step will never result in an abrupt completion.**
 - d. Increment *lengthA* by 1.
 - e. If *lengthA* = *lim*, return *A*.
 9. Let *q* = *p*.

Deleted: characters

16. Let *T* be a String value equal to the substring of *S* consisting of the **elements** at positions *p* (inclusive) through *s* (exclusive).
17. Call the **[[DefineOwnProperty]]** internal method of *A* with arguments **ToString(*lengthA*)**, Property Descriptor **{[[Value]]: *T*, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}**, and **false**.
- 18. Assert: the previous step will never result in an abrupt completion.**

Deleted: characters

19. Return *A*.

The abstract operation *SplitMatch* takes three parameters, a String *S*, an integer *q*, and a String or RegExp *R*, and performs the following in order to return a MatchResult (see 15.10.2.1):

1. If *R* has a **[[NativeBrand]]** internal property whose value is **NativeRegExp**, then
 - a. Call the **[[Match]]** internal method of *R* giving it the arguments *S* and *q*, and return the MatchResult result.
2. Type(*R*) must be String. Let *r* be the number of **elements** in *R*.
3. Let *s* be the number of **elements** in *S*.
4. If *q+r* > *s* then return the MatchResult **failure**.
5. If there exists an integer *i* between 0 (inclusive) and *r* (exclusive) such that the **code unit** at position *q+i* of *S* is different from the **code unit** at position *i* of *R*, then return **failure**.
6. Let *cap* be an empty array of captures (see 15.10.2.1).
7. Return the State (*q+r*, *cap*). (see 15.10.2.1)

Deleted: the

Deleted: IsRegExp

Deleted: is a RegExp object (its **[[Class]]** is "**RegExp**")

Deleted: characters

Deleted: characters

Deleted: character

Deleted: character

Comment [AWB7127]: TODO: Probably needs some Completion Record work, assume that **[[Match]]** can fail

The **length** property of the **split** method is 2.

NOTE 1 The **split** method ignores the value of separator **.global** for separators that are RegExp objects.

NOTE 2 The **split** function is intentionally generic; it does not require that its **this** value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.15 String.prototype.substring (start, end)

The **substring** method takes two arguments, *start* and *end*, and returns a substring of the result of converting this object to a String, starting from element position *start* and running to, but not including, element position *end* of the String (or through the end of the String if *end* is **undefined**). The result is a String value, not a String object.

If either argument is **NaN** or negative, it is replaced with zero; if either argument is larger than the length of the String, it is replaced with the length of the String.

If *start* is larger than *end*, they are swapped.

The following steps are taken:

1. [ReturnIfAbrupt\(CheckObjectCoercible\(this value\)\)](#).
2. Let *S* be the result of calling `ToString`, giving it the **this** value as its argument.
3. [ReturnIfAbrupt\(*S*\)](#).
4. Let *len* be the number of elements in *S*.
5. Let *intStart* be `ToInteger(start)`.
6. If *end* is **undefined**, let *intEnd* be *len*; else let *intEnd* be `ToInteger(end)`.
7. Let *finalStart* be `min(max(intStart, 0), len)`.
8. Let *finalEnd* be `min(max(intEnd, 0), len)`.
9. Let *from* be `min(finalStart, finalEnd)`.
10. Let *to* be `max(finalStart, finalEnd)`.
11. Return a String whose length is *to* - *from*, containing code units from *S*, namely the code units with indices *from* through *to* - 1, in ascending order.

The **length** property of the **substring** method is 2.

NOTE The **substring** function is intentionally generic; it does not require that its **this** value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.16 String.prototype.toLowerCase ()

This function interprets a string value as a sequence of code points, as described in 8.4. The following steps are taken:

1. [ReturnIfAbrupt\(CheckObjectCoercible\(this value\)\)](#).
2. Let *S* be the result of calling `ToString`, giving it the **this** value as its argument.
3. [ReturnIfAbrupt\(*S*\)](#).
4. Let *cpList* be a List containing in order the code points as defined in 8.4 of *S*, starting at the first element of *S*.
5. For each code point *c* in *cpList*, if the Unicode Character Database provides a language insensitive lower case equivalent of *c* then replace *c* in *cpList* with that equivalent code point(s).
6. Let *cuList* be a new List.
7. For each code point *c* in *cpList*, in order, append to *cuList* the elements of the UTF-16 Encoding (clause 6) of *c*.
8. Let *L* be a String whose elements are, in order, the elements of *cuList*.
9. Return *L*.

The result must be derived according to the case mappings in the Unicode character database (this explicitly includes not only the `UnicodeData.txt` file, but also the `SpecialCasings.txt` file that accompanies it).

NOTE 1 The case mapping of some code points may produce multiple code points. In this case the result String may not be the same length as the source String. Because both `toUpperCase` and `toLowerCase` have context-sensitive behaviour, the functions are not symmetrical. In other words, `s.toUpperCase().toLowerCase()` is not necessarily equal to `s.toLowerCase()`.

NOTE 2 The `toLowerCase` function is intentionally generic; it does not require that its **this** value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

Deleted: character
Deleted: character

Deleted: Call `CheckObjectCoercible` passing the **this** value as its argument.

Deleted: characters

Deleted: characters
Deleted: characters

Deleted: Call `CheckObjectCoercible` passing the **this** value as its argument.

Deleted: replace

Deleted: where each character of *L* is either the Unicode lowercase equivalent of the corresponding character of *S* or the actual corresponding character of *S* if no Unicode lowercase equivalent exists

Deleted: For the purposes of this operation, the 16-bit code units of the Strings are treated as code points in the Unicode Basic Multilingual Plane. Surrogate code points are directly transferred from *S* to *L* without any mapping.

Deleted: in Unicode 2.1.8 and later

Deleted: characters

Deleted: characters

15.5.4.17 String.prototype.toLocaleLowerCase ()

[This function interprets a string value as a sequence of code points, as described in 8.4.](#)

This function works exactly the same as `toLowerCase` except that its result is intended to yield the correct result for the host environment's current locale, rather than a locale-independent result. There will only be a difference in the few cases (such as Turkish) where the rules for that language conflict with the regular Unicode case mappings.

NOTE 1 The first parameter to this function is likely to be used in a future version of this standard; it is recommended that implementations do not use this parameter position for anything else.

NOTE 2 The `toLocaleLowerCase` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.18 String.prototype.toUpperCase ()

[This function interprets a string value as a sequence of code points, as described in 8.4.](#)

This function behaves in exactly the same way as `String.prototype.toLowerCase`, except that [code points](#) are mapped to their *uppercase* equivalents as specified in the Unicode Character Database.

Deleted: characters

NOTE The `toUpperCase` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.19 String.prototype.toLocaleUpperCase ()

[This function interprets a string value as a sequence of code points, as described in 8.4.](#)

This function works exactly the same as `toUpperCase` except that its result is intended to yield the correct result for the host environment's current locale, rather than a locale-independent result. There will only be a difference in the few cases (such as Turkish) where the rules for that language conflict with the regular Unicode case mappings.

NOTE 1 The first parameter to this function is likely to be used in a future version of this standard; it is recommended that implementations do not use this parameter position for anything else.

NOTE 2 The `toLocaleUpperCase` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.20 String.prototype.trim ()

[This function interprets a string value as a sequence of code points, as described in 8.4.](#)

The following steps are taken:

1. [ReturnIfAbrupt\(CheckObjectCoercible\(this value\)\)](#).
2. Let *S* be the result of calling `ToString`, giving it the `this` value as its argument.
3. [ReturnIfAbrupt\(*S*\)](#).
4. Let *T* be a String value that is a copy of *S* with both leading and trailing white space removed. The definition of white space is the union of `WhiteSpace` and `LineTerminator`. [When determining whether a Unicode character is in Unicode general category “Zs”, code unit sequences are interpreted as UTF-16 encoded code point sequences as specified in 8.4.](#)
5. Return *T*.

Deleted: Call `CheckObjectCoercible` passing the `this` value as its argument.

NOTE The `trim` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.21 String.prototype.repeat (count)

The following steps are taken:

1. ReturnIfAbrupt(CheckObjectCoercible(**this** value)).
2. Let *S* be the result of calling ToString, giving it the **this** value as its argument.
3. ReturnIfAbrupt(*S*).
4. Let *n* be the result of calling ToInteger(*count*).
5. ReturnIfAbrupt(*n*).
6. If *n* ≤ 0, then throw a RangeError exception.
7. If *n* is +∞, then throw a RangeError exception.
8. Let *T* be a String value that is made from *n* copies of *S* appended together.
9. Return *T*.

NOTE 1 This method creates a String consisting of the string elements of this object (converted to String) repeated *count* time.

NOTE 2 The repeat function is intentionally generic; it does not require that its **this** value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.22 String.prototype.startsWith (searchString [, position])

The following steps are taken:

1. ReturnIfAbrupt(CheckObjectCoercible(**this** value)).
2. Let *S* be the result of calling ToString, giving it the **this** value as its argument.
3. ReturnIfAbrupt(*S*).
4. Let *searchStr* be ToString(*searchString*).
5. ReturnIfAbrupt(*searchStr*).
6. Let *pos* be ToInteger(*position*). (If *position* is undefined, this step produces the value 0.)
7. ReturnIfAbrupt(*pos*).
8. Let *len* be the number of elements in *S*.
9. Let *start* be min(max(*pos*, 0), *len*).
10. Let *searchLength* be the number of elements in *searchString*.
11. If *searchLength*+*start* is greater than *len*, return false.
12. If the *searchLength* sequence of elements of *S* starting at *start* is the same as the full element sequence of *searchString*, return true.
13. Otherwise, return false.

The **length** property of the **startsWith** method is 1.

NOTE 1 This method returns true if the sequence of elements of *searchString* converted to a String is the same as the corresponding elements of this object (converted to a String) starting at *position*. Otherwise returns false.

NOTE 2 The **startsWith** function is intentionally generic; it does not require that its **this** value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.23 String.prototype.endsWith (searchString [, endPosition])

The following steps are taken:

1. ReturnIfAbrupt(CheckObjectCoercible(**this** value)).
2. Let *S* be the result of calling ToString, giving it the **this** value as its argument.
3. ReturnIfAbrupt(*S*).
4. Let *searchStr* be ToString(*searchString*).
5. ReturnIfAbrupt(*searchStr*).
6. Let *len* be the number of elements in *S*.
7. If *endPosition* is undefined, let *pos* be *len*, else let *pos* be ToInteger(*endPosition*).
8. ReturnIfAbrupt(*pos*).
9. Let *end* be min(max(*pos*, 0), *len*).

Comment [AWB7128]: Is this the right error handling?

Deleted: characters

10. Let `searchLength` be the number of elements in `searchString`.
11. Let `start` be `end - searchLength`.
12. If `start` is less than 0, return `false`.
13. If the `searchLength` sequence of elements of `S` starting at `start` is the same as the full element sequence of `searchString`, return `true`.
14. Otherwise, return `false`.

Deleted: characters

Deleted: characters

Deleted: character

The `length` property of the `endsWith` method is 1.

NOTE 1 Returns `true` if the sequence of elements of `searchString` converted to a String is the same as the corresponding elements of this object (converted to a String) starting at `endPosition - length(this)`. Otherwise returns `false`.

Deleted: characters

Deleted: characters

NOTE 2 The `endsWith` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.24 String.prototype.contains (searchString [, position])

The `contains` method takes two arguments, `searchString` and `position`, and performs the following steps:

1. `ReturnIfAbrupt(CheckObjectCoercible(this value))`.
2. Let `S` be the result of calling `ToString`, giving it the `this` value as its argument.
3. `ReturnIfAbrupt(S)`.
4. Let `searchStr` be `ToString(searchString)`.
5. `ReturnIfAbrupt(searchStr)`.
6. Let `pos` be `ToInteger(position)`. (If `position` is `undefined`, this step produces the value 0).
7. `ReturnIfAbrupt(pos)`.
8. Let `len` be the number of elements in `S`.
9. Let `start` be `min(max(pos, 0), len)`.
10. Let `searchLen` be the number of characters in `searchStr`.
11. If there exists any integer `k` not smaller than `start` such that `k + searchLen` is not greater than `len`, and for all nonnegative integers `j` less than `searchLen`, the character at position `k+j` of `S` is the same as the character at position `j` of `searchStr`, return `true`; but if there is no such integer `k`, return `false`.

Deleted: characters

The `length` property of the `contains` method is 1.

NOTE 1 If `searchString` appears as a substring of the result of converting this object to a String, at one or more positions that are greater than or equal to `position`, then return `true`; otherwise, returns `false`. If `position` is `undefined`, 0 is assumed, so as to search all of the String.

NOTE 2 The `contains` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

15.5.4.25 String.prototype.codePointAt (pos)

NOTE Returns a Number (a nonnegative integer less than 1114112) that is the UTF-16 encoded code point value starting at the string element at position `pos` in the String resulting from converting this object to a String. If there is no element at that position, the result is `Nan`. If a valid UTF-16 surrogate pair does not begin at `pos`, the result is the code unit at `pos`.

Comment [AWB9129]: Do we also need `UnicodeCharAt` that returns a string of length 1 or 2?

Deleted: dsa

When the `codePointAt` method is called with one argument `pos`, the following steps are taken:

1. `ReturnIfAbrupt(CheckObjectCoercible(this value))`.
2. Let `S` be the result of calling `ToString`, giving it the `this` value as its argument.
3. `ReturnIfAbrupt(S)`.
4. Let `position` be `ToInteger(pos)`.
5. `ReturnIfAbrupt(position)`.
6. Let `size` be the number of elements in `S`.
7. If `position < 0` or `position > size`, return `undefined`.
8. Let `first` be the code unit value of the element at index `position` in the String `S`.
9. If `first < 0xD800` or `first > 0xDBFF` or `position+1 = size`, then return `first`.

Comment [AWB9130]: Note that this is inconsistent with the pre-existing behaviour of `charCodeAt` which returns `NaN` for out of bounds positions

Deleted: `NaN`

Deleted: position

Deleted: , where the first (leftmost) element in `S` is considered to be at position 0, the next one at position 1, and on

10. Let *second* be the code unit value of the element at position *position*+1 in the String *S*.

11. If *second* < 0xDC00 or *first* > 0xDFFF, then return *first*.

12. Return ((*first* - 0xD800) × 1024) + (*second* - 0xDC00) + 0x10000.

NOTE The `codePointAt` function is intentionally generic; it does not require that its `this` value be a String object. Therefore it can be transferred to other kinds of objects for use as a method.

15.5.5 Properties of String Instances

String instances inherit properties from the String prototype object and have a `[[NativeBrand]]` internal property with value `StringWrapper`. String instances also have a `[[PrimitiveValue]]` internal property, a `length` property, and a set of enumerable properties with array index names.

The `[[PrimitiveValue]]` internal property is the String value represented by this String object. The array index named properties correspond to the individual `elements` of the String value. A special `[[GetOwnProperty]]` internal method is used to specify the number, values, and attributes of the array index named properties.

15.5.5.1 length

The number of `elements` in the String value represented by this String object.

Once a String object is created, this property is unchanging. It has the attributes { `[[Writable]]: false`, `[[Enumerable]]: false`, `[[Configurable]]: false` }.

15.5.5.2 `[[GetOwnProperty]](P)`

String objects use a variation of the `[[GetOwnProperty]]` internal method used for other native ECMAScript objects (8.12.1). This special internal method provides access to named properties corresponding to the individual `elements` of String objects.

Assume *S* is a String object and *P* is a String.

When the `[[GetOwnProperty]]` internal method of *S* is called with property name *P*, the following steps are taken:

1. Let *desc* be the result of calling the default `[[GetOwnProperty]]` internal method (8.12.1) on *S* with argument *P*.
2. If *desc* is not `undefined` return *desc*.
3. If `ToString(abs(ToInteger(P)))` is not the same value as *P*, return `undefined`.
4. Let *str* be the String value of the `[[PrimitiveValue]]` internal property of *S*.
5. Let *index* be `ToInteger(P)`.
6. Let *len* be the number of `elements` in *str*.
7. If *len* ≤ *index*, return `undefined`.
8. Let *resultStr* be a String of length 1, containing one `code unit` from *str*, specifically the `code unit` at position *index*, where the first (leftmost) `element` in *str* is considered to be at position 0, the next one at position 1, and so on.
9. Return a Property Descriptor { `[[Value]]: resultStr`, `[[Enumerable]]: true`, `[[Writable]]: false`, `[[Configurable]]: false` }

15.6 Boolean Objects

15.6.1 The Boolean Constructor Called as a Function

When `Boolean` is called as a function rather than as a constructor, it performs a type conversion.

15.6.1.1 Boolean (*value*)

Returns a Boolean value (not a Boolean object) computed by `ToBoolean(value)`.

Deleted: `charCode`

Deleted: 15.5.4.25 `String.prototype.toArray()`

The following steps are taken:
 ↪ ReturnIfAbrupt(CheckObjectCoercible(this value)).
 ↪ Let *S* be the result of calling `ToString`, giving this value as its argument.
 ↪ ReturnIfAbrupt(*S*).
 ↪ Let *len* be the number of characters in *S*.
 ↪ Let *array* be the result of the abstraction operation `ArrayCreate` (15.4) with argument *len*.
 ↪ Let *n* be 0.
 ↪ Repeat, while *n* < *len*:
 ↪ Let *c* be the character at position *n* in *S*.
 ↪ Call the `[[DefineOwnProperty]]` internal method of *array* with arguments `ToString(n)`, the `PropertyDescriptor` { `[[Value]]: c`, `[[Writable]]: true`, `[[Enumerable]]: true`, `[[Configurable]]: true` }, and `false`.
 ↪ Increment *n* by 1.
 ↪ Return *array*.

The `length` property of the `toArray` method is
NOTE 1 . Returns an Array object with elements corresponding to the characters of this object (converted to a String).
NOTE 2 The `toArray` function is intentionally generic; it does not require that its `this` value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

Deleted: their `[[Class]]`

Deleted: `IsString`

Deleted: `value is "String"`

Deleted: `characters`

Deleted: `characters`

Deleted: `characters`

Deleted: `characters`

Deleted: `character`

Deleted: `character`

Deleted: `character`

15.6.2 The Boolean Constructor

When `Boolean` is called as part of a `new` expression it is a constructor: it initialises the newly created object.

15.6.2.1 new Boolean (value)

The `[[Prototype]]` internal property of the newly constructed object is set to the original Boolean prototype object, the one that is the initial value of `Boolean.prototype` (15.6.3.1).

The newly constructed Boolean object has a `[[NativeBrand]]` internal property with value `BooleanWrapper`.

The `[[PrimitiveValue]]` internal property of the newly constructed Boolean object is set to `ToBoolean(value)`.

The `[[Extensible]]` internal property of the newly constructed object is set to `true`.

Deleted: `[[Class]]` internal property of the

Deleted: is set to "Boolean"

Deleted: `IsBoolean`

15.6.3 Properties of the Boolean Constructor

The value of the `[[Prototype]]` internal property of the Boolean constructor is the Function prototype object (15.3.4).

Besides the internal properties and the `length` property (whose value is `1`), the Boolean constructor has the following property:

15.6.3.1 Boolean.prototype

The initial value of `Boolean.prototype` is the Boolean prototype object (15.6.4).

This property has the attributes `{ [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }`.

15.6.4 Properties of the Boolean Prototype Object

The Boolean prototype object is itself a Boolean object whose value is `false`. The Boolean prototype object has a `[[NativeBrand]]` internal property whose value is `BooleanWrapper`.

Deleted: (its `[[Class]]` is "Boolean")

Deleted: `IsBoolean`

The value of the `[[Prototype]]` internal property of the Boolean prototype object is the standard built-in Object prototype object (15.2.4).

15.6.4.1 Boolean.prototype.constructor

The initial value of `Boolean.prototype.constructor` is the built-in `Boolean` constructor.

15.6.4.2 Boolean.prototype.toString ()

The following steps are taken:

1. Let `B` be the `this` value.
2. If `Type(B)` is Boolean, then let `b` be `B`.
3. Else if `Type(B)` is Object and `B` has a `[[NativeWrapper]]` internal property whose value is `BooleanWrapper`, then let `b` be the value of the `[[PrimitiveValue]]` internal property of `B`.
4. Else throw a `TypeError` exception.
5. If `b` is `true`, then return "`true`"; else return "`false`".

Deleted: the value of the `[[Class]]` internal property of

Deleted: is "Boolean"

Deleted: `IsBoolean`

15.6.4.3 Boolean.prototype.valueOf ()

The following steps are taken:

1. Let `B` be the `this` value.
2. If `Type(B)` is Boolean, then let `b` be `B`.

3. Else if Type(*B*) is Object and *B* has a [[NativeWrapper]] internal property whose value is BooleanWrapper, then let *b* be the value of the [[PrimitiveValue]] internal property of *B*.
4. Else throw a **TypeError** exception.
5. Return *b*.

Deleted: the value of the [[Class]] internal property of
Deleted: is "Boolean"
Deleted: IsBoolean

15.6.5 Properties of Boolean Instances

Boolean instances inherit properties from the Boolean prototype object and have a [[NativeBrand]] internal property whose value is BooleanWrapper. Boolean instances also have a [[PrimitiveValue]] internal property.

The [[PrimitiveValue]] internal property is the Boolean value represented by this Boolean object.

Deleted: their
Deleted: Class
Deleted: IsBoolean
Deleted: value is "Boolean"

15.7 Number Objects

15.7.1 The Number Constructor Called as a Function

When **Number** is called as a function rather than as a constructor, it performs a type conversion.

15.7.1.1 Number ([value])

Returns a Number value (not a Number object) computed by `ToNumber(value)` if *value* was supplied, else returns `+0`.

15.7.2 The Number Constructor

When **Number** is called as part of a `new` expression it is a constructor: it initialises the newly created object.

15.7.2.1 new Number ([value])

The [[Prototype]] internal property of the newly constructed object is set to the original Number prototype object, the one that is the initial value of `Number.prototype` (15.7.3.1).

Deleted: [[Class]] internal property of the
Deleted: set to "Number"
Deleted: IsNumber

The newly constructed object is has a [[NativeBrand]] internal property whose value is NumberWrapper.

The [[PrimitiveValue]] internal property of the newly constructed object is set to `ToNumber(value)` if *value* was supplied, else to `+0`.

The [[Extensible]] internal property of the newly constructed object is set to `true`.

15.7.3 Properties of the Number Constructor

The value of the [[Prototype]] internal property of the Number constructor is the Function prototype object (15.3.4).

Besides the internal properties and the `length` property (whose value is `1`), the Number constructor has the following properties:

15.7.3.1 Number.prototype

The initial value of `Number.prototype` is the Number prototype object (15.7.4).

This property has the attributes { [[Writable]]: `false`, [[Enumerable]]: `false`, [[Configurable]]: `false` }.

15.7.3.2 Number.MAX_VALUE

The value of `Number.MAX_VALUE` is the largest positive finite value of the Number type, which is approximately $1.7976931348623157 \times 10^{308}$.

This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.7.3.3 Number.MIN_VALUE

The value of **Number.MIN_VALUE** is the smallest positive value of the Number type, which is approximately 5×10^{-324} .

In the IEEE-764 double precision binary representation, the smallest possible value is a denormalized number. If an implementation does not support denormalized values, the value of **Number.MIN_VALUE** must be the smallest non-zero positive value that can actually be represented by the implementation.

This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.7.3.4 Number.NaN

The value of **Number.NaN** is **NaN**.

This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.7.3.5 Number.NEGATIVE_INFINITY

The value of **Number.NEGATIVE_INFINITY** is $-\infty$.

This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.7.3.6 Number.POSITIVE_INFINITY

The value of **Number.POSITIVE_INFINITY** is $+\infty$.

This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.7.3.7 Number.EPSILON

The value of **Number.EPSILON** is the difference between 1 and the smallest value greater than 1 that is representable as a Number value, which is approximately $2.2204460492503130808472633361816 \times 10^{-16}$.

This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.7.3.8 Number.MAX_INTEGER

Deleted: 7

The value of **Number.MAX_INTEGER** is the largest integer value that can be represented as a Number value without losing precision, which is 9007199254740991.

This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.7.3.9 Number.parseInt (string, radix)

Deleted: 8

Same as 15.1.2.2.

15.7.3.10 Number.parseFloat (string)

Comment [AWB7131]: Same specification or same value?

Same as 15.1.2.3.

Deleted: 9

15.7.3.11 Number.isNaN (number)

Comment [AWB7132]: Same specification or same value?

When the **Number.isNaN** is called with one argument *number*, the following steps are taken:

1. If Type(*number*) is not Number, return false.

2. If *number* is NaN, return true.
3. Otherwise, return false.

NOTE This function differs from the global isNaN function (15.1.2.4) in that it does not convert its argument to a Number before determining whether it is NaN.

15.7.3.12 Number.isFinite (*number*)

When the `Number.isFinite` is called with one argument *number*, the following steps are taken:

1. If Type(*number*) is not Number, return false.
2. If *number* is NaN, +∞ or -∞, return false.
3. Otherwise, return true.

15.7.3.13 Number.isInteger (*number*)

When the `Number.isInteger` is called with one argument *number*, the following steps are taken:

1. If Type(*number*) is not Number, return false.
2. Let *integer* be ToInteger(*number*).
3. If *integer* is not equal to *number*, return false.
4. Otherwise, return true.

15.7.3.14 Number.toInt (*number*)

When the `Number.toInt` is called with one argument *number*, the following steps are taken:

1. Return ToInteger(*number*).

15.7.4 Properties of the Number Prototype Object

The Number prototype object is itself a Number object with a [[NativeBrand]] internal property whose value is NumberWrapper. Its value is +0.

The value of the [[Prototype]] internal property of the Number prototype object is the standard built-in Object prototype object (15.2.4).

Unless explicitly stated otherwise, the methods of the Number prototype object defined below are not generic and the this value passed to them must be either a Number value or an object that has a [[NativeBrand]] internal property whose value is NumberWrapper.

In the following descriptions of functions that are properties of the Number prototype object, the phrase "this Number object" refers to either the object that is the this value for the invocation of the function or, if Type(this value) is Number, an object that is created as if by the expression new Number (this value) where Number is the standard built-in constructor with that name. Also, the phrase "this Number value" refers to either the Number value represented by this Number object, that is, the value of the [[PrimitiveValue]] internal property of this Number object or the this value if its type is Number. A TypeError exception is thrown if the this value is neither an object that has a [[NativeBrand]] internal property whose value is NumberWrapper or a value whose type is Number.

15.7.4.1 Number.prototype.constructor

The initial value of `Number.prototype.constructor` is the built-in `Number` constructor.

15.7.4.2 Number.prototype.toString ([radix])

The optional *radix* should be an integer value in the inclusive range 2 to 36. If *radix* not present or is undefined the Number 10 is used as the value of *radix*. If ToInteger(*radix*) is the Number 10 then this Number value is given as an argument to the ToString abstract operation; the resulting String value is returned.

Deleted: 1

Deleted: 2

Comment [AWB7133]: Name changed from toInt to Marcdh 29 TC39 meeting

Deleted: 3

Deleted: eger

Deleted: (its [[Class]] is "Number")

Deleted: IsNumber

Deleted: whose

Deleted: Object

Deleted: for which the value of

Deleted: the

Deleted: Class

Deleted: IsNumber

Deleted: is "Number"

Deleted: for which the value of the

Deleted: n

Deleted: Class

Deleted: IsNumber

Deleted: is "Number"

Comment [AWB7134]: TODO: need to private algorithm that ordered abnormal completion detection

If `ToInteger(radix)` is not an integer between 2 and 36 inclusive throw a `RangeError` exception. If `ToInteger(radix)` is an integer from 2 to 36, but not 10, the result is a String representation of this Number value using the specified radix. Letters `a-z` are used for digits with values 10 through 35. The precise algorithm is implementation-dependent if the radix is not 10, however the algorithm should be a generalisation of that specified in 9.8.1.

The `toString` function is not generic; it throws a `TypeError` exception if its `this` value is not a Number or a Number object. Therefore, it cannot be transferred to other kinds of objects for use as a method.

15.7.4.3 Number.prototype.toLocaleString()

Produces a String value that represents this Number value formatted according to the conventions of the host environment's current locale. This function is implementation-dependent, and it is permissible, but not encouraged, for it to return the same thing as `toString`.

NOTE The first parameter to this function is likely to be used in a future version of this standard; it is recommended that implementations do not use this parameter position for anything else.

15.7.4.4 Number.prototype.valueOf()

1. Let `x` be this Number value.
2. Return `x`.

The `valueOf` function is not generic; it throws a `TypeError` exception if its `this` value is not a Number or a Number object. Therefore, it cannot be transferred to other kinds of objects for use as a method.

Deleted: Returns this Number value. ¶

15.7.4.5 Number.prototype.toFixed (fractionDigits)

Return a String containing this Number value represented in decimal fixed-point notation with `fractionDigits` digits after the decimal point. If `fractionDigits` is `undefined`, 0 is assumed. Specifically, perform the following steps:

3. Let `f` be `ToInteger(fractionDigits)`. (If `fractionDigits` is `undefined`, this step produces the value 0).
4. ReturnIfAbrupt(f).
5. If `f < 0` or `f > 20`, throw a `RangeError` exception.
6. Let `x` be this Number value.
7. ReturnIfAbrupt(x).
8. If `x` is `NaN`, return the String "`NaN`".
9. Let `s` be the empty String.
10. If `x < 0`, then
 - a. Let `s` be `"-"`.
 - b. Let `x = -x`.
11. If `x ≥ 1021`, then
 - a. Let `m` = `ToString(x)`.
12. Else, `x < 1021`
 - a. Let `n` be an integer for which the exact mathematical value of $n \div 10^f - x$ is as close to zero as possible. If there are two such `n`, pick the larger `n`.
 - b. If `n = 0`, let `m` be the String "`0`". Otherwise, let `m` be the String consisting of the digits of the decimal representation of `n` (in order, with no leading zeroes).
 - c. If `f ≠ 0`, then
 - i. Let `k` be the number of elements in `m`.
 - ii. If `k ≤ f`, then
 1. Let `z` be the String consisting of $f+1-k$ occurrences of the code unit 0x0030.
 2. Let `m` be the concatenation of Strings `z` and `m`.
 3. Let `k = f + 1`.
 - iii. Let `a` be the first $k-f$ elements of `m`, and let `b` be the remaining f elements of `m`.
 - iv. Let `m` be the concatenation of the three Strings `a`, `"."`, and `b`.
13. Return the concatenation of the Strings `s` and `m`.

Deleted: characters

Deleted: character

Deleted: '`0`'

Deleted: characters

Deleted: characters

The `length` property of the `toFixed` method is 1.

If the `toFixed` method is called with more than one argument, then the behaviour is undefined (see clause 15).

An implementation is permitted to extend the behaviour of `toFixed` for values of `fractionDigits` less than 0 or greater than 20. In this case `toFixed` would not necessarily throw `RangeError` for such values.

NOTE The output of `toFixed` may be more precise than `toString` for some values because `toString` only prints enough significant digits to distinguish the number from adjacent number values. For example, `(1000000000000000128).toString()` returns "1000000000000000100", while `(1000000000000000128).toFixed(0)` returns "1000000000000000128".

15.7.4.6 Number.prototype.toExponential (fractionDigits)

Return a String containing this Number value represented in decimal exponential notation with one digit before the significand's decimal point and `fractionDigits` digits after the significand's decimal point. If `fractionDigits` is `undefined`, include as many significand digits as necessary to uniquely specify the Number (just like in `ToString` except that in this case the Number is always output in exponential notation). Specifically, perform the following steps:

1. Let x be this Number value.
2. ReturnIfAbrupt(x).
3. Let f be `ToInteger(fractionDigits)`.
4. ReturnIfAbrupt(f).
5. If x is `NaN`, return the String "`NaN`".
6. Let s be the empty String.
7. If $x < 0$, then
 - a. Let s be `"-"`.
 - b. Let $x = -x$.
8. If $x = +\infty$, then
 - a. Return the concatenation of the Strings s and "`Infinity`".
9. If `fractionDigits` is not `undefined` and ($f < 0$ or $f > 20$), throw a `RangeError` exception.
10. If $x = 0$, then
 - a. If `fractionDigits` is `undefined`, then let $f = 0$.
 - b. Let m be the String consisting of $f+1$ occurrences of the `code unit 0x0030`.
 - c. Let $e = 0$.
11. Else, $x \neq 0$
 - a. If `fractionDigits` is not `undefined`, then
 - i. Let e and n be integers such that $10^f \leq n < 10^{f+1}$ and for which the exact mathematical value of $n \times 10^{e-f} - x$ is as close to zero as possible. If there are two such sets of e and n , pick the e and n for which $n \times 10^{e-f}$ is larger.
 - b. Else, `fractionDigits` is `undefined`
 - i. Let e , n , and f be integers such that $f \geq 0$, $10^f \leq n < 10^{f+1}$, the number value for $n \times 10^{e-f}$ is x , and f is as small as possible. Note that the decimal representation of n has $f+1$ digits, n is not divisible by 10, and the least significant digit of n is not necessarily uniquely determined by these criteria.
 - c. Let m be the String consisting of the digits of the decimal representation of n (in order, with no leading zeroes).
12. If $f \neq 0$, then
 - a. Let a be the first `element` of m , and let b be the remaining `elements` of m .
 - b. Let m be the concatenation of the three Strings a , `"."`, and b .
13. If $e = 0$, then
 - a. Let $c = "+"$.
 - b. Let $d = "0"$.
14. Else
 - a. If $e > 0$, then let $c = "+"$.
 - b. Else, $e \leq 0$

Deleted: `al`
Deleted: `Let`
Deleted: character
Deleted: `'0'`

Deleted: character
Deleted: characters

- i. Let $c = "-".$
 - ii. Let $e = -e.$
 - c. Let d be the String consisting of the digits of the decimal representation of e (in order, with no leading zeroes).
15. Let m be the concatenation of the four Strings m , " e ", c , and d .
16. Return the concatenation of the Strings s and m .

The `length` property of the `toExponential` method is 1.

If the `toExponential` method is called with more than one argument, then the behaviour is undefined (see clause 15).

An implementation is permitted to extend the behaviour of `toExponential` for values of `fractionDigits` less than 0 or greater than 20. In this case `toExponential` would not necessarily throw `RangeError` for such values.

NOTE For implementations that provide more accurate conversions than required by the rules above, it is recommended that the following alternative version of step 9.b.i be used as a guideline:

- i. Let e , n , and f be integers such that $f \geq 0$, $10^f \leq n < 10^{f+1}$, the number value for $n \times 10^{e+f}$ is x , and f is as small as possible. If there are multiple possibilities for n , choose the value of n for which $n \times 10^{e+f}$ is closest in value to x . If there are two such possible values of n , choose the one that is even.

15.7.4.7 Number.prototype.toPrecision (precision)

Return a String containing this Number value represented either in decimal exponential notation with one digit before the significand's decimal point and `precision`-1 digits after the significand's decimal point or in decimal fixed notation with `precision` significant digits. If `precision` is `undefined`, call `ToString` (9.8.1) instead. Specifically, perform the following steps:

1. Let x be this Number value.
2. ReturnIfAbrupt(x).
3. If `precision` is `undefined`, return `ToString(x)`.
4. Let p be `ToInteger(precision)`.
5. ReturnIfAbrupt(p).
6. If x is `NaN`, return the String "`NaN`".
7. Let s be the empty String.
8. If $x < 0$, then
 - a. Let s be `"-".`
 - b. Let $x = -x.$
9. If $x = +\infty$, then
 - a. Return the concatenation of the Strings s and "`Infinity`".
10. If $p < 1$ or $p > 21$, throw a `RangeError` exception.
11. If $x = 0$, then
 - a. Let m be the String consisting of p occurrences of the [code unit 0x0030 \(the Unicode character '0'\)](#).
 - b. Let $e = 0.$
12. Else $x \neq 0$,
 - a. Let e and n be integers such that $10^{p-1} \leq n < 10^p$ and for which the exact mathematical value of $n \times 10^{e-p+1} - x$ is as close to zero as possible. If there are two such sets of e and n , pick the e and n for which $n \times 10^{e-p+1}$ is larger.
 - b. Let m be the String consisting of the digits of the decimal representation of n (in order, with no leading zeroes).
 - c. If $e < -6$ or $e \geq p$, then
 - i. Let a be the first [element](#) of m , and let b be the remaining $p-1$ [elements](#) of m .
 - ii. Let m be the concatenation of the three Strings a , `"."`, and b .
 - iii. If $e = 0$, then
 1. Let $c = "+"$ and $d = "0".$
 - iv. Else $e \neq 0$,
 1. If $e > 0$, then

Deleted: character

Deleted: character

Deleted: characters

- a Let $c = "+".$
2. Else $e < 0,$
a Let $c = "-".$
b Let $e = -e.$
3. Let d be the String consisting of the digits of the decimal representation of e (in order, with no leading zeroes).
- v. Let m be the concatenation of the five Strings $s, m, "e", c$, and d .
13. If $e = p-1$, then return the concatenation of the Strings s and m .
14. If $e \geq 0$, then
a. Let m be the concatenation of the first $e+1$ elements of m , the code unit 0x002E (Unicode character ‘.’), and the remaining $p-(e+1)$ elements of m .
15. Else $e < 0,$
a. Let m be the concatenation of the String " $0 .$ ", $-(e+1)$ occurrences of code unit 0x0030 (the Unicode character ‘0’), and the String m .
16. Return the concatenation of the Strings s and m .

The `length` property of the `toPrecision` method is 1.

If the `toPrecision` method is called with more than one argument, then the behaviour is undefined (see clause 15).

An implementation is permitted to extend the behaviour of `toPrecision` for values of *precision* less than 1 or greater than 21. In this case `toPrecision` would not necessarily throw `RangeError` for such values.

15.7.4.8 Number.prototype.clz()

When the `Number.prototype.clz` is called with one argument *number*, the following steps are taken:

1. Let x be this `Number` value.
2. Let n be `ToUint32(x)`.
3. ReturnIfAbrupt(n).
4. Let p be the number of leading zero bits in the 32-bit binary representation of n .
5. Return p .

NOTE If n is 0, p will be 32. If the most significant bit of the 32-bit binary encoding of n is 1, p will be 0.

15.7.5 Properties of Number Instances

Number instances inherit properties from the `Number` prototype object and have a `[[NativeBrand]]` internal property whose value is `NumberWrapper`. Number instances also have a `[[PrimitiveValue]]` internal property.

The `[[PrimitiveValue]]` internal property is the `Number` value represented by this `Number` object.

15.8 The Math Object

The `Math` object is a single object that has some named properties, some of which are functions.

The value of the `[[Prototype]]` internal property of the `Math` object is the standard built-in `Object` prototype object (15.2.4). The `Math` object has a `[[NativeBrand]]` internal property whose value is `NativeMath`.

The `Math` object does not have a `[[Construct]]` internal property; it is not possible to use the `Math` object as a constructor with the `new` operator.

The `Math` object does not have a `[[Call]]` internal property; it is not possible to invoke the `Math` object as a function.

NOTE In this specification, the phrase “the `Number` value for x ” has a technical meaning defined in 8.5.

Deleted: characters
Deleted: s
Deleted: characters
Deleted: c

Comment [AWB7135]: Added at March 29 TC39 meeting

Deleted: 3
Deleted: 14

Comment [AWB7136]: Unsigned seems most general, signed values could be converted in a previous step.

Deleted: f

Deleted: their
Deleted: n
Deleted: Class
Deleted: IsNumber
Deleted: value is "Number"

Deleted: value of the `[[Class]]` internal property of the
Deleted: is "Math"
Deleted: the
Deleted: IsMath

15.8.1 Value Properties of the Math Object

15.8.1.1 E

The Number value for e , the base of the natural logarithms, which is approximately 2.7182818284590452354.

This property has the attributes { **[[Writable]]: false**, **[[Enumerable]]: false**, **[[Configurable]]: false** }.

15.8.1.2 LN10

The Number value for the natural logarithm of 10, which is approximately 2.302585092994046.

This property has the attributes { **[[Writable]]: false**, **[[Enumerable]]: false**, **[[Configurable]]: false** }.

15.8.1.3 LN2

The Number value for the natural logarithm of 2, which is approximately 0.6931471805599453.

This property has the attributes { **[[Writable]]: false**, **[[Enumerable]]: false**, **[[Configurable]]: false** }.

15.8.1.4 LOG2E

The Number value for the base-2 logarithm of e , the base of the natural logarithms; this value is approximately 1.4426950408889634.

This property has the attributes { **[[Writable]]: false**, **[[Enumerable]]: false**, **[[Configurable]]: false** }.

NOTE The value of `Math.LOG2E` is approximately the reciprocal of the value of `Math.LN2`.

15.8.1.5 LOG10E

The Number value for the base-10 logarithm of e , the base of the natural logarithms; this value is approximately 0.4342944819032518.

This property has the attributes { **[[Writable]]: false**, **[[Enumerable]]: false**, **[[Configurable]]: false** }.

NOTE The value of `Math.LOG10E` is approximately the reciprocal of the value of `Math.LN10`.

15.8.1.6 PI

The Number value for π , the ratio of the circumference of a circle to its diameter, which is approximately 3.1415926535897932.

This property has the attributes { **[[Writable]]: false**, **[[Enumerable]]: false**, **[[Configurable]]: false** }.

15.8.1.7 SQRT1_2

The Number value for the square root of $\frac{1}{2}$, which is approximately 0.7071067811865476.

This property has the attributes { **[[Writable]]: false**, **[[Enumerable]]: false**, **[[Configurable]]: false** }.

NOTE The value of `Math.SQRT1_2` is approximately the reciprocal of the value of `Math.SQRT2`.

15.8.1.8 SQRT2

The Number value for the square root of 2, which is approximately 1.4142135623730951.

This property has the attributes { **[[Writable]]: false**, **[[Enumerable]]: false**, **[[Configurable]]: false** }.

15.8.2 Function Properties of the Math Object

Each of the following `Math` object functions applies the `ToNumber` abstract operator to each of its arguments (in left-to-right order if there is more than one). If `ToNumber` returns an abrupt completion, that completion record is immediately returned. Otherwise, `function` performs a computation on the resulting Number value(s).

Deleted: and then

In the function descriptions below, the symbols `NaN`, `-0`, `+0`, `-∞` and `+∞` refer to the Number values described in 8.5.

NOTE The behaviour of the functions `acos`, `asin`, `atan`, `atan2`, `cos`, `exp`, `log`, `pow`, `sin`, `sqrt`, and `tan` is not precisely specified here except to require specific results for certain argument values that represent boundary cases of interest. For other argument values, these functions are intended to compute approximations to the results of familiar mathematical functions, but some latitude is allowed in the choice of approximation algorithms. The general intent is that an implementer should be able to use the same mathematical library for ECMAScript on a given hardware platform that is available to C programmers on that platform.

Although the choice of algorithms is left to the implementation, it is recommended (but not specified by this standard) that implementations use the approximation algorithms for IEEE 754 arithmetic contained in `fdlibm`, the freely distributable mathematical library from Sun Microsystems (<http://www.netlib.org/fdlibm>).

15.8.2.1 `abs (x)`

Returns the absolute value of x ; the result has the same magnitude as x but has positive sign.

- If x is `NaN`, the result is `NaN`.
- If x is `-0`, the result is `+0`.
- If x is `-∞`, the result is `+∞`.

15.8.2.2 `acos (x)`

Returns an implementation-dependent approximation to the arc cosine of x . The result is expressed in radians and ranges from `+0` to `+π`.

- If x is `NaN`, the result is `NaN`.
- If x is greater than `1`, the result is `NaN`.
- If x is less than `-1`, the result is `NaN`.
- If x is exactly `1`, the result is `+0`.

15.8.2.3 `asin (x)`

Returns an implementation-dependent approximation to the arc sine of x . The result is expressed in radians and ranges from `-π/2` to `+π/2`.

- If x is `NaN`, the result is `NaN`.
- If x is greater than `1`, the result is `NaN`.
- If x is less than `-1`, the result is `NaN`.
- If x is `+0`, the result is `+0`.
- If x is `-0`, the result is `-0`.

15.8.2.4 `atan (x)`

Returns an implementation-dependent approximation to the arc tangent of x . The result is expressed in radians and ranges from `-π/2` to `+π/2`.

- If x is `NaN`, the result is `NaN`.
- If x is `+0`, the result is `+0`.
- If x is `-0`, the result is `-0`.

- If x is $+\infty$, the result is an implementation-dependent approximation to $+\pi/2$.
- If x is $-\infty$, the result is an implementation-dependent approximation to $-\pi/2$.

15.8.2.5 atan2 (y , x)

Returns an implementation-dependent approximation to the arc tangent of the quotient y/x of the arguments y and x , where the signs of y and x are used to determine the quadrant of the result. Note that it is intentional and traditional for the two-argument arc tangent function that the argument named y be first and the argument named x be second. The result is expressed in radians and ranges from $-\pi$ to $+\pi$.

- If either x or y is NaN, the result is NaN.
- If $y > 0$ and $x = 0$, the result is an implementation-dependent approximation to $+\pi/2$.
- If $y > 0$ and $x = -0$, the result is an implementation-dependent approximation to $+\pi/2$.
- If $y = 0$ and $x > 0$, the result is $+0$.
- If $y = 0$ and $x = +0$, the result is $+0$.
- If $y = 0$ and $x = -0$, the result is an implementation-dependent approximation to $+\pi$.
- If $y = +0$ and $x < 0$, the result is an implementation-dependent approximation to $+\pi$.
- If $y = -0$ and $x > 0$, the result is -0 .
- If $y = -0$ and $x = +0$, the result is -0 .
- If $y = -0$ and $x = -0$, the result is an implementation-dependent approximation to $-\pi$.
- If $y < 0$ and $x < 0$, the result is an implementation-dependent approximation to $-\pi$.
- If $y < 0$ and $x = +0$, the result is an implementation-dependent approximation to $-\pi/2$.
- If $y < 0$ and $x = -0$, the result is an implementation-dependent approximation to $-\pi/2$.
- If $y > 0$ and y is finite and $x = +\infty$, the result is $+0$.
- If $y > 0$ and y is finite and $x = -\infty$, the result is an implementation-dependent approximation to $+\pi$.
- If $y < 0$ and y is finite and $x = +\infty$, the result is -0 .
- If $y < 0$ and y is finite and $x = -\infty$, the result is an implementation-dependent approximation to $-\pi$.
- If $y = +\infty$ and x is finite, the result is an implementation-dependent approximation to $+\pi/2$.
- If $y = -\infty$ and x is finite, the result is an implementation-dependent approximation to $-\pi/2$.
- If $y = +\infty$ and $x = +\infty$, the result is an implementation-dependent approximation to $+\pi/4$.
- If $y = +\infty$ and $x = -\infty$, the result is an implementation-dependent approximation to $+3\pi/4$.
- If $y = -\infty$ and $x = +\infty$, the result is an implementation-dependent approximation to $-\pi/4$.
- If $y = -\infty$ and $x = -\infty$, the result is an implementation-dependent approximation to $-3\pi/4$.

15.8.2.6 ceil (x)

Returns the smallest (closest to $-\infty$) Number value that is not less than x and is equal to a mathematical integer. If x is already an integer, the result is x .

- If x is NaN, the result is NaN.
- If x is $+0$, the result is $+0$.
- If x is -0 , the result is -0 .
- If x is $+\infty$, the result is $+\infty$.
- If x is $-\infty$, the result is $-\infty$.
- If x is less than 0 but greater than -1 , the result is -0 .

The value of `Math.ceil(x)` is the same as the value of `-Math.floor(-x)`.

15.8.2.7 cos (x)

Returns an implementation-dependent approximation to the cosine of x . The argument is expressed in radians.

- If x is NaN, the result is NaN.
- If x is $+0$, the result is 1 .
- If x is -0 , the result is 1 .
- If x is $+\infty$, the result is NaN.
- If x is $-\infty$, the result is NaN.

15.8.2.8 `exp (x)`

Returns an implementation-dependent approximation to the exponential function of x (e raised to the power of x , where e is the base of the natural logarithms).

- If x is NaN, the result is NaN.
- If x is +0, the result is 1.
- If x is -0, the result is 1.
- If x is $+\infty$, the result is $+\infty$.
- If x is $-\infty$, the result is +0.

15.8.2.9 `floor (x)`

Returns the greatest (closest to $+\infty$) Number value that is not greater than x and is equal to a mathematical integer. If x is already an integer, the result is x .

- If x is NaN, the result is NaN.
- If x is +0, the result is +0.
- If x is -0, the result is -0.
- If x is $+\infty$, the result is $+\infty$.
- If x is $-\infty$, the result is $-\infty$.
- If x is greater than 0 but less than 1, the result is +0.

NOTE The value of `Math.floor(x)` is the same as the value of `-Math.ceil(-x)`.

15.8.2.10 `log (x)`

- Returns an implementation-dependent approximation to the natural logarithm of x .
- If x is NaN, the result is NaN.
- If x is less than 0, the result is NaN.
- If x is +0 or -0, the result is $-\infty$.
- If x is 1, the result is +0.
- If x is $+\infty$, the result is $+\infty$.

15.8.2.11 `max ([value1 [, value2 [, ...]]])`

Given zero or more arguments, calls `ToNumber` on each of the arguments and returns the largest of the resulting values.

- If no arguments are given, the result is $-\infty$.
- If any value is NaN, the result is NaN.
- The comparison of values to determine the largest value is done [using the Abstract Relational Comparison Algorithm](#) (11.8.1) except that +0 is considered to be larger than -0.

Deleted: as in
Deleted: 5

The `length` property of the `max` method is 2.

15.8.2.12 `min ([value1 [, value2 [, ...]]])`

Given zero or more arguments, calls `ToNumber` on each of the arguments and returns the smallest of the resulting values.

- If no arguments are given, the result is $+\infty$.
- If any value is NaN, the result is NaN.
- The comparison of values to determine the smallest value is done [using the Abstract Relational Comparison Algorithm](#) (11.8.1) except that +0 is considered to be larger than -0.

Deleted: as in
Deleted: 5

The `length` property of the `min` method is 2.

15.8.2.13 pow (x, y)

Returns an implementation-dependent approximation to the result of raising x to the power y .

- If y is NaN, the result is NaN.
- If y is +0, the result is 1, even if x is NaN.
- If y is -0, the result is 1, even if x is NaN.
- If x is NaN and y is nonzero, the result is NaN.
- If $\text{abs}(x) > 1$ and y is $+\infty$, the result is $+\infty$.
- If $\text{abs}(x) > 1$ and y is $-\infty$, the result is +0.
- If $\text{abs}(x) == 1$ and y is $+\infty$, the result is NaN.
- If $\text{abs}(x) == 1$ and y is $-\infty$, the result is NaN.
- If $\text{abs}(x) < 1$ and y is $+\infty$, the result is +0.
- If $\text{abs}(x) < 1$ and y is $-\infty$, the result is $+\infty$.
- If x is $+\infty$ and $y > 0$, the result is $+\infty$.
- If x is $+\infty$ and $y < 0$, the result is +0.
- If x is $-\infty$ and $y > 0$ and y is an odd integer, the result is $-\infty$.
- If x is $-\infty$ and $y > 0$ and y is not an odd integer, the result is $+\infty$.
- If x is $-\infty$ and $y < 0$ and y is an odd integer, the result is -0.
- If x is $-\infty$ and $y < 0$ and y is not an odd integer, the result is +0.
- If x is +0 and $y > 0$, the result is +0.
- If x is +0 and $y < 0$, the result is $+\infty$.
- If x is -0 and $y > 0$ and y is an odd integer, the result is -0.
- If x is -0 and $y > 0$ and y is not an odd integer, the result is +0.
- If x is -0 and $y < 0$ and y is an odd integer, the result is $-\infty$.
- If x is -0 and $y < 0$ and y is not an odd integer, the result is $+\infty$.
- If $x < 0$ and x is finite and y is finite and y is not an integer, the result is NaN.

15.8.2.14 random ()

Returns a Number value with positive sign, greater than or equal to 0 but less than 1, chosen randomly or pseudo randomly with approximately uniform distribution over that range, using an implementation-dependent algorithm or strategy. This function takes no arguments.

15.8.2.15 round (x)

Returns the Number value that is closest to x and is equal to a mathematical integer. If two integer Number values are equally close to x , then the result is the Number value that is closer to $+\infty$. If x is already an integer, the result is x .

- If x is NaN, the result is NaN.
- If x is +0, the result is +0.
- If x is -0, the result is -0.
- If x is $+\infty$, the result is $+\infty$.
- If x is $-\infty$, the result is $-\infty$.
- If x is greater than 0 but less than 0.5, the result is +0.
- If x is less than 0 but greater than or equal to -0.5, the result is -0.

NOTE 1 `Math.round(3.5)` returns 4, but `Math.round(-3.5)` returns -3.

NOTE 2 The value of `Math.round(x)` is the same as the value of `Math.floor(x+0.5)`, except when x is -0 or is less than 0 but greater than or equal to -0.5; for these cases `Math.round(x)` returns -0, but `Math.floor(x+0.5)` returns +0.

15.8.2.16 sin (x)

Returns an implementation-dependent approximation to the sine of x . The argument is expressed in radians.

- If x is NaN, the result is NaN.
- If x is +0, the result is +0.
- If x is -0, the result is -0.
- If x is $+\infty$ or $-\infty$, the result is NaN.

15.8.2.17 `sqrt (x)`

Returns an implementation-dependent approximation to the square root of x .

- If x is NaN, the result is NaN.
- If x is less than 0, the result is NaN.
- If x is +0, the result is +0.
- If x is -0, the result is -0.
- If x is $+\infty$, the result is $+\infty$.

15.8.2.18 `tan (x)`

Returns an implementation-dependent approximation to the tangent of x . The argument is expressed in radians.

- If x is NaN, the result is NaN.
- If x is +0, the result is +0.
- If x is -0, the result is -0.
- If x is $+\infty$ or $-\infty$, the result is NaN.

15.8.2.19 `log10 (x)`

Returns an implementation-dependent approximation to the base 10 logarithm of x .

- If x is NaN, the result is NaN.
- If x is less than 0, the result is NaN.
- If x is +0, the result is $-\infty$.
- If x is -0, the result is $-\infty$.
- If x is 1, the result is +0.
- If x is $+\infty$, the result is $+\infty$.

15.8.2.20 `log2 (x)`

Returns an implementation-dependent approximation to the base 2 logarithm of x .

- If x is NaN, the result is NaN.
- If x is less than 0, the result is NaN.
- If x is +0, the result is $-\infty$.
- If x is -0, the result is $-\infty$.
- If x is 1, the result is +0.
- If x is $+\infty$, the result is $+\infty$.

15.8.2.21 `log1p (x)`

Returns an implementation-dependent approximation to the natural logarithm of $1 + x$. The result is computed in a way that is accurate even when the value of x is close to zero.

- If x is NaN, the result is NaN.
- If x is less than -1, the result is NaN.
- If x is -1, the result is $-\infty$.

- If x is $+0$, the result is $+0$.
- If x is -0 , the result is -0 .
- If x is $+\infty$, the result is $+\infty$.

15.8.2.22 expm1(x)

Returns an implementation-dependent approximation to subtracting 1 from the exponential function of x (e raised to the power of x , where e is the base of the natural logarithms). The result is computed in a way that is accurate even when the value of x is close 0.

- If x is NaN, the result is NaN.
- If x is $+0$, the result is $+0$.
- If x is -0 , the result is -0 .
- If x is $+\infty$, the result is $+\infty$.
- If x is $-\infty$, the result is -1 .

15.8.2.23 cosh(x)

Returns an implementation-dependent approximation to the hyperbolic cosine of x .

- If x is NaN, the result is NaN.
- If x is $+0$, the result is 1.
- If x is -0 , the result is 1.
- If x is $+\infty$, the result is $+\infty$.
- If x is $-\infty$, the result is $+\infty$.

NOTE The value of $\cosh(x)$ is the same as $(\exp(x) + \exp(-x))/2$.

15.8.2.24 sinh(x)

Returns an implementation-dependent approximation to the hyperbolic sine of x .

- If x is NaN, the result is NaN.
- If x is $+0$, the result is $+0$.
- If x is -0 , the result is -0 .
- If x is $+\infty$, the result is $+\infty$.
- If x is $-\infty$, the result is $-\infty$.

NOTE The value of $\sinh(x)$ is the same as $(\exp(x) - \exp(-x))/2$.

15.8.2.25 tanh(x)

Returns an implementation-dependent approximation to the hyperbolic tangent of x .

- If x is NaN, the result is NaN.
- If x is $+0$, the result is $+0$.
- If x is -0 , the result is -0 .
- If x is $+\infty$, the result is $+1$.
- If x is $-\infty$, the result is -1 .

NOTE The value of $\tanh(x)$ is the same as $(\exp(x) - \exp(-x))/(\exp(x) + \exp(-x))$.

15.8.2.26 acosh(x)

Returns an implementation-dependent approximation to the inverse hyperbolic cosine of x .

- If x is NaN, the result is NaN.

- If x is less than 1, the result is NaN.
- If x is 1, the result is +0.
- If x is $+\infty$, the result is $+\infty$.

15.8.2.27 asinh(x)

Returns an implementation-dependent approximation to the inverse hyperbolic sine of x .

- If x is NaN, the result is NaN.
- If x is +0, the result is +0.
- If x is -0, the result is -0.
- If x is $+\infty$, the result is $+\infty$.
- If x is $-\infty$, the result is $-\infty$.

15.8.2.28 atanh(x)

Returns an implementation-dependent approximation to the inverse hyperbolic tangent of x .

- If x is NaN, the result is NaN.
- If x is less than -1, the result is NaN.
- If x is greater than 1, the result is NaN.
- If x is -1, the result is $-\infty$.
- If x is +1, the result is $+\infty$.
- If x is +0, the result is +0.
- If x is -0, the result is -0.

15.8.2.29 hypot(value1 , value2 , value3 = 0,)

Given two or three arguments, `hypot` returns an implementation-dependent approximation of the square root of the sum of squares of up to three arguments.

Deleted: [

Deleted:]

Deleted: its

- If any argument is $+\infty$, the result is $+\infty$.
- If any argument is $-\infty$, the result is $+\infty$.
- If no argument is $+\infty$ or $-\infty$, and any argument is NaN, the result is NaN.
- If all arguments are either +0 or -0, the result is +0.

15.8.2.30 hypot2(value1 , value2 [, value3])

Given two or three arguments, `hypot2` returns an implementation-dependent approximation of the sum of squares of its arguments.

Comment [AWB7137]: Concensus at March29 TC39 meeting was to drop this function. See March29 meeting notes

- If no arguments are given, the result is +0.
- If any argument is $+\infty$, the result is $+\infty$.
- If any argument is $-\infty$, the result is $+\infty$.
- If no argument is $+\infty$ or $-\infty$, and any argument is NaN, the result is NaN.
- If all arguments are either +0 or -0, the result is +0.

15.8.2.30 trunc(x)

Returns the integral part of the number x , removing any fractional digits. If x is already an integer, the result is x .

- If x is NaN, the result is NaN.
- If x is -0, the result is -0.
- If x is +0, the result is +0.
- If x is $+\infty$, the result is $+\infty$.

- If x is $-\infty$, the result is $-\infty$.

15.8.2.31 sign(x)

Returns the sign of the x , indicating whether x is positive, negative or zero.

- If x is NaN, the result is NaN.
- If x is -0 , the result is -0 .
- If x is $+0$, the result is $+0$.
- If x is negative and not -0 , the result is -1 .
- If x is positive and not $+0$, the result is $+1$.

15.8.2.32 cbrt(x)

Returns an implementation-dependent approximation to the cube root of x .

- If x is NaN, the result is NaN.
- If x is $+0$, the result is $+0$.
- If x is -0 , the result is -0 .
- If x is $+\infty$, the result is $+\infty$.
- If x is $-\infty$, the result is $-\infty$.

15.9 Date Objects

15.9.1 Overview of Date Objects and Definitions of Abstract Operators

The following functions are abstract operations that operate on time values (defined in 15.9.1.1). Note that, in every case, if any argument to one of these functions is NaN, the result will be NaN.

15.9.1.1 Time Values and Time Range

A Date object contains a Number indicating a particular instant in time to within a millisecond. Such a Number is called a *time value*. A time value may also be NaN, indicating that the Date object does not represent a specific instant of time.

Time is measured in ECMAScript in milliseconds since 01 January, 1970 UTC. In time values leap seconds are ignored. It is assumed that there are exactly 86,400,000 milliseconds per day. ECMAScript Number values can represent all integers from -9,007,199,254,740,992 to 9,007,199,254,740,992; this range suffices to measure times to millisecond precision for any instant that is within approximately 285,616 years, either forward or backward, from 01 January, 1970 UTC.

The actual range of times supported by ECMAScript Date objects is slightly smaller: exactly -100,000,000 days to 100,000,000 days measured relative to midnight at the beginning of 01 January, 1970 UTC. This gives a range of 8,640,000,000,000,000 milliseconds to either side of 01 January, 1970 UTC.

The exact moment of midnight at the beginning of 01 January, 1970 UTC is represented by the value +0.

15.9.1.2 Day Number and Time within Day

A given time value t belongs to day number

$$\text{Day}(t) = \text{floor}(t / \text{msPerDay})$$

where the number of milliseconds per day is

$$\text{msPerDay} = 86400000$$

The remainder is called the time within the day:

$$\text{TimeWithinDay}(t) = t \bmod \text{msPerDay}$$

15.9.1.3 Year Number

ECMAScript uses an extrapolated Gregorian system to map a day number to a year number and to determine the month and date within that year. In this system, leap years are precisely those which are (divisible by 4) and ((not divisible by 100) or (divisible by 400)). The number of days in year number y is therefore defined by

$$\begin{aligned}\text{DaysInYear}(y) &= 365 \text{ if } (y \bmod 4) \neq 0 \\ &= 366 \text{ if } (y \bmod 4) = 0 \text{ and } ((y \bmod 100) \neq 0) \\ &= 365 \text{ if } ((y \bmod 100) = 0) \text{ and } ((y \bmod 400) \neq 0) \\ &= 366 \text{ if } ((y \bmod 400) = 0)\end{aligned}$$

All non-leap years have 365 days with the usual number of days per month and leap years have an extra day in February. The day number of the first day of year y is given by:

$$\text{DayFromYear}(y) = 365 \times (y - 1970) + \text{floor}((y - 1969)/4) - \text{floor}((y - 1901)/100) + \text{floor}((y - 1601)/400)$$

The time value of the start of a year is:

$$\text{TimeFromYear}(y) = \text{msPerDay} \times \text{DayFromYear}(y)$$

A time value determines a year by:

$$\text{YearFromTime}(t) = \text{the largest integer } y \text{ (closest to positive infinity) such that } \text{TimeFromYear}(y) \leq t$$

The leap-year function is 1 for a time within a leap year and otherwise is zero:

$$\begin{aligned}\text{InLeapYear}(t) &= 0 \text{ if } \text{DaysInYear}(\text{YearFromTime}(t)) = 365 \\ &= 1 \text{ if } \text{DaysInYear}(\text{YearFromTime}(t)) = 366\end{aligned}$$

15.9.1.4 Month Number

Months are identified by an integer in the range 0 to 11, inclusive. The mapping $\text{MonthFromTime}(t)$ from a time value t to a month number is defined by:

$$\begin{array}{lll}\text{MonthFromTime}(t) & = 0 & \text{if } 0 \leq \text{DayWithinYear}(t) < 31 \\ & = 1 & \text{if } 31 \leq \text{DayWithinYear}(t) < 59+\text{InLeapYear}(t) \\ & = 2 & \text{if } 59+\text{InLeapYear}(t) \leq \text{DayWithinYear}(t) < 90+\text{InLeapYear}(t) \\ & = 3 & \text{if } 90+\text{InLeapYear}(t) \leq \text{DayWithinYear}(t) < 120+\text{InLeapYear}(t) \\ & = 4 & \text{if } 120+\text{InLeapYear}(t) \leq \text{DayWithinYear}(t) < 151+\text{InLeapYear}(t) \\ & = 5 & \text{if } 151+\text{InLeapYear}(t) \leq \text{DayWithinYear}(t) < 181+\text{InLeapYear}(t) \\ & = 6 & \text{if } 181+\text{InLeapYear}(t) \leq \text{DayWithinYear}(t) < 212+\text{InLeapYear}(t) \\ & = 7 & \text{if } 212+\text{InLeapYear}(t) \leq \text{DayWithinYear}(t) < 243+\text{InLeapYear}(t) \\ & = 8 & \text{if } 243+\text{InLeapYear}(t) \leq \text{DayWithinYear}(t) < 273+\text{InLeapYear}(t) \\ & = 9 & \text{if } 273+\text{InLeapYear}(t) \leq \text{DayWithinYear}(t) < 304+\text{InLeapYear}(t) \\ & = 10 & \text{if } 304+\text{InLeapYear}(t) \leq \text{DayWithinYear}(t) < 334+\text{InLeapYear}(t) \\ & = 11 & \text{if } 334+\text{InLeapYear}(t) \leq \text{DayWithinYear}(t) < 365+\text{InLeapYear}(t)\end{array}$$

where

$$\text{DayWithinYear}(t) = \text{Day}(t) - \text{DayFromYear}(\text{YearFromTime}(t))$$

A month value of 0 specifies January; 1 specifies February; 2 specifies March; 3 specifies April; 4 specifies May; 5 specifies June; 6 specifies July; 7 specifies August; 8 specifies September; 9 specifies October; 10 specifies November; and 11 specifies December. Note that $\text{MonthFromTime}(0) = 0$, corresponding to Thursday, 01 January, 1970.

15.9.1.5 Date Number

A date number is identified by an integer in the range 1 through 31, inclusive. The mapping $\text{DateFromTime}(t)$ from a time value t to a month number is defined by:

$$\begin{array}{ll}\text{DateFromTime}(t) & = \text{DayWithinYear}(t)+1 & \text{if } \text{MonthFromTime}(t)=0 \\ & = \text{DayWithinYear}(t)-30 & \text{if } \text{MonthFromTime}(t)=1 \\ & = \text{DayWithinYear}(t)-58-\text{InLeapYear}(t) & \text{if } \text{MonthFromTime}(t)=2\end{array}$$

```

= DayWithinYear(t)–89–InLeapYear(t)           if MonthFromTime(t)=3
= DayWithinYear(t)–119–InLeapYear(t)           if MonthFromTime(t)=4
= DayWithinYear(t)–150–InLeapYear(t)           if MonthFromTime(t)=5
= DayWithinYear(t)–180–InLeapYear(t)           if MonthFromTime(t)=6
= DayWithinYear(t)–211–InLeapYear(t)           if MonthFromTime(t)=7
= DayWithinYear(t)–242–InLeapYear(t)           if MonthFromTime(t)=8
= DayWithinYear(t)–272–InLeapYear(t)           if MonthFromTime(t)=9
= DayWithinYear(t)–303–InLeapYear(t)           if MonthFromTime(t)=10
= DayWithinYear(t)–333–InLeapYear(t)           if MonthFromTime(t)=11

```

15.9.1.6 Week Day

The weekday for a particular time value t is defined as

$$\text{WeekDay}(t) = (\text{Day}(t) + 4) \text{ modulo } 7$$

A weekday value of 0 specifies Sunday; 1 specifies Monday; 2 specifies Tuesday; 3 specifies Wednesday; 4 specifies Thursday; 5 specifies Friday; and 6 specifies Saturday. Note that $\text{WeekDay}(0) = 4$, corresponding to Thursday, 01 January, 1970.

15.9.1.7 Local Time Zone Adjustment

An implementation of ECMAScript is expected to determine the local time zone adjustment. The local time zone adjustment is a value LocalTZA measured in milliseconds which when added to UTC represents the local *standard* time. Daylight saving time is *not* reflected by LocalTZA .

NOTE It is recommended that implementations use the time zone information of the IANA Time Zone Database.

15.9.1.8 Daylight Saving Time Adjustment

An implementation of ECMAScript is expected to make its best effort to determine the local daylight saving time adjustment. An implementation dependent algorithm using best available information on time zones to determine the local daylight saving time adjustment $\text{DaylightSavingTA}(t)$, measured in milliseconds.

15.9.1.9 Local Time

Conversion from UTC to local time is defined by

$$\text{LocalTime}(t) = t + \text{LocalTZA} + \text{DaylightSavingTA}(t)$$

Conversion from local time to UTC is defined by

$$\text{UTC}(t) = t - \text{LocalTZA} - \text{DaylightSavingTA}(t - \text{LocalTZA})$$

Note that $\text{UTC}(\text{LocalTime}(t))$ is not necessarily always equal to t .

15.9.1.10 Hours, Minutes, Second, and Milliseconds

The following functions are useful in decomposing time values:

```

HourFromTime(t) = floor(t / msPerHour) modulo HoursPerDay
MinFromTime(t) = floor(t / msPerMinute) modulo MinutesPerHour
SecFromTime(t) = floor(t / msPerSecond) modulo SecondsPerMinute
msFromTime(t) = t modulo msPerSecond

```

where

```

HoursPerDay = 24
MinutesPerHour = 60
SecondsPerMinute = 60
msPerSecond = 1000

```

Deleted: The value LocalTZA does not vary with time but depends only on the geographic location.

Comment [AWB8138]: Need a reference

Formatted: Note

Deleted: algorithm

Deleted: The

Deleted: .

Deleted: must depend only on four things:
(1) the time since the beginning of the year
 $t - \text{TimeFromYear}(\text{YearFromTime}(t))$
(2) whether t is in a leap year
 $\text{InLeapYear}(t)$
(3) the week day of the beginning of the year
 $\text{WeekDay}(\text{TimeFromYear}(\text{YearFromTime}(t)))$
and (4) the geographic location.

The implementation of ECMAScript should not try to determine whether the exact time was subject to daylight saving time, but just whether daylight saving time would have been in effect if the current daylight saving time algorithm had been used at the time. This avoids complications such as taking into account the years that the locale observed daylight saving time year round. If the host environment provides functionality for determining daylight saving time, the implementation of ECMAScript is free to map the year in question to an equivalent year (same leap-year-ness and same starting week day for the year) for which the host environment provides daylight saving time information. The only restriction is that all equivalent years should produce the same result.

$$\begin{aligned} \text{msPerMinute} &= 60000 = \text{msPerSecond} \times \text{SecondsPerMinute} \\ \text{msPerHour} &= 3600000 = \text{msPerMinute} \times \text{MinutesPerHour} \end{aligned}$$

15.9.1.11 MakeTime (hour, min, sec, ms)

The operator `MakeTime` calculates a number of milliseconds from its four arguments, which must be ECMAScript Number values. This operator functions as follows:

1. If `hour` is not finite or `min` is not finite or `sec` is not finite or `ms` is not finite, return `NaN`.
2. Let `h` be `ToInteger(hour)`.
3. Let `m` be `ToInteger(min)`.
4. Let `s` be `ToInteger(sec)`.
5. Let `milli` be `ToInteger(ms)`.
6. Let `t` be `h * msPerHour + m * msPerMinute + s * msPerSecond + milli`, performing the arithmetic according to IEEE 754 rules (that is, as if using the ECMAScript operators `*` and `+`).
7. Return `t`.

15.9.1.12 MakeDay (year, month, date)

The operator `MakeDay` calculates a number of days from its three arguments, which must be ECMAScript Number values. This operator functions as follows:

1. If `year` is not finite or `month` is not finite or `date` is not finite, return `NaN`.
2. Let `y` be `ToInteger(year)`.
3. Let `m` be `ToInteger(month)`.
4. Let `dt` be `ToInteger(date)`.
5. Let `ym` be `y + floor(m / 12)`.
6. Let `mn` be `m` modulo 12.
7. Find a value `t` such that `YearFromTime(t) == ym` and `MonthFromTime(t) == mn` and `DateFromTime(t) == 1`; but if this is not possible (because some argument is out of range), return `NaN`.
8. Return `Day(t) + dt - 1`.

15.9.1.13 MakeDate (day, time)

The operator `MakeDate` calculates a number of milliseconds from its two arguments, which must be ECMAScript Number values. This operator functions as follows:

1. If `day` is not finite or `time` is not finite, return `NaN`.
2. Return `day * msPerDay + time`.

15.9.1.14 TimeClip (time)

The operator `TimeClip` calculates a number of milliseconds from its argument, which must be an ECMAScript Number value. This operator functions as follows:

1. If `time` is not finite, return `NaN`.
2. If $\text{abs}(\text{time}) > 8.64 \times 10^{15}$, return `NaN`.
3. Return an implementation-dependent choice of either `ToInteger(time)` or `ToInteger(time) + (+0)`. (Adding a positive zero converts `-0` to `+0`.)

NOTE The point of step 3 is that an implementation is permitted a choice of internal representations of time values, for example as a 64-bit signed integer or as a 64-bit floating-point value. Depending on the implementation, this internal representation may or may not distinguish `-0` and `+0`.

15.9.1.15 Date Time String Format

ECMAScript defines a string interchange format for date-times based upon a simplification of the ISO 8601 Extended Format. The format is as follows: `YYYY-MM-DDTHH:mm:ss.sssZ`

Where the fields are as follows:

- YYYY** is the decimal digits of the year 0000 to 9999 in the Gregorian calendar.
- “-” (hyphen) appears literally twice in the string.
- MM** is the month of the year from 01 (January) to 12 (December).
- DD** is the day of the month from 01 to 31.
- T** “T” appears literally in the string, to indicate the beginning of the time element.
- HH** is the number of complete hours that have passed since midnight as two decimal digits from 00 to 24.
- :
- : (colon) appears literally twice in the string.
- mm** is the number of complete minutes since the start of the hour as two decimal digits from 00 to 59.
- ss** is the number of complete seconds since the start of the minute as two decimal digits from 00 to 59.
- .
- . (dot) appears literally in the string.
- sss** is the number of complete milliseconds since the start of the second as three decimal digits.
- z** is the time zone offset specified as “z” (for UTC) or either “+” or “-” followed by a time expression **HH:mm**

This format includes date-only forms:

YYYY
YYYY-MM
YYYY-MM-DD

It also includes “date-time” forms that consist of one of the above date-only forms immediately followed by one of the following time forms with an optional time zone offset appended:

THH:mm
THH:mm:ss
THH:mm:ss.sss

All numbers must be base 10. If the **MM** or **DD** fields are absent “01” is used as the value. If the **HH**, **mm**, or **ss** fields are absent “00” is used as the value and the value of an absent **sss** field is “000”. If the time zone offset is absent, the date-time is interpreted as a local time.

Illegal values (out-of-bounds as well as syntax errors) in a format string means that the format string is not a valid instance of this format.

NOTE 1 As every day both starts and ends with midnight, the two notations 00:00 and 24:00 are available to distinguish the two midnights that can be associated with one date. This means that the following two notations refer to exactly the same point in time: 1995-02-04T24:00 and 1995-02-05T00:00

NOTE 2 There exists no international standard that specifies abbreviations for civil time zones like CET, EST, etc. and sometimes the same abbreviation is even used for two very different time zones. For this reason, ISO 8601 and this format specifies numeric representations of date and time.

15.9.1.15.1 Extended years

ECMAScript requires the ability to specify 6 digit years (extended years); approximately 285,426 years, either forward or backward, from 01 January, 1970 UTC. To represent years before 0 or after 9999, ISO 8601 permits the expansion of the year representation, but only by prior agreement between the sender and the receiver. In the simplified ECMAScript format such an expanded year representation shall have 2 extra year digits and is always prefixed with a + or – sign. The year 0 is considered positive and hence prefixed with a + sign.

NOTE Examples of extended years:

Deleted: The value of an

Deleted: absent

Deleted: is “z”

-283457-03-21T15:00:59.008Z	283458 B.C.
-000001-01-01T00:00:00Z	2 B.C.
+000000-01-01T00:00:00Z	1 B.C.
+000001-01-01T00:00:00Z	1 A.D.
+001970-01-01T00:00:00Z	1970 A.D.
+002009-12-15T00:00:00Z	2009 A.D.
+287396-10-12T08:59:00.992Z	287396 A.D.

15.9.2 The Date Constructor Called as a Function

When `Date` is called as a function rather than as a constructor, it returns a String representing the current time (UTC).

NOTE The function call `Date(...)` is not equivalent to the object creation expression `new Date(...)` with the same arguments.

15.9.2.1 `Date ([year [, month [, date [, hours [, minutes [, seconds [, ms]]]]]])`

All of the arguments are optional; any arguments supplied are accepted but are completely ignored. A String is created and returned as if by the expression `(new Date()).toString()` where `Date` is the standard built-in constructor with that name and `toString` is the standard built-in method `Date.prototype.toString`.

15.9.3 The Date Constructor

When `Date` is called as part of a `new` expression, it is a constructor: it initialises the newly created object.

15.9.3.1 `new Date (year, month [, date [, hours [, minutes [, seconds [, ms]]]])`

When `Date` is called with two to seven arguments, it computes the date from `year`, `month`, and (optionally) `date`, `hours`, `minutes`, `seconds` and `ms`.

The `[[Prototype]]` internal property of the newly constructed object is set to the original Date prototype object, the one that is the initial value of `Date.prototype` (15.9.4.1).

The newly constructed object has a `[[NativeBrand]]` internal property whose value is `NativeDate`.

Deleted: `[[Class]]` internal property of the object
Deleted: is set to "Date"
Deleted: `IsDate`

The `[[Extensible]]` internal property of the newly constructed object is set to `true`.

The `[[PrimitiveValue]]` internal property of the newly constructed object is set as follows:

1. Let `y` be `ToNumber(year)`.
2. `ReturnIfAbrupt(y)`.
3. Let `m` be `ToNumber(month)`.
4. `ReturnIfAbrupt(month)`.
5. If `date` is supplied then let `dt` be `ToNumber(date)`; else let `dt` be `1`.
6. `ReturnIfAbrupt(dt)`.
7. If `hours` is supplied then let `h` be `ToNumber(hours)`; else let `h` be `0`.
8. `ReturnIfAbrupt(h)`.
9. If `minutes` is supplied then let `min` be `ToNumber(minutes)`; else let `min` be `0`.
10. `ReturnIfAbrupt(min)`.
11. If `seconds` is supplied then let `s` be `ToNumber(seconds)`; else let `s` be `0`.
12. `ReturnIfAbrupt(s)`.
13. If `ms` is supplied then let `milli` be `ToNumber(ms)`; else let `milli` be `0`.
14. `ReturnIfAbrupt(milli)`.
15. If `y` is not `NaN` and $0 \leq \text{ToInteger}(y) \leq 99$, then let `yr` be $1900 + \text{ToInteger}(y)$; otherwise, let `yr` be `y`.
16. Let `finalDate` be `MakeDate(MakeDay(yr, m, dt), MakeTime(h, min, s, milli))`.
17. Set the `[[PrimitiveValue]]` internal property of the newly constructed object to `TimeClip(UTC(finalDate))`.

15.9.3.2 new Date (value)

The [[Prototype]] internal property of the newly constructed object is set to the original Date prototype object, the one that is the initial value of `Date.prototype` (15.9.4.1).

The newly constructed object has a [[NativeBrand]] internal property whose value is NativeDate.

The [[Extensible]] internal property of the newly constructed object is set to `true`.

The [[PrimitiveValue]] internal property of the newly constructed object is set as follows:

1. Let v be `ToPrimitive(value)`.
2. If `Type(v)` is String, then
 - a. Parse v as a date, in exactly the same manner as for the `parse` method (15.9.4.2); let V be the time value for this date. If the parse resulted in an abrupt completion, return the Completion Record.
3. Else, let V be `ToNumber(v)`.
4. ReturnIfAbrupt(V).
5. Set the [[PrimitiveValue]] internal property of the newly constructed object to `TimeClip(V)`.
6. Return the newly constructed object.

15.9.3.3 new Date ()

The [[Prototype]] internal property of the newly constructed object is set to the original Date prototype object, the one that is the initial value of `Date.prototype` (15.9.4.1).

The newly constructed object has a [[NativeBrand]] internal property whose value is NativeDate.

The [[Extensible]] internal property of the newly constructed object is set to `true`.

The [[PrimitiveValue]] internal property of the newly constructed object is set to the time value (UTC) identifying the current time.

15.9.4 Properties of the Date Constructor

The value of the [[Prototype]] internal property of the Date constructor is the Function prototype object (15.3.4).

Besides the internal properties and the `length` property (whose value is 7), the Date constructor has the following properties:

15.9.4.1 Date.prototype

The initial value of `Date.prototype` is the built-in Date prototype object (15.9.5).

This property has the attributes { [[Writable]]: `false`, [[Enumerable]]: `false`, [[Configurable]]: `false` }.

15.9.4.2 Date.parse (string)

The `parse` function applies the `ToString` operator to its argument. If `ToString` results in an abrupt completion the Completion Record is immediately returned. Otherwise, `parse` interprets the resulting String as a date and time; it returns a Number, the UTC time value corresponding to the date and time. The String may be interpreted as a local time, a UTC time, or a time in some other time zone, depending on the contents of the String. The function first attempts to parse the format of the String according to the rules called out in Date Time String Format (15.9.1.15). If the String does not conform to that format the function may fall back to any implementation-specific heuristics or implementation-specific date formats. Unrecognisable Strings or dates containing illegal element values in the format String shall cause `Date.parse` to return `Nan`.

Deleted: IsDate

Deleted: The [[Class]] internal property of the newly constructed object is set to "Date".

Deleted: <#> Set the [[PrimitiveValue]] internal property of the newly constructed object to `TimeClip(V)` and return. ¶

Deleted: IsDate

Deleted: The [[Class]] internal property of the newly constructed object is set to "Date".

Deleted:

Deleted: and

If x is any Date object whose milliseconds amount is zero within a particular implementation of ECMAScript, then all of the following expressions should produce the same numeric value in that implementation, if all the properties referenced have their initial values:

```
x.valueOf()
Date.parse(x.toString())
Date.parse(x.toUTCString())
Date.parse(x.toISOString())
```

However, the expression

```
Date.parse(x.toLocaleString())
```

is not required to produce the same Number value as the preceding three expressions and, in general, the value produced by `Date.parse` is implementation-dependent when given any String value that does not conform to the Date Time String Format (15.9.1.15) and that could not be produced in that implementation by the `toString` or `toUTCString` method.

15.9.4.3 Date.UTC (year, month [, date [, hours [, minutes [, seconds [, ms]]]]])

When the `UTC` function is called with fewer than two arguments, the behaviour is implementation-dependent. When the `UTC` function is called with two to seven arguments, it computes the date from *year*, *month* and (optionally) *date*, *hours*, *minutes*, *seconds* and *ms*. The following steps are taken:

1. Let y be `ToNumber(year)`.
- ~~2. `ReturnIfAbrupt(y)`.~~
3. Let m be `ToNumber(month)`.
- ~~4. `ReturnIfAbrupt(m)`.~~
5. If *date* is supplied then let dt be `ToNumber(date)`; else let dt be **1**.
- ~~6. `ReturnIfAbrupt(dt)`.~~
7. If *hours* is supplied then let h be `ToNumber(hours)`; else let h be **0**.
- ~~8. `ReturnIfAbrupt(h)`.~~
9. If *minutes* is supplied then let min be `ToNumber(minutes)`; else let min be **0**.
- ~~10. `ReturnIfAbrupt(min)`.~~
11. If *seconds* is supplied then let s be `ToNumber(seconds)`; else let s be **0**.
- ~~12. `ReturnIfAbrupt(s)`.~~
13. If *ms* is supplied then let $milli$ be `ToNumber(ms)`; else let $milli$ be **0**.
- ~~14. `ReturnIfAbrupt(milli)`.~~
15. If y is not `NaN` and $0 \leq \text{ToInteger}(y) \leq 99$, then let yr be $1900 + \text{ToInteger}(y)$; otherwise, let yr be y .
16. Return `TimeClip(MakeDate(MakeDay(yr, m, dt), MakeTime(h, min, s, milli)))`.

Deleted: *s*

The `length` property of the `UTC` function is **7**.

NOTE The `UTC` function differs from the `Date` constructor in two ways: it returns a time value as a Number, rather than creating a Date object, and it interprets the arguments in UTC rather than as local time.

15.9.4.4 Date.now ()

The `now` function return a Number value that is the time value designating the UTC date and time of the occurrence of the call to `now`.

15.9.5 Properties of the Date Prototype Object

The Date prototype object is itself a Date object ~~and has a [[NativeBrand]] internal property whose value is NativeDate~~. ~~Its [[PrimitiveValue]] is NaN~~.

Deleted: (its [[Class]] is "Date")

Deleted: IsDate

Deleted: whose

The value of the [[Prototype]] internal property of the Date prototype object is the standard built-in Object prototype object (15.2.4).

In following descriptions of functions that are properties of the Date prototype object, the phrase “this Date object” refers to the object that is the `this` value for the invocation of the function. Unless explicitly noted otherwise, none of these functions are generic; a `TypeError` exception is thrown if the `this` value is not an

object with a [[NativeBrand]] internal property whose value is NativeDate. Also, the phrase “this time value” refers to the Number value for the time represented by this Date object, that is, the value of the [[PrimitiveValue]] internal property of this Date object.

Deleted: for which the value of the [[Class]]

Deleted: IsDate

Deleted: is "Date"

15.9.5.1 Date.prototype.constructor

The initial value of `Date.prototype.constructor` is the built-in `Date` constructor.

15.9.5.2 Date.prototype.toString ()

This function returns a String value. If this time value is NaN, the String value is "Invalid Date", otherwise the contents of the String are implementation-dependent, but are intended to represent the Date in the current time zone in a convenient, human-readable form.

Deleted: The

NOTE For any Date value d whose milliseconds amount is zero, the result of `Date.parse(d.toString())` is equal to `d.valueOf()`. See 15.9.4.2.

15.9.5.3 Date.prototype.toDateString ()

This function returns a String value. The contents of the String are implementation-dependent, but are intended to represent the “date” portion of the Date in the current time zone in a convenient, human-readable form.

15.9.5.4 Date.prototype.toTimeString ()

This function returns a String value. The contents of the String are implementation-dependent, but are intended to represent the “time” portion of the Date in the current time zone in a convenient, human-readable form.

15.9.5.5 Date.prototype.toLocaleString ()

This function returns a String value. The contents of the String are implementation-dependent, but are intended to represent the Date in the current time zone in a convenient, human-readable form that corresponds to the conventions of the host environment’s current locale.

NOTE The first parameter to this function is likely to be used in a future version of this standard; it is recommended that implementations do not use this parameter position for anything else.

15.9.5.6 Date.prototype.toLocaleDateString ()

This function returns a String value. The contents of the String are implementation-dependent, but are intended to represent the “date” portion of the Date in the current time zone in a convenient, human-readable form that corresponds to the conventions of the host environment’s current locale.

NOTE The first parameter to this function is likely to be used in a future version of this standard; it is recommended that implementations do not use this parameter position for anything else.

15.9.5.7 Date.prototype.toLocaleTimeString ()

This function returns a String value. The contents of the String are implementation-dependent, but are intended to represent the “time” portion of the Date in the current time zone in a convenient, human-readable form that corresponds to the conventions of the host environment’s current locale.

NOTE The first parameter to this function is likely to be used in a future version of this standard; it is recommended that implementations do not use this parameter position for anything else.

15.9.5.8 Date.prototype.valueOf ()

The `valueOf` function returns a Number, which is this time value.

15.9.5.9 Date.prototype.getTime ()

1. Return this time value.

15.9.5.10 Date.prototype.getFullYear ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is NaN, return NaN.
4. Return YearFromTime(LocalTime(t)).

15.9.5.11 Date.prototype.getUTCFullYear ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is NaN, return NaN.
4. Return YearFromTime(t).

15.9.5.12 Date.prototype.getMonth ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is NaN, return NaN.
4. Return MonthFromTime(LocalTime(t)).

15.9.5.13 Date.prototype.getUTCMonth ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is NaN, return NaN.
4. Return MonthFromTime(t).

15.9.5.14 Date.prototype.getDate ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is NaN, return NaN.
4. Return DateFromTime(LocalTime(t)).

15.9.5.15 Date.prototype.getUTCDate ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is NaN, return NaN.
4. Return DateFromTime(t).

15.9.5.16 Date.prototype.getDay ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is NaN, return NaN.
4. Return WeekDay(LocalTime(t)).

15.9.5.17 Date.prototype.getUTCDay ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is NaN, return NaN.
4. Return WeekDay(t).

15.9.5.18 Date.prototype.getHours ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is **NaN**, return **NaN**.
4. Return HourFromTime(LocalTime(t)).

15.9.5.19 Date.prototype.getUTCHours ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is **NaN**, return **NaN**.
4. Return HourFromTime(t).

15.9.5.20 Date.prototype.getMinutes ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is **NaN**, return **NaN**.
4. Return MinFromTime(LocalTime(t)).

15.9.5.21 Date.prototype.getUTCMinutes ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is **NaN**, return **NaN**.
4. Return MinFromTime(t).

15.9.5.22 Date.prototype.getSeconds ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is **NaN**, return **NaN**.
4. Return SecFromTime(LocalTime(t)).

15.9.5.23 Date.prototype.getUTCSSeconds ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is **NaN**, return **NaN**.
4. Return SecFromTime(t).

15.9.5.24 Date.prototype.getMilliseconds ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is **NaN**, return **NaN**.
4. Return msFromTime(LocalTime(t)).

15.9.5.25 Date.prototype.getUTCMilliseconds ()

1. Let t be this time value.
2. ReturnIfAbrupt(t).
3. If t is **NaN**, return **NaN**.
4. Return msFromTime(t).

15.9.5.26 Date.prototype.getTimezoneOffset ()

Returns the difference between local time and UTC time in minutes.

1. Let t be this time value.
2. [ReturnIfAbrupt\(\$t\$ \)](#).
3. If t is NaN, return NaN.
4. Return $(t - \text{LocalTime}(t)) / \text{msPerMinute}$.

15.9.5.27 Date.prototype.setTime (time)

1. Let v be TimeClip(ToNumber($time$)).
2. [ReturnIfAbrupt\(\$v\$ \)](#).
3. Set the [[PrimitiveValue]] internal property of this Date object to v .
4. Return v .

15.9.5.28 Date.prototype.setMilliseconds (ms)

1. Let t be the result of LocalTime(this time value).
2. Let $time$ be MakeTime(HourFromTime(t), MinFromTime(t), SecFromTime(t), ToNumber(ms)).
3. Let u be TimeClip(UTC(MakeDate(Day(t), $time$))).
4. Set the [[PrimitiveValue]] internal property of this Date object to u .
5. Return u .

15.9.5.29 Date.prototype.setUTCMilliseconds (ms)

1. Let t be this time value.
2. [ReturnIfAbrupt\(\$t\$ \)](#).
3. Let $time$ be MakeTime(HourFromTime(t), MinFromTime(t), SecFromTime(t), ToNumber(ms)).
4. Let v be TimeClip(MakeDate(Day(t), $time$)).
5. Set the [[PrimitiveValue]] internal property of this Date object to v .
6. Return v .

15.9.5.30 Date.prototype.setSeconds (sec [, ms])

If ms is not specified, this behaves as if ms were specified with the value `getMilliseconds()`.

1. Let t be the result of LocalTime(this time value).
2. Let s be ToNumber(sec).
3. If ms is not specified, then let $milli$ be $\text{msFromTime}(t)$; otherwise, let $milli$ be ToNumber(ms).
4. Let $date$ be MakeDate(Day(t), MakeTime(HourFromTime(t), MinFromTime(t), s , $milli$)).
5. Let u be TimeClip(UTC($date$)).
6. Set the [[PrimitiveValue]] internal property of this Date object to u .
7. Return u .

The `length` property of the `setSeconds` method is 2.

15.9.5.31 Date.prototype.setUTCSeconds (sec [, ms])

If ms is not specified, this behaves as if ms were specified with the value `getUTCMilliseconds()`.

1. Let t be this time value.
2. [ReturnIfAbrupt\(\$t\$ \)](#).
3. Let s be ToNumber(sec).
4. If ms is not specified, then let $milli$ be $\text{msFromTime}(t)$; otherwise, let $milli$ be ToNumber(ms).
5. Let $date$ be MakeDate(Day(t), MakeTime(HourFromTime(t), MinFromTime(t), s , $milli$)).
6. Let v be TimeClip($date$).
7. Set the [[PrimitiveValue]] internal property of this Date object to v .
8. Return v .

The `length` property of the `setUTCSeconds` method is 2.

15.9.5.32 Date.prototype.setMinutes (min [, sec [, ms]])

If *sec* is not specified, this behaves as if *sec* were specified with the value `getSeconds ()`.

If *ms* is not specified, this behaves as if *ms* were specified with the value `getMilliseconds ()`.

1. Let *t* be the result of `LocalTime(this time value)`.
2. Let *m* be `ToNumber(min)`.
3. If *sec* is not specified, then let *s* be `SecFromTime(t)`; otherwise, let *s* be `ToNumber(sec)`.
4. If *ms* is not specified, then let *milli* be `msFromTime(t)`; otherwise, let *milli* be `ToNumber(ms)`.
5. Let *date* be `MakeDate(Day(t), MakeTime(HourFromTime(t), m, s, milli))`.
6. Let *u* be `TimeClip(UTC(date))`.
7. Set the `[[PrimitiveValue]]` internal property of this Date object to *u*.
8. Return *u*.

The `length` property of the `setMinutes` method is 3.

15.9.5.33 Date.prototype.setUTCMinutes (min [, sec [, ms]])

If *sec* is not specified, this behaves as if *sec* were specified with the value `getUTCSSeconds ()`.

If *ms* is not specified, this function behaves as if *ms* were specified with the value return by `getUTCMilliseconds ()`.

1. Let *t* be this time value.
2. [ReturnIfAbrupt\(*t*\)](#).
3. Let *m* be `ToNumber(min)`.
4. If *sec* is not specified, then let *s* be `SecFromTime(t)`; otherwise, let *s* be `ToNumber(sec)`.
5. If *ms* is not specified, then let *milli* be `msFromTime(t)`; otherwise, let *milli* be `ToNumber(ms)`.
6. Let *date* be `MakeDate(Day(t), MakeTime(HourFromTime(t), m, s, milli))`.
7. Let *v* be `TimeClip(date)`.
8. Set the `[[PrimitiveValue]]` internal property of this Date object to *v*.
9. Return *v*.

The `length` property of the `setUTCMinutes` method is 3.

15.9.5.34 Date.prototype.setHours (hour [, min [, sec [, ms]]])

If *min* is not specified, this behaves as if *min* were specified with the value `getMinutes ()`.

If *sec* is not specified, this behaves as if *sec* were specified with the value `getSeconds ()`.

If *ms* is not specified, this behaves as if *ms* were specified with the value `getMilliseconds ()`.

1. Let *t* be the result of `LocalTime(this time value)`.
2. Let *h* be `ToNumber(hour)`.
3. If *min* is not specified, then let *m* be `MinFromTime(t)`; otherwise, let *m* be `ToNumber(min)`.
4. If *sec* is not specified, then let *s* be `SecFromTime(t)`; otherwise, let *s* be `ToNumber(sec)`.
5. If *ms* is not specified, then let *milli* be `msFromTime(t)`; otherwise, let *milli* be `ToNumber(ms)`.
6. Let *date* be `MakeDate(Day(t), MakeTime(h, m, s, milli))`.
7. Let *u* be `TimeClip(UTC(date))`.
8. Set the `[[PrimitiveValue]]` internal property of this Date object to *u*.
9. Return *u*.

The `length` property of the `setHours` method is 4.

15.9.5.35 Date.prototype.setUTCHours (hour [, min [, sec [, ms]]])

If *min* is not specified, this behaves as if *min* were specified with the value `getUTCMinutes()`.

If *sec* is not specified, this behaves as if *sec* were specified with the value `getUTCSeconds()`.

If *ms* is not specified, this behaves as if *ms* were specified with the value `getUTCMilliseconds()`.

1. Let *t* be this time value.
2. [ReturnIfAbrupt\(*t*\)](#).
3. Let *h* be `ToNumber(hour)`.
4. If *min* is not specified, then let *m* be `MinFromTime(t)`; otherwise, let *m* be `ToNumber(min)`.
5. If *sec* is not specified, then let *s* be `SecFromTime(t)`; otherwise, let *s* be `ToNumber(sec)`.
6. If *ms* is not specified, then let *milli* be `msFromTime(t)`; otherwise, let *milli* be `ToNumber(ms)`.
7. Let *newDate* be `MakeDate(Day(t), MakeTime(h, m, s, milli))`.
8. Let *v* be `TimeClip(newDate)`.
9. Set the `[[PrimitiveValue]]` internal property of this Date object to *v*.
10. Return *v*.

The `length` property of the `setUTCHours` method is 4.

15.9.5.36 Date.prototype.setDate (date)

1. Let *t* be the result of `LocalTime(this time value)`.
2. Let *dt* be `ToNumber(date)`.
3. Let *newDate* be `MakeDate(MakeDay(YearFromTime(t), MonthFromTime(t), dt), TimeWithinDay(t))`.
4. Let *u* be `TimeClip(UTC(newDate))`.
5. Set the `[[PrimitiveValue]]` internal property of this Date object to *u*.
6. Return *u*.

15.9.5.37 Date.prototype.setUTCDate (date)

1. Let *t* be this time value.
2. [ReturnIfAbrupt\(*t*\)](#).
3. Let *dt* be `ToNumber(date)`.
4. Let *newDate* be `MakeDate(MakeDay(YearFromTime(t), MonthFromTime(t), dt), TimeWithinDay(t))`.
5. Let *v* be `TimeClip(newDate)`.
6. Set the `[[PrimitiveValue]]` internal property of this Date object to *v*.
7. Return *v*.

15.9.5.38 Date.prototype.setMonth (month [, date])

If *date* is not specified, this behaves as if *date* were specified with the value `getDate()`.

1. Let *t* be the result of `LocalTime(this time value)`.
2. Let *m* be `ToNumber(month)`.
3. If *date* is not specified, then let *dt* be `DateFromTime(t)`; otherwise, let *dt* be `ToNumber(date)`.
4. Let *newDate* be `MakeDate(MakeDay(YearFromTime(t), m, dt), TimeWithinDay(t))`.
5. Let *u* be `TimeClip(UTC(newDate))`.
6. Set the `[[PrimitiveValue]]` internal property of this Date object to *u*.
7. Return *u*.

The `length` property of the `setMonth` method is 2.

15.9.5.39 Date.prototype.setUTCMonth (month [, date])

If *date* is not specified, this behaves as if *date* were specified with the value `getUTCDate()`.

1. Let *t* be this time value.

2. ReturnIfAbrupt(*t*).

3. Let *m* be ToNumber(*month*).
4. If *date* is not specified, then let *dt* be DateFromTime(*t*); otherwise, let *dt* be ToNumber(*date*).
5. Let *newDate* be MakeDate(MakeDay(YearFromTime(*t*), *m*, *dt*), TimeWithinDay(*t*)).
6. Let *v* be TimeClip(*newDate*).
7. Set the [[PrimitiveValue]] internal property of this Date object to *v*.
8. Return *v*.

The `length` property of the `setUTCMonth` method is **2**.

15.9.5.40 Date.prototype.setFullYear (year [, month [, date]])

If *month* is not specified, this behaves as if *month* were specified with the value `getMonth()`.

If *date* is not specified, this behaves as if *date* were specified with the value `getDate()`.

1. Let *t* be the result of LocalTime(this time value); but if this time value is `NaN`, let *t* be `+0`.
2. Let *y* be ToNumber(*year*).
3. If *month* is not specified, then let *m* be MonthFromTime(*t*); otherwise, let *m* be ToNumber(*month*).
4. If *date* is not specified, then let *dt* be DateFromTime(*t*); otherwise, let *dt* be ToNumber(*date*).
5. Let *newDate* be MakeDate(MakeDay(*y*, *m*, *dt*), TimeWithinDay(*t*)).
6. Let *u* be TimeClip(UTC(*newDate*)).
7. Set the [[PrimitiveValue]] internal property of this Date object to *u*.
8. Return *u*.

The `length` property of the `setFullYear` method is **3**.

15.9.5.41 Date.prototype.setUTCFullYear (year [, month [, date]])

If *month* is not specified, this behaves as if *month* were specified with the value `getUTCMonth()`.

If *date* is not specified, this behaves as if *date* were specified with the value `getUTCDate()`.

1. Let *t* be this time value; but if this time value is `NaN`, let *t* be `+0`.
2. ReturnIfAbrupt(*t*).
3. Let *y* be ToNumber(*year*).
4. If *month* is not specified, then let *m* be MonthFromTime(*t*); otherwise, let *m* be ToNumber(*month*).
5. If *date* is not specified, then let *dt* be DateFromTime(*t*); otherwise, let *dt* be ToNumber(*date*).
6. Let *newDate* be MakeDate(MakeDay(*y*, *m*, *dt*), TimeWithinDay(*t*)).
7. Let *v* be TimeClip(*newDate*).
8. Set the [[PrimitiveValue]] internal property of this Date object to *v*.
9. Return *v*.

The `length` property of the `setUTCFullYear` method is **3**.

15.9.5.42 Date.prototype.toUTCString ()

This function returns a String value. The contents of the String are implementation-dependent, but are intended to represent the Date in a convenient, human-readable form in UTC.

NOTE The intent is to produce a String representation of a date that is more readable than the format specified in 15.9.1.15. It is not essential that the chosen format be unambiguous or easily machine parsable. If an implementation does not have a preferred human-readable format it is recommended to use the format defined in 15.9.1.15 but with a space rather than a “T” used to separate the date and time elements.

15.9.5.43 Date.prototype.toISOString ()

This function returns a String value represent the instance in time represented by this Date object. The format of the String is the Date Time string format defined in 15.9.1.15. All fields are present in the String. The time

zone is always UTC, denoted by the suffix Z. If the time value of this object is not a finite Number a **RangeError** exception is thrown.

15.9.5.44 Date.prototype.toJSON (key)

This function provides a String representation of a Date object for use by `JSON.stringify` (15.12.3).

When the `toJSON` method is called with argument `key`, the following steps are taken:

1. Let `O` be the result of calling `ToObject`, giving it the `this` value as its argument.
2. Let `tv` be `ToPrimitive(O, hint Number)`.
3. If `tv` is a Number and is not finite, return `null`.
4. Let `toISO` be the result of calling the `[[Get]]` internal method of `O` with argument `"toISOString"`.
5. `ReturnIfAbrupt(toISO)`.
6. If `IsCallable(toISO)` is `false`, throw a `TypeError` exception.
7. Return the result of calling the `[[Call]]` internal method of `toISO` with `O` as the `this` value and an empty argument list.

NOTE 1 The argument is ignored.

NOTE 2 The `toJSON` function is intentionally generic; it does not require that its `this` value be a Date object. Therefore, it can be transferred to other kinds of objects for use as a method. However, it does require that any such object have a `toISOString` method. An object is free to use the argument `key` to filter its stringification.

15.9.6 Properties of Date Instances

Date instances inherit properties from the Date prototype object and have a `[[NativeBrand]]` internal whose value is `NativeDate`. Date instances also have a `[[PrimitiveValue]]` internal property.

The `[[PrimitiveValue]]` internal property is time value represented by this Date object.

Deleted: their
Deleted: Class
Deleted: IsDate
Deleted: property value is "Date"

15.10 RegExp (Regular Expression) Objects

A RegExp object contains a regular expression and the associated flags.

NOTE The form and functionality of regular expressions is modelled after the regular expression facility in the Perl 5 programming language.

15.10.1 Patterns

The `RegExp` constructor applies the following grammar to the input pattern String. An error occurs if the grammar cannot interpret the String as an expansion of `Pattern`.

Syntax

Pattern ::=
Disjunction

Disjunction ::=
Alternative
Alternative | *Disjunction*

Alternative ::=
[empty]
Alternative Term

Term ::=
Assertion
Atom
Atom Quantifier

Assertion ::

```

^
$ 
\ b
\ B
( ? = Disjunction )
( ? ! Disjunction )

```

Quantifier ::

```

QuantifierPrefix
QuantifierPrefix ?

```

QuantifierPrefix ::

```

*
+
?
{ DecimalDigits }
{ DecimalDigits , }
{ DecimalDigits , DecimalDigits }

```

Atom ::

```

PatternCharacter
.
\ AtomEscape
CharacterClass
( Disjunction )
( ? : Disjunction )

```

PatternCharacter ::

```

SourceCharacter but not one of
^ $ \ . * + ? ( ) [ ] { } |

```

AtomEscape ::

```

DecimalEscape
CharacterEscape
CharacterClassEscape

```

CharacterEscape ::

```

ControlEscape
c ControlLetter
HexEscapeSequence
UnicodeEscapeSequence
IdentityEscape

```

*ControlEscape :: **one of***

a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z

*ControlLetter :: **one of***

IdentityEscape ::

```

SourceCharacter but not IdentifierPart
<ZWJ>
<ZWNJ>

```

DecimalEscape ::

```

DecimalIntegerLiteral [lookahead ≠ DecimalDigit]

```

CharacterClassEscape :: one of
 d D s S w W

CharacterClass ::
 [[lookahead $\notin \{\}\}$] *ClassRanges*]
 [^ *ClassRanges*]

ClassRanges ::
 [empty]
NonemptyClassRanges

NonemptyClassRanges ::
ClassAtom
ClassAtom NonemptyClassRangesNoDash
ClassAtom - *ClassAtom ClassRanges*

NonemptyClassRangesNoDash ::
ClassAtom
ClassAtomNoDash NonemptyClassRangesNoDash
ClassAtomNoDash - *ClassAtom ClassRanges*

ClassAtom ::
 -
ClassAtomNoDash

ClassAtomNoDash ::
SourceCharacter but not one of \ or] or -
 \ *ClassEscape*

ClassEscape ::
DecimalEscape
b
CharacterEscape
CharacterClassEscape

15.10.2 Pattern Semantics

A regular expression pattern is converted into an internal procedure using the process described below. An implementation is encouraged to use more efficient algorithms than the ones listed below, as long as the results are the same. The internal procedure is used as the value of a *RegExp* object's *[[Match]]* internal property.

15.10.2.1 Notation

The descriptions below use the following variables:

- *Input* is the String being matched by the regular expression pattern. The notation *input*[*n*] means the *n*th character of *input*, where *n* can range between 0 (inclusive) and *InputLength* (exclusive).
- *InputLength* is the number of characters in the *Input* String.
- *NcapturingParens* is the total number of left capturing parentheses (i.e. the total number of times the *Atom* :: (*Disjunction*) production is expanded) in the pattern. A left capturing parenthesis is any (pattern character that is matched by the (terminal of the *Atom* :: (*Disjunction*) production.
- *IgnoreCase* is the setting of the *RegExp* object's *ignoreCase* property.
- *Multiline* is the setting of the *RegExp* object's *multiline* property.

Furthermore, the descriptions below use the following internal data structures:

- A *CharSet* is a mathematical set of characters.

- A *State* is an ordered pair $(\text{endIndex}, \text{captures})$ where endIndex is an integer and captures is an internal array of $N\text{capturingParens}$ values. *States* are used to represent partial match states in the regular expression matching algorithms. The endIndex is one plus the index of the last input character matched so far by the pattern, while captures holds the results of capturing parentheses. The n^{th} element of captures is either a String that represents the value obtained by the n^{th} set of capturing parentheses or **undefined** if the n^{th} set of capturing parentheses hasn't been reached yet. Due to backtracking, many *States* may be in use at any time during the matching process.
- A *MatchResult* is either a *State* or the special token **failure** that indicates that the match failed.
- A *Continuation* procedure is an internal closure (i.e. an internal procedure with some arguments already bound to values) that takes one *State* argument and returns a *MatchResult* result. If an internal closure references variables bound in the function that creates the closure, the closure uses the values that these variables had at the time the closure was created. The *Continuation* attempts to match the remaining portion (specified by the closure's already-bound arguments) of the pattern against the input String, starting at the intermediate state given by its *State* argument. If the match succeeds, the *Continuation* returns the final *State* that it reached; if the match fails, the *Continuation* returns **failure**.
- A *Matcher* procedure is an internal closure that takes two arguments -- a *State* and a *Continuation* -- and returns a *MatchResult* result. A *Matcher* attempts to match a middle subpattern (specified by the closure's already-bound arguments) of the pattern against the input String, starting at the intermediate state given by its *State* argument. The *Continuation* argument should be a closure that matches the rest of the pattern. After matching the subpattern of a pattern to obtain a new *State*, the *Matcher* then calls *Continuation* on that new *State* to test if the rest of the pattern can match as well. If it can, the *Matcher* returns the *State* returned by *Continuation*; if not, the *Matcher* may try different choices at its choice points, repeatedly calling *Continuation* until it either succeeds or all possibilities have been exhausted.
- An *AssertionTester* procedure is an internal closure that takes a *State* argument and returns a Boolean result. The assertion tester tests a specific condition (specified by the closure's already-bound arguments) against the current place in the input String and returns **true** if the condition matched or **false** if not.
- An *EscapeValue* is either a character or an integer. An *EscapeValue* is used to denote the interpretation of a *DecimalEscape* escape sequence: a character *ch* means that the escape sequence is interpreted as the character *ch*, while an integer *n* means that the escape sequence is interpreted as a backreference to the n^{th} set of capturing parentheses.

15.10.2.2 Pattern

The production *Pattern* :: *Disjunction* evaluates as follows:

1. Evaluate *Disjunction* to obtain a *Matcher* *m*.
2. Return an internal closure that takes two arguments, a String *str* and an integer *index*, and performs the following:
 1. Let *Input* be the given String *str*. This variable will be used throughout the algorithms in 15.10.2.
 2. Let *InputLength* be the length of *Input*. This variable will be used throughout the algorithms in 15.10.2.
 3. Let *c* be a *Continuation* that always returns its *State* argument as a successful *MatchResult*.
 4. Let *cap* be an internal array of *NcapturingParens* **undefined** values, indexed 1 through *NcapturingParens*.
 5. Let *x* be the *State* (*index*, *cap*).
 6. Call *m(x, c)* and return its result.

NOTE A Pattern evaluates ("compiles") to an internal procedure value. `RegExp.prototype.exec` can then apply this procedure to a String and an offset within the String to determine whether the pattern would match starting at exactly that offset within the String, and, if it does match, what the values of the capturing parentheses would be. The algorithms in 15.10.2 are designed so that compiling a pattern may throw a **SyntaxError** exception; on the other hand, once the pattern is successfully compiled, applying its result internal procedure to find a match in a String cannot throw an exception (except for any host-defined exceptions that can occur anywhere such as out-of-memory).

15.10.2.3 Disjunction

The production *Disjunction :: Alternative* evaluates by evaluating *Alternative* to obtain a *Matcher* and returning that *Matcher*.

The production *Disjunction :: Alternative | Disjunction* evaluates as follows:

1. Evaluate *Alternative* to obtain a *Matcher* *m1*.
2. Evaluate *Disjunction* to obtain a *Matcher* *m2*.
3. Return an internal *Matcher* closure that takes two arguments, a State *x* and a Continuation *c*, and performs the following:
 1. Call *m1(x, c)* and let *r* be its result.
 2. If *r* isn't **false**, return *r*.
 3. Call *m2(x, c)* and return its result.

NOTE The `|` regular expression operator separates two alternatives. The pattern first tries to match the left *Alternative* (followed by the sequel of the regular expression); if it fails, it tries to match the right *Disjunction* (followed by the sequel of the regular expression). If the left *Alternative*, the right *Disjunction*, and the sequel all have choice points, all choices in the sequel are tried before moving on to the next choice in the left *Alternative*. If choices in the left *Alternative* are exhausted, the right *Disjunction* is tried instead of the left *Alternative*. Any capturing parentheses inside a portion of the pattern skipped by `|` produce **undefined** values instead of Strings. Thus, for example,

```
/a|ab/.exec("abc")
```

returns the result "a" and not "ab". Moreover,

```
/((a)|(ab))((c)|(bc))/.exec("abc")
```

returns the array

```
["abc", "a", "a", undefined, "bc", undefined, "bc"]
```

and not

```
["abc", "ab", undefined, "ab", "c", "c", undefined]
```

15.10.2.4 Alternative

The production *Alternative :: [empty]* evaluates by returning a *Matcher* that takes two arguments, a State *x* and a Continuation *c*, and returns the result of calling *c(x)*.

The production *Alternative :: Alternative Term* evaluates as follows:

1. Evaluate *Alternative* to obtain a *Matcher* *m1*.
2. Evaluate *Term* to obtain a *Matcher* *m2*.
3. Return an internal *Matcher* closure that takes two arguments, a State *x* and a Continuation *c*, and performs the following:
 1. Create a Continuation *d* that takes a State argument *y* and returns the result of calling *m2(y, c)*.
 2. Call *m1(x, d)* and return its result.

NOTE Consecutive *Terms* try to simultaneously match consecutive portions of the input String. If the left *Alternative*, the right *Term*, and the sequel of the regular expression all have choice points, all choices in the sequel are tried before moving on to the next choice in the right *Term*, and all choices in the right *Term* are tried before moving on to the next choice in the left *Alternative*.

15.10.2.5 Term

The production *Term :: Assertion* evaluates by returning an internal *Matcher* closure that takes two arguments, a State *x* and a Continuation *c*, and performs the following:

1. Evaluate *Assertion* to obtain an *AssertionTester* *t*.
2. Call *t(x)* and let *r* be the resulting Boolean value.
3. If *r* is **false**, return **false**.
4. Call *c(x)* and return its result.

The production *Term :: Atom* evaluates by evaluating *Atom* to obtain a *Matcher* and returning that *Matcher*.

The production *Term* :: *Atom Quantifier* evaluates as follows:

1. Evaluate *Atom* to obtain a Matcher *m*.
2. Evaluate *Quantifier* to obtain the three results: an integer *min*, an integer (or ∞) *max*, and Boolean *greedy*.
3. If *max* is finite and less than *min*, then throw a **SyntaxError** exception.
4. Let *parenIndex* be the number of left capturing parentheses in the entire regular expression that occur to the left of this production expansion's *Term*. This is the total number of times the *Atom* :: (*Disjunction*) production is expanded prior to this production's *Term* plus the total number of *Atom* :: (*Disjunction*) productions enclosing this *Term*.
5. Let *parenCount* be the number of left capturing parentheses in the expansion of this production's *Atom*. This is the total number of *Atom* :: (*Disjunction*) productions enclosed by this production's *Atom*.
6. Return an internal Matcher closure that takes two arguments, a State *x* and a Continuation *c*, and performs the following:
 1. Call *RepeatMatcher*(*m*, *min*, *max*, *greedy*, *x*, *c*, *parenIndex*, *parenCount*) and return its result.

The abstract operation *RepeatMatcher* takes eight parameters, a Matcher *m*, an integer *min*, an integer (or ∞) *max*, a Boolean *greedy*, a State *x*, a Continuation *c*, an integer *parenIndex*, and an integer *parenCount*, and performs the following:

1. If *max* is zero, then call *c(x)* and return its result.
2. Create an internal Continuation closure *d* that takes one State argument *y* and performs the following:
 1. If *min* is zero and *y*'s *endIndex* is equal to *x*'s *endIndex*, then return **failure**.
 2. If *min* is zero then let *min2* be zero; otherwise let *min2* be *min*-1.
 3. If *max* is ∞ , then let *max2* be ∞ ; otherwise let *max2* be *max*-1.
 4. Call *RepeatMatcher*(*m*, *min2*, *max2*, *greedy*, *y*, *c*, *parenIndex*, *parenCount*) and return its result.
3. Let *cap* be a fresh copy of *x*'s *captures* internal array.
4. For every integer *k* that satisfies *parenIndex* < *k* and *k* ≤ *parenIndex*+*parenCount*, set *cap[k]* to **undefined**.
5. Let *e* be *x*'s *endIndex*.
6. Let *xr* be the State (*e*, *cap*).
7. If *min* is not zero, then call *m(xr, d)* and return its result.
8. If *greedy* is **false**, then
 - a. Call *c(x)* and let *z* be its result.
 - b. If *z* is not **failure**, return *z*.
 - c. Call *m(xr, d)* and return its result.
9. Call *m(xr, d)* and let *z* be its result.
10. If *z* is not **failure**, return *z*.
11. Call *c(x)* and return its result.

NOTE 1 An *Atom* followed by a *Quantifier* is repeated the number of times specified by the *Quantifier*. A *Quantifier* can be non-greedy, in which case the *Atom* pattern is repeated as few times as possible while still matching the sequel, or it can be greedy, in which case the *Atom* pattern is repeated as many times as possible while still matching the sequel. The *Atom* pattern is repeated rather than the input String that it matches, so different repetitions of the *Atom* can match different input substrings.

NOTE 2 If the *Atom* and the sequel of the regular expression all have choice points, the *Atom* is first matched as many (or as few, if non-greedy) times as possible. All choices in the sequel are tried before moving on to the next choice in the last repetition of *Atom*. All choices in the last (*n*th) repetition of *Atom* are tried before moving on to the next choice in the next-to-last (*n*-1)st repetition of *Atom*; at which point it may turn out that more or fewer repetitions of *Atom* are now possible; these are exhausted (again, starting with either as few or as many as possible) before moving on to the next choice in the (*n*-1)st repetition of *Atom* and so on.

Compare

```
/a[a-z]{2,4}/.exec("abcdefghijkl")
```

which returns "abcde" with

```
/a[a-z]{2,4}?/.exec("abcdefghijkl")
```

which returns "abc".

Consider also

```
/ (aa|aabaac|ba|b|c) */ .exec("aabaac")
```

which, by the choice point ordering above, returns the array

```
["aabaa", "ba"]
```

and not any of:

```
["aabaac", "aabaac"]
["aabaac", "c"]
```

The above ordering of choice points can be used to write a regular expression that calculates the greatest common divisor of two numbers (represented in unary notation). The following example calculates the gcd of 10 and 15:

```
"aaaaaaaaaaa,aaaaaaaaaaaaaaa".replace(/^(\w+)\1*,\1+$/,"$1")
```

which returns the gcd in unary notation "aaaaa".

NOTE 3 Step 4 of the RepeatMatcher clears *Atom*'s captures each time *Atom* is repeated. We can see its behaviour in the regular expression

```
/ (\w) ((\w)+)?((\w)) */ .exec("zaacbbbcac")
```

which returns the array

```
["zaacbbbcac", "z", "ac", "a", undefined, "c"]
```

and not

```
["zaacbbbcac", "z", "ac", "a", "bbb", "c"]
```

because each iteration of the outermost * clears all captured Strings contained in the quantified *Atom*, which in this case includes capture Strings numbered 2, 3, 4, and 5.

NOTE 4 Step 1 of the RepeatMatcher's *d* closure states that, once the minimum number of repetitions has been satisfied, any more expansions of *Atom* that match the empty String are not considered for further repetitions. This prevents the regular expression engine from falling into an infinite loop on patterns such as:

```
/ (\w*) */ .exec("b")
```

or the slightly more complicated:

```
/ (\w*)\b\1+ */ .exec("baaaac")
```

which returns the array

```
["b", ""]
```

15.10.2.6 Assertion

The production *Assertion* :: ^ evaluates by returning an internal AssertionTester closure that takes a State argument *x* and performs the following:

1. Let *e* be *x*'s *endIndex*.
2. If *e* is zero, return **true**.
3. If *Multiline* is **false**, return **false**.
4. If the character *Input*[*e*-1] is one of *LineTerminator*, return **true**.
5. Return **false**.

The production *Assertion* :: \$ evaluates by returning an internal AssertionTester closure that takes a State argument *x* and performs the following:

1. Let *e* be *x*'s *endIndex*.
2. If *e* is equal to *InputLength*, return **true**.
3. If *Multiline* is **false**, return **false**.
4. If the character *Input*[*e*] is one of *LineTerminator*, return **true**.
5. Return **false**.

Deleted: multiline

The production *Assertion* :: \ b evaluates by returning an internal AssertionTester closure that takes a State argument *x* and performs the following:

1. Let *e* be *x*'s *endIndex*.
2. Call *IsWordChar*(*e*-1) and let *a* be the Boolean result.
3. Call *IsWordChar*(*e*) and let *b* be the Boolean result.
4. If *a* is **true** and *b* is **false**, return **true**.
5. If *a* is **false** and *b* is **true**, return **true**.

6. Return **false**.

The production *Assertion :: \ b* evaluates by returning an internal AssertionTester closure that takes a State argument *x* and performs the following:

1. Let *e* be *x*'s *endIndex*.
2. Call *IsWordChar*(*e*-1) and let *a* be the Boolean result.
3. Call *IsWordChar*(*e*) and let *b* be the Boolean result.
4. If *a* is **true** and *b* is **false**, return **false**.
5. If *a* is **false** and *b* is **true**, return **false**.
6. Return **true**.

The production *Assertion :: (? = Disjunction)* evaluates as follows:

1. Evaluate *Disjunction* to obtain a Matcher *m*.
2. Return an internal Matcher closure that takes two arguments, a State *x* and a Continuation *c*, and performs the following steps:
 1. Let *d* be a Continuation that always returns its State argument as a successful MatchResult.
 2. Call *m*(*x*, *d*) and let *r* be its result.
 3. If *r* is **failure**, return **failure**.
 4. Let *y* be *r*'s State.
 5. Let *cap* be *y*'s *captures* internal array.
 6. Let *xe* be *x*'s *endIndex*.
 7. Let *z* be the State (*xe*, *cap*).
 8. Call *c*(*z*) and return its result.

The production *Assertion :: (? ! Disjunction)* evaluates as follows:

1. Evaluate *Disjunction* to obtain a Matcher *m*.
2. Return an internal Matcher closure that takes two arguments, a State *x* and a Continuation *c*, and performs the following steps:
 1. Let *d* be a Continuation that always returns its State argument as a successful MatchResult.
 2. Call *m*(*x*, *d*) and let *r* be its result.
 3. If *r* isn't **failure**, return **failure**.
 4. Call *c*(*x*) and return its result.

The abstract operation *IsWordChar* takes an integer parameter *e* and performs the following:

1. If *e* == -1 or *e* == *InputLength*, return **false**.
2. Let *c* be the character *Input*[*e*].
3. If *c* is one of the sixty-three characters below, return **true**.

a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
0	1	2	3	4	5	6	7	8	9	_															
4. Return **false**.

15.10.2.7 Quantifier

The production *Quantifier :: QuantifierPrefix* evaluates as follows:

1. Evaluate *QuantifierPrefix* to obtain the two results: an integer *min* and an integer (or ∞) *max*.
2. Return the three results *min*, *max*, and **true**.

The production *Quantifier :: QuantifierPrefix ?* evaluates as follows:

1. Evaluate *QuantifierPrefix* to obtain the two results: an integer *min* and an integer (or ∞) *max*.
2. Return the three results *min*, *max*, and **false**.

The production *QuantifierPrefix* :: * evaluates by returning the two results 0 and ∞ .

The production *QuantifierPrefix* :: + evaluates by returning the two results 1 and ∞ .

The production *QuantifierPrefix* :: ? evaluates by returning the two results 0 and 1.

The production *QuantifierPrefix* :: { *DecimalDigits* } evaluates as follows:

1. Let *i* be the MV of *DecimalDigits* (see 7.8.3).
2. Return the two results *i* and *i*.

The production *QuantifierPrefix* :: { *DecimalDigits* , } evaluates as follows:

1. Let *i* be the MV of *DecimalDigits*.
2. Return the two results *i* and ∞ .

The production *QuantifierPrefix* :: { *DecimalDigits* , *DecimalDigits* } evaluates as follows:

1. Let *i* be the MV of the first *DecimalDigits*.
2. Let *j* be the MV of the second *DecimalDigits*.
3. Return the two results *i* and *j*.

15.10.2.8 Atom

The production *Atom* :: *PatternCharacter* evaluates as follows:

1. Let *ch* be the character represented by *PatternCharacter*.
2. Let *A* be a one-element CharSet containing the character *ch*.
3. Call *CharacterSetMatcher*(*A*, **false**) and return its Matcher result.

The production *Atom* :: . evaluates as follows:

1. Let *A* be the set of all characters except *LineTerminator*.
2. Call *CharacterSetMatcher*(*A*, **false**) and return its Matcher result.

The production *Atom* :: \ *AtomEscape* evaluates by evaluating *AtomEscape* to obtain a Matcher and returning that Matcher.

The production *Atom* :: *CharacterClass* evaluates as follows:

1. Evaluate *CharacterClass* to obtain a CharSet *A* and a Boolean *invert*.
2. Call *CharacterSetMatcher*(*A*, *invert*) and return its Matcher result.

The production *Atom* :: (*Disjunction*) evaluates as follows:

1. Evaluate *Disjunction* to obtain a Matcher *m*.
2. Let *parenIndex* be the number of left capturing parentheses in the entire regular expression that occur to the left of this production expansion's initial left parenthesis. This is the total number of times the *Atom* :: (*Disjunction*) production is expanded prior to this production's *Atom* plus the total number of *Atom* :: (*Disjunction*) productions enclosing this *Atom*.
3. Return an internal Matcher closure that takes two arguments, a State *x* and a Continuation *c*, and performs the following steps:
 1. Create an internal Continuation closure *d* that takes one State argument *y* and performs the following steps:
 1. Let *cap* be a fresh copy of *y*'s *captures* internal array.
 2. Let *xe* be *x*'s *endIndex*.
 3. Let *ye* be *y*'s *endIndex*.
 4. Let *s* be a fresh String whose characters are the characters of *Input* at positions *xe* (inclusive) through *ye* (exclusive).

5. Set $cap[parenIndex+1]$ to s .
 6. Let z be the State (ye, cap).
 7. Call $c(z)$ and return its result.
2. Call $m(x, d)$ and return its result.

The production $Atom :: (? : Disjunction)$ evaluates by evaluating $Disjunction$ to obtain a Matcher and returning that Matcher.

The abstract operation $CharacterSetMatcher$ takes two arguments, a CharSet A and a Boolean flag $invert$, and performs the following:

1. Return an internal Matcher closure that takes two arguments, a State x and a Continuation c , and performs the following steps:
 1. Let e be x 's *endIndex*.
 2. If $e == InputLength$, return **failure**.
 3. Let ch be the character $Input[e]$.
 4. Let cc be the result of $Canonicalize(ch)$.
 5. If $invert$ is **false**, then
 - a. If there does not exist a member a of set A such that $Canonicalize(a) == cc$, return **failure**.
 6. Else $invert$ is **true**,
 - a. If there exists a member a of set A such that $Canonicalize(a) == cc$, return **failure**.
7. Let cap be x 's *captures* internal array.
8. Let y be the State ($e+1, cap$).
9. Call $c(y)$ and return its result.

The abstract operation $Canonicalize$ takes a character parameter ch and performs the following steps:

1. If $IgnoreCase$ is **false**, return ch .
2. Let u be ch converted to upper case as if by calling the standard built-in method `String.prototype.toUpperCase` on the one-character String ch .
3. If u does not consist of a single character, return ch .
4. Let cu be u 's character.
5. If ch 's code unit value is greater than or equal to decimal 128 and cu 's code unit value is less than decimal 128, then return ch .
6. Return cu .

NOTE 1 Parentheses of the form $(Disjunction)$ serve both to group the components of the $Disjunction$ pattern together and to save the result of the match. The result can be used either in a backreference (\ followed by a nonzero decimal number), referenced in a replace String, or returned as part of an array from the regular expression matching internal procedure. To inhibit the capturing behaviour of parentheses, use the form $(?: Disjunction)$ instead.

NOTE 2 The form $(?= Disjunction)$ specifies a zero-width positive lookahead. In order for it to succeed, the pattern inside $Disjunction$ must match at the current position, but the current position is not advanced before matching the sequel. If $Disjunction$ can match at the current position in several ways, only the first one is tried. Unlike other regular expression operators, there is no backtracking into a $(?=$ form (this unusual behaviour is inherited from Perl). This only matters when the $Disjunction$ contains capturing parentheses and the sequel of the pattern contains backreferences to those captures.

For example,

```
/(?=(a+))/ . exec("baaabac")
```

matches the empty String immediately after the first **b** and therefore returns the array:

```
[" ", "aaa"]
```

To illustrate the lack of backtracking into the lookahead, consider:

```
/(?=(a+))a*b\1/. exec("baaabac")
```

This expression returns

```
["aba", "a"]
```

and not:

```
[ "aaaba", "a" ]
```

NOTE 3 The form `(?! Disjunction)` specifies a zero-width negative lookahead. In order for it to succeed, the pattern inside `Disjunction` must fail to match at the current position. The current position is not advanced before matching the sequel. `Disjunction` can contain capturing parentheses, but backreferences to them only make sense from within `Disjunction` itself. Backreferences to these capturing parentheses from elsewhere in the pattern always return `undefined` because the negative lookahead must fail for the pattern to succeed. For example,

```
/ (.*)? a (?! (a+) b \2 c) \2 (.*) / .exec ("baaabaaac")
```

looks for an `a` not immediately followed by some positive number `n` of `a`'s, a `b`, another `n` `a`'s (specified by the first `\2`) and a `c`. The second `\2` is outside the negative lookahead, so it matches against `undefined` and therefore always succeeds. The whole expression returns the array:

```
[ "baaabaaac", "ba", undefined, "abaac" ]
```

In case-insensitive matches all characters are implicitly converted to upper case immediately before they are compared. However, if converting a character to upper case would expand that character into more than one character (such as converting "`B`" (`\u000DE`) into "`ss`"), then the character is left as-is instead. The character is also left as-is if it is not an ASCII character but converting it to upper case would make it into an ASCII character. This prevents Unicode characters such as `\u0131` and `\u017F` from matching regular expressions such as `/[a-z]/i`, which are only intended to match ASCII letters. Furthermore, if these conversions were allowed, then `/[^w]/i` would match each of `a`, `b`, ..., `h`, but not `i` or `s`.

15.10.2.9 AtomEscape

The production `AtomEscape :: DecimalEscape` evaluates as follows:

1. Evaluate `DecimalEscape` to obtain an `EscapeValue E`.
2. If `E` is a character, then
 - a. Let `ch` be `E`'s character.
 - b. Let `A` be a one-element CharSet containing the character `ch`.
 - c. Call `CharacterSetMatcher(A, false)` and return its Matcher result.
3. `E` must be an integer. Let `n` be that integer.
4. If `n=0` or `n>NCapturingParens` then throw a **SyntaxError** exception.
5. Return an internal Matcher closure that takes two arguments, a State `x` and a Continuation `c`, and performs the following:
 1. Let `cap` be `x`'s `captures` internal array.
 2. Let `s` be `cap[n]`.
 3. If `s` is `undefined`, then call `c(x)` and return its result.
 4. Let `e` be `x`'s `endIndex`.
 5. Let `len` be `s`'s length.
 6. Let `f` be `e+len`.
 7. If `f>InputLength`, return **failure**.
 8. If there exists an integer `i` between 0 (inclusive) and `len` (exclusive) such that `Canonicalize(s[i])` is not the same character as `Canonicalize(Input[e+i])`, then return **failure**.
 9. Let `y` be the State `(f, cap)`.
 10. Call `c(y)` and return its result.

The production `AtomEscape :: CharacterEscape` evaluates as follows:

1. Evaluate `CharacterEscape` to obtain a character `ch`.
2. Let `A` be a one-element CharSet containing the character `ch`.
3. Call `CharacterSetMatcher(A, false)` and return its Matcher result.

The production `AtomEscape :: CharacterClassEscape` evaluates as follows:

1. Evaluate `CharacterClassEscape` to obtain a CharSet `A`.
2. Call `CharacterSetMatcher(A, false)` and return its Matcher result.

NOTE An escape sequence of the form `\` followed by a nonzero decimal number `n` matches the result of the `n`th set of capturing parentheses (see 15.10.2.11). It is an error if the regular expression has fewer than `n` capturing parentheses.

If the regular expression has n or more capturing parentheses but the n th one is **undefined** because it has not captured anything, then the backreference always succeeds.

15.10.2.10 CharacterEscape

The production *CharacterEscape* :: *ControlEscape* evaluates by returning the character according to [Table 29](#).

Table 29 — ControlEscape Character Values

ControlEscape	Code Unit	Name	Symbol
t	\u0009	horizontal tab	<HT>
n	\u000A	line feed (new line)	<LF>
v	\u000B	vertical tab	<VT>
f	\u000C	form feed	<FF>
r	\u000D	carriage return	<CR>

Formatted Table

The production *CharacterEscape* :: c *ControlLetter* evaluates as follows:

1. Let *ch* be the character represented by *ControlLetter*.
2. Let *i* be *ch*'s code unit value.
3. Let *j* be the remainder of dividing *i* by 32.
4. Return the character whose code unit value is *j*.

The production *CharacterEscape* :: *HexEscapeSequence* evaluates by evaluating the CV of the *HexEscapeSequence* (see 7.8.4) and returning its character result.

The production *CharacterEscape* :: *UnicodeEscapeSequence* evaluates by evaluating the CV of the *UnicodeEscapeSequence* (see 7.8.4) and returning its character result.

The production *CharacterEscape* :: *IdentityEscape* evaluates by returning the character represented by *IdentityEscape*.

15.10.2.11 DecimalEscape

The production *DecimalEscape* :: *DecimalIntegerLiteral* [lookahead ≠ *DecimalDigit*] evaluates as follows:

1. Let *i* be the MV of *DecimalIntegerLiteral*.
2. If *i* is zero, return the EscapeValue consisting of a <NUL> character (Unicode value 0000).
3. Return the EscapeValue consisting of the integer *i*.

The definition of “the MV of *DecimalIntegerLiteral*” is in 7.8.3.

NOTE If \ is followed by a decimal number *n* whose first digit is not 0, then the escape sequence is considered to be a backreference. It is an error if *n* is greater than the total number of left capturing parentheses in the entire regular expression. \0 represents the <NUL> character and cannot be followed by a decimal digit.

15.10.2.12 CharacterClassEscape

The production *CharacterClassEscape* :: d evaluates by returning the ten-element set of characters containing the characters 0 through 9 inclusive.

The production *CharacterClassEscape* :: D evaluates by returning the set of all characters not included in the set returned by *CharacterClassEscape* :: d.

The production *CharacterClassEscape* :: s evaluates by returning the set of characters containing the characters that are on the right-hand side of the *WhiteSpace* (7.2) or *LineTerminator* (7.3) productions.

The production *CharacterClassEscape :: s* evaluates by returning the set of all characters not included in the set returned by *CharacterClassEscape :: s*.

The production *CharacterClassEscape :: w* evaluates by returning the set of characters containing the sixty-three characters:

a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
0	1	2	3	4	5	6	7	8	9	_															

The production *CharacterClassEscape :: w* evaluates by returning the set of all characters not included in the set returned by *CharacterClassEscape :: w*.

15.10.2.13 CharacterClass

The production *CharacterClass :: [lookahead ∈ {^}] ClassRanges]* evaluates by evaluating *ClassRanges* to obtain a CharSet and returning that CharSet and the Boolean **false**.

The production *CharacterClass :: [^ ClassRanges]* evaluates by evaluating *ClassRanges* to obtain a CharSet and returning that CharSet and the Boolean **true**.

15.10.2.14 ClassRanges

The production *ClassRanges :: [empty]* evaluates by returning the empty CharSet.

The production *ClassRanges :: NonemptyClassRanges* evaluates by evaluating *NonemptyClassRanges* to obtain a CharSet and returning that CharSet.

15.10.2.15 NonemptyClassRanges

The production *NonemptyClassRanges :: ClassAtom* evaluates by evaluating *ClassAtom* to obtain a CharSet and returning that CharSet.

The production *NonemptyClassRanges :: ClassAtom NonemptyClassRangesNoDash* evaluates as follows:

1. Evaluate *ClassAtom* to obtain a CharSet *A*.
2. Evaluate *NonemptyClassRangesNoDash* to obtain a CharSet *B*.
3. Return the union of CharSets *A* and *B*.

The production *NonemptyClassRanges :: ClassAtom - ClassAtom ClassRanges* evaluates as follows:

1. Evaluate the first *ClassAtom* to obtain a CharSet *A*.
2. Evaluate the second *ClassAtom* to obtain a CharSet *B*.
3. Evaluate *ClassRanges* to obtain a CharSet *C*.
4. Call *CharacterRange(A, B)* and let *D* be the resulting CharSet.
5. Return the union of CharSets *D* and *C*.

The abstract operation *CharacterRange* takes two CharSet parameters *A* and *B* and performs the following:

1. If *A* does not contain exactly one character or *B* does not contain exactly one character then throw a **SyntaxError** exception.
2. Let *a* be the one character in CharSet *A*.
3. Let *b* be the one character in CharSet *B*.
4. Let *i* be the code unit value of character *a*.
5. Let *j* be the code unit value of character *b*.
6. If *i > j* then throw a **SyntaxError** exception.
7. Return the set containing all characters numbered *i* through *j*, inclusive.

15.10.2.16 NonemptyClassRangesNoDash

The production *NonemptyClassRangesNoDash* :: *ClassAtom* evaluates by evaluating *ClassAtom* to obtain a CharSet and returning that CharSet.

The production *NonemptyClassRangesNoDash* :: *ClassAtomNoDash* *NonemptyClassRangesNoDash* evaluates as follows:

1. Evaluate *ClassAtomNoDash* to obtain a CharSet *A*.
2. Evaluate *NonemptyClassRangesNoDash* to obtain a CharSet *B*.
3. Return the union of CharSets *A* and *B*.

The production *NonemptyClassRangesNoDash* :: *ClassAtomNoDash* – *ClassAtom* *ClassRanges* evaluates as follows:

1. Evaluate *ClassAtomNoDash* to obtain a CharSet *A*.
2. Evaluate *ClassAtom* to obtain a CharSet *B*.
3. Evaluate *ClassRanges* to obtain a CharSet *C*.
4. Call *CharacterRange*(*A*, *B*) and let *D* be the resulting CharSet.
5. Return the union of CharSets *D* and *C*.

NOTE 1 *ClassRanges* can expand into single *ClassAtoms* and/or ranges of two *ClassAtoms* separated by dashes. In the latter case the *ClassRanges* includes all characters between the first *ClassAtom* and the second *ClassAtom*, inclusive; an error occurs if either *ClassAtom* does not represent a single character (for example, if one is \w) or if the first *ClassAtom*'s code unit value is greater than the second *ClassAtom*'s code unit value.

NOTE 2 Even if the pattern ignores case, the case of the two ends of a range is significant in determining which characters belong to the range. Thus, for example, the pattern /[\E-\F]/i matches only the letters E, F, e, and f, while the pattern /[\E-\f]/i matches all upper and lower-case ASCII letters as well as the symbols [, \,], ^, _, and `.

NOTE 3 A – character can be treated literally or it can denote a range. It is treated literally if it is the first or last character of *ClassRanges*, the beginning or end limit of a range specification, or immediately follows a range specification.

15.10.2.17 ClassAtom

The production *ClassAtom* :: – evaluates by returning the CharSet containing the one character –.

The production *ClassAtom* :: *ClassAtomNoDash* evaluates by evaluating *ClassAtomNoDash* to obtain a CharSet and returning that CharSet.

15.10.2.18 ClassAtomNoDash

The production *ClassAtomNoDash* :: *SourceCharacter* **but not one of \ or] or –** evaluates by returning a one-element CharSet containing the character represented by *SourceCharacter*.

The production *ClassAtomNoDash* :: \ *ClassEscape* evaluates by evaluating *ClassEscape* to obtain a CharSet and returning that CharSet.

15.10.2.19 ClassEscape

The production *ClassEscape* :: *DecimalEscape* evaluates as follows:

1. Evaluate *DecimalEscape* to obtain an EscapeValue *E*.
2. If *E* is not a character then throw a **SyntaxError** exception.
3. Let *ch* be *E*'s character.
4. Return the one-element CharSet containing the character *ch*.

The production *ClassEscape* :: \b evaluates by returning the CharSet containing the one character <BS> (Unicode value 0008).

The production *ClassEscape* :: *CharacterEscape* evaluates by evaluating *CharacterEscape* to obtain a character and returning a one-element CharSet containing that character.

The production *ClassEscape* :: *CharacterClassEscape* evaluates by evaluating *CharacterClassEscape* to obtain a CharSet and returning that CharSet.

NOTE A *ClassAtom* can use any of the escape sequences that are allowed in the rest of the regular expression except for `\b`, `\B`, and backreferences. Inside a *CharacterClass*, `\b` means the backspace character, while `\B` and backreferences raise errors. Using a backreference inside a *ClassAtom* causes an error.

15.10.3 The RegExp Constructor Called as a Function

15.10.3.1 RegExp(pattern, flags)

The following steps are taken:

1. If `Type(pattern)` is object and `pattern` has a `[[NativeBrand]]` internal property whose value is `NativeRegExp` and `flags` is `undefined`, then return `pattern`.
2. Return the result of the abstract operation `RegExpCreate` with arguments `pattern` and `flags`.

Deleted: abstraction operation

15.10.4 The RegExp Constructor

When `RegExp` is called as part of a `new` expression, it is a constructor: it initialises the newly created object.

15.10.4.1 new RegExp(pattern, flags)

The following steps are taken:

1. Return the result of the abstract operation `RegExpCreate` with arguments `pattern` and `flags`.

Deleted: abstraction operation

The abstract operation `RegExpCreate` with arguments `pattern` and `flags` does the following:

If `pattern` is an object `R` that has a `[[NativeBrand]]` internal property whose value is `NativeRegExp` and `flags` is `undefined`, then let `P` be the `pattern` used to construct `R` and let `F` be the `flags` used to construct `R`. If `pattern` is an object `R` that has a `[[NativeBrand]]` internal property whose value is `NativeRegExp` and `flags` is not `undefined`, then throw a `TypeError` exception. Otherwise, let `P` be the empty String if `pattern` is `undefined` and `Tostring(pattern)` otherwise, and let `F` be the empty String if `flags` is `undefined` and `Tostring(flags)` otherwise.

Deleted: n

Deleted: IsRegExp

Deleted: whose `[[Class]]` internal property is "RegExp"

Deleted: n

Deleted: IsRegExp

Deleted: whose `[[Class]]` internal property is "RegExp"

If the characters of `P` do not have the syntactic form `Pattern`, then throw a `SyntaxError` exception. Otherwise let the newly constructed object have a `[[Match]]` internal property obtained by evaluating ("compiling") the characters of `P` as a `Pattern` as described in 15.10.2.

If `F` contains any character other than `"g"`, `"i"`, or `"m"`, or if it contains the same character more than once, then throw a `SyntaxError` exception.

If a `SyntaxError` exception is not thrown, then:

Let `S` be a String in the form of a `Pattern` equivalent to `P`, in which certain characters are escaped as described below. `S` may or may not be identical to `P` or `pattern`; however, the internal procedure that would result from evaluating `S` as a `Pattern` must behave identically to the internal procedure given by the constructed object's `[[Match]]` internal property.

The characters `/` occurring in the pattern shall be escaped in `S` as necessary to ensure that the String value formed by concatenating the Strings `"/", S, "/"`, and `F` can be parsed (in an appropriate lexical context) as a `RegularExpressionLiteral` that behaves identically to the constructed regular expression. For example, if `P` is `"/"`, then `S` could be `"\/"` or `"\u002F"`, among other possibilities, but not `"/"`, because `///` followed by `F` would be parsed as a `SingleLineComment` rather than a `RegularExpressionLiteral`. If `P` is the empty String, this specification can be met by letting `S` be `"(?:)"`.

The following properties of the newly constructed object are data properties with the attributes that are specified in 15.10.7. The `[[Value]]` of each property is set as follows:

The `source` property of the newly constructed object is set to `S`.

The `global` property of the newly constructed object is set to a Boolean value that is `true` if `F` contains the character "g" and `false` otherwise.

The `ignoreCase` property of the newly constructed object is set to a Boolean value that is `true` if `F` contains the character "i" and `false` otherwise.

The property of the newly constructed object is set to a Boolean value that is `true` if `F` contains the character "m" and `false` otherwise.

The `lastIndex` property of the newly constructed object is set to `0`.

The `[[Prototype]]` internal property of the newly constructed object is set to the standard built-in `RegExp` prototype object as specified in 15.10.6.

The newly constructed object has a `[[NativeBrand]] internal property` whose value is `NativeRegExp`.

NOTE If pattern is a *StringLiteral*, the usual escape sequence substitutions are performed before the String is processed by `RegExp`. If pattern must contain an escape sequence to be recognised by `RegExp`, any backslash \ characters must be escaped within the *StringLiteral* to prevent them being removed when the contents of the *StringLiteral* are formed.

15.10.5 Properties of the `RegExp` Constructor

The value of the `[[Prototype]]` internal property of the `RegExp` constructor is the standard built-in `Function` prototype object (15.3.4).

Besides the internal properties and the `length` property (whose value is `2`), the `RegExp` constructor has the following properties:

15.10.5.1 `RegExp.prototype`

The initial value of `RegExp.prototype` is the `RegExp` prototype object (15.10.6).

This property shall have the attributes { `[[Writable]]: false`, `[[Enumerable]]: false`, `[[Configurable]]: false` }.

15.10.6 Properties of the `RegExp` Prototype Object

The value of the `[[Prototype]]` internal property of the `RegExp` prototype object is the standard built-in `Object` prototype object (15.2.4). The `RegExp` prototype object is itself a regular expression object; it has a `[[NativeBrand]] internal property` whose value is `NativeRegExp`. The initial values of the `RegExp` prototype object's data properties (15.10.7) are set as if the object was created by the expression `new RegExp()` where `RegExp` is that standard built-in constructor with that name.

The `RegExp` prototype object does not have a `valueOf` property of its own; however, it inherits the `valueOf` property from the `Object` prototype object.

In the following descriptions of functions that are properties of the `RegExp` prototype object, the phrase "this `RegExp` object" refers to the object that is the `this` value for the invocation of the function; a `TypeError` exception is thrown if the `this` value is not an object that has a `[[NativeBrand]] internal property` whose value is `NativeRegExp`.

Deleted: `[[Class]]` internal property of the
Deleted: `n`
Deleted: `IsRegExp`
Deleted: is set to "`RegExp`".

Deleted: `s`
Deleted: `n`
Deleted: `IsRegExp`
Deleted: `[[Class]]` is "`RegExp`".

Deleted: or an object for which the value of the
Deleted: `n`
Deleted: `Class`
Deleted: `IsRegExp`
Deleted: is not "`RegExp`".

15.10.6.1 RegExp.prototype.constructor

The initial value of `RegExp.prototype.constructor` is the standard built-in `RegExp` constructor.

15.10.6.2 RegExp.prototype.exec(string)

Performs a regular expression match of `string` against the regular expression and returns an Array object containing the results of the match, or `null` if `string` did not match.

The String `ToString(string)` is searched for an occurrence of the regular expression pattern as follows:

1. Let `R` be this `RegExp` object.
2. `ReturnIfAbrupt(R)`.
3. Let `S` be the value of `ToString(string)`
4. `ReturnIfAbrupt(S)`.
5. `Return the result of the RegExpExec abstract operation with arguments R and S.`

Deleted: abstraction operation

The abstract operation `RegExpExec` with arguments `R` (an object) and `S` (a string) performs the following steps:

1. Let `length` be the length of `S`.
2. Let `lastIndex` be the result of calling the `[[Get]]` internal method of `R` with argument `"lastIndex"`.
3. Let `i` be the value of `ToInteger(lastIndex)`.
4. `ReturnIfAbrupt(i)`.
5. Let `global` be the result of calling the `[[Get]]` internal method of `R` with argument `"global"`.
6. `ReturnIfAbrupt(global)`.
7. If `global` is `false`, then let `i = 0`.
8. Let `matchSucceeded` be `false`.
9. Repeat, while `matchSucceeded` is `false`
 - a. If `i < 0` or `i > length`, then
 - i. Let `putStatus` be the result of calling the `[[Put]]` internal method of `R` with arguments `"lastIndex"`, `0`, and `true`.
 - ii. ReturnIfAbrupt(putStatus).
 - iii. Return `null`.
 - b. Let `r` be the result of calling the `[[Match]]` internal method of `R` with arguments `S` and `i`.
 - c. If `r` is failure, then
 - i. Let `i = i + 1`.
 - d. else
 - i. Assert: r is a State.
 - ii. Set `matchSucceeded` to `true`.
10. Let `e` be `r`'s `endIndex` value.
11. If `global` is `true`,
 - a. Let `putStatus` be the result of calling the `[[Put]]` internal method of `R` with arguments `"lastIndex"`, `e`, and `true`.
 - b. ReturnIfAbrupt(putStatus).
12. Let `n` be the length of `r`'s `captures` array. (This is the same value as 15.10.2.1's `NCapturingParens`.)
13. Let `A` be the result of the abstract operation `ArrayCreate` with argument `0`.
14. Let `matchIndex` be `i`.
15. Assert: The following [DefineOwnProperty] calls will not result in an abrupt completion.
16. Call the `[[DefineOwnProperty]]` internal method of `A` with arguments `"index"`, Property Descriptor `{[[Value]]: matchIndex, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `true`.
17. Call the `[[DefineOwnProperty]]` internal method of `A` with arguments `"input"`, Property Descriptor `{[[Value]]: S, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `true`.
18. Call the `[[DefineOwnProperty]]` internal method of `A` with arguments `"length"`, Property Descriptor `{[[Value]]: n + 1}`, and `true`.
19. Let `matchedSubstr` be the matched substring (i.e. the portion of `S` between offset `i` inclusive and offset `e` exclusive).
20. Call the `[[DefineOwnProperty]]` internal method of `A` with arguments `"0"`, Property Descriptor `{[[Value]]: matchedSubstr, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `true`.

Deleted: Call

Deleted: Call

Deleted: `[[Match]]` returned

Deleted: Let

Deleted: be the

Deleted: result of the call to `[[Match]]`

Deleted: Call

Deleted: a new array created as if by the expression `new Array()` where `Array` is the standard built-in constructor with that name.

21. For each integer i such that $i > 0$ and $i \leq n$
 - a. Let $captureI$ be i^{th} element of r 's *captures* array.
 - b. Call the `[[DefineOwnProperty]]` internal method of A with arguments `ToString(i)`, `Property Descriptor {[[Value]]: captureI, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `true`.
22. Return A .

15.10.6.3 `RegExp.prototype.test(string)`

The following steps are taken:

1. Let R be this `RegExp` object.
2. ReturnIfAbrupt(R).
3. Let S be the value of `ToString(string)`.
4. ReturnIfAbrupt(S).
5. Let $match$ be the result of the `RegExpExec` abstract operation with arguments R and S .
6. ReturnIfAbrupt($match$).
7. If $match$ is not null, then return `true`; else return `false`.

15.10.6.4 `RegExp.prototype.toString()`

Return the String value formed by concatenating the Strings `"/"`, the String value of the `source` property of this `RegExp` object, and `"/"`; plus `"g"` if the `global` property is `true`, `"i"` if the `ignoreCase` property is `true`, and `"m"` if the `multiline` property is `true`.

NOTE The returned String has the form of a *RegularExpressionLiteral* that evaluates to another `RegExp` object with the same behaviour as this object.

15.10.7 Properties of `RegExp` Instances

`RegExp` instances inherit properties from the `RegExp` prototype object and have a `[[NativeBrand]]` internal property whose value is `NativeRegExp`. `RegExp` instances also have a `[[Match]]` internal property and a `length` property.

The value of the `[[Match]]` internal property is an implementation dependent representation of the *Pattern* of the `RegExp` object.

`RegExp` instances also have the following properties.

15.10.7.1 `source`

The value of the `source` property is a String in the form of a *Pattern* representing the current regular expression. This property shall have the attributes { `[[Writable]]: false`, `[[Enumerable]]: false`, `[[Configurable]]: false` }.

15.10.7.2 `global`

The value of the `global` property is a Boolean value indicating whether the flags contained the character `"g"`. This property shall have the attributes { `[[Writable]]: false`, `[[Enumerable]]: false`, `[[Configurable]]: false` }.

15.10.7.3 `ignoreCase`

The value of the `ignoreCase` property is a Boolean value indicating whether the flags contained the character `"i"`. This property shall have the attributes { `[[Writable]]: false`, `[[Enumerable]]: false`, `[[Configurable]]: false` }.

Deleted: abstraction operation

Deleted: evaluating the `RegExp.prototype.exec` (15.10.6.2) algorithm upon this `RegExp` object using `string` the argument

Comment [AWB7139]: Needs an algorithm

Deleted: their

Deleted: Class

Deleted: IsRegExp

Deleted: value is "RegExp"

15.10.7.4 multiline

The value of the `multiline` property is a Boolean value indicating whether the flags contained the character “`m`”. This property shall have the attributes { `[[Writable]]: false`, `[[Enumerable]]: false`, `[[Configurable]]: false` }.

15.10.7.5 lastIndex

The value of the `lastIndex` property specifies the String position at which to start the next match. It is coerced to an integer when used (see 15.10.6.2). This property shall have the attributes { `[[Writable]]: true`, `[[Enumerable]]: false`, `[[Configurable]]: false` }.

NOTE Unlike the other standard built-in properties of RegExp instances, `lastIndex` is writable.

15.11 Error Objects

Instances of Error objects are thrown as exceptions when runtime errors occur. The Error objects may also serve as base objects for user-defined exception classes.

15.11.1 The Error Constructor Called as a Function

When `Error` is called as a function rather than as a constructor, it creates and initialises a new Error object. Thus the function call `Error(...)` is equivalent to the object creation expression `new Error(...)` with the same arguments.

15.11.1.1 Error (message)

The `[[Prototype]]` internal property of the newly constructed object is set to the original Error prototype object, the one that is the initial value of `Error.prototype` (15.11.3.1).

The newly constructed object has a `[[NativeBrand]]` internal property whose value is NativeError.

The `[[Extensible]]` internal property of the newly constructed object is set to `true`.

If the argument `message` is not `undefined`, the `message` own property of the newly constructed object is set to `ToString(message)`.

- Deleted:** `[[Class]]` internal property of the
- Deleted:** is set to "Error"
- Deleted:** `n`
- Deleted:** `IsError`

15.11.2 The Error Constructor

When `Error` is called as part of a `new` expression, it is a constructor: it initialises the newly created object.

15.11.2.1 new Error (message)

The `[[Prototype]]` internal property of the newly constructed object is set to the original Error prototype object, the one that is the initial value of `Error.prototype` (15.11.3.1).

The newly constructed object has a `[[NativeBrand]]` internal property whose value is NativeError.

The `[[Extensible]]` internal property of the newly constructed object is set to `true`.

If the argument `message` is not `undefined`, the `message` own property of the newly constructed object is set to `ToString(message)`.

- Deleted:** `[[Class]]` internal property of the
- Deleted:** `Error`
- Deleted:** `n`
- Deleted:** `IsError`
- Deleted:** is set to "Error"

15.11.3 Properties of the Error Constructor

The value of the `[[Prototype]]` internal property of the Error constructor is the Function prototype object (15.3.4).

Besides the internal properties and the `length` property (whose value is `1`), the Error constructor has the following property:

15.11.3.1 Error.prototype

The initial value of `Error.prototype` is the Error prototype object (15.11.4).

This property has the attributes { `[[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false` }.

15.11.4 Properties of the Error Prototype Object

The Error prototype object is itself an Error object and has a `[[NativeBrand]] internal property` whose value is `NativeError`.

The value of the `[[Prototype]]` internal property of the Error prototype object is the standard built-in Object prototype object (15.2.4).

15.11.4.1 Error.prototype.constructor

The initial value of `Error.prototype.constructor` is the built-in `Error` constructor.

15.11.4.2 Error.prototype.name

The initial value of `Error.prototype.name` is "Error".

15.11.4.3 Error.prototype.message

The initial value of `Error.prototype.message` is the empty String.

15.11.4.4 Error.prototype.toString ()

The following steps are taken:

1. Let *O* be the `this` value.
2. If `Type(O)` is not `Object`, throw a `TypeError` exception.
3. Let *name* be the result of calling the `[[Get]]` internal method of *O* with argument "`name`".
4. `ReturnIfAbrupt(name)`.
5. If *name* is `undefined`, then let *name* be "Error"; else let *name* be `ToString(name)`.
6. Let *msg* be the result of calling the `[[Get]]` internal method of *O* with argument "`message`".
7. `ReturnIfAbrupt(msg)`.
8. If *msg* is `undefined`, then let *msg* be the empty String; else let *msg* be `ToString(msg)`.
9. If *name* is the empty String, return *msg*.
10. If *msg* is the empty String, return *name*.
11. Return the result of concatenating *name*, ":" , a single space character, and *msg*.

15.11.5 Properties of Error Instances

Error instances inherit properties from the Error prototype object and have a `[[NativeBrand]] internal property` whose value is `NativeError`. Error instances have no special properties.

15.11.6 Native Error Types Used in This Standard

One of the `NativeError` objects below is thrown when a runtime error is detected. All of these objects share the same structure, as described in 15.11.7.

15.11.6.1 EvalError

This exception is not currently used within this specification. This object remains for compatibility with previous editions of this specification.

Deleted: `n`

Deleted: `IsError`

Deleted: (its `[[Class]]` is "Error")

Deleted: <#>If *msg* is `undefined`, then let *msg* be the empty String; else let *msg* be `ToString(msg)`.¶

Deleted: `n`

Deleted: `IsError`

Deleted: their `[[Class]]` internal property value is "Error"

15.11.6.2 RangeError

Indicates a numeric value has exceeded the allowable range. See 15.4.2.2, 15.4.5.1, 15.7.4.2, 15.7.4.5, 15.7.4.6, 15.7.4.7, and 15.9.5.43.

15.11.6.3 ReferenceError

Indicate that an invalid reference value has been detected. See 8.9.1, 8.9.2, 10.2.1, 10.2.1.1.4, 10.2.1.2.4, and 11.13.1.

Deleted: 7

Deleted: 7

15.11.6.4 SyntaxError

Indicates that a parsing error has occurred. See 11.1.5, 11.3.1, 11.3.2, 11.4.1, 11.4.4, 11.4.5, 11.13.1, 11.13.2, 12.2.1, 12.10.1, 12.14.1, 13.1, 15.1.2.1, 15.3.2.1, 15.10.2.2, 15.10.2.5, 15.10.2.9, 15.10.2.15, 15.10.2.19, 15.10.4.1, and 15.12.2.

15.11.6.5 TypeError

Indicates the actual type of an operand is different than the expected type. See 8.6.2, 8.9.2, 8.10.5, 8.12.5, 8.12.7, 8.12.8, 8.12.9, 9.9, 9.10, 10.2.1, 10.2.1.1.3, 10.6, 11.2.2, 11.2.3, 11.4.1, 11.8.6, 11.8.7, 11.3.1, 13.2, 13.2.3, 15, 15.2.3.2, 15.2.3.3, 15.2.3.4, 15.2.3.5, 15.2.3.6, 15.2.3.7, 15.2.3.8, 15.2.3.9, 15.2.3.10, 15.2.3.11, 15.2.3.12, 15.2.3.13, 15.2.3.14, 15.2.4.3, 15.3.4.2, 15.3.4.3, 15.3.4.4, 15.3.4.5, 15.3.4.5.2, 15.3.4.5.3, 15.3.5, 15.3.5.3, 15.3.5.4, 15.4.4.3, 15.4.4.11, 15.4.4.16, 15.4.4.17, 15.4.4.18, 15.4.4.19, 15.4.4.20, 15.4.4.21, 15.4.4.22, 15.4.5.1, 15.5.4.2, 15.5.4.3, 15.6.4.2, 15.6.4.3, 15.7.4, 15.7.4.2, 15.7.4.4, 15.9.5, 15.9.5.44, 15.10.4.1, 15.10.6, 15.11.4.4 and 15.12.3.

Deleted: 7

15.11.6.6 URIError

Indicates that one of the global URI handling functions was used in a way that is incompatible with its definition. See 15.1.3.

Comment [AWB10140]: Sectin references have not yet been updated to reflect ES6

15.11.7 NativeError Object Structure

When an ECMAScript implementation detects a runtime error, it throws an instance of one of the *NativeError* objects defined in 15.11.6. Each of these objects has the structure described below, differing only in the name used as the constructor name instead of *NativeError*, in the **name** property of the prototype object, and in the implementation-defined **message** property of the prototype object.

For each error object, references to *NativeError* in the definition should be replaced with the appropriate error object name from 15.11.6.

15.11.7.1 NativeError Constructors Called as Functions

When a *NativeError* constructor is called as a function rather than as a constructor, it creates and initialises a new object. A call of the object as a function is equivalent to calling it as a constructor with the same arguments.

15.11.7.2 NativeError (message)

The **[[Prototype]]** internal property of the newly constructed object is set to the prototype object for this error constructor. The **[[newly constructed object has a [[NativeBrand]] internal property]]** whose value is *NativeError*. The **[[Extensible]]** internal property of the newly constructed object is set to **true**.

Deleted: **[[Class]]** internal property of the

Deleted: **n**

Deleted: **IsError**

Deleted: **is set to "Error"**

15.11.7.3 The *NativeError* Constructors

When a *NativeError* constructor is called as part of a `new` expression, it is a constructor: it initialises the newly created object.

15.11.7.4 `new NativeError (message)`

The `[[Prototype]]` internal property of the newly constructed object is set to the prototype object for this *NativeError* constructor. The newly constructed object has a `[[NativeBrand]]` internal property whose value is `NativeError`. The `[[Extensible]]` internal property of the newly constructed object is set to `true`.

If the argument `message` is not `undefined`, the `message` own property of the newly constructed object is set to `ToString(message)`.

15.11.7.5 Properties of the *NativeError* Constructors

The value of the `[[Prototype]]` internal property of a *NativeError* constructor is the Function prototype object (15.3.4).

Besides the internal properties and the `length` property (whose value is `1`), each *NativeError* constructor has the following property:

15.11.7.6 `NativeError.prototype`

The initial value of `NativeError.prototype` is a *NativeError* prototype object (15.11.7.7). Each *NativeError* constructor has a separate prototype object.

This property has the attributes `{ [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }`.

15.11.7.7 Properties of the *NativeError* Prototype Objects

Each *NativeError* prototype object is an Error object and has a `[[NativeBrand]]` internal property whose value is `NativeError`.

The value of the `[[Prototype]]` internal property of each *NativeError* prototype object is the standard built-in Error prototype object (15.11.4).

15.11.7.8 `NativeError.prototype.constructor`

The initial value of the `constructor` property of the prototype for a given *NativeError* constructor is the *NativeError* constructor function itself (15.11.7).

15.11.7.9 `NativeError.prototype.name`

The initial value of the `name` property of the prototype for a given *NativeError* constructor is the name of the constructor (the name used instead of *NativeError*).

15.11.7.10 `NativeError.prototype.message`

The initial value of the `message` property of the prototype for a given *NativeError* constructor is the empty String.

NOTE The prototypes for the *NativeError* constructors do not themselves provide a `toString` function, but instances of errors will inherit it from the Error prototype object.

Deleted: `[[Class]]` internal property of the
Deleted: `n`
Deleted: `IsError`
Deleted: is set to "Error"

Deleted: `n`
Deleted: `IsError`
Deleted: (its `[[Class]]` is "Error")

15.11.7.11 Properties of NativeError Instances

NativeError instances inherit properties from their NativeError prototype object and have a [[NativeBrand]] internal property whose value is NativeError. NativeError instances have no special properties.

Deleted: n
Deleted: IsError

Deleted: their [[Class]] internal property value is "Error"

15.12 The JSON Object

The **JSON** object is a single object that contains two functions, **parse** and **stringify**, that are used to parse and construct JSON texts. The JSON Data Interchange Format is described in RFC 4627 <<http://www.ietf.org/rfc/rfc4627.txt>>. The JSON interchange format used in this specification is exactly that described by RFC 4627 with two exceptions:

- The top level **JSONText** production of the ECMAScript JSON grammar may consist of any **JSONValue** rather than being restricted to being a **JSONObject** or a **JSONArray** as specified by RFC 4627.
- Conforming implementations of **JSON.parse** and **JSON.stringify** must support the exact interchange format described in this specification without any deletions or extensions to the format. This differs from RFC 4627 which permits a JSON parser to accept non-JSON forms and extensions.

The value of the [[Prototype]] internal property of the **JSON** object is the standard built-in Object prototype object (15.2.4). The **JSON** object *has a [[NativeBrand]] internal property whose value is NativeJSON.* The value of the [[Extensible]] internal property of the **JSON** object is set to **true**.

Deleted: value of the [[Class]] internal property of the
Deleted: n
Deleted: IsJSON
Deleted: is "JSON"

The **JSON** object does not have a [[Construct]] internal property; it is not possible to use the **JSON** object as a constructor with the **new** operator.

The **JSON** object does not have a [[Call]] internal property; it is not possible to invoke the **JSON** object as a function.

15.12.1 The JSON Grammar

JSON.stringify produces a String that conforms to the following JSON grammar. **JSON.parse** accepts a String that conforms to the JSON grammar.

15.12.1.1 The JSON Lexical Grammar

JSON is similar to ECMAScript source text in that it consists of a sequence of **Unicode** characters conforming to the rules of **SourceCharacter**. The JSON Lexical Grammar defines the tokens that make up a JSON text similar to the manner that the ECMAScript lexical grammar defines the tokens of an ECMAScript source text. The JSON Lexical grammar only recognises the white space character specified by the production **JSONWhiteSpace**. The JSON lexical grammar shares some productions with the ECMAScript lexical grammar. All nonterminal symbols of the grammar that do not begin with the characters "JSON" are defined by productions of the ECMAScript lexical grammar.

Syntax

```

JSONWhiteSpace ::
  <TAB>
  <CR>
  <LF>
  <SP>

JSONString ::
  " JSONStringCharactersopt "

JSONStringCharacters ::
  JSONStringCharacter JSONStringCharactersopt

JSONStringCharacter ::

```

*SourceCharacter but not one of " or \ or U+0000 through U+001F
 \ JSONEscapeSequence*

*JSONEscapeSequence ::
 JSONEscapeCharacter
 u HexDigit HexDigit HexDigit HexDigit*

*JSONEscapeCharacter :: one of
 " / \ b f n r t*

*JSONNumber ::
 -_{opt} DecimalIntegerLiteral JSONFraction_{opt} ExponentPart_{opt}*

*JSONFraction ::
 . DecimalDigits*

*JSONNullLiteral ::
 NullLiteral*

*JSONBooleanLiteral ::
 BooleanLiteral*

15.12.1.2 The JSON Syntactic Grammar

The JSON Syntactic Grammar defines a valid JSON text in terms of tokens defined by the JSON lexical grammar. The goal symbol of the grammar is *JSONText*.

Syntax

JSONText :
JSONValue

JSONValue :
JSONNullLiteral
JSONBooleanLiteral
JSONObject
JSONArray
JSONString
JSONNumber

JSONObject :
 { }
 { *JSONMemberList* }

JSONMember :
JSONString : *JSONValue*

JSONMemberList :
JSONMember
JSONMemberList , *JSONMember*

JSONArray :
 []
 [*JSONElementList*]

JSONElementList :
JSONValue
JSONElementList , *JSONValue*

Deleted: *UnicodeEscapeSequence*

15.12.2 `parse (text [, reviver])`

The `parse` function parses a JSON text (a JSON-formatted String) and produces an ECMAScript value. The JSON format is a restricted form of ECMAScript literal. JSON objects are realized as ECMAScript objects. JSON arrays are realized as ECMAScript arrays. JSON strings, numbers, booleans, and `null` are realized as ECMAScript Strings, Numbers, Booleans, and `null`. JSON uses a more limited set of white space characters than `WhiteSpace` and allows Unicode code points U+2028 and U+2029 to directly appear in `JSONString` literals without using an escape sequence. The process of parsing is similar to 11.1.4 and 11.1.5 as constrained by the JSON grammar.

The optional `reviver` parameter is a function that takes two parameters, `(key and value)`. It can filter and transform the results. It is called with each of the `key/value` pairs produced by the `parse`, and its return value is used instead of the original value. If it returns what it received, the structure is not modified. If it returns `undefined` then the property is deleted from the result.

1. Let `JText` be `ToString(text)`.
2. `ReturnIfAbrupt(text)`.
3. Parse `JText` interpreted as UTF-16 encoded Unicode characters using the grammars in 15.12.1. Throw a `SyntaxError` exception if `JText` did not conform to the JSON grammar for the goal symbol `JSONText`.
4. Let `unfiltered` be the result of parsing and evaluating `JText` as if it was the source text of an ECMAScript `Program` but using `JSONString` in place of `StringLiteral`. Note that since `JText` conforms to the JSON grammar this result will be either a primitive value or an object that is defined by either an `ArrayLiteral` or an `ObjectLiteral`.
5. If `IsCallable(reviver)` is `true`, then
 - a. Let `root` be the result of the abstract operation `ObjectCreate (15.2)`.
 - b. Call the `[[DefineOwnProperty]]` internal method of `root` with the empty String, the `PropertyDescriptor {[[Value]]: unfiltered, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `false` as arguments.
 - c. Return the result of calling the abstract operation `Walk`, passing `root` and the empty String. The abstract operation `Walk` is described below.
6. Else
 - a. Return `unfiltered`.

Deleted: er

The abstract operation `Walk` is a recursive abstract operation that takes two parameters: a `holder` object and the String `name` of a property in that object. `Walk` uses the value of `reviver` that was originally passed to the above `parse` function.

1. Let `val` be the result of calling the `[[Get]]` internal method of `holder` with argument `name`.
2. `ReturnIfAbrupt(val)`.
3. If `val` is an object, then
 - a. If `val` has a `[[NativeBrand]]` internal property with value `NativeArray`, then
 - i. Set `I` to 0.
 - ii. Let `len` be the result of calling the `[[Get]]` internal method of `val` with argument `"length"`.
 - iii. Assert: len is not an abrupt completion and its value is a positive integer.
 - iv. Repeat while `I < len`,
 1. Let `newElement` be the result of calling the abstract operation `Walk`, passing `val` and `ToString(I)`.
 2. If `newElement` is `undefined`, then
 - a. Let `status` be the result of calling the `[[Delete]]` internal method of `val` with `ToString(I)` and `false` as arguments.
 3. Else
 - a. Let `status` be the result of calling the `[[DefineOwnProperty]]` internal method of `val` with arguments `ToString(I)`, the `PropertyDescriptor {[[Value]]: newElement, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}`, and `false`.
 4. ReturnIfAbrupt(status).
 5. Add 1 to `I`.
 - b. Else

Deleted: abstraction operation

Deleted: a new object created as if by the expression `new Object()`, where `Object` is a standard built-in constructor with that name

Deleted: the `[[Class]]` internal property of

Deleted: is "Array"

Deleted: IsArray

Deleted: Call

Deleted: Call

- i. Let *keys* be an internal List of String values consisting of the names of all the own properties of *val* whose *[[Enumerable]]* attribute is **true**. The ordering of the Strings is the same as that used by the **Object.keys** standard built-in function.
 - ii. For each String *P* in *keys* do,
 1. Let *newElement* be the result of calling the abstract operation *Walk*, passing *val* and *P*.
 2. If *newElement* is **undefined**, then
 - a. Let *status* be the result of calling the *[[Delete]]* internal method of *val* with *P* and **false** as arguments.
 3. Else
 - a. Let *status* be the result of calling the *[[DefineOwnProperty]]* internal method of *val* with arguments *P*, the Property Descriptor *{[[Value]]: newElement, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}*, and **false**.
 4. **4. ReturnIfAbrupt(*status*)**.
4. Return the result of calling the *[[Call]]* internal method of *reviver* passing *holder* as the **this** value and with an argument list consisting of *name* and *val*.

It is not permitted for a conforming implementation of **JSON.parse** to extend the JSON grammars. If an implementation wishes to support a modified or extended JSON interchange format it must do so by defining a different parse function.

NOTE In the case where there are duplicate name Strings within an object, lexically preceding values for the same key shall be overwritten.

15.12.3 **stringify (value [, replacer [, space]])**

The **stringify** function returns a String in **UTF-16 encoded** JSON format representing an ECMAScript value. It can take three parameters. The *value* parameter is an ECMAScript value, which is usually an object or array, although it can also be a String, Boolean, Number or **null**. The optional *replacer* parameter is either a function that alters the way objects and arrays are stringified, or an array of Strings and Numbers that acts as a white list for selecting the object properties that will be stringified. The optional *space* parameter is a String or Number that allows the result to have white space injected into it to improve human readability.

These are the steps in stringifying an object:

1. Let *stack* be an empty List.
2. Let *indent* be the empty String.
3. Let *PropertyList* and *ReplacerFunction* be **undefined**.
4. If *Type(replacer)* is Object, then
 - a. If *IsCallable(replacer)* is **true**, then
 - i. Let *ReplacerFunction* be *replacer*.
 - b. Else if *replacer* has a *[[NativeBrand]] internal property* with value *NativeArray*, then
 - i. Let *PropertyList* be an empty internal List
 - ii. For each value *v* of a property of *replacer* that has an array index property name. The properties are enumerated in the ascending array index order of their names.
 1. Let *item* be **undefined**.
 2. If *Type(v)* is String then let *item* be *v*.
 3. Else if *Type(v)* is Number then let *item* be *ToString(v)*.
 4. Else if *Type(v)* is Object then,
 - a. If *v* has a *[[NativeBrand]] internal property* whose value is either *StringWrapper* or *NumberWrapper* then let *item* be *ToString(v)*.
 5. If *item* is not **undefined** and *item* is not currently an element of *PropertyList* then,
 - a. Append *item* to the end of *PropertyList*.
 5. If *Type(space)* is Object then,
 - a. If *space* has a *[[NativeBrand]] internal property* whose value is *NumberWrapper*, then,
 - i. Let *space* be *ToNumber(space)*.
 - b. Else if *space* has a *[[NativeBrand]] internal property* with value *StringWrapper*, then,
 - i. Let *space* be *ToString(space)*.
 6. If *Type(space)* is Number

Deleted: should

Deleted: be

Deleted: Call

Deleted: Call

Deleted: The first parameter is required.

Deleted: the *[[Class]]* internal property of

Deleted: IsArray

Deleted: is "Array"

Deleted: the *[[Class]]* internal property of

Deleted: is "String" or "Number"

Deleted: either

Deleted: n

Deleted: IsString

Deleted: or an *[[IsNumber]]*

Deleted: the *[[Class]]* internal property of

Deleted: IsNumber

Deleted: is "Number"

Deleted: the *[[Class]]* internal property of

Deleted: IsString

Deleted: is "String"

- a. Let *space* be $\min(10, \text{ToInteger}(\text{space}))$.
- b. Set *gap* to a String containing *space* occurrences of code unit 0x0020 (the Unicode space character). This will be the empty String if *space* is less than 1.
7. Else if *Type(space)* is String
 - a. If the number of *elements* in *space* is 10 or less, set *gap* to *space* otherwise set *gap* to a String consisting of the first 10 *elements* of *space*.
8. Else
 - a. Set *gap* to the empty String.
9. Let *wrapper* be the result of the abstract operation *ObjectCreate* (15.2).
10. Call the *[[DefineOwnProperty]]* internal method of *wrapper* with arguments the empty String, the Property Descriptor *{[[Value]]: value, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}*, and *false*.
11. Return the result of calling the abstract operation *Str* with the empty String and *wrapper*.

The abstract operation *Str(key, holder)* has access to *ReplacerFunction* from the invocation of the *stringify* method. Its algorithm is as follows:

1. Let *value* be the result of calling the *[[Get]]* internal method of *holder* with argument *key*.
2. *ReturnIfAbrupt(value)*.
3. If *Type(value)* is Object, then
 - a. Let *toJSON* be the result of calling the *[[Get]]* internal method of *value* with argument "toJSON".
 - b. If *IsCallable(toJSON)* is *true*
 - i. Let *value* be the result of calling the *[[Call]]* internal method of *toJSON* passing *value* as the *this* value and with an argument list consisting of *key*.
 - ii. *ReturnIfAbrupt(value)*.
4. If *ReplacerFunction* is not *undefined*, then
 - a. Let *value* be the result of calling the *[[Call]]* internal method of *ReplacerFunction* passing *holder* as the *this* value and with an argument list consisting of *key* and *value*.
 - b. *ReturnIfAbrupt(value)*.
5. If *Type(value)* is Object then,
 - a. If *value* has an *[[NativeBrand]] internal property* with value *NumberWrapper*, then
 - i. Let *value* be *ToNumber(value)*.
 - b. Else if *value* has an *[[NativeBrand]] internal property* with value *StringWrapper*, then
 - i. Let *value* be *ToString(value)*.
 - c. Else if *value* has an *[[NativeBrand]] internal property* with value *BooleanWrapper*, then
 - i. Let *value* be the value of the *[[PrimitiveValue]]* internal property of *value*.
6. If *value* is *null* then return "null".
7. If *value* is *true* then return "true".
8. If *value* is *false* then return "false".
9. If *Type(value)* is String, then return the result of calling the abstract operation *Quote* with argument *value*.
10. If *Type(value)* is Number
 - a. If *value* is finite then return *ToString(value)*.
 - b. Else, return "null".
11. If *Type(value)* is Object, and *IsCallable(value)* is *false*
 - a. If *value* has an *[[NativeBrand]] internal property* with value *NativeArray*, then
 - i. Return the result of calling the abstract operation *J4* with argument *value*.
 - b. Else, return the result of calling the abstract operation *JO* with argument *value*.
12. Return *undefined*.

The abstract operation *Quote(value)* wraps a String value in double quotes and escapes characters within it.

1. Let *product* be code unit 0x0022 (the Unicode double quote character).
2. For each code unit *C* in *value*
 - a. If *C* is 0x0022 or 0x005C (the Unicode reverse solidus character)
 - i. Let *product* be the concatenation of *product* and code unit 0x005C (the Unicode backslash character).
 - ii. Let *product* be the concatenation of *product* and code unit 0x005C.
 - b. Else if *C* is backspace, formfeed, newline, carriage return, or tab
 - i. Let *product* be the concatenation of *product* and code unit 0x005C (the Unicode backslash character).

Deleted: occurrences
Deleted: characters
Deleted: characters
Deleted: characters
Deleted: be
Deleted: abstraction operation
Deleted: a new object created as if by the expression `new Object()`, where `Object` is standard built-in constructor with that name

Deleted: the *[[Class]]* internal property of
Deleted: IsNumber
Deleted: is "Number"
Deleted: the *[[Class]]* internal property of
Deleted: IsString
Deleted: is "String"
Deleted: the *[[Class]]* internal property of
Deleted: IsBoolean
Deleted: is "Boolean"
Deleted: the *[[Class]]* internal property of
Deleted: IsArray
Deleted: is "Array"

Deleted: character
Deleted: the double quote character
Deleted: or
Deleted: backslash
Deleted: *product* and the backslash character
Deleted: C
Deleted: and

ii. Let *abbrev* be the string_value corresponding to the value of *C* as follows:

backspace	"\b"
formfeed	"\f"
newline	"\n"
carriage return	"\r"
tab	"\t"

Deleted: character

Deleted: value

iii. Let *product* be the concatenation of *product* and *abbrev*.

- c. Else if *C* has a code unit value less than 0x0020 (the Unicode space character)
 - i. Let *product* be the concatenation of *product* and code unit 0x005C (the Unicode backslash character).
 - ii. Let *product* be the concatenation of *product* and "u".
 - iii. Let *hex* be the string result of converting the numeric code unit value of *C* to a String of four hexadecimal digits. Alphabetic hexadecimal digits are presented as lowercase characters.
 - iv. Let *product* be the concatenation of *product* and *hex*.
- d. Else
 - i. Let *product* be the concatenation of *product* and *C*.

Deleted: is

Deleted: control character having a

Deleted: and

- 3. Let *product* be the concatenation of *product* and code unit 0x0022 (the Unicode double quote character).
- 4. Return *product*.

Deleted: and the double quote character

The abstract operation *JO(value)* serializes an object. It has access to the *stack*, *indent*, *gap*, and *PropertyList*, of the invocation of the *stringify* method.

Deleted: ,

Deleted: *ReplacerFunction*, and *space*

1. If *stack* contains *value* then throw a **TypeError** exception because the structure is cyclical.
2. Append *value* to *stack*.
3. Let *stepback* be *indent*.
4. Let *indent* be the concatenation of *indent* and *gap*.
5. If *PropertyList* is not **undefined**, then
 - a. Let *K* be *PropertyList*.
6. Else
 - a. Let *K* be an internal List of Strings consisting of the names of all the own properties of *value* whose **[[Enumerable]]** attribute is **true**. The ordering of the Strings is the same as that used by the **Object.keys** standard built-in function.
7. Let *partial* be an empty List.
8. For each element *P* of *K*.
 - a. Let *strP* be the result of calling the abstract operation *Str* with arguments *P* and *value*.
 - b. ReturnIfAbrupt(strP).
 - c. If *strP* is not **undefined**
 - i. Let *member* be the result of calling the abstract operation *Quote* with argument *P*.
 - ii. Let *member* be the concatenation of *member* and the string ":".
 - iii. If *gap* is not the empty String
 1. Let *member* be the concatenation of *member* and code unit 0x0020 (the Unicode space character).
 - iv. Let *member* be the concatenation of *member* and *strP*.
 - v. Append *member* to *partial*.
9. If *partial* is empty, then
 - a. Let *final* be "{}".
10. Else
 - a. If *gap* is the empty String
 - i. Let *properties* be a String formed by concatenating all the element Strings of *partial* with each adjacent pair of Strings separated with code unit 0x002C (the Unicode comma character). A comma is not inserted either before the first String or after the last String.
 - ii. Let *final* be the result of concatenating "{}", *properties*, and "{}".
 - b. Else *gap* is not the empty String
 - i. Let *separator* be the result of concatenating code unit 0x002C (the comma character), code unit 0x000A (the line feed character), and *indent*.
 - ii. Let *properties* be a String formed by concatenating all the element Strings of *partial* with each adjacent pair of Strings separated with *separator*. The *separator* String is not inserted either before the first String or after the last String.

Deleted: should be

Deleted: colon character

iii. Let *final* be the result of concatenating " { ", code unit 0x000A (the line feed character), *indent*, *properties*, code unit 0x000A, *stepback*, and " } ".

Deleted: the line feed character

11. Remove the last element of *stack*.

12. Let *indent* be *stepback*.

13. Return *final*.

The abstract operation *JA*(*value*) serializes an array. It has access to the *stack*, *indent*, and gap of the invocation of the *stringify* method. The representation of arrays includes only the elements between zero and **array.length - 1** inclusive. Named properties are excluded from the stringification. An array is stringified as an open left bracket, elements separated by comma, and a closing right bracket.

Deleted: , and space

1. If *stack* contains *value* then throw a **TypeError** exception because the structure is cyclical.
2. Append *value* to *stack*.
3. Let *stepback* be *indent*.
4. Let *indent* be the concatenation of *indent* and *gap*.
5. Let *partial* be an empty List.
6. **Assert: value is a native array and hence its "length" property is a non-negative integer.**
7. Let *len* be the result of calling the [[Get]] internal method of *value* with argument "**length**".
8. Let *index* be 0.
9. Repeat while *index < len*
 - a. Let *strP* be the result of calling the abstract operation *Str* with arguments *ToString(index)* and *value*.
 - b. ReturnIfAbrupt(strP).
 - c. If *strP* is **undefined**
 - i. Append "null" to *partial*.
 - d. Else
 - i. Append *strP* to *partial*.
 - e. Increment *index* by 1.
10. If *partial* is empty ,then
 - a. Let *final* be "[]".
11. Else
 - a. If *gap* is the empty String
 - i. Let *properties* be a String formed by concatenating all the element Strings of *partial* with each adjacent pair of Strings separated with code unit 0x002C (the comma character). A comma is not inserted either before the first String or after the last String.
 - ii. Let *final* be the result of concatenating "[", *properties*, and "] ".
 - b. Else
 - i. Let *separator* be the result of concatenating code unit 0x002C (the comma character), code unit 0x000A (the line feed character), and *indent*.
 - ii. Let *properties* be a String formed by concatenating all the element Strings of *partial* with each adjacent pair of Strings separated with *separator*. The *separator* String is not inserted either before the first String or after the last String.
 - iii. Let *final* be the result of concatenating "[", code unit 0x000A (the line feed character), *indent*, *properties*, code unit 0x000A, *stepback*, and "] ".
12. Remove the last element of *stack*.
13. Let *indent* be *stepback*.
14. Return *final*.

Deleted: the line feed character

NOTE 1 JSON structures are allowed to be nested to any depth, but they must be acyclic. If *value* is or contains a cyclic structure, then the *stringify* function must throw a **TypeError** exception. This is an example of a value that cannot be stringified:

```
a = [];
a[0] = a;
my_text = JSON.stringify(a); // This must throw an TypeError.
```

NOTE 2 Symbolic primitive values are rendered as follows:

- The **null** value is rendered in JSON text as the String **null**.
- The **undefined** value is not rendered.
- The **true** value is rendered in JSON text as the String **true**.
- The **false** value is rendered in JSON text as the String **false**.

NOTE 3 String values are wrapped in double quotes. The characters " and \ are escaped with \ prefixes. Control characters are replaced with escape sequences \uHHHH, or with the shorter forms, \b (backspace), \f (formfeed), \n (newline), \r (carriage return), \t (tab).

NOTE 4 Finite numbers are stringified as if by calling `ToString(number)`. `Nan` and `Infinity` regardless of sign are represented as the String `null`.

NOTE 5 Values that do not have a JSON representation (such as `undefined` and functions) do not produce a String. Instead they produce the `undefined` value. In arrays these values are represented as the String `null`. In objects an unrepresentable value causes the property to be excluded from stringification.

NOTE 6 An object is rendered as an opening left brace followed by zero or more properties, separated with commas, closed with a right brace. A property is a quoted String representing the key or property name, a colon, and then the stringified property value. An array is rendered as an opening left bracket followed by zero or more values, separated with commas, closed with a right bracket.

[15.13 Binary Data Objects](#)

[15.13.1 The BinaryData Module](#)

[15.13.2 The BinaryData.Type Object](#)

[15.13.2.5 BinaryData.ScalarType Type Instance Objects](#)

[15.13.3 The BinaryData.ArrayType Object](#)

[15.13.4 The BinaryData.StructType Object](#)

[15.13.5 ArrayBufferObjects](#)

[15.13.5.1 The ArrayBuffer Object Called as a Function](#)

When `ArrayBuffer` is called as a function rather than as a constructor, it creates and initialises a new `ArrayBuffer` object. Thus the function call `ArrayBuffer(...)` is equivalent to the object creation expression `new ArrayBuffer(...)` with the same arguments.

[15.13.5.2 The ArrayBuffer Constructor](#)

When `ArrayBuffer` is called as part of a new expression, it is a constructor: it initialises the newly created object.

[15.13.5.2.1 new ArrayBuffer\(len\)](#)

The `[[Prototype]]` internal property of the newly constructed object is set to the original `ArrayBuffer` prototype object, the one that is the initial value of `ArrayBuffer.prototype` (16.1.3.1). The `[[Class]]` internal property of the newly constructed object is set to "ArrayBuffer". The `[[Extensible]]` internal property of the newly constructed object is set to true.

The `length` property of the newly constructed object is set to `ToUInt32(len)`.

A fresh native buffer `nativeBuffer` of `length` bytes is allocated. The contents of this native buffer are zero initialized. If the requested number of bytes could not be allocated, a `RangeError` is raised. The `[[NativeBuffer]]` internal property of the newly constructed object is set to `nativeBuffer`.

[15.13.5.3 Properties of the ArrayBuffer Constructor](#)

The value of the `[[Prototype]]` internal property of the `ArrayBuffer` constructor is the Function prototype object (15.3.4).

Comment [AWB10141]: This is a place holder for material in the Binary Data proposal
http://wiki.ecmascript.org/doku.php?id=harmony:binary_data

Comment [AWB10142]: The following sections defined "typed arrays" derived from the Kronos specification. This material is a very early draft based upon the strawman at
http://wiki.ecmascript.org/doku.php?id=strawman:typed_arrays. This material still needs significant work to fully integrate it into the ES6 spec. and also to integrate typed arrays with ES6 binary data.

Besides the internal properties and the length property (whose value is 1), the ArrayBuffer constructor has the following properties:

15.13.5.3 ArrayBuffer.prototype

The initial value of ArrayBuffer.prototype is the ArrayBuffer prototype object (16.1.4).

This property has the attributes { [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }.

15.13.5.4 Properties of the ArrayBuffer Prototype Object

The value of the [[Prototype]] internal property of the ArrayBuffer prototype object is the standard built-in Object prototype object (15.2.4). The [[Class]] internal property of the newly constructed object is set to "Object". The [[Extensible]] internal property of the newly constructed object is set to true.

15.13.5.4.1 ArrayBuffer.prototype.constructor

The initial value of ArrayBuffer.prototype.constructor is the standard built-in ArrayBuffer constructor.

15.13.5.5 Properties of the ArrayBuffer Instances

ArrayBuffer instances inherit properties from the ArrayBuffer prototype object and their [[Class]] internal property value is "ArrayBuffer". ArrayBuffer instances also have the following properties.

15.13.5.5.1 byteLength

The byteLength property of this ArrayBuffer object is a data property whose value is the length of the ArrayBuffer in bytes, as fixed at construction time.

The length property has the attributes { [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }.

15.13.6 TypeArray Object Structures

For each constructor in the following table is a separate TypeArray constructor object, with corresponding prototype and instances. Each of these TypeArray constructor objects has the structure described below, differing only in the name used as the constructor name instead of TypeArray, in [XXXXXX].

Comment [AWB10143]: Need to fill in

Constructor Name	Element Type	Size Element	Description	Equivalent C Type
Int8Array	Int8	1	8-bit 2's complement signed integer	signed char
Uint8Array	Uint8	1	8-bit unsigned integer	unsigned char
Int16Array	Int16	2	16-bit 2's complement signed integer	Short
Uint16Array	Uint16	2	16-bit unsigned integer	unsigned short
Int32Array	Int32	4	32-bit 2's complement signed integer	Int
Uint32Array	Uint32	4	32-bit unsigned integer	unsigned int
Float32Array	Float32	4	32-bit IEEE floating point	Float
Float64Array	Float64	8	64-bit IEEE floating point	Double

In the definitions below, references to TypeArray should be replaced with the appropriate constructor name from the above table. The phrase "the element size in bytes" refers to the value in the Element Size column of the table in the row corresponding to the constructor. The phrase "element Type" refers to the value in the Element Type column for that row.

15.13.6.1 TypeArray Constructors Called as a Function

When a `TypeArray` constructor is called as a function rather than as a constructor, it creates and initialises a new object. A call of the constructor as a function is equivalent to calling it as a constructor with the same arguments.

15.13.6.2 The TypeArray Constructors

When a `TypeArray` constructor is called as part of a new expression, it is a constructor: it initialises the newly created object.

15.13.6.2.1 new TypeArray(arg0 [, arg1, [, arg2]])

The `[[Prototype]]` internal property of the newly constructed object is set to the original `TypeArray` prototype object, the one that is the initial value of `TypeArray.prototype` (16.2.3.1). The `[[Class]]` internal property of the newly constructed object is set to "TypeArray". The `[[Extensible]]` internal property of the newly constructed object is set to true.

The remaining properties of the newly constructed object are set as follows:

1. If `Type(arg0)` is Number, then
 - a. Let `length` be `ToUInt32(arg0)`.
 - b. `ReturnIfAbrupt(length)`.
 - c. The `length` property of the newly constructed object is set to `length`.
 - d. The `byteLength` property of the newly constructed object is set to `length` multiplied by the element size in bytes.
 - e. Let `arrayBuffer` be an object constructed as if by a call to the built-in `ArrayBuffer` constructor, as `"new ArrayBuffer(byteLength)"`.
 - f. The `buffer` property of the newly constructed object is set to `arrayBuffer`.
 - g. The `byteOffset` property of the newly constructed object is set to 0.
2. Else,
 - a. Let `O` be the result of calling `ToObject(arg0)`.
 - b. `ReturnIfAbrupt(O)`.
 - c. Let `class` be the value of the `[[Class]]` internal property of `O`.
 - d. If `class` is "ArrayBuffer", then
 - i. Let `byteOffset` be the result of calling `ToUInt32` on `arg1`, if provided, or else 0.
 - ii. If `byteOffset` is not an integer multiple of the element size in bytes, throw a `RangeError` exception.
 - iii. Let `bufferLength` be the result of calling `[[Get]]` on `O` with property name "byteLength".
 - iv. Let `byteLength` be the result of calling `ToUInt32` on `arg2`, if provided, or else `bufferLength - byteOffset`.
 - v. If `byteOffset + byteLength` is greater than `bufferLength`, throw a `RangeError` exception.
 - vi. Let `length` be the result of dividing `byteLength` by the element size in bytes.
 - vii. If `ToUInt32(length) != length`, throw a `RangeError` exception.
 - viii. The `length` property of the newly constructed object is set to `length`.
 - ix. The `byteLength` property of the newly constructed object is set to `byteLength`.
 - x. The `buffer` property of the newly constructed object is set to `O`.
 - xi. The `byteOffset` property of the newly constructed object is set to `byteOffset`.
 - e. Else,
 - i. Let `n` to be the result of calling `[[Get]]` on `V` with property name "length".
 - ii. Let `length` be the result of calling `ToUInt32(n)`.
 - iii. The `length` property of the newly constructed object is set to `length`.
 - iv. The `byteLength` property of the newly constructed object is set to `length` multiplied by the element size in bytes.
 - v. Let `arrayBuffer` be an object constructed as if by a call to the built-in `ArrayBuffer` constructor, as `"new ArrayBuffer(byteLength)"`.
 - vi. Let `i` to be 0.
 - vii. While `i < length`:
 1. Let `x` be the result of calling `[[Get]]` on `arrayBuffer` with property name `ToString(i)`.

Comment [AWB10144]: This is a very preliminary version of this algorithm based upon the wiki strawman. It needs to be thoroughly reviewed and better integrated into the Es spec. conventions.

2. Let *indexDesc* be Property Descriptor {[[Value]]: *x*, [[Writable]]: **true**,
[[Enumerable]]: **true**, [[Configurable]]: **false**}.
3. Call [[DefineOwnProperty]] on the newly constructed object with arguments
 ToString(i), *indexDesc*, and **false**.
4. Set *i* to *i* + 1.
- viii. The buffer property of the newly constructed object is set to *arrayBuffer*.
- ix. The byteOffset property of the newly constructed object is set to 0.

15.13.6.3 Properties of the *TypeArray* Constructors

The value of the [[Prototype]] internal property of each *TypeArray* constructor is the Function prototype object (15.3.4).

Besides the internal properties and the length property (whose value is 3), each *TypeArray* constructor has the following properties:

15.13.6.3.1 *TypeArray.prototype*

The initial value of *TypeArray.prototype* is the *TypeArray* prototype object (15.13.2.4).

This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.13.6.3.2 *TypeArray.BYTES PER ELEMENT*

The initial value of *TypeArray.BYTES PER ELEMENT* is the element size in bytes.

This property has the attributes { [[Writable]]: **false**, [[Enumerable]]: **false**, [[Configurable]]: **false** }.

15.13.6.4 Properties of the *TypeArray* Prototype Object

The value of the [[Prototype]] internal property of each *TypeArray* prototype object is the standard built-in Object prototype object (15.2.4). Its [[Class]] is “*TypeArray*”.

15.13.6.4.1 *TypeArray.prototype.constructor*

The initial value of *TypeArray.prototype.constructor* is the standard built-in *TypeArray* constructor.

15.13.6.4.2 *TypeArray.prototype.set(array [, offset])*

Set multiple values in the *TypedArray*, reading from the *array* input., reading input values from the array. The optional *offset* value indicates the index in the current array where values are written. If omitted, it is assumed to be 0.

1. If this does not have class “*TypeArray*”, throw a *TypeError*.
2. Let *offsetIndex* be *ToUint32(offset)*.
3. Let *O* be the result of calling *ToObject(array)*.
4. Let *srcLength* be the result of calling [[Get]] on *O* with property name “length”.
5. Let *targetLength* be the result of calling [[Get]] on this with property name “length”.
6. If *srcLength* + *offset* > *targetLength*, throw a *RangeError*.
7. Let *temp* be a new *TypeArray* created as if by a call to “new *TypeArray(srcLength)*”.
8. Let *k* be 0.
9. While *k* < *srcLength*
 - a. Let *v* be the result of calling [[Get]] on *src* with property name *toString(k)*.
 - b. Call [[Put]] on *temp* with arguments *ToString(k)*, *v*, and **false**.
10. Let *k* be *offset*.
11. While *k* < *targetLength*
 - c. Let *v* be the result of calling [[Get]] on *temp* with property name *ToString(k-offset)*.
 - d. Call [[Put]] on *temp* with arguments *ToString(k)*, *v*, and **false**.

Comment [AWB10145]: Not yet audited

15.13.6.4.3 TypeArray.prototype.subarray(begin [, end])

Returns a new *TypedArray* view of the *ArrayBuffer* store for this *TypedArray*, referencing the elements at *begin*, inclusive, up to *end*, exclusive. If either *begin* or *end* is negative, it refers to an index from the end of the array, as opposed to from the beginning.

1. If this does not have class “TypeArray”, throw a *TypeError*.
2. Let *srcLength* be the result of calling *[[Get]]* on this with property name “length”
3. Let *beginInt* be *ToInt32(begin)*
4. If *beginInt* < 0, let *beginInt* be *srcLength* + *beginInt*
5. Let *beginIndex* be *min(srcLength, max(0, beginInt))*
6. Let *endInt* be *ToInt32(end)* if *end* was provided, else *srcLength*.
7. If *endInt* < 0, let *endInt* be *srcLength* + *endInt*
8. Let *endIndex* be *max(0, min(srcLength, endInt))*
9. If *endIndex* < *beginIndex*, let *endIndex* be *beginIndex*
10. Return a new *TypeArray* with the following values for its properties:
 - The *length* property of the newly constructed object is set to *endIndex - beginIndex*
 - The *byteLength* property of the newly constructed object is set to *length* multiplied by the size in bytes of *Type*.
 - The *buffer* property of the newly constructed object is set to *this.buffer*.
 - The *byteOffset* property of the newly constructed object is set to *this.offset + beginIndex*.

Comment [AWB10146]: Not yet audited

15.13.6.5 Properties of TypeArray instances

TypeArray instances inherit properties from the *TypeArray* prototype object and their *[[Class]]* internal property value is “*TypeArray*”. *TypeArray* instances also have the following properties.

15.13.6.5.1 *[[DefineOwnProperty]]* (p, desc, throw)

TypeArray objects use a variation of the *[[DefineOwnProperty]]* internal method used for other native ECMAScript objects (8.12.9).

When the *[[DefineOwnProperty]]* internal method of *A* is called with property *P*, Property Descriptor *Desc* and Boolean flag *Throw*, the following steps are taken:

1. Let *succeeded* be the result of calling the default *[[DefineOwnProperty]]* internal method (8.12.9) on *A* passing *P*, *Desc*, and *Throw* as arguments.
2. If *succeeded* is false, return false.
3. If *Desc* contains a *Value* field, let *newValue* be *Desc.Value*.
4. Let *convertedValue* to *ToType(newValue)*
5. Let *index* be *ToUInt32(P)*
6. Call the *SetValueInBuffer* internal operation with arguments *A.buffer.[[NativeBuffer]]*, *A.byteOffset*, *index*, *convertedValue*, and *Type*.
7. Return true.

Comment [AWB10147]: Not yet audited

The internal operation *SetValueInBuffer* takes five parameters, a native buffer *nativeBuffer*, an integer *byteOffset*, an integer *index*, a value of type *Type* *newValue*, and a *Type* *valueType*. It operates as follows:

1. Let *size* be the size in bytes of the type *valueType*.
2. Let *bytes* be the array of bytes from *nativeBuffer* between offset *byteOffset+(index*size)* and offset *byteOffset+((index+1)*size)-1* inclusive.
3. Let *newValueBytes* be the result of converting *newValue* to an array of bytes, using the platform endianness.
4. Set each byte of *bytes* from the corresponding byte of *newValueBytes*.

Comment [AWB10148]: Not yet audited

15.13.6.5.2 [[GetOwnProperty]] (P)

TypeArray objects use a variation of the [[GetOwnProperty]] internal method used for other native ECMAScript objects (8.12.1). This special internal method provides access to named properties corresponding to the individual index values of the TypeArray objects.

When the [[GetOwnProperty]] internal method of A is called with property name P, the following steps are taken:

1. Let desc be the result of calling the default [[GetOwnProperty]] internal method (8.12.1) on A with argument P.
2. If desc is not undefined return desc.
3. If ToString(`abs(ToInteger(P))`) is not the same value as P, return undefined.
4. Let length be the result of a calling [[Get]] on A with parameter "length".
5. Let index be `ToInteger(P)`.
6. If `length ≤ index`, return undefined.
7. Let isLittleEndian be true if the platform endianness is little endian, else false.
8. Let value be the result of calling the GetValueFromBuffer internal operation with arguments `A.buffer[[NativeBuffer]], A.byteOffset, index, Type, and littleEndian`.
9. Return a Property Descriptor { [[Value]]: value, [[Enumerable]]: true, [[Writable]]: true, [[Configurable]]: false }.

Comment [AWB10149]: Not yet audited

The internal operation GetValueFromBuffer takes three parameters, a native buffer nativeBuffer, an integer byteOffset, an integer index, a Type valueType, and a boolean isLittleEndian. It operates as follows:

1. Let size be the size in bytes of the type valueType.
2. Let bytes be the array of bytes from nativeBuffer between offset byteOffset+(index*size) and offset byteOffset+((index+1)*size)-1 inclusive.
3. Let rawValue be the result of convert the array bytes to a value of type valueType, using little endian if isLittleEndian is true, otherwise big endian.
4. If valueType is Float32 and rawValue is a Float32 representation of IEEE754 NaN, return the NaN Number value.
5. Else, if valueType is Float64 and rawValue is a Float64 representation of IEEE754 NaN, return the NaN Number value.
6. Else, return the Number value that that represents the same numeric value as rawValue.

Comment [AWB10150]: Not yet audited

15.13.6.5.3 length

The value of the length property is the length of the TypeArray object, which was fixed at creation. This property has attributes { [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }.

15.13.6.5.4 byteLength

The value of the byteLength property is the length of the TypeArray object, which was fixed at creation. This property has attributes { [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }.

15.13.6.5.5 buffer

The value of the buffer property is the length of the TypeArray object, which was fixed at creation. This property has attributes { [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }.

15.13.6.5.6 byteOffset

The value of the byteOffset property is the length of the TypeArray object, which was fixed at creation. This property has attributes { [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }.

[15.13.7 DataView Objects](#)

[15.13.7.1 The DataView Constructor Called as a Function](#)

When `DataView` is called as a function rather than as a constructor, it creates and initialises a new `DataView` object. Thus the function call `DataView(...)` is equivalent to the object creation expression `new DataView(...)` with the same arguments.

[15.13.7.2 The DataView Constructor](#)

When `DataView` is called as part of a new expression, it is a constructor: it initialises the newly created object.

[15.13.7.2.1 `new DataView\(buffer \[, byteOffset \[, byteLength\]\]\)`](#)

The `[[Prototype]]` internal property of the newly constructed object is set to the original `DataView` prototype object, the one that is the initial value of `DataView.prototype` (15.13.3.3.1). The `[[Class]]` internal property of the newly constructed object is set to "DataView". The `[[Extensible]]` internal property of the newly constructed object is set to true.

The remaining properties are set as follows:

1. Let `O` be `ToObject(buffer)`
2. If the `[[Class]]` internal property of `O` is not "ArrayBuffer", raise a `TypeError`.
3. Let `byteOffset` be the result of calling `ToUInt32` on `byteOffset`, if provided, or else 0.
4. Let `bufferLength` be the result of calling `[[Get]]` on `O` with property name "byteLength".
5. Let `byteLength` be the result of calling `ToUInt32` on `byteLength`, if provided, or else `bufferLength - byteOffset`.
6. If `byteOffset + byteLength` is greater than `bufferLength`, raise a `RangeError` exception.
7. The `byteLength` property of the newly constructed object is set to `byteLength`.
8. The `buffer` property of the newly constructed object is set to `O`.
9. The `byteOffset` property of the newly constructed object is set to `byteOffset`.

Comment [AWB10151]: This entire section has been copied from the strawman with only minor formatting fixes. It has not yet had any technical review or integration.

[15.13.7.3 Properties of the DataView Constructor](#)

The value of the `[[Prototype]]` internal property of the `DataView` constructor is the Function prototype object (15.3.4).

Besides the internal properties and the `length` property (whose value is 3), the `DataView` constructor has the following properties:

[15.13.7.3.1 `DataView.prototype`](#)

The initial value of `DataView.prototype` is the `DataView` prototype object (15.13.3.4).

This property has the attributes `{ [[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false }`.

[15.13.7.4 Properties of the DataView Prototype Object](#)

The value of the `[[Prototype]]` internal property of the `DataView` prototype object is the standard built-in `Object` prototype object (15.2.4). The `[[Class]]` internal property of the newly constructed object is set to "Object". The `[[Extensible]]` internal property of the newly constructed object is set to true.

The internal operation `GetValue(byteOffset, isLittleEndian, type)` used by functions on `DataView` instances is defined as follows:

1. Let `byteOffsetInt` be `ToUInt32(byteOffset)`
2. Let `totalOffset` be `byteOffsetInt` plus the result of calling `[[Get]]` on this with parameter "byteOffset"
3. Let `byteLength` be the result of calling `[[Get]]` on this with parameter "byteLength"
4. If `totalOffset >= byteLength`, raise a `RangeError`

Comment [AWB10152]: Not yet audited

5. Let value be the result of calling the `GetValueFromBuffer` internal operation (2.5.2) with arguments `this.buffer.[[NativeBuffer]], totalOffset, 0` and `type`.
6. Return value

The `internal_operation_SetValue(byteOffset, isLittleEndian, type, value)` used by functions on `DataView` instances is defined as follows:

1. Let `byteOffsetInt` be `ToUInt32(byteOffset)`
2. Let `totalOffset` be `byteOffsetInt` plus the result of calling `[[Get]]` on `this` with parameter “`byteOffset`”
3. Let `byteLength` be the result of calling `[[Get]]` on `this` with parameter “`byteLength`”
4. If `totalOffset >= byteLength`, raise a `RangeError`
5. Let `value` be the result of calling the `SetValueInBuffer` internal operation (2.5.2) with arguments `this.buffer.[[NativeBuffer]], totalOffset, 0, value` and `type`.
6. Return value

15.13.7.4.1 DataView.prototype.constructor

The initial value of `DataView.prototype.constructor` is the standard built-in `DataView` constructor.

15.13.7.4.2 DataView.prototype.getInt8(byteOffset)

Gets the `Int8` value at offset `byteOffset` in the `DataView`.

1. Let `O` be `ToObject(this)`
2. If the `[[Class]]` internal property of `O` is not “`DataView`”, raise a `TypeError`.
3. Return `GetValue(byteOffset, true, Int8)`

15.13.7.4.3 DataView.prototype.getUint8(byteOffset)

Gets the `Uint8` value at offset `byteOffset` in the `DataView`.

1. Let `O` be `ToObject(this)`
2. If the `[[Class]]` internal property of `O` is not “`DataView`”, raise a `TypeError`.
3. Return `GetValue(byteOffset, true, Uint8)`

15.13.7.4.4 DataView.prototype.getInt16(byteOffset, littleEndian)

Gets the `Int16` value at offset `byteOffset` in the `DataView`, using the provided endianness.

1. Let `O` be `ToObject(this)`
2. Let `isLittleEndian` be `ToBoolean(littleEndian)` if provided, else `false`
3. If the `[[Class]]` internal property of `O` is not “`DataView`”, raise a `TypeError`.
4. Return `GetValue(byteOffset, isLittleEndian, Int16)`

15.13.7.4.5 DataView.prototype.getUint16(byteOffset, littleEndian)

Gets the `Uint16` value at offset `byteOffset` in the `DataView`, using the provided endianness.

1. Let `O` be `ToObject(this)`
2. Let `isLittleEndian` be `ToBoolean(littleEndian)` if provided, else `false`
3. If the `[[Class]]` internal property of `O` is not “`DataView`”, raise a `TypeError`.
4. Return `GetValue(byteOffset, isLittleEndian, Uint16)`

15.13.7.4.6 DataView.prototype.getInt32(byteOffset, littleEndian)

Gets the `Int32` value at offset `byteOffset` in the `DataView`, using the provided endianness.

1. Let `O` be `ToObject(this)`
2. Let `isLittleEndian` be `ToBoolean(littleEndian)` if provided, else `false`

3. If the [[Class]] internal property of O is not “DataView”, raise a `TypeError`.
4. Return `GetValue(byteOffset, isLittleEndian, Int32)`

[15.13.7.4.7 DataView.prototype.getUint32\(byteOffset, littleEndian\)](#)

Gets the `Uint32` value at offset `byteOffset` in the `DataView`, using the provided endianness.

1. Let O be `ToObject(this)`
2. Let `isLittleEndian` be `ToBoolean(littleEndian)` if provided, else `false`
3. If the [[Class]] internal property of O is not “DataView”, raise a `TypeError`.
4. Return `GetValue(byteOffset, isLittleEndian, Uint32)`

[15.13.7.4.8 DataView.prototype.getFloat32\(byteOffset, littleEndian\)](#)

Gets the `Float32` value at offset `byteOffset` in the `DataView`, using the provided endianness.

1. Let O be `ToObject(this)`
2. Let `isLittleEndian` be `ToBoolean(littleEndian)` if provided, else `false`
3. If the [[Class]] internal property of O is not “DataView”, raise a `TypeError`.
4. Return `GetValue(byteOffset, isLittleEndian, Float32)`

[15.13.7.4.9 DataView.prototype.getFloat64\(byteOffset, littleEndian\)](#)

Gets the `Float64` value at offset `byteOffset` in the `DataView`, using the provided endianness.

1. Let O be `ToObject(this)`
2. Let `isLittleEndian` be `ToBoolean(littleEndian)` if provided, else `false`
3. If the [[Class]] internal property of O is not “DataView”, raise a `TypeError`.
4. Return `GetValue(byteOffset, isLittleEndian, Float64)`

[15.13.7.4.10 DataView.prototype.setInt8\(byteOffset, value\)](#)

Sets the `Int8` value at offset `byteOffset` in the `DataView`.

1. Let O be `ToObject(this)`
2. If the [[Class]] internal property of O is not “DataView”, raise a `TypeError`.
3. Return `GetValue(byteOffset, true, Int8, ToInt8(value))`

[15.13.7.4.11 DataView.prototype.setUint8\(byteOffset, value\)](#)

Sets the `Uint8` value at offset `byteOffset` in the `DataView`.

4. Let O be `ToObject(this)`
5. If the [[Class]] internal property of O is not “DataView”, raise a `TypeError`.
6. Return `GetValue(byteOffset, true, Uint8, ToUint8(value))`

[15.13.7.4.12 DataView.prototype.setInt16\(byteOffset, value, littleEndian\)](#)

Sets the `Int16` value at offset `byteOffset` in the `DataView`.

1. Let O be `ToObject(this)`
2. Let `isLittleEndian` be `ToBoolean(littleEndian)` if provided, else `false`
3. If the [[Class]] internal property of O is not “DataView”, raise a `TypeError`.
4. Return `GetValue(byteOffset, isLittleEndian, Int16,ToInt16(value))`

[15.13.7.4.13 DataView.prototype.setUint16\(byteOffset, value, littleEndian\)](#)

Sets the `Uint16` value at offset `byteOffset` in the `DataView`.

1. Let O be ToObject(this)
2. Let isLittleEndian be ToBoolean(littleEndian) if provided, else false
3. If the [[Class]] internal property of O is not "DataView", raise a TypeError.
4. Return GetValue(byteOffset, isLittleEndian, Uint16, ToUint16(value))

15.13.7.4.14 DataView.prototype.setInt32(byteOffset, value, littleEndian)

Sets the Int32 value at offset byteOffset in the DataView.

1. Let O be ToObject(this)
2. Let isLittleEndian be ToBoolean(littleEndian) if provided, else false
3. If the [[Class]] internal property of O is not "DataView", raise a TypeError.
4. Return GetValue(byteOffset, isLittleEndian, Int32,ToInt32(value))

15.13.7.4.15 DataView.prototype.setUint32(byteOffset, value, littleEndian)

Sets the Uint32 value at offset byteOffset in the DataView.

1. Let O be ToObject(this)
2. Let isLittleEndian be ToBoolean(littleEndian) if provided, else false
3. If the [[Class]] internal property of O is not "DataView", raise a TypeError.
4. Return GetValue(byteOffset, isLittleEndian, Uint32, ToUint32(value))

15.13.7.4.16 DataView.prototype.setFloat32(byteOffset, value, littleEndian)

Sets the Float32 value at offset byteOffset in the DataView.

1. Let O be ToObject(this)
2. Let isLittleEndian be ToBoolean(littleEndian) if provided, else false
3. If the [[Class]] internal property of O is not "DataView", raise a TypeError.
4. Return GetValue(byteOffset, isLittleEndian, Float32, ToFloat32(value))

15.13.7.4.17 DataView.prototype.setUint16(byteOffset, value, littleEndian)

Sets the Float64 value at offset byteOffset in the DataView.

1. Let O be ToObject(this)
2. Let isLittleEndian be ToBoolean(littleEndian) if provided, else false
3. If the [[Class]] internal property of O is not "DataView", raise a TypeError.
4. Return GetValue(byteOffset, isLittleEndian, Float64, ToFloat64(value))

15.13.7.5 Properties of DataView Instances

DataView instances inherit properties from the `DataView.prototype` object and their [[Class]] internal property value is "DataView". DataView instances also have the following properties.

15.13.7.5.1 byteLength

The value of the `byteLength` property is the length of the `DataView` object, which was fixed at creation. This property has attributes { `[[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false` }.

15.13.7.5.2 buffer

The value of the `buffer` property is the length of the `DataView` object, which was fixed at creation. This property has attributes { `[[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false` }.

15.13.7.5.3 byteOffset

The value of the `byteOffset` property is the length of the `DataView` object, which was fixed at creation. This property has attributes { `[Writable]`: `false`, `[Enumerable]`: `false`, `[Configurable]`:`false` }.

15.14 Map Objects

Map objects are collections of key/value pairs where both the keys and values may be arbitrary ECMAScript values. A Map object can also iterate its elements in insertion order. Map object must be implemented using hash tables or other mechanisms that, on average, provide access times that are sublinear on the number of elements in the collection. The data structures used in this Map objects specification is only intended to describe the required observable semantics of Map objects. It is not intended to be a viable implementation model.

15.14.1 Abstract Operations For Map Objects

15.14.1.1 MapInitialization

The abstract operation `MapInitialization` with arguments `object` and `iterable` is used to initialize an object as a map. It performs the following steps:

1. If `Type(obj)` is not `Object`, throw a `TypeError` exception.
2. If `obj` already has a `[[MapData]]` internal property, throw a `TypeError` exception.
3. If the `[[Extensible]]` internal property of `obj` is `false`, throw a `TypeError` exception.
4. If `iterable` is not `undefined`, then
 - a. Let `iterable` be `ToObject(iterable)`.
 - b. `ReturnIfAbrupt(iterable)`.
 - c. Let `iterator` be the `@@iterator`.
 - d. Let `itr` be the result of calling the `Invoke` abstraction operation with `iterator`, `obj`, and an empty List as arguments.
 - e. `ReturnIfAbrupt(itr)`.
 - f. Let `addr` be the result of calling the `[[Get]]` internal method of `obj` with argument `"set"`.
 - g. `ReturnIfAbrupt(addr)`.
 - h. If `IsCallable(addr)` is `false`, throw a `TypeError` Exception.
5. Add a `[[MapData]]` internal property to `obj`.
6. Set `obj`'s `[[MapData]]` internal method to a new empty List.
7. If `iterable` is `undefined`, return `obj`.
8. Repeat
 - a. Let `next` be the result of performing `Invoke` with arguments `"next"`, `itr`, and an empty arguments List.
 - b. If `IteratorComplete(next)` is `true`, then return `NormalCompletion(obj)`.
 - c. Let `next` be `ToObject(next)`.
 - d. `ReturnIfAbrupt(next)`.
 - e. Let `k` be the result of calling the `[[Get]]` internal method of `next` with argument `"0"`.
 - f. `ReturnIfAbrupt(k)`.
 - g. Let `v` be the result of calling the `[[Get]]` internal method of `next` with argument `"1"`.
 - h. `ReturnIfAbrupt(v)`.
 - i. Let `status` be the result of calling the `[[Call]]` internal method of `addr` with arguments `obj` and a List whose elements are `k` and `v`.
 - j. `ReturnIfAbrupt(status)`.

Comment [AWB7153]: TODO: need to define

15.14.2 The Map Constructor Called as a Function

When `Map` is called as a function rather than as a constructor, it initializes its `this` value with the internal state necessary to support the `Map.prototype` internal methods. This permits super invocation of the `Map` constructor by `Map` subclasses.

15.14.2.1 Map (iterable = [])

1. Let *m* be the **this** value.
2. If *m* is **undefined** or the intrinsic **%MapPrototype%**
 - a. Let *map* be the result of the abstract operation **ObjectCreate** (15.2) with the intrinsic **%MapPrototype%** as the argument.
3. Else
 - a. Let *map* be the result of **ToObject**(*m*).
4. ReturnIfAbrupt(*map*).
5. If *iterable* is not present, let *iterable* be **undefined**.
6. Let *status* be the result of **MapInitialization** with *map* and *iterable* as arguments.
7. ReturnIfAbrupt(*status*).
8. Return *map*.

15.14.3 The Map Constructor

When **Map** is called as part of a **new** expression it is a constructor: it initialises the newly created object.

15.14.3.1 new Map (iterable = [])

1. Let *map* be the result of the abstract operation **ObjectCreate** (15.2) with the intrinsic **%MapPrototype%** as the argument.
2. If *iterable* is not present, let *iterable* be **undefined**.
3. Let *status* be the result of **MapInitialization** with *map* and *iterable* as arguments.
4. ReturnIfAbrupt(*status*).
5. Return *map*.

15.14.4 Properties of the Map Constructor

The value of the **[[Prototype]]** internal property of the **Map** constructor is the **Function** prototype object (15.3.4).

Besides the internal properties and the **length** property (whose value is **0**), the **Map** constructor has the following property:

15.14.4.1 Map.prototype

The initial value of **Map.prototype** is the **Map** prototype object (15.14.4).

This property has the attributes { **[[Writable]]: false, [[Enumerable]]: false, [[Configurable]]: false** }.

15.14.5 Properties of the Map Prototype Object

The value of the **[[Prototype]]** internal property of the **Map** prototype object is the standard built-in **Object** prototype object (15.2.4).

15.14.5.1 Map.prototype.constructor

The initial value of **Map.prototype.constructor** is the built-in **Map** constructor.

15.14.5.2 Map.prototype.delete (key)

The following steps are taken:

1. Let *M* be the result of calling **ToObject** with the **this** value as its argument.
2. ReturnIfAbrupt(*M*).
3. If *M* does not have a **[[MapData]]** internal property throw a **TypeError** exception.
4. Let *entries* be the List that is the value of *M*'s **[[MapData]]** internal property.
5. Repeat for each Record **{[[key]], [[value]]}** *p* that is an element of *entries*.
 - a. If **SameValue**(*p*.**[[key]]**, *key*), then
 - i. Set *p*.**[[key]]** to **empty**.

- ii. Set $p.[[value]]$ to empty.
- iii. Return **true**.

6. Return **false**.

15.14.5.3 Map.prototype.forEach (callbackfn , thisArg = undefined)

callbackfn should be a function that accepts three arguments. **forEach** calls *callbackfn* once for each key/value pair present in the map object, in key insertion order. *callbackfn* is called only for keys of the map which actually exist; it is not called for keys that have been deleted from the map.

If a *thisArg* parameter is provided, it will be used as the **this** value for each invocation of *callbackfn*. If it is not provided, **undefined** is used instead.

callbackfn is called with three arguments: the value of the item, the key of the item, and the Map object being traversed.

forEach does not directly mutate the object on which it is called but the object may be mutated by the calls to *callbackfn*.

NOTE Each key is visited only once with the value that is current at the time of the visit. If the value associated with a key is modified after it has been visited, it is not re-visited. Keys that are deleted after the call to **forEach** begins and before being visited are not visited. New keys added, after the call to **forEach** begins are visited.

When the **forEach** method is called with one or two arguments, the following steps are taken:

1. Let M be the result of calling **ToObject** with the **this** value as its argument.
2. ReturnIfAbrupt(M).
3. If M does not have a **[[MapData]]** internal property throw a **TypeError** exception.
4. If **IsCallable(callbackfn)** is **false**, throw a **TypeError** exception.
5. If *thisArg* was supplied, let T be *thisArg*; else let T be **undefined**.
6. Let *entries* be the List that is the value of M 's **[[MapData]]** internal property.
7. Repeat for each Record $\{[[key]], [[value]]\}$ e that is an element of *entries*, in original key insertion order
 - a. If $e.[[key]]$ is not empty, then
 - i. Let *funcResult* be the result of calling the **[[Call]]** internal method of *callbackfn* with T as the **this** value and argument list containing $e.[[value]]$, $e.[[key]]$, and M .
 - ii. ReturnIfAbrupt(*funcResult*).
8. Return **undefined**.

The **length** property of the **forEach** method is **1**.

15.14.5.4 Map.prototype.get (key)

The following steps are taken:

1. Let M be the result of calling **ToObject** with the **this** value as its argument.
2. ReturnIfAbrupt(M).
3. If M does not have a **[[MapData]]** internal property throw a **TypeError** exception.
4. Let *entries* be the List that is the value of M 's **[[MapData]]** internal property.
5. Repeat for each Record $\{[[key]], [[value]]\}$ p that is an element of *entries*.
 - a. If **SameValue(p.[[key]], key)**, then return $p.[[value]]$
6. Return **undefined**.

15.14.5.5 Map.prototype.has (key)

The following steps are taken:

1. Let M be the result of calling **ToObject** with the **this** value as its argument.
2. ReturnIfAbrupt(M).
3. If M does not have a **[[MapData]]** internal property throw a **TypeError** exception.
4. Let *entries* be the List that is the value of M 's **[[MapData]]** internal property.

5. Repeat for each Record $\{[[key]], [[value]]\}$ p that is an element of $entries$.
 - a. If $SameValue(p.[[key]], key)$, then return **true**.
6. Return **false**.

15.14.5.6 Map.prototype.items ()

The following steps are taken:

1. Return the result of calling the `CreateMapIterator` abstract operation with arguments O and "**key+value**".

15.14.5.7 Map.prototype.keys ()

The following steps are taken:

1. Return the result of calling the `CreateMapIterator` abstract operation with arguments O and "**key**".

15.14.5.8 Map.prototype.set (key , value)

The following steps are taken:

1. Let M be the result of calling `ToObject` with the `this` value as its argument.
2. `ReturnIfAbrupt(M)`.
3. If M does not have a `[[MapData]]` internal property throw a **TypeError** exception.
4. Let $entries$ be the List that is the value of M 's `[[MapData]]` internal property.
5. Repeat for each Record $\{[[key]], [[value]]\}$ p that is an element of $entries$.
 - a. If $SameValue(p.[[key]], key)$, then
 - i. Set $p.[[value]]$ to $value$.
 - ii. Return **undefined**.
6. Let p be the Record $\{[[key]]: key, [[value]]: value\}$.
7. Append p as the last element of $entries$.
8. Return **undefined**.

15.14.5.9 Map.prototype.size (key)

The following steps are taken:

1. Let M be the result of calling `ToObject` with the `this` value as its argument.
2. `ReturnIfAbrupt(M)`.
3. If M does not have a `[[MapData]]` internal property throw a **TypeError** exception.
4. Let $entries$ be the List that is the value of M 's `[[MapData]]` internal property.
5. Let $count$ be 0 .
6. For each Record $\{[[key]], [[value]]\}$ p that is an element of $entries$
 - a. $p.[[key]]$ is not empty then
 - i. Set $count$ to $count+1$.
7. Return $count$.

15.14.5.10 Map.prototype.values ()

The following steps are taken:

1. Return the result of calling the `CreateMapIterator` abstract operation with arguments O and "**value**".

15.14.5.11 Map.prototype[@@iterator] ()

The initial value of the `@@iterator` property is the same function object as the initial value of the `items` property.

Comment [AWB10154]: This is how we identify a property whose key is a built-in Symbol

Comment [AWB10155]: Do we really want to do this sort of method sharing. It has a bad smell.

[15.14.5.12 Map.prototype.@@toStringTag \(\)](#)

The initial value of the @@toStringTag property is the string value "Map".

[15.14.6 Properties of Map Instances](#)

Map instances inherit properties from the Map prototype. After initialization by the Map constructor, Map instances also have a [[MapData]] internal property.

[15.14.7 Map Iterator Objects](#)

A Map Iterator is an object that represent a specific iteration over some specific Map instance object. There is not a named constructor for Map Iterator objects. Instead, map iterator objects are created by calling certain methods of Map instance objects.

[15.14.7.1 CreateMapIterator Abstract Operation](#)

Several methods of Map objects return iterator objects. The abstract operation CreateMapIterator with arguments *map* and *kind* is used to create such iterator objects. It performs the following steps:

1. Let *M* be the result of calling `ToObject(map)`.
2. ReturnIfAbrupt(*M*).
3. If *M* does not have a [[MapData]] internal property throw a `TypeError` exception.
4. Let *entries* be the List that is the value of *M*'s [[MapData]] internal property.
5. Let *itr* be the result of the abstract operation `ObjectCreate` with the intrinsic object %MapIteratorPrototype% as its argument.
6. Add a [[Map]] internal property to *itr* with value *M*.
7. Add a [[MapNextIndex]] internal property to *itr* with value 0.
8. Add a [[MapIterationKind]] internal property of *itr* with value *kind*.
9. Return *itr*.

[15.14.7.2 The Map Iterator Prototype](#)

All Map Iterator Objects inherit properties from a common Map Iterator Prototype objects. The [[Prototype]] internal property of the Map Iterator Prototype is the %ObjectPrototype% intrinsic object. In addition, the Map Iterator Prototype has the following properties:

[15.14.7.2.1 MapIterator.prototype.constructor](#)

Comment [AWB10156]: TODO: need to decide what to use for a constructor for these sort of objects.

[15.14.7.2.2 MapIterator.prototype.next](#)

1. Let *O* be the `this` value.
2. If `Type(O)` is not `Object`, throw a `TypeError` exception.
3. If *O* does not have all of the internal properties of a Map Iterator Instance (15.14.7.1.2), throw a `TypeError` exception.
4. Let *m* be the value of the [[Map]] internal property of *O*.
5. Let *index* be the value of the [[MapNextIndex]] internal property of *O*.
6. Let *itemKind* be the value of the [[MapIterationKind]] internal property of *O*.
7. Assert: *m* has a [[MapData]] internal property.
8. Let *entries* be the List that is the value of the [[MapData]] internal property of *m*.
9. Repeat while *index* is less than the total number of elements of *entries*. The number of elements must be redetermine each time this method is evaluated.
 - a. Let *e* be the Record {[key], [value]} at 0-originated insertion position *index* of *entries*.
 - b. Set the [[MapNextIndex]] internal property of *O* to *index*.
 - c. If *e*.[[key]] is not empty, then
 - i. If *itemKind* is "key" then, let *result* be *e*.[[key]].
 - ii. Else if *itemKind* is "value" then, let *result* be *e*.[[value]].
 - iii. Else,
 1. Assert: *itemKind* is "key+value"

2. Let *result* be the result of the abstract operation *ObjectArray* with argument *2*.
3. Assert: *result* is a new, well-formed Array object so the following operations will never fail.
4. Call the *[[DefineOwnProperty]]* internal method of *result* with arguments "**0**", Property Descriptor *{[[Value]]: e.[[key]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}*, and **false**.
5. Call the *[[DefineOwnProperty]]* internal method of *result* with arguments "**1**", Property Descriptor *{[[Value]]: e.[[value]], [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}*, and **false**.
- iv. Return *result*.

10. Return Completion *{[[type]]: throw, [[value]]: %StopIteration%, [[target]]: empty}*.

15.14.5.11 MapIterator.prototype.[@@iterator] ()

The following steps are taken:

1. Return the **this** value.

15.14.7.2.3 MapIterator.prototype.[@@toStringTag]

The initial value of the *[@@toStringTag]* property is the string value **"Map Iterator"**.

15.14.7.3 Properties of Map Iterator Instances

Map Iterator instances inherit properties from the Map Iterator prototype (the intrinsic, `%MapIteratorPrototype%`.) Map Iterator instances are initially created with the following internal properties.

Table 30 Internal Properties of Map Iterator Instances

Internal Property Name	Description
<code>[[Map]]</code>	The Map object that is being iterated.
<code>[[MapNextIndex]]</code>	The integer index of the next Map data element to be examined by this iteration.
<code>[[MapIterationKind]]</code>	A string value that identifies what is to be returned for each element of the iteration. The possible values are: <code>"key"</code> , <code>"value"</code> , <code>"key+value"</code> .

15.15 WeakMap Objects

15.16 Set Objects

15.17 The Reflect Module

This is a place holder for the material in http://wiki.ecmascript.org/doku.php?id=harmony:reflect_api

Comment [AWB10159]: TODO

15.18 Proxy Objects

16 Errors

An implementation must report most errors at the time the relevant ECMAScript language construct is evaluated. An *early error* is an error that can be detected and reported prior to the evaluation of any construct in the *Program* containing the error. An implementation must report early errors in a *Program* prior to the first

evaluation of that *Program*. Early errors in **eval** code are reported at the time **eval** is called but prior to evaluation of any construct within the **eval** code. All errors that are not early errors are runtime errors.

An implementation must treat any instance of the following kinds of errors as an early error:

- Any syntax error.
- Attempts to define an *ObjectLiteral* that has multiple **get** property assignments with the same name or multiple **set** property assignments with the same name.
- Attempts to define an *ObjectLiteral* that has both a data property assignment and a **get** or **set** property assignment with the same name.
- Errors in regular expression literals that are not implementation-defined syntax extensions.
- Attempts in strict mode code to define an *ObjectLiteral* that has multiple data property assignments with the same name.
- The occurrence of a *WithStatement* in strict mode code.
- The occurrence of an *Identifier* value appearing more than once within a *FormalParameterList* of an individual strict mode *FunctionDeclaration* or *FunctionExpression*.
- Improper uses of **return**, **break**, and **continue**.
- Attempts to call **PutValue** on any value for which an early determination can be made that the value is not a *Reference* (for example, executing the assignment statement `3=4`).

An implementation shall not treat other kinds of errors as early errors even if the compiler can prove that a construct cannot execute without error under any circumstances. An implementation may issue an early warning in such a case, but it should not report the error until the relevant construct is actually executed.

An implementation shall report all errors as specified, except for the following:

- An implementation may extend program syntax and regular expression pattern or flag syntax. To permit this, all operations (such as calling **eval**, using a regular expression literal, or using the **Function** or **RegExp** constructor) that are allowed to throw **SyntaxError** are permitted to exhibit implementation-defined behaviour instead of throwing **SyntaxError** when they encounter an implementation-defined extension to the program syntax or regular expression pattern or flag syntax.
- An implementation may provide additional types, values, objects, properties, and functions beyond those described in this specification. This may cause constructs (such as looking up a variable in the global scope) to have implementation-defined behaviour instead of throwing an error (such as **ReferenceError**).
- An implementation may define behaviour other than throwing **RangeError** for **toFixed**, **toExponential**, and **toPrecision** when the *fractionDigits* or *precision* argument is outside the specified range.

DRAFT

Annex A (informative)

Grammar Summary

Field Code Changed
Field Code Changed
Field Code Changed

A.1 Lexical Grammar

SourceCharacter ::
any Unicode code unit

InputElementDiv ::
WhiteSpace
LineTerminator
Comment
Token
DivPunctuator

InputElementRegExp ::
WhiteSpace
LineTerminator
Comment
Token
RegularExpressionLiteral

WhiteSpace ::
<TAB>
<VT>
<FF>
<SP>
<NBSP>
<BOM>
<USP>

LineTerminator ::
<LF>
<CR>
<LS>
<PS>

LineTerminatorSequence ::
<LF>
<CR> [lookahead ≠ <LF>]
<LS>
<PS>
<CR> <LF>

Comment ::
MultiLineComment
SingleLineComment

See clause 6

See clause 7

See clause 7

See 7.2

See 7.3

See 7.3

See 7.4

<i>MultiLineComment ::</i>	See 7.4
<i>/* MultiLineCommentChars_{opt} */</i>	
<i>MultiLineCommentChars ::</i>	See 7.4
<i>MultiLineNotAsteriskChar MultiLineCommentChars_{opt}</i>	
<i>* PostAsteriskCommentChars_{opt}</i>	
<i>PostAsteriskCommentChars ::</i>	See 7.4
<i>MultiLineNotForwardSlashOrAsteriskChar MultiLineCommentChars_{opt}</i>	
<i>* PostAsteriskCommentChars_{opt}</i>	
<i>MultiLineNotAsteriskChar ::</i>	See 7.4
<i>SourceCharacter but not *</i>	
<i>MultiLineNotForwardSlashOrAsteriskChar ::</i>	See 7.4
<i>SourceCharacter but not one of / or *</i>	
<i>SingleLineComment ::</i>	See 7.4
<i>// SingleLineCommentChars_{opt}</i>	
<i>SingleLineCommentChars ::</i>	See 7.4
<i>SingleLineCommentChar SingleLineCommentChars_{opt}</i>	
<i>SingleLineCommentChar ::</i>	See 7.4
<i>SourceCharacter but not LineTerminator</i>	
<i>Token ::</i>	See 7.5
<i>IdentifierName</i>	
<i>Punctuator</i>	
<i>NumericLiteral</i>	
<i>StringLiteral</i>	
<i>Identifier ::</i>	See 7.6
<i>IdentifierName but not ReservedWord</i>	
<i>IdentifierName ::</i>	See 7.6
<i>IdentifierStart</i>	
<i>IdentifierName IdentifierPart</i>	
<i>IdentifierStart ::</i>	See 7.6
<i>UnicodeLetter</i>	
<i>\$</i>	
<i>\ UnicodeEscapeSequence</i>	

IdentifierPart :: See 7.6

IdentifierStart
UnicodeCombiningMark
UnicodeDigit
UnicodeConnectorPunctuation
<ZWNJ>
<ZWJ>

UnicodeLetter :: See 7.6

any character in the Unicode categories “Uppercase letter (Lu)”, “Lowercase letter (Ll)”, “Titlecase letter (Lt)”, “Modifier letter (Lm)”, “Other letter (Lo)”, or “Letter number (Ni)”.
See 7.6

UnicodeCombiningMark :: See 7.6

any character in the Unicode categories “Non-spacing mark (Mn)” or “Combining spacing mark (Mc)”
See 7.6

UnicodeDigit :: See 7.6

any character in the Unicode category “Decimal number (Nd)”
See 7.6

UnicodeConnectorPunctuation :: See 7.6

any character in the Unicode category “Connector punctuation (Pc)”
See 7.6

ReservedWord :: See 7.6.1

Keyword
FutureReservedWord
NullLiteral
BooleanLiteral

Keyword :: one of See 7.6.1.1

break	do	instanceof	typeof
case	else	new	var
catch	finally	return	void
continue	for	switch	while
debugger	function	this	with
default	if	throw	
delete	in	try	

FutureReservedWord :: one of See 7.6.1.2

class	enum	extends	super
const	export	import	

The following tokens are also considered to be *FutureReservedWords* when parsing strict mode code (see 10.1.1).

implements	let	private	public
interface	package	protected	static
yield			

<i>Punctuator :: one of</i>						<i>See 7.7</i>
{	}	()	[]	
,	;	,	<	>	<=	
>=	==	!=	====	!==		
+	-	*	%	++	--	
<<	>>	>>>	&		^	
!	~	&&		?	:	
=	+=	-=	*=	%=	<<=	
>>=	>>>=	&=	=	^=		
<i>DivPunctuator :: one of</i>						<i>See 7.7</i>
/	/=					<i>See 7.8</i>
<i>Literal ::</i>						
<i>NullLiteral</i>						
<i>BooleanLiteral</i>						
<i>NumericLiteral</i>						
<i>StringLiteral</i>						
<i>RegularExpressionLiteral</i>						
<i>NullLiteral ::</i>	null					<i>See 7.8.1</i>
<i>BooleanLiteral ::</i>	true					<i>See 7.8.2</i>
<i>false</i>						
<i>NumericLiteral ::</i>						<i>See 7.8.3</i>
<i>DecimalLiteral</i>						
<i>HexIntegerLiteral</i>						
<i>DecimalLiteral ::</i>						<i>See 7.8.3</i>
<i>DecimalIntegerLiteral</i>	.	<i>DecimalDigits_{opt}</i>	<i>ExponentPart_{opt}</i>			
.	<i>DecimalDigits</i>	<i>ExponentPart_{opt}</i>				
<i>DecimalIntegerLiteral</i>		<i>ExponentPart_{opt}</i>				
<i>DecimalIntegerLiteral ::</i>	0					<i>See 7.8.3</i>
	<i>NonZeroDigit</i>	<i>DecimalDigits_{opt}</i>				
<i>DecimalDigits ::</i>						<i>See 7.8.3</i>
<i>DecimalDigit</i>						
<i>DecimalDigits DecimalDigit</i>						
<i>DecimalDigit :: one of</i>						<i>See 7.8.3</i>
0	1	2	3	4	5	6
7	8	9				

NonZeroDigit :: **one of**
 1 2 3 4 5 6 7 8 9

See 7.8.3

ExponentPart ::
ExponentIndicator *SignedInteger*

See 7.8.3

ExponentIndicator :: **one of**
 e E

See 7.8.3

SignedInteger ::
DecimalDigits
 + *DecimalDigits*
 - *DecimalDigits*

See 7.8.3

HexIntegerLiteral ::
 0x *HexDigit*
 0X *HexDigit*
HexIntegerLiteral *HexDigit*

See 7.8.3

HexDigit :: **one of**
 0 1 2 3 4 5 6 7 8 9 a b c d e f A B C D E F

See 7.8.3

StringLiteral ::
 " *DoubleStringCharacters*_{opt} "
 ' *SingleStringCharacters*_{opt} '

See 7.8.4

DoubleStringCharacters ::
DoubleStringCharacter *DoubleStringCharacters*_{opt}

See 7.8.4

SingleStringCharacters ::
SingleStringCharacter *SingleStringCharacters*_{opt}

See 7.8.4

DoubleStringCharacter ::
SourceCharacter **but not one of** " or \ or *LineTerminator*
 \ *EscapeSequence*
LineContinuation

See 7.8.4

SingleStringCharacter ::
SourceCharacter **but not one of** ' or \ or *LineTerminator*
 \ *EscapeSequence*
LineContinuation

See 7.8.4

LineContinuation ::
 \ *LineTerminatorSequence*

See 7.8.4

EscapeSequence ::
CharacterEscapeSequence
 0 [lookahead \notin *DecimalDigit*]
HexEscapeSequence
UnicodeEscapeSequence

See 7.8.4

CharacterEscapeSequence ::
SingleEscapeCharacter
NonEscapeCharacter

See 7.8.4

SingleEscapeCharacter :: **one of**
 ' " \ b f n r t v

See 7.8.4

<i>NonEscapeCharacter ::</i>	<i>SourceCharacter but not one of EscapeCharacter or LineTerminator</i>	See 7.8.4
<i>EscapeCharacter ::</i>		See 7.8.4
<i>SingleEscapeCharacter</i>		
<i>DecimalDigit</i>		
<i>x</i>		
<i>u</i>		
<i>HexEscapeSequence ::</i>		See 7.8.4
<i>x HexDigit HexDigit</i>		
<i>UnicodeEscapeSequence ::</i>		See 7.8.4
<i>u HexDigit HexDigit HexDigit HexDigit</i>		
<i>RegularExpressionLiteral ::</i>		See 7.8.5
<i>/ RegularExpressionBody / RegularExpressionFlags</i>		
<i>RegularExpressionBody ::</i>		See 7.8.5
<i>RegularExpressionFirstChar RegularExpressionChars</i>		
<i>RegularExpressionChars ::</i>		See 7.8.5
<i>[empty]</i>		
<i>RegularExpressionChars RegularExpressionChar</i>		
<i>RegularExpressionFirstChar ::</i>		See 7.8.5
<i>RegularExpressionNonTerminator but not one of * or \ or / or [</i>		
<i>RegularExpressionBackslashSequence</i>		
<i>RegularExpressionClass</i>		
<i>RegularExpressionChar ::</i>		See 7.8.5
<i>RegularExpressionNonTerminator but not \ or / or [</i>		
<i>RegularExpressionBackslashSequence</i>		
<i>RegularExpressionClass</i>		
<i>RegularExpressionBackslashSequence ::</i>		See 7.8.5
<i>\ RegularExpressionNonTerminator</i>		
<i>RegularExpressionNonTerminator ::</i>		See 7.8.5
<i>SourceCharacter but not LineTerminator</i>		
<i>RegularExpressionClass ::</i>		See 7.8.5
<i>[RegularExpressionClassChars]</i>		
<i>RegularExpressionClassChars ::</i>		See 7.8.5
<i>[empty]</i>		
<i>RegularExpressionClassChars RegularExpressionClassChar</i>		
<i>RegularExpressionClassChar ::</i>		See 7.8.5
<i>RegularExpressionNonTerminator but not] or \</i>		
<i>RegularExpressionBackslashSequence</i>		

RegularExpressionFlags ::=
 [empty]
RegularExpressionFlags IdentifierPart

See 7.8.5

A.2 Number Conversions

<i>StringNumericLiteral</i> ::= <i>StrWhiteSpace_{opt}</i> <i>StrWhiteSpace_{opt} StrNumericLiteral StrWhiteSpace_{opt}</i>	See 9.1.3.1
<i>StrWhiteSpace</i> ::= <i>StrWhiteSpaceChar StrWhiteSpace_{opt}</i>	See 9.1.3.1
<i>StrWhiteSpaceChar</i> ::= <i>WhiteSpace</i> <i>LineTerminator</i>	See 9.1.3.1
<i>StrNumericLiteral</i> ::= <i>StrDecimalLiteral</i> <i>HexIntegerLiteral</i>	See 9.1.3.1
<i>StrDecimalLiteral</i> ::= <i>StrUnsignedDecimalLiteral</i> <i>+ StrUnsignedDecimalLiteral</i> <i>- StrUnsignedDecimalLiteral</i>	See 9.1.3.1
<i>StrUnsignedDecimalLiteral</i> ::= Infinity <i>DecimalDigits . DecimalDigits_{opt} ExponentPart_{opt}</i> <i>. DecimalDigits ExponentPart_{opt}</i> <i>DecimalDigits ExponentPart_{opt}</i>	See 9.1.3.1
<i>DecimalDigits</i> ::= <i>DecimalDigit</i> <i>DecimalDigits DecimalDigit</i>	See 9.1.3.1
<i>DecimalDigit</i> :: one of 0 1 2 3 4 5 6 7 8 9	See 9.1.3.1
<i>ExponentPart</i> ::= <i>ExponentIndicator SignedInteger</i>	See 9.1.3.1
<i>ExponentIndicator</i> :: one of e E	See 9.1.3.1
<i>SignedInteger</i> ::= <i>DecimalDigits</i> <i>+ DecimalDigits</i> <i>- DecimalDigits</i>	See 9.1.3.1

HexIntegerLiteral :::
 0x *HexDigit*
 0X *HexDigit*
HexIntegerLiteral *HexDigit*

See 9.1.3.1

HexDigit ::: one of
 0 1 2 3 4 5 6 7 8 9 a b c d e f A B C D E F

See 9.1.3.1

A.3 Expressions

PrimaryExpression :
 this
Identifier
Literal
ArrayLiteral
ObjectLiteral
 (Expression)

See 11.1

ArrayLiteral :
 [*Elision*_{opt}]
 [*ElementList*]
 [*ElementList* , *Elision*_{opt}]

See 11.1.4

ElementList :
*Elision*_{opt} AssignmentExpression
ElementList , *Elision*_{opt} AssignmentExpression

See 11.1.4

Elision :

'
Elision ,

See 11.1.4

ObjectLiteral :
 { }
 { *PropertyNameAndValueList* }
 { *PropertyNameAndValueList* , }

See 11.1.5

PropertyNameAndValueList :
PropertyNameAssignment
PropertyNameAndValueList , *PropertyNameAssignment*

See 11.1.5

PropertyNameAssignment :
PropertyName : AssignmentExpression
get *PropertyName* () { *FunctionBody* }
set *PropertyName* (*PropertySetParameterList*) { *FunctionBody* }

See 11.1.5

PropertyName :
IdentifierName
StringLiteral
NumericLiteral

See 11.1.5

PropertySetParameterList :
Identifier

See 11.1.5

MemberExpression :

- PrimaryExpression*
- FunctionExpression*
- MemberExpression [Expression]*
- MemberExpression . IdentifierName*
- new MemberExpression Arguments**

See 11.2

NewExpression :

- MemberExpression*
- new NewExpression**

See 11.2

CallExpression :

- MemberExpression Arguments*
- CallExpression Arguments*
- CallExpression [Expression]*
- CallExpression . IdentifierName*

See 11.2

Arguments :

- ()*
- (ArgumentList)*

See 11.2

ArgumentList :

- AssignmentExpression*
- ArgumentList , AssignmentExpression*

See 11.2

LeftHandSideExpression :

- NewExpression*
- CallExpression*

See 11.2

PostfixExpression :

- LeftHandSideExpression*
- LeftHandSideExpression [no LineTerminator here] ++*
- LeftHandSideExpression [no LineTerminator here] --*

See 11.3

UnaryExpression :

- PostfixExpression*
- delete UnaryExpression**
- void UnaryExpression**
- typeof UnaryExpression**
- ++ UnaryExpression**
- UnaryExpression**
- + UnaryExpression**
- UnaryExpression**
- ~ UnaryExpression**
- ! UnaryExpression**

See 11.4

MultiplicativeExpression :

- UnaryExpression*
- MultiplicativeExpression * UnaryExpression*
- MultiplicativeExpression / UnaryExpression*
- MultiplicativeExpression % UnaryExpression*

See 11.5

AdditiveExpression : See 11.6

MultiplicativeExpression
AdditiveExpression + MultiplicativeExpression
AdditiveExpression - MultiplicativeExpression

ShiftExpression : See 11.7

AdditiveExpression
ShiftExpression << AdditiveExpression
ShiftExpression >> AdditiveExpression
ShiftExpression >>> AdditiveExpression

RelationalExpression : See 11.8

ShiftExpression
RelationalExpression < ShiftExpression
RelationalExpression > ShiftExpression
RelationalExpression <= ShiftExpression
RelationalExpression >= ShiftExpression
RelationalExpression instanceof ShiftExpression
RelationalExpression in ShiftExpression

RelationalExpressionNoIn : See 11.8

ShiftExpression
RelationalExpressionNoIn < ShiftExpression
RelationalExpressionNoIn > ShiftExpression
RelationalExpressionNoIn <= ShiftExpression
RelationalExpressionNoIn >= ShiftExpression
RelationalExpressionNoIn instanceof ShiftExpression

EqualityExpression : See 11.9

RelationalExpression
EqualityExpression == RelationalExpression
EqualityExpression != RelationalExpression
EqualityExpression === RelationalExpression
EqualityExpression !== RelationalExpression

EqualityExpressionNoIn : See 11.9

RelationalExpressionNoIn
EqualityExpressionNoIn == RelationalExpressionNoIn
EqualityExpressionNoIn != RelationalExpressionNoIn
EqualityExpressionNoIn === RelationalExpressionNoIn
EqualityExpressionNoIn !== RelationalExpressionNoIn

BitwiseANDExpression : See 11.10

EqualityExpression
BitwiseANDExpression & EqualityExpression

BitwiseANDExpressionNoIn : See 11.10

EqualityExpressionNoIn
BitwiseANDExpressionNoIn & EqualityExpressionNoIn

BitwiseXORExpression :
BitwiseANDExpression
BitwiseXORExpression ^ BitwiseANDExpression

See 11.10

BitwiseXORExpressionNoIn :
BitwiseANDExpressionNoIn
BitwiseXORExpressionNoIn ^ BitwiseANDExpressionNoIn

See 11.10

BitwiseORExpression :
BitwiseXORExpression
BitwiseORExpression | BitwiseXORExpression

See 11.10

BitwiseORExpressionNoIn :
BitwiseXORExpressionNoIn
BitwiseORExpressionNoIn | BitwiseXORExpressionNoIn

See 11.10

LogicalANDExpression :
BitwiseORExpression
LogicalANDExpression && BitwiseORExpression

See 11.11

LogicalANDExpressionNoIn :
BitwiseORExpressionNoIn
LogicalANDExpressionNoIn && BitwiseORExpressionNoIn

See 11.11

LogicalORExpression :
LogicalANDExpression
LogicalORExpression || LogicalANDExpression

See 11.11

LogicalORExpressionNoIn :
LogicalANDExpressionNoIn
LogicalORExpressionNoIn || LogicalANDExpressionNoIn

See 11.11

ConditionalExpression :
LogicalORExpression
LogicalORExpression ? AssignmentExpression : AssignmentExpression

See 11.12

ConditionalExpressionNoIn :
LogicalORExpressionNoIn
LogicalORExpressionNoIn ? AssignmentExpression : AssignmentExpressionNoIn

See 11.12

AssignmentExpression :
ConditionalExpression
LeftHandSideExpression = AssignmentExpression
LeftHandSideExpression AssignmentOperator AssignmentExpression

See 11.13

AssignmentExpressionNoIn :
ConditionalExpressionNoIn
LeftHandSideExpression = AssignmentExpressionNoIn
LeftHandSideExpression AssignmentOperator AssignmentExpressionNoIn

See 11.13

AssignmentOperator : **one of**
 $\ast\ast=$ $/=$ $\%=$ $+=$ $-=$ $<<=$ $>>=$ $>>>=$ $\&=$ $\wedge=$ $\mid=$

See 11.13

Expression :
AssignmentExpression
Expression , *AssignmentExpression*

See 11.14

ExpressionNoIn :
AssignmentExpressionNoIn
ExpressionNoIn , *AssignmentExpressionNoIn*

See 11.14

A.4 Statements

Statement :
Block
VariableStatement
EmptyStatement
ExpressionStatement
IfStatement
IterationStatement
ContinueStatement
BreakStatement
ReturnStatement
WithStatement
LabelledStatement
SwitchStatement
ThrowStatement
TryStatement
DebuggerStatement

See clause 12

Block :
 $\{ \text{StatementList}_{\text{opt}} \}$

See 12.1

StatementList :
Statement
StatementList Statement

See 12.1

VariableStatement :
 $\text{var } \text{VariableDeclarationList} ;$

See 12.2

VariableDeclarationList :
VariableDeclaration
VariableDeclarationList , *VariableDeclaration*

See 12.2

VariableDeclarationListNoIn :
VariableDeclarationNoIn
VariableDeclarationListNoIn , *VariableDeclarationNoIn*

See 12.2

VariableDeclaration :
*Identifier Initialiser*_{opt}

See 12.2

VariableDeclarationNoIn :
*Identifier InitialiserNoIn*_{opt}

See 12.2

Initialiser :
 $= \text{AssignmentExpression}$ See 12.2

InitialiserNoIn :
 $= \text{AssignmentExpressionNoIn}$ See 12.2

EmptyStatement :
 $; \quad$ See 12.3

ExpressionStatement :
 $[\text{lookahead } \notin \{\}, \text{ function}] \text{Expression} ; \quad$ See 12.4

IfStatement :
 $\text{if} (\text{Expression}) \text{ Statement} \text{ else Statement}$
 $\text{if} (\text{Expression}) \text{ Statement}$ See 12.5

IterationStatement :
 $\text{do Statement while} (\text{Expression}) ;$
 $\text{while} (\text{Expression}) \text{ Statement}$
 $\text{for} (\text{ExpressionNoIn}_{\text{opt}}; \text{Expression}_{\text{opt}}; \text{Expression}_{\text{opt}}) \text{ Statement}$
 $\text{for} (\text{var VariableDeclarationListNoIn}; \text{Expression}_{\text{opt}}; \text{Expression}_{\text{opt}}) \text{ Statement}$
 $\text{for} (\text{LeftHandSideExpression in Expression}) \text{ Statement}$
 $\text{for} (\text{var VariableDeclarationNoIn in Expression}) \text{ Statement}$ See 12.6

ContinueStatement :
 $\text{continue} ;$
 $\text{continue} [\text{no LineTerminator here}] \text{ Identifier} ;$ See 12.7

BreakStatement :
 $\text{break} ;$
 $\text{break} [\text{no LineTerminator here}] \text{ Identifier} ;$ See 12.8

ReturnStatement :
 $\text{return} ;$
 $\text{return} [\text{no LineTerminator here}] \text{ Expression} ;$ See 12.9

WithStatement :
 $\text{with} (\text{Expression}) \text{ Statement}$ See 12.10

SwitchStatement :
 $\text{switch} (\text{Expression}) \text{ CaseBlock}$ See 12.11

CaseBlock :
 $\{ \text{CaseClauses}_{\text{opt}} \}$
 $\{ \text{CaseClauses}_{\text{opt}} \text{ DefaultClause} \text{ CaseClauses}_{\text{opt}} \}$ See 12.11

CaseClauses :
 CaseClause
 $\text{CaseClauses CaseClause}$ See 12.11

CaseClause :
case Expression : StatementList_{opt}

See 12.11

DefaultClause :
default : StatementList_{opt}

See 12.11

LabelledStatement :
Identifier : Statement

See 12.12

ThrowStatement :
throw [no LineTerminator here] Expression ;

See 12.13

TryStatement :
try Block Catch
try Block Finally
try Block Catch Finally

See 12.14

Catch :
catch (Identifier) Block

See 12.14

Finally :
finally Block

See 12.14

DebuggerStatement :
debugger ;

See 12.15

A.5 Functions and Programs

FunctionDeclaration :
function Identifier (FormalParameterList_{opt}) { FunctionBody }

See clause 13

FunctionExpression :
function Identifier_{opt} (FormalParameterList_{opt}) { FunctionBody }

See clause 13

FormalParameterList :
Identifier
FormalParameterList , Identifier

See clause 13

FunctionBody :
SourceElements_{opt}

See clause 13

Program :
SourceElements_{opt}

See clause 14

SourceElements :
SourceElement
SourceElements SourceElement

See clause 14

SourceElement :
Statement
FunctionDeclaration

See clause 14

A.6 Universal Resource Identifier Character Classes

uri ::=

 $\text{uriCharacters}_{\text{opt}}$ See 15.1.3

uriCharacters ::=

 $\text{uriCharacter } \text{uriCharacters}_{\text{opt}}$ See 15.1.3

uriCharacter ::=

 uriReserved
 uriUnescaped
 uriEscaped See 15.1.3

uriReserved :: **one of**
 $\text{; } / \text{? } \text{: } @ \text{& } = \text{+ } \$ \text{, , }$ See 15.1.3

uriUnescaped ::=

 uriAlpha
 DecimalDigit
 uriMark See 15.1.3

uriEscaped ::=

 $\% \text{HexDigit} \text{ HexDigit}$ See 15.1.3

uriAlpha :: **one of**
 $a \text{ b } c \text{ d } e \text{ f } g \text{ h } i \text{ j } k \text{ l } m \text{ n } o \text{ p } q \text{ r } s \text{ t } u \text{ v } w \text{ x } y \text{ z }$
 $A \text{ B } C \text{ D } E \text{ F } G \text{ H } I \text{ J } K \text{ L } M \text{ N } O \text{ P } Q \text{ R } S \text{ T } U \text{ V } W \text{ X } Y \text{ Z }$ See 15.1.3

uriMark :: **one of**
 $- \text{ _ } . \text{ ! } \text{ ~ } \text{ * } \text{ ' } \text{ () }$ See 15.1.3

A.7 Regular Expressions

Pattern ::=

 Disjunction See 15.10.1

Disjunction ::=

 Alternative
 $\text{Alternative } | \text{ Disjunction}$ See 15.10.1

Alternative ::=

 $[\text{empty}]$
 Alternative Term See 15.10.1

Term ::=

 Assertion
 Atom
 Atom Quantifier See 15.10.1

Assertion ::

```

    ^
    $ 
    \ b
    \ B
    (? = Disjunction )
    (? ! Disjunction )
  
```

See 15.10.1

Quantifier ::

```

    QuantifierPrefix
    QuantifierPrefix ?
  
```

See 15.10.1

QuantifierPrefix ::

```

    *
    +
    ?
    { DecimalDigits }
    { DecimalDigits , }
    { DecimalDigits , DecimalDigits }
  
```

See 15.10.1

Atom ::

```

    PatternCharacter
    .
    \ AtomEscape
    CharacterClass
    ( Disjunction )
    (? : Disjunction )
  
```

See 15.10.1

PatternCharacter ::

SourceCharacter **but not one of-**

```

    ^ $ \ . * + ? ( ) [ ] { } |
  
```

See 15.10.1

AtomEscape ::

```

    DecimalEscape
    CharacterEscape
    CharacterClassEscape
  
```

See 15.10.1

CharacterEscape ::

```

    ControlEscape
    ControlLetter
    HexEscapeSequence
    UnicodeEscapeSequence
    IdentityEscape
  
```

See 15.10.1

ControlEscape :: one of

```

    f n r t v
  
```

See 15.10.1

ControlLetter :: one of

a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z

See 15.10.1

IdentityEscape ::
SourceCharacter but not IdentifierPart
<ZWJ>
<ZWNJ>

See 15.10.1

DecimalEscape ::
DecimalIntegerLiteral [lookahead \notin DecimalDigit]

See 15.10.1

CharacterClassEscape :: one of
d D s S w W

See 15.10.1

CharacterClass ::
[lookahead \notin {}] ClassRanges]
[^ ClassRanges]

See 15.10.1

ClassRanges ::
[empty]
NonemptyClassRanges

See 15.10.1

NonemptyClassRanges ::
ClassAtom
ClassAtom NonemptyClassRangesNoDash
ClassAtom - ClassAtom ClassRanges

See 15.10.1

NonemptyClassRangesNoDash ::
ClassAtom
ClassAtomNoDash NonemptyClassRangesNoDash
ClassAtomNoDash - ClassAtom ClassRanges

See 15.10.1

ClassAtom ::
-
ClassAtomNoDash

See 15.10.1

ClassAtomNoDash ::
SourceCharacter but not one of \ or] or -
\ ClassEscape

See 15.10.1

ClassEscape ::
DecimalEscape
b
CharacterEscape
CharacterClassEscape

See 15.10.1

A.8 JSON

A.8.1 JSON Lexical Grammar

JSONWhiteSpace ::
<TAB>
<CR>

See 15.12.1.1

<LF>	
<SP>	
<i>JSONString</i> ::	<i>See 15.12.1.1</i>
" <i>JSONStringCharacters_{opt}</i> "	
<i>JSONStringCharacters</i> ::	<i>See 15.12.1.1</i>
<i>JSONStringCharacter</i> <i>JSONStringCharacters_{opt}</i>	
<i>JSONStringCharacter</i> ::	<i>See 15.12.1.1</i>
<i>SourceCharacter</i> but not one of " or \ or U+0000 through U+001F	
\ <i>JSONEscapeSequence</i>	
<i>JSONEscapeSequence</i> ::	<i>See 15.12.1.1</i>
<i>JSONEscapeCharacter</i>	
<i>UnicodeEscapeSequence</i>	
<i>JSONEscapeCharacter</i> :: one of	<i>See 15.12.1.1</i>
" / \ b f n r t	
<i>JSONNumber</i> ::	<i>See 15.12.1.1</i>
- _{opt} <i>DecimalIntegerLiteral</i> <i>JSONFraction_{opt}</i> <i>ExponentPart_{opt}</i>	
<i>JSONFraction</i> ::	<i>See 15.12.1.1</i>
. <i>DecimalDigits</i>	
<i>JSONNullLiteral</i> ::	<i>See 15.12.1.1</i>
<i>NullLiteral</i>	
<i>JSONBooleanLiteral</i> ::	<i>See 15.12.1.1</i>
<i>BooleanLiteral</i>	
A.8.2 JSON Syntactic Grammar	
<i>JSONText</i> :	<i>See 15.12.1.2</i>
<i>JSONValue</i>	
<i>JSONValue</i> :	<i>See 15.12.1.2</i>
<i>JSONNullLiteral</i>	
<i>JSONBooleanLiteral</i>	
<i>JSONObject</i>	
<i>JSONArray</i>	
<i>JSONString</i>	
<i>JSONNumber</i>	
<i>JSONObject</i> :	<i>See 15.12.1.2</i>
{ }	
{ <i>JSONMemberList</i> }	
<i>JSONMember</i> :	<i>See 15.12.1.2</i>
<i>JSONString</i> : <i>JSONValue</i>	
<i>JSONMemberList</i> :	<i>See 15.12.1.2</i>
<i>JSONMember</i>	
<i>JSONMemberList</i> , <i>JSONMember</i>	
<i>JSONArray</i> :	<i>See 15.12.1.2</i>
[]	
[<i>JSONElementList</i>]	

JSONElementList :
JSONValue
JSONElementList , JSONValue

See 15.12.1.2

DRAFT

DRAFT

Annex B (normative)

Additional ECMAScript Features for Web Browsers

The ECMAScript language syntax and semantics defined in this annex are required when the ECMAScript host is a web browser. The content of this annex is normative but optional if the ECMAScript host is not a web browser.

B.1 Additional Syntax

B.1.1 Numeric Literals

The syntax and semantics of 7.8.3 is extended as follows except that this extension is not allowed for strict mode code:

Syntax

```
NumericLiteral ::  
  DecimalLiteral  
  BinaryIntegerLiteral  
  OctalIntegerLiteral  
  HexIntegerLiteral  
  LegacyOctalIntegerLiteral
```

```
LegacyOctalIntegerLiteral ::  
  0 OctalDigit  
  LegacyOctalIntegerLiteral OctalDigit
```

Static Semantics

- The MV of LegacyOctalIntegerLiteral :: 0 OctalDigit is the MV of OctalDigit.
- The MV of LegacyOctalIntegerLiteral :: LegacyOctalIntegerLiteral OctalDigit is (the MV of LegacyOctalIntegerLiteral times 8) plus the MV of OctalDigit.

B.1.2 String Literals

The syntax and semantics of 7.8.4 is extended as follows except that this extension is not allowed for strict mode code:

Syntax

```
EscapeSequence ::  
  CharacterEscapeSequence  
  OctalEscapeSequence  
  HexEscapeSequence  
  UnicodeEscapeSequence
```

```
OctalEscapeSequence ::  
  OctalDigit [lookahead ≠ DecimalDigit]  
  ZeroToThree OctalDigit [lookahead ≠ DecimalDigit]  
  FourToSeven OctalDigit  
  ZeroToThree OctalDigit OctalDigit
```

```
ZeroToThree :: one of  
  0 1 2 3
```

Comment [AW160]: Need to add new material that is not in previous versions of annex B

Deleted: informative

Deleted: Compatibility

Deleted: is

Deleted: s

Deleted: It

Deleted: Past editions of ECMAScript have included additional syntax and semantics for specifying octal literals and octal escape sequences. These have been removed from this edition of ECMAScript. This non-normative annex presents uniform syntax and semantics for octal literals and octal escape sequences for compatibility with some older ECMAScript programs.

Deleted: can be

Deleted: OctalDigit :: one of
 0 1 2 3 4 5 6 7

Deleted: <#>The MV of NumericLiteral :: OctalIntegerLiteral is the MV of OctalIntegerLiteral.
<#>The MV of OctalDigit :: 0 is 0.
<#>The MV of OctalDigit :: 1 is 1.
<#>The MV of OctalDigit :: 2 is 2.
<#>The MV of OctalDigit :: 3 is 3.
<#>The MV of OctalDigit :: 4 is 4.
<#>The MV of OctalDigit :: 5 is 5.
<#>The MV of OctalDigit :: 6 is 6.
<#>The MV of OctalDigit :: 7 is 7.

Deleted: can be

FourToSeven :: one of
4 5 6 7

Static Semantics

- The CV of *EscapeSequence* :: *OctalEscapeSequence* is the CV of the *OctalEscapeSequence*.
- The CV of *OctalEscapeSequence* :: *OctalDigit* [lookahead \notin *DecimalDigit*] is the character whose code unit value is the MV of the *OctalDigit*.
- The CV of *OctalEscapeSequence* :: *ZeroToThree OctalDigit* [lookahead \notin *DecimalDigit*] is the character whose code unit value is (8 times the MV of the *ZeroToThree*) plus the MV of the *OctalDigit*.
- The CV of *OctalEscapeSequence* :: *FourToSeven OctalDigit* is the character whose code unit value is (8 times the MV of the *FourToSeven*) plus the MV of the *OctalDigit*.
- The CV of *OctalEscapeSequence* :: *ZeroToThree OctalDigit OctalDigit* is the character whose code unit value is (64 (that is, 8^2) times the MV of the *ZeroToThree*) plus (8 times the MV of the first *OctalDigit*) plus the MV of the second *OctalDigit*.
- The MV of *ZeroToThree* :: 0 is 0.
- The MV of *ZeroToThree* :: 1 is 1.
- The MV of *ZeroToThree* :: 2 is 2.
- The MV of *ZeroToThree* :: 3 is 3.
- The MV of *FourToSeven* :: 4 is 4.
- The MV of *FourToSeven* :: 5 is 5.
- The MV of *FourToSeven* :: 6 is 6.
- The MV of *FourToSeven* :: 7 is 7.

B.2 Additional Properties

When the ECMAScript host is a web browser the following additional properties of the standard built-in objects are defined.

B.2.1 Additional Properties of the Global Object

B.2.1.1 escape (string)

The `escape` function is a property of the global object. It computes a new version of a String value in which certain characters have been replaced by a hexadecimal escape sequence.

For those characters being replaced whose code unit value is `0xFF` or less, a two-digit escape sequence of the form `%xx` is used. For those characters being replaced whose code unit value is greater than `0xFF`, a four-digit escape sequence of the form `%uxxxx` is used.

When the `escape` function is called with one argument *string*, the following steps are taken:

1. Call `ToString(string)`.
2. Compute the number of characters in *Result(1)*.
3. Let *R* be the empty string.
4. Let *k* be 0.
5. If *k* equals *Result(2)*, return *R*.
6. Get the character (represented as a 16-bit unsigned integer) at position *k* within *Result(1)*.
7. If *Result(6)* is one of the 69 nonblank characters
`"ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz0123456789@*_+-./"`
then go to step 13.
8. If *Result(6)* is less than 256, go to step 11.
9. Let *S* be a String containing six characters "`%uvwxyz`" where *wxyz* are four hexadecimal digits encoding the value of *Result(6)*.
10. Go to step 14.
11. Let *S* be a String containing three characters "`%xy`" where *xy* are two hexadecimal digits encoding the value of *Result(6)*.

Deleted: Some implementations of
Deleted: have included
Deleted: these
Deleted: for some
Deleted: native

Deleted: This non-normative annex suggests uniform semantics for such properties without making the properties or their semantics part of this standard.

12. Go to step 14.
13. Let *S* be a String containing the single character Result(6).
14. Let *R* be a new String value computed by concatenating the previous value of *R* and *S*.
15. Increase *k* by 1.
16. Go to step 5.

NOTE The encoding is partly based on the encoding described in RFC 1738, but the entire encoding specified in this standard is described above without regard to the contents of RFC 1738. This encoding does not reflect changes to RFC 1738 made by RFC 3986.

B.2.1.2 `unescape(string)`

The `unescape` function is a property of the global object. It computes a new version of a String value in which each escape sequence of the sort that might be introduced by the `escape` function is replaced with the character that it represents.

When the `unescape` function is called with one argument *string*, the following steps are taken:

1. Call `ToString(string)`.
2. Compute the number of characters in Result(1).
3. Let *R* be the empty String.
4. Let *k* be 0.
5. If *k* equals Result(2), return *R*.
6. Let *c* be the character at position *k* within Result(1).
7. If *c* is not %, go to step 18.
8. If *k* is greater than Result(2)–6, go to step 14.
9. If the character at position *k*+1 within Result(1) is not u, go to step 14.
10. If the four characters at positions *k*+2, *k*+3, *k*+4, and *k*+5 within Result(1) are not all hexadecimal digits, go to step 14.
11. Let *c* be the character whose code unit value is the integer represented by the four hexadecimal digits at positions *k*+2, *k*+3, *k*+4, and *k*+5 within Result(1).
12. Increase *k* by 5.
13. Go to step 18.
14. If *k* is greater than Result(2)–3, go to step 18.
15. If the two characters at positions *k*+1 and *k*+2 within Result(1) are not both hexadecimal digits, go to step 18.
16. Let *c* be the character whose code unit value is the integer represented by two zeroes plus the two hexadecimal digits at positions *k*+1 and *k*+2 within Result(1).
17. Increase *k* by 2.
18. Let *R* be a new String value computed by concatenating the previous value of *R* and *c*.
19. Increase *k* by 1.
20. Go to step 5.

B.2.2 Additional Properties of the `String.prototype` Object

B.2.2.1 `String.prototype.substr(start, length)`

The `substr` method takes two arguments, *start* and *length*, and returns a substring of the result of converting the this object to a String, starting from character position *start* and running for *length* characters (or through the end of the String if *length* is `undefined`). If *start* is negative, it is treated as `(sourceLength+start)` where *sourceLength* is the length of the String. The result is a String value, not a String object. The following steps are taken:

1. `ReturnIfAbrupt(CheckObjectCoercible(this value))`.
2. Let *S* be the result of performing `ToString`, giving it the `this` value as its argument.
3. Let *intStart* be `ToInteger(start)`.
4. `ReturnIfAbrupt(intStart)`.
5. If *length* is `undefined`, let *end* be $+\infty$; otherwise let *end* be `ToInteger(length)`.
6. `ReturnIfAbrupt(end)`.

Deleted: Call

Deleted: Call

Deleted: use

Deleted: call

7. Let *size* be the number of characters in *S*.
8. If *intStart* is negative, then let *intStart* be $\max(\text{size} + \text{intStart}, 0)$.
9. Let *resultLength* be $\min(\max(\text{end}, 0), \text{size} - \text{intStart})$.
10. If *resultLength* ≤ 0, return the empty String "".
11. Return a String containing *resultLength* consecutive characters from *S* beginning with the character at position *intStart*.

The `length` property of the `substr` method is 2.

NOTE The `substr` function is intentionally generic; it does not require that its `this` value be a String object. Therefore it can be transferred to other kinds of objects for use as a method.

B.2.2.2 `String.prototype.anchor (name)`

When the `anchor` method is called with argument *name*, the following steps are taken:

1. Let *S* be the `this` value.
2. Return the result of performing the abstract operation `CreateHTML` with arguments *S*, "a", "`name`" and *name*.

The abstract operation `CreateHTML` is called with arguments *string*, *tag*, *attribute*, and *value*. The arguments *tag* and *attribute* must be string values. The following steps are taken:

1. ReturnIfAbrupt(`CheckObjectCoercible(string)`).
2. Let *S* be the result of performing `ToString(string)`.
3. ReturnIfAbrupt(*S*).
4. Let *p1* be the string value that is the concatenation of "<" and *tag*.
5. If *attribute* is not the empty String, then
 - a. Let *V* be the result of performing `ToString(value)`.
 - b. ReturnIfAbrupt(*V*).
 - c. Let *escapedV* be the string value that is the same as *V* except that each occurrence of the character " (code unit value 0x0022) in *V* has been replaced with the six character sequence """.
 - d. Let *p1* be the string value that is the concatenation of the following string values:
 - *p1*
 - a single space code unit 0x0020
 - *attribute*
 - "="
 - " "
 - *escapedV*
 - " "
6. Let *p2* be the string value that is the concatenation of *p1* and ">".
7. Let *p3* be the string value that is the concatenation of *p2*, "</", *tag*, and ">".
8. Return *p3*.

- Deleted:** Compute
- Deleted:** Result(1)
- Deleted:** Result(2)
- Deleted:** positive or zero
- Deleted:** use Result(2); else
- Deleted:** use
- Deleted:** Result(4)
- Deleted:** Result(2)
- Deleted:** Compute
- Deleted:** Result(3)
- Deleted:** Result(4)
- Deleted:** Result(5)
- Deleted:** Result(6)
- Deleted:** ""
- Deleted:** Result(6)
- Deleted:** Result(1)
- Deleted:** Result(5)

Deleted: <#>If *attribute* is not the empty String
then
<#>Let *V* be the result of performing
`ToString(value)`.¶
<#>ReturnIfAbrupt(*V*).¶

Deleted: character

Deleted: *V*

B.2.2.3 `String.prototype.big ()`

When the `big` method is called with no arguments, the following steps are taken:

1. Let *S* be the `this` value.
2. Return the result of performing the abstract operation `CreateHTML` with arguments *S*, "big", "" and "".

B.2.2.4 `String.prototype.blink ()`

When the `blink` method is called with no arguments, the following steps are taken:

1. Let *S* be the `this` value.
2. Return the result of performing the abstract operation `CreateHTML` with arguments *S*, "blink", "" and "".

Deleted: c

B.2.2.5 String.prototype.bold ()

When the **bold** method is called with no arguments, the following steps are taken:

1. Let *S* be the **this** value.
2. Return the result of performing the abstract operation **CreateHTML** with arguments *S*, "b", "" and "".

B.2.2.6 String.prototype.fixed ()

Deleted: A

When the **fixed** method is called with no arguments, the following steps are taken:

1. Let *S* be the **this** value.
2. Return the result of performing the abstract operation **CreateHTML** with arguments *S*, "tt", "" and "".

B.2.2.7 String.prototype.fontcolor (color)

Deleted: A

When the **fontcolor** method is called with argument *color*, the following steps are taken:

1. Let *S* be the **this** value.
2. Return the result of performing the abstract operation **CreateHTML** with arguments *S*, "font", "color" and *color*.

B.2.2.8 String.prototype.fontSize (size)

Deleted: A

When the **fontSize** method is called with argument *size*, the following steps are taken:

1. Let *S* be the **this** value.
2. Return the result of performing the abstract operation **CreateHTML** with arguments *S*, "font", "size" and *size*.

B.2.2.9 String.prototype.italics ()

Deleted: A

When the **italics** method is called with no arguments, the following steps are taken:

1. Let *S* be the **this** value.
2. Return the result of performing the abstract operation **CreateHTML** with arguments *S*, "i", "" and "".

B.2.2.10 String.prototype.link (url)

Deleted: A

When the **link** method is called with argument *url*, the following steps are taken:

1. Let *S* be the **this** value.
2. Return the result of performing the abstract operation **CreateHTML** with arguments *S*, "a", "href" and *url*.

B.2.2.11 String.prototype.small ()

Deleted: A

When the **small** method is called with no arguments, the following steps are taken:

1. Let *S* be the **this** value.
2. Return the result of performing the abstract operation **CreateHTML** with arguments *S*, "small", "" and "".

Deleted: s

B.2.2.12 String.prototype.strike ()

Deleted: A

When the **strike** method is called with no arguments, the following steps are taken:

1. Let *S* be the **this** value.

2. Return the result of performing the abstract operation `CreateHTML` with arguments *S*, `"strike"`, `""` and `""`.

Deleted: return

Deleted: *s*

Deleted: *A*

B.2.2.13 `String.prototype.sub()`

When the `sub` method is called with no arguments, the following steps are taken:

1. Let *S* be the `this` value.
2. Return the result of performing the abstract operation `CreateHTML` with arguments *S*, `"sub"`, `""` and `""`.

Deleted: return

Deleted: *s*

Deleted: *A*

B.2.2.14 `String.prototype.sup()`

When the `sup` method is called with no arguments, the following steps are taken:

1. Let *S* be the `this` value.
2. Return the result of performing the abstract operation `CreateHTML` with arguments *S*, `"sup"`, `""` and `""`.

Deleted: return

Deleted: *s*

B.2.3 Additional Properties of the `Date.prototype` Object

B.2.3.1 `Date.prototype.getYear()`

NOTE The `getFullYear` method is preferred for nearly all purposes, because it avoids the “year 2000 problem.”

When the `getYear` method is called with no arguments, the following steps are taken:

1. Let *t* be this time value.
2. ReturnIfAbrupt(*t*).
3. If *t* is `NAN`, return `NAN`.
4. Return `YearFromTime(LocalTime(t)) - 1900`.

Deleted: return

Deleted: *s*

B.2.3.2 `Date.prototype.setYear(year)`

NOTE The `setFullYear` method is preferred for nearly all purposes, because it avoids the “year 2000 problem.”

When the `setYear` method is called with one argument *year*, the following steps are taken:

1. Let *t* be the result of `LocalTime(this time value)`; but if this time value is `NAN`, let *t* be `+0`.
2. Let *y* be `ToNumber(year)`.
3. If *y* is `NAN`, set the `[[PrimitiveValue]]` internal property of the `this` value to `NAN` and return `NAN`.
4. If *y* is not `NAN` and $0 \leq y \leq 99$ then let *vyyv* be `ToInteger(y) + 1900`. Otherwise, let *vyyv* be *y*.
5. Let *d* be `MakeDay(vyyv, MonthFromTime(t), DateFromTime(t))`.
6. Let *date* be `UTC(MakeDate(d, TimeWithinDay(t)))`.
7. Set the `[[PrimitiveValue]]` internal property of the `this` value to `TimeClip(date)`.
8. Return the value of the `[[PrimitiveValue]]` internal property of the `this` value.

Deleted: Call

Deleted: Result(2)

Deleted: Result(2)

Deleted: Result(2)

Deleted: Result(4)

Deleted: is

Deleted: Result(2)

Deleted: Result(4)

Deleted: is

Deleted: Result(2)

Deleted: Compute

Deleted: Result(4)

Deleted: Compute

Deleted: Result(5)

Deleted: Result(6)

B.2.3.3 `Date.prototype.toGMTString()`

NOTE The property `toUTCString` is preferred. The `toGMTString` property is provided principally for compatibility with old code. It is recommended that the `toUTCString` property be used in new ECMAScript code.

The Function object that is the initial value of `Date.prototype.toGMTString` is the same Function object that is the initial value of `Date.prototype.toUTCString`.

B.3 Other Additional Features

B.3.1 The `proto` pseudo property.

B.3.1.1 `Object.prototype.proto`

The initial value of the `__proto__` property of the Object prototype object is a data property whose initial value is `null`. This property initially has the attributes `{ [[Writable]]: true, [[Enumerable]]: false, [[Configurable]]: true }`.

Manipulations of this property are tracked by the Boolean valued primordial internal variable `UnderscoreProtoEnabled`. The default initial value of `UnderscoreProtoEnabled` is `true` only if this property is initially present on the primordial Object prototype object.

NOTE Any modification of this property or its attributes causes `UnderscoreProtoEnabled` to be set to `false`.

B.3.1.2 Changes To Internal Methods

The definition of the `[[Get]]` internal method given in 8.12.3 is replaced with the following:

1. If P is the string value "`proto`" and `UnderscoreProtoEnabled` is `true`, then
 - a. Let $desc$ be the result of calling the `[[GetProperty]]` internal method of O with property name P .
 - b. If $desc$ is not `undefined` and was created by step 1.a to describe the property defined in B.3.1.1 then,
 - i. Return the value of the `[[Prototype]]` internal property of O .
2. Continue by executing the steps of 8.12.3 starting with step 1.

The definition of the `[[Put]]` internal method given in 8.12.5 is replaced with the following:

1. If P is the string value "`proto`" and `UnderscoreProtoEnabled` is `true` and O is not the standard built-in Object prototype object, then
 - a. Let $desc$ be the result of calling the `[[GetProperty]]` internal method of O with property name P .
 - b. If $desc$ is not `undefined` and was created by step 1.a to describe the property defined in B.3.1.1 then,
 - i. If the type of V is neither Object or Null, return
 - ii. Set the value of the `[[Prototype]]` internal property of O to V .
 - iii. Return.
2. Continue by executing the steps of 8.12.5 starting with step 1.

The definition of the `[[Delete]]` internal method given in 8.12.7 is replaced with the following:

1. If `UnderscoreProtoEnabled` is `true` and P is the string value "`proto`" and O is the standard built-in Object prototype object, then
 - a. Set `UnderscoreProtoEnabled` to `false`.
2. Continue by executing the steps of 8.12.7 starting with step 1.

The definition of the `[[DefineOwnProperty]]` internal method given in 8.12.9 is replaced with the following:

1. If `UnderscoreProtoEnabled` is `true` and P is the string value "`proto`" and O is the standard built-in Object prototype object, then
 - a. If any attribute contained in $Desc$ is not present or has a different value from the corresponding attribute in `{ [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true }` then,
 - i. Set `UnderscoreProtoEnabled` to `false`.
2. Continue by executing the steps of 8.12.9 starting with step 1.

Comment [AWB161]: The section and algorithm reference in this draft are based upon the ES5.1 spec. When the corresponding sections of this document are stable, this section will need to be updated.

Comment [AWB8162]: This material is going to be made mandatory and integrated into the main body of spec.

Comment [AWB163]: This is anticipating new specification material related to Module loaders and establishing a primordial environment. The basic assumption is that a module loader must be able to disable this feature. This seems to suggest that the ability to do so must exist in the module loader API even if this feature is not present in an implementation.

B.3.1.3 proto Object Initialisers

Definitions of two algorithms in 11.1.5 are replaced with the following:

The production *PropertyDefinitionList : PropertyDefinition* is evaluated as follows:

1. Let *obj* be the result of creating a new object as if by the expression `new Object()` where `Object` is the standard built-in constructor with that name.
2. Let *propId* be the result of evaluating *PropertyDefinition*.
3. If *propId.name* is the string value "`proto`" and `UnderscoreProtoEnabled` is `true` and `IsDataDescriptor(propId.descriptor)` is `true`, then
 - a. Let *v* be *propId.descriptor.value*.
 - b. If *desc* be *propId.descriptor*
 - c. If the type of *v* is either `Object` or `Null`,
 - i. Set the value of the `[[Prototype]]` internal property of *obj* to *v*.
 - ii. Return *obj*.
4. Call the `[[DefineOwnProperty]]` internal method of *obj* with arguments *propId.name*, *propId.descriptor*, and `false`.
5. Return *obj*.

Deleted: *PropertyNameAndValueList*
Deleted: *PropertyAssignment*

Deleted: *PropertyAssignment*

Deleted: *O*
Deleted: *V*

The production

PropertyDefinitionList : PropertyDefinitionList , PropertyDefinition
 is evaluated as follows:

1. Let *obj* be the result of evaluating *PropertyDefinitionList*.
2. Let *propId* be the result of evaluating *PropertyDefinition*.
3. Let *previous* be the result of calling the `[[GetOwnProperty]]` internal method of *obj* with argument *propId.name*.
4. If *previous* is not `undefined` then throw a `SyntaxError` exception if any of the following conditions are true
 - a. This production is contained in strict code and `IsDataDescriptor(previous)` is `true` and `IsDataDescriptor(propId.descriptor)` is `true`.
 - b. `IsDataDescriptor(previous)` is `true` and `IsAccessorDescriptor(propId.descriptor)` is `true`.
 - c. `IsAccessorDescriptor(previous)` is `true` and `IsDataDescriptor(propId.descriptor)` is `true`.
 - d. `IsAccessorDescriptor(previous)` is `true` and `IsAccessorDescriptor(propId.descriptor)` is `true` and either both *previous* and *propId.descriptor* have `[[Get]]` fields or both *previous* and *propId.descriptor* have `[[Set]]` fields
5. If *propId.name* is the string value "`proto`" and `UnderscoreProtoEnabled` is `true` and `IsDataDescriptor(propId.descriptor)` is `true`, then
 - a. Let *v* be *propId.descriptor.value*.
 - b. If *desc* be *propId.descriptor*
 - c. If the type of *v* is either `Object` or `Null`,
 - i. Set the value of the `[[Prototype]]` internal property of *obj* to *v*.
 - ii. Return *obj*.
5. Call the `[[DefineOwnProperty]]` internal method of *obj* with arguments *propId.name*, *propId.descriptor*, and `false`.
6. Return *obj*.

Deleted: *PropertyNameAndValueList*
Deleted: *PropertyNameAndValueList*
Deleted: *PropertyAssignment*
Deleted: *PropertyNameAndValueList*
Deleted: *PropertyAssignment*

Deleted: *O*
Deleted: *V*

Annex C (informative)

The Strict Mode of ECMAScript

Field Code Changed
Field Code Changed
Field Code Changed

The strict mode restriction and exceptions

- The identifiers "implements", "interface", "let", "package", "private", "protected", "public", "static", and "yield" are classified as *FutureReservedWord* tokens within strict mode code. (7.6.12).
- A conforming implementation, when processing strict mode code, may not extend the syntax of *NumericLiteral* (7.8.3) to include *OctalIntegerLiteral* as described in B.1.1.
- A conforming implementation, when processing strict mode code (see 10.1.1), may not extend the syntax of *EscapeSequence* to include *OctalEscapeSequence* as described in B.1.2.
- Assignment to an undeclared identifier or otherwise unresolvable reference does not create a property in the global object. When a simple assignment occurs within strict mode code, its *LeftHandSide* must not evaluate to an unresolvable Reference. If it does a **ReferenceError** exception is thrown (8.9.2). The *LeftHandSide* also may not be a reference to a data property with the attribute value `{[[Writable]]:false}`, to an accessor property with the attribute value `{[[Set]]:undefined}`, nor to a non-existent property of an object whose `[[Extensible]]` internal property has the value **false**. In these cases a **TypeError** exception is thrown (11.13.1).
- The identifier **eval** or **arguments** may not appear as the *LeftHandSideExpression* of an Assignment operator (11.13) or of a *PostfixExpression* (11.3) or as the *UnaryExpression* operated upon by a Prefix Increment (11.4.4) or a Prefix Decrement (11.4.5) operator.
- Arguments objects for strict mode functions define non-configurable accessor properties named "**caller**" and "**callee**" which throw a **TypeError** exception on access (10.6).
- Arguments objects for strict mode functions do not dynamically share their array indexed property values with the corresponding formal parameter bindings of their functions. (10.6).
- For strict mode functions, if an arguments object is created the binding of the local identifier **arguments** to the arguments object is immutable and hence may not be the target of an assignment expression. (10.5).
- It is a **SyntaxError** if strict mode code contains an *ObjectLiteral* with more than one definition of any data property (11.1.5).
- It is a **SyntaxError** if the Identifier "**eval**" or the Identifier "**arguments**" occurs as the Identifier in a *PropertySetParameterList* of a *PropertyDefinition* that is contained in strict code or if its *FunctionBody* is strict code (11.1.5).
- Strict mode eval code cannot instantiate variables or functions in the variable environment of the caller to eval. Instead, a new variable environment is created and that environment is used for declaration binding instantiation for the eval code (10.4.2).
- If **this** is evaluated within strict mode code, then the **this** value is not coerced to an object. A **this** value of **null** or **undefined** is not converted to the global object and primitive values are not converted to wrapper objects. The **this** value passed via a function call (including calls made using `Function.prototype.apply` and `Function.prototype.call`) do not coerce the passed this value to an object (10.4.3, 11.1.1, 15.3.4.3, 15.3.4.4).
- When a **delete** operator occurs within strict mode code, a **SyntaxError** is thrown if its *UnaryExpression* is a direct reference to a variable, function argument, or function name(11.4.1).

Deleted: 7

Deleted: *PropertyAssignment*

- When a `delete` operator occurs within strict mode code, a **TypeError** is thrown if the property to be deleted has the attribute `{ [[Configurable]]:false }` (11.4.1).
- It is a **SyntaxError** if a `VariableDeclaration` or `VariableDeclarationNoIn` occurs within strict code and its `Identifier` is `eval` or `arguments` (12.2.1).
- Strict mode code may not include a `WithStatement`. The occurrence of a `WithStatement` in such a context is an **SyntaxError** (12.10).
- It is a **SyntaxError** if a `TryStatement` with a `Catch` occurs within strict code and the `Identifier` of the `Catch` production is `eval` or `arguments` (12.14.1).
- It is a **SyntaxError** if the identifier `eval` or `arguments` appears within a `FormalParameterList` of a strict mode `FunctionDeclaration` or `FunctionExpression` (13.1).
- A strict mode function may not have two or more formal parameters that have the same name. An attempt to create such a function using a `FunctionDeclaration`, `FunctionExpression`, or `Function` constructor is a **SyntaxError** (13.1, 15.3.2).
- An implementation may not extend, beyond that defined in this specification, the meanings within strict mode functions of properties named `caller` or `arguments` of function instances. ECMAScript code may not create or modify properties with these names on function objects that correspond to strict mode functions (10.6, 13.6, 15.3.4.5.3).
- It is a **SyntaxError** to use within strict mode code the identifiers `eval` or `arguments` as the `Identifier` of a `FunctionDeclaration` or `FunctionExpression` or as a formal parameter name (13.1). Attempting to dynamically define such a strict mode function using the `Function` constructor (15.3.2) will throw a **SyntaxError** exception.

Deleted: 2

DRY

Annex D (informative)

Corrections and Clarifications with Possible Compatibility Impact

Deleted: in the 5th Edition

Deleted: 3rd Edition

Deleted: the 6th

In Edition 6

15.9.1.15: If a time zone offset is not present, the local time zone is used. Edition 5.1 incorrectly stated that a missing time zone should be interpreted as "z".

15.9.5.2: Previous editions did not specify the value returned by Date.prototype.toString when this time value is NaN. The 6th Edition specifies the result to be the String value is "**Invalid Date**".

In 5.1 Edition 5.1

7.8.4: CV definitions added for DoubleStringCharacter :: LineContinuation and SingleStringCharacter :: LineContinuation.

10.2.1.1.3: The argument S is not ignored. It controls whether an exception is thrown when attempting to set an immutable binding.

10.2.1.2.2: In algorithm step 5, **true** is passed as the last argument to [[DefineOwnProperty]].

10.5: Former algorithm step 5.e is now 5.f and a new step 5.e was added to restore compatibility with 3rd Edition when redefining global functions.

11.5.3: In the final bullet item, use of IEEE 754 round-to-nearest mode is specified.

12.6.3: Missing ToBoolean restored in step 3.a.ii of both algorithms.

12.6.4: Additional final sentences in each of the last two paragraphs clarify certain property enumeration requirements.

12.7, 12.8, 12.9: BNF modified to clarify that a **continue** or **break** statement without an Identifier or a **return** statement without an Expression may have a LineTerminator before the semi-colon.

12.14: Step 3 of algorithm 1 and step 2.a of algorithm 3 are corrected such that the value field of B is passed as a parameter rather than B itself.

15.1.2.2: In step 2 of algorithm, clarify that S may be the empty string.

15.1.2.3: In step 2 of algorithm clarify that trimmedString may be the empty string.

15.1.3: Added notes clarifying that ECMAScript's URI syntax is based upon RFC 2396 and not the newer RFC 3986. In the algorithm for Decode, a step was removed that immediately preceded the current step 4.d.vii.10.a because it tested for a condition that cannot occur.

15.2.3.7: Corrected use of variable P in steps 5 and 6 of algorithm.

15.2.4.2: Edition 5 handling of **undefined** and **null** as **this** value caused existing code to fail. Specification modified to maintain compatibility with such code. New steps 1 and 2 added to the algorithm.

15.3.4.3: Steps 5 and 7 of Edition 5 algorithm have been deleted because they imposed requirements upon the argArray argument that are inconsistent with other uses of generic array-like objects.

15.4.4.12: In step 9.a, incorrect reference to *relativeStart* was replaced with a reference to *actualStart*.

15.4.4.15: Clarified that the default value for *fromIndex* is the length minus 1 of the array.

15.4.4.18: In step 9 of the algorithm, **undefined** is now the specified return value.

15.4.4.22: In step 9.c.ii the first argument to the **[[Call]]** internal method has been changed to **undefined** for consistency with the definition of `Array.prototype.reduce`.

15.4.5.1: In Algorithm steps 3.l.ii and 3.l.iii the variable name was inverted resulting in an incorrectly inverted test.

15.5.4.9: Normative requirement concerning canonically equivalent strings deleted from paragraph following algorithm because it is listed as a recommendation in NOTE 2.

15.5.4.14: In `split` algorithm step 11.a and 13.a, the positional order of the arguments to *SplitMatch* was corrected to match the actual parameter signature of *SplitMatch*. In step 13.a.iii.7.d, *lengthA* replaces *A.length*.

15.5.5.2: In first paragraph, removed the implication that the individual character property access had “array index” semantics. Modified algorithm steps 3 and 5 such that they do not enforce “array index” requirement.

15.9.1.15: Specified legal value ranges for fields that lacked them. Eliminated “time-only” formats. Specified default values for all optional fields.

15.10.2.2: The step numbers of the algorithm for the internal closure produced by step 2 were incorrectly numbered in a manner that implied that they were steps of the outer algorithm.

15.10.2.6: In the abstract operation *IsWordChar* the first character in the list in step 3 is “*a*” rather than “*A*”.

15.10.2.8: In the algorithm for the closure returned by the abstract operation *CharacterSetMatcher*, the variable defined by step 3 and passed as an argument in step 4 was renamed to *ch* in order to avoid a name conflict with a formal parameter of the closure.

15.10.6.2: Step 9.e was deleted because it performed an extra increment of *i*.

15.11.1.1: Removed requirement that the *message own* property is set to the empty String when the *message* argument is **undefined**.

15.11.1.2: Removed requirement that the *message own* property is set to the empty String when the *message* argument is **undefined**.

15.11.4.4: Steps 6-10 modified/added to correctly deal with missing or empty *message* property value.

15.11.1.2: Removed requirement that the *message own* property is set to the empty String when the *message* argument is **undefined**.

15.12.3: In step 10.b.iii of the *J4* internal operation, the last element of the concatenation is “1”.

B.2.1: Added to NOTE that the encoding is based upon RFC 1738 rather than the newer RFC 3986.

Annex C: An item was added corresponding to 7.6.12 regarding *FutureReservedWords* in strict mode.

In 5th Edition 5

Deleted: the

Throughout: In the Edition 3 specification the meaning of phrases such as “as if by the expression `new Array()`” are subject to misinterpretation. In the Edition 5 specification text for all internal references and invocations of standard built-in objects and methods has been clarified by making it explicit that the intent is

that the actual built-in object is to be used rather than the current dynamic value of the correspondingly named property.

11.8.1: ECMAScript generally uses a left to right evaluation order, however the Edition 3 specification language for the `>` and `<=` operators resulted in a partial right to left order. The specification has been corrected for these operators such that it now specifies a full left to right evaluation order. However, this change of order is potentially observable if side-effects occur during the evaluation process.

Deleted: 2

Deleted: , 11.8.3, 11.8.5

11.1.4: Edition 5 clarifies the fact that a trailing comma at the end of an *ArrayInitialiser* does not add to the length of the array. This is not a semantic change from Edition 3 but some implementations may have previously misinterpreted this.

11.2.3: Edition 5 reverses the order of steps 2 and 3 of the algorithm. The original order as specified in Editions 1 through 3 was incorrectly specified such that side-effects of evaluating *Arguments* could affect the result of evaluating *MemberExpression*.

12.4: In Edition 3, an object is created, as if by `new Object()` to serve as the scope for resolving the name of the exception parameter passed to a `catch` clause of a `try` statement. If the actual exception object is a function and it is called from within the `catch` clause, the scope object will be passed as the `this` value of the call. The body of the function can then define new properties on its `this` value and those property names become visible identifiers bindings within the scope of the `catch` clause after the function returns. In Edition 5, when an exception parameter is called as a function, `undefined` is passed as the `this` value.

13: In Edition 3, the algorithm for the production *FunctionExpression* with an *Identifier* adds an object created as if by `new Object()` to the scope chain to serve as a scope for looking up the name of the function. The identifier resolution rules (10.1.4 in Edition 3) when applied to such an object will, if necessary, follow the object's prototype chain when attempting to resolve an identifier. This means all the properties of `Object.prototype` are visible as identifiers within that scope. In practice most implementations of Edition 3 have not implemented this semantics. Edition 5 changes the specified semantics by using a Declarative Environment Record to bind the name of the function.

14: In Edition 3, the algorithm for the production *SourceElements : SourceElements SourceElement* did not correctly propagate statement result values in the same manner as *Block*. This could result in the `eval` function producing an incorrect result when evaluating a *Program* text. In practice most implementations of Edition 3 have implemented the correct propagation rather than what was specified in Edition 5.

15.10.6: `RegExp.prototype` is now a `RegExp` object rather than an instance of `Object`. The value of its `[[Class]]` internal property which is observable using `Object.prototype.toString` is now "RegEx" rather than "Object".

DRAFT

Annex E (informative)

Additions and Changes that Introduce Incompatibilities with Prior Editions

Field Code Changed
Field Code Changed
Field Code Changed
Deleted: in the 5th Edition
Deleted: the 3rd

In the 6th Edition

12.6: In Edition 6, a terminating semi-colon is no longer required at the end of a do-while statement.

12.14: In Edition 6, it is an early error for a *Catch* clause to contain a *var* declaration for the same *Identifier* that appears as the *Catch* clause parameter. In previous editions, such a variable declaration would be instantiated in the enclosing variable environment but the declaration's *Initializer* value would be assigned to the *Catch* parameter.

Deleted:

13.3 In Edition 6, the function objects that are created as the values of the *[[Get]]* or *[[Set]]* attribute of accessor properties in an *ObjectLiteral* are not constructor functions. In Edition 5, they were constructors.

In the 5th Edition

7.1: Unicode format control characters are no longer stripped from ECMAScript source text before processing. In Edition 5, if such a character appears in a *StringLiteral* or *RegularExpressionLiteral* the character will be incorporated into the literal where in Edition 3 the character would not be incorporated into the literal.

7.2: Unicode character <BOM> is now treated as whitespace and its presence in the middle of what appears to be an identifier could result in a syntax error which would not have occurred in Edition 3

7.3: Line terminator characters that are preceded by an escape sequence are now allowed within a string literal token. In Edition 3 a syntax error would have been produced.

7.8.5: Regular expression literals now return a unique object each time the literal is evaluated. This change is detectable by any programs that test the object identity of such literal values or that are sensitive to the shared side effects.

7.8.5: Edition 5 requires early reporting of any possible RegExp constructor errors that would be produced when converting a *RegularExpressionLiteral* to a RegExp object. Prior to Edition 5 implementations were permitted to defer the reporting of such errors until the actual execution time creation of the object.

7.8.5: In Edition 5 unescaped "/" characters may appear as a *CharacterClass* in a regular expression literal. In Edition 3 such a character would have been interpreted as the final character of the literal.

10.4.2: In Edition 5, indirect calls to the *eval* function use the global environment as both the variable environment and lexical environment for the eval code. In Edition 3, the variable and lexical environments of the caller of an indirect *eval* was used as the environments for the eval code.

15.4.4: In Edition 5 all methods of *Array.prototype* are intentionally generic. In Edition 3 *toString* and *toLocaleString* were not generic and would throw a *TypeError* exception if applied to objects that were not instances of Array.

10.6: In Edition 5 the array indexed properties of argument objects that correspond to actual formal parameters are enumerable. In Edition 3, such properties were not enumerable.

10.6: In Edition 5 the value of the *[[Class]]* internal property of an arguments object is "Arguments". In Edition 3, it was "Object". This is observable if *toString* is called as a method of an arguments object.

12.6.4: for-in statements no longer throw a **TypeError** if the `in` expression evaluates to `null` or `undefined`. Instead, the statement behaves as if the value of the expression was an object with no enumerable properties.

15: In Edition 5, the following new properties are defined on built-in objects that exist in Edition 3:

```
Object.getPrototypeOf, Object.getOwnPropertyDescriptor, Object.getOwnPropertyNames,  
Object.create, Object.defineProperty, Object.defineProperties, Object.seal,  
Object.freeze, Object.preventExtensions, Object.isSealed, Object.isFrozen,  
Object.isExtensible, Object.keys, Function.prototype.bind, Array.prototype.indexOf,  
Array.prototype.lastIndexOf, Array.prototype.every, Array.prototype.some,  
Array.prototype.forEach, Array.prototype.map, Array.prototype.filter,  
Array.prototype.reduce, Array.prototype.reduceRight, String.prototype.trim, Date.now,  
Date.prototype.toISOString, Date.prototype.toJSON.
```

15: Implementations are now required to ignore extra arguments to standard built-in methods unless otherwise explicitly specified. In Edition 3 the handling of extra arguments was unspecified and implementations were explicitly allowed to throw a **TypeError** exception.

15.1.1: The value properties `NaN`, `Infinity`, and `undefined` of the Global Object have been changed to be read-only properties.

15.1.2.1: Implementations are no longer permitted to restrict the use of `eval` in ways that are not a direct call. In addition, any invocation of `eval` that is not a direct call uses the global environment as its variable environment rather than the caller's variable environment.

15.1.2.2: The specification of the function `parseInt` no longer allows implementations to treat Strings beginning with a `0` character as octal values.

15.3.4.3: In Edition 3, a **TypeError** is thrown if the second argument passed to `Function.prototype.apply` is neither an array object nor an arguments object. In Edition 5, the second argument may be any kind of generic array-like object that has a valid `length` property.

15.3.4.3, 15.3.4.4: In Edition 3 passing `undefined` or `null` as the first argument to either `Function.prototype.apply` or `Function.prototype.call` causes the global object to be passed to the indirectly invoked target function as the `this` value. If the first argument is a primitive value the result of calling `ToObject` on the primitive value is passed as the `this` value. In Edition 5, these transformations are not performed and the actual first argument value is passed as the `this` value. This difference will normally be unobservable to existing ECMAScript Edition 3 code because a corresponding transformation takes place upon activation of the target function. However, depending upon the implementation, this difference may be observable by host object functions called using `apply` or `call`. In addition, invoking a standard built-in function in this manner with `null` or `undefined` passed as the `this` value will in many cases cause behaviour in Edition 5 implementations that differ from Edition 3 behaviour. In particular, in Edition 5 built-in functions that are specified to actually use the passed `this` value as an object typically throw a **TypeError** exception if passed `null` or `undefined` as the `this` value.

15.3.5.2: In Edition 5, the `prototype` property of Function instances is not enumerable. In Edition 3, this property was enumerable.

15.5.5.2: In Edition 5, the individual characters of a String object's `[[PrimitiveValue]]` may be accessed as array indexed properties of the String object. These properties are non-writable and non-configurable and shadow any inherited properties with the same names. In Edition 3, these properties did not exist and ECMAScript code could dynamically add and remove writable properties with such names and could access inherited properties with such names.

15.9.4.2: `Date.parse` is now required to first attempt to parse its argument as an ISO format string. Programs that use this format but depended upon implementation specific behaviour (including failure) may behave differently.

15.10.2.12: In Edition 5, `\s` now additionally matches <BOM>.

15.10.4.1: In Edition 3, the exact form of the String value of the `source` property of an object created by the `RegExp` constructor is implementation defined. In Edition 5, the String must conform to certain specified requirements and hence may be different from that produced by an Edition 3 implementation.

15.10.6.4: In Edition 3, the result of `RegExp.prototype.toString` need not be derived from the value of the `RegExp` object's `source` property. In Edition 5 the result must be derived from the `source` property in a specified manner and hence may be different from the result produced by an Edition 3 implementation.

15.11.2.1, 15.11.4.3: In Edition 5, if an initial value for the `message` property of an `Error` object is not specified via the `Error` constructor the initial value of the property is the empty String. In Edition 3, such an initial value is implementation defined.

15.11.4.4: In Edition 3, the result of `Error.prototype.toString` is implementation defined. In Edition 5, the result is fully specified and hence may differ from some Edition 3 implementations.

15.12: In Edition 5, the name `JSON` is defined in the global environment. In Edition 3, testing for the presence of that name will show it to be undefined unless it is defined by the program or implementation.

DRAFT

DRAFT

Annex F (informative)

Static Semantic Rule Cross Reference

Routine Name	Purpose	Definitions	Uses
BoundNames	Produces a list of the Identifiers bound by a production. Does not include Identifiers that are bound within inner environments associated with the production.	12.2.1 , 12.2.2 , 12.2.4 , 12.6.4 , 13.1 , 13.2 , 13.5	
ConstructorMethod	From a <i>ClassBody</i> return the first <i>ClassElement</i> whose PropName is "constructor". Returns empty if the <i>ClassBody</i> does not contain one.	13.5	
Contains	Determine if a grammar production either directly or indirectly includes a grammar symbol.	5.3 , 13.1 , 13.2 , 13.5	
CoveredFormalsList	Reparse a covered <i>Expression</i> using <i>FormalsList</i> as the goal symbol.	13.2	
CV	Determines the "character value" of a component of a <i>StringLiteral</i> .	7.8.4	
Elision Width	Determine the number of commas in an <i>Elision</i> .	11.1.4.1	
ExpectedArgumentCount	Determine the "length" of an argument list for the purpose of initializing the "length" property of a function object.	13.1 , 13.2 , 13.3	
HasInitialiser	Determines whether the production contains an <i>Initialiser</i> production.	12.2.4 , 13.1	
IsConstantDeclaration	Determines whether the production introduces a immutable environment record binding.	12.2 , 13.1 , 13.5	
IsInvalidAssignmentPattern	Determines if a <i>LeftHandSideExpression</i> is a valid assignment target. Primarily for dealing with destructuring assignment targets.	11.2	
LexicalDeclarations	Return a List containing the components of a production that are processed as lexical declarations	12.1 , 12.11 , 12.5	
LexicallyDeclaredNames	Returns a list of the lexically scoped identifiers declared by a production.	12.1 , 13.1 , 13.2 , 13.5	
MethodDefinitions	Return a list of the <i>MethodDefinition</i> productions that are part of a <i>ClassElementList</i> .	13.5	
MV	Determines the "mathematical value" of a numeric	7.8.3	

Field Code Changed

Field Code Changed

Field Code Changed

Deleted: Technically Significant Corrections and Clarifications in the 5.1 Edition

Deleted: s

	<u>literal or component of a numeric literal.</u>		
<u>PropName</u>	<u>Determines the string value of the property name referenced by a production.</u>	<u>11.1.5.1, 13.3, 13.5</u>	
<u>PropNameList</u>	<u>Returns a List of the string values of the property names referenced by a production. The list reflects the order of the references in the source text. The list may contain duplicate elements.</u>	<u>11.5.1, 13.5</u>	
<u>ReferencesSuper</u>	<u>Determine if a <i>MethodDefinition</i> contains any references to the ReservedWord super.</u>	<u>13.3</u>	
<u>SpecialMethod</u>	<u>Determine if a <i>MethodDefinition</i> defines a generator method or an accessor property.</u>	<u>13.3</u>	
<u>SV</u>	<u>Determines the "string value" of a <i>StringLiteral</i> or component of a <i>StringLiteral</i>.</u>	<u>7.8.4</u>	
<u>VarDeclaredNames</u>	<u>Returns a list of the local top-level scoped identifiers declared by a production. These are identifier that are scoped as if by a var statement.</u>	<u>12.1, 12.5, 12.6.1, 12.6.2, 12.6.3, 12.6.4, 12.12, 13.1, 13.5</u>	

← Formatted: Heading 1

Scrap Heap

A place to temporarily hand on to stuff that's been deleted

MemberExpression :
MemberExpression <| TriangleLiteral

TriangleLiteral :
SealedArrayLiteral
SealedObjectLiteral
FunctionExpression
ArrowFunction
ValueLiteral

CallExpression :
CallExpression <| TriangleLiteral

15.2.3.15 Object.isObject (O)

When the **isObject** function is called with argument *O*, the following steps are taken:

1. If **Type(O)** is **Object** return **true**.
2. Return **false**.

15.5.4.25 String.prototype.toArray()

The following steps are taken:

1. ReturnIfAbrupt(**CheckObjectCoercible(this value)**).
2. Let *S* be the result of calling **ToString**, giving it the **this** value as its argument.
3. ReturnIfAbrupt(*S*).
4. Let *len* be the number of characters in *S*.
5. Let *array* be the result of the abstract operation **ArrayCreate** (15.4) with argument *len*.
6. Let *n* be 0.
7. Repeat, while *n* < *len*:
 - a. Let *c* be the character at position *n* in *S*.
 - b. Call the **[[DefineOwnProperty]]** internal method of *array* with arguments **ToString(n)**, the **PropertyDescriptor** **{[[Value]]: *c*, [[Writable]]: true, [[Enumerable]]: true, [[Configurable]]: true}**, and **false**.
 - c. Increment *n* by 1.
8. Return *array*.

The **length** property of the **toArray** method is **0**.

NOTE 1 Returns an Array object with elements corresponding to the characters of this object (converted to a String).

NOTE 2 The **toArray** function is intentionally generic; it does not require that its **this** value be a String object. Therefore, it can be transferred to other kinds of objects for use as a method.

DRAFT

Bibliography

- [1] IEEE Std 754-2008: IEEE Standard for Floating-Point Arithmetic. Institute of Electrical and Electronic Engineers, New York (2008)
- [2] The Unicode Consortium. The Unicode Standard, Version 3.0, defined by: The Unicode Standard, Version 3.0 (Reading, MA, Addison-Wesley, 2000. ISBN 0-201-61633-5)
- [3] Unicode Inc. (2010), Unicode Technical Report #15: Unicode Normalization Forms
- [4] ISO 8601:2004(E) *Data elements and interchange formats – Information interchange -- Representation of dates and times*
- [5] RFC 1738 "Uniform Resource Locators (URL)", available at <<http://tools.ietf.org/html/rfc1738>>
- [6] RFC 2396 "Uniform Resource Identifiers (URI): Generic Syntax", available at <<http://tools.ietf.org/html/rfc2396>>
- [7] RFC 3629 "UTF-8, a transformation format of ISO 10646", available at <<http://tools.ietf.org/html/rfc3629>>
- [8] RFC 4627 "The application/json Media Type for JavaScript Object Notation (JSON)" , available at <<http://tools.ietf.org/html/rfc4627>>

DRAFT