

MY PLUG IN

MY PLUG IN

One knob. Exactly as loud as you want.

pedal screenshot goes here

Gain utility for MOD Desktop and MOD Dwarf

USER MANUAL · JULY 2026 EDITION

WHAT MY PLUGIN DOES

My Plugin is a **volume tool**. It takes your mono signal, adjusts its level with a single **GAIN** knob — from a whisper 24 dB quieter to a roar 24 dB louder — and sends it to both sides of a stereo output.

Use it to balance one instrument against another, to push a quiet synth up in front of a band, or as a clean boost anywhere in your chain.

Good to know: gain changes are smoothed, so sweeping the knob while you play never clicks or zippers — even under automation.

QUICK START

1. **Add My Plugin to your pedalboard.** In the MOD web interface, find it under the brand **myplugin** and drag it into your signal chain.
2. **Play.** At the default (noon) the plugin passes your signal through at exactly the level it came in.
3. **Turn GAIN** right to boost, left to cut, until it sits where you want it in the mix.

THE CONTROLS

1 GAIN

How loud the output is compared to the input.

- **Left (-24 dB):** a distant whisper
- **Noon (0 dB, default):** exactly as loud as what comes in
- **Right (+24 dB):** a big, clean boost

Stereo out of a mono pedal? My Plugin sends the same signal to left and right, so it slots cleanly in front of stereo effects like reverb, delay, or chorus.

INSTALLING MY PLUGIN

Download the build for your platform from the plugin's **GitHub Releases** page — each release ships a MOD Desktop bundle (`myplugin-vX.Y.Z-linux-x86_64.tar.gz`) and a MOD Dwarf bundle (`myplugin-vX.Y.Z-dwarf-aarch64.tar.gz`).

MOD Desktop (Linux)

1. Extract the archive: `tar xzf myplugin-vX.Y.Z-linux-x86_64.tar.gz`
2. Move the extracted `myplugin.lv2` folder into `~/Documents/MOD Desktop/lv2/`
3. Restart MOD Desktop. My Plugin appears in the plugin library under the brand **myplugin**.

MOD Dwarf

1. Connect the Dwarf over USB and extract the Dwarf archive on your computer.
2. Copy the bundle onto the unit:

```
scp -0 -r myplugin.lv2 root@192.168.51.1:/root/.lv2/
```

3. Restart the audio services (or simply reboot the Dwarf):

```
ssh root@192.168.51.1 'systemctl restart jack2 mod-ui'
```

4. Hard-refresh the MOD web interface in your browser (**Ctrl-Shift-R**) and drag My Plugin onto a pedalboard.

QUESTIONS & ANSWERS

I hear nothing after installing.

Make sure the pedal is connected on the pedalboard — the input jack on its left, both output jacks on its right — and that GAIN is not fully left. On the Dwarf, restart `jack2` and `mod-ui` (or reboot) after copying the bundle.

Does the boost distort?

My Plugin itself stays clean at any setting, but a big boost can push the *next* pedal — or the output stage — into clipping. If you hear crackling, back GAIN off or lower the level further down the chain.

SPECIFICATIONS

FORMAT	LV2 audio plugin, mono in → stereo out
PLATFORMS	MOD Desktop (Linux x86_64), MOD Dwarf (aarch64)
CONTROLS	Gain: -24 dB ... +24 dB, default 0 dB
LATENCY	None

My Plugin is free software built with the DISTRHO Plugin Framework. Manual edition July 2026 — for the plugin version it shipped with; see the [GitHub release page](#) for the latest.