

Loading & Cleaning Data in R

I know the file exists, why doesn't R?

 [steffilazerte](#)
 @steffilazerte@fosstodon.org
 [@steffilazerte](#)
 [steffilazerte.ca](#)

Dr. Steffi LaZerte 
Analysis and Data Tools for Science

	River	Site	Ele	Amo	Wea
1	Grasse	Up stream	Al	0.605555555555556	sunny
2	Grasse	Mid stream	Al	0.425	snowy
3	Grasse	Down stream	Al	0.194444444444444	wet
4	Oswegatchie	Up stream	Al	1	cloudy
5	Oswegatchie	Mid stream	Al	0.161111111111111	cloudy
6	Oswegatchie	Down stream	Al	0.033333333333333	sunny
7	Raquette	Up stream	Al	0.291666666666667	sunny
8	Raquette	Mid stream	Al	0.038888888888889	cloudy
9	Raquette	Down stream	Al	0	sunny
10	St. Regis	Up stream	Al	0.680555555555556	sunny
11	St. Regis	Mid stream	Al	0.45	snowy
12	St. Regis	Down stream	Al	0.286111111111111	cloudy
13	Grasse	Up stream	Ba	0.505283381364073	wet
14	Grasse	Mid stream	Ba	0.564841498559078	snowy
15	Grasse	Down stream	Ba	0.523535062439962	cloudy
16	Oswegatchie	Up stream	Ba	0.357348703170029	snowy
17	Oswegatchie	Mid stream	Ba	0.560038424591739	sunny
18	Oswegatchie	Down stream	Ba	1	wet
19	Raquette	Up stream	Ba	0	cloudy
20	Raquette	Mid stream	Ba	0.22478386167147	sunny
21	Raquette	Dow stream	Ba	0.364073006724304	cloudy
22	St. Regis	Up stream	Ba	0.379442843419789	wet
23	St. Regis	Mid stream	Ba	0.296829971181556	snowy
24	St. Regis	Down stream	Ba	0.577329490874159	snowy
25	Grasse	Up stream	Br	0.107142857142857	snowy

Compiled: 2024-02-21

First things first

 Save previous script

 Open New File

(make sure you're in the RStudio Project)

 Write `library(tidyverse)` at the top

 Save this new script

(consider names like `cleaning.R` or `3_loading_and_cleaning.R`)

Side Note

R base vs. tidyverse

R base vs. tidyverse

R base

- Basic R
- Packages are installed and loaded by default
- Base pipe `|>*`



tidyverse

- Collection of 'new' packages developed by a team closely affiliated with RStudio
 - e.g., `ggplot2`, `dplyr`, `tidyr`, `readr`
 - Packages designed to work well together
- Use a slightly different syntax
- tidyverse pipe `%>%` or base pipe `|>*`



Useful to know if functions
are
tidyverse or R base

Dealing with data

1. Loading data

- Get your data into R

2. Looking for problems

- Typos
- Incorrectly loaded data

3. Fixing problems

- Corrections
- Renaming

4. Setting formats

- Dates
- Numbers
- Factors

5. Saving your data

Loading Data

Data types: What kind of data do you have?

Specific program files

Type	Extension	R Package	R function
Excel	.xls, .xlsx	<code>readxl*</code>	<code>read_excel()</code>
Open Document	.ods	<code>readODS</code>	<code>read_ods()</code>
SPSS	.sav, .zsav, .por	<code>haven</code>	<code>read_spss()</code>
SAS	.sas7bdat	<code>haven</code>	<code>read_sas()</code>
Stata	.dta	<code>haven</code>	<code>read_dta()</code>
Database Files	.dbf	<code>foreign</code>	<code>read.dbf()</code>



Convenient but...

- Can be unreliable
- Can take longer

For files that don't change, better to save as
a `*.CSV`

(Comma-separated-variables file)

Data types: What kind of data do you have?

General text files

Type	R base	readr package *
Comma separated	<code>read.csv()</code>	<code>read_csv()</code> , <code>read_csv2()</code>
Tab separated	<code>read.delim()</code>	<code>read_tsv()</code>
Space separated	<code>read.table()</code>	<code>read_table()</code>
Fixed-width	<code>read.fwf()</code>	<code>read_fwf()</code>



- **readr** package especially useful for big data sets (fast!)
- Error/warnings from **readr** are a bit more helpful

We'll focus on

- **readxl** package → `read_excel()`

Where is my data?

Common error

```
1 my_data <- read_csv("weather.csv")
```

```
Error: 'weather.csv' does not exist in current working directory ('/home/steffi/Projects/Workshops/workshop-dealing-with-data').
```

With no folder (just file name) R expects file to be in **Working directory**

Working directory is:

- Where your RStudio project is
- Your home directory (My Documents, etc.) [If not using RStudio Projects]
- Where you've set it (using `setwd()` or RStudio's Session > Set Working Directory)

Don't use `setwd()`

Do use Projects in RStudio

Where is my data?

A note on file paths (file locations)

```
1 /home
```

- folders separated by /
- `home` is a folder

Where is my data?

A note on file paths (file locations)

```
1 /home/steffi/
```


- folders separated by /
- `home` and `steffi` are folders
- `steffi` is a folder inside of `home`

Where is my data?

A note on file paths (file locations)

```
1 /home/steffi/Documents/R Projects/mydata.csv
```

- folders separated by /
- `home`, `steffi`, `Documents`, `R Projects` are folders
- `steffi` is inside of `home`, `Documents` is inside of `steffi`, etc.
- `mydata.csv` is a data file inside `R Projects` folder



RStudio Files Pane

Where is my data?

Absolute Paths

OS	Path
LINUX	/home/steffi/Documents/R Projects/mydata.csv
WINDOWS	C:/Users/steffi/My Documents/R Projects/mydata.csv
MAC	/users/steffi/Documents/R Projects/mydata.csv

Full location, folders and filename

Relative Paths

Path	Where to look
mydata.csv	Here (current directory)
../mydata.csv	Go up one directory (../)
data/mydata.csv	Stay here, go into “data” folder (data/)
../data/mydata.csv	Go up one directory (../), then into “data” folder (data/)

Only *relative* info
Use relative symbols (e.g.,
../)

Keep yourself organized

For simple projects

- Create an 'RStudio Project' for each Project
- Create a specific "data" folder within each project (one per project)

```
1 - Prospect Lake Quality          # Project Folder
2   - prospect_analysis.R
3   - data                          # Data Folder
4       - prospect_data_2017-01-01.csv
5       - prospect_data_2017-02-01.csv
```

- Use **relative** paths to refer to this folder

```
1 d <- read_csv("data/prospect_data_2017-01-01.csv")
```

Let's Load Some Data!

Your turn: Load some data


1. Create a 'data' folder in your RStudio project
2. Put `rivers_correct.xlsx` file in the "data" folder
3. Load the package

```
1 library(readxl)
```


4. Read in the Excel file and assign to object `rivers`

```
1 rivers <- read_excel("data/rivers_correct.xlsx")
```

5. Use `head()` and `tail()` functions to look at the data
e.g., `head(rivers)` and `tail(rivers)`
6. Click on the `rivers` object in your "Environment" pane to look at the whole data set



Click on "New Folder"



Use the 'tab' key in RStudio when typing in the file name for auto-complete

How do I know which function to use?

Program-specific files

- Files which only normally open in a particular program (e.g., Excel)
- Load with function from specific package (e.g. `read_excel` from readxl package)

Text files

- Files which open in notepad
- Files which open in RStudio when you click on them in the Files Pane
- Load with function from readr package (e.g. `read_csv()`, `read_tsv()`, etc.)

Look at the file extension:

- `rivers_correct.xlsx` → Excel file → `read_excel()`
- `rivers_raw.csv` → Comma-separated-variables → `read_csv()`

But sometimes not clear...

How do I know which function to use?

Look at the file: `master_moch.txt`

- Put this file in your `data` folder
- In lower right-hand pane, click on **Files**
 - Click on `data` folder
 - Click on `master_moch.txt`
 - Click “View File” (if asked)

ID	region	hab	freq	freq.sd	p.notes
MCB02	kam	0.5266879074	3.9806600009	3.9806600009	0.4592592593
MCB03	kam	-0.9707703735	4.1090031783	4.1090031783	0.5
MCB04	kam	-0.9707703735	4.2463067674	4.2463067674	0.5151515152

This **does not** read the file into R, but only shows you the contents as text.

How do I know which function to use?

Peak:

- Pick a read function with your best guess (`read_csv()` is a good start)
- Use `n_max` to read only first few rows

```
1 read_csv("data/master_moch.txt", n_max = 3)

# A tibble: 3 × 1
  `ID\tregion\thab\tfreq\tfreq.sd\tp.notes`
  <chr>
1 "MCB02\tkam\t0.5266879074\t3.9806600009\t3.9806600009\t0.4592592593"
2 "MCB03\tkam\t-0.9707703735\t4.1090031783\t4.1090031783\t0.5"
3 "MCB04\tkam\t-0.9707703735\t4.2463067674\t4.2463067674\t0.5151515152"
```

`\t` means tab, so this is tab-separated data

How do I know what to use?

Peak:

- Try again with `read_tsv()`

```
1 read_tsv("data/master_moch.txt", n_max = 3) # note change in function!
```

```
# A tibble: 3 × 6
  ID      region    hab  freq freq.sd p.notes
<chr> <chr>    <dbl> <dbl>   <dbl>   <dbl>
1 MCB02 kam      0.527  3.98    3.98    0.459
2 MCB03 kam     -0.971  4.11    4.11    0.5
3 MCB04 kam     -0.971  4.25    4.25    0.515
```

Excellent!

Specifics of loading functions

col_names

- Geolocator data

```
1 my_data <- read_csv("data/geolocators.csv")
2 my_data

# A tibble: 20 × 2
#   `02/05/11 22:29:59` `64`
#   <chr>              <dbl>
1 02/05/11 22:31:59    64
2 02/05/11 22:33:59    38
3 02/05/11 22:35:59    38
4 02/05/11 22:37:59    34
5 02/05/11 22:39:59    30
6 02/05/11 22:41:59    34
7 02/05/11 22:43:59    40
8 02/05/11 22:45:59    46
9 02/05/11 22:47:59    48
10 02/05/11 22:49:59    46
# i 10 more rows
```

- `read_csv`, `read_tsv`, etc. assume that the first row contains the column names
- This file doesn't have headers

Oops?

col_names

- Geolocator data

Declare no headings

```
1 my_data <- read_csv("data/geolocators.csv",
2                       col_names = FALSE)
3 my_data
```

```
# A tibble: 21 × 2
  X1                X2
  <chr>            <dbl>
1 02/05/11 22:29:59    64
2 02/05/11 22:31:59    64
3 02/05/11 22:33:59    38
4 02/05/11 22:35:59    38
5 02/05/11 22:37:59    34
6 02/05/11 22:39:59    30
7 02/05/11 22:41:59    34
8 02/05/11 22:43:59    40
9 02/05/11 22:45:59    46
10 02/05/11 22:47:59    48
# i 11 more rows
```

Name headings

```
1 my_data <- read_csv("data/geolocators.csv",
2                       col_names = c("date", "light"))
3 my_data
```

```
# A tibble: 21 × 2
  date                light
  <chr>            <dbl>
1 02/05/11 22:29:59    64
2 02/05/11 22:31:59    64
3 02/05/11 22:33:59    38
4 02/05/11 22:35:59    38
5 02/05/11 22:37:59    34
6 02/05/11 22:39:59    30
7 02/05/11 22:41:59    34
8 02/05/11 22:43:59    40
9 02/05/11 22:45:59    46
10 02/05/11 22:47:59    48
# i 11 more rows
```

skip info rows before data

- Grain size data

```
1 my_data <- read_tsv("data/grain_size.txt")
2 my_data
```

```
# A tibble: 36 × 7
  `DATA DOWNLOAD: 2015-09-23` ...2 ...3 ...4 ...5 ...6 ...7
  <chr> <chr> <chr> <chr> <chr> <chr> <chr>
1 SYSTEM 001 <NA> <NA> <NA> <NA> <NA> <NA>
2 LOGGER X <NA> <NA> <NA> <NA> <NA> <NA> <NA>
3 lab_num CSP sample_num depth_lb csa msa fsa
4 3177 CSP01 CSP01-P-1-1 4 13.04 17.37 8.19
5 3178 CSP01 CSP01-P-1-2 12 10.74 16.9 7.92
6 3179 CSP01 CSP01-P-1-3 35 12.11 17.75 6.99
7 3180 CSP01 CSP01-P-1-4 53 17.61 18.16 6.29
8 3181 CSP01 CSP01-P-1-5 83 21.05 18.38 6.26
9 3182 CSP01 CSP01-P-1-6 105 19.02 18.43 6.28
10 3183 CSP08 CSP08-P-1-1 10 11.6 17.14 8.18
# i 26 more rows
```


skip info rows before data

- Grain size data

```
1 my_data <- read_tsv("data/grain_size.txt")
2 my_data
```

Look at the file:

- Click on **Files** tab
- Click on **data** folder
- Click on **grain_size.txt**
- Click “**View file**” (if asked)

```
DATA DOWNLOAD: 2015-09-23
SYSTEM 001
LOGGER X
lab_num CSP sample_num depth_lb csa msa fsa
3177 CSP01 CSP01-P-1-1 4 13.04 17.37 8.19
3178 CSP01 CSP01-P-1-2 12 10.74 16.9 7.92
3179 CSP01 CSP01-P-1-3 35 12.11 17.75 6.99
3180 CSP01 CSP01-P-1-4 53 17.61 18.16 6.29
3181 CSP01 CSP01-P-1-5 83 21.05 18.38 6.26
```

Ah ha!

Metadata was stored at the top of the file

skip info rows before data

- Grain size data
- Add `skip = 3` to skip the first three rows

```
1 my_data <- read_tsv("data/grain_size.txt", skip = 3)
2 my_data
```

```
# A tibble: 33 × 7
  lab_num CSP sample_num depth_lb csa msa fsa
  <dbl> <chr> <chr>      <dbl> <dbl> <dbl> <dbl>
1    3177 CSP01 CSP01-P-1-1         4 13.0 17.4  8.19
2    3178 CSP01 CSP01-P-1-2        12 10.7 16.9  7.92
3    3179 CSP01 CSP01-P-1-3        35 12.1 17.8  6.99
4    3180 CSP01 CSP01-P-1-4        53 17.6 18.2  6.29
5    3181 CSP01 CSP01-P-1-5        83 21.0 18.4  6.26
6    3182 CSP01 CSP01-P-1-6       105 19.0 18.4  6.28
7    3183 CSP08 CSP08-P-1-1        10 11.6 17.1  8.18
8    3184 CSP08 CSP08-P-1-2        27 15.4 16.2  6.76
9    3185 CSP08 CSP08-P-1-3        90 14.9 15.8  7.12
10   3186 CSP02 CSP02-P-1-1         5  8.75  8.64  3.41
# i 23 more rows
```

Much better!

Your turn: Load this data set

Load the telemetry data set: `Sta A Data 2006-11-07.dmp`

1. Look at the file
2. Decide which R function to use based on delimiter (comma, space, or tab?)
3. Any other options need to be specified?

It should look like this:

```
# A tibble: 19 × 7
  StartDate Time      Frequency `Rate/Temp`   Pwr Ant      SD
    <dbl> <time>      <dbl>      <dbl> <dbl> <chr> <dbl>
1   39022 17:15:36    150.      34.8   175 M0      0
2   39022 17:19:14    148.      19.2    72 M0      0
3   39022 17:19:25    148.      19.7   194 M1      0
4   39022 17:20:04    149.      33.8   104 M0      0
5   39022 17:20:17    149.      33.7   152 M1      0
6   39022 17:20:57    150.      34.2   188 M0      0
7   39022 17:22:50    148.       9.8   188 M0      0
# i 12 more rows
```

Too Easy?

Load some of your own tricky data

OR

Try to load the second sheet of `rivers_correct.xlsx` and

Looking for problems

Look at the data

- Make sure columns as expected (correctly assigned file format)
- Make sure no extra lines above the data (should we have used a skip?)
- Make sure column names look appropriate

```
1 library(palmerpenguins)
2 penguins

# A tibble: 344 × 8
  species island bill_length_mm bill_depth_mm flipper_length_mm body_mass_g sex    year
  <fct>   <fct>         <dbl>         <dbl>         <int>         <int> <fct> <int>
1 Adelie  Torgersen      39.1           18.7           181           3750 male   2007
2 Adelie  Torgersen      39.5           17.4           186           3800 female 2007
3 Adelie  Torgersen      40.3            18           195           3250 female 2007
4 Adelie  Torgersen      NA             NA             NA             NA <NA>   2007
5 Adelie  Torgersen      36.7           19.3           193           3450 female 2007
6 Adelie  Torgersen      39.3           20.6           190           3650 male   2007
7 Adelie  Torgersen      38.9           17.8           181           3625 female 2007
8 Adelie  Torgersen      39.2           19.6           195           4675 male   2007
9 Adelie  Torgersen      34.1           18.1           193           3475 <NA>   2007
10 Adelie Torgersen      42            20.2           190           4250 <NA>   2007
# i 334 more rows
```

Look at the data

- Did the whole data set load?
- Are there extra blank lines at the end of the data?

```
1 tail(penguins)
```

```
# A tibble: 6 × 8
```

	species	island	bill_length_mm	bill_depth_mm	flipper_length_mm	body_mass_g	sex	year
	<fct>	<fct>	<dbl>	<dbl>	<int>	<int>	<fct>	<int>
1	Chinstrap	Dream	45.7	17	195	3650	female	2009
2	Chinstrap	Dream	55.8	19.8	207	4000	male	2009
3	Chinstrap	Dream	43.5	18.1	202	3400	female	2009
4	Chinstrap	Dream	49.6	18.2	193	3775	male	2009
5	Chinstrap	Dream	50.8	19	210	4100	male	2009
6	Chinstrap	Dream	50.2	18.7	198	3775	female	2009

skim() the data

skim() is from skimr

- Are the formats correct?
 - numbers (**numeric**),
 - text (**character**)
 - date (**date**, **POSIXct**, **datetime**)
 - categories (**factor**)
- Are values appropriate?
 - Should there be **NAs**?
- Are there any typos?
- Number of rows expected?



```
1 library(skimr)
2 skim(penguins)
```

```
— Data Summary —
Name                Values
Number of rows      344
Number of columns    8






Column type frequency:
  factor              3
  numeric             5

Group variables      None

— Variable type: factor
```

	skim_variable	n_missing	complete_rate	ordered	n_unique	top_counts
1	species	0	1	FALSE	3	Ade: 152, Gen: 124, Chi: 68
2	island	0	1	FALSE	3	Bis: 168, Dre: 124, Tor: 52
3	sex	11	0.968	FALSE	2	mal: 168, fem: 165

```
— Variable type: numeric
```

	skim_variable	n_missing	complete_rate	mean	sd	p0	p25	p50	p75	p100	hist
1	bill_length_mm	2	0.994	43.9	5.46	32.1	39.2	44.4	48.5	59.6	
2	bill_depth_mm	2	0.994	17.2	1.97	13.1	15.6	17.3	18.7	21.5	
3	flipper_length_mm	2	0.994	201.	14.1	172	190	197	213	231	
4	body_mass_g	2	0.994	4202.	802.	2700	3550	4050	4750	6300	
5	year	0	1	2008.	0.818	2007	2007	2008	2009	2009	

count () categories

count () is from dplyr*

- Check for sample sizes and potential typos in categorical columns
- Assess missing values



```
1 count(penguins, species)
```

```
# A tibble: 3 × 2
  species      n
  <fct>    <int>
1 Adelie   152
2 Chinstrap 68
3 Gentoo  124
```

```
1 count(penguins, island)
```





```
# A tibble: 3 × 2
  island      n
  <fct>    <int>
1 Biscoe   168
2 Dream   124
3 Torgersen 52
```

```
1 count(penguins, sex)
```

```
# A tibble: 3 × 2
  sex      n
  <fct> <int>
1 female 165
2 male   168
3 <NA>    11
```







Plot categories

```
1 ggplot(data = penguins, aes(x = COLUMN)) +  
2   geom_bar()
```



Plot numbers

```
1 ggplot(data = penguins, aes(x = COLUMN)) +  
2   geom_histogram() ()
```



Example of problematic data

`rivers_raw.csv`

Look at the data

```
1 rivers <- read_csv("data/rivers_raw.csv")
2 rivers
```

```
# A tibble: 300 × 7
  `River Name` Site      Ele      Amo `Temperature C°` Year Wea
  <chr>         <chr>    <chr>    <dbl>    <dbl> <dbl> <chr>
1 Grasse       Up stream Al      0.606    10.9   2019 sunny
2 Grasse       Mid stream Al      0.425     8.68   2020 sunny
3 Grase        Down stream Al      0.194     8.75   2021 sunny
4 Oswegatchie Up stream  Al      1         0.791   2022 snowy
5 Oswegatchie Mid stream Al      0.161     9.32   2023 sunny
6 Oswegatchie Down stream Al      0.0333    10.6   2019 wet
7 Raquette     Up stream  Al      0.292     4.01   2020 cloudy
8 Raquette     Mid stream Al      0.0389     5.96   2021 wet
9 Raquette     Down stream Al      NA         6.21   2022 wet
10 St. Regis   Up stream  Al      0.681     8.02   2023 cloudy
# i 290 more rows
```

- Column names are not R-friendly (**R**iver **N**ame and **T**emperature **C°**) or obvious (what is **E**le?)
- At least one typo in River (**G**rase should be **G**rasse)

Looking for problems

Your Turn!

```
1 rivers <- read_csv("data/rivers_raw.csv")
2 rivers
```

A tibble: 300 × 7

	`River Name` <chr>	Site <chr>	Ele <chr>	Amo <dbl>	`Temperature C°` <dbl>	Year <dbl>	Wea <chr>
1	Grasse	Up stream	Al	0.606	10.9	2019	sunny
2	Grasse	Mid stream	Al	0.425	8.68	2020	sunny
3	Grase	Down stream	Al	0.194	8.75	2021	sunny
4	Oswegatchie	Up stream	Al	1	0.791	2022	snowy
5	Oswegatchie	Mid stream	Al	0.161	9.32	2023	sunny
6	Oswegatchie	Down stream	Al	0.0333	10.6	2019	wet
7	Raquette	Up stream	Al	0.292	4.01	2020	cloudy
8	Raquette	Mid stream	Al	0.0389	5.96	2021	wet
9	Raquette	Down stream	Al	NA	6.21	2022	wet
10	St. Regis	Up stream	Al	0.681	8.02	2023	cloudy

i 290 more rows

- `skim()` the data
- `count()` some columns
- Perhaps make some `ggplot()`s

Find any problems?

Fixing problems

Cleaning column names




`clean_names()` is from **janitor***

```
1 library(janitor)
2 rivers <- clean_names(rivers)
3 rivers

1 # A tibble: 300 × 7
2   river_name site      ele      amo temperature_c year wea
3   <chr>      <chr>    <chr>    <dbl>      <dbl> <dbl> <chr>
4 1 Grasse    Up stream  Al      0.606      10.9    2019 sunny
5 2 Grasse    Mid stream Al      0.425      8.68    2020 sunny
6 3 Grasse    Down stream Al      0.194      8.75    2021 sunny
7 4 Oswegatchie Up stream  Al      1          0.791    2022 snowy
8 5 Oswegatchie Mid stream Al      0.161      9.32    2023 sunny
9 6 Oswegatchie Down stream Al      0.0333    10.6    2019 wet
10 7 Raquette   Up stream  Al      0.292      4.01    2020 cloudy
11 8 Raquette   Mid stream Al      0.0389      5.96    2021 wet
12 9 Raquette   Down stream Al      NA        6.21    2022 wet
13 10 St. Regis Up stream  Al      0.681      8.02    2023 cloudy
14 # i 290 more rows
```


Side Note: Naming conventions

in that case...



Side Note: Naming conventions

failed programming cases



@allison-horst

Cleaning column names

`rename()` is from **dplyr***

`rename()` columns



```
1 rivers <- rename(rivers, element = ele, amount = amo, temperature = temperature_c)
2 rivers
```

```
# A tibble: 300 × 7
  river_name site      element amount temperature year wea
  <chr>      <chr>      <chr>      <dbl>      <dbl> <dbl> <chr>
1 Grasse    Up stream    Al          0.606      10.9    2019 sunny
2 Grasse    Mid stream  Al          0.425       8.68    2020 sunny
3 Grasse    Down stream Al          0.194       8.75    2021 sunny
4 Oswegatchie Up stream  Al           1          0.791    2022 snowy
5 Oswegatchie Mid stream  Al          0.161       9.32    2023 sunny
6 Oswegatchie Down stream Al          0.0333     10.6    2019 wet
7 Raquette  Up stream    Al          0.292       4.01    2020 cloudy
8 Raquette  Mid stream    Al          0.0389       5.96    2021 wet
9 Raquette  Down stream  Al          NA          6.21    2022 wet
10 St. Regis Up stream    Al          0.681       8.02    2023 cloudy
# i 290 more rows
```

Subsetting columns



`select()` is from **dplyr***

`select()` columns you want

```
1 rivers <- select(rivers, river_name, site, element, amount)
```

OR, `unselect()` columns you don't want

```
1 rivers <- select(rivers, -wea)
2 rivers
```

```
# A tibble: 300 × 6
  river_name site      element amount temperature year
  <chr>      <chr>      <chr>      <dbl>      <dbl> <dbl>
1 Grasse    Up stream    Al         0.606      10.9  2019
2 Grasse    Mid stream   Al         0.425       8.68  2020
3 Grasse    Down stream  Al         0.194       8.75  2021
4 Oswegatchie Up stream    Al          1         0.791  2022
5 Oswegatchie Mid stream   Al         0.161       9.32  2023
6 Oswegatchie Down stream  Al         0.0333     10.6  2019
7 Raquette  Up stream    Al         0.292       4.01  2020
8 Raquette  Mid stream   Al         0.0389       5.96  2021
9 Raquette  Down stream  Al          NA         6.21  2022
10 St. Regis Up stream    Al         0.681       8.02  2023
# i 290 more rows
```

Cleaning columns

Put it all together

```
1 rivers <- read_csv("data/rivers_raw.csv")
2 rivers <- clean_names(rivers)
3 rivers <- rename(rivers, element = ele, amount = amo, temperature = temperature_c)
4 rivers <- select(rivers, -wea)
5 rivers
```

```
# A tibble: 300 × 6
  river_name site      element amount temperature year
  <chr>      <chr>      <chr>      <dbl>      <dbl> <dbl>
1 Grasse    Up stream    Al         0.606      10.9  2019
2 Grasse    Mid stream   Al         0.425      8.68  2020
3 Grasse    Down stream  Al         0.194      8.75  2021
4 Oswegatchie Up stream    Al         1          0.791  2022
5 Oswegatchie Mid stream   Al         0.161      9.32  2023
6 Oswegatchie Down stream  Al         0.0333     10.6  2019
7 Raquette  Up stream    Al         0.292      4.01  2020
8 Raquette  Mid stream   Al         0.0389      5.96  2021
9 Raquette  Down stream  Al         NA         6.21  2022
10 St. Regis Up stream    Al         0.681      8.02  2023
# i 290 more rows
```

Fixing typos

Remember the typos...

```
1 count(rivers, river_name)
```

```
# A tibble: 7 × 2
```

	river_name	n
	<chr>	<int>
1	Grase	1
2	Grasse	73
3	Oswegatchie	75
4	Raquette	74
5	St. Regis	75
6	grasse	1
7	raquette	1

Fixing typos

Replace typos

Combine the `if_else` function with the `mutate()` function

```
1 rivers <- mutate(rivers, river_name = if_else(river_name == "Grase", "Grasse", river_name))
```

Check that it's gone:

```
1 count(rivers, river_name)
```

```
# A tibble: 6 × 2
  river_name      n
  <chr>         <int>
1 Grasse         74
2 Oswegatchie    75
3 Raquette       74
4 St. Regis      75
5 grasse         1
6 raquette       1
```

Fixing typos



if_else() and **mutate()** from **dplyr** package*

mutate() creates or changes columns in a data frame:

```
1 mutate(dataframe, column = new_values)
```

if_else() tests for a condition, and returns one value if **FALSE** and another if **TRUE**

```
1 if_else(condition, value_if_true, value_if_false)
```

Iterative process

- Make some corrections
- Check the data
- Make some more corrections (either add to or modify existing code)



Many corrections?

Try `case_when()` from `dplyr` package*

`case_when()` tests for multiple conditions, and returns different values depending

```
1 case_when(condition1 ~ value_if_true1,  
2           condition2 ~ value_if_true2,  
3           condition3 ~ value_if_true3,  
4           TRUE ~ default_value)
```


Your Turn: Fix another “Grasse” typo

1. Check the data with `count()`
2. Use `mutate()` and `if_else()` to fix the typo

```
1 rivers <- read_csv("data/rivers_raw.csv")
2 rivers <- clean_names(rivers)
3 rivers <- rename(rivers, element = ele, amount = amo, temperature = temperature_c)
4 rivers <- select(rivers, -wea)
5 rivers <- mutate(rivers, river_name = if_else(river_name == "Grase", "Grasse", river_name))
6
7 rivers <- mutate(???, ??? = ???)
```

Too Easy?

Examine and fix problems in your own data

OR

Use `case_when()` to fix all the river name typos at once...

Tangent: tidyverse functions

tidyverse functions



`rename()`, `select()`, `mutate()`

- `tidyverse` functions always start with the **data**, followed by other arguments
- you can reference any **column** from '**data**'

```
1 rivers <- read_csv("data/rivers_raw.csv")
2 rivers <- clean_names(rivers)
3 rivers <- rename(rivers, element = ele, amount = amo, temperature = temperature_c)
4 rivers <- select(rivers, -wea)
5 rivers <- mutate(rivers, river_name = if_else(river_name %in% c("Grase", "grasse"), "Grasse", river_name))
```

- `rename()` changes column names
- `select()` chooses columns to keep or to remove (with -)
- `mutate()` changes column contents

Why use tidyverse functions?



Pipes! `|>*` Allow you to string commands together

Instead of:

```
1 rivers <- read_csv("data/rivers_raw.csv")
2 rivers <- clean_names(rivers)
3 rivers <- rename(rivers, element = ele, amount = amo, temperature = temperature_c)
4 rivers <- select(rivers, -wea)
5 rivers <- mutate(rivers,
6                   river_name = case_when(river_name %in% c("Grase", "grasse") ~ "Grasse",
7                                         river_name == "raquette" ~ "Raquette",
8                                         TRUE ~ river_name))
```

We have:

```
1 rivers <- read_csv("data/rivers_raw.csv") |>
2   clean_names() |>
3   rename(element = ele, amount = amo, temperature = temperature_c) |>
4   select(-wea) |>
5   mutate(river_name = case_when(river_name %in% c("Grase", "grasse") ~ "Grasse",
6                                 river_name == "raquette" ~ "Raquette",
7                                 TRUE ~ river_name))
```

Play around

Take a moment to play with this code in your console

Convert this:

```
1 rivers <- read_csv("data/rivers_raw.csv")
2 rivers <- clean_names(rivers)
3 rivers <- rename(rivers, element = ele, amount = amo, temperature = temperature_c)
4 rivers <- select(rivers, -wea)
5 rivers <- mutate(rivers,
6                   river_name = case_when(river_name %in% c("Grase", "grasse") ~ "Grasse",
7                                           river_name == "raquette" ~ "Raquette",
8                                           TRUE ~ river_name))
```



To this:

```
1 rivers <- read_csv("data/rivers_raw.csv") |>
2   clean_names() |>
3   rename(element = ele, amount = amo, temperature = temperature_c) |>
4   select(-wea) |>
5   mutate(river_name = case_when(river_name %in% c("Grase", "grasse") ~ "Grasse",
6                                   river_name == "raquette" ~ "Raquette",
7                                   TRUE ~ river_name))
```

Dealing with NAs

Data that *is* missing

Data that *should* be missing

Exploring NAs

- We saw missing values in `amount`
- Use `filter()` to take a closer look

```
1 filter(rivers, is.na(amount))
```

```
# A tibble: 39 × 6
  river_name site      element amount temperature year
  <chr>      <chr>      <chr>    <dbl>         <dbl> <dbl>
1 Raquette  Down stream Al         NA          6.21  2022
2 Raquette  Up stream  Ba         NA          5.23  2022
3 Raquette  Up stream  Br         NA         -99    2019
4 Oswegatchie Up stream  Ca         NA          4.76  2023
5 Raquette  Down stream Ce         NA         13.9   2020
6 Grasse    Up stream  Cu         NA          9.13  2019
7 Raquette  Down stream Dy         NA          4.98  2019
8 Raquette  Down stream Er         NA          3.07  2021
9 Raquette  Down stream Fe         NA          7.20  2023
10 Raquette Down stream Gd         NA          4.73  2020
# i 29 more rows
```

Omitting NAs

`drop_na()` is from **tidyr***



Omit **NAs** from the **amount** column only (drop those rows)

```
1 rivers_no_na <- drop_na(rivers, amount)
```

Omit **all NAs** from **all** columns (drop those rows)

```
1 rivers_no_na <- drop_na(rivers)
```

Check...

```
1 filter(rivers_no_na, is.na(amount))
```

```
# A tibble: 0 × 6
```

```
# i 6 variables: river_name <chr>, site <chr>, element <chr>, amount <dbl>, temperature <dbl>, year <dbl>
```

```
1 nrow(rivers_no_na)
```

```
[1] 261
```


Side Note: `filter()` also omits NAs 🤯

If we filter by the column with NAs, they are silently dropped

```
1 filter(rivers, amount < 0.05)

# A tibble: 15 × 6
  river_name site      element amount temperature year
  <chr>      <chr>      <chr>    <dbl>      <dbl> <dbl>
1 Oswegatchie Down stream Al      0.0333      10.6  2019
2 Raquette   Mid stream  Al      0.0389       5.96  2021
3 Grasse     Mid stream  Br      0.0357      12.4  2019
4 St. Regis  Up stream   Br      0.0357       3.52  2022
5 St. Regis  Mid stream  Br      0.0357      0.936  2023
6 Raquette   Mid stream  Ce      0.0116       6.61  2019
7 Raquette   Mid stream  Fe      0.00656     10.8  2022
8 Grasse     Up stream   K       0.0313       3.61  2021
9 Raquette   Mid stream  La      0.0275       2.50  2020
10 Oswegatchie Down stream Mn      0.00672      8.89  2019
# i 5 more rows
```

We need to be explicit if we want to keep them

```
1 filter(rivers, amount < 0.05 | is.na(amount))

# A tibble: 54 × 6
  river_name site      element amount temperature year
  <chr>      <chr>      <chr>    <dbl>      <dbl> <dbl>
1 Oswegatchie Down stream Al      0.0333      10.6  2019
2 Raquette   Mid stream  Al      0.0389       5.96  2021
3 Raquette   Down stream Al      NA          6.21  2022
4 Raquette   Up stream   Ba      NA          5.23  2022
5 Grasse     Mid stream  Br      0.0357      12.4  2019
6 Raquette   Up stream   Br      NA        -99    2019
7 St. Regis  Up stream   Br      0.0357       3.52  2022
8 St. Regis  Mid stream  Br      0.0357      0.936  2023
9 Oswegatchie Up stream   Ca      NA          4.76  2023
10 Raquette   Mid stream  Ce      0.0116       6.61  2019
# i 44 more rows
```

Replacing NAs

`replace_na()` is from **tidyr***

```
1 rivers_no_na <- mutate(rivers, amount = replace_na(amount, 0))
```

Check...

```
1 filter(rivers_no_na, is.na(amount))
```

```
# A tibble: 0 × 6
```

```
# i 6 variables: river_name <chr>, site <chr>, element <chr>, amount <dbl>, temperature <dbl>, year <dbl>
```

```
1 nrow(rivers_no_na)
```

```
[1] 300
```

No more NAs!

(If you want to do a more complex replacement, you'll have to use `case_when()` like we did for typos.)



Converting to NA

Remember the problem with `temperature`?



```
1 filter(rivers, temperature < -10)
```

A tibble: 3 × 6

	river_name	site	element	amount	temperature	year
	<chr>	<chr>	<chr>	<dbl>	<dbl>	<dbl>
1	Raquette	Up stream	Br	NA	-99	2019
2	Oswegatchie	Mid stream	K	0.426	-99	2020
3	St. Regis	Mid stream	La	0.367	-99	2023

`na_if()` is from `dplyr`*

```
1 rivers <- mutate(rivers, temperature = na_if(temperature, -99))
```

Check...

```
1 filter(rivers, is.na(temperature))
```

A tibble: 3 × 6

	river_name	site	element	amount	temperature	year
	<chr>	<chr>	<chr>	<dbl>	<dbl>	<dbl>
1	Raquette	Up stream	Br	NA	NA	2019
2	Oswegatchie	Mid stream	K	0.426	NA	2020
3	St. Regis	Mid stream	La	0.367	NA	2023

Fixing formats

Changing classes

Function	Input	Output
<code>as.character()</code>	Any vector	Text (Characters)
<code>as.numeric()</code>	Any vector (but returns NAs if not numbers)	Numbers
<code>as.logical()</code>	TRUE, FALSE, T, F, 0 (FALSE), any other number (all TRUE)	TRUE or FALSE
<code>as.factor()</code>	Any vector	Categories

Your turn, try the following. We'll deal with dates and times later...

```
1 a <- c("hi", "hello", "bonjour")
```

```
1 as.character(a)
2 as.numeric(a)
3 as.logical(a)
4 as.factor(a)
```

```
1 b <- c(1, 0, 20)
```

```
1 as.character(b)
2 as.numeric(b)
3 as.logical(b)
4 as.factor(b)
```

Look for problems

```
1 rivers

# A tibble: 300 × 6
  river_name site      element amount temperature year
  <chr>      <chr>      <chr>      <dbl>      <dbl> <dbl>
1 Grasse    Up stream    Al         0.606      10.9  2019
2 Grasse    Mid stream  Al         0.425       8.68  2020
3 Grasse    Down stream Al         0.194       8.75  2021
4 Oswegatchie Up stream  Al          1         0.791  2022
5 Oswegatchie Mid stream  Al         0.161       9.32  2023
6 Oswegatchie Down stream Al        0.0333     10.6  2019
7 Raquette  Up stream    Al         0.292       4.01  2020
8 Raquette  Mid stream  Al        0.0389       5.96  2021
9 Raquette  Down stream Al         NA         6.21  2022
10 St. Regis Up stream    Al         0.681       8.02  2023
# i 290 more rows
```

Year could be categorical (factor)
Better for plotting!
(although it really depends)

Convert to categorical

```
1 rivers <- mutate(rivers, year = factor(year))
2 rivers
```

```
# A tibble: 300 × 6
  river_name site      element amount temperature year
  <chr>      <chr>      <chr>    <dbl>      <dbl> <fct>
1 Grasse    Up stream    Al      0.606      10.9  2019
2 Grasse    Mid stream   Al      0.425       8.68  2020
3 Grasse    Down stream  Al      0.194       8.75  2021
4 Oswegatchie Up stream    Al      1          0.791  2022
5 Oswegatchie Mid stream   Al      0.161       9.32  2023
6 Oswegatchie Down stream  Al      0.0333     10.6   2019
7 Raquette  Up stream    Al      0.292       4.01  2020
8 Raquette  Mid stream   Al      0.0389       5.96  2021
9 Raquette  Down stream  Al      NA          6.21  2022
10 St. Regis Up stream    Al      0.681       8.02  2023
# i 290 more rows
```

Put it all together...

```
1 rivers <- read_csv("data/rivers_raw.csv") |>
2   clean_names() |>
3   rename(element = ele, amount = amo, temperature = temperature_c) |>
4   select(-wea) |>
5   mutate(river_name = case_when(river_name %in% c("Grase", "grasse") ~ "Grasse",
6                                 river_name == "raquette" ~ "Raquette",
7                                 TRUE ~ river_name),
8         amount = replace_na(amount, 0),
9         temperature = na_if(temperature, -99),
10        year = factor(year))
```

And you have a clean, corrected data frame ready to use

- You have not changed the original data
- You have a **reproducible** record of all corrections
- You can alter these corrections at any time
- You have formatted your data for use in R
- Read these steps line by line to remind yourself what you did

Put it all together...

Feel free to annotate within a pipe

```
1 rivers <- read_csv("data/rivers_raw.csv") |>
2   # Fix column names
3   clean_names() |>
4   rename(element = ele, amount = amo, temperature = temperature_c) |>
5   select(-wea) |>
6   mutate(
7     # Correct typos
8     river_name = case_when(river_name %in% c("Grase", "grasse") ~ "Grasse",
9                           river_name == "raquette" ~ "Raquette",
10                          TRUE ~ river_name),
11   # Missing amounts should be 0
12   amount = replace_na(amount, 0),
13   # Problems with temperature logger, -99 is a mistake
14   temperature = na_if(temperature, -99),
15   # Convert for plotting
16   year = factor(year))
```

Dates and Times

(Or why does R hate me?)

Dates and Times

- Date/times aren't always recognized as date/times
- Geolocator data

```
1 geolocators <- read_csv("data/geolocators.csv", col_names = c("time", "light"))
2 geolocators
```

```
# A tibble: 21 × 2
  time          light
<chr>         <dbl>
1 02/05/11 22:29:59    64
2 02/05/11 22:31:59    64
3 02/05/11 22:33:59    38
4 02/05/11 22:35:59    38
5 02/05/11 22:37:59    34
6 02/05/11 22:39:59    30
# i 15 more rows
```

Here `time` column is considered `chr` (character/text)

You may know it's a date, but R does not



lubridate package *

- Part of [tidyverse](#), but needs to be loaded separately
- Great for converting date/times (i.e. telling R this is a date/time)



```
1 library(lubridate)
2 geolocators <- mutate(geolocators, time_fixed = dmy_hms(time))
3 geolocators
```

```
# A tibble: 21 × 3
  time          light time_fixed
<chr>         <dbl> <dtm>
1 02/05/11 22:29:59    64 2011-05-02 22:29:59
2 02/05/11 22:31:59    64 2011-05-02 22:31:59
3 02/05/11 22:33:59    38 2011-05-02 22:33:59
4 02/05/11 22:35:59    38 2011-05-02 22:35:59
5 02/05/11 22:37:59    34 2011-05-02 22:37:59
6 02/05/11 22:39:59    30 2011-05-02 22:39:59
# i 15 more rows
```

Now `time_fixed` column is considered `dtm` (Date/Time)

So **You** know it's a Date/Time and now **R** knows too

lubridate package *

Generally, only the order of the **year**, **month**, **day**, **hour**, **minute**, or **second** matters.

For example

date/time format	function	output class
2018-01-01 13:09:11	<code>ymd_hms()</code>	dtm (POSIXct/POSIXt)
12/20/2019 10:00 PM	<code>mdy_hm()</code>	dtm (POSIXct/POSIXt)
31/01/2000 10 AM	<code>dmy_h()</code>	dtm (POSIXct/POSIXt)
31-01/2000	<code>dmy()</code>	Date



lubridate is smart enough to detect AMs and PMs

Saving data

(For the love of all that is good don't *lose* that data!!!)*

* but if you've been paying attention, you know that you only need the script 😊

Saving data

Keep yourself organized

- Keep your R-created data in a **different** folder from your 'raw' data *
- If you have a lot going on, split your work into several scripts, and number the both the scripts AND the data sets produced:
- `1_cleaned.csv`
- `2_summarized.csv`
- `3_graphing.csv`

Save your data to file:

```
1 write_csv(rivers, "datasets/rivers_cleaned.csv")
```



Dealing with data

1. Loading data

- Get your data into R

2. Looking for problems

- Typos
- Incorrectly loaded data

3. Fixing problems

- Corrections
- Renaming

4. Setting formats

- Dates
- Numbers
- Factors

5. Saving your data

Wrapping up: Common mistakes

Assuming your data is in one format when it's not

- Print your data to the console and use `skim()` to explore the format of your data
- Use `skim()`, `count()`, `filter()`, `select()`, `ggplot()` to explore the content of your data

Wrapping up: Common mistakes

Confusing pipes with function arguments

- Pipes (`|>` or `%>%`) pass the *output* from one function as *input* to the next function:

```
1 my_data <- my_data |>           # Pass my_data
2   filter(my_column > 5) |>      # Pass my_data, filtered
3   select(my_column, my_second_column)
```

- Arguments may be on different lines, but all part of *one* function

```
1 my_data <- my_data |>           # Pass my_data
2   mutate(my_column1 = if_else(...), # No passing (no pipes!)
3         my_column2 = if_else(...),  # Instead, give 3 arguments to mutate:
4         my_column3 = if_else(...)) # Arguments separated by ",", and surrounded by ( )
```

Wrapping up: Further reading

- R for Data Science
 - [Chapter 3: Data transformation](#)
 - [Chapter 6: Workflow: scripts and projects](#)
 - [Chapter 14: Strings](#)
 - [Chapter 16: Factors](#)
 - [Chapter 4.3: Workflow: code style > Pipes](#)