Conformal-Calibrated Rewards for Scientific RLVR: Procedural Regeneration Against Benchmark Contamination

Stelios Zacharioudakis
National and Kapodistrian University of Athens
ORCID: [pending registration]
stelios.zach@[email placeholder]

Abstract

Reinforcement learning from verifiable rewards (RLVR) has become the dominant training signal for frontier reasoning models, but existing verified environments are dominated by symbolic or code-centred tasks. Scientific inverse problems—CT, MRI, compressed sensing, phase retrieval—remain unmeasured despite their continuous, ill-posed, uncertainty-sensitive structure. We release ten RL environments spanning five scientific modalities with two design properties absent from current benchmarks: (i) every reward is split-conformal calibrated to a target $1-\alpha$ coverage, so honest posterior width is rewarded alongside point-estimate quality; and (ii) every measurement y is procedurally regenerated per query, making fixed-string contamination mathematically impossible at $\sim 10^{22}$ effective instances per environment. On 43 paired (env, model) comparisons across six frontier models, classical baselines significantly outperform every tested LLM on 29 ($p<0.05$, 10k paired bootstrap), with a mean $\Delta=+0.213$ reward. We further document a corrected tool-use finding—an earlier oracle-delegation artefact ($r=0.858$) was traced and removed; primitive-only reruns cluster all models at the empty-answer floor ($r\approx 0.40$). Empirical conformal coverage across all ten environments lands at 0.901 ± 0.016 against a 0.90 target. Environments are open-source (MIT) on the Prime Intellect Hub and ready for use as RLVR training signal.

1 Introduction

Frontier-model training has pivoted on RLVR: a verifier checks each completion against a formal spec, and the resulting reward fine-tunes the policy. DeepSeek-R1 [DeepSeek-AI, 2025] and OpenAI o1 [OpenAI, 2024] popularised the recipe; SWE-bench [Jimenez et al., 2024], HumanEval [Chen et al., 2021], MATH [Hendrycks et al., 2021], and GPQA [Rein et al., 2023] supplied most of the verifiers. These benchmarks share a property: answers are discrete (a patch, a number, a multiple-choice letter), so verification is a string/execution check. *Scientific* reasoning, in contrast, operates on continuous fields under ill-posed forward operators whose inverses admit a range of answers that only calibrated uncertainty can discriminate. Classical algorithms in this domain—OMP [Donoho, 2006, Candès and Tao, 2006], FBP [Adler and Öktem, 2018], zero-filled inverse FFT [Fessler, 2020], Gerchberg–Saxton [Gerchberg and Saxton, 1972]—achieve calibrated answers via mathematical guarantees; whether frontier LLMs match them is an open empirical question that existing verified-env frameworks cannot pose.

We contribute: (i) a reward construction combining split-conformal coverage [Angelopoulos and Bates, 2023, Vovk et al., 2005, Lei and Wasserman, 2014] with task-specific point metrics, landing at the $1-\alpha$ target across all ten shipped envs; (ii) a procedural measurement-regeneration protocol that eliminates fixed-string memorisation as a valid strategy by construction; (iii) a benchmark of six

Preprint. Under review.

frontier models across five scientific domains with paired- bootstrap significance tests; and (iv) ten open-source (MIT) environments on Prime Intellect Environments Hub [Prime Intellect, 2024].

2 Related Work

RLVR environments. Coding and symbolic tasks dominate the current ecosystem: SWE-bench [Jimenez et al., 2024], GPQA [Rein et al., 2023], MATH [Hendrycks et al., 2021], HumanEval [Chen et al., 2021]. Scientific inverse problems are absent. Infrastructure such as `verifiers` [Brown and contributors, 2024] simplifies adapter implementation but does not prescribe reward calibration.
Scientific ML. Learned primal-dual CT [Adler and Öktem, 2018], deep CNNs [Jin et al., 2017], and MRI optimisation [Fessler, 2020] established supervised baselines; Ongie et al. [2020] survey the space. None treat the problem as an RL environment with uncertainty-aware rewards for RLVR.
Conformal prediction. Split-conformal theory [Vovk et al., 2005], distribution-free regression bands [Lei and Wasserman, 2014], and conformalised quantile regression [Romano et al., 2019]; Angelopoulos and Bates [2023] give a modern treatment. We apply split-conformal calibration as the reward-shaping mechanism for scientific RLVR—a novel application to our knowledge.

3 Method

Environment framework. An environment $\mathcal{E} = (\mathcal{F}, \mathcal{P}, \mathcal{R})$ specifies a forward operator $\mathcal{F}$, a ground-truth distribution $\mathcal{P}$, and a conformal-calibrated reward $\mathcal{R}$. Per query the env draws $x_{\text{true}} \sim \mathcal{P}$, samples fresh noise η, and presents the measurement $y{=}\mathcal{F}(x_{\text{true}}) + \eta$. The solver returns $(\hat{x}, \hat{\sigma})$; reward factors into a point metric (PSNR / SSIM / NMSE / support-F1) and a split-conformal term.

Conformal-calibrated rewards. Fix $\alpha{=}0.1$ and a non-conformity score $s(\hat{x}, x_{\text{true}}, \hat{\sigma}) = \max_j |x_{\text{true},j} - \hat{x}_j|/\hat{\sigma}_j$. At calibration time we run the classical baseline on n_{cal} fresh seeds, compute s, and set $q_\alpha{=}\,\text{Quantile}_{1-\alpha}(\{s_i\})$. At score time the conformal component is $\mathcal{R}_{\text{conf}} = 1 - |\text{cov}(\hat{x}, \hat{\sigma}, q_\alpha) - (1-\alpha)|/(1-\alpha)$, penalising both over-narrow (over-confident) and over-wide (under-confident) posterior widths.

Procedural regeneration. Each env factors into $(\text{seed}, \text{image_id})$. With a 64-bit seed and 10^3 ground-truth images the effective instance count is $\sim 10^{22}$ measurement strings per env. No fixed (y, x_{true}) pair reappears; any reward a model achieves by pattern-matching on y alone must be indistinguishable from the reward on the regenerated instance.

Multi-turn and tool-use. Three envs expose a 3-turn dialogue where the server returns a forward-model residual between turns. A tool-use variant of sparse recovery exposes five primitives (`fft`, `ifft`, soft-`threshold`, `compute_residual`, `sparsity_norm`) from which the solver must compose ISTA. An earlier v0.1 of this env bundled an `ista_tool` oracle; empirical byte-identical rewards ($r{=}0.858$) across three distinct models revealed the oracle-delegation artefact, and we now regression-test against any single primitive raising reward above the empty-answer floor.

4 Experiments

Setup. Ten envs across five domains: compressed sensing (sparse Fourier, single/multi/tool-use), super-resolution (DIV2K [Agustsson and Timofte, 2017], $4\times$), CT (LoDoPaB [Leuschner et al., 2021], single/multi), phase retrieval (single/multi), MRI knee (single/multi). Baselines: OMP, bicubic, FBP, Gerchberg–Saxton, zero-filled IFFT. Models via OpenRouter: Claude Opus 4.7, Sonnet 4.6, Haiku 4.5, GPT-5.4, -mini, -nano [Anthropic, 2025, OpenAI, 2025]. Conformal: $\alpha{=}0.1$, $n_{\text{cal}}{\geq}30$. Total LLM spend: $\sim\$8$.

Finding 1 — classical beats every tested LLM (Figure 2). Across 43 paired (env, model) comparisons and 10 000 paired-bootstrap resamples, classical significantly outperforms the LLM on 29 ($p{<}0.05$); nine show no significant difference, five show the LLM significantly better (all at super-resolution, where the LLM is fed a bicubic-prior input). Pooled mean $\Delta{=}\,+\,0.213$ with all-positive per-env sub-means.

Finding 2 — multi-turn separates tiers (Figure 3, appendix). Five models with data on both sparse-F and CT single-turn and multi-turn variants split cleanly. Opus 4.7 and GPT-5.4 gain >0.04 reward from the 3-turn residual-feedback protocol; Sonnet 4.6 gains $+0.04$; Haiku 4.5 and GPT-5.4-mini regress (-0.063 and -0.055). Small models fail to maintain coherence across three turns



Figure 1: Reward per (model, env) across the five cross-env test envs. Six models, two instances per cell. Classical baselines printed below; '—' denotes parse-failure-only pairs.

of dense pixel-grid residuals; the 3-turn variant thus measures continuous-reasoning orthogonal to single-turn scoring.

Finding 3 — primitive composition gap (Figure 4, appendix). On the v0.3 primitive-only tool-use benchmark, Haiku 4.5 and GPT-5.4-mini converge near the empty-answer floor (0.40 ± 0.01), far below classical OMP (0.87) on the same instances, with up to 30 tool calls per episode. The v0.1 oracle-artefact value (0.858) is shown for contrast. LLMs cannot yet compose ISTA from primitive operators over compressed-sensing measurements at the tested scale.



Figure 2: **(L)** Finding 1: 5-env mean reward per model vs classical baseline (0.630); top LLM is Opus 4.7 at 0.574. **(R)** Conformal coverage validation at n=100 per env: grand mean 0.901 ± 0.016 against the 0.90 target.

5 Discussion

Scientific inverse problems surface capability gaps invisible on symbolic benchmarks: a $+0.21$ mean classical-vs-LLM gap is dense training signal, not a saturated leaderboard. The multi-turn sign- flip by model tier isolates continuous-reasoning coherence; the primitive tool-use result is a negative capability finding (LLMs cannot execute compressed-sensing reasoning from primitives at the tested scales). **Limitations.** Sample sizes are small (2–5 per cell), so bootstrap CIs are wide even when

p is small. Images are rendered at 16×16 or 32×32 for LLM-token tractability. Phase retrieval is hard even for Gerchberg–Saxton (r=0.29), so the corresponding LLM gaps should be read in context. We report no training experiments—only evaluation. **Future work.** RL fine-tuning with the envs as training signal; expansion to seismic FWI and retrosynthesis (deferred for install and verifier-design complexity).

6 Conclusion

Ten RL environments with conformal-calibrated rewards and procedural measurement regeneration expose systematic capability gaps in frontier LLMs on scientific inverse problems. Code: github.com/stelioszach03/verifiable-labs-envs; envs: app.primeintellect.ai/dashboard/environments/stelioszach; leaderboard: huggingface.co/spaces/stelioszach03/scientific-rl-benchmark.

Acknowledgments

The author thanks the Prime Intellect team for hosting environments on the Environments Hub, and HuggingFace for hosting the interactive benchmark Space. This research did not receive funding. **AI-assistance disclosure.** The author used Claude (Anthropic) and Codex (OpenAI) for code generation of benchmark infrastructure, figure generation scripts, and manuscript drafting assistance. All scientific claims, experimental design, baseline selection, statistical analysis, and conclusions were developed and verified by the author. Benchmark numerical results are computed directly from CSV outputs of model API calls without AI intermediation.

References

Jonas Adler and Ozan Öktem. Learned primal-dual reconstruction. *IEEE Transactions on Medical Imaging*, 37 (6):1322–1332, 2018. doi: 10.1109/TMI.2018.2799231.

Eirikur Agustsson and Radu Timofte. NTIRE 2017 challenge on single image super-resolution: Dataset and study. In *CVPR Workshops*, 2017. doi: 10.1109/CVPRW.2017.150.

Anastasios N. Angelopoulos and Stephen Bates. A gentle introduction to conformal prediction and distribution-free uncertainty quantification. *Foundations and Trends in Machine Learning*, 16(4):494–591, 2023. doi: 10.1561/2200000101.

Anthropic. Claude 4 and claude 4.5 model card. https://www.anthropic.com/claude, 2025.

Will Brown and contributors. Verifiers: A framework for LLM environment evaluation. https://github.com/willccbb/verifiers, 2024.

Emmanuel J. Candès and Terence Tao. Near-optimal signal recovery from random projections: Universal encoding strategies? *IEEE Transactions on Information Theory*, 52(12):5406–5425, 2006. doi: 10.1109/TIT.2006.885507.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021. URL https://arxiv.org/abs/2107.03374.

DeepSeek-AI. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025. URL https://arxiv.org/abs/2501.12948.

David L. Donoho. Compressed sensing. *IEEE Transactions on Information Theory*, 52(4):1289–1306, 2006. doi: 10.1109/TIT.2006.871582.

Jeffrey A. Fessler. Optimization methods for magnetic resonance image reconstruction: Key models and optimization algorithms. *IEEE Signal Processing Magazine*, 37(1):33–40, 2020. doi: 10.1109/MSP.2019.2943645.

R. W. Gerchberg and W. O. Saxton. A practical algorithm for the determination of the phase from image and diffraction plane pictures. *Optik*, 35:237–246, 1972.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the MATH dataset. In *NeurIPS Datasets and Benchmarks Track*, 2021. URL https://arxiv.org/abs/2103.03874.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *International Conference on Learning Representations (ICLR)*, 2024. URL https://arxiv.org/abs/2310.06770.

Kyong Hwan Jin, Michael T. McCann, Emmanuel Froustey, and Michael Unser. Deep convolutional neural network for inverse problems in imaging. *IEEE Transactions on Image Processing*, 26(9):4509–4522, 2017. doi: 10.1109/TIP.2017.2713099.

Jing Lei and Larry Wasserman. Distribution-free prediction bands for non-parametric regression. *Journal of the Royal Statistical Society: Series B*, 76(1):71–96, 2014. doi: 10.1111/rssb.12021.

Johannes Leuschner, Maximilian Schmidt, Daniel Otero Baguer, and Peter Maass. LoDoPaB-CT, a benchmark dataset for low-dose computed tomography reconstruction. *Scientific Data*, 8(1):109, 2021. doi: 10.1038/s41597-021-00893-z.

Gregory Ongie, Ajil Jalal, Christopher A. Metzler, Richard G. Baraniuk, Alexandros G. Dimakis, and Rebecca Willett. Deep learning techniques for inverse problems in imaging. *IEEE Journal on Selected Areas in Information Theory*, 1(1):39–56, 2020. doi: 10.1109/JSAIT.2020.2991563.

OpenAI. Learning to reason with LLMs. https://openai.com/index/learning-to-reason-with-llms/, 2024.

OpenAI. GPT-5 system card. https://openai.com/research, 2025.

Prime Intellect. Prime intellect environments hub. https://app.primeintellect.ai/environments, 2024.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. GPQA: A graduate-level google-proof Q&A benchmark. *arXiv preprint arXiv:2311.12022*, 2023. URL https://arxiv.org/abs/2311.12022.

Yaniv Romano, Evan Patterson, and Emmanuel J. Candès. Conformalized quantile regression. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019. URL https://arxiv.org/abs/1905.03222.

Vladimir Vovk, Alexander Gammerman, and Glenn Shafer. *Algorithmic Learning in a Random World*. Springer, 2005. ISBN 978-0-387-00152-4.

A Supplementary figures



Figure 3: Mean reward delta (multi-turn minus single-turn) per model averaged over sparse-Fourier and CT. Frontier models (Sonnet 4.6, GPT-5.4, Opus 4.7) gain; budget models (Haiku 4.5, GPT-5.4-mini) regress.



Figure 4: Tool-use rewards on sparse Fourier recovery. v0.3 removed the `ista_tool` oracle; tested LLMs (Haiku 4.5, GPT-5.4-mini) drop to the empty-answer floor, while classical OMP remains at 0.87. The v0.1 oracle-artefact value (0.858) is shown for contrast.