
Search...


	home	software	hardware	support	downloads	purchase	training	account	
	Overview	Support							Logout
Translate to Sp	anish : ON			[Back To Ma	ain Menu]				
1. We are	configuring D	ual Nstreme link.	Which MAC-add	dress should we	put to 'Remote-M	AC' field in Dual	Nstreme confi	guration ?	
O A. Ra	ndom generate	ed							
		of transmitting card	i						
		of receiving card		27:44					
		ss interface is in '	stat	at connect to the access point in the same band with the same SSID and					
_		profile, the poss	Save	Save progress					
		s tools, e.g., scanne	·	-					
■ B. The station has different frequency setting from that of the AP									
C. the station has setting "scan-list=default" and the APs frequency is not within the default range									
☐ D. the station has "wmm-support=disabled", but the AP has " wmm-support=enabled"									
3. ¿En qué	orden las en	tradas Access Lis	t y Connect List	son procesadas	?				
A. Po	r nombre de in	terfaz							
B. En	orden secuend	cial							
C. Po	r potencia de la	a señal							
O D. En	cualquier orde	n							
4. Is it req	uired to use I	RADIUS when you	are using EAP-	TLS method in t	the Security profile	e?			
false ▼									
		required on AP to	authenticate cl	ients using EAP	-TLS and				
eap-metno	d=passthrou	gn?							
A. CA	certificates								
B. No	ne								
O C. Se	rver certificates	3							
O D. Cli	ent certificates								
					GHz (with no nstreethan a few secon			z. When you ch	nange the
protocol\' s		bled on the clien			correct encryption ect the protocol u				
A. nv2	2-nstreme-802.	11							
B. any	/								
C. Nv	2								
D. uns	specified								
7. With wh	at mode set	wireless interface	can be added a	s bridge port:					
✓ A. sta	tion-WDS								
□ В. ар-	bridge								
C. sta	tion								
					GHz (with no nstreet than a few secon			z. When you ch	nange the
protocol' sl		oled on the client			correct encryption ect the protocol us				
A. any	,								
_	2-nstreme-802.	11							
C. uns									
D. Nv.									
D. INV	=								

 $\boldsymbol{9.}$ The maximum number of Virtual AP on a single wireless interface is 2007

- 10. Wireless Security Profile, Management Protection Key is for:
 - A. Frame Protection only on RouterOS Devices
 - B. Frame Protection on RouterOS Devices and any other devices with Frame Protection Support
 - C. Frame Protection on any Device
- 11. You enable the wireless card while it is in AP mode, but no clients are able to connect for at least 60 seconds. The reason for this is
 - A. Proprietary Extensions is incorrectly set to 'pre-2.9.25'
 - B. DFS with radar-detect is enabled
 - C. 'Hide SSID' is enabled
 - D. 'Periodic Calibration' is enabled and 'Calibration Interval' is set to 60 seconds
- 12. Which command will analyze spectrum on channel 5180 ?
 - A. /interface wireless spectral-scan wlan1 range=5100,5280
 - ☑ B. /interface wireless spectral-history wlan1 range=5100-5280
 - C. /interface wireless spectral-history wlan1 range=5100,5280
 - ☑ D. /interface wireless spectral-scan wlan1 range=5100-5280
- 13. In the screenshot, why are two of the three 'Tx/Rx Signal Strength ChX' boxes empty?
 - A. Nv2 is not configured correctly
 - B. The CCQ is too low.
 - C. The signal strength is too low or too high
 - D. The radio is not configured to use 802.11n.



- 14. Picture shows signal,
 - A. 802.11a 5 MHZ channel width.
 - B. 802.11n 20/40ht below 5180 MHz.
 - C. Microwave oven.
 - O. 802.11a 20mhz channel. width.
 - E. 802.11n 20/40ht above 5180 MHz.



- 15. What is the minimum number of connect-list rules that are required on an AP to allow 2 clients to connect during working days from 9am to 5pm and on holidays from 8am to 11pm?
 - A. 4
 - B. 5
 - O C. 0
 - O D. 14
- 16. Personal WPA-PSK key in an Access List can be used even if there is no WPA security profile enabled on the Wireless AP.

17. WPA2 Pre-Shared Key (PSK) is enabled on AP, all the clients have to use the same PSK. Only Virtual AP could be used to allow clients to connect with a different PSK.

18. It is possible to connect a MikroTik RouterOS device to a wireless device made by another manufacturer using Nv2 protocol.

- 19. Which type of encryption could be used to establish a connection with a simple passkey without using a 802.1X authentication server?
 - A. WPA PSK/WPA2 PSK
 - B. WPA EAP/WPA2 EAP

20. what changes if "WDS slave" wireless mode is set					
A. Adapts to Master WDS frequency					
B. Enables WDS on AP					
C. Connect to an SSID as a client in slave mode					
21. Access Point configuration is configured to "Management Protection=allowed" and a Management Protection Key is set.					
Which clients can connect to the AP (Choose the most universal answer)?					
A. Mikrotik Client with Management Protection=allowed					
B. Any wireless client					
C. Any Mikrotik Client					
D. Mikrotik Client with Management Protection=required					
22. These are ways to protect your wireless connections from unauthorized access.					
A. WPA Encryption					
☐ B. Creating a different SSID					
C. ppp tunnels					
☑ D. RADIUS Authentication using mac-address as username					
23. When several Virtual AP Interfaces are configured, you can add them to a bridge and apply layer 2 filter rules between them.					
false ▼					
24. What encryption algorithm for WPA/WPA2 is more secure?					
A. AES - Advanced Encryption Standard					
B. TKIP - Temporal Key Integrity Protocol					
25. Which WDS wireless modes are compatible with one other:					
A. Dynamic mode with Dynamic-mesh mode					
☐ B. Dynamic mode with Static mode					
C. Static mode with Static-mesh mode					
D. Static mode with Dynamic-mesh mode					
☐ E. Static-mesh mode with Dynamic-mesh mode					
F. Static-mesh mode with Dynamic mode					
Finish					

Mikrotik: RouterBOARD: Forum: MUM: Training: Wiki: Newsletters: Twitter