



progress engine
we will develop it

#tceh

2016

Врубиться в Ruby

Лекция 21


Лекция 21



- Что такое API
- Какие существуют форматы данных?
- action controller, rails api или grape?
- Инструменты для тестирования API

API

API = Application Programming Interface



Форматы данных

XML

```
<Cars>
  <Car Make="Ford" Model="Fiesta">
    <Seats>4</Seats>
    <Interior>Cloth</Interior>
  </Car>
  <Car Make="Porsche" Model="911">
    <Seats>2</Seats>
    <Interior>Leather</Interior>
  </Car>
  <Car Make="Toyota" Model="Sienna">
    <Seats>8</Seats>
    <Interior>Cloth</Interior>
  </Car>
</Cars>|
```


JSON

```
{ "users": [  
  {  
    "firstName": "Ray",  
    "lastName": "Villalobos",  
    "joined": {  
      "month": "January",  
      "day": 12,  
      "year": 2012  
    }  
  },  
  {  
    "firstName": "John",  
    "lastName": "Jones",  
    "joined": {  
      "month": "April",  
      "day": 28,  
      "year": 2010  
    }  
  }  
]  
}
```



MsgPack

JSON 27 bytes

```
{ "compact": true, "schema": 0 }
```

MessagePack 18 bytes





Action Controller, Rails API
или Grape

Action Controller

Rails API


```
$ rails new my_api --api
```

Grape

gem 'grape'

```
config.paths.add File.join('app', 'api'), glob: File.join('**', '*.rb')  
config.autoload_paths += Dir[Rails.root.join('app', 'api', '*')]
```

routes.rb

```
mount SuperApplication::API => '/'
```

```
module SuperApplication
  class API < Grape::API
    version 'v1', using: :header, vendor: 'twitter'
    format :json
    prefix :api

    helpers do
      def current_user
        @current_user ||= User.authorize!(env)
      end

      def authenticate!
        error!('401 Unauthorized', 401) unless current_user
      end
    end
  end
end
```

```
resource :statuses do
  desc 'Return a public timeline.'
  get :public_timeline do
    Status.limit(20)
  end
end
```

```
  desc 'Return a personal timeline.'
  get :home_timeline do
    authenticate!
    current_user.statuses.limit(20)
  end
end
```

```
desc 'Update a status.'
params do
  requires :id, type: String, desc: 'Status ID.'
  requires :status, type: String, desc: 'Your status.'
end
put ':id' do
  authenticate!
  current_user.statuses.find(params[:id]).update({
    user: current_user,
    text: params[:status]
  })
end
```


Версионирование API

Path

version 'v1', using: :path

curl http://localhost:9292/v1/statuses/public_timeline

Header

version 'v1', using: :header, vendor: 'twitter'

format - vnd.vendor-and-or-resource-v1234+format

curl -H Accept:application/vnd.twitter-v1+json
http://localhost:9292/statuses/public_timeline

Accept-Version Header

version 'v1', using: :accept_version_header

```
curl -H "Accept-Version:v1" http://localhost:9292/statuses/  
public_timeline
```

Parameter

version 'v1', using: :param, parameter: 'v'

curl http://localhost:9292/statuses/public_timeline?v=v1

Документация

Swagger

<http://swagger.io/>

Blueprint

<https://apiblueprint.org/>

RAML

<http://raml.org/>

Тестирование API

<https://github.com/brooklynDev/airborne>

УТИЛИТЫ

<https://curl.haxx.se>

<https://github.com/jkbrzt/httpie>

<https://luckymarmot.com/paw>

Paw.paw | Sent Repo Commits 200 OK | 665 ms

GET https://api.github.com/repos/luckymarmot/Paw-EmailRandomizerDynamicValue/commits 200 OK

Headers URL Params Body Options

Header Name	Header Value
Accept	application/vnd.github.v3+json
Accept-Language	User Language
Authorization	OAuth OAuth 2 Authorization
If-None-Match	Response Header Repo Commits...
Add Header Name	Add Header Value

Key or Index Type Value

Root	
Item	
commit	
tree	
sha	fc8581742b11feb971a05adf034a5ca8d2c2...
url	https://api.github.com/repos/luckymarmot/Paw-EmailRandomizerDynamicValue/commits
author	
committer	
message	Updated README.
url	https://api.github.com/repos/luckymarmot/Paw-EmailRandomizerDynamicValue/commits
comment_count	0

1 GET /repos/luckymarmot/Paw-EmailRandomizerDynamicValue/commits HTTP/1.1
2 Accept: application/vnd.github.v3+json
3 Accept-Language: en-US
4 Authorization: ***** Hidden credentials *****
5 If-None-Match: "ce37dcee34bdad1704098d7807ed200c"
6 Host: api.github.com
7 Connection: close
8 User-Agent: Paw/2.3 (Macintosh; OS X/10.11.3) GCDHTTPRequest

3.commit

Прочитать

<http://www.datto.com/blog/a-framework-comparison-of-grape-vs-railsapi-part-1-performance>

<https://www.toptal.com/ruby/grape-gem-tutorial-how-to-build-a-rest-like-api-in-ruby>

<https://blog.codeship.com/building-a-json-api-with-rails-5/>

<https://blog.pivotal.io/pivotal-labs/labs/api-versioning>

<https://habrahabr.ru/company/geekfamily/blog/256495/>

Практика

Вопросы?

+7 (926) 889-16-32

alec@alec-c4.com

<http://alec-c4.com/>