



progress engine
we will develop it

#tceh

2016

Врубиться в Ruby

Лекция 17

Лекция 17



- Foreman gem
- Deployment on Heroku
- puma, unicorn, thin, passenger
- Настройка сервера
- capistrano и mina

foreman

<https://github.com/ddollar/foreman>


Procfile

```
web: bundle exec thin start -p $PORT
worker: bundle exec rake resque:work QUEUE=*
clock: bundle exec rake resque:scheduler
```


Heroku




<https://heroku.com>




puma, unicorn, thin, passenger





<https://github.com/puma/puma>




[https://github.com/jrochkind/fake_work_app/blob/master/
README.md](https://github.com/jrochkind/fake_work_app/blob/master/README.md)

<http://code.macournoyer.com/thin/>

<https://unicorn.bogomips.org>



<https://www.phusionpassenger.com>



https://www.phusionpassenger.com/compare_ruby

capistrano + mina

<http://capistranorb.com/>

<http://nadarei.co/mina/>

```
|— current -> /var/www/my_app_name/releases/20150120114500/
|— releases
|   |— 20150080072500
|   |— 20150090083000
|   |— 20150100093500
|   |— 20150110104000
|   └— 20150120114500
|— repo
|   └— <VCS related data>
|— revisions.log
└— shared
    └— <linked_files and linked_dirs>
```

```
# config valid only for current version of Capistrano  
lock '3.4.0'
```

```
set :application, 'domochat'  
set :repo_url, 'git@github.com:domochat/domochat.git'  
set :ruby_version, '2.2.3'
```

```
# Default branch is :master  
# ask :branch, `git rev-parse --abbrev-ref HEAD`.chomp
```

```
# Default deploy_to directory is /var/www/my_app_name  
set :deploy_to, "/var/www/#{fetch(:application)}"  
set :keep_releases, 5
```

```
set :rails_env, -> { fetch(:stage) }  
set :scm, :git # Default value for :scm is :git  
set :format, :pretty # Default value for :format is :pretty  
set :log_level, :info # Default value for :log_level is :debug
```

```
set :linked_dirs, %w{bin log tmp/pids tmp/cache tmp/sockets vendor/  
bundle public/system public/uploads}  
set :linked_files, %w{config/application.yml config/database.yml  
config/secrets.yml}
```

```
# rbenv config
```

```
set :rbenv_type, :user # or :system, depends on your rbenv setup  
set :rbenv_ruby, -> { fetch(:ruby_version) }  
set :rbenv_prefix, "RBENV_ROOT=#{fetch(:rbenv_path)}  
RBENV_VERSION=#{fetch(:rbenv_ruby)} #{fetch(:rbenv_path)}/bin/  
rbenv exec"  
set :rbenv_map_bins, %w{rake gem bundle ruby rails}  
set :rbenv_roles, :all # default value
```

[https://gist.github.com/alec-c4/](https://gist.github.com/alec-c4/8761bd9cf0d8f0983b2ebebbae7516d3d)
8761bd9cf0d8f0983b2ebebbae7516d3d

Практика

Вопросы?

+7 (926) 889-16-32

alec@alec-c4.com

<http://alec-c4.com/>