

# Onyx — FontKit reference

Onyx · multi-process OS on Raspberry Pi 4

The reference of **FontKit** (`SD:/lib/fontkit.so`, `user/Kits/fontkit`): what it is for, how a program uses it, and every operation it exposes. The operations' part is made from the kit's headers by `tools/docgen/kitdocs.py` — the headers are the source. Overview of all the kits: [The Kits](#).

## Contents

1. What it is
2. Using it
3. Index
4. `fontkit/uikitface.h`
5. `fontkit/fonts.h`

## What it is

FontKit is fonts and text: FreeType as a shared library, the font manager (the card's families, a font at a size, its glyphs cached) and UIKit's anti-aliased text face.

|         |                                                                                                                           |
|---------|---------------------------------------------------------------------------------------------------------------------------|
|         |                                                                                                                           |
| Include | <code>#include "fontkit/uikitface.h"</code><br><code>// or "fontkit/fonts.h"</code>                                       |
| Link    | <code>lib/fontkit.imp.a</code>                                                                                            |
| Library | <code>SD:/lib/fontkit.so</code> — 135 entries in its table<br>( <code>user/Kits/fontkit/fontkit.abi</code> , append-only) |
| Sources | <code>user/Kits/fontkit/</code>                                                                                           |

## Using it

FontKit is FreeType for the applications, with the card's fonts (`SD:/res/fonts`).

**Anti-aliased text in a UIKit application** — one call before the widgets are built:

```
#include "uikit/uikit.h"
#include "fontkit/uikitface.h"
using namespace uikit;

int main (void)
{
    ft_uikit_install ("DejaVu Sans", 13);           // every widget's text from now on
    Root root (400, 200, "Smooth text");
    root.addChild (new Label (12, 12, 376, 24, "FreeType draws this"));
    root.run ();
    return 0;
}
```

**The font manager** — the families installed, a font at a size, text measured (a word processor, a canvas):

```
#include "fontkit/fonts.h"
```

```
fnt::init ();  
for (int i = 0; i < fnt::count (); i++) ax_putln (fnt::name (i));
```

```
int fam = fnt::find ("DejaVu Serif");  
fnt::Font *f = fnt::get (fam, 0, 14 * 64);           // style 0 (regular), 14 px in  
26.6  
int width = fnt::advance (f, 'A');                 // in 26.6 units
```

## FreeType's own functions

The library exports FreeType's API under its own names — 135 functions (FT\_Init\_FreeType, FT\_New\_Memory\_Face, FT\_Load\_Glyph, FT\_Render\_Glyph...), used as FreeType's documentation says (freetype.org). The apps' build is lean: TrueType, the auto-hinter, the smooth rasterizer. Most programs do not call them: they use the font manager and the text face below.

## Index

Everything the headers declare, in their order — the details are in each header's part below.

| Name             | What it does                                                                                                                                                                | Header      |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| FtTextFace       | ft/uikitface.h --<br>FreeType's anti-aliased<br>text for every uikit<br>widget                                                                                              | uikitface.h |
| ft_uikit_install | Installs FreeType's text<br>for every uikit widget<br>with the family by name<br>(DejaVu Sans when<br>absent) at px pixels,<br>false when the card has<br>no TrueType font. | uikitface.h |
| ft_uikit_face    | The face ft_uikit_install<br>made (0                                                                                                                                        | uikitface.h |
| ft_dialog_face   | The face of the dialogs<br>(0                                                                                                                                               | uikitface.h |
| ft_messagebox    | uikit's message box<br>(uk_messagebox) in<br>FreeType's text.                                                                                                               | uikitface.h |
| ft_file_open     | uikit's file dialogs<br>(uk_file_open /<br>uk_file_save /<br>uk_folder_open) in<br>FreeType's text.                                                                         | uikitface.h |
| ft_file_save     | uikit's file dialogs<br>(uk_file_open /<br>uk_file_save /<br>uk_folder_open) in                                                                                             | uikitface.h |

| Name                        | What it does                                                                                                                                                 | Header                   |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
|                             | FreeType's text.                                                                                                                                             |                          |
| <code>ft_folder_open</code> | UIKit's file dialogs ( <code>uk_file_open</code> / <code>uk_file_save</code> / <code>uk_folder_open</code> ) in FreeType's text.                             | <code>uikitface.h</code> |
| <code>Glyph</code>          | (a type)                                                                                                                                                     | <code>fonts.h</code>     |
| <code>Font</code>           | (a type)                                                                                                                                                     | <code>fonts.h</code>     |
| <code>FaceFile</code>       | (a type)                                                                                                                                                     | <code>fonts.h</code>     |
| <code>s_len</code>          | A string's length in bytes (0 for a null pointer).                                                                                                           | <code>fonts.h</code>     |
| <code>s_cpy</code>          | Copies <code>s</code> into <code>d</code> , cut to <code>cap - 1</code> bytes and always ended by a 0 (a null <code>s</code> gives an empty string).         | <code>fonts.h</code>     |
| <code>lc</code>             | An ASCII capital letter as its small letter, anything else unchanged.                                                                                        | <code>fonts.h</code>     |
| <code>s_icmp</code>         | Compares two strings with ASCII letters' case ignored, returning 0 when equal, else < 0 or > 0 as <code>strcmp</code> .                                      | <code>fonts.h</code>     |
| <code>be16</code>           | The big-endian 16-bit value at <code>p</code> .                                                                                                              | <code>fonts.h</code>     |
| <code>be32</code>           | The big-endian 32-bit value at <code>p</code> .                                                                                                              | <code>fonts.h</code>     |
| <code>read_at</code>        | Reads <code>n</code> bytes of the open file <code>f</code> at offset <code>pos</code> into <code>buf</code> , false when the seek fails or fewer bytes come. | <code>fonts.h</code>     |
| <code>scan_file</code>      | A font file's family name and style from its own tables (no FreeType)                                                                                        | <code>fonts.h</code>     |
| <code>is_ttf</code>         | True when the file name <code>n</code> ends in ".ttf" (letters' case ignored).                                                                               | <code>fonts.h</code>     |
| <code>scan_dir</code>       | Adds every .ttf file of the folder <code>dir</code> that <code>scan_file</code> accepts to <code>g_face</code> (MAXFACE files at most).                      | <code>fonts.h</code>     |

| Name                       | What it does                                                                                                                                     | Header               |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| <code>add_to_family</code> | The style slot a file fills in its family                                                                                                        | <code>fonts.h</code> |
| <code>init</code>          | Starts FreeType and sorts the fonts of SD:/res/fonts and SD:/fonts into families (once), false when FreeType fails or no TrueType font is there. | <code>fonts.h</code> |
| <code>count</code>         | The number of families <code>init ()</code> found.                                                                                               | <code>fonts.h</code> |
| <code>name</code>          | Family i's name, "" when there is no such family.                                                                                                | <code>fonts.h</code> |
| <code>find</code>          | A family's index by its name (letters' case ignored), -1 when there is none.                                                                     | <code>fonts.h</code> |
| <code>styles</code>        | The styles a family has (a mask of $1 << \text{style}$ ).                                                                                        | <code>fonts.h</code> |
| <code>open_face</code>     | A face file's FreeType face, the file read at its first use.                                                                                     | <code>fonts.h</code> |
| <code>free_glyphs</code>   | Frees a font's glyph table and its bitmaps and lowers the cache's byte count (the Font itself stays).                                            | <code>fonts.h</code> |
| <code>make</code>          | Builds a family's style at size64 (1/64 px, 1 px at least) with its metrics and an empty glyph table, 0 when the family or its face file fails.  | <code>fonts.h</code> |
| <code>get</code>           | A family's style at a size (1/64 px).                                                                                                            | <code>fonts.h</code> |
| <code>void</code>          | Forget the fonts not used lately when the cache holds too much (a Font from <code>get ()</code> is then stale)                                   | <code>fonts.h</code> |
| <code>trim</code>          | Forget the fonts not used lately when the cache holds too much (a Font from <code>get ()</code> is then stale)                                   | <code>fonts.h</code> |
| <code>slot</code>          | The glyph table's slot                                                                                                                           | <code>fonts.h</code> |

| Name     | What it does                                                                                                                             | Header  |
|----------|------------------------------------------------------------------------------------------------------------------------------------------|---------|
|          | for the character cp, either the one holding it or the empty one where it goes.                                                          |         |
| grow     | Doubles the glyph table and puts its glyphs back in their new slots (earlier Glyph pointers are stale).                                  | fonts.h |
| glyph    | A character's cached glyph entry (0 is read as a space), made at its first use with its glyph index and advance.                         | fonts.h |
| advance  | A character's advance in 1/64 px, 0 without a font.                                                                                      | fonts.h |
| kern     | The kerning between the characters a and b in 1/64 px, 0 when there is none (no font, no kerning table, a glyph from the fallback font). | fonts.h |
| render   | The coverage bitmap of a glyph at a quarter-pixel position.                                                                              | fonts.h |
| blend    | Lays the colour c (0xRRGGBB) over the pixel d at opacity a (0..255) keeping d's top byte, or replaces d by c when a >= 255.              | fonts.h |
| draw     | A character at x64 (1/64 px) on the baseline y, in colour c, clipped to [cx0, cx1) x [cy0, cy1).                                         | fonts.h |
| draw_str | A string (Latin-1 / ASCII) at x, baseline y, the pen's end returned (1/64 px).                                                           | fonts.h |
| str_w    | A string (Latin-1 / ASCII) at x, baseline y, the pen's end returned (1/64 px).                                                           | fonts.h |

## fontkit/uikitface.h

ft/uikitface.h -- FreeType's anti-aliased text for every uikit widget: a uikit::TextFace (uikit/text.h) built on ft/fonts.h (the card's TrueType families, FreeType's glyphs cached per quarter-pixel position). Header-only, like ft/fonts.h: include it once, in the app's one translation unit, and link ft/libft.a -- a newlib app (Letters' rule in user/Makefile is the model).

```
#include "fontkit/uikitface.h"
int main () {
    ft_uikit_install ("DejaVu Sans", 13);    // before building the widgets;
false: none (bitmap)
    Root root (...);    ...
}
```

Text is UTF-8 (a stray byte is read as Latin-1); styles 0 regular, 1 italic, 2 bold, 3 bold italic (a style the family lacks is made by fnt::). The line height is the font's (DejaVu Sans at 13 px: 16 px, as the bitmap font's), the text centred in it. More faces (a display's large digits):

```
FtTextFace *big = new FtTextFace; big->open ("DejaVu Sans", 24);    lcd->face =
big;
```

fnt::trim () may run at any moment no fnt::Font pointer is held: the face holds none between calls.

```
class FtTextFace : public uikit::TextFace
{
public:
    bool kerning;    // the pairs' kerning (on)

    FtTextFace () : kerning (true), m_fam (-1), m_px (0), m_h (16), m_asc (12)
{ reset (); }

    // The family by name (falls back to DejaVu Sans), px the size (the em, in
pixels). fnt::init ()
// is called here. False: no TrueType font on the card.
    bool open (const char *family, int px)
    {
        if (!fnt::init ()) return false;
        int fam = family ? fnt::find (family) : -1;
        if (fam < 0) fam = fnt::find ("DejaVu Sans");
        if (fam < 0) fam = 0;
        if (px < 4) px = 4;
        m_fam = fam; m_px = px;
        reset ();
        fnt::Font *f = font (0);
        if (!f) { m_fam = -1; return false; }
        int glyphs = f->ascent + f->descent;    // (1/64 px)
        m_h = (f->height + 63) >> 6;
        if (m_h * 64 < glyphs) m_h = (glyphs + 63) >> 6;
        m_asc = ((m_h * 64 - glyphs) / 2 + f->ascent + 32) >> 6;    // the glyphs
centred in the line
        return true;
    }
    int family () const { return m_fam; }
    int px () const { return m_px; }

    int height () override { return m_h; }
    int ascent () override { return m_asc; }
    int width (const char *s, int style) override { return widthN (s, 1 << 30,
style); }
```

```

// The first n bytes' width (up to a NUL): the advances and kerning in 1/64 px,
rounded -- the
// same pen draw () moves. Remembered in a small cache (a label is measured at
each redraw).

```

```

int widthN (const char *s, int n, int style) override
{
    if (!s || n <= 0 || m_fam < 0) return 0;
    style &= 3;
    unsigned h = 2166136261u; int len = 0;
    for (; len < n && s[len]; len++) h = (h ^ (unsigned char) s[len]) *
16777619u;
    if (len == 0) return 0;
    h ^= (unsigned) style * 0x9E3779B9u;
    WCache &c = m_wc[(h ^ (h >> 16)) & (WC - 1)];
    if (c.len == len && c.hash == h && c.style == style) return c.w;
    fnt::Font *f = font (style);
    if (!f) return 0;
    long x64 = 0; unsigned prev = 0;
    for (int i = 0; i < len; )
    {
        int k; unsigned cp = uikit::uk_u8_get (s + i, len - i, &k); i += k;
        if (kerning && prev) x64 += fnt::kern (f, prev, cp);
        x64 += adv (f, style, cp);
        prev = cp;
    }
    int w = (int) ((x64 + 32) >> 6);
    c.hash = h; c.len = len; c.style = style; c.w = w;
    return w;
}

```

```

void draw (uikit::Canvas &cv, int x, int yTop, const char *s, unsigned color, int
style) override

```

```

{
    if (!s || !*s || m_fam < 0) return;
    style &= 3;
    fnt::Font *f = font (style);
    if (!f) return;
    int base = yTop + m_asc, n = 0;
    while (s[n]) n++;
    long x64 = (long) x * 64; unsigned prev = 0;
    color &= 0x00FFFFFFu;
    for (int i = 0; i < n; )
    {
        int k; unsigned cp = uikit::uk_u8_get (s + i, n - i, &k); i += k;
        if (kerning && prev) x64 += fnt::kern (f, prev, cp);
        if (x64 >= (long) cv.w * 64) break; // (the rest is past the
edge)
        fnt::draw (cv, f, (int) x64, base, cp, color, 0, 0, cv.w, cv.h);
        x64 += adv (f, style, cp);
        prev = cp;
    }
}

```

private:

```

enum { WC = 128 };
struct WCache { unsigned hash; int len, style, w; };
int m_fam, m_px, m_h, m_asc;
int m_adv[4][128]; // the ASCII advances per style, 1/64 px (-1: not yet
asked)
WCache m_wc[WC];

```

```

void reset ()
{
    for (int s = 0; s < 4; s++) for (int c = 0; c < 128; c++) m_adv[s][c] = -1;
    for (int i = 0; i < WC; i++) { m_wc[i].len = -1; m_wc[i].hash = 0; }
    m_wc[i].style = 0; m_wc[i].w = 0; }
}
// uikit's style (1 italic, 2 bold) -> fnt's (BOLD 1, ITALIC 2); the sized font
asked each time
// (no pointer kept: fnt::trim may drop it between two calls).
fnt::Font *font (int style)
{
    int fs = ((style & 2) ? fnt::BOLD : 0) | ((style & 1) ? fnt::ITALIC : 0);
    return fnt::get (m_fam, fs, m_px * 64);
}
int adv (fnt::Font *f, int style, unsigned cp)
{
    if (cp < 128)
    {
        int &a = m_adv[style][cp];
        if (a < 0) a = fnt::advance (f, cp);
        return a;
    }
    return fnt::advance (f, cp);
}
};

```

Install FreeType's text for every uikit widget: the family by name ("DejaVu Sans", "Liberation Sans", "Selawik"..., DejaVu Sans when absent) at px pixels. False: no TrueType font (uikit keeps its bitmap fonts). Call it before building the widgets.

```
static FcTextFace *g_ftUIKitFace; // (the one ft_uikit_install made)
```

Installs FreeType's text for every uikit widget with the family by name (DejaVu Sans when absent) at px pixels, false when the card has no TrueType font.

```
bool ft_uikit_install (const char *family, int px);
```

The face ft\_uikit\_install made (0: none yet).

```
FcTextFace *ft_uikit_face ();
```

uikit's own dialogs in FreeType's text, in a program that does NOT install a face for all its widgets (Letters, Slides: their own interface has the bitmap text's metrics): the face is in use for the dialog's time only -- a message box, the file dialog, with their buttons and fields.

```
ft_messagebox (title, text, MB_YESNO); ft_file_open (path, sizeof path, dir);
```

A program that called ft\_uikit\_install has that face already: these then do as uikit's.

```
static FcTextFace *g_ftDialogFace; // (made at the first dialog: DejaVu Sans, 13
px)
```

The face of the dialogs (0: no TrueType font on the card -- the dialog keeps the bitmap text).

```
FcTextFace *ft_dialog_face ();
```

uikit's message box (uk\_messagebox) in FreeType's text.

```
int ft_messagebox (const char *title, const char *text, int buttons);
```

uikit's file dialogs (uk\_file\_open / uk\_file\_save / uk\_folder\_open) in FreeType's text.

```
bool ft_file_open (char *out, unsigned cap, const char *startDir, const char *filters
= 0);
bool ft_file_save (char *out, unsigned cap, const char *startDir, const char
*defName, const char *filters = 0);
bool ft_folder_open (char *out, unsigned cap, const char *startDir);
```

## fontkit/fonts.h

ft/fonts.h -- the apps' TrueType text (Letters' pages): the fonts on the card by family, at any size, their glyphs rendered by FreeType (user/Kits/fontkit/: TrueType only, anti-aliased, auto- hinted vertically) and cached. Header-only: include it once, in the app's one translation unit; link ft/libft.a (a newlib app: FreeType wants a libc).

|                                                                |                                                               |
|----------------------------------------------------------------|---------------------------------------------------------------|
| fnt::init ();                                                  | the families of SD:/res/fonts and SD:/fonts                   |
| (sorted)                                                       |                                                               |
| fnt::count (), fnt::name (i)                                   | ... their names ("Liberation Serif", "DejaVu Sans Mono"...) ) |
| fnt::find ("Liberation Sans")                                  | a family by name (-1: none)                                   |
| fnt::Font *f = fnt::get (fam, fnt::BOLD   fnt::ITALIC, size64) | a family's style at a size in 1/64 px (a style                |
| the family                                                     |                                                               |
| f->ascent, f->descent, f->height                               | lacks is made: bold thickened, italic slanted)                |
| the next)                                                      | its metrics, 1/64 px (height: from a line to                  |
| fnt::advance (f, cp)                                           | a character's advance, 1/64 px (the design's:                 |
| exact at any                                                   |                                                               |
| fnt::kern (f, a, b)                                            | size, so a line breaks the same at every zoom)                |
| fnt::draw (cv, f, x64, y, cp, c, clip...)                      | the pair's kerning, 1/64 px                                   |
| pixel)                                                         | a character at x (1/64 px: 4 positions a                      |
|                                                                | on the baseline y, in colour c, blended over                  |
| the canvas                                                     |                                                               |
| fnt::trim ()                                                   | drop the least used sizes when the cache is big               |
| (at a                                                          |                                                               |
|                                                                | moment no Font pointer is held: after a redraw)               |

A character a font lacks is taken from DejaVu Sans (the card's widest one), same style.

```
enum { BOLD = 1, ITALIC = 2 };
enum { MAXFACE = 96, MAXFAM = 48, MAXFONT = 512 };
```

## struct Glyph

```
{
    unsigned cp;           // the character (0: an empty slot)
    int gi;                // its glyph in src's face (0: none, a box drawn)
    int adv;               // advance, 1/64 px
    struct Font *src;       // the font it comes from (this one or the fallback)
    unsigned char *bmp[4]; // coverage bitmaps, one per quarter-pixel position
    (lazily)
    short bl[4], bt[4], bw[4], bh[4]; // their left / top (from the pen) / size
};
```

## struct Font

```
{
    int fam, style, size64;
    int face;              // g_face[] index used
    bool fakeBold, fakeItalic; // the style is made
    FT_Size size;
```

```

    int ascent, descent, height;    // 1/64 px (descent positive, below the baseline)
    int ulPos, ulThick;             // underline: its top below the baseline, its thickness
(1/64 px)
    int xHeight;                   // the x-height (strike-through line: at its half)
    int boldX;                     // a made bold's extra advance
    Glyph *tab; int cap, n;        // the glyphs (open addressing on cp)
    Font *fallback;                // DejaVu Sans at the same style and size (lazily; 0:
none)
    bool fbTried;
    unsigned used;                 // last get () (the least used go first)
    unsigned bytes;                // its bitmaps' size
};

```

```

struct FaceFile
{
    char path[112];
    char family[48];
    int style;                     // BOLD / ITALIC from the file's own tables
    int weight;                    // OS/2 usWeightClass (400 regular, 700 bold)
    unsigned char *data; unsigned len;
    FT_Face face;
    bool failed;
};

```

```

struct Family { char name[48]; int file[4]; }; // file[style]: g_face[] index, -1
none

```

## state

```

static FT_Library g_lib;
static bool g_init, g_ok;
static FaceFile g_face[MAXFACE]; static int g_nface;
static Family g_fam[MAXFAM]; static int g_nfam;
static Font *g_font[MAXFONT]; static int g_nfont;
static unsigned g_tick, g_bytes;
static int g_fallbackFam = -1;
static unsigned char g_gamma[256]; // coverage -> opacity (a slightly heavier stroke
on screen)

```

## small helpers

A string's length in bytes (0 for a null pointer).

```
int s_len (const char *s);
```

Copies s into d, cut to cap - 1 bytes and always ended by a 0 (a null s gives an empty string).

```
void s_cpy (char *d, const char *s, int cap);
```

An ASCII capital letter as its small letter, anything else unchanged.

```
int lc (int c);
```

Compares two strings with ASCII letters' case ignored, returning 0 when equal, else < 0 or > 0 as strcmp.

```
int s_icmp (const char *a, const char *b);
```

The big-endian 16-bit value at p.

```
unsigned be16 (const unsigned char *p);
```

The big-endian 32-bit value at p.

```
unsigned be32 (const unsigned char *p);
```

Reads n bytes of the open file f at offset pos into buf, false when the seek fails or fewer bytes come.

```
bool read_at (void *f, unsigned pos, void *buf, unsigned n);
```

A font file's family name and style from its own tables (no FreeType: 3 small reads). False: not a TrueType font.

```
bool scan_file (const char *path, FaceFile &ff);
```

True when the file name n ends in ".ttf" (letters' case ignored).

```
bool is_ttf (const char *n);
```

Adds every .ttf file of the folder dir that scan\_file accepts to g\_face (MAXFACE files at most).

```
void scan_dir (const char *dir);
```

The style slot a file fills in its family: the one it says; a family with two files for one slot (a light and a regular...) keeps the one nearest the slot's weight.

```
void add_to_family (int fi);
```

## the families

Starts FreeType and sorts the fonts of SD:/res/fonts and SD:/fonts into families (once), false when FreeType fails or no TrueType font is there.

```
bool init ();
```

The number of families init () found.

```
int count ();
```

Family i's name, "" when there is no such family.

```
const char *name (int i);
```

A family's index by its name (letters' case ignored), -1 when there is none.

```
int find (const char *n);
```

The styles a family has (a mask of 1 << style).

```
int styles (int fam);
```

A face file's FreeType face, the file read at its first use.

```
FT_Face open_face (int fi);
```

## sized fonts

Frees a font's glyph table and its bitmaps and lowers the cache's byte count (the Font itself stays).

```
void free_glyphs (Font *f);
```

Builds a family's style at size64 (1/64 px, 1 px at least) with its metrics and an empty glyph table, 0 when the family or its face file fails. A style the family lacks is made from another of its files (bold thickened, italic slanted).

```
Font *make (int fam, int style, int size64);
```

A family's style at a size (1/64 px).

```
Font *get (int fam, int style, int size64);
```

Forget the fonts not used lately when the cache holds too much (a Font from get () is then stale: only at a moment no Font pointer is held -- after a redraw; the app forgets its own, g\_onTrim).

```
static void (*g_onTrim) ();  
void trim (unsigned maxBytes = 6u << 20, int maxFonts = 96);
```

## glyphs

The glyph table's slot for the character cp, either the one holding it or the empty one where it goes.

```
Glyph *slot (Font *f, unsigned cp);
```

Doubles the glyph table and puts its glyphs back in their new slots (earlier Glyph pointers are stale).

```
void grow (Font *f);
```

A character's cached glyph entry (0 is read as a space), made at its first use with its glyph index and advance. A character the font lacks comes from DejaVu Sans (nowhere either: gi 0, half the size wide). The pointer holds until the table grows.

```
Glyph *glyph (Font *f, unsigned cp);
```

A character's advance in 1/64 px, 0 without a font.

```
int advance (Font *f, unsigned cp);
```

The kerning between the characters a and b in 1/64 px, 0 when there is none (no font, no kerning table, a glyph from the fallback font).

```
int kern (Font *f, unsigned a, unsigned b);
```

The coverage bitmap of a glyph at a quarter-pixel position.

```
void render (Font *f, Glyph *g, int ph);
```

Lays the colour c (0xRRGGBB) over the pixel d at opacity a (0..255) keeping d's top byte, or replaces d by c when a >= 255.

```
void blend (unsigned &d, unsigned c, int a);
```

A character at x64 (1/64 px) on the baseline y, in colour c, clipped to [cx0, cx1) x [cy0, cy1).

```
void draw (UIKit::Canvas &cv, Font *f, int x64, int y, unsigned cp, unsigned c, int cx0, int cy0, int cx1, int cy1);
```

A string (Latin-1 / ASCII) at x, baseline y, the pen's end returned (1/64 px). For labels.

```
int draw_str (UIKit::Canvas &cv, Font *f, int x64, int y, const char *s, unsigned c);  
int str_w (Font *f, const char *s);
```