Onyx — UIKit reference

Onyx · multi-process OS on Raspberry Pi 4

*The reference of **UIKit** (`SD:/lib/uikit.so`, `user/Kits/uikit`): what it is for, how a program uses it, and every operation it exposes. The operations' part is made from the kit's headers by `tools/docgen/kitdocs.py` — the headers are the source. Overview of all the kits: The Kits.*

Contents

1. What it is
2. Using it
3. Index
4. `uikit/uikit.h`
5. `uikit/widget.h`
6. `uikit/root.h`
7. `uikit/win.h`
8. `uikit/canvas.h`
9. `uikit/theme.h`
10. `uikit/text.h`
11. `uikit/label.h`
12. `uikit/button.h`
13. `uikit/dialog.h`
14. `uikit/adapt.h`
15. `uikit/bmp.h`
16. `uikit/calendar.h`
17. `uikit/checkbox.h`
18. `uikit/codeedit.h`
19. `uikit/colorpick.h`
20. `uikit/combobox.h`
21. `uikit/datagrid.h`
22. `uikit/dropdown.h`
23. `uikit/flat.h`
24. `uikit/font.h`
25. `uikit/form.h`
26. `uikit/global.h`
27. `uikit/groupbox.h`
28. `uikit/icon.h`
29. `uikit/imagebox.h`
30. `uikit/knob.h`
31. `uikit/lang.h`
32. `uikit/layout.h`
33. `uikit/lcd.h`

34. `uikit/listbox.h`
35. `uikit/menu.h`
36. `uikit/numeric.h`
37. `uikit/paint.h`
38. `uikit/panel.h`
39. `uikit/progress.h`
40. `uikit/radio.h`
41. `uikit/richtextbox.h`
42. `uikit/scrollbar.h`
43. `uikit/segmented.h`
44. `uikit/sidepanel.h`
45. `uikit/skin.h`
46. `uikit/slider.h`
47. `uikit/splitter.h`
48. `uikit/sysclip.h`
49. `uikit/tabhost.h`
50. `uikit/tabstrip.h`
51. `uikit/textarea.h`
52. `uikit/textbox.h`
53. `uikit/toggle.h`
54. `uikit/toolbar.h`
55. `uikit/treeview.h`
56. `uikit/vpaint.h`
57. `uikit/vumeter.h`

What it is

UIKit is the interface: the windows and their frames, the widgets, the dialogs, the theme, the icons — and the window API itself, `uk_win_*` (`uikit/win.h`, plain C functions: what speaks to the graphics server; a C program links `lib/uikit.imp_c.a`). The rest is in the namespace `uikit`. A window is a `Root`; widgets are added to it; `run ()` is the event loop.

Include	`#include "uikit/uikit.h"`
Link	`lib/uikit.imp.a`
Library	`SD:/lib/uikit.so` — 950 entries in its table (`user/Kits/uikit/uikit.abi`, append-only)
Sources	`user/Kits/uikit/`

Using it

A window is a `Root`; widgets are added to it; `run ()` is the event loop. Everything is in the namespace `uikit`.

A window, a label, a button:

```
#include "appkit/appkit.h"
#include "uikit/uikit.h"
using namespace uikit;

static Label *g_label;
static int g_count;

static void onClick (Widget &)
{
    char text[32]; int n = 0;
    ax_strcat (text, sizeof text, &n, "clicked ");
    char num[12]; ax_itoa (++g_count, num);
    ax_strcat (text, sizeof text, &n, num);
    g_label->setText (text);                          // the widget redraws itself
}

int main (void)
{
    Root root (320, 120, "Hello");                    // a decorated window
    g_label = new Label (12, 12, 296, 20, "Press the button");
    root.addChild (g_label);
    root.addChild (new Button (12, 44, 100, 28, "Click me", onClick));
    root.run ();                                      // until the window is closed
    return 0;
}
```

Dialogs are modal calls:

```
if (uk_messagebox ("Delete", "Delete this file?", MB_YESNO))
{
    char path[256];
    if (uk_file_open (path, sizeof path, "SD:/docs"))  // the file chooser
        g_label->setText (path);
}

unsigned colour = 0x2060C0;
if (uk_color_dialog (&colour, "Pick a colour")) root.setBg (colour);
```

Tabs (`TabStrip`, `uikit/tabstrip.h`): a row of closable tabs over the program's own view — the strip shows them, the program shows the chosen one's content. Each tab carries a pointer for the program; a close is only **asked** (the cross, a middle click): the program decides, then removes it.

```
static TabStrip *g_tabs;
static void onTab (Widget &)   { show (g_tabs->data (g_tabs->selected)); }
static void onClose (Widget &) { int i = g_tabs->closing; Doc *d = (Doc *) g_tabs->data (i);
                                 if (doc_close (d)) g_tabs->remove (i); }    // (a question
first, if need be)
static void onNew (Widget &)   { g_tabs->select (g_tabs->add ("Untitled", new_doc ()), true);
}
...
g_tabs = new TabStrip (0, 0, root.width, 30, onTab);
g_tabs->onClose = onClose; g_tabs->onNew = onNew;
g_tabs->anchor = ANCHOR_LEFT | ANCHOR_TOP | ANCHOR_RIGHT;
root.addChild (g_tabs);
```

`setTitle (i, s)`, `setMark (i, on)` (a dot: something runs, something new), `selectNext (±1)` (the program's Ctrl+Tab), `activeFace` (the chosen tab opens onto the content's colour). The Terminal's tabs.

The theme: draw with the palette (`C_BG`, `C_TEXT`, `C_ACCENT`, `C_FACE`…), never with fixed colours, so that the program follows the user's theme.

Text in an owner-drawn widget (`uikit/text.h`): `uk_text_fit` cuts a line with "…", `uk_text_wrap` word-wraps a paragraph into lines of a width (Stickies' cards), `uk_text_over` writes straight on a see-through window — the wallpaper — blended by coverage, with a soft shadow or engraved (the agenda's and Stickies' headers). The tool bar's icons (`uikit/toolbar.h`, `WKT_*`) include `WKT_TRASH` and `WKT_PIN`:

```
int st[6], ln[6]; bool more;
int k = uk_text_wrap (text, len, 196, 6, st, ln, &more);   // up to 6 lines of 196 px
for (int i = 0; i < k; i++) { char l[256]; int n = ln[i] < 255 ? ln[i] : 255;
    memcpy (l, text + st[i], n); l[n] = 0; uk_text (canvas, 22, 33 + 17 * i, l, ink); }
uk_text_over (canvas, 38, 9, "Pinned notes", 0x00FAFCFF, 2, 1);   // bold, a soft shadow, on the wallpaper
```

Without C++ (`uikit/flat.h`, in `uikit/uikit.h`): the same window and widgets as handles, behind plain C functions — what a BASIC program calls (`#import UIKit`), what QBStudio's generated code is made of, and what a C program can use:

```
void *win = uk_window ("Hello", 320, 120, 0);
uk_label (win, 12, 12, 200, 20, "Your name:");
void *name = uk_textbox (win, 12, 36, 200, 24, "", 0);
uk_button (win, 220, 36, 80, 24, "OK", on_ok);          /* void on_ok (void *button) */
uk_window_run (win);                                     /* until the window is closed */
```

```
#import UIKit
win = UIKit.window("Hello", 320, 120, 0)
ok = UIKit.button(win, 220, 36, 80, 24, "OK", ADDRESSOF(Clicked))
DO WHILE UIKit.window_wait(win): LOOP
```

`uk_panel (window, x, y, w, h)` is an area with widgets of its own — every maker takes the window *or a panel* as what holds the widget —: a page shown in place of another (`uk_show`), moved elsewhere (`uk_set_parent`). QBStudio's user controls are panels.

A widget added to UIKit that BASIC should reach gets its functions there (a maker, and `uk_set_text` / `uk_get_value` … taught its kind).

An icon — any picture ImageKit reads (BMP today, PNG tomorrow), given as icons are drawn (magenta = see-through):

```
#include "uikit/bmp.h"

int w, h;
unsigned *px = ui::icon_load ("SD:/apps/tinypad.app/icon.bmp", &w, &h);
if (px) { /* draw it ... */ delete [] px; }
```

A code editor (`uikit/codeedit.h`, 2026-10-06 — QBStudio's, made a widget of the kit for every program that edits code: QBStudio, Turtle Quest): BASIC in a monospaced face with its colours, the line numbers, the indentation's guides, a line lit (`hiLine`: an error's, a debugger's current line), the lines with a problem marked, undo / redo, the clipboard, the completion, UTF-8 comments:

```
CodeEdit *ed = new CodeEdit (10, 10, 400, 300);
ed->mono = myMonoFace;                  // (0: the UI's face)
```

```
ed->isKeyword = is_basic_word;          // bool (const char *w, int n): the words coloured
and put in capitals
ed->setText ("FOR i = 1 TO 3\n  PRINT i\nNEXT\n");
ed->onChange = changed;                 // Action: the text changed
root.addChild (ed);
ed->hiLine = 2; ed->showLine (1);       // line 2 lit and shown (hiLine 1-based, showLine 0-
based)
ed->clearMarks (); ed->addMark (3);     // line 3 has a problem
```

The completion: set `complete` (`void (CodeEdit &, const char *object)`), which calls `ed.addCompletion (name, kind, detail)` for each item offered after `object.` (or Ctrl+Space: `object` empty).

A timer or polling: derive from `Root` and override `onTick ()` (called about 60 times a second).

Several windows (2026-10-07, kapi v94): one more window of the program is a `Root` made with `NewWindow`; the first window's `run ()` serves them all (their events, `onTick`, drawing), a click in one makes it `Root::current ()`, its close box calls `onClose ()` (by default `closeWindow ()`; closing the first window ends the program). Telegram has one a conversation (docs/03 §6 *Several windows*).

```
class ChatWin : public Root
{
public:
    ChatWin (const char *who) : Root (NewWindow (), -1, -1, 500, 400, who) { if (!winOpened
()) return; /* its widgets */ }
    void onClose () override { closeWindow (); gone = true; }   // (deleted later, by the
main window's onTick)
    bool gone = false;
};
ChatWin *w = new ChatWin ("Alice");
if (!w->winOpened ()) { delete w; /* one window only: show it beside */ }
```

An icon in the menu bar's status area (kapi v95): `uk_tray ("SD:/apps/myapp.app/icon.bmp", "My App - 3 new")`; a double click on it shows the program's first window again (even minimised) and calls the first `Root`'s `onTray (KAPI_TRAY_OPEN)`, a right click `onTray (KAPI_TRAY_MENU)`; `uk_tray_clear ()` takes it away.

The window API (`uikit/win.h`, 2026-10-08; in `uikit/uikit.h`, or included alone by a C program, which links `lib/uikit.imp_c.a`): the program's windows and what it asks of the graphics server, as plain C functions — `uk_win_create`, `uk_win_present`, `uk_win_on_key`, `uk_win_menu_set`, `uk_win_list`, `uk_win_tray_set`, `uk_win_fullscreen_begin`… (they were AppKit's `kapi_create_window`, `kapi_present`…: docs/03 §5.10.1 has the table). A `Root` calls them for you; a game that draws its own canvas, a full-screen program or a shell program (the dock, the menu bar) calls them itself. Each graphics server has its own UIKit (the desktop's speaks to Elegant), so the same binary runs on every one; `uk_win_server` says which.

```
#include "appkit/appkit.h"
#include "uikit/win.h"

static void on_key (unsigned long sender, int ev, gui_value v) { (void) sender; if (ev ==
GUI_EVENT_KEY && v == 27) kapi_exit (0); }

int main (void)
{
    unsigned *fb = uk_win_create (320, 200, "Plasma");     /* the canvas: 0x00RRGGBB, 320 a
row */
    if (fb == 0) return 1;
    uk_win_on_key (on_key);
```

```
    for (int t = 0; !kapi_should_exit (); t++)
    {
        for (int i = 0; i < 320 * 200; i++) fb[i] = (unsigned) (i + t) * 2654435761u >> 8;
        uk_win_present ();                              /* the server shows it */
        kapi_pump_wait (16);                            /* the events (AppKit's pump) */
    }
    return 0;
}
```

The adaptive widgets (`uikit/adapt.h`, `sidepanel.h`, `form.h`, PocketUI's phase P6; docs/03 §5.10.6): the same binary runs on the desktop, in pocket and in console; the app says **what** its parts are and each UIKit shows them for its mode — on the desktop exactly as before. A navigation **SidePanel** (a rail, a drawer, a console column away from the desktop), tools with **priorities** (pocket: one row and »), **column roles** (portrait: cards), a **FormDialog** (portrait: a sheet), a field's **type**, the **size class**:

```
#include "uikit/uikit.h"
#include "uikit/toolbar.h"

SidePanel *nav = new SidePanel (0, 40, 200, 560, UK_SP_LEFT, UK_SP_NAVIGATION);
nav->addHeading ("LIBRARY");  nav->addItem (1, "Songs", WKG_HOME);  nav->setBadge (1, 12);
nav->onSelect = [] (SidePanel &, int id) { show (id); };
bar->setPriority (cut, UK_TB_IF_ROOM, 2);  bar->setPriority (settings, UK_TB_OVERFLOW);
grid->setColumnRole (0, UK_COL_PRIMARY);  grid->setColumnRole (1, UK_COL_SECONDARY);  grid-
>setColumnRole (3, UK_COL_DETAIL, 1);
uk_set_input_type (urlBox, UK_IN_URL);
void relayout () {                                      // the window's resize,
Root::onSizeClass, nav->onPresentation
    nav->place (0, 40, 200, height - 40);
    content->left = nav->reservedWidth ();              // 200 whole, 48 a rail, 0 a drawer
    if (uk_size_class () == UK_SC_NARROW) { /* portrait: the app's own choices */ }
}
FormDialog f ("New Playlist");  f.addRow ("Name:", new Textbox (0, 0, 240, 26, ""));
f.addButton ("Create", UK_FB_DEFAULT, 1);  f.addButton ("Cancel", UK_FB_CANCEL, 0);  int r =
f.run ();
```

Index

Everything the headers declare, in their order — the details are in each header's part below.

Name	What it does	Header
`uk_len`	uk_fh	`widget.h`
`uk_fw`	uk_fh	`widget.h`
`uk_fh`	uk_fh	`widget.h`
`uk_thumb`	The thumb of a trackH px track for `total` units of content, `view` of them visible, scrolled to pos, with show false when all fits (or the track is 6 px or les	`widget.h`
`uk_thumb_pos`	A cursor offset `cy` within the track -> scroll pos in [0, total-view] (thumb	`widget.h`

Name	What it does	Header
	centred).	
`uk_draw_vscroll`	Paint the bar (a groove in a shade of `bg`, the thumb a raised pill) at the right-edge gutter (x,y, w x trackH)	`widget.h`
`UkBarDrag`	A list's own scroll bar under the mouse (a widget that draws uk_draw_vscroll)	`widget.h`
`uk_cursor`	The pointer's shape (kapi v81, KAPI_CURSOR_*).	`widget.h`
`Action`	fired on click/toggle/change; gets the widget	`widget.h`
`Widget`	(a type)	`widget.h`
`uk_applet`	running as an applet? (its arguments said so)	`root.h`
`uk_pump`	the events: the window's (pump_events), an applet's host's	`root.h`
`uk_present`	what was drawn shown: uk_win_present, or told to the host	`root.h`
`uk_quit`	time to end: the close box, or the host's AP_CLOSE / its end	`root.h`
`uk_applet_send`	a message to the host	`root.h`
`uk_applet_on_message`	The host's messages other than AP_PTR / AP_KEY / AP_CLOSE (an applet's own protocol	`root.h`
`uk_tray`	(v95) The program's icon in the menu bar's status area	`root.h`
`uk_tray_clear`	(v95) The program's icon in the menu bar's status area	`root.h`
`Root`	(a type)	`root.h`
`uk_win_create`	The program's first window, a client area of w x h pixels titled title,	`win.h`

Name	What it does	Header
	placed by the server -> its canvas (0x00RRGGBB pixels, w a row), 0 on failure (no server	
`uk_win_create_ex`	The program's first window at x, y (its frame's top left	`win.h`
`uk_win_new`	Another window of the program (after its first	`win.h`
`uk_win_select`	The window the calls act on (0	`win.h`
`uk_win_destroy`	window win (> 0) closed and forgotten (the first: the program's end)	`win.h`
`uk_win_move`	its frame moved to x, y (screen coordinates)	`win.h`
`uk_win_resize`	Its client area set to w x h, within the canvas it was created with (which stays) -> the canvas, 0 no window.	`win.h`
`uk_win_resize2`	As uk_win_resize, but the canvas and the frame's copies grow past their first size when needed (new memory at the same addresses	`win.h`
`uk_win_resizable`	on != 0	`win.h`
`uk_win_alpha`	its opacity, 0 .. 255 (fades)	`win.h`
`uk_win_geometry`	Its frame's place and size, its client area's size, the work area (the screen less the menu bar and the dock) and its KAPI_WIN_* state into *out -> 0, -1 no win	`win.h`
`uk_win_chrome`	Its surfaces for the frame UIKit draws (uikit/skin.cpp)	`win.h`
`uk_win_present`	its pixels changed: the server shows them	`win.h`
`uk_win_draw_text`	One line of text in the kernel's bitmap font at x,	`win.h`

Name	What it does	Header
	y of its canvas, colour c (0x00RRGGBB), the background kept.	
`uk_win_on_key`	GUI_EVENT_KEY to fn (value: the character or KEY_*)	`win.h`
`uk_win_on_click`	GUI_EVENT_CANVAS_CLICK / _MOTION to fn (the old click handler)	`win.h`
`uk_win_on_pointer`	the whole pointer stream to fn (GUI_EVENT_PTR_*, drops, WINCTL, WINRESIZE)	`win.h`
`uk_win_cursor`	The pointer's shape over its client area (KAPI_CURSOR_*), kept until changed -> the shape it had, -1.	`win.h`
`uk_win_cursor_pos`	the pointer, relative to its client area	`win.h`
`uk_win_cursor_shown`	1 the pointer is drawn, 0 hidden (keyboard only), -1 not known	`win.h`
`uk_win_menu_set`	This program's menus (the first window's) and the handler that gets GUI_EVENT_MENU (value	`win.h`
`uk_win_menu_get`	For the menu bar	`win.h`
`uk_win_menu_command`	item id sent to the active window (MENU_QUIT: asked to close) -> 1 delivered	`win.h`
`uk_win_list`	the windows, bottom to top (at most max) -> how many	`win.h`
`uk_win_raise`	window id to the front (it gets the keys) -> 0, -1	`win.h`
`uk_win_close`	window id asked to close (as its close box) -> 0, -1	`win.h`
`uk_win_minimise`	window id (0: the caller's) minimised until raised -> 0, -1	`win.h`

Name	What it does	Header
`uk_win_place`	window id's frame moved to x, y -> 0, -1	`win.h`
`uk_win_to_desk`	Window id (0	`win.h`
`uk_win_desk`	The workspaces	`win.h`
`uk_win_read`	The pixels of a rectangle of window id's client area (part 0) or of its frame (1 active, 2 inactive) into dst (stride pixels a row), clipped to it -> 0, -1.	`win.h`
`uk_win_apps`	The names of the open apps (a window on the current workspace, not a WIN_FLAG_SYSTEM one), one a line -> how many.	`win.h`
`uk_win_app_raise`	app name's window to the front -> 1, 0 not running / no window	`win.h`
`uk_win_app_toggle`	App name toggled -> 0 it was running and is asked to close, 1 it was started, -1 on error.	`win.h`
`uk_win_wallpaper_buffer`	the screen-sized wallpaper to draw into -> its pixels, 0	`win.h`
`uk_win_wallpaper_commit`	... drawn: shown	`win.h`
`uk_win_wallpaper_generate`	the server's own Voronoi wallpaper	`win.h`
`uk_win_drag_begin`	A drag from this window while the left button is held	`win.h`
`uk_win_drag_data`	the last drop's payload (cap bytes) -> its length	`win.h`
`uk_win_tray_set`	This program's icon (KAPI_TRAY_PX square, 0xTTRRGGBB) and tip	`win.h`
`uk_win_tray_clear`	This program's icon (KAPI_TRAY_PX square, 0xTTRRGGBB) and tip	`win.h`
`uk_win_tray_list`	for the menu bar: the icons -> how many	`win.h`
`uk_win_tray_icon`	... one's pixels -> 1, 0	`win.h`

Name	What it does	Header
`uk_win_tray_activate`	... clicked (KAPI_TRAY_OPEN, _MENU) -> 1, 0	`win.h`
`uk_win_wheel_get`	lines scrolled a notch, system-wide	`win.h`
`uk_win_wheel_set`	... set (1 .. 16; the theme editor keeps it in theme.txt)	`win.h`
`uk_win_fullscreen_begin`	The display for this program alone (the server told, then the kernel's kapi_fullscreen_begin) -> the screen's pixels (*w x *h	`win.h`
`uk_win_fullscreen_end`	The display for this program alone (the server told, then the kernel's kapi_fullscreen_begin) -> the screen's pixels (*w x *h	`win.h`
`uk_win_server_info`	(a type)	`win.h`
`uk_win_server`	The server this program's UIKit speaks to (each server has its UIKit) -> 1, 0 none runs (*out then says what the desktop would be).	`win.h`
`uk_shell_register`	The desktop's UIKit answers -KAPI_ENOSYS to each	`win.h`
`uk_shell_events`	The windows' news to fn, as events UK_SHELL_EVENT (value	`win.h`
`uk_shell_keys`	The system keys the shell takes before the front app (UK_SHELL_KEY each	`win.h`
`uk_shell_grab`	While on	`win.h`
`uk_shell_thumb`	Window id's client area as last presented, scaled to w x h (at most 512 x 512) into dst (w a row) -> 1, 0 no such window, -1 refused.	`win.h`

Name	What it does	Header
`uk_shell_front`	front 1	`win.h`
`uk_shell_split`	two programs' windows side by side (0 0: none) -> 1, 0 the work area is too small or upright (PocketUI: P8)	`win.h`
`uk_shell_dim`	a dim behind an overlay -- (not yet: the overlays draw theirs)	`win.h`
`uk_shell_task`	The running programs, the most recently in front first	`win.h`
`uk_shell_tasks`		`win.h`
`create_window`	Friendly aliases used by the demos (they were appkit.h's).	`win.h`
`present`	Friendly aliases used by the demos (they were appkit.h's).	`win.h`
`Canvas`	(a type)	`canvas.h`
`UIKIT_VAR`	an app's background (its face)	`theme.h`
`uk_style_palette`	UK_STYLE_MILK: Milk's; any other value: CDE's	`theme.h`
`uk_theme_palette`	a named theme's colours (its own, else its style's)	`theme.h`
`uk_theme_load`	(uikit::init () calls it; idempotent)	`theme.h`
`uk_theme_reload`	read SD:/etc/theme.txt again (a new theme applied: the dock)	`theme.h`
`uk_theme_face`	the palette's shades from a face colour (a preview)	`theme.h`
`UkTheme`	(a type)	`theme.h`
`uk_theme_take_style`	A theme's style changed (a scheme chosen)	`theme.h`
`uk_theme_take`	A named theme chosen (uk_themes[theme])	`theme.h`
`uk_theme_defaults`	A named theme chosen (uk_themes[theme])	`theme.h`
`uk_theme_parse`	theme.txt's keys over t	`theme.h`

Name	What it does	Header
`uk_theme_get`	the palette in use	`theme.h`
`uk_theme_set`	... made this one (every shade computed)	`theme.h`
`uk_theme_write`	theme.txt's text -> its length	`theme.h`
`TextFace`	uikit/text.h -- the text-rendering hook	`text.h`
`UIKIT_VAR`	(the face in use: uk_textface ())	`text.h`
`uk_set_textface`	install a face; 0: back to the bitmap fonts	`text.h`
`uk_textface`	The face uk_set_textface installed, 0 while the bitmap fonts are in use.	`text.h`
`UkFaceScope`	Another face for the time of a scope -- a widget's own captions, a display's large digits --, the one before back at its end.	`text.h`
`uk_bfw`	The bitmap fonts' cell (the kernel's font	`text.h`
`uk_bfh`	The bitmap fonts' cell (the kernel's font	`text.h`
`uk_tw`	The width of s as Canvas::text draws it (no face	`text.h`
`uk_tw_n`	The width of s as Canvas::text draws it (no face	`text.h`
`uk_tpos`	The place (a byte index <= n, a character's start) whose caret is the nearest to x px from the text's start	`text.h`
`uk_text`	s at (x, y) -- the line's top-left -- in `style` (the bitmap path	`text.h`
`uk_text_clip`	...	`text.h`
`uk_text_fit`	Fit s into w px (a copy in out, cap bytes)	`text.h`
`uk_text_wrap`	Word-wrap the first n bytes of s into lines of w	`text.h`

Name	What it does	Header
	px at most, maxLines at most	
`uk_text_over`	s at (x, y) -- the line's top-left -- straight over a see-through canvas (a WIN_FLAG_ALPHA window	`text.h`
`uk_u8_len`	A sequence's length from its first byte and what follows it (1 for a byte that does not start a valid sequence	`text.h`
`uk_u8_get`	The character at s (its length in *len), a stray byte as its Latin-1 character.	`text.h`
`uk_u8_next`	The next / the previous character's start from byte i (of n).	`text.h`
`uk_u8_prev`	The next / the previous character's start from byte i (of n).	`text.h`
`uk_u8_put`	cp written as UTF-8 into o (4 bytes room) -> its length.	`text.h`
`uk_u8_key`	A typed key as the text widgets store it with a face	`text.h`
`Label`	uikit/label.h -- non-interactive text on a solid background.	`label.h`
`Button`	uikit/button.h -- a push button (the theme's raised face, as a drop-down's	`button.h`
`Modal`	uikit/dialog.h -- modal dialogs as uikit objects.	`dialog.h`
`MessageBox`	(a type)	`dialog.h`
`FileDialog`	The file dialog (uk_file_open / uk_file_save / uk_folder_open show it)	`dialog.h`
`ColorDialog`	Colour dialog (WPF-style	`dialog.h`

Name	What it does	Header
	ColorPicker dialog)	
`PopupMenu`	Convenience	`dialog.h`
`uk_messagebox`	modal; buttons: MB_* -> 1 OK / Yes, 0 Cancel / No / Esc (2: Yes-No-Cancel's No)	`dialog.h`
`uk_file_open`	The file dialogs	`dialog.h`
`uk_file_save`	with a name box (defName in it)	`dialog.h`
`uk_folder_open`	pick a directory	`dialog.h`
`uk_color_dialog`	true = OK (*color set)	`dialog.h`
`uk_size_class`	UK_SC_REGULAR (the desktop), UK_SC_COMPACT, UK_SC_NARROW, UK_SC_CONSOLE	`adapt.h`
`uk_mode`	UK_MODE_DESKTOP, UK_MODE_POCKET, UK_MODE_CONSOLE	`adapt.h`
`uk_compact`		`adapt.h`
`UkMetrics`	(a type)	`adapt.h`
`uk_metrics`		`adapt.h`
`uk_scroll_gutter`	UK_SBW (10) on the desktop, 0 under the overlay bars (pocket, console)	`adapt.h`
`uk_lp`	logical pixels at the metrics' scale (v on the desktop)	`adapt.h`
`uk_logical_units`	The app draws only through UIKit (its widgets and Canvas' methods)	`adapt.h`
`uk_logical_units_on`	The app draws only through UIKit (its widgets and Canvas' methods)	`adapt.h`
`uk_set_input_type`	any widget that takes text (a Textbox, a terminal's view...)	`adapt.h`
`uk_input_type`	UK_IN_* (a Textbox with `password` set: UK_IN_PASSWORD; else	`adapt.h`

Name	What it does	Header
	UK_IN_TEXT)	
`uk_focus_move`	The focus moved from the focused control of root's tree to the nearest focusable one in that direction (dx, dy	`adapt.h`
`icon_load`	The picture of a file (new[]	`bmp.h`
`bmp_decode`	(the name the programs knew	`bmp.h`
`Calendar`	uikit/calendar.h -- Calendar	`calendar.h`
`DatePicker`	(a type)	`calendar.h`
`Checkbox`	uikit/checkbox.h -- a box + check mark + label	`checkbox.h`
`CodeEdit`	(a type)	`codeedit.h`
`ColorPicker`	uikit/colorpick.h -- a colour swatch	`colorpick.h`
`Combobox`	uikit/combobox.h -- an editable Textbox with a drop-down list of suggestions (WinForms ComboBox, DropDown style)	`combobox.h`
`DataGrid`	(a type)	`datagrid.h`
`Dropdown`	uikit/dropdown.h -- a non-editable drop-down list (the sibling of Combobox, same look)	`dropdown.h`
`uk_draw_option_list`	The open list of a drop-down (Dropdown, Combobox)	`dropdown.h`
`uk_event`	a widget's event: the widget it comes from	`flat.h`
`uk_resized`	uikit/flat.h -- UIKit for a program that is not C++	`flat.h`
`uk_chosen`	a menu item chosen	`flat.h`
`uk_window`	the program's window (w x h: its inside); 0: none	`flat.h`
`uk_window_run`	the events, until the window is closed (its box, uk_window_close)	`flat.h`

Name	What it does	Header
`uk_window_step`	... one round of them, for a program with its own loop: 0 once closed	`flat.h`
`uk_window_wait`	... one round and the wait before the next (16 ms): WHILE uk_window_wait (w) ... WEND	`flat.h`
`uk_window_close`	uk_window_run returns, uk_window_step gives 0	`flat.h`
`uk_window_width`		`flat.h`
`uk_window_height`		`flat.h`
`uk_window_min_size`	the smallest a resizable window goes	`flat.h`
`uk_window_on_resize`	after the user resized it: place the widgets again	`flat.h`
`uk_panel`	What holds a widget -- the `window` every maker takes -- is the window itself or a panel	`flat.h`
`uk_set_parent`	the widget taken from what holds it and put into a window or a panel	`flat.h`
`uk_width`	a widget's, a panel's, the window's size	`flat.h`
`uk_height`	What holds a widget -- the `window` every maker takes -- is the window itself or a panel	`flat.h`
`uk_label`	What holds a widget -- the `window` every maker takes -- is the window itself or a panel	`flat.h`
`uk_button`	What holds a widget -- the `window` every maker takes -- is the window itself or a panel	`flat.h`
`uk_textbox`	What holds a widget -- the `window` every maker takes -- is the window itself or a panel	`flat.h`
`uk_checkbox`	What holds a widget -- the `window` every maker	`flat.h`

Name	What it does	Header
	takes -- is the window itself or a panel	
`uk_listbox`	items: "one|two|three"	`flat.h`
`uk_dropdown`	What holds a widget -- the `window` every maker takes -- is the window itself or a panel	`flat.h`
`uk_slider`	from 0 to max	`flat.h`
`uk_progress`	What holds a widget -- the `window` every maker takes -- is the window itself or a panel	`flat.h`
`uk_set_range`	a slider, a progress bar: its ends	`flat.h`
`uk_set_text`	A widget's text	`flat.h`
`uk_get_text`	A widget's text	`flat.h`
`uk_set_value`	Its number	`flat.h`
`uk_get_value`	Its number	`flat.h`
`uk_add_item`	a list: one more item	`flat.h`
`uk_clear_items`	a list: emptied	`flat.h`
`uk_item_count`	a list, a drop-down	`flat.h`
`uk_move`	Its number	`flat.h`
`uk_show`	Its number	`flat.h`
`uk_enable`	Its number	`flat.h`
`uk_shown`	Its number	`flat.h`
`uk_enabled`	Its number	`flat.h`
`uk_focus`	Its number	`flat.h`
`uk_menu_item`	One more item in the menu `title` (made at its first item)	`flat.h`
`uk_message`	buttons 0 OK, 1 OK Cancel, 2 Yes No, 3 Yes No Cancel -> 1 OK / Yes, 0 Cancel / No (3: 2 for No)	`flat.h`
`uk_ask_open`	the file chosen ("": none); good until the next call	`flat.h`
`uk_ask_save`		`flat.h`
`Font`	uikit/font.h -- Font	`font.h`
`init`	load the theme	`font.h`

Name	What it does	Header
	(SD:/etc/theme.txt) and the font families; only the first call works	
`font`	the family for `id`, or Sans if it isn't loaded	`font.h`
`draw_text`	Draw `s` into a raw 0x00RRGGBB framebuffer (W x H) via the font registry -- for app-drawn windows that don't own a uikit Canvas.	`font.h`
`FormDialog`	(a type)	`form.h`
`GroupBox`	uikit/groupbox.h -- GroupBox	`groupbox.h`
`Icon`	uikit/icon.h -- a magenta-keyed BMP centred above an optional label	`icon.h`
`ImageBox`	(a type)	`imagebox.h`
`Knob`	uikit/knob.h -- Knob	`knob.h`
`uk_tr`	the translation, else en itself	`lang.h`
`uk_trc`	"ctx|en"'s, else en's, else en	`lang.h`
`uk_lang_init`	the system's language loaded -- before the UI is built	`lang.h`
`uk_lang_load`	that language's catalogues ("en": none) -> false: none found	`lang.h`
`uk_lang`	the language in use: "en", "fr"...	`lang.h`
`uk_lang_chosen`	the system's (locale_language: "en" when none is said)	`lang.h`
`uk_lang_choose`	the system's language changed (locale_set_language; taken by the programs started next)	`lang.h`
`VerticalStackPanel`	uikit/layout.h -- automatic layout containers (Panels that re-	`layout.h`

Name	What it does	Header
	flow their children on resize and on child add/remove, via the Widget::layout() hook).	
`HorizontalStackPanel`	(a type)	`layout.h`
`UniformGridLayout`	(a type)	`layout.h`
`LcdDisplay`	uikit/lcd.h -- LcdDisplay	`lcd.h`
`ListBox`	uikit/listbox.h -- ListBox	`listbox.h`
`MenuAction`	a menu item's callback (chosen in the bar, or its shortcut typed)	`menu.h`
`Menu`	(a type)	`menu.h`
`NumericUpDown`	uikit/numeric.h -- NumericUpDown	`numeric.h`
`uk_paint_alpha`	The alpha mode	`paint.h`
`uk_blend_px`	One pixel of c at opacity a (0..255) over what the canvas holds (the alpha mode heeded).	`paint.h`
`uk_tone`	the grey profile: 128 = c, 255 = white, 0 = black	`paint.h`
`uk_mix`	t = 0 (a) .. 256 (b)	`paint.h`
`uk_over`	0..255 (0.30 R + 0.59 G + 0.11 B)	`paint.h`
`uk_ink_on`	dark or white text on c	`paint.h`
`uk_corner`	the table for radius r (clamped to 1..16), computed once and kept	`paint.h`
`uk_rbox`	fill a rounded box with a vertical gradient, top to bottom	`paint.h`
`uk_rline`	Its 1-px outline in colour c at opacity alpha.	`paint.h`
`uk_framed`	The push button in the box, from its face colour	`paint.h`
`uk_raised`	A raised face (a header, a tab, a handle, a scroll bar's thumb)	`paint.h`
`uk_sunken`	A sunken field (a text box, a list, a display)	`paint.h`
`uk_etch_h`	An etched line (a groove	`paint.h`

Name	What it does	Header
`uk_etch_v`	An etched line (a groove	`paint.h`
`uk_etch_box`	An etched rounded frame (a group box's), the same groove all round.	`paint.h`
`uk_check_mark`	The controls' marks, s x s at (x, y) (state	`paint.h`
`uk_radio_mark`	The controls' marks, s x s at (x, y) (state	`paint.h`
`uk_switch_mark`	The controls' marks, s x s at (x, y) (state	`paint.h`
`uk_scroll_bar`	A scroll bar in the box	`paint.h`
`uk_slider_mark`	A slider's groove (the accent up to `fill` px) and its knob at `kx` (a raised rounded thumb), across w x h.	`paint.h`
`uk_progress_bar`	A bar that fills (a progress bar)	`paint.h`
`uk_popup`	A floating panel (a drop-down list, a menu, a drawer, a tooltip)	`paint.h`
`uk_corner_key`	Set the pixels of the box's rounded corners that are mostly outside to the magenta key.	`paint.h`
`uk_hilite`	A highlighted row (a selection, the item under the pointer)	`paint.h`
`uk_hilite_ink`	A highlighted row (a selection, the item under the pointer)	`paint.h`
`uk_title_strip`	A small window-like title strip (a dialog's)	`paint.h`
`uk_bead`	A glossy bead d x d at (x, y) in colour c (the Milk theme's title buttons, as OS X's)	`paint.h`
`uk_glyph`	A glyph centred on (cx, cy), about `size` px across, in colour c.	`paint.h`
`uk_text_c`	The theme's text in a box	`paint.h`
`uk_text_l`	The theme's text in a box	`paint.h`

Name	What it does	Header
`uk_ink_for`	The text colour for a background	`paint.h`
`uk_text_w`	The text colour for a background	`paint.h`
`Panel`	uikit/panel.h -- a plain container with a solid background	`panel.h`
`Progress`	uikit/progress.h -- non-interactive bar, fills proportionally.	`progress.h`
`RadioButton`	uikit/radio.h -- RadioButton	`radio.h`
`uk_radio_checked`	The checked button of `group` among parent's children (0 = none).	`radio.h`
`RtStyle`	Unpacked character style (public API + the "current typing style").	`richtextbox.h`
`rt_pack`	RtStyle -> packed u32	`richtextbox.h`
`rt_unpack`	packed u32 -> RtStyle	`richtextbox.h`
`rt_color`	palette index -> 0x00RRGGBB	`richtextbox.h`
`RichTextBox`	(a type)	`richtextbox.h`
`Scrollbar`	uikit/scrollbar.h -- draggable thumb (vertical or horizontal), value in [0,vmax].	`scrollbar.h`
`SegmentedControl`	uikit/segmented.h -- SegmentedControl	`segmented.h`
`SpIconFn`	The app's icons	`sidepanel.h`
`SidePanel`	(a type)	`sidepanel.h`
`uk_tint`	Multiply a 0x00RRGGBB pixel by a 0x00RRGGBB tint (per channel /255).	`skin.h`
`Skin`	(a type)	`skin.h`
`uk_decorate_window`	Draw the window's frame (the modernised CDE	`skin.h`
`uk_window_state`	set the frame's state (UK_WIN_* flags) for the next uk_decorate_window	`skin.h`
`uk_window_flags`	the UK_WIN_* flags last	`skin.h`

Name	What it does	Header
	set (0 at start)	
`uk_draw_frame`	A frame as uk_decorate_window draws it, into any W x H buffer (T	`skin.h`
`Slider`	uikit/slider.h -- horizontal value in [vmin,vmax]	`slider.h`
`Splitter`	(a type)	`splitter.h`
`HSplitter`	(a type)	`splitter.h`
`VSplitter`	(a type)	`splitter.h`
`uk_clip_ready`	SystemKit is there (false: no clipboard -- the field does nothing)	`sysclip.h`
`TabHost`	uikit/tabhost.h -- a section that hosts several "tasks" (apps) and shows ONE at a time, chosen from a popup menu in its header (the activity-shell tab strip, po	`tabhost.h`
`TabStrip`	(a type)	`tabstrip.h`
`Textarea`	uikit/textarea.h -- multi-line editable text (own '\n'-separated buffer), caret-driven vertical+horizontal scroll, click to position.	`textarea.h`
`Textbox`	uikit/textbox.h -- single-line editable field	`textbox.h`
`ToggleSwitch`	uikit/toggle.h -- ToggleSwitch	`toggle.h`
`uk_tool_glyph`	draw the icon `kind` (WKT_*); size: 6 px at least	`toolbar.h`
`ToolIconFn`	An app's icon	`toolbar.h`
`ToolButton`	(a type)	`toolbar.h`
`ToolBar`	(a type)	`toolbar.h`
`TreeView`	uikit/treeview.h -- TreeView	`treeview.h`
`V`	uikit/vpaint.h -- shapes from their geometry, anti-aliased	`vpaint.h`

Name	What it does	Header
`uk_sin`	sin and cos of an angle in degrees, x 16384.	`vpaint.h`
`uk_cos`	sin and cos of an angle in degrees, x 16384.	`vpaint.h`
`VPath`	(a type)	`vpaint.h`
`uk_q16_to_cdb`	A linear level (65536 = 1.0 = 0 dBFS) -> 1/100 dB (0 -> -20000).	`vumeter.h`
`VuMeter`	(a type)	`vumeter.h`

`uikit/uikit.h`

uikit/uikit.h -- umbrella header for the uikit widget toolkit. Apps:

```
  #include "uikit/uikit.h"          (declarations)
  ... build a tree of uikit::Widget subclasses, root.run() ...
  and link uikit/libuikit.a         (the compiled toolkit).
```

The toolkit is a recursive, retained-mode widget tree (port of VMKernel's GUI_ELEMENT/GIMAGE): every Widget owns a Canvas; damage propagates up (valid / shouldRedraw); draw() recomposes only dirty subtrees; handleMouse() routes down with coordinate conversion; the Root adopts the kapi window canvas and presents.

(uikit/toolbar.h -- ToolBar, ToolButton, the WKT_* icons -- is included by the app itself: Letters, the Spreadsheet and Cardfile have their own ToolBar / ToolButton next to `using namespace uikit`.)

`uikit/widget.h`

uikit/widget.h -- Widget: the base node of the recursive tree (port of VMKernel's GUI_ELEMENT). Owns a Canvas; lives in a sibling linked-list tree. Subclasses override the virtual onDraw/onMouse/onKey. Two damage bits drive lazy recompose:

```
  shouldRedraw = MY content changed (repaint me) ; valid = my subtree is current.
```

shared helpers + theme palette (ported from uikit's Ui defaults)

uk_fh: the line height widgets lay text out with; uk_fw: a character's width (a digit's with a proportional face installed -- measure real text with uk_tw / uk_text_w).

```
int uk_len (const char *s);
int uk_fw  ();
int uk_fh  ();
```

(the palette -- C_BG, C_FACE, C_TEXT, C_ACCENT, C_FIELD... -- is the theme's: uikit/theme.h)

integrated vertical scrollbar (Textarea / RichTextBox)

A widget that scrolls its own content reserves UK_SBW px on its right edge and shows a draggable thumb there only when the content overflows. uk_thumb computes the thumb rect; uk_thumb_pos is the drag inverse; uk_draw_vscroll paints it.

```
static const int UK_SBW = 10;           // reserved right-edge gutter width

struct UkThumb { bool show; int y, h; };    // thumb top/height within a track of trackH px
```

The thumb of a trackH px track for `total` units of content, `view` of them visible, scrolled to pos, with show false when all fits (or the track is 6 px or less).

```
UkThumb uk_thumb (long total, long view, long pos, int trackH);
```

A cursor offset `cy` within the track -> scroll pos in [0, total-view] (thumb centred).

```
long uk_thumb_pos (int cy, int trackH, long total, long view, int thumbH);
```

Paint the bar (a groove in a shade of `bg`, the thumb a raised pill) at the right-edge gutter (x,y, w x trackH); hot: pointed / dragged.

```
void uk_draw_vscroll (Canvas &cv, int x, int y, int w, int trackH, const UkThumb &t, unsigned
bg, bool hot = false);
```

A list's own scroll bar under the mouse (a widget that draws uk_draw_vscroll): its thumb dragged, a press on its groove a page up / down. The bar: barW px from barX, its track trackH px from ty; total / view / *pos in the list's units (rows, px). Called from onMouse before the rows are looked at: true = the bar took the event (*pos may have moved: repaint, and leave the rows alone). The thumb held goes on following the pointer outside the bar (mx < 0: the pointer left, it is let go).

```
struct UkBarDrag
{
    bool held, wasDown;
    UkBarDrag () : held (false), wasDown (false) {}
    bool mouse (int mx, int my, int bl, int barX, int barW, int ty, int trackH, long total,
long view, long *pos)
    {
        bool down = bl != 0, press = down && !wasDown;
        wasDown = down;
        if (held)
        {
            if (!down || mx < 0) held = false;
            else { UkThumb t = uk_thumb (total, view, *pos, trackH); *pos = uk_thumb_pos (my
- ty, trackH, total, view, t.h); }
            return true;
        }
        if (total <= view || mx < barX || mx >= barX + barW || my < ty || my >= ty + trackH)
return false;
        if (press)
        {
            UkThumb t = uk_thumb (total, view, *pos, trackH);
            int cy = my - ty;
            if (cy >= t.y && cy < t.y + t.h) held = true;
            else
            {
                long p = *pos + (cy < t.y ? -view : view), most = total - view;
                *pos = p < 0 ? 0 : p > most ? most : p;
            }
        }
        return true;
    }
};
```

The pointer's shape (kapi v81, KAPI_CURSOR_*). A widget asks for its shape from its onMouse, each time the pointer moves over it: uk_cursor (KAPI_CURSOR_TEXT) in a text field, _HAND over a link, _SIZE_H on a column's edge... Root::ptrEvent (root.cpp) starts each pointer event with the arrow and tells the kernel when what the widgets asked for has changed -- so a widget that asks nothing shows the arrow, and nobody has to put it back.

```
void uk_cursor (int shape);

class Widget;
class RadioButton;
typedef void (*Action) (Widget &);      // fired on click/toggle/change; gets the widget
```

Anchors (WinForms-style): which parent edges a child keeps a constant distance to as the parent resizes. The DEFAULT container layout() honours these so a child resizes / repositions passively (the app never recomputes geometry on resize):

```
  LEFT+RIGHT  -> width stretches      | LEFT only  -> pinned left (default, fixed w)
  TOP+BOTTOM  -> height stretches     | RIGHT only -> rides the right edge (reposition)
  FILL        -> stretches both       | BOTTOM only-> rides the bottom edge (reposition)
```

Resizing an anchored child cascades into ITS layout() (e.g. a grid re-flows its keys).

```
enum {
    ANCHOR_LEFT = 1, ANCHOR_TOP = 2, ANCHOR_RIGHT = 4, ANCHOR_BOTTOM = 8,
    ANCHOR_FILL = ANCHOR_LEFT | ANCHOR_TOP | ANCHOR_RIGHT | ANCHOR_BOTTOM
};

class Widget
{
public:
    Canvas   canvas;
    int  left, top, width, height;  // geometry RELATIVE to the parent
    int  scrollX, scrollY;      // content offset (scrollview)
    int  tag;               // app/dialog-defined id (e.g. dialog button result)
    int  colSpan, rowSpan;      // cells spanned in a UniformGridLayout (default 1)
    int  anchor;            // ANCHOR_* mask (default LEFT|TOP = pinned top-left)
    int  lytW, lytH;            // my size at the last layout (for anchor deltas)
    bool     transparent;           // blit me with the magenta key?
    bool     valid;             // subtree composited & current  (IsValid)
    bool     shouldRedraw;          // my own content needs repaint   (ShouldRedraw)
    bool     hidden;            // skip me in composite + hit-test (e.g. an inactive tab)
    bool     hasFocus, canFocus, catchOutside;
    bool     modal;             // a modal child captures ALL of the parent's input
    bool     disabled, hover, pressed;  // interaction state (widgets use these)
    const char *tip;            // tooltip text (0 = none): Root shows it after a hover pause

    Widget  *parent, *firstChild, *lastChild, *prevSib, *nextSib;
    Widget  *prevHandled;           // last child that took the mouse (for mouse-leave)
    // The reserve (uikit is a shared library: uikit/abi.h). Programs allocate and derive
widgets with
    // the layout they were built with: a field added by a later version of the library goes
HERE
    // (or behind `ext`, which the library may allocate) -- never in the middle of a class,
never
    // at the end of a derived one.
    void    *ext = 0;
    unsigned long reserved_[4] = { 0, 0, 0, 0 };
```

```
    Widget (int l, int t, int w, int h);
    virtual ~Widget ();

    // ---- damage ------------------------------------------------------------
    void invalidate (bool redraw);      // redraw=true: repaint me; false: just recompose up
    virtual void resizeTo (int w, int h);   // virtual: a surface-backed view overrides to
pin its size
    void setBounds (int w, int h);      // resize the LOGICAL size (no canvas realloc) +
relayout;
                        // for surface-backed widgets (adopted over-allocated buffer)

    // ---- tree --------------------------------------------------------------
    void addChild    (Widget *c);
    void removeChild (Widget *c);
    void bringToFront ();           // move me last in z-order (topmost)

    // ---- recursive composite + event routing -------------------------------
    void draw ();               // recompose this subtree's canvas (lazy)
    bool handleMouse (int mx, int my, int bl, int br, int bm, int wheel);   // (mx,my) local
    bool handleKey   (long k);

    // ---- focus -------------------------------------------------------------
    void clearFocusTree ();
    void focusPathUp ();
    void setFocus ();           // focus me (clear the tree, light up my path)
    // Tab / Shift+Tab (back): the focus to the next / previous control of this subtree, in
the
    // order they were added (depth first; hidden or disabled ones skipped, the ends wrap).
fields:
    // only the text fields (isField). Done by handleKey when no one takes the Tab: in a
dialog
    // (a modal) every control; in a window, from a text field to the next text field.
    bool tabFocus (bool back, bool fields);

    // ---- overridables ------------------------------------------------------
    virtual void onDraw () {}                   // paint own content into `canvas`
    virtual bool onMouse (int, int, int, int, int, int) { return false; }
    virtual bool onKey (long) { return false; }
    virtual RadioButton *asRadio () { return 0; }   // (no RTTI) a RadioButton says so
    virtual bool isField () { return false; }   // a text field (Textbox and kin): a Tab stop
in a window
    virtual void onTabFocus () {}           // focused by Tab (a field: its caret at the end)
    // The colour behind this widget (its parent's background): what its rounded, anti-
aliased
    // corners blend into. A container with its own background returns it.
    virtual unsigned bgColor () { return parent ? parent->bgColor () : C_BG; }
    // Reposition/resize children on resize / child add/remove. The DEFAULT applies the
    // children's ANCHOR_* (passive resize); layout containers (Splitter, StackPanel,
    // UniformGridLayout, TabHost) override with explicit placement. Never call directly.
    virtual void layout ();
    // The reserve of virtual functions (uikit/abi.h): a program's vtables are built by its
compiler
    // with the slots of the headers it was built with. A virtual added to Widget by a later
version
    // of the library TAKES ONE OF THESE (renamed, same place): an older program's widgets
then
    // answer with this empty default. Never add a virtual anywhere else in an exposed class.
    virtual void uk_reserved0 () {}
    virtual void uk_reserved1 () {}
```

```
    virtual void uk_reserved2 () {}
    virtual void uk_reserved3 () {}
    virtual void uk_reserved4 () {}
    virtual void uk_reserved5 () {}
    virtual void uk_reserved6 () {}
    virtual void uk_reserved7 () {}
};
```

uikit/root.h

uikit/root.h -- the top widget, bound to the kapi WINDOW canvas. Runs the event loop: feeds the kapi pointer/key streams into handleMouse/handleKey, and recomposes + uk_win_present()s only when the tree is dirty (valid==false).

The loop's three steps, the same for a window and for an applet (a Control Panel applet: applet_proto.h -- the app started with "--applet " draws into the host's pane instead of a window of its own; a Root made then adopts that surface). Root::run and the modal dialogs go through them; an app with its own loop should too.

```
bool uk_applet ();              // running as an applet? (its arguments said so)
void uk_pump ();                // the events: the window's (pump_events), an applet's host's
void uk_present ();         // what was drawn shown: uk_win_present, or told to the host
bool uk_quit ();                // time to end: the close box, or the host's AP_CLOSE / its
end
bool uk_applet_send (int type, const void *data = 0, unsigned len = 0); // a message to the
host
```

The host's messages other than AP_PTR / AP_KEY / AP_CLOSE (an applet's own protocol: Jet's web view, Apps/jet/webview_proto.h) given to fn (data NUL-terminated after its len bytes), from uk_pump. A host other than the Control Panel names its IPC service: "--applet " (the applet ends when that service is gone).

```
void uk_applet_on_message (void (*fn) (int type, const void *data, int len));
```

(v94) A program's other windows (docs/MULTI-WINDOW-STUDY.md): a Root made with NewWindow is one more window of the program (uk_win_new, uikit/win.h), beside the first Root (its main window). The first Root's run () / step () serves every one: their events (routed by the window they are for), their onTick, their drawing. Its close box asks onClose () (the default: closeWindow ()); the program's end is still the first window's close.

```
struct NewWindow {};
```

(v95) The program's icon in the menu bar's status area: a picture file (an app's icon.bmp: brought to KAPI_TRAY_PX square, its magenta see-through) and a tip -> true; false (an older system, no picture). A double click on it shows the program's first window again (even minimised) and calls its onTray (KAPI_TRAY_OPEN); a right click onTray (KAPI_TRAY_MENU). uk_tray_clear: taken away (the program's end does it too).

```
bool uk_tray (const char *picture, const char *tip);
void uk_tray_clear ();

class Root : public Widget
{
public:
    unsigned bg;                // client-area background colour
    Root (int w, int h, const char *title);             // decorated window
```

```
    Root (int x, int y, int w, int h, const char *title, unsigned flags); // positioned /
borderless
    // (v94) Another window of the program (x, y negative: placed by the system). If it
cannot be
    // made (no graphics server's windows left, no memory), winOpened () says false (nothing
is drawn).
    Root (NewWindow, int x, int y, int w, int h, const char *title, unsigned flags = 0);
    int winNumber () const { return (int) m_reserved[0]; }  // its number in the program (0:
the first)
    bool winOpened () const { return m_reserved[1] == 0; }  // (false: not made, or closed)
    void closeWindow ();            // this window closed (not the first: the program ends
then)
    void winSelect ();              // the window calls (uk_win_*) act on this window
(uk_win_select)
    static Root *winFirst ();           // the program's first window
    static int winCount ();         // how many windows are open
    static void paintAll ();        // every window that changed drawn and shown
    void setBg (unsigned c) { bg = c; invalidate (true); }
    unsigned bgColor () override { return bg; }
    void onDraw () override;
    void run ();
    bool step ();               // one round of run (): false once it is time to end (attach
() first)
    void attach ();             // hook the kapi pointer / key streams (run () does it); for
                        // an app that pumps its own loop (pump_events + draw + present)
    virtual void onTick () {}       // called once per run() loop (~60 Hz): polling, timers

    // Drag & drop (ABI v42). onDrop: something was dropped at (x,y) (client coords) --
    // type DND_TEXT / DND_FILES ('\n'-separated paths), data NUL-terminated, flags
    // DND_F_COPY (Ctrl held). onDragOver: a drag hovers (x,y); leave = it went away
    // (highlight a drop target). onDragDone: our own drag (uk_win_drag_begin) ended --
    // targetPid (0 = none), flags DND_F_COPY / DND_F_CANCEL / DND_F_DESKTOP.
    virtual void onDrop (int x, int y, int type, const char *data, int len, unsigned flags)
    { (void) x; (void) y; (void) type; (void) data; (void) len; (void) flags; }
    virtual void onDragOver (int x, int y, bool leave, unsigned flags) { (void) x; (void) y;
(void) leave; (void) flags; }
    virtual void onDragDone (int targetPid, unsigned flags) { (void) targetPid; (void) flags;
}

    static Root *current ();        // the active window (for modal dialogs)

    // The window's frame (kapi v64). setResizable (true): the app lays itself out at any
size
    // (its anchors, its layout do) -- then its maximise button works: the window fills the
    // work area (between the menu bar and the dock) and back; onResized () follows (the new
    // size: width, height). The window menu (its button, top left): Restore / Maximise,
    // Minimise, Close.
    void setResizable (bool on);
    // The smallest client area the frame can be dragged to (kapi v82). Without it: half the
size
    // the window has when it becomes resizable (160 x 100 at least). Before or after
setResizable.
    void setMinSize (int w, int h);
    bool resizable () const { return m_resizable; }
    bool maximised () const { return m_maxed; }
    void maximise (bool on);
    // A resizable window taller (or wider) than the work area: shrunk to it and moved into
it
    // (the dock no longer over its bottom) -- at the start, once its children are anchored.
    void fitWorkArea ();
```

```
    virtual void onResized () {}
    // The screen's size changed (GUI_EVENT_DISPLAY_RESIZE, kernel v66: the Control Panel's
Display
    // applet): an app placed by the screen's size (the menu bar, the dock...) places itself
again
    // here. Then, ~0.3 s later (the dock moved: the work area is the new one), run () fits
the
    // window: maximised, to the whole work area again (the size it goes back to kept inside
it);
    // else a window past the work area is moved into it, shrunk if it is resizable.
    virtual void onDisplayResize (int w, int h) { (void) w; (void) h; }
    // The reserve of virtual functions for the window (uikit/abi.h; Widget's own come
before): a
    // virtual added to Root by a later version of the library takes one of these.
    virtual void onClose ();        // (v94) its close box (not the first window's):
closeWindow ()
    void uk_rootReserved0 ();       // (the slots' former names: entries of the table, never
removed)
    void uk_rootReserved1 ();
    // (v95) A click on the program's icon of the status area (uk_tray): KAPI_TRAY_OPEN (a
double click:
    // the first window already shown again), KAPI_TRAY_MENU (a right click). To the first
window.
    virtual void onTray (int kind);
    // (P6) The size class changed (uikit/adapt.h: UK_SC_REGULAR on the desktop, _COMPACT,
_NARROW, _CONSOLE under
    // PocketUI -- the screen turned, the mode): the app lays itself out again for it (its
adaptive widgets -- SidePanel,
    // ToolBar, TabStrip, DataGrid -- already have). Called on every window of the program;
never on the desktop.
    virtual void onSizeClass (int sizeClass);
    void uk_rootReserved2 ();       // (the slot's former name: an entry of the table)
    virtual void uk_rootReserved3 () {}
    virtual void uk_rootReserved4 () {}
    virtual void uk_rootReserved5 () {}
    virtual void uk_rootReserved6 () {}
    virtual void uk_rootReserved7 () {}
    void windowMenu ();

    // Tooltips (Widget::tip): after the pointer rests ~0.6 s over a widget with a tip,
    // a small box shows the text next to it; any pointer event hides it.
    void tooltipTick ();
    void tooltipHide ();

private:
    Widget  *m_tipBox;          // the shown tooltip (a child), or 0
    int      m_mx, m_my;            // last pointer position (client coords)
    unsigned m_moveT;           // ticks of the last pointer event
    bool     m_tipDone;         // already shown for this rest
    bool     m_resizable, m_maxed;      // (setResizable, maximise)
    int      m_minW = 0, m_minH = 0;    // (setMinSize; 0: chosen by setResizable)
    void frameResize (int x, int y, int cw, int ch);    // the frame was dragged
(GUI_EVENT_WINRESIZE)
    int      m_rx, m_ry, m_rw, m_rh;    // the window's place and size before it was
maximised
    bool     m_dispPending;         // (GUI_EVENT_DISPLAY_RESIZE: displayTick fits the
window)
    unsigned m_winFlags;            // (its WIN_FLAG_*: a borderless one places itself)
    unsigned m_dispT;
    void displayTick ();
```

```
    void init (unsigned *fb);       // shared ctor tail (adopt canvas + decorate + register)
    void initApplet ();         // ... an applet's: the host's surface, no window
    static Root *&active ();        // single active window per app (reachable from C
callbacks)
    void    *m_ext = 0;         // the reserve (uikit/abi.h): the window's later fields
    unsigned long m_reserved[4] = { 0, 0, 0, 0 };   // [0] the window's number (v94), [1] 1:
not opened / closed
public:
    static void ptrEvent (unsigned long, int ev, gui_value v);  // (the kernel's event
streams; an
    static void keyEvent (unsigned long, int ev, gui_value v);  // applet's host's, re-packed
alike)
};
```

uikit/win.h

uikit/win.h -- UIKit's window API: a program's windows and what it asks of the graphics server, as plain C functions (uk_win_*, C linkage: entries of SD:/lib/uikit.so; a C program includes this header alone and links lib/uikit.imp_c.a, a C++ one has it through uikit/uikit.h and links lib/uikit.imp.a).

Until 2026-10-08 these were AppKit's kapi_* window calls (kapi_create_window, kapi_present, kapi_set_menu, kapi_win_list...). The graphics server is a program of its own (Elegant on the desktop; PocketUI, the pocket and console modes' server, to come -- docs/POCKETUI-TECH-STUDY.md), and each server has its UIKit, loaded under the name SD:/lib/uikit.so: UIKit's port (uikit/port/) is the only code that speaks its server's protocol (Elegant's: uikit/port/elegant.h). So the window API is UIKit's, and a program's binary runs on every server. AppKit keeps the kernel's side: the transport (kapi_ws_ctl), the event pump (kapi_pump_*, kapi_should_exit), the screen (kapi_screen_size), the full screen's kernel primitives (kapi_present_fb, kapi_fullscreen_direct).

The renaming, for a program written with the old names: kapi_create_window -> uk_win_create, and every other window call kapi_ -> uk_win_ without a doubled "win_" (kapi_win_list -> uk_win_list), with these: kapi_move_window -> uk_win_move, kapi_resize_window(2) -> uk_win_resize(2), kapi_set_window_alpha -> uk_win_alpha, kapi_get_chrome -> uk_win_chrome, kapi_set_key / click / pointer_handler -> uk_win_on_key / _on_click / _on_pointer, kapi_set_cursor -> uk_win_cursor, kapi_set_menu / get_menu -> uk_win_menu_set / _menu_get, kapi_win_move -> uk_win_place, kapi_win_desk -> uk_win_to_desk, kapi_list_windows -> uk_win_apps, kapi_raise_app / toggle_app -> uk_win_app_raise / _app_toggle, kapi_get / set_wheel_speed -> uk_win_wheel_get / _wheel_set, kapi_fullscreen_begin / _end -> uk_win_fullscreen_begin / _end.

The window flags (WIN_FLAG*_), the events (GUI_EVENT_*, GUI_PTR*_, KEY_*) and the structures (struct kapi_chrome, kapi_win_geom, kapi_win_info, kapi_tray_info) keep their names and their definitions (appkit/appkit.h, kern/kapi_abi.h): the events still come through the kernel's pump.

A program's windows: its first (0, made by uk_win_create / _ex) and others (uk_win_new); the calls below that act on "this window" act on the one uk_win_select chose (0 until then). What each window was asked is kept by UIKit and asked again of a graphics server started again (a crash, a restart): the program does nothing.

MIT License -- Copyright (c) 2026 Stéphane Wegener and the Onyx contributors. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above

copyright notice and this permission notice shall be included in all copies or substantial portions of the Software. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED.

the program's windows

The program's first window, a client area of w x h pixels titled title, placed by the server -> its canvas (0x00RRGGBB pixels, w a row), 0 on failure (no server, bigger than the screen, no memory).

```
unsigned *uk_win_create (int w, int h, const char *title);
```

The program's first window at x, y (its frame's top left; negative: placed by the server) with the flags (WIN_FLAG_*) -> its canvas, 0 on failure.

```
unsigned *uk_win_create_ex (int x, int y, int w, int h, const char *title, unsigned flags);
```

Another window of the program (after its first: 1 .. KAPI_WS_WINDOWS_MORE of them), as uk_win_create_ex -> its number (> 0) and its canvas in *canvas, -1 (no room, no server). The calls act on it once uk_win_select chose it.

```
int uk_win_new (int x, int y, int w, int h, const char *title, unsigned flags, unsigned
**canvas);
```

The window the calls act on (0: the first; -1: only asked) -> the one they acted on until now, -1 no such window.

```
int uk_win_select (int win);
void uk_win_destroy (int win);      // window win (> 0) closed and forgotten (the first: the
program's end)
```

this window

```
void uk_win_move (int x, int y);    // its frame moved to x, y (screen coordinates)
```

Its client area set to w x h, within the canvas it was created with (which stays) -> the canvas, 0 no window.

```
unsigned *uk_win_resize (int w, int h);
```

As uk_win_resize, but the canvas and the frame's copies grow past their first size when needed (new memory at the same addresses: their pixels are lost -- redraw them; the frame: uk_win_chrome again) -> the canvas, *stride its pixels a row; 0 (no memory: the size kept).

```
unsigned *uk_win_resize2 (int w, int h, int *stride);
```

on != 0: its edges and corners can be dragged, its client area never under min_w x min_h -> 0, -1 (no window, a borderless or fixed one). At the release its pointer handler gets GUI_EVENT_WINRESIZE: the program resizes itself.

```
int uk_win_resizable (int on, int min_w, int min_h);
void uk_win_alpha (int alpha);      // its opacity, 0 .. 255 (fades)
```

Its frame's place and size, its client area's size, the work area (the screen less the menu bar and the dock) and its KAPI_WIN_* state into *out -> 0, -1 no window.

```
int uk_win_geometry (struct kapi_win_geom *out);
```

Its surfaces for the frame UIKit draws (uikit/skin.cpp): the client canvas, the frame's active and inactive copies (0: borderless), their size, the insets, the title -> 1, 0 no window.

```
int uk_win_chrome (struct kapi_chrome *out);
void uk_win_present (void);     // its pixels changed: the server shows them
```

One line of text in the kernel's bitmap font at x, y of its canvas, colour c (0x00RRGGBB), the background kept.

```
void uk_win_draw_text (int x, int y, const char *s, unsigned c);
void uk_win_on_key (gui_handler fn);        // GUI_EVENT_KEY to fn (value: the character or KEY_*)
void uk_win_on_click (gui_handler fn);      // GUI_EVENT_CANVAS_CLICK / _MOTION to fn (the old click handler)
void uk_win_on_pointer (gui_handler fn);    // the whole pointer stream to fn (GUI_EVENT_PTR_*, drops, WINCTL, WINRESIZE)
```

The pointer's shape over its client area (KAPI_CURSOR_*), kept until changed -> the shape it had, -1.

```
int uk_win_cursor (int shape);
void uk_win_cursor_pos (int *x, int *y);    // the pointer, relative to its client area
int uk_win_cursor_shown (void);     // 1 the pointer is drawn, 0 hidden (keyboard only), -1 not known
```

the menu bar

This program's menus (the first window's) and the handler that gets GUI_EVENT_MENU (value: the item's id). The spec, '\n'-separated: "M" a menu, "I\t\t" an item, "-" a separator (programs normally use uikit::Menu) -> 1, 0.

```
int uk_win_menu_set (const char *spec, gui_handler h);
```

For the menu bar: the active window's spec and title -> a serial that changes with them (0: none).

```
unsigned uk_win_menu_get (char *buf, unsigned cap, char *title, unsigned tcap);
int uk_win_menu_command (int id);   // item id sent to the active window (MENU_QUIT: asked to close) -> 1 delivered
```

every window: the shell's, the remote desktop's

```
int uk_win_list (struct kapi_win_info *out, int max);   // the windows, bottom to top (at most max) -> how many
int uk_win_raise (unsigned id);     // window id to the front (it gets the keys) -> 0, -1
int uk_win_close (unsigned id);     // window id asked to close (as its close box) -> 0, -1
int uk_win_minimise (unsigned id);  // window id (0: the caller's) minimised until raised -> 0, -1
int uk_win_place (unsigned id, int x, int y);   // window id's frame moved to x, y -> 0, -1
```

Window id (0: the caller's) to workspace n (-1: every one; -2: only asked) -> its workspace (-1: all), -3 no window.

```
int uk_win_to_desk (unsigned id, int n);
```

The workspaces: set >= 0 shows that one, count > 0 sets how many (1 .. KAPI_DESK_MAX); -1 / 0 keep them -> the current one | the count << 8 | a counter bumped at every change << 16.

```
int uk_win_desk (int set, int count);
```

The pixels of a rectangle of window id's client area (part 0) or of its frame (1 active, 2 inactive) into dst (stride pixels a row), clipped to it -> 0, -1. KAPI_WIN_DESKTOP: the desktop, read whole.

```
int uk_win_read (unsigned id, int part, int x, int y, int w, int h, unsigned *dst, int
stride);
```

The names of the open apps (a window on the current workspace, not a WIN_FLAG_SYSTEM one), one a line -> how many.

```
int uk_win_apps (char *b, unsigned s);
int uk_win_app_raise (const char *name);    // app name's window to the front -> 1, 0 not
running / no window
```

App name toggled -> 0 it was running and is asked to close, 1 it was started, -1 on error.

```
int uk_win_app_toggle (const char *name);
```

the wallpaper

```
unsigned *uk_win_wallpaper_buffer (int *w, int *h); // the screen-sized wallpaper to draw
into -> its pixels, 0
void uk_win_wallpaper_commit (void);            // ... drawn: shown
int uk_win_wallpaper_generate (unsigned base, int pts, unsigned seed);  // the server's own
Voronoi wallpaper
```

drag and drop

A drag from this window while the left button is held: type DND_TEXT / DND_FILES ('\n'-separated paths), len bytes (4 KB at most), a label on the pointer -> 1 started. The targets get GUI_EVENT_DRAG_OVER / _DROP, the source GUI_EVENT_DRAG_DONE (to the pointer handler).

```
int uk_win_drag_begin (int type, const void *data, unsigned len, const char *label);
int uk_win_drag_data (int *type, void *buf, unsigned cap);  // the last drop's payload (cap
bytes) -> its length
```

the status area (the menu bar's tray)

This program's icon (KAPI_TRAY_PX square, 0xTTRRGGBB) and tip; h gets GUI_EVENT_TRAY (KAPI_TRAY_OPEN, _MENU) -> 1, 0. (uikit::uk_tray does it from a picture.)

```
int uk_win_tray_set (const unsigned *px, const char *tip, gui_handler h);
void uk_win_tray_clear (void);
int uk_win_tray_list (struct kapi_tray_info *out, int max); // for the menu bar: the icons ->
how many
int uk_win_tray_icon (unsigned pid, unsigned *px);      // ... one's pixels -> 1, 0
int uk_win_tray_activate (unsigned pid, int kind);      // ... clicked (KAPI_TRAY_OPEN,
_MENU) -> 1, 0
```

the wheel

```
int uk_win_wheel_get (void);        // lines scrolled a notch, system-wide
void uk_win_wheel_set (int lines);  // ... set (1 .. 16; the theme editor keeps it in
theme.txt)
```

the full screen

The display for this program alone (the server told, then the kernel's kapi_fullscreen_begin) -> the screen's pixels (*w x *h; kapi_present_fb shows them), 0 refused. uk_win_fullscreen_end gives it back.

```
unsigned *uk_win_fullscreen_begin (int *w, int *h);
void uk_win_fullscreen_end (void);
```

the graphics server

```
#define UK_MODE_DESKTOP     0   // uk_win_server's mode: Elegant's desktop
#define UK_MODE_POCKET      1   // PocketUI's pocket mode
#define UK_MODE_CONSOLE     2   // PocketUI's console mode
#define UK_SC_REGULAR       0   // size classes: the desktop
#define UK_SC_COMPACT       1   // a small landscape screen
#define UK_SC_NARROW        2   // a portrait screen
#define UK_SC_CONSOLE       3   // a television, a pad
struct uk_win_server_info
{
    unsigned size;          // set by the caller: sizeof (struct uk_win_server_info) (it may
grow at its end)
    char     name[16];      // the server's name ("elegant")
    int  mode;          // UK_MODE_*
    int  screen_w, screen_h;    // the screen, in the windows' pixels
    int  work_x, work_y, work_w, work_h;    // the work area: where a filled window goes
    int  scale;         // the composition's scale, in percent (100: none)
    int  size_class;        // UK_SC_*
    int  reserved[8];
};
```

The server this program's UIKit speaks to (each server has its UIKit) -> 1, 0 none runs (*out then says what the desktop would be).

```
int uk_win_server (struct uk_win_server_info *out);
```

the shell's calls (PocketUI's: the pocket and console shells)

The desktop's UIKit answers -KAPI_ENOSYS to each: Elegant's shell programs (menubar, dock) use the calls above. Their meaning is PocketUI's (docs/POCKETUI-TECH-STUDY.md section 4.3; phase P5, docs/03 "The pocket shell"): the shell (pocketshell; consolehome later) is the program whose windows are the home behind the apps (its BACKMOST window: placed at the work area, the keys' when no app is in front), its overlays (its TOPMOST windows: where it asks, even across the screen's top edge) and its toasts.

"I am the shell" -> 1; -KAPI_EBUSY another running program is; -KAPI_ENOSYS not PocketUI. Asked first, before its windows; UIKit asks it again of a PocketUI started again (with the events' handler and the keys).

```
int uk_shell_register (void);
```

The windows' news to fn, as events UK_SHELL_EVENT (value: UK_SHELL_EV_*) and UK_SHELL_KEYEV (value: a key, UK_SHELL_KEY) -> 1. No polling: the switcher, the launcher's running apps read uk_shell_tasks when told.

```
int uk_shell_events (gui_handler fn);
#define UK_SHELL_EVENT      64  // the event: value UK_SHELL_EV_*
#define UK_SHELL_EV_TASKS   1   // a program's window opened, closed, retitled, minimised;
the front one changed; home
#define UK_SHELL_EV_AREA    2   // the work area changed (the menu bar came or went, the
screen's size): uk_win_server
#define UK_SHELL_EV_TEXT    3   // (value & 0xFF; PocketUI's P10) the app in front's focused
text field changed: its type + 1
```

in bits 8..15 (UK_IN_* of uikit/adapt.h; 0: no field has the focus) -- the on-screen keyboard

```
#define UK_SHELL_KEYEV      65  // the event: value UK_SHELL_KEY (mods, code) -- a system
key, or every key while grabbed
```

A key as the shell names it: the modifiers (1 Ctrl, 2 Shift, 4 Alt, 8 Super) and the code (a character, KEY_*, KEY_ENTER, KEY_BACKSPACE, 0x1b Esc, 9 Tab; or one of the two below).

```
#define UK_SHELL_KEY(mods, code)    ((int) (((unsigned) (mods) << 16) | (unsigned) (code)))
#define UK_SHELL_KEY_MODS(k)        ((unsigned) (k) >> 16)
#define UK_SHELL_KEY_CODE(k)        ((int) ((unsigned) (k) & 0xFFFF))
#define UK_SHELL_MOD_SUPER  8   // a Super key (the Windows key)
#define UK_SHELL_KEY_SUPER  0x1000  // a Super pressed and released with no key between
(Home)
#define UK_SHELL_KEY_HELD   0x1001  // (grabbed) the modifiers held changed:
UK_SHELL_KEY_MODS says which now
```

The system keys the shell takes before the front app (UK_SHELL_KEY each; count 0: none) -> how many. A program in full screen keeps every key.

```
int uk_shell_keys (const int *keys, int count);
```

While on: every key and every change of the modifiers to the shell (an overlay is up: the switcher, quick settings) -> 1.

```
int uk_shell_grab (int on);
```

Window id's client area as last presented, scaled to w x h (at most 512 x 512) into dst (w a row) -> 1, 0 no such window, -1 refused.

```
int uk_shell_thumb (unsigned id, unsigned *dst, int w, int h);
```

front 1: window id's program to the front (home left); front 0 and id 0: HOME -- every app set aside, the shell's home has the keys; front 0 and an id: its program behind the others -> 1, 0 no such window.

```
int uk_shell_front (unsigned id, int front);
int uk_shell_split (unsigned left, unsigned right); // two programs' windows side by side (0
0: none) -> 1, 0 the work area is too small or upright (PocketUI: P8)
int uk_shell_dim (int alpha);               // a dim behind an overlay -- (not yet: the
overlays draw theirs)
```

The running programs, the most recently in front first: each its topmost window -> how many (none in front of them: home).

```
struct uk_shell_task
{
    unsigned id;            // its topmost window (uk_win_list's id: uk_shell_thumb,
uk_win_close, uk_shell_front)
    unsigned pid;
    unsigned flags;         // UK_TASK_*
    int  w, h;          // that window's client area
    char     title[48];     // its title
    char     name[24];      // the program's name (its app: SD:/apps/<name>.app)
};
#define UK_TASK_FRONT       1   // the program in front
#define UK_TASK_CARD        2   // its window is a card (a small fixed window, framed)
#define UK_TASK_MINIMISED   4   // every window of it minimised
#define UK_TASKS_MAX        32
int uk_shell_tasks (struct uk_shell_task *out, int max);
```

```
}
#endif
```

Friendly aliases used by the demos (they were appkit.h's).

```
unsigned *create_window (int w, int h, const char *t);
void      present (void);
```

uikit/canvas.h

uikit/canvas.h -- Canvas: a 0x00RRGGBB pixel buffer with blit/fill/text (port of VMKernel's GIMAGE). Each Widget owns one. It either OWNS its pixels (alloc) or borrows them (adopt, e.g. the window canvas from uk_win_create).

`stride` is the buffer's real row width in pixels; `w` is the LOGICAL (visible) width. They differ when a Canvas shows a sub-rect of an over-allocated buffer -- e.g. a shell surface allocated at screen width but displayed at the (smaller, resizable) viewport size. All blits step rows by `stride` and clamp to `w`.

```
#define UK_TRANSPARENT_KEY 0x00FF00FFu      // magenta = skipped on a transparent blit

class Font;                 // uikit/font.h -- bitmap glyph table (drawFont)

class Canvas
{
public:
    unsigned *px; int w, h, stride; bool owns;
    int capH;                   // allocated rows (stride = allocated row width)
    // The reserve (uikit is a shared library: uikit/abi.h): a program allocates a Canvas
with the size
    // it was built with, so a later version of the library can only use what is kept here.
    void *ext = 0;
    unsigned long reserved_[2] = { 0, 0 };

    Canvas ();
    ~Canvas ();

    void release ();
    bool alloc  (int W, int H);         // own a fresh WxH buffer (stride = W)
    void adopt  (unsigned *p, int W, int H);    // borrow a buffer, stride = W (window
canvas)
    void adopt  (unsigned *p, int W, int H, int Stride);    // borrow a sub-rect of a wider
buffer
    // Grow-only: reuses the buffer when W<=stride && H<=capH (just changes the logical
    // size); otherwise reallocates to ~2x (amortised). So a resizing widget (a key in a
    // reflowing grid) rarely reallocates. Content is lost on a real grow (caller repaints).
    bool resize (int W, int H);
    void setLogical (int W, int H);         // change the visible w/h only (buffer/stride
kept)

    void clear     (unsigned c);
    void pixel     (int x, int y, unsigned c);
    void fillRect  (int x, int y, int rw, int rh, unsigned c);
    void frameRect (int x, int y, int rw, int rh, unsigned c);
    void text      (int x, int y, const char *s, unsigned c);
    // Draw `s` from a loaded bitmap Font at (x,y), top-left, scaled by `scale` (>=1), in
    // `style` (0=reg 1=italic 2=bold 3=bold+italic). Only ink pixels are written (the
    // background shows through). Implemented in font.cpp.
    void drawFont  (int x, int y, const char *s, const Font &f, unsigned color, int scale =
```

```
1, int style = 0);
    // Blit src into this canvas at (dx,dy); if transparent, magenta pixels are skipped.
    // Clipped to this canvas -> the parent only takes what fits (free clipping).
    void putOther  (const Canvas &src, int dx, int dy, bool transparent);
};
```

uikit/theme.h

uikit/theme.h -- the desktop's look (docs/gui-redesign/README.md, "a modernised CDE"): the palette every widget and every window frame draws with. A theme gives ONE colour per kind of window frame (active: the window in front; inactive: the others) and the apps' face; every other shade is computed from those (uikit/paint.h: the grey profile). Read once by uikit::init () from SD:/etc/theme.txt:

```
    theme    = Peach        a named theme. Two kinds: CDE's framed title buttons -- Peach,
Steel,
                            Sage, Brick, Slate (the frame of the window in front; the ones
                            behind: Grey) --, or OS X's coloured beads, the frame melting
into
                            the window (no line between them) -- Milk (soft greys) and Dark
                            Coffee (black coffee's browns, a caramel accent)
    style    = cde          the frames' look, if not the theme's: cde or milk
    active   = 0xF0B07A     or the colours themselves (they override the theme's)
    inactive = 0xACACB0
    window   = 0xD0C2BA     the windows' content: the apps' face, their background ("face"
                            before: still read)
    button   = 0xD0C2BA     the push buttons, the drop-downs' faces (default: the window's)
    field    = 0xF6F3F1     the text fields and the lists (default: the window's, nearly
white)
    accent   = 0x4992A7     focus, selection, checks
    outline  = dark         the frames' 1-px outline: none, dark or black
    menubar  = 0xD0C2BA     the menu bar (default: the window's)
    dock     = 0xA4BACE     the dock's face
```

Without the file (or a key), the defaults below: Peach over CDE's beige, a teal accent; a colour left out takes the style's own (uk_style_palette: Milk's greys, its Aqua blue...). Each text colour is black or white by the brightness of what it is written on.

The palette (0x00RRGGBB), set by uk_theme_load (); the names are the toolkit's since its start.

```
UIKIT_VAR (unsigned, C_BG);          // an app's background (its face)
UIKIT_VAR (unsigned, C_FACE);            // a control's face (a button, a handle)
UIKIT_VAR (unsigned, C_FACE_HI);         // ... under the pointer
UIKIT_VAR (unsigned, C_FACE_DN);         // ... pressed
UIKIT_VAR (unsigned, C_BORDER);      // a control's outline
UIKIT_VAR (unsigned, C_TEXT);            // text on the face
UIKIT_VAR (unsigned, C_ACCENT);      // focus, selection, checks, carets
UIKIT_VAR (unsigned, C_DIS);             // disabled text
UIKIT_VAR (unsigned, C_FIELD);       // a text field's, a list's background
UIKIT_VAR (unsigned, C_FIELD_TEXT);      // text in a field
UIKIT_VAR (unsigned, C_SEL_TEXT);        // text on the accent (a selected row)
UIKIT_VAR (unsigned, C_FRAME_ACTIVE);        // the window in front's frame
UIKIT_VAR (unsigned, C_FRAME_INACTIVE); // the other windows' frames
UIKIT_VAR (int, UK_OUTLINE);         // the frames' 1-px outline: 0 none, 1 dark, 2 black
UIKIT_VAR (unsigned, C_DOCK);            // the dock's face (and the drawers' frame)
UIKIT_VAR (unsigned, C_BUTTON);      // a push button's / a drop-down's face (the window's by
default)
UIKIT_VAR (unsigned, C_BUTTON_TEXT);         // ... its text
UIKIT_VAR (unsigned, C_MENUBAR);         // the menu bar's face (the window's by default)
```

The frames' look: CDE's (framed title buttons) or Milk's (Xfce's Milk theme, as OS X: the title buttons coloured beads -- close red, minimise amber, maximise green --, the title's gradient down to the window's colour, C_BG, the borders that colour: the frame melts into the window).

```
enum { UK_STYLE_CDE = 0, UK_STYLE_MILK = 1 };
UIKIT_VAR (int, UK_STYLE);
```

A style's own colours: what a theme of it takes when theme.txt does not say. (button, field: 0xFF000000 = from the window's, UK_AUTO below; outline: 0 none, 1 dark, 2 black.)

```
struct UkPalette { unsigned face, accent, inactive, dock, button, field; int outline; };
const UkPalette &uk_style_palette (int style);  // UK_STYLE_MILK: Milk's; any other value: CDE's
```

The named themes (the active frame's colour, the frames' style; pal: a theme with colours of its own -- Dark Coffee --, 0: its style's).

```
struct UkNamedTheme { const char *name; unsigned frame; int style; const UkPalette *pal; };
const UkPalette &uk_theme_palette (int theme);  // a named theme's colours (its own, else its style's)
extern const UkNamedTheme uk_themes[];  // ..., { 0, 0, 0 }
static const unsigned UK_GREY = 0x00ACACB0; // the inactive frames

void uk_theme_load ();          // (uikit::init () calls it; idempotent)
void uk_theme_reload ();        // read SD:/etc/theme.txt again (a new theme applied: the dock)
void uk_theme_face (unsigned face); // the palette's shades from a face colour (a preview)
```

The whole theme as values (the Theme applet edits one, previews it, writes it). UK_AUTO: a colour derived from the window's (button, field, menubar).

```
static const unsigned UK_AUTO = 0xFF000000u;
struct UkTheme
{
    int theme;              // uk_themes[] index of the active frame's colour, -1: `active`
    unsigned active, inactive, window, button, field, accent, menubar, dock;
    int outline;               // 0 none, 1 dark, 2 black
    int style;              // the frames' look: UK_STYLE_CDE / UK_STYLE_MILK
};
```

A theme's style changed (a scheme chosen): the colours that are the style's own -- the window, the accent, the frames behind, the dock -- become the new style's (what the user set otherwise is kept); the buttons, the fields and the menu bar follow the window's.

```
void uk_theme_take_style (UkTheme &t, int style);
```

A named theme chosen (uk_themes[theme]): its frame, its style, and -- when its colours are not those of the theme left -- its window, accent, frames behind, dock, buttons, fields, outline.

```
void uk_theme_take (UkTheme &t, int theme);
void uk_theme_defaults (UkTheme &t);
void uk_theme_parse (const char *text, UkTheme &t); // theme.txt's keys over t
void uk_theme_get (UkTheme &t);         // the palette in use
void uk_theme_set (const UkTheme &t);       // ... made this one (every shade computed)
int  uk_theme_write (const UkTheme &t, char *out, int cap); // theme.txt's text -> its length
```

uikit/text.h

uikit/text.h -- the text-rendering hook: a TextFace an app installs (uk_set_textface) so that every text path of uikit draws and measures with it -- Canvas::text, uk_text_l / _c / _w, the line height widgets lay out with (uk_fh ()), the widths they compute (a NumericUpDown's right alignment, tooltips, icon labels, the grid's cells, the text boxes' carets...). Without a face (the default) uikit draws with its bitmap fonts exactly as before, byte for byte.

A face is proportional and its text is UTF-8 (the bitmap path stays Latin-1, one byte a glyph). Styles: 0 regular, 1 italic, 2 bold, 3 bold italic (as the bitmap families). Install it before building the widgets (some size themselves from uk_fh () when made):

```
  #include "fontkit/uikitface.h"              (a newlib app linking fontkit/libft.a:
FreeType's anti-aliased text)
  int main () { ft_uikit_install ("DejaVu Sans", 13); Root root (...); ... }
```

The window's frame (its title) has a face of its own, the same in every app: SD:/res/fonts/title.aaf (DejaVu Sans Bold rendered by FreeType ahead of time: uikit/skin.cpp), else the desktop's bitmap font.

```
struct TextFace
{
    virtual int  height () = 0;     // a line's height, px (uk_fh () while installed)
    virtual int  ascent () = 0;     // from a line's top to its baseline, px
    virtual int  width (const char *utf8, int style) = 0;           // the advance, px
    // Draw at x, the line's top at yTop (a line of height () px), blended over the canvas.
    virtual void draw (Canvas &cv, int x, int yTop, const char *utf8, unsigned color, int
style) = 0;
    // The width of the first n bytes (a prefix: the caret's place). The default copies them
and
    // asks width (); a face overrides it to measure in place.
    virtual int  widthN (const char *utf8, int n, int style);
    virtual ~TextFace () {}
};

UIKIT_VAR (TextFace *, uk_face_);           // (the face in use: uk_textface ())
UIKIT_VAR (int, uk_face_fw_);          // (its digit's width: uk_fw () while installed)
void uk_set_textface (TextFace *f);     // install a face; 0: back to the bitmap fonts
```

The face uk_set_textface installed, 0 while the bitmap fonts are in use.

```
TextFace *uk_textface ();
```

Another face for the time of a scope -- a widget's own captions, a display's large digits --, the one before back at its end. f = 0: no change.

```
struct UkFaceScope
{
    TextFace *keep; int keepFw;
    UkFaceScope (TextFace *f) : keep (uk_face_), keepFw (uk_face_fw_)
    { if (f) { uk_face_ = f; uk_face_fw_ = f->width ("0", 0); if (uk_face_fw_ < 1)
uk_face_fw_ = 1; } }
    ~UkFaceScope () { uk_face_ = keep; uk_face_fw_ = keepFw; }
};
```

measuring and drawing, through the face when one is installed

The bitmap fonts' cell (the kernel's font: what uk_fw () / uk_fh () give without a face).

```
int  uk_bfw ();
int  uk_bfh ();
```

The width of s as Canvas::text draws it (no face: its length x uk_fw ()); of its first n bytes.

```
int  uk_tw (const char *s, int style = 0);
int  uk_tw_n (const char *s, int n, int style = 0);
```

The place (a byte index <= n, a character's start) whose caret is the nearest to x px from the text's start: a click in a text.

```
int  uk_tpos (const char *s, int n, int x, int style = 0);
```

s at (x, y) -- the line's top-left -- in `style` (the bitmap path: the loaded family's style).

```
void uk_text (Canvas &cv, int x, int y, const char *s, unsigned c, int style = 0);
```

... clipped to the box (cx, cy, cw, ch): a text that runs past a field's edge.

```
void uk_text_clip (Canvas &cv, int x, int y, const char *s, unsigned c, int style,
           int cx, int cy, int cw, int ch);
```

Fit s into w px (a copy in out, cap bytes): cut at a character, "..." at its end when it did not fit. Returns its width.

```
int  uk_text_fit (const char *s, int w, char *out, int cap, int style = 0);
```

Word-wrap the first n bytes of s into lines of w px at most, maxLines at most: line k is the bytes [start[k], start[k] + len[k]) of s (start and len: maxLines entries each). A '\n' ends a line (an empty line for "\n\n"); a line is broken at its last space that fits (the spaces at the break dropped); a word wider than w is cut at a character (UTF-8). *more (when given): text is left past the last line (more than blanks). -> the number of lines. (A card showing a paragraph: Stickies.)

```
int  uk_text_wrap (const char *s, int n, int w, int maxLines, int *start, int *len, bool
*more = 0, int style = 0);
```

s at (x, y) -- the line's top-left -- straight over a see-through canvas (a WIN_FLAG_ALPHA window: the wallpaper shows through; uk_paint_alpha on), its glyphs blended by their coverage with the bitmap fonts or the installed face alike (a face's own draw ignores the alpha mode). shade: 0 none; 1 a soft shadow (for a light ink on a dark wallpaper); 2 engraved: a light edge under each glyph, of `back` (the wallpaper's colour there; for a dark ink on a light wallpaper). The agenda's header, Stickies'.

```
void uk_text_over (Canvas &cv, int x, int y, const char *s, unsigned ink, int style = 0, int
shade = 0, unsigned back = 0);
```

UTF-8 (the face's text)

A sequence's length from its first byte and what follows it (1 for a byte that does not start a valid sequence: read as Latin-1, so older text still shows), bounded by n bytes.

```
int uk_u8_len (const char *s, int n);
```

The character at s (its length in *len), a stray byte as its Latin-1 character.

```
unsigned uk_u8_get (const char *s, int n, int *len);
```

The next / the previous character's start from byte i (of n).

```
int uk_u8_next (const char *s, int i, int n);
int uk_u8_prev (const char *s, int i);
```

cp written as UTF-8 into o (4 bytes room) -> its length.

```
int uk_u8_put (char *o, unsigned cp);
```

A typed key as the text widgets store it with a face: its UTF-8 (Latin-1 0xA0..0xFF, 0x80 the euro sign as the keymaps send it) -> the length (0: not a character).

```
int uk_u8_key (long k, char *o);
```

uikit/label.h

uikit/label.h -- non-interactive text on a solid background.

```
class Label : public Widget
{
public:
    char     text[128];
    unsigned bg, fg;
    Label (int l, int t, int w, int h, const char *s, unsigned fg_ = C_TEXT, unsigned bg_ =
C_BG);
    void setText (const char *s);
    void onDraw () override;
};
```

uikit/button.h

uikit/button.h -- a push button (the theme's raised face, as a drop-down's: uikit/paint.h); fires cb on release-over.

```
class Button : public Widget
{
public:
    char     text[64];
    Action   cb;
    Button (int l, int t, int w, int h, const char *s, Action cb_ = 0);
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;       // focused (Tab): Space / Enter press it
};
```

uikit/dialog.h

uikit/dialog.h -- modal dialogs as uikit objects. A dialog is just a normal uikit Widget added as the TOP child of the Root and flagged `modal`, so Root routes all input to it (see Widget::handleMouse/handleKey) until it closes and removes itself. It is built from ordinary uikit controls (Button / Textbox / Scrollbar) for a uniform look.

```
  uikit::Modal      -- base: box widget + the nested run() loop.
  uikit::MessageBox -- title + message + OK / Yes-No / OK-Cancel.
  uikit::FileDialog -- navigable file browser (open / save).
```

Convenience: uk_messagebox / uk_file_open / uk_file_save.

```
class Modal : public Widget
{
public:
    bool done; int result;
```

```
    Modal (int w, int h);           // box-sized widget, centred + flagged modal by run()
    int  run ();                // add to Root, pump until closed, remove; returns result
    void close (int r) { result = r; done = true; }
    virtual void onButton (int tag)   { (void) tag; }   // from a dialog button
    virtual void onScroll (int value) { (void) value; } // from a dialog scrollbar
    unsigned bgColor () override;       // the face (its controls blend into it)
    // The box: a rounded panel of the face, a title strip in the active frame's colour, an
    // outline; its corners see-through. The title strip's height: titleH ().
    void drawBox (const char *title);
    static int titleH ();
};

class MessageBox : public Modal
{
    const char *m_title, *m_text; int m_def;
public:
    MessageBox (const char *title, const char *text, int buttons);
    void onButton (int tag) override { close (tag); }
    bool onKey (long k) override;       // Enter = default, Esc = cancel
    void onDraw () override;
};
```

The file dialog (uk_file_open / uk_file_save / uk_folder_open show it): an Up button and the folder's path, the volumes at the left, the folder's content (the folders first, sorted, the files' sizes); a click selects, a double click / Enter / the button opens a folder or takes the file; the arrows, Backspace (up). startDir may be a file's path: its folder (a save dialog proposes its name). ITS SIZE AND ITS FUNCTIONS ARE THE LIBRARY'S ABI: the fields below are kept as they always were (dialog.cpp says how the dialog uses them), nothing is added.

```
class FileDialog : public Modal
{
    enum { MAXENT = 128 };
    char  m_dir[256], m_ent[MAXENT][96], m_isdir[MAXENT];
    int   m_count, m_sel, m_top, m_rows, m_rowH;
    int   m_lastRow; unsigned m_lastTick;   // a double click on a file: confirmed
    int   m_lx, m_ly, m_lw, m_lh;       // file-list rect (box-local)
    bool  m_save, m_folder;     // m_folder: pick a directory (no filename box)
    Textbox   *m_nameBox;
    Scrollbar *m_sb;
    void read (); void goUp (); void enter (const char *name); void click (int row); void
syncSb ();
public:
    FileDialog (const char *startDir, const char *defName, bool save, bool folder = false);
    void onScroll (int v) override { m_top = v; invalidate (true); }
    void onButton (int tag) override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;  // list area
    bool onKey (long k) override;       // Enter = Open / Save, Esc = Cancel
    void onDraw () override;
    void getResult (char *out, unsigned cap);       // dir + "/" + filename (folder mode:
dir)
    // The kinds of files shown: "Text files|*.txt;*.md|All files|*" -- pairs of a name and
its patterns
    // (';' between them; "*": every file), '|' between everything. A drop-down beside the
buttons chooses
    // one; the folder shows the files that match it (and every folder). A save: a name typed
without an
    // extension takes the kind's first one. 0 / "": every file, no drop-down. The text must
live as long
    // as the dialog (it is not copied).
```

```
    void setFilters (const char *filters);
    const char *fileName () const { return m_nameBox ? m_nameBox->text : ""; }  // the name
box's text
};
```

Colour dialog (WPF-style ColorPicker dialog): R / G / B sliders, a 16-colour palette, a preview (old | new) and the hex value; OK / Enter keeps it, Cancel / Esc does not.

```
class ColorDialog : public Modal
{
public:
    unsigned color, orig;
    ColorDialog (unsigned initial, const char *title);
    void onButton (int tag) override { close (tag); }
    bool onKey (long k) override;
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    void syncSliders ();
    class Slider *r, *g, *b;
private:
    const char *m_title;
};
```

Convenience: spin a one-shot dialog and return its outcome. A pop-up menu at (x, y) of the window (a context menu, the window menu): a floating panel of items -- the one under the pointer in the accent -- and separators. run () shows it until an item is picked (its id), or a click elsewhere / Esc (-1).

```
class PopupMenu : public Modal
{
    enum { MAXI = 16 };
    const char *m_label[MAXI], *m_hint[MAXI]; int m_id[MAXI]; bool m_on[MAXI], m_sep[MAXI];
    int m_n, m_hot;
    int rowY (int i) const;
    int rowAt (int mx, int my) const;
public:
    PopupMenu (int x, int y);
    void add (const char *label, int id, bool enabled = true, const char *hint = 0);
    void separator ();
    int  run ();                // fits the menu in the window, shows it -> id / -1
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
};

int  uk_messagebox (const char *title, const char *text, int buttons);  // modal; buttons:
MB_* -> 1 OK / Yes, 0 Cancel / No / Esc (2: Yes-No-Cancel's No)
```

The file dialogs: modal, from startDir (a folder, or a file's path: its folder); true = OK (out: the chosen path). filters: the kinds of files offered, "Text files|.*txt;*.md|All files|*" (FileDialog::setFilters); 0: all.

```
bool uk_file_open (char *out, unsigned cap, const char *startDir, const char *filters = 0);
bool uk_file_save (char *out, unsigned cap, const char *startDir, const char *defName, const
char *filters = 0);    // with a name box (defName in it)
bool uk_folder_open (char *out, unsigned cap, const char *startDir);    // pick a directory
bool uk_color_dialog (unsigned *color, const char *title = "Colour");   // true = OK (*color
set)
```

`uikit/adapt.h`

uikit/adapt.h -- the adaptive layer: what an app asks to lay itself out in every mode (docs/POCKETUI-TECH-STUDY.md sections 6.5-6.14, phase P6; docs/03 "The adaptive widgets"). One binary runs on the desktop's UIKit (Elegant: lib/uikit.so) and on PocketUI's (pocket and console: lib/pocket/uikit.so, loaded under the same name): the app declares WHAT its parts are -- a navigation or inspector SidePanel (uikit/sidepanel.h), tools with priorities (uikit/toolbar.h), tabs (uikit/tabstrip.h), a dialog of rows (uikit/form.h), columns with roles (uikit/datagrid.h), a field's type -- and each UIKit renders it for its mode. On the desktop every call below answers what today is (the size class regular, today's metrics): an app that uses them looks the same there.

```
  int sc = uk_size_class ();                // UK_SC_REGULAR (desktop), _COMPACT, _NARROW
(portrait), _CONSOLE
  const UkMetrics &m = uk_metrics ();       // the rows', buttons', rail's sizes of the
profile
  int gw = uk_scroll_gutter ();             // what a scrolled view leaves at its right for
the bar (10; 0 in pocket)
  uk_set_input_type (urlBox, UK_IN_URL);    // the on-screen keyboard's layout (pocket), "a
keyboard is needed" (console)
  class MyRoot : public Root { void onSizeClass (int sc) override { ...lay out again... } };
```

The size class (uikit/win.h's UK_SC_*): the server's (uk_win_server), asked once and again when the window or the screen changes size; Root::onSizeClass (uikit/root.h) is called on each Root when it changes.

MIT License -- Copyright (c) 2026 Stéphane Wegener and the Onyx contributors. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED.

the mode and the size class

```
int uk_size_class ();           // UK_SC_REGULAR (the desktop), UK_SC_COMPACT, UK_SC_NARROW,
UK_SC_CONSOLE
int uk_mode ();              // UK_MODE_DESKTOP, UK_MODE_POCKET, UK_MODE_CONSOLE
bool uk_compact ();
```

the metrics: the profile's sizes (SD:/etc/theme.txt "metrics = regular | compact | touch", pocket)

```
enum { UK_PROFILE_REGULAR = 0, UK_PROFILE_COMPACT = 1, UK_PROFILE_TOUCH = 2,
UK_PROFILE_CONSOLE = 3 };
struct UkMetrics
{
    int  profile;           // UK_PROFILE_* (the desktop: regular; console: its own)
    int  scale;             // percent (100; "scale =" of theme.txt in pocket) -- the sizes
below include it
    int  row;               // a list's, a grid's row (regular: the text's height + 8)
    int  menuRow;           // a popup menu's row
    int  button;            // a push button's height
    int  field;             // a text field's height
    int  tab;               // a tab strip's height
```

```
    int  toolbar;           // a toolbar's height (and a tool's 28 + 6)
    int  rail;              // a SidePanel's rail: its width (48 lp)
    int  scrollbar;         // the scroll bar as drawn (regular 10; pocket's overlay 4)
    int  gutter;            // what a scrolled view leaves for it (uk_scroll_gutter)
    int  pad;               // the padding between controls
    int  touch;             // a touch target's least size (0: no touch)
    int  reserved[8];
};
const UkMetrics &uk_metrics ();
int uk_scroll_gutter ();        // UK_SBW (10) on the desktop, 0 under the overlay bars
(pocket, console)
int uk_lp (int v);          // logical pixels at the metrics' scale (v on the desktop)
```

The app draws only through UIKit (its widgets and Canvas' methods): its window may be given device pixels when the display is scaled (the native scale of docs/POCKETUI-TECH-STUDY.md section 6.3, phase P10) -- said to the server, kept; nothing changes on the desktop.

```
void uk_logical_units (bool on);
bool uk_logical_units_on ();
```

a field's type: the on-screen keyboard's layout (pocket), "a keyboard is needed" (console)

```
enum { UK_IN_TEXT = 0, UK_IN_NUMBER, UK_IN_DECIMAL, UK_IN_URL, UK_IN_EMAIL, UK_IN_PASSWORD,
UK_IN_TERMINAL, UK_IN_SEARCH };
void uk_set_input_type (Widget *w, int type);   // any widget that takes text (a Textbox, a
terminal's view...)
int  uk_input_type (Widget *w);     // UK_IN_* (a Textbox with `password` set:
UK_IN_PASSWORD; else UK_IN_TEXT)
```

the focus by the arrows (pocket, console: a d-pad)

The focus moved from the focused control of root's tree to the nearest focusable one in that direction (dx, dy: -1, 0, 1) -> true moved. UIKit does it itself with the arrows nobody took, in pocket and console.

```
bool uk_focus_move (Widget *root, int dx, int dy);
```

the console's shoulders

L1 / R1 (on a keyboard: Ctrl+Page Up / Ctrl+Page Down) step through the window's tabs, else through its navigation SidePanel's sections; L2 / R2 (Page Up / Page Down) page a list. The pad's buttons are given these keys by the console's shell (phase P9).

uikit/bmp.h

bmp.h -- an icon's picture for UIKit and the apps (the docks, the lists, the skins).

ui::icon_load reads a picture file through ImageKit -- any format it reads: the icons are BMP today, they may be PNG tomorrow -- and gives it as the icons are drawn: 0x00RRGGBB, top-down, the see-through pixels in the icons' key colour (magenta, 0x00FF00FF). (Until 2026-10-05 this was user/bmp.hpp, a 24-bit BMP reader compiled into each program.)

The picture of a file (new[]: the caller's to delete[]), its size in *pw, *ph; 0 if it cannot be read.

```
unsigned *icon_load (const char *path, int *pw, int *ph);
```

(the name the programs knew: the same)

```
unsigned *bmp_decode (const char *path, int *pw, int *ph);
```

uikit/calendar.h

uikit/calendar.h -- Calendar: a month grid to pick a date (WPF Calendar); DatePicker: a date field that opens a Calendar below it (WPF DatePicker).

```
  Calendar: < / > (or Page Up / Page Down) change the month; click a day (or arrows +
  Enter) picks it: year/month/day + cb. Today is outlined.
  DatePicker: shows YYYY-MM-DD; click to open the calendar, pick a day to close it
  (Esc or a click outside cancels); cb fires on a new date.
```

```
class Calendar : public Widget
{
public:
    int year, month, day;           // the selected date (month 1..12)
    int viewYear, viewMonth;        // the month shown
    Action cb;
    Calendar (int l, int t, int y, int m, int d, Action cb_);   // size: CAL_W x CAL_H
    void setDate (int y, int m, int d);
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
    static int daysIn (int y, int m);
    static int dayOfWeek (int y, int m, int d); // 0 = Monday
};
enum { CAL_CELL_W = 28, CAL_CELL_H = 20, CAL_HDR = 24, CAL_W = 7 * CAL_CELL_W + 2,
       CAL_H = CAL_HDR + 18 + 6 * CAL_CELL_H + 4 };

class DatePicker : public Widget
{
public:
    int year, month, day; Action cb; bool open;
    DatePicker (int l, int t, int w, int h, int y, int m, int d, Action cb_);
    ~DatePicker ();
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
    void setOpen (bool o);
    void format (char *out) const;      // "YYYY-MM-DD"
    Calendar *cal;              // the drop-down: made at the first opening, a child while
open
    int rowH, origW;
};
```

uikit/checkbox.h

uikit/checkbox.h -- a box + check mark + label; toggles on click.

```
class Checkbox : public Widget
{
public:
    char     text[64]; bool checked; Action cb; unsigned bg;
    Checkbox (int l, int t, int w, int h, const char *s, bool chk, Action cb_, unsigned bg_ =
C_BG);
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;       // Space / Enter toggle
};
```

uikit/codeedit.h

uikit/codeedit.h -- CodeEdit: a code editor. BASIC (or QBStudio's .form text) in a monospaced face, the language's colours, the line numbers, the indentation's guides, the lines with a problem marked (a red dot in the margin, the text underlined), a line lit (an error's, a debugger's current line), undo / redo, the clipboard, and the completion (after a name and a dot, or Ctrl+Space: the program gives the items). The words of the language are written in capitals as you type (as QBasic does) when isKeyword is set. Made from QBStudio's editor (2026-10-06) for every program that edits code: QBStudio, Turtle Quest.

```
  CodeEdit *ed = new CodeEdit (x, y, w, h);
  ed->mono = myMonoFace; ed->isKeyword = is_basic_word; // (0: the UI's face; no keyword
colours)
  ed->setText (src); ed->onChange = changed;
  ed->hiLine = 4; ed->invalidate (true);                // line 4 lit (1-based; 0 none)
  ed->clearMarks (); ed->addMark (7);           // line 7 has a problem
```

Keys: the arrows (Ctrl: by word), Home / End (Ctrl: the text's), Page Up / Down, Shift: select; Ctrl+A, C, X, V, Z, Y; Tab / Shift+Tab: indent / unindent the lines chosen; Enter keeps the indentation (two spaces more after a line that opens a block); Ctrl+Space: the completion. Mouse: click, drag, double click (a word), the wheel, the scroll bar.

MIT License -- Copyright (c) 2026 Stéphane Wegener and the Onyx contributors (docs/LICENSING.md).

```
enum { CODE_BASIC = 0, CODE_FORM = 1 };         // CodeEdit::lang (CODE_FORM:
QBStudio's .form text)
struct CodeEditState;                    // (the editor's text, lines, undo: codeedit.cpp)

class CodeEdit : public Widget
{
public:
    bool     readonly;
    int  lang;                  // CODE_BASIC / CODE_FORM
    int  hiLine;                // a line lit (1-based; 0 none)
    Action   onChange;              // the text changed
    Action   onCaret;               // the caret moved
    TextFace *mono;                 // the code's face (0: the UI's)
    TextFace *ui;                   // the completion list's face (0: the UI's)
    bool     (*isKeyword) (const char *w, int n);   // a word of the language? (colours,
capitals; 0: none)
    bool     (*isFlag) (const char *w, int n);  // CODE_FORM: a flag word (0: none)
    // The completion: called with the name before the dot ("" for Ctrl+Space); it calls
addCompletion for each
    // item -- kind: 'p' property, 'm' method, 'c' control, 's' a SUB, 'k' a word, 'f' a
function, 't' a type...
    void     (*complete) (CodeEdit &ed, const char *object);
    void    *user;                  // the program's (e.g. the document this editor shows)

    CodeEdit (int l, int t, int w, int h);
    ~CodeEdit () override;

    const char *text () const;
    int  length () const;
    void setText (const char *s);           // a new text: no undo, the caret at the start
    void replaceAll (const char *s, int caret); // the whole text replaced as one step that
can be undone
    void insertText (const char *s);        // at the caret, replacing the selection
    int  caret () const;
    int  caretLine () const;            // 0-based
```

```
    int  caretCol () const;
    int  lineCount () const;
    int  lineStart (int ln) const;          // the offset of a line (0-based)
    void gotoLine (int ln, bool select = false);    // the caret at a line's text (0-based),
shown in the middle
    void setCaret (int p);
    void showLine (int ln);             // a line (0-based) scrolled into view, the caret
left where it is
    bool hasSel () const;
    void selectAll ();
    void copy ();
    void cut ();
    void paste ();
    void undo ();
    void redo ();
    bool find (const char *w);          // the next w (any case) from the caret, chosen;
false: none
    void wordAt (int p, char *obj, int ocap, int *wordStart);   // the name before p, and the
object before its dot
    // The lines with a problem (1-based)
    void clearMarks ();
    void addMark (int line);
    bool hasMark (int line) const;
    void addCompletion (const char *name, char kind, const char *detail);   // (from
complete)

    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
    void resizeTo (int w, int h) override;
private:
    friend struct CodeEditOps;
    CodeEditState *m;
    unsigned long m_reserved[4] = { 0, 0, 0, 0 };   // (uikit/abi.h)
};
```

uikit/colorpick.h

uikit/colorpick.h -- a colour swatch; clicking expands a fixed 8x5 palette grid below it (the widget grows + comes to front while open, grabs outside clicks to close). cb fires when a colour is picked; read it from `color`.

```
class ColorPicker : public Widget
{
public:
    unsigned color; bool open; Action cb;
    ColorPicker (int l, int t, int w, int h, unsigned initial, Action cb_);
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
private:
    int m_boxW, m_boxH;
    void setOpen (bool o);
};
```

uikit/combobox.h

uikit/combobox.h -- an editable Textbox with a drop-down list of suggestions (WinForms ComboBox, DropDown style): type any text, or click the arrow (or press Down / Up) to pick one of the options -> the

text becomes that option and onPick fires with `picked` = its index. While open the widget grows downward over its siblings (like Dropdown).

```
class Combobox : public Textbox
{
public:
    enum { MAXOPT = 16, ARROW_W = 20 };
    char     opts[MAXOPT][64]; int nopts, picked, rowH; bool open; Action onPick;
    Combobox (int l, int t, int w, int h, const char *s = "", Action enter = 0, Action pick =
0);
    void clearOptions ();
    void addOption (const char *s);
    void pick (int i);          // set the text to option i, fire onPick
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
private:
    int  m_hot;             // the list's row under the pointer (-1 none)
    bool m_arrowHot = false;        // the pointer over the arrow
    int  rowAt (int mx, int my) const;
    void setOpen (bool o);
};
```

uikit/datagrid.h

uikit/datagrid.h -- DataGrid: a read-only table of rows and columns (WPF's DataGrid, a file manager's details view, a database's list). Virtual: the app says how many rows there are and gives each cell's text (cellText) -- or draws the cell itself (cellDraw: a colour swatch, a check mark...). On top, the header: the columns' titles in bold; a click on a title asks the app to sort (onSort, clickedCol: the app orders its rows, the grid shows sortCol / sortDesc as an arrow); a drag on a title's right edge resizes its column. Below, the rows: every other one a shade darker (stripes), a light line between the columns, the one under the pointer tinted, the selected one in the accent (dimmer while the grid has not the focus); both scroll bars when the rows or the columns do not fit (their thumbs drag, a click on the groove jumps there).

```
  Mouse: a click selects (onSelect), a double click activates (onActivate), a right click
  selects the row under it and asks for a menu (onContext: ctxRow -- -1 below the rows --,
  ctxX, ctxY: where, in the grid's coordinates); the wheel scrolls (with Shift: sideways).
  Keys (focused): Up / Down / Page Up / Page Down / Home / End move the selection (onSelect),
  Left / Right scroll sideways, Enter activates; the others go to the parent (Delete...).
```

A cell's text is cut to its column with "..." (the app's text: control characters shown as spaces). Integer only, as the rest of uikit.

```
  DataGrid *g = new DataGrid (0, 0, 600, 400);
  g->setColumns (2);
  g->setColumn (0, "Name", 200); g->setColumn (1, "Size", 90, GRID_RIGHT);
  g->cellText = my_text;          // const char *my_text (DataGrid &g, int row, int col, char
*buf, int cap)
  g->setRows (n);
```

```
enum { GRID_LEFT = 0, GRID_RIGHT = 1, GRID_CENTRE = 2 };
```

(P6) A column's role (setColumnRole; docs/POCKETUI-TECH-STUDY.md section 6.12): what a portrait card shows of it -- the PRIMARY column its title, the SECONDARY ones its subtitle, the DETAIL ones only the detail view.

```
enum { UK_COL_NONE = 0, UK_COL_PRIMARY = 1, UK_COL_SECONDARY = 2, UK_COL_DETAIL = 3 };
```

```
class DataGrid : public Widget
{
public:
    enum { MAXCOLS = 64 };
    struct Column { char title[48]; int width, align; };
    // A cell's text: written into buf (cap bytes) and returned, or a constant string
returned.
    typedef const char *(*CellText) (DataGrid &g, int row, int col, char *buf, int cap);
    // A cell drawn by the app: cv is clipped to the cell, whose box is (x, y, w, h) there;
ink is
    // the text's colour (on the selection or not). Return false to have the text drawn
instead.
    typedef bool (*CellDraw) (DataGrid &g, Canvas &cv, int row, int col, int x, int y, int w,
int h,
                  unsigned ink, bool selected);

    int  nrows, sel, top, left;     // the rows; the selected one (-1 none); the first shown;
px scrolled sideways
    int  rowH, headH;           // (default: the font's height + 8, + 10)
    int  sortCol; bool sortDesc;        // the title showing the sort's arrow (-1 none)
    bool sortable, stripes;         // titles clickable (onSort); every other row shaded
    CellText cellText; CellDraw cellDraw;
    Action onSelect, onActivate, onSort, onContext;
    int  clickedCol;            // (onSort) the title clicked
    int  ctxRow, ctxX, ctxY;        // (onContext) the row right-clicked (-1 none), where
    const char *emptyText;          // written in the body when there is no row (0: nothing)
    void *user;             // the app's (e.g. which table the grid shows)

    DataGrid (int l, int t, int w, int h);
    void setColumns (int n);        // n columns (untitled, 100 px wide, left-aligned)
    int  columns () const { return m_ncol; }
    void setColumn (int c, const char *title, int width, int align = GRID_LEFT);
    Column &column (int c) { return m_col[c < 0 ? 0 : c >= MAXCOLS ? MAXCOLS - 1 : c]; }
    // Column c as wide as its title and the texts of its first `sample` rows need, within
[minW, maxW].
    void autoSize (int c, int minW, int maxW, int sample = 300);
    void setRows (int n);           // the number of rows (the selection kept among them)
    void setSel (int r);            // select row r (-1: none) and scroll it into view; no
callback
    void ensureVisible (int r);
    int  rowAt (int y) const;       // the row under y (grid coordinates), -1 none
    int  totalWidth () const;       // the columns' widths added
    int  visibleRows () const;      // how many rows the body shows
    // (P6) The adaptive part (its state behind Widget::ext: the class's fields are frozen).
On the desktop the grid is
    // as always; in pocket the columns of the highest priorities give way when the grid is
too narrow (priority 0:
    // never), the rows are the profile's; in portrait a grid with a PRIMARY column draws its
rows as two-line cards
    // (the primary column, then the secondary ones) and a click opens the detail view
(setDetailView: the app's widget,
    // filled by its onActivate; Esc or Backspace goes back); console: big rows, the
selection glowing.
    void setColumnRole (int c, int role, int priority = 0); // UK_COL_*; priority 0: never
hidden, 1, 2...: hidden first
    bool columnShown (int c);           // (pocket: false when it gave way to the room)
    bool cards ();                  // the rows drawn as cards now (portrait, a primary
column)
    void setDetailView (Widget *w);         // (portrait) the widget shown over the grid when
a card is opened
```

```
    void closeDetail ();
    // Several rows chosen: Ctrl + a click adds or takes away one, Shift + a click a range
(sel stays the current row).
    void setMultiSelect (bool on);
    bool isSelected (int r);            // (single selection: r == sel)
    void setSelected (int r, bool on);
    int  selectedCount ();

    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
private:
    Column m_col[MAXCOLS]; int m_ncol;
    int  m_hotRow, m_hotHead;       // under the pointer (-1 none)
    int  m_drag;                // what the left button holds: a G_* below
    int  m_dragCol, m_dragX0, m_dragW0;
    unsigned m_lastClick; int m_lastRow;
    bool m_rdown;
    // The geometry: the body (the rows, below the header) and the scroll bars.
    void bars (bool *vbar, bool *hbar, int *bodyW, int *bodyH) const;
    int  colX (int c) const;        // a column's left edge in the body (scrolled)
    int  headAt (int mx) const;     // the title under x, -1
    int  edgeAt (int mx) const;     // the column whose right edge is under x, -1
    void clampScroll ();
    void pick (int r, bool fire);
};
```

uikit/dropdown.h

uikit/dropdown.h -- a non-editable drop-down list (the sibling of Combobox, same look): a closed box showing the selected option + a drop button; clicking expands a list below it (the widget grows downward while open and grabs outside clicks to close) -- above it when it does not fit below in the window and fits better there. Open, the list is over everything in the window (the widget is the window's child meanwhile -- the dialog's when it is in one --: uikit/lift.h): no parent clips it, nothing is drawn over it, wherever the box stands. Keyboard (when focused): Up / Down pick the previous / next option, Enter or Space opens / closes the list, Esc closes it. cb fires when the selection changes. The option strings are NOT copied: they must outlive the widget.

```
class Dropdown : public Widget
{
public:
    const char *const *opts; int nopts, sel, rowH; bool open; Action cb;
    Dropdown (int l, int t, int w, int h, const char *const *options, int n, int initial,
Action cb_);
    void setOptions (const char *const *options, int n, int initial);
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
private:
    int  m_hot;             // the row under the pointer while open (-1 none)
    bool m_up;              // open upward (the box at the bottom, `top` moved up)
    int  m_top0;                // ... its `top` when closed
    int  listTop () const;          // the open list's first row
    int  boxY () const { return m_up ? height - rowH : 0; } // the box's row
    int  rowAt (int mx, int my) const;  // the row at (mx, my) while open, or -1
    void setOpen (bool o);
};
```

The open list of a drop-down (Dropdown, Combobox): a floating panel at y0, n rows of rowH (sel: the chosen one, hot: the one under the pointer, -1 none).

```
void uk_draw_option_list (Canvas &cv, int y0, int w, int rowH, const char *const *opts, int
n,
              int sel, int hot);
```

uikit/flat.h

uikit/flat.h -- UIKit for a program that is not C++: a window and its widgets as handles, plain C functions on them. It is what Onyx BASIC calls (#import uikit: UIKit.window, UIKit.button ...; the code QBStudio makes of a form), and what a C program may call.

```
  void *win = uk_window ("Hello", 320, 120, 0);
  uk_label (win, 12, 12, 200, 20, "Your name:");
  void *name = uk_textbox (win, 12, 36, 200, 24, "", 0);
  uk_button (win, 220, 36, 80, 24, "OK", on_ok);          // void on_ok (void *button)
  uk_window_run (win);                                     // until the window is closed
```

A handle is a pointer the program keeps and gives back; 0 is "none" (a function given 0 does nothing). A program has one window. The widgets belong to their window and end with it. A text is Latin-1. A callback is called from uk_window_run (or uk_window_step), on the program's own thread.

MIT License -- Copyright (c) 2026 Stéphane Wegener and the Onyx contributors (docs/LICENSING.md).

```
typedef void (*uk_event) (void *widget);        // a widget's event: the widget it comes from
typedef void (*uk_resized) (void *window, int w, int h);
typedef void (*uk_chosen) (void);           // a menu item chosen
```

the window

```
enum { UK_FLAT_RESIZABLE = 1 };
void *uk_window (const char *title, int w, int h, int flags);   // the program's window (w x
h: its inside); 0: none
void uk_window_run (void *window);          // the events, until the window is closed (its
box, uk_window_close)
int  uk_window_step (void *window);         // ... one round of them, for a program with its
own loop: 0 once closed
int  uk_window_wait (void *window);         // ... one round and the wait before the next (16
ms): WHILE uk_window_wait (w) ... WEND
void uk_window_close (void *window);            // uk_window_run returns, uk_window_step
gives 0
int  uk_window_width (void *window);
int  uk_window_height (void *window);
void uk_window_min_size (void *window, int w, int h);   // the smallest a resizable window
goes
void uk_window_on_resize (void *window, uk_resized fn); // after the user resized it: place
the widgets again
```

the widgets (x, y, w, h: their place in what holds them)

What holds a widget -- the `window` every maker takes -- is the window itself or a panel: a plain area with widgets of its own, placed from its top left corner. Hiding, showing, moving a panel does it to all it holds: a page of an app is a panel, shown in place of another.

```
void *uk_panel (void *window, int x, int y, int w, int h);
void uk_set_parent (void *widget, void *window);    // the widget taken from what holds it
and put into a window or a panel
int  uk_width (void *widget);               // a widget's, a panel's, the window's size
```

```
int  uk_height (void *widget);
void *uk_label (void *window, int x, int y, int w, int h, const char *text);
void *uk_button (void *window, int x, int y, int w, int h, const char *text, uk_event
on_click);
void *uk_textbox (void *window, int x, int y, int w, int h, const char *text, uk_event
on_change);
void *uk_checkbox (void *window, int x, int y, int w, int h, const char *text, int checked,
uk_event on_click);
void *uk_listbox (void *window, int x, int y, int w, int h, const char *items, uk_event
on_change); // items: "one|two|three"
void *uk_dropdown (void *window, int x, int y, int w, int h, const char *items, uk_event
on_change);
void *uk_slider (void *window, int x, int y, int w, int h, int max, int value, uk_event
on_change); // from 0 to max
void *uk_progress (void *window, int x, int y, int w, int h, int max, int value);
void uk_set_range (void *widget, int min, int max); // a slider, a progress bar: its ends
```

A widget's text: a label's, a button's, a checkbox's, what a text box holds, the chosen item of a list or a drop-down. uk_get_text's result is good until the next call of UIKit.

```
void uk_set_text (void *widget, const char *text);
const char *uk_get_text (void *widget);
```

Its number: a checkbox's state (1 / 0), the chosen item's place in a list or a drop-down (from 0; -1: none), a slider's or a progress bar's value.

```
void uk_set_value (void *widget, int value);
int  uk_get_value (void *widget);
void uk_add_item (void *widget, const char *text);  // a list: one more item
void uk_clear_items (void *widget);          // a list: emptied
int  uk_item_count (void *widget);           // a list, a drop-down
void uk_move (void *widget, int x, int y, int w, int h);
void uk_show (void *widget, int on);
void uk_enable (void *widget, int on);
int  uk_shown (void *widget);
int  uk_enabled (void *widget);
void uk_focus (void *widget);
```

the menus (in the screen's menu bar while the window is the active one)

One more item in the menu `title` (made at its first item); item "-": a separator; key: "Ctrl+S" or "".

```
void uk_menu_item (void *window, const char *title, const char *item, const char *key,
uk_chosen on_choose);
```

the dialogs

```
int uk_message (const char *title, const char *text, int buttons);  // buttons 0 OK, 1 OK
Cancel, 2 Yes No, 3 Yes No Cancel -> 1 OK / Yes, 0 Cancel / No (3: 2 for No)
const char *uk_ask_open (const char *folder);       // the file chosen (": none); good until
the next call
const char *uk_ask_save (const char *folder, const char *name);

}
#endif
```

uikit/font.h

uikit/font.h -- Font: a bitmap font *family* loaded from one Onyx ".fnt" file on the SD card (e.g. SD:/fonts/ns-sans.fnt, the MIT "ns-sans" face exported by tools/fonts/ gen_nssans.py from NetSurf's

glyph_data). One file embeds all four styles; the header carries the glyph size and the file offset of each style block:

```
    0   "ONYF"  magic
    4   version (u8) | width (u8) | height (u8) | styles (u8)
    8   glyphs  (u16 LE, per style) | reserved (u16)
    12  offset[styles] (u32 LE each): file offset of each style block
        style index = (bold?2:0)|(italic?1:0): 0=reg 1=italic 2=bold 3=bold+italic
    ..  style blocks: glyphs * height bytes, 1 byte/row, bit 0x80 = leftmost px.
```

(A legacy 2-byte-header single-style .fon is also accepted, as one regular style.)

Draw with Canvas::drawFont (declared in canvas.h, implemented in font.cpp). A global default family is loaded once by uikit::init() and reachable via uikit::font(), so any widget can render styled text from a real face, not just the kernel's single font.

```
class Font
{
public:
    static const int MAXSTYLE = 4;
    unsigned char *data;        // whole file image; 0 = not loaded
    int  gw, gh, gcount, nstyles;   // glyph width/height, glyphs per style, style count
    unsigned off[MAXSTYLE];     // byte offset (within data) of each style block

    Font ();
    ~Font ();

    bool load (const char *path);               // (re)load an Onyx .fnt/.fon
    bool valid () const { return data != 0 && nstyles > 0; }
    int  width () const { return gw; }
    int  height () const { return gh; }
    int  styles () const { return nstyles; }
    // gh bytes (MSB-left rows), or 0. style 0=reg 1=italic 2=bold 3=bold+italic; a style
    // beyond what this family carries falls back to regular.
    const unsigned char *glyph (unsigned ch, int style = 0) const;

    // Named global families (loaded by uikit::init from SD:/fonts/<name>.fnt). Convenience
    // over font(id); a family whose file is absent falls back to Sans when drawn.
    static Font &Sans ();
    static Font &Serif ();
    static Font &Cursive ();
    static Font &Mono ();
};
```

The global named font registry. uikit::init() loads every known family once (idempotent; Root calls it at startup, so EVERY uikit app gets the fonts -- an app that builds no Root must call uikit::init() itself). A widget chooses a face by passing font(id) to drawFont.

```
enum { FONT_SANS = 0, FONT_SERIF, FONT_CURSIVE, FONT_MONO, FONT_COUNT };
void  init ();  // load the theme (SD:/etc/theme.txt) and the font families; only the first
call works
Font &font (int id = FONT_SANS);        // the family for `id`, or Sans if it isn't loaded
```

Draw `s` into a raw 0x00RRGGBB framebuffer (W x H) via the font registry -- for app-drawn windows that don't own a uikit Canvas. Scaled by `scale`, in `style`, family `id`. Falls back to the kernel font (kapi_draw_text_buf) when the family isn't loaded.

```
void draw_text (unsigned *fb, int W, int H, int x, int y, const char *s, unsigned color,
        int scale = 1, int style = 0, int id = FONT_SANS);
```

uikit/form.h

uikit/form.h -- FormDialog: a dialog that says what its rows are (a label and its control, a section's title, a paragraph, buttons with a role) and lets each UIKit lay them out (docs/POCKETUI-TECH-STUDY.md section 6.7, phase P6; docs/03 "The adaptive widgets"):

```
  the desktop, pocket in landscape  a box centred on the window: the labels in a column at
the left, the controls
                                    beside them, the buttons at the bottom right (the default
first, then Cancel)
  pocket in portrait                a sheet the window's width: each label over its control,
the controls the
                                    whole width, Cancel at the title's left and the default
at its right
  console                           the PS2's panel; Enter / the pad's cross the default, Esc
/ the circle Cancel
```

(Named FormDialog: QBStudio has a Form of its own, beside `using namespace uikit`.)

```
  FormDialog f (TR ("New Playlist"));
  Textbox *name = new Textbox (0, 0, 240, 26, "");
  f.addRow (TR ("Name:"), name);
  f.addButton (TR ("Create"), UK_FB_DEFAULT, 1);
  f.addButton (TR ("Cancel"), UK_FB_CANCEL, 0);
  if (f.run () == 1) ... name->text ...
```

A row's control keeps its height; a control 100 px wide or more takes the column's width (a field, a list), a narrower one keeps its own (a check box, a spin box). The controls are the dialog's children (freed with it).

MIT License -- Copyright (c) 2026 Stéphane Wegener and the Onyx contributors. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED.

```
enum { UK_FB_DEFAULT = 0, UK_FB_CANCEL = 1, UK_FB_DESTRUCTIVE = 2, UK_FB_OTHER = 3 };   // a
button's role

class FormDialog : public Modal
{
public:
    FormDialog (const char *title, int width = 0);  // width: the desktop's box (0: what the
rows need, 360 at least)
    ~FormDialog () override;
    void addSection (const char *title);        // a section's title over the rows that
follow (copied)
    Widget *addRow (const char *label, Widget *w);  // a label (copied; 0: the control alone,
the row's width) -> w
    void addText (const char *text);        // a paragraph, wrapped (copied)
    Button *addButton (const char *label, int role, int result);    // UK_FB_*; run () gives
`result` when it is pressed
    int  run ();                    // laid out, shown -> the result of the button pressed
```

```
(Enter: the default's,
                            // Esc: the Cancel's -- 0 without one)
    void onButton (int tag) override;
    bool onKey (long k) override;
    void onDraw () override;
    void layout () override;
    unsigned long fm_reserved_[2] = { 0, 0 };   // (uikit/abi.h rule 2: room for later; the
rows are behind ext)
    virtual void fm_reserved0 () {}         // (rule 3)
    virtual void fm_reserved1 () {}
};
```

uikit/global.h

uikit/global.h -- uikit's global variables (the palette, the installed text face: uikit/globals.inc).

They are the PROGRAM's variables: a program is linked at a fixed address and reads them directly (C_BG, uk_face_...), also from the toolkit's inline code compiled into it. When uikit is the shared library SD:/lib/uikit.so (ONYX_LIB_BUILD; docs/SHARED-LIBS-PLAN.md) its code cannot name a program's address: each variable is then a REFERENCE, bound when the library starts in a process to the address the program handed over (user/Runtime/lib.h TLibImports.data, in globals.inc's order) -- or to a copy of the library's own for a variable added after the program was built.

```
#define UIKIT_VAR(type, name)   extern type &name
#define UIKIT_VAR(type, name)   extern type name
```

uikit/groupbox.h

uikit/groupbox.h -- GroupBox: a titled frame around a group of controls (WPF GroupBox). Add the controls as its children; their (0,0) is the box's top-left, the frame line runs at y = font height / 2 and the content starts below the title (contentTop()).

```
class GroupBox : public Widget
{
public:
    char title[48]; unsigned bg, frame; // frame: 0 = etched (the default), else a line's
colour
    GroupBox (int l, int t, int w, int h, const char *title_, unsigned bg_ = C_BG);
    int  contentTop () const { return uk_fh () + 4; }
    void onDraw () override;
    unsigned bgColor () override { return bg; }
};
```

uikit/icon.h

uikit/icon.h -- a magenta-keyed BMP centred above an optional label; hover/press highlight + an optional "running" badge.

```
class Icon : public Widget
{
public:
    char     text[64]; unsigned *pix; int iw, ih; bool badged; Action cb; unsigned bg;
    Icon (int l, int t, int w, int h, const char *bmp, const char *label, Action cb_,
unsigned bg_ = C_BG);
    ~Icon () override;
    void setBadge (bool b);
    void setIcon (const char *bmp);     // (re)load the image (0/"" clears); repaints
    void onDraw () override;
```

```
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
};
```

uikit/imagebox.h

uikit/imagebox.h -- ImageBox: shows an image (WPF Image). load (path) reads BMP / GIF / PNG / JPEG / PCX / WebP (img/imgload.hpp -- first frame), or setPixels () takes 0x(AA)RRGGBB pixels (copied). stretch: IMG_NONE (1:1, centred, clipped), IMG_FIT (uniform, never enlarged beyond 1:1 unless `grow`), IMG_FILL (stretched to the box). Transparent pixels show the box background.

```
enum { IMG_NONE, IMG_FIT, IMG_FILL };

class ImageBox : public Widget
{
public:
    int stretch; bool grow; unsigned bg;
    ImageBox (int l, int t, int w, int h, int stretch_ = IMG_FIT, unsigned bg_ = C_BG);
    ~ImageBox ();
    bool load (const char *path);       // false: unreadable (the box shows nothing)
    void setPixels (const unsigned *px, int w, int h, bool hasAlpha = true);
    void clearImage ();
    int  imageWidth () const { return m_w; }
    int  imageHeight () const { return m_h; }
    void onDraw () override;
private:
    unsigned *m_px; int m_w, m_h;
};
```

uikit/knob.h

uikit/knob.h -- Knob: a rotary control (a studio's gain, pan, rate...). A 270-degree track (open at the bottom), the value's arc on it in the accent (or `arcColor`) -- from the start, or from the value 0 for a bipolar one (a pan: the top) --, a round cap with a pointer; an optional label and the value's text under it. Integer values in [vmin, vmax] (the apps are integer-only: a gain of -60.0 .. +6.0 dB is -600 .. 60, shown by a `format` callback).

```
  Knob *k = new Knob (x, y, 48, 64, -600, 60, 0, onGain);
  k->setLabel ("Gain"); k->format = fmt_db; k->setDefault (0);
```

Mouse: drag up / down (the whole range in 200 px; Shift held: 1000 px, fine), the wheel (a step), a double click: back to the default (setDefault). Keys when focused: Up / Right, Down / Left (a step), Page Up / Down (ten), Home / End (the ends), Delete (the default). onChange fires at each change of `value`. Sizes: the dial is the widget's width, less the captions' lines under it (about 24 .. 64 px across).

```
class Knob : public Widget
{
public:
    int  value, vmin, vmax;
    int  step;              // the wheel's / the keys' step (default: a 100th of the range)
    int  def; bool hasDef;      // the default (a double click, Delete); setDefault
    bool     bipolar;           // the arc from 0 (a pan, a detune: the top), not from the
start
    bool     showValue;         // the value's text under the dial (and the label)
    unsigned arcColor;          // the value's arc (UK_AUTO: the accent)
    TextFace *face;             // the captions' face (0: uikit's -- the installed face or
the bitmap font)
    void     (*format) (int value, char *out, int cap); // the value's text (0: the number)
    Action   onChange;
```

```
    Knob (int l, int t, int w, int h, int lo, int hi, int val, Action cb = 0);
    void setValue (int v, bool fire = false);   // clamped; repainted; onChange if fire and
it changed
    void setRange (int lo, int hi);
    void setDefault (int v) { def = v; hasDef = true; }
    void setLabel (const char *s);
    const char *label () const { return m_label; }
    void valueText (char *out, int cap) const;  // what is shown under the dial

    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
private:
    char     m_label[24];
    bool     m_drag, m_fine;
    int  m_y0, m_v0;            // the drag's start: its y, the value then
    unsigned m_lastClick;           // ticks (a double click)
    int  lines () const { return (m_label[0] ? 1 : 0) + (showValue ? 1 : 0); }
};
```

uikit/lang.h

uikit/lang.h -- an app's words in the user's language. The sources keep their English words, wrapped: TR ("Save") is the word in the language chosen, else the English one. TRC ("status", "Open") for a word whose translation depends on where it stands (the key "status|Open" in the catalogue).

The catalogues are UTF-8 text files, a line a word: "Englishtranslation" (\t, \n, \ escaped; "#" begins a comment line):

```
  SD:/res/lang/<code>.txt                 uikit's own words (the dialogs' buttons, the
months...)
  SD:/apps/<app>.app/lang/<code>.txt      the app's
```

The language is the system's (SD:/etc/system.ini's "language=", systemkit/locale.h: the Control Panel's Language & Region applet, Setup); none said: English. An app has no choice of its own. (An app ported to another system -- the Mac's Ledger -- keeps its own there: SD:/apps/.app/lang.txt, uk_lang_choose.) An app drawing with uikit's bitmap fonts gets the words in Latin-1 (as they draw it), one with a text face (FreeType's) in UTF-8: install the face before uk_lang_init. tools/lang/check.py says the words of an app its catalogue has not.

```
const char *uk_tr (const char *en);         // the translation, else en itself
const char *uk_trc (const char *ctx, const char *en);   // "ctx|en"'s, else en's, else en
#define TR(s)       uk_tr (s)
#define TRC(c, s)   uk_trc (c, s)
#define TRN(s)      (s)         // a word kept in English in a table and given to TR () where
it is drawn: marked for tools/lang/check.py

void        uk_lang_init ();                // the system's language loaded -- before the UI
is built
bool        uk_lang_load (const char *code);        // that language's catalogues ("en":
none) -> false: none found
const char *uk_lang ();                 // the language in use: "en", "fr"...
const char *uk_lang_chosen ();              // the system's (locale_language: "en" when none
is said)
bool        uk_lang_choose (const char *code);      // the system's language changed
(locale_set_language; taken by the programs started next)
```

uikit/layout.h

uikit/layout.h -- automatic layout containers (Panels that re-flow their children on resize and on child add/remove, via the Widget::layout() hook). The children stay passive: they never recompute their own geometry -- the container places them, so a resize cascades down for free (e.g. a calculator filling the secondary section).

```
  VerticalStackPanel   -- single column, children top->bottom, full width, each keeps
                          its own HEIGHT (no fixed row height).
  HorizontalStackPanel -- single row,   children left->right, full height, each keeps
                          its own WIDTH  (no fixed column width).
  UniformGridLayout    -- cols columns of uniform cells, filled in reading order
                          (left->right, top->bottom). Cell WIDTH derives from the
                          panel width; cell HEIGHT is either a fixed `rowH` (px) or,
                          when `rows > 0`, the panel height divided into `rows` rows.
                          A child may span several columns/rows via its colSpan /
                          rowSpan (default 1) -- e.g. a calculator display spanning 4
                          of 5 columns. Reflows on resize / child add.
                          NB: rowSpan only sizes the child taller; it does not reserve
                          the cells below for following children (simple flow model).
```

All take a `pad` (outer margin) and `gap` (inter-child spacing), public for tuning.

```
class VerticalStackPanel : public Panel
{
public:
    int pad, gap;
    VerticalStackPanel (int l, int t, int w, int h, unsigned bg = C_BG, int pad_ = 0, int
gap_ = 4)
      : Panel (l, t, w, h, bg), pad (pad_), gap (gap_) {}
    void layout () override;
};

class HorizontalStackPanel : public Panel
{
public:
    int pad, gap;
    HorizontalStackPanel (int l, int t, int w, int h, unsigned bg = C_BG, int pad_ = 0, int
gap_ = 4)
      : Panel (l, t, w, h, bg), pad (pad_), gap (gap_) {}
    void layout () override;
};

class UniformGridLayout : public Panel
{
public:
    int cols, rows, rowH, pad, gap;     // rows > 0 -> cell H = height/rows; else rowH (px)
    UniformGridLayout (int l, int t, int w, int h, int cols_, int rowH_,
                       unsigned bg = C_BG, int pad_ = 4, int gap_ = 4)
      : Panel (l, t, w, h, bg), cols (cols_ < 1 ? 1 : cols_), rows (0), rowH (rowH_),
        pad (pad_), gap (gap_) {}
    void setRows (int n) { rows = n; layout (); invalidate (true); }    // divide height into
n rows
    void layout () override;
};
```

uikit/lcd.h

uikit/lcd.h -- LcdDisplay: a label drawn as a studio's time / position display: a sunken well (dark in a dark theme, the accent's pale tint in a light one), large digits in the accent (a face given to it, else the bitmap font scaled up), and at its right a small caption over a second line ("BAR.BEAT.16" over "0:14.83").

```
  LcdDisplay *pos = new LcdDisplay (x, y, 190, 40, "6.3.2", "BAR.BEAT.16");
  pos->setSub ("0:14.83");  ...  pos->setText ("6.3.3");    (repainted only when it changed)
  pos->face = bigFace;      (e.g. an FtTextFace at 24 px: fontkit/uikitface.h)
```

```
class LcdDisplay : public Widget
{
public:
    TextFace *face;             // the digits' face (0: the bitmap font, scaled)
    TextFace *smallFace;            // the caption's and the second line's (0: uikit's)
    int  scale;             // the bitmap digits' scale (0: from the height, as large as
fits)
    unsigned ink;               // the digits' colour (UK_AUTO: the accent, for the well)
    bool     centred;           // the digits centred in the room left (else from the left)

    LcdDisplay (int l, int t, int w, int h, const char *text = "", const char *caption = 0);
    void setText (const char *s);
    void setCaption (const char *s);
    void setSub (const char *s);
    const char *text () const { return m_text; }

    void onDraw () override;
private:
    char     m_text[32], m_cap[32], m_sub[32];
};
```

uikit/listbox.h

uikit/listbox.h -- ListBox: a scrollable list of text items with a selection (WPF ListBox). Click selects (onSelect), double-click or Enter activates (onActivate); Up / Down / Page Up / Page Down / Home / End move; the wheel and the scrollbar (drag the thumb or click the track) scroll. Items are copied (64 chars max each).

```
class ListBox : public Widget
{
public:
    int count, sel, top; Action onSelect, onActivate;
    ListBox (int l, int t, int w, int h, Action onSelect_ = 0, Action onActivate_ = 0);
    ~ListBox ();
    void add (const char *s);
    void clear ();
    const char *item (int i) const { return (i >= 0 && i < count) ? m_items[i] : ""; }
    void setSel (int i);            // select + scroll into view (no callback)
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
private:
    char (*m_items)[64]; int m_cap;
    unsigned m_lastClick; int m_lastIdx; bool m_thumb;
    int rows () const;
    void scrollTo (int t);
    void pick (int i, bool fire);
};
```

uikit/menu.h

uikit/menu.h -- an app's menus for the SYSTEM menu bar (top of the screen, the `menubar` app). Build them once after the Root window exists, then publish():

```
  static Menu menu;
  menu.menu ("File");
  menu.item ("Open...", "^O", UK_CTRL ('O'), onOpen);
  menu.separator ();
  menu.item ("Save",    "^S", UK_CTRL ('S'), onSave);
  menu.publish ();
```

The menu bar shows them while this app is the active one and sends the chosen item back (GUI_EVENT_MENU); Menu runs the item's callback. Menu also handles the items' keyboard shortcuts (Root routes every key through Menu::shortcut first) and ^Q = Quit. The bar adds the app-name menu with "Quit" itself.

```
#define UK_CTRL(c)  ((long) ((c) & 0x1F))   // Ctrl+letter key code (^A = 1 ... ^Z = 26)

typedef void (*MenuAction) ();  // a menu item's callback (chosen in the bar, or its shortcut
typed)

class Menu
{
public:
    Menu ();
    void menu (const char *title);              // start a new menu
    void item (const char *label, const char *shortcutText, long key, MenuAction cb);
    void separator ();
    void publish ();                    // hand the menus to the menu bar
    bool shortcut (long key);               // run the item bound to `key`
    static Menu *current ();                // the published menu (or 0)
private:
    enum { MAXITEMS = 64 };
    char       m_spec[WIN_MENU_MAX_USER];
    int    m_len;
    MenuAction m_cb[MAXITEMS];
    long       m_key[MAXITEMS];
    int    m_count;
    void put (const char *s);
    static void handler (unsigned long, int ev, gui_value v);
};
```

uikit/numeric.h

uikit/numeric.h -- NumericUpDown: an integer field with up/down arrows (WPF-style spinner). Arrows / the wheel / Up / Down / Page Up / Page Down step it; typing digits (and '-') edits it, Enter or leaving the field commits. Clamped to [vmin, vmax]; cb fires on every change of `value`.

```
class NumericUpDown : public Widget
{
public:
    int value, vmin, vmax, step; Action cb;
    NumericUpDown (int l, int t, int w, int h, int lo, int hi, int val, int step_, Action
cb_);
    void setValue (int v);          // clamp, repaint, fire cb if it changed
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
```

```
private:
    char m_edit[16]; int m_elen;        // digits being typed (m_elen < 0: not editing)
    int  m_down;                // the arrow held: 1 up, 2 down, 0 none
    void commit ();
};
```

uikit/paint.h

uikit/paint.h -- the procedural painter of the desktop's look: no skin bitmap, everything drawn by code from a few theme colours (uikit/theme.h), integer arithmetic only (the apps build with -mgeneral-regs-only).

```
  * A shade from a colour: a grey profile -- level 128 = the colour itself, above toward
white,
    below toward black -- so any hue lightens as well as darkens (uk_tone).
  * A gradient: a colour a row, computed at the size being drawn (a button stretches at
will).
  * Rounded corners without a formula at draw time: per radius, a table made once of each of
the
    corner's rows' first pixel and the opacities of its partly covered pixels (the anti-
    aliasing); a row is then a straight span plus a few pixels blended over what the canvas
    holds -- so a widget first fills its canvas with its parent's background.
  * The push button: a raised face (a gradient, a light top edge, an outline; pressed: a
shade
    darker), the same as a drop-down's box -- no frame round it.
  * Small glyphs (a check, arrows, a cross...) from their geometry, anti-aliased by coverage.
```

the canvas

The alpha mode: the canvas's pixels carry a transparency in their top byte (0 opaque .. 255 see-through: a WIN_FLAG_ALPHA window -- clear it to 0xFF000000 first); what is drawn over a see-through pixel keeps its own colour, partly see-through where it is anti-aliased. Off by default (an opaque canvas: the blends are over what it holds).

```
void uk_paint_alpha (bool on);
```

One pixel of c at opacity a (0..255) over what the canvas holds (the alpha mode heeded).

```
void uk_blend_px (Canvas &cv, int x, int y, unsigned c, int a);
```

colours

```
unsigned uk_tone (unsigned c, int level);       // the grey profile: 128 = c, 255 = white, 0
= black
unsigned uk_mix (unsigned a, unsigned b, int t);    // t = 0 (a) .. 256 (b)
static inline unsigned uk_over (unsigned dst, unsigned c, int alpha)    // c at opacity
0..255 over dst
{ return uk_mix (dst, c, alpha + (alpha >> 7)); }
int      uk_bright (unsigned c);            // 0..255 (0.30 R + 0.59 G + 0.11 B)
unsigned uk_ink_on (unsigned c);            // dark or white text on c
```

shapes

The rounded corner of radius r (1..16): for each of its rows (the top one first), the x offset of its first pixel, the number of partly covered pixels from there and their opacities (0..255).

```
struct UkCorner { int r; unsigned char off[16], n[16], a[16][16]; };
const UkCorner &uk_corner (int r);  // the table for radius r (clamped to 1..16), computed
once and kept
```

A rounded box [x, x + w) x [y, y + h), corners of radius r (0 = square; which ones: UK_TL | UK_TR | UK_BL | UK_BR, all by default), filled with a vertical gradient from `top` (its first row) to `bottom` (its last), at opacity alpha (255 = opaque); the corners' edges blended over what the canvas holds.

```
enum { UK_TL = 1, UK_TR = 2, UK_BL = 4, UK_BR = 8, UK_ALL = 15 };
void uk_rbox (Canvas &cv, int x, int y, int w, int h, int r, unsigned top, unsigned bottom,
          int alpha = 255, int corners = UK_ALL);   // fill a rounded box with a vertical
gradient, top to bottom
```

Its 1-px outline in colour c at opacity alpha.

```
void uk_rline (Canvas &cv, int x, int y, int w, int h, int r, unsigned c, int alpha = 255,
           int corners = UK_ALL);
```

the look's pieces

```
enum { UK_NORMAL = 0, UK_HOT = 1, UK_PRESSED = 2, UK_DISABLED = 3, UK_FOCUS = 0x10 };
```

The push button in the box, from its face colour: a raised face as a drop-down's (uk_raised; it had a frame and a well round it: the name); returns the label's box in *bx..*bh (already 1 px lower right when pressed) if the pointers are given.

```
void uk_framed (Canvas &cv, int x, int y, int w, int h, unsigned face, int state,
        int *bx = 0, int *by = 0, int *bw = 0, int *bh = 0);
```

A raised face (a header, a tab, a handle, a scroll bar's thumb): a gradient, a light top edge, an outline.

```
void uk_raised (Canvas &cv, int x, int y, int w, int h, int r, unsigned face, int state =
UK_NORMAL);
```

A sunken field (a text box, a list, a display): its background, a shadow along the top, an outline -- the accent's when focused.

```
void uk_sunken (Canvas &cv, int x, int y, int w, int h, int r, unsigned bg, bool focus =
false);
```

An etched line (a groove: dark over light) across a face.

```
void uk_etch_h (Canvas &cv, int x, int y, int w, unsigned face);
void uk_etch_v (Canvas &cv, int x, int y, int h, unsigned face);
```

An etched rounded frame (a group box's), the same groove all round.

```
void uk_etch_box (Canvas &cv, int x, int y, int w, int h, int r, unsigned face);
```

The controls' marks, s x s at (x, y) (state: UK_NORMAL / HOT / PRESSED / DISABLED | FOCUS): a check box (a sunken rounded field; checked: the accent, a white check), a radio button (the same, round; checked: a white dot on the accent), a switch (a pill: the accent when on, a knob that slides) w x h.

```
void uk_check_mark (Canvas &cv, int x, int y, int s, bool checked, int state);
void uk_radio_mark (Canvas &cv, int x, int y, int s, bool checked, int state);
void uk_switch_mark (Canvas &cv, int x, int y, int w, int h, bool on, int state);
```

A scroll bar in the box: a groove (the track, a shade of `bg`), the thumb a raised pill at [pos, pos + len) along it (state: UK_HOT while pointed / dragged).

```
void uk_scroll_bar (Canvas &cv, int x, int y, int w, int h, bool vertical, int pos, int len,
            unsigned bg, int state = UK_NORMAL);
```

A slider's groove (the accent up to `fill` px) and its knob at `kx` (a raised rounded thumb), across w x h.

```
void uk_slider_mark (Canvas &cv, int x, int y, int w, int h, int fill, int kx, int kw, int
state);
```

A bar that fills (a progress bar): a sunken track, `fill` px of the accent's gradient.

```
void uk_progress_bar (Canvas &cv, int x, int y, int w, int h, int fill);
```

A floating panel (a drop-down list, a menu, a drawer, a tooltip): a light face, rounded, an outline; its corners' outside set to the magenta key (the widget is blitted transparent: what lies below shows there), their inside blended toward the outline.

```
void uk_popup (Canvas &cv, int x, int y, int w, int h, int r, unsigned face);
```

Set the pixels of the box's rounded corners that are mostly outside to the magenta key.

```
void uk_corner_key (Canvas &cv, int x, int y, int w, int h, int r);
```

A highlighted row (a selection, the item under the pointer): the accent, rounded; dimmer when its list does not have the focus. The text on it: uk_hilite_ink.

```
void uk_hilite (Canvas &cv, int x, int y, int w, int h, int r, bool strong = true);
unsigned uk_hilite_ink (bool strong = true);
```

A small window-like title strip (a dialog's): the active frame's colour, a gradient (Milk's down to C_FACE: the box under it, the dialog's face), its text bold and centred.

```
void uk_title_strip (Canvas &cv, int x, int y, int w, int h, const char *s, int r = 0);
```

A glossy bead d x d at (x, y) in colour c (the Milk theme's title buttons, as OS X's): a sphere of gel -- darker at the top, lit at the bottom, a white gloss over its upper half, a dark rim; anti-aliased over what the canvas holds.

```
void uk_bead (Canvas &cv, int x, int y, int d, unsigned c);
```

glyphs

```
enum { WKG_CHECK, WKG_UP, WKG_DOWN, WKG_LEFT, WKG_RIGHT, WKG_CLOSE, WKG_MIN, WKG_MAX,
WKG_MENU,
       WKG_DOT, WKG_PLUS, WKG_MINUS, WKG_RESTORE, WKG_CHEV_UP, WKG_CHEV_DOWN, WKG_CHEV_LEFT,
       WKG_CHEV_RIGHT, WKG_RING, WKG_LOCK, WKG_GEAR, WKG_POWER,
       WKG_RELOAD, WKG_HOME,    // (a circular arrow, a house: a browser's toolbar)
       WKG_HISTORY };       // (a clock: a browser's history)
```

A glyph centred on (cx, cy), about `size` px across, in colour c.

```
void uk_glyph (Canvas &cv, int kind, int cx, int cy, int size, unsigned c);
```

text

The theme's text in a box: centred, or left-aligned at x (vertically centred).

```
void uk_text_c (Canvas &cv, int x, int y, int w, int h, const char *s, unsigned c, int style
= 0);
void uk_text_l (Canvas &cv, int x, int y, int h, const char *s, unsigned c, int style = 0);
```

The text colour for a background: C_TEXT on the window's face and on what is as light (or as dark), else black or white (uk_ink_on): a label on a program's own colour stays readable.

```
unsigned uk_ink_for (unsigned bg);
int  uk_text_w (const char *s, int style = 0);
```

uikit/panel.h

uikit/panel.h -- a plain container with a solid background; holds child widgets.

```
class Panel : public Widget
{
public:
    unsigned bg;
    Panel (int l, int t, int w, int h, unsigned bg_ = C_BG);
    unsigned bgColor () override { return bg; }
    void onDraw () override;
};
```

uikit/progress.h

uikit/progress.h -- non-interactive bar, fills proportionally.

```
class Progress : public Widget
{
public:
    int value, vmin, vmax;
    Progress (int l, int t, int w, int h, int lo, int hi, int val);
    void setValue (int v);
    void onDraw () override;
};
```

uikit/radio.h

uikit/radio.h -- RadioButton: a round button + label; the buttons of the same `group` under the same parent are exclusive (selecting one clears the others). cb fires on selection. GroupBox (groupbox.h) is the usual container for a set of them.

```
class RadioButton : public Widget
{
public:
    char     text[64]; int group; bool checked; Action cb; unsigned bg;
    RadioButton (int l, int t, int w, int h, const char *s, int group_, bool chk, Action cb_,
unsigned bg_ = C_BG);
    void select ();             // check me, uncheck my group's siblings, fire cb
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;       // Space / Enter select
    RadioButton *asRadio () override { return this; }
};
```

The checked button of `group` among parent's children (0 = none).

```
RadioButton *uk_radio_checked (Widget *parent, int group);
```

uikit/richtextbox.h

uikit/richtextbox.h -- multi-line *styled* text editor (word processor body). Unlike Textarea (one colour, one size), every character carries its own style: bold / italic / underline / strikethrough / highlight, a 16-colour foreground + highlight palette, and an integer size multiplier (x1..x8, smoothed). Paragraphs carry a heading "level" (Normal / Titre 1-3) applied as a preset across the paragraph.

All styling is synthesised user-side from Onyx's single monospace bitmap font: the glyph mask is fetched via kapi_draw_text_buf, then emboldened / sheared / bilinearly upscaled and blended -- no kernel/ABI change, no FreeType. Default page is white, text black. The widget owns its text buffer + a parallel per-char attribute buffer.

character style flags (bits 0..7 of the packed attribute)

```
enum {
    RT_BOLD   = 0x01,
    RT_ITALIC = 0x02,
    RT_UNDER  = 0x04,
    RT_STRIKE = 0x08,
    RT_HILITE = 0x10,   // draw the highlight (background) band
};
```

16-colour palette indices (see RT_PAL[] in the .cpp)

```
enum {
    RT_BLACK = 0, RT_WHITE, RT_GRAY,  RT_SILVER,
    RT_RED,       RT_GREEN, RT_BLUE,  RT_YELLOW,
    RT_CYAN,      RT_MAGENTA, RT_ORANGE, RT_PURPLE,
    RT_DKRED,     RT_DKGREEN, RT_DKBLUE, RT_TEAL,
};
```

paragraph heading levels (presets applied by setLevel)

```
enum { RT_NORMAL = 0, RT_TITLE1, RT_TITLE2, RT_TITLE3 };
```

Unpacked character style (public API + the "current typing style"). Packs into one u32 stored per character, parallel to the text buffer.

```
struct RtStyle
{
    unsigned char flags;    // RT_BOLD | RT_ITALIC | ...
    unsigned char fg;   // foreground palette index
    unsigned char bg;   // highlight palette index (used when RT_HILITE set)
    unsigned char size; // 1..8 (font cell multiplier)
    RtStyle () : flags (0), fg (RT_BLACK), bg (RT_YELLOW), size (1) {}
};

unsigned rt_pack   (const RtStyle &s);      // RtStyle  -> packed u32
RtStyle  rt_unpack (unsigned a);        // packed u32 -> RtStyle
unsigned rt_color  (int paletteIndex);      // palette index -> 0x00RRGGBB

class RichTextBox : public Widget
{
public:
    char     *buf;      // text ('\n' between paragraphs), NUL-terminated
    unsigned *attr;     // packed RtStyle per character (parallel to buf)
    int       cap, len, caret, sel; // sel = selection anchor (-1 = none)
    int       top;      // first visible VISUAL (wrapped) row
    int       goalX;    // desired caret x for vertical moves (pixels, row-relative)
    bool      readonly;
    RtStyle   cur;      // style stamped onto newly typed characters

    RichTextBox (int l, int t, int w, int h, int capacity);
    ~RichTextBox () override;

    void        setContent (const char *s); // load plain text in the default style
```

```
    const char *content () const { return buf; }
    int         length  () const { return len; }

    // ---- styling: applies to the selection, else to `cur` (next typed text) ----
    void toggleFlag  (unsigned flag);   // bold/italic/underline/strike/hilite
    void setFg       (int paletteIndex);
    void setHilite   (int paletteIndex);    // set RT_HILITE + highlight colour
    void clearHilite ();
    void setSize     (int mult);        // 1..8
    void setLevel    (int level);       // RT_NORMAL / RT_TITLE1.. on caret paragraph(s)
    void selectAll   ();

    // ---- clipboard support (plain text) ----
    bool hasSelection () const { return hasSel (); }
    int  selectedText (char *out, int cap) const;   // copy the selection, NUL-terminated
    void cutSelection ();               // delete the selection
    void insertText  (const char *s);       // replace the selection / insert at the caret
    RtStyle caretStyle () const;        // style at the caret (for toolbar state)

    // ---- scrolling (a host Scrollbar wires value<->topRow, vmax<->rowCount-1) ----
    int  rowCount ();           // total visual rows
    int  topRow () const { return top; }
    void setTopRow (int r);

    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;

private:
    // text buffer
    bool grow (int need);
    void insertChar (char ch);
    void deleteRange (int a, int b);    // remove [a,b)
    bool hasSel () const { return sel >= 0 && sel != caret; }
    void selRange (int &a, int &b) const;
    void deleteSelection ();

    // paragraph / glyph metrics
    int  paraStart (int i) const { while (i > 0 && buf[i - 1] != '\n') i--; return i; }
    int  paraEnd   (int i) const { while (i < len && buf[i] != '\n') i++; return i; }
    int  glyphAdvance (int i) const;

    // word-wrap layout cache (rebuilt lazily on edit / resize)
    int *rowStart, *rowH, *rowY;    // rowY has rowN+1 entries (prefix tops + total)
    int  rowN, rowCap, lastWrapW;
    bool layoutDirty;
    bool barDrag;               // dragging the integrated scrollbar thumb
    void ensureLayout ();
    void relayout (int wrapW);
    void rowAt (int s, int wrapW, int &end, int &h, int &nextStart, bool &hard) const;
    bool growRows (int need);
    int  rowOfChar (int c);
    int  xInRow (int pos);
    void ensureVisible ();
    void moveVert (int dir);
    int  hitTest (int mx, int my);

    // styled glyph rasteriser
```

```
    void drawGlyph (int px, int py, char ch, const RtStyle &st);
};
```

uikit/scrollbar.h

uikit/scrollbar.h -- draggable thumb (vertical or horizontal), value in [0,vmax].

```
class Scrollbar : public Widget
{
public:
    bool vertical; int value, vmax; Action cb;
    Scrollbar (int l, int t, int w, int h, bool vert, int maxv, int val, Action cb_);
    void setFromXY (int px, int py);
    void scrollBy (int units);      // clamp value+=units, fire cb (wheel / keyboard)
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
};
```

uikit/segmented.h

uikit/segmented.h -- SegmentedControl: a row of mutually exclusive labelled segments drawn as one pill (a radio group, a small tab strip): the chosen one filled with the accent. Click a segment, or Left / Right when focused; onChange fires when `selected` changes. The labels are copied.

```
  static const char *const MODES[] = { "Articulation", "Melodic cell", "Voicing" };
  SegmentedControl *sc = new SegmentedControl (x, y, 300, 26, MODES, 3, 0, onMode);
```

```
class SegmentedControl : public Widget
{
public:
    static const int MAXSEG = 12;
    int  selected;          // the chosen segment (-1: none)
    bool     equalWidths;           // every segment as wide (default); false: each its
text's width,
                        // the room left shared out
    Action   onChange;
```

```
    SegmentedControl (int l, int t, int w, int h, const char *const *labels, int n, int sel =
0, Action cb = 0);
    void setLabels (const char *const *labels, int n);
    void select (int i, bool fire = false); // repainted; onChange if fire and it changed
    int  count () const { return m_n; }
    const char *label (int i) const { return i >= 0 && i < m_n ? m_label[i] : ""; }
    void setEnabled (int i, bool on);   // a segment greyed out (not chosen by a click)
    int  segmentAt (int mx) const;      // the segment under x (-1: none)
```

```
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
private:
    char     m_label[MAXSEG][32];
    bool     m_off[MAXSEG];
    int  m_n, m_hot, m_x[MAXSEG + 1];   // the segments' edges (m_x[i] .. m_x[i + 1])
    void     place ();
};
```

uikit/sidepanel.h

uikit/sidepanel.h -- SidePanel: a side panel that says what it is -- a NAVIGATION list at the left (the places of a library, the mailboxes, the modules) or an INSPECTOR at the right (a layers' list, the properties) -- so

that each UIKit shows it as its mode wants (docs/POCKETUI-TECH-STUDY.md section 6.8, phase P6; docs/03 "The adaptive widgets"):

```
  presentation    the desktop       pocket, landscape            pocket, portrait
console
  navigation      UK_SP_FULL        UK_SP_RAIL (icons; the       UK_SP_DRAWER (opened by
UK_SP_COLUMN (big rows,
                  (today's sidebar)  labels on hover / focus)      its button or its tab)
L1 / R1 the sections)
  inspector       UK_SP_FULL        UK_SP_SLIDEOVER (over the    UK_SP_SHEET (a bottom
UK_SP_SLIDEOVER (opened
                                    content from the right)      sheet, half or whole)     on
demand)
  (a wide pocket screen -- the window at least four times the panel's width -- keeps
UK_SP_FULL; a navigation panel
   of free content only, without items, goes from UK_SP_FULL to a drawer: a rail could not
show it)
```

Its content: STRUCTURED ITEMS (what a rail, a drawer, a console column can all draw) -- headings (foldable), items with an icon, an indent, a badge (a count, a dot), a short value at the right, a picture (a layer, a page), a toggle (a layer's eye) -- and FREE CONTENT as the fallback: pages (an inspector's tabs: any widget each), a content under the items (a tree, a month), a footer (the chosen item's controls, buttons). The app lays its own content out with reservedWidth () (what the panel takes now at its side: the rail's width, 0 for an overlay) and onPresentation.

```
  SidePanel *sp = new SidePanel (0, 52, 208, h, UK_SP_LEFT, UK_SP_NAVIGATION);
  sp->setIconFn (my_icon);                          // the app's icons (else: icon = a WKG_*
glyph)
  sp->addItem (1, "Home", I_HOME);
  sp->addHeading ("LIBRARY");  sp->addItem (2, "Artists", I_PERSON);  ...
  sp->onSelect = go;  sp->select (1);
  sp->place (0, 52, 208, h);  content->left = sp->reservedWidth ();  (again in onPresentation
and the window's resize)
```

On the desktop it is today's sidebar (rows of 28 px, the chosen one in the accent; the headings small, bold, dim); its width is the app's (setWidths gives the range a splitter may use).

MIT License -- Copyright (c) 2026 Stéphane Wegener and the Onyx contributors. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED.

```
enum { UK_SP_LEFT = 0, UK_SP_RIGHT = 1 };                // the side
enum { UK_SP_NAVIGATION = 0, UK_SP_INSPECTOR = 1 };          // the role
enum { UK_SP_FULL = 0, UK_SP_RAIL, UK_SP_DRAWER, UK_SP_SLIDEOVER, UK_SP_SHEET, UK_SP_COLUMN,
UK_SP_HIDDEN };    // presentation ()
enum { UK_SPI_HEADING = 1, UK_SPI_FOLDABLE = 2, UK_SPI_DISABLED = 4, UK_SPI_SEPARATOR = 8,
UK_SPI_FOLDED = 16 };    // an item's flags
enum { UK_SP_TOGGLE_ON = -2, UK_SP_TOGGLE_OFF = -3 };       // the icon ids an icon function
gets for a toggle
```

The app's icons: icon `id` drawn in the size x size box at (x, y) in ink (selected: on the accent).

```
typedef void (*SpIconFn) (Canvas &cv, int id, int x, int y, int size, unsigned ink, bool
selected);

class SidePanel : public Widget
{
public:
    SidePanel (int l, int t, int w, int h, int side = UK_SP_LEFT, int role =
UK_SP_NAVIGATION);
    ~SidePanel () override;

    // ---- the structured items
-------------------------------------------------------------------------------
    int  addHeading (const char *label, unsigned flags = 0);    // -> its id
(UK_SPI_FOLDABLE: a click folds it)
    int  addSeparator ();                   // -> its id
    // An item (id: the app's, >= 0) with an icon (-1: none), an indent level, under a
heading (-1: the last one added).
    int  addItem (int id, const char *label, int icon = -1, int level = 0, int under = -1);
    void setLabel (int id, const char *label);      // (labels are copied, 63 bytes at most)
    void setIcon (int id, int icon);
    void setBadge (int id, int count);          // 0: none; > 0 a pill ("3"); -1 a dot
    void setTrailing (int id, const char *text);        // a short value at the right ("80
%", "12")
    // A line of help under the label (copied, 95 bytes at most): shown when the panel is
whole, 240 px wide or more
    // and every item fits at two lines (a settings list on a big screen); else the label
alone.
    void setSubtitle (int id, const char *text);
    void setThumb (int id, const unsigned *px, int w, int h);   // a picture (copied; 0:
none) -- the rows grow for it
    void setToggle (int id, int on);            // -1: none; 0 / 1: a toggle (a layer's eye)
before the label
    void setFlags (int id, unsigned flags);
    unsigned flags (int id);
    void moveItem (int id, int beforeId);           // (-1: to the end)
    void remove (int id);
    void clear ();                      // every item (the pages, the content and the footer
stay)
    void select (int id, bool fire = false);        // (-1: none)
    int  selected ();
    int  itemAt (int x, int y);             // the item under (x, y) of the panel, -1
    bool dropAt (int x, int y, int type, const char *data, int len);    // a drop the app's
Root got over the panel -> onDrop

    void (*onSelect) (SidePanel &, int id);         // an item chosen (a click, Enter, L1 /
R1)
    void (*onToggle) (SidePanel &, int id, int on);     // its toggle clicked (on: the new
state)
    void (*onItemMenu) (SidePanel &, int id, int x, int y); // a right click (x, y: the
window's)
    bool (*onDrop) (SidePanel &, int id, int type, const char *data, int len);  // a file
dropped on a place (dropAt)
    void (*onReorder) (SidePanel &, int id, int beforeId);  // an item dragged (0: the items
do not move)
    void (*onPresentation) (SidePanel &, int presentation); // the presentation changed: lay
the content out again

    // ---- the free content
-------------------------------------------------------------------------------
```

```
    int  addPage (const char *label, int icon, Widget *content);    // an inspector's page ->
its number (2 and more: tabs)
    void setPage (int page);
    int  page ();
    void setContent (Widget *w);            // a navigation panel's content under its items
(a tree, a month)
    void setFooter (Widget *w, int h);      // under the rest: h px (the chosen item's
controls, a button)
    // Over the rest: h px at the panel's top (whose library this is, a period's chooser) --
shown with the panel's box
    // (whole, a drawer, a column, a rail expanded), hidden in a rail of icons. (uikit
1.950.)
    void setHeader (Widget *w, int h);

    // ---- the look, the geometry, the state
-------------------------------------------------------------------
    void setIconFn (SpIconFn fn);
    void setFaces (TextFace *item, TextFace *heading);  // (0: the installed face; the
headings bold)
    void setColors (unsigned bg, unsigned edge);        // UK_AUTO: the sidebar's (the
window's face towards the fields')
    // The panel's rectangle in its parent as the app lays it out (its resize code): what the
presentation shows of it
    // follows (a rail narrows it, a closed drawer is a tab at its edge). Use it rather than
left / top / resizeTo,
    // which are taken as what the parent's anchors did to the panel shown.
    void place (int l, int t, int w, int h);
    void setWidths (int minW, int prefW, int maxW);     // the desktop: a splitter's range;
prefW the panel's width
    // false: never a rail -- in pocket's landscape a navigation panel whose labels matter (a
settings list) stays whole
    void setRail (bool allowed);
    int  presentation ();               // UK_SP_* now (the desktop: UK_SP_FULL)
    int  reservedWidth ();              // what the app leaves for it at its side now (a
rail: its width; 0: overlaid)
    void open (bool on);                // a drawer, a slide-over, a sheet opened / closed
(the rail: expanded)
    bool isOpen ();
    // A button for the app's own bar that opens and closes it (portrait's "menu" of a
navigation drawer, an
    // inspector's): made once, the app places it (hidden on the desktop and whenever the
panel is shown whole);
    // asked, the panel draws no tab of its own at its edge.
    Widget *toggleButton ();

    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
    void layout () override;
    void resizeTo (int w, int h) override;      // (the app's size kept: the presentation
decides the panel's)
    unsigned bgColor () override;

    unsigned long sp_reserved_[4] = { 0, 0, 0, 0 }; // (uikit/abi.h rule 2: room for later;
the state is behind ext)
    virtual void sp_reserved0 () {}         // (rule 3: room for later virtuals)
    virtual void sp_reserved1 () {}
private:
    int m_side, m_role;
};
```

uikit/skin.h

uikit/skin.h -- 9-slice bitmap skin (port of uikit's Skin / the kernel CSkin) plus user-side window decoration (drawn by code: uikit/paint.h). A skin BMP holds `count` states stacked vertically (button.bmp: normal/hover/pressed); margins mark the fixed corners/edges, the middle tiles. Magenta (UK_TRANSPARENT_KEY) is the transparency key. Skins draw into RAW 0x00RRGGBB buffers -- a Canvas's `px`, or a window-chrome buffer from uk_win_chrome.

Multiply a 0x00RRGGBB pixel by a 0x00RRGGBB tint (per channel /255). 0xFFFFFF = no-op.

```
unsigned uk_tint (unsigned c, unsigned t);
```

```
class Skin
{
public:
    unsigned *pix; int imgW, imgH, count, sw, sh, ml, mr, mt, mb;
    Skin ();
    ~Skin ();
    bool valid () const { return pix != 0 && sh > 0; }
    bool load (const char *path, int cnt, int l, int r, int t, int b);
    // Blit a magenta-keyed sub-rect of the skin into a raw target (fb, W x H).
    void blit (unsigned *fb, int W, int H, int sx, int sy, int bw, int bh,
           int dx, int dy, unsigned tint = 0xFFFFFF);
    // 9-slice draw of `state` into the (x,y,w,h) box: fixed corners, tiled edges/centre.
    void drawOn (unsigned *fb, int W, int H, int state, int x, int y, int w, int h,
             unsigned tint = 0xFFFFFF);
};
```

Draw the window's frame (the modernised CDE: kapi v64 -- a gradient from the theme's frame colour, rounded corners, the theme's outline, the title buttons: the window menu, minimise, maximise, close; the title in bold) into both chrome copies of this window. No-op for a borderless window / no window. Drawn once per size, title, theme and state (guarded); Root calls it after creating its window; call it again after uk_win_resize (the frame then follows the new size).

```
void uk_decorate_window ();
```

The frame's state, drawn by uk_decorate_window (Root keeps it): the window can be maximised (its maximise button active), it is maximised (the button shows "restore"), the app answers the window menu (GUI_EVENT_WINCTL, as a Root does: else its button is greyed -- an app drawing its own window without a Root).

```
enum { UK_WIN_RESIZABLE = 1, UK_WIN_MAXIMISED = 2, UK_WIN_MENU = 4, UK_WIN_FIXED = 8 }; //
(FIXED: no buttons)
void uk_window_state (int flags);   // set the frame's state (UK_WIN_* flags) for the next
uk_decorate_window
int  uk_window_flags ();    // the UK_WIN_* flags last set (0 at start)
```

A frame as uk_decorate_window draws it, into any W x H buffer (T: its title bar's height), in the colour `frame` -- a preview (the Theme app). Its corners' outside: see-through (top byte).

```
void uk_draw_frame (unsigned *fb, int W, int H, int T, const char *title, unsigned frame,
bool active);
```

uikit/slider.h

uikit/slider.h -- horizontal value in [vmin,vmax]; drag the thumb.

```
class Slider : public Widget
{
public:
    int value, vmin, vmax; Action cb; unsigned bg;
    Slider (int l, int t, int w, int h, int lo, int hi, int val, Action cb_, unsigned bg_ =
C_BG);
    void setFromX (int px);
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
};
```

uikit/splitter.h

uikit/splitter.h -- a two-pane container with a draggable divider ("grip"). Add the two content panes with setPanes(); the splitter sizes them and paints/handles a GRIP-px divider between, re-laying out automatically when it is resized (so a parent collapse/resize cascades straight through). Dragging the grip moves the split. Two orientations:

```
  HSplitter -- panes side by side  (vertical grip, drag left/right)
  VSplitter -- panes stacked       (horizontal grip, drag up/down)

class SplitGrip;            // internal draggable divider (defined in splitter.cpp)

class Splitter : public Widget
{
public:
    bool     vertical;      // true = stacked (VSplitter); false = side by side (HSplitter)
    int  split;         // size of the FIRST pane along the split axis (px)
    int  grip;          // divider thickness (px)
    int  minA, minB;        // minimum pane sizes along the split axis
    unsigned gripCol, gripHi;   // divider colour (idle / hover)
    unsigned bg;            // backdrop (normally hidden: panes + grip tile us)
    unsigned bgColor () override { return bg; }

    Splitter (int l, int t, int w, int h, bool vertical_, int split_ = -1,
          unsigned bg_ = C_BG);
    void setPanes (Widget *a, Widget *b);   // adopt the two content panes (call once)
    void setSplit (int s);          // move the divider (clamped to mins), relayout
    void layout () override;
    void onDraw () override;

private:
    Widget    *paneA, *paneB;
    SplitGrip *gripW;
};

class HSplitter : public Splitter
{ public: HSplitter (int l, int t, int w, int h, int split = -1, unsigned bg = C_BG)
    : Splitter (l, t, w, h, false, split, bg) {} };

class VSplitter : public Splitter
{ public: VSplitter (int l, int t, int w, int h, int split = -1, unsigned bg = C_BG)
    : Splitter (l, t, w, h, true, split, bg) {} };
```

uikit/sysclip.h

sysclip.h -- UIKit's own use of the system clipboard (its text fields' copy and paste): SystemKit, opened when a field first copies or pastes. (A program calls SystemKit's clip_* itself: systemkit/clipboard.h.)

```
bool uk_clip_ready ();          // SystemKit is there (false: no clipboard -- the field does
nothing)
}
#endif
```

uikit/tabhost.h

uikit/tabhost.h -- a section that hosts several "tasks" (apps) and shows ONE at a time, chosen from a popup menu in its header (the activity-shell tab strip, popup variant). addTab() adopts a content widget; the header Dropdown lists the tab titles; selecting one shows that content (the others are hidden, not destroyed). The content fills the area below the header and is resized with the host, so the hosted app stays passive about geometry.

```
class TabHost : public Panel
{
public:
    static const int MAXTABS = 8;
    int headerH;                // height of the header strip (holds the popup)

    TabHost (int l, int t, int w, int h, int headerH_ = 26, unsigned bg = C_BG);
    int  addTab (const char *title, Widget *content);   // -> tab index, or -1 if full
    void select (int i);            // show tab i (hide the previous)
    int  count   () const { return ntabs; }
    int  current () const { return active; }
    void layout () override;
    void onDraw () override;

private:
    Dropdown   *picker;         // the task popup menu
    Widget     *content[MAXTABS];
    char        titles[MAXTABS][32];
    const char *titlePtr[MAXTABS];      // stable pointers into titles[] for the Dropdown
    int     ntabs, active;
    static void onPick (Widget &w);     // Dropdown cb -> select the picked tab
};
```

uikit/tabstrip.h

uikit/tabstrip.h -- TabStrip: a row of tabs over a view (a terminal's shells, a reader's documents): each a title, a close cross, a mark (a dot: something runs, something new), and a "+" after them. A click picks a tab; the wheel, or selectNext (Ctrl+Tab, Ctrl+PgUp / PgDn: the app's keys), steps through them. The cross or a middle click ASKS for a tab's close: onClose fires with `closing` set, and the app decides (a question first, its own state freed) and calls remove (). The strip only shows the tabs: the app shows the chosen one's content. Each tab carries a pointer for the app (data ()), moved with it when a tab before it goes. The titles are copied; a long one is cut with an ellipsis.

```
  TabStrip *ts = new TabStrip (0, 0, w, 30, onTab);
  ts->onClose = onTabClose; ts->onNew = onNewTab;
  int i = ts->add ("SD:/", myTab); ts->select (i);
```

MIT licence (Onyx).

(P6) The adaptive tabs (docs/POCKETUI-TECH-STUDY.md section 6.10): the edge the strip stands on, its style, and how it is shown now -- the desktop: as always (a strip, the bottom edge mirrored); pocket landscape: a strip that scrolls, a "..." list when the tabs do not fit; portrait: the current tab's title and a list (or a segmented control for 2 or 3 short fixed tabs -- no "+", no close); console: a header row (the current tab big, its neighbours dim; L1 / R1 switch).

```
enum { UK_TAB_TOP = 0, UK_TAB_BOTTOM = 1 };          // setEdge
enum { UK_TAB_AUTO = 0, UK_TAB_STRIP = 1, UK_TAB_SEGMENTED = 2 };   // setStyle
enum { UK_TABP_STRIP = 0, UK_TABP_SCROLL, UK_TABP_MENU, UK_TABP_SEGMENTED, UK_TABP_HEADER };
// presentation ()

class TabStrip : public Widget
{
public:
    static const int MAXTABS = 32;
    int  selected;          // the chosen tab (-1: none)
    int  closing;           // the tab whose close was asked (onClose's)
    bool     closable;          // a close cross on each tab (true)
    bool     newButton;         // the "+" after the tabs (true)
    unsigned activeFace;            // the chosen tab's face: the content's background below
it,
                        // which it opens onto (0: the window's, C_BG)
    Action   onChange;          // `selected` changed (a click, the wheel, selectNext)
    Action   onClose;           // a close asked: the cross, a middle click (closing = the
tab)
    Action   onNew;             // the "+"

    TabStrip (int l, int t, int w, int h, Action change = 0);
    int  add (const char *title, void *data = 0);   // at the end -> its index (-1: full)
    void remove (int i);            // the tabs after it move down; selected follows its tab
                        // (the removed one's: the tab now there, else the one before)
    int  count () const { return m_n; }
    void setTitle (int i, const char *title);
    const char *title (int i) const { return i >= 0 && i < m_n ? m_title[i] : ""; }
    void *data (int i) const { return i >= 0 && i < m_n ? m_data[i] : 0; }
    void setData (int i, void *p) { if (i >= 0 && i < m_n) m_data[i] = p; }
    void setMark (int i, bool on);      // the dot before the title
    bool marked (int i) const { return i >= 0 && i < m_n && m_mark[i]; }
    void select (int i, bool fire = false); // repainted; onChange if fire and it changed
    void selectNext (int d, bool fire = true);  // d = +1 / -1, round
    int  tabAt (int mx) const;      // the tab under x (-1: none)

    // (P6) The adaptive part (its state behind Widget::ext: the class's fields are frozen).
    void setEdge (int edge);        // UK_TAB_TOP (the default), UK_TAB_BOTTOM (a
spreadsheet's sheets)
    void setStyle (int style);      // UK_TAB_AUTO (the default), _STRIP, _SEGMENTED
(portrait, 3 tabs at most)
    // This strip takes the console's L1 / R1 (the first strip made in a window does without
asking).
    void setNav (bool on);
    int  presentation ();           // UK_TABP_* now (the desktop: UK_TABP_STRIP)
    void showList ();           // the list of the tabs (portrait's title, the "..." button):
pick, close, new

    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
private:
    char     m_title[MAXTABS][48];
    void    *m_data[MAXTABS];
    bool     m_mark[MAXTABS];
    int  m_n, m_hot, m_hotPart;     // the tab under the pointer; 1 its cross, 2 the "+"
    int  m_x[MAXTABS + 1], m_plusX; // the tabs' edges (m_x[i] .. m_x[i + 1] - gap), the
"+"'s
    bool     m_mid;             // the middle button held (one close a press)
    void     place ();
```

```
    bool     inCross (int i, int mx, int my) const;
};
```

uikit/textarea.h

uikit/textarea.h -- multi-line editable text (own '\n'-separated buffer), caret-driven vertical+horizontal scroll, click to position. Clipped to its own canvas. Selection: Shift + arrows / Home / End / Page Up / Down (kapi_get_modifiers), a mouse drag, Shift+click, Ctrl+A. Typing, Enter, Backspace and Delete replace / remove it; Ctrl+C / Ctrl+X / Ctrl+V copy / cut / paste through the system clipboard (unless the app's menu takes those shortcuts first -- then it can call copy () / cut () / paste ()). With a text face installed (uikit/text.h) the text is UTF-8 and the caret, the clicks and the selection follow the glyphs' widths (the horizontal scroll is then leftPx, in pixels).

```
class Textarea : public Widget
{
public:
    char *buf; int cap, len, caret, top, left, rows, cols; bool readonly, barDrag;
    int leftPx;                 // with a text face: the horizontal scroll, px
    int anchor;                 // selection = [anchor, caret) either way; -1 = none
    // Own colours (0x00RRGGBB) instead of the theme's: e.g. QBasic's grey on blue.
    bool ownColors; unsigned colBg, colText, colCaret, colSel;
    void setColors (unsigned bg, unsigned text, unsigned caretC, unsigned sel) { ownColors =
true; colBg = bg; colText = text; colCaret = caretC; colSel = sel; invalidate (true); }
    Textarea (int l, int t, int w, int h, int capacity);
    ~Textarea () override;
    const char *content () const { return buf; }
    void setContent (const char *s);
    void insertText (const char *s);        // insert at the caret (clipboard paste)
    void gotoLine (int line);           // caret to the start of line (0-based), scrolled
into view
    int  caretLine () const;            // 0-based line / column of the caret
    int  caretCol () const { return caret - lineStart (caret); }
    bool hasSelection () const { return anchor >= 0 && anchor != caret; }
    int  selStart () const { return hasSelection () ? (anchor < caret ? anchor : caret) :
caret; }
    int  selEnd () const { return hasSelection () ? (anchor < caret ? caret : anchor) :
caret; }
    int  selectedText (char *out, int cap) const;   // copies the selection; returns its
length
    void deleteSelection ();
    void selectAll ();
    void copy ();                   // selection -> clipboard
    void cut ();
    void paste ();                  // clipboard text -> caret (replaces the selection)
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
private:
    int  lineStart (int i) const { while (i > 0 && buf[i - 1] != '\n') i--; return i; }
    int  lineEnd   (int i) const { while (buf[i] && buf[i] != '\n') i++; return i; }
    void insertAt (int ch);
    void moveCaret (long k);            // one navigation key (no selection logic)
    void deleteAt (int i);
    void ensureVisible (int vr, int vc);
    // With a proportional face installed (uikit/text.h): UTF-8, the caret and the clicks by
measure.
    int  lineW (int ls, int i);         // px from the line's start ls to byte i
    int  placeAt (int ls, int x);           // the byte of line ls nearest x px (text
coordinates)
```

```
    int  placeRow (int row, int mx);        // the byte at mx on the row shown `row`
    void drawFace ();
};
```

uikit/textbox.h

uikit/textbox.h -- single-line editable field; click to position caret, type to edit; Ctrl+V pastes the clipboard at the caret, Ctrl+C / Ctrl+X copy / cut the whole field (not a password). (With a text face installed -- uikit/text.h -- its text is UTF-8 and the caret follows the glyphs' widths.)

```
class Textbox : public Widget
{
public:
    enum { TEXT_CAP = 512 };        // the buffer; how much of it is used: maxLen
    char     text[TEXT_CAP]; int caret; bool password; Action cb;
    int  maxLen;            // the most bytes typed or set (63; up to TEXT_CAP - 1: a chat
line)
    int  padR;              // px kept free at the right (a Combobox's arrow)
    int  vstart;            // the first character shown (set by onDraw)
    Action   changed;           // called after each edit typed or pasted (0: none; cb is
Enter's)
    Textbox (int l, int t, int w, int h, const char *s = "", Action cb_ = 0);
    void setText (const char *s);
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
    bool isField () override { return true; }       // a Tab stop
    void onTabFocus () override;            // Tab: the caret at the end
private:
    bool editKey (long k);
    // With a proportional face installed (uikit/text.h): the text is UTF-8, measured; vstart
is then
    // the byte the field shows from.
    int  shown (char *d) const;     // what is shown (a password's '*'s) -> its length
    int  shownAt (int i) const;     // byte i of the text -> its place in what is shown
    int  textAt (int d) const;      // ... and back
    void drawFace ();
    bool keyFace (long k);
    bool clipKey (long k);          // Ctrl+C / X / V -> true if taken
};
```

uikit/toggle.h

uikit/toggle.h -- ToggleSwitch: an on/off pill switch + label (WPF-style ToggleButton / UWP ToggleSwitch). Click (or Space) flips it; cb fires; read `on`.

```
class ToggleSwitch : public Widget
{
public:
    char text[64]; bool on; Action cb; unsigned bg;
    ToggleSwitch (int l, int t, int w, int h, const char *s, bool on_, Action cb_, unsigned
bg_ = C_BG);
    void setOn (bool v) { if (v != on) { on = v; invalidate (true); } }
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
};
```

uikit/toolbar.h

uikit/toolbar.h -- ToolBar + ToolButton: a strip of small buttons (generalised from Letters'): an icon (one of the WKT_* set below, drawn from its geometry at any size, or the app's own drawer), a text label beside it or alone, a toggle state (lit: the accent's tint, or filled -- a play button), a split part (an arrow opening a palette or a menu), a tooltip; separators and gaps.

```
  #include "uikit/toolbar.h"       (NOT in uikit/uikit.h: Letters, the Spreadsheet and
Cardfile have
                                  their own ToolBar / ToolButton and `using namespace uikit`)
  ToolBar *tb = new ToolBar (0, 0, W, 38);
  tb->add ((new ToolButton (30, 28, "Save (Ctrl+S)", onSave))->setGlyph (WKT_SAVE));
  tb->sep ();
  ToolButton *play = (new ToolButton (34, 28, "Play (Space)", onPlay))->setGlyph (WKT_PLAY)-
>setToggle (true);
  play->filled = true;  tb->add (play);
  tb->add ((new ToolButton (0, 28, "Loop"))->setGlyph (WKT_LOOP)->setText ("Loop")->fitWidth
());
```

onClick gets the button (a toggle's `on` already flipped). A button is flat until pointed (`raised`: always a face, as a transport's); it does not take the keyboard focus.

The toolbar icons, drawn in a size x size box at (x, y) in `ink` (anti-aliased, uikit/vpaint.h).

```
enum { WKT_NONE = -1, WKT_NEW = 0, WKT_OPEN, WKT_SAVE, WKT_UNDO, WKT_REDO, WKT_CUT, WKT_COPY,
WKT_PASTE,
       WKT_PLAY, WKT_PAUSE, WKT_STOP, WKT_RECORD, WKT_TO_START, WKT_TO_END, WKT_REWIND,
WKT_FORWARD,
       WKT_LOOP, WKT_METRONOME, WKT_PLUS, WKT_MINUS, WKT_SEARCH, WKT_MIXER, WKT_SPARK,
WKT_GEAR,
       WKT_TRASH, WKT_PIN,      // (2026-10-06: a waste bin -- delete to the Trash --, a push
pin -- on the desktop)
       WKT_COUNT };
void uk_tool_glyph (Canvas &cv, int kind, int x, int y, int size, unsigned ink);    // draw
the icon `kind` (WKT_*); size: 6 px at least
```

An app's icon: drawn in the size x size box at (x, y), `ink` the text's colour (greyed when off).

```
typedef void (*ToolIconFn) (Canvas &cv, int id, int x, int y, int size, unsigned ink, bool
off);

class ToolButton : public Widget
{
public:
    int    glyph;           // a WKT_* icon (WKT_NONE: none)
    ToolIconFn iconFn; int iconId;      // ... or the app's drawer
    int    iconSize;            // the icon's box, px (18)
    char       text[32];            // a label (right of the icon; alone: a text button)
    bool       toggle, on;          // a toggle: a click flips `on`; on: lit
    bool       filled;          // on: filled with onColor (a play button) rather than tinted
    bool       raised;          // a face even when not pointed (a transport's buttons)
    unsigned   onColor;         // UK_AUTO: the accent
    unsigned   iconColor;           // the icon's own colour (UK_AUTO: the text's): a
record's red
    Action     onClick;
    void       (*arrow) (ToolButton &); // a split button's arrow part (0: none)

    ToolButton (int w, int h, const char *tip = 0, Action cb = 0);
    ToolButton *setGlyph (int kind);
```

```
    ToolButton *setIcon (ToolIconFn fn, int id);
    ToolButton *setText (const char *s);
    ToolButton *setToggle (bool isToggle, bool isOn = false);
    ToolButton *setSplit (void (*arrowCb) (ToolButton &));  // (adds the arrow part's width)
    ToolButton *fitWidth ();        // as wide as its icon and label need
    void setOn (bool v);
    void setDisabled (bool d);

    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    static const int SPLIT_W = 13;
private:
    int m_part, m_down;         // the part under the pointer, the one pressed (-1 none; 1
the arrow)
    unsigned face ();
};
```

(P6) The adaptive toolbar (docs/POCKETUI-TECH-STUDY.md section 6.9): each tool may say how much it matters --

```
  UK_TB_ALWAYS    always shown (the default),
  UK_TB_IF_ROOM   shown when there is room (the lower its rank, the longer it stays),
  UK_TB_OVERFLOW  only in the overflow;
```

on the desktop the bar is as built (every tool, its rows); in pocket and console ONE row of what fits by priority, the rest behind "»": a panel that hosts the tools themselves (a toggle stays a toggle, a drop-down a drop-down), group by group (a separator's run is a group). A second bar folded into the first (foldInto) joins its row when compact. The app lays itself out with rows () (the rows the bar takes now).

```
enum { UK_TB_ALWAYS = 0, UK_TB_IF_ROOM = 1, UK_TB_OVERFLOW = 2 };

class ToolBar : public Widget
{
public:
    unsigned bg;                // its face (UK_AUTO: the window's, C_BG)
    bool     line;          // an etched line along its bottom
    ToolBar (int l, int t, int w, int h = 34);
    void add (Widget *w, int gap = 1);  // at the next place (after a gap), centred
vertically
    void addRight (Widget *w, int gap = 4); // from the right end leftward (they follow a
resize)
    void sep ();                // an etched separator
    void space (int px) { m_x += px; }  // a gap
    int  next () const { return m_x; }  // where the next one goes
    unsigned bgColor () override { return bg == UK_AUTO ? C_BG : bg; }
    void onDraw () override;
    // (P6) The adaptive part (its state behind Widget::ext: the class's fields are frozen).
    void setPriority (Widget *w, int prio, int rank = 0);   // UK_TB_*; rank: IF_ROOM's order
of leaving (0 last)
    void setLabel (Widget *w, const char *label);       // its words (the console's Tools
section; kept, not copied)
    void setGroup (Widget *w, int group);           // its group (default: its separator's
run)
    void setShortcut (Widget *w, int padButton);        // the console's button for it
(gamepad.h's numbers; P9)
    void foldInto (ToolBar *first); // this second row's tools join first's row when compact
(this one then hidden)
    int  rows () const;         // the rows the bar takes now: the desktop 1 + the bars
folded into it; else 1
```

```
                        // (a bar folded into another: 0 when compact)
    void showOverflow ();           // the "»" panel (its button does it)
    void layout () override;        // (the tools placed again for the room: a new override
-- an older program
                        //  keeps the bar as built until it is rebuilt)
private:
    int m_x, m_rx, m_nsep, m_sepX[24];
};
```

uikit/treeview.h

uikit/treeview.h -- TreeView: a hierarchy of labelled nodes with expand / collapse (WPF TreeView). add (parent, label) returns the node id (parent -1 = a root node). Click the [+]/[-] box (or double-click, or Right / Left) to expand / collapse; click selects (onSelect), double-click on a leaf or Enter activates (onActivate); Up / Down move; the wheel and the scrollbar scroll. Read `sel` (node id, -1 = none).

```
class TreeView : public Widget
{
public:
    int sel, top; Action onSelect, onActivate;
    TreeView (int l, int t, int w, int h, Action onSelect_ = 0, Action onActivate_ = 0);
    ~TreeView ();
    int  add (int parent, const char *label);
    void clear ();
    void expand (int id, bool open);
    bool expanded (int id) const { return id >= 0 && id < m_n && m_nodes[id].open; }
    bool hasChildren (int id) const;
    const char *label (int id) const { return (id >= 0 && id < m_n) ? m_nodes[id].label : "";
}
    int  parentOf (int id) const { return (id >= 0 && id < m_n) ? m_nodes[id].parent : -1; }
    int  userData (int id) const { return (id >= 0 && id < m_n) ? m_nodes[id].data : 0; }
    void setUserData (int id, int d) { if (id >= 0 && id < m_n) m_nodes[id].data = d; }
    // (P6) Portrait: one level at a time (docs/POCKETUI-TECH-STUDY.md section 6.12) -- the
children of the level shown,
    // "<" and its parent's name at the top; a node with children opens its level (a click,
Right, Enter), "<" (Left,
    // Backspace) goes back. Elsewhere (the desktop, landscape) the tree as always.
    void setDrillDown (bool on);
    int  drillLevel ();         // the node whose children are shown (-1: the roots), -2: not
drilling now
    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
    bool onKey (long k) override;
private:
    struct Node { char label[48]; int parent, depth, data; bool open; };
    Node *m_nodes; int m_n, m_cap;
    int *m_vis; int m_nvis;         // visible node ids, in display order
    unsigned m_lastClick; int m_lastRow; bool m_thumb;
    void rebuild ();
    void walk (int parent);
    int  rows () const;
    int  rowOf (int id) const;
    void scrollTo (int t);
    void pick (int id, bool fire);
};
```

uikit/vpaint.h

uikit/vpaint.h -- shapes from their geometry, anti-aliased: a toolbar's icons (a page, a folder, a floppy, arrows, scissors...), markers, anything drawn at any size without a bitmap. A VPath gathers outlines --

polygons, rectangles (rounded), discs, strokes (a line, a polyline, an arc: round ends and joins) -- then fill () paints their union in one colour over the canvas (the non-zero rule: the shapes added are all turned the same way, a hole () the other way). Coordinates are in 1/16 px (V (x) = x * 16), integers: the apps build without the FPU.

```
  VPath p;
  p.rrect (V (2), V (1), V (12), V (14), V (2));   p.fill (cv, 0xFFFFFF);
  p.clear (); p.line (V (4), V (5), V (11), V (5), V (1)); p.fill (cv, ink);

int V (int px);
```

sin and cos of an angle in degrees, x 16384.

```
int uk_sin (int deg);
int uk_cos (int deg);

class VPath
{
public:
    VPath ();
    ~VPath ();
    void clear ();
    // Outlines (closed): a polygon of n points (xy: x0, y0, x1, y1...), a box, a rounded
box,
    // a disc, a hole (a disc cut out of what is under it), an ellipse.
    void poly (const int *xy, int n);
    void rect (int x, int y, int w, int h);
    void rrect (int x, int y, int w, int h, int r);
    void circle (int cx, int cy, int r);
    void hole (int cx, int cy, int r);
    void ellipse (int cx, int cy, int rx, int ry);
    // Strokes w wide: a line, a polyline (closed: a loop), an arc from a0 to a1 degrees
    // (counter-clockwise from 3 o'clock, y down: 90 = 12 o'clock... as on paper).
    void line (int x0, int y0, int x1, int y1, int w);
    void polyline (const int *xy, int n, int w, bool closed = false);
    void arc (int cx, int cy, int r, int a0, int a1, int w);
    // An arrow head at (x, y) pointing toward angle deg, `len` long, `half` wide each side.
    void arrowHead (int x, int y, int deg, int len, int half);
    // Paint it: c at opacity alpha, shifted by (dx, dy) px.
    void fill (Canvas &cv, unsigned c, int alpha = 255, int dx = 0, int dy = 0);
private:
    int *m_x, *m_y, m_n, m_cap;     // the points
    int *m_cs, m_nc, m_ccap;        // each outline's first point
    void add (int x, int y);
    void begin ();
    void end (bool asHole = false);     // close the outline (turned the right way)
};
```

uikit/vumeter.h

uikit/vumeter.h -- VuMeter: a level meter (stereo or mono, vertical or horizontal) as a studio's: segments on a dark well, green, then amber, then red toward the top of the scale; a peak held a moment then falling; a clip light (a level over 0 dBFS; a click clears it). Levels are linear (1.0 = 0 dBFS, may go over), mapped to dB inside; the bars fall back at `fallDb` dB a second.

```
  VuMeter *m = new VuMeter (x, y, 14, 120);            (vertical, stereo)
  ... at the UI's rate (Root::onTick):  m->setQ16 (peakL, peakR);   (65536 = 1.0)
  ... or, in an FP-enabled translation unit:  m->set (0.5f, 0.25f);
```

Call it regularly, silence included (set (0, 0)): the falls and the peaks' hold follow the clock (kapi_get_ticks) at each call. Cheap: it repaints only when a lit segment or a peak moves.

A linear level (65536 = 1.0 = 0 dBFS) -> 1/100 dB (0 -> -20000).

```
int uk_q16_to_cdb (unsigned q16);

class VuMeter : public Widget
{
public:
    bool     vertical, stereo;
    int  floorDb, topDb;        // the scale, dB (-48 .. +6)
    int  amberDb, redDb;        // where the segments turn amber, then red (-12, -3)
    int  segPx;             // a segment's length with its 1-px gap (3; 0: a continuous bar)
    int  holdTicks;         // the peak's hold (150 = 1.5 s at 100 Hz)
    int  fallDb, peakFallDb;        // the bar's, the peak's fall after its hold, dB a second
(26, 14)
    bool     showPeak, showClip;
    bool     clip[2];           // a level went over 0 dBFS (a click on the meter clears
them)

    VuMeter (int l, int t, int w, int h, bool vertical = true, bool stereo = true);
    void setQ16 (int l, int r);     // linear levels, 65536 = 0 dBFS (mono: l)
    void setCdb (int l, int r);     // levels in 1/100 dB
    void reset ();              // all down, the peaks and clips cleared
    int  levelCdb (int ch) const { return m_lvl[ch & 1]; }  // shown, 1/100 dB
    int  peakCdb (int ch) const { return m_pk[ch & 1]; }
#if defined (__ARM_FP) || !defined (__aarch64__)    // (an FP-enabled unit: uikit itself is
integer-only)
    void set (float l, float r)
    {
        if (l < 0) l = -l;
        if (r < 0) r = -r;
        setQ16 (l > 16.f ? 1 << 20 : (int) (l * 65536.f), r > 16.f ? 1 << 20 : (int) (r *
65536.f));
    }
#endif

    void onDraw () override;
    bool onMouse (int mx, int my, int bl, int br, int bm, int wheel) override;
private:
    int  m_lvl[2], m_pk[2];     // shown level, peak (1/100 dB)
    unsigned m_pkT[2], m_last;      // when each peak was set; the last call (ticks)
    int  m_drawn[5];            // what the canvas shows (lit lengths, peak places, clips)
    int  len () const;          // the scale's length, px
    int  pos (int cdb) const;       // a level's place along it, px
    unsigned colourAt (int cdb) const;
    void     state (int *s) const;
};
```