

# Onyx — The Kits: a developer's guide

## Onyx · multi-process OS on Raspberry Pi 4

How an Onyx program is built on the system's shared libraries — the **kits** — with a short example for each. Each kit has its reference, with every operation it exposes (documents 10 to 18, linked in the table below). Companion of the [Developer Guide](#) (the build, the application model, the ports) and of [Kernel Internals](#).

### Table of contents

1. One kit per domain
2. Using a kit in a program
3. AppKit — what makes a program run
4. UIKit — the interface
5. SystemKit — talking to the system and the other programs
6. NetKit — the network
7. FileKit — files, folders, archives
8. ImageKit — pictures
9. AudioKit — sound
10. FontKit — fonts and text
11. PrinterKit — printing
12. Adding to a kit, creating a kit
13. Quick reference

## 1. One kit per domain

An Onyx program does not talk to the kernel, and does not carry copies of common code. It is built on **kits**: shared libraries, one per domain, loaded once for the whole system and bound to each program that uses them.

| Kit           | Domain                                                                                                         | On the card                    | Sources                       | Reference                   |
|---------------|----------------------------------------------------------------------------------------------------------------|--------------------------------|-------------------------------|-----------------------------|
| <b>AppKit</b> | What makes a program run: the system's calls, strings, the console, <code>.ini</code> files, starting programs | <code>SD:/lib/appkit.so</code> | <code>user/Kits/appkit</code> | <a href="#">10 — AppKit</a> |
| <b>UIKit</b>  | The interface: windows, widgets,                                                                               | <code>SD:/lib/uikit.so</code>  | <code>user/Kits/uikit</code>  | <a href="#">11 — UIKit</a>  |

| Kit               | Domain                                                                                                                        | On the card                        | Sources                           | Reference                       |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------|------------------------------------|-----------------------------------|---------------------------------|
|                   | dialogs, the theme, icons                                                                                                     |                                    |                                   |                                 |
| <b>SystemKit</b>  | Talking to the system and the other programs: notifications, clipboard, trash, volume, wallpaper, file associations, the dock | <code>SD:/lib/systemkit.so</code>  | <code>user/Kits/systemkit</code>  | <a href="#">12 — SystemKit</a>  |
| <b>NetKit</b>     | The network: HTTP, the FTP volumes                                                                                            | <code>SD:/lib/netkit.so</code>     | <code>user/Kits/netkit</code>     | <a href="#">13 — NetKit</a>     |
| <b>FileKit</b>    | Files and folders, paths, compression, archives                                                                               | <code>SD:/lib/filekit.so</code>    | <code>user/Kits/filekit</code>    | <a href="#">14 — FileKit</a>    |
| <b>ImageKit</b>   | Pictures: reading, writing, resizing, adjusting                                                                               | <code>SD:/lib/imagekit.so</code>   | <code>user/Kits/imagekit</code>   | <a href="#">15 — ImageKit</a>   |
| <b>AudioKit</b>   | Sound: playing files, notes, synthesis, the sound output                                                                      | <code>SD:/lib/audiokit.so</code>   | <code>user/Kits/audiokit</code>   | <a href="#">16 — AudioKit</a>   |
| <b>FontKit</b>    | Fonts: FreeType, the font manager, anti-aliased text                                                                          | <code>SD:/lib/fontkit.so</code>    | <code>user/Kits/fontkit</code>    | <a href="#">17 — FontKit</a>    |
| <b>PrinterKit</b> | Printing: the Print dialog, a job's pages                                                                                     | <code>SD:/lib/printerkit.so</code> | <code>user/Kits/printerkit</code> | <a href="#">18 — PrinterKit</a> |

Three rules follow from this layout, and they hold for every new development:

- **Reusable code goes into the adequate kit** — not into a new shared header, not copied into an application. If no kit fits the domain, a new kit is created (§12).
- **A program draws on the kits as much as it can**, and never reaches the kernel itself. Only AppKit reads the kernel's table; so the kernel can change without any program being rebuilt.
- **What one program alone uses stays beside that program**, in its own folder.

A kit has **one header**, `<kit>/<kit>.h`, which **declares**; the code is in the library. The memory cost of a kit is paid once: its code is shared by every program that uses it.

## 2. Using a kit in a program

### Including

`user/Kits` is on every include path. A source includes a kit's header by the kit's name, whatever its own folder:

```
#include "appkit/appkit.h"      // AppKit
#include "uikit/uikit.h"        // UIKit
#include "systemkit/systemkit.h" // SystemKit
#include "netkit/netkit.h"      // NetKit
#include "filekit/filekit.h"    // FileKit
#include "imagekit/imagekit.h"  // ImageKit
#include "audiokit/audiokit.h"  // AudioKit
#include "fontkit/uikitface.h"  // FontKit
#include "printerkit/printerkit.h" // PrinterKit
```

### Linking

AppKit needs nothing: the kernel loads it and binds it to every program. Every other kit is linked through its **import archive**, a few bytes of stubs and a constructor that opens the library before `main`:

| The program is       | It links                             |
|----------------------|--------------------------------------|
| C++ (an application) | <code>lib/&lt;kit&gt;.imp.a</code>   |
| C (a console tool)   | <code>lib/&lt;kit&gt;.imp_c.a</code> |

An archive only brings what the program calls: listing a kit a program does not use costs nothing, and the library is not opened. The applications' rules in `user/Makefile` already list UIKit, FileKit, SystemKit and NetKit; a console tool names its kits in `user/BinUtils/Makefile`:

```
# a C tool that uses SystemKit
mytool.elf: KITLIBS = ../lib/systemkit.imp_c.a
mytool.elf: ../lib/systemkit.imp_c.a
```

### Versions

A kit's table only grows: a function is never removed nor renamed, so a newer library always runs an older program. A program built against a table that grew needs at least that library: its package says so (`needs = systemkit >= 1.56` in `tools/pkg/packages.ini`), and the package manager installs the library first.

### From BASIC

A BASIC program uses the kits too: `#import filekit`, then `FileKit.copy (a$, b$, 0, 0)` — every function of a kit that takes and returns numbers, strings and pointers, by its name (docs/04 §13, *The system's kits*). BASIC knows a kit by its **description**, `SD:/lib/<kit>.bi`, made from the kit's `.abi` and its headers by `tools/kitbi/kitbi.py` when the kits are built: nothing in BASIC names a kit, so **a new kit is importable as soon as it is built** (docs/03, *BASIC and the kits*). What BASIC cannot call — C++ classes, structures passed by value — is left out of the description: a kit meant for BASIC too exposes plain C functions.

## On a PC

The same sources build on a PC for the tests and the screenshots. There is no shared library there: the kits' headers bring their code inline, and UIKit's sources are compiled with the program. Nothing changes in the program's code.

## 3. AppKit — what makes a program run

`#include "appkit/appkit.h"` — nothing to link.

AppKit is the program's link to the system: files, processes, time, windows, sockets... (the `kapi_*` calls, listed in the Developer Guide), plus the small services every program needs: strings without a C library, the console, a reader of `.ini` files, the starting of other programs.

**A console tool:** read a file, print to the console.

```
#include "appkit/appkit.h"

int main (void)
{
    char buf[256];
    void *f = kapi_open ("SD:/etc/autostart");
    if (f == 0) { ax_putln ("no such file"); return 1; }
    int n = kapi_read (f, buf, sizeof buf - 1);
    kapi_close (f);
    buf[n > 0 ? n : 0] = '\0';

    ax_putln ("SD:/etc/autostart says:");
    ax_putln (buf);
    return 0;
}
```

**Settings from an `.ini` file** in the program's own folder:

```
if (app_ini_load ("config.ini") >= 0)
{
    const char *name = app_ini_get ("window", "title", "Untitled");
    int width = app_ini_get_int ("window", "width", 640);
    for (int i = 0; i < app_ini_count (); i++) // or every entry, in the file's order
        ax_putln (app_ini_key (i));
}
```

**Strings** (no C library needed):

```
char path[96]; int n = 0;
ax_strcat (path, sizeof path, &n, "SD:/docs/"); // never overflows, always terminated
ax_strcat (path, sizeof path, &n, "notes.txt");
char num[12]; ax_itoa (42, num);
if (ax_streq (num, "42")) ax_putln (path);
```

**Starting a program** — an application by its name, or a file by whatever runs it (a `.bas` program by BASIC, a game by its emulator):

```
lx_launch ("tinypad", "SD:/docs/notes.txt"); // an app, with its arguments
lx_open ("SD:/games/tetris.gb", 0); // a file: by its runner
```

## 4. UIKit — the interface

`#include "uikit/uikit.h"` — link `lib/uikit.imp.a` (the applications' rules do).

A window is a `Root`; widgets are added to it; `run ()` is the event loop. Everything is in the namespace `uikit`.

### A window, a label, a button:

```
#include "appkit/appkit.h"
#include "uikit/uikit.h"
using namespace uikit;

static Label *g_label;
static int g_count;

static void onClick (Widget &)
{
    char text[32]; int n = 0;
    ax_strcat (text, sizeof text, &n, "clicked ");
    char num[12]; ax_itoa (++g_count, num);
    ax_strcat (text, sizeof text, &n, num);
    g_label->setText (text); // the widget redraws itself
}

int main (void)
{
    Root root (320, 120, "Hello"); // a decorated window
    g_label = new Label (12, 12, 296, 20, "Press the button");
    root.addChild (g_label);
    root.addChild (new Button (12, 44, 100, 28, "Click me", onClick));
    root.run (); // until the window is closed
    return 0;
}
```

**Dialogs** are modal calls:

```
if (uk_messagebox ("Delete", "Delete this file?", MB_YESNO))
{
    char path[256];
    if (uk_file_open (path, sizeof path, "SD:/docs")) // the file chooser
        g_label->setText (path);
}

unsigned colour = 0x2060C0;
if (uk_color_dialog (&colour, "Pick a colour")) root.setBg (colour);
```

**The theme:** draw with the palette (`C_BG`, `C_TEXT`, `C_ACCENT`, `C_FACE...`), never with fixed colours, so that the program follows the user's theme.

**An icon** — any picture ImageKit reads (BMP today, PNG tomorrow), given as icons are drawn (magenta = see-through):

```
#include "uikit/bmp.h"

int w, h;
unsigned *px = ui::icon_load ("SD:/apps/tinypad.app/icon.bmp", &w, &h);
if (px) { /* draw it ... */ delete [] px; }
```

**A timer or polling:** derive from `Root` and override `onTick ()` (called about 60 times a second).

## 5. SystemKit — talking to the system and the other programs

`#include "systemkit/systemkit.h"` — link `lib/systemkit.imp.a` (C++) or `lib/systemkit.imp_c.a` (C). The one header brings every subject below (a C program gets those written in C: notifications, volume, preload list, the applets' protocol).

**A notification** (a bubble under the menu bar; `notify_action` adds what a click starts):

```
#include "systemkit/systemkit.h"

notify ("Backup", "3 files copied");
notify_action ("Updates", "2 updates available", "control pkgman");
```

**The clipboard**, shared by every application:

```
#include "systemkit/systemkit.h"

clip_set_text ("copied text");

char buf[1024];
if (clip_get_text (buf, sizeof buf)) { /* paste buf */ }

int w, h;
unsigned *px = clip_get_image (&w, &h); // a picture, if one was copied
if (px) { /* ... */ delete [] px; }
```

**The trash** — a file is moved there instead of being deleted:

```
#include "systemkit/systemkit.h"

if (trash_move ("SD:/docs/old.txt")) notify ("Trash", "old.txt moved to the trash");
int n = trash_count (); // what the trash holds
```

**Opening a file with the right application** (the user's file associations):

```
#include "systemkit/systemkit.h"

char app[32];
if (fa_app_for ("SD:/photos/cat.png", app, sizeof app)) { /* "imageview" */ }
fa_open ("SD:/photos/cat.png"); // a folder, an app, a document: opened
```

**The volume, the wallpaper, the dock** — a settings program changes the file and tells the system:

```
#include "systemkit/systemkit.h"

volume_save (7, 0); // 0..10, not muted: kept for the next start

Wallpaper wp;
wp_load (wp); // SD:/etc/wallpaper.ini
/* change wp ... */
wp_save (wp);

dock_reload (); // the dock reads its settings again
```

|                                                                      |                                                      |
|----------------------------------------------------------------------|------------------------------------------------------|
| Its part (a header of its own, beside <code>systemkit.h</code> )     | Subject                                              |
| <code>notify.h</code>                                                | Notifications                                        |
| <code>clipboard.h</code> ( <code>clippproto.h</code> : its protocol) | The clipboard                                        |
| <code>trash.h</code>                                                 | The trash                                            |
| <code>fileassoc.h</code>                                             | Which application opens which file                   |
| <code>volume.h</code>                                                | The master volume, the output, each program's volume |
| <code>wallpaper.h</code>                                             | The wallpaper's settings and its painter             |
| <code>dockconf.h</code>                                              | The dock's settings                                  |
| <code>preloadini.h</code>                                            | The programs loaded ahead at boot                    |
| <code>applet_proto.h</code>                                          | A settings applet shown inside the Control Panel     |

## 6. NetKit — the network

`#include "netkit/netkit.h"` — link `lib/netkit.imp.a` (C++) or `lib/netkit.imp_c.a` (C). The `HttpClient` class is apart: `#include "netkit/http.hpp"`.

**A page fetched** (HTTP/1.0, no allocation: the caller gives the buffer):

```
#include "appkit/appkit.h"
#include "netkit/netkit.h"

static char buf[32 * 1024];

int main (void)
{
    http_response r;
    if (http_get ("http://example.com/", buf, sizeof buf, &r) < 0 || !r.ok)
    {
        ax_putln ("request failed");
        return 1;
    }
    kapi_stdout_write (r.body, (unsigned) r.body_len);
    return 0;
}
```

**A web API** (HTTP/1.1, headers, HTTPS with the TLS transport) — the `HttpClient` class:

```
#include "netkit/http.hpp"

static char buf[64 * 1024];
HttpClient http;
http.user_agent ("MyApp/1.0").accept ("application/json");
HttpResponse r = http.get ("http://api.example.com/status", buf, sizeof buf);
if (!r.is_error ()) { /* r.status, the body in buf */ }
```

**An FTP server as a volume:** once logged in, `FTP:host/dir/file` is a path like any other, for every program.

```
#include "netkit/netkit.h"
```

```
if (ftpfs_login ("ftp.example.com", "me", "secret", 1))    // 1: remembered
{
    void *f = kapi_open ("FTP:ftp.example.com/pub/readme.txt");
    /* kapi_read ... kapi_close */
}
```

The raw sockets (kapi\_tcp\_connect, kapi\_tcp\_send...) are AppKit's; NetKit is where protocols built on them belong.

## 7. FileKit — files, folders, archives

```
#include "filekit/filekit.h" — link lib/filekit.imp.a.
```

### A whole file, read and written:

```
#include "filekit/filekit.h"
```

```
void *data; unsigned n;
if (fk_load ("SD:/docs/notes.txt", &data, &n) == 0)
{
    /* data: n bytes, a 0 after them */
    fk_save ("SD:/docs/notes.bak", data, n);
    fk_free (data);
}
```

### Folders and paths:

```
#include "filekit/filekit.h"
```

```
char path[FS_PATHL];
fs_join (path, sizeof path, "SD:/docs", "report.txt");
if (!fs_exists (path)) { /* ... */ }
```

```
fk_mkdirs ("SD:/backup/2026/docs");           // every folder of the path
fk_copy ("SD:/docs", "SD:/backup/2026/docs", 0, 0); // a file, or a folder and all it holds
fk_remove ("SD:/tmp/work");                   // the same, removed
```

### A ZIP archive, read:

```
char err[80];
fk_zip *z = fk_zip_open ("SD:/downloads/pack.zip", err, sizeof err);
if (z)
{
    struct fk_zip_entry e;
    for (int i = 0; i < fk_zip_count (z); i++)
        if (fk_zip_entry (z, i, &e)) ax_putln (e.name);
    fk_zip_extract_all (z, 0, "SD:/downloads/pack", 0, 0);
    fk_zip_close (z);
}
```

### A ZIP archive, written:

```
fk_zipw *w = fk_zipw_create ("SD:/backup/docs.zip");
fk_zipw_add (w, "SD:/docs", 0);           // the folder and all it holds
fk_zipw_close (w, 0, 0, err, sizeof err);
```

Other archive formats (tar, tar.gz, gzip) are read through the same calls (`fk_arc_*`); a program asks the library which formats it handles (`fk_arc_formats`) instead of keeping its own list.

## 8. ImageKit — pictures

`#include "imagekit/imagekit.h"` — link `lib/imagekit.imp.a`.

ImageKit is the system's one picture codec: BMP, GIF, PNG, JPEG, PCX and WebP read; PNG, JPEG, BMP and GIF written.

**A picture read, turned, saved in another format:**

```
#include "imagekit/imagekit.h"

ik_image *im = ik_load ("SD:/photos/cat.jpg", 0);
if (im)
{
    int w = ik_width (im), h = ik_height (im);
    unsigned *px = ik_pixels (im);           // w * h pixels, 0xAARRGGBB
    ik_rotate (im, 1);                       // a quarter turn clockwise
    ik_save (im, "SD:/photos/cat.png", 90);   // the format: the extension's
    ik_image_free (im);
}
```

**Pixels of the program's own, saved:**

```
ik_image *shot = ik_image_from (pixels, width, height, width);
ik_save (shot, "SD:/screenshots/shot.png", 0);
ik_image_free (shot);
```

**The formats, asked** — a file chooser's filter follows what the library knows:

```
struct ik_format f[16];
int n = ik_formats (f, 16);
```

Resizing (`ik_scale`), flipping (`ik_flip`), the photo adjustments and the EXIF orientation are in the same header.

## 9. AudioKit — sound

`#include "audiokit/audiokit.h"` — link `lib/audiokit.imp.a`.

Several programs play at once: the system mixes them, each with its own volume (Control Panel ► Sound).

**A sound file** (WAV, MP3, OGG, FLAC, MIDI, FM Tracker songs), played in the background:

```
#include "audiokit/audiokit.h"

if (ak_play ("SD:/music/song.mp3", 0) < 0) ax_putln (ak_play_error ());
ak_play_volume (80);                               // 0..100
/* ... the program goes on ... */
ak_play_stop ();
```

**Notes** (the General MIDI instruments, a SoundFont):

```
ak_note_on (0, 60, 100);                           // channel, key (60 = middle C),
velocity
```

```
kapi_msleep (400);
ak_note_off (0, 60);
```

**A sound effect** (the FM synthesizer's voices — what the games use):

```
ak_fm_start (0, 440000, 0, 200);           // voice 0, 440 Hz (in milli-Hz),
volume 0..255
kapi_msleep (120);
ak_fm_stop (0);
```

**The program's own samples** (an emulator, a synthesizer): stereo, 16 bits, 44.1 kHz (AUDIOKIT\_RATE).

```
if (ak_out_open (256, 1024) == 1)
{
    short frames[256 * 2];
    /* fill frames ... */
    ak_out_write (frames, 256);           // waits for room
    ak_out_close ();
}
```

## 10. FontKit — fonts and text

#include "fontkit/uikitface.h" or "fontkit/fonts.h" — link lib/fontkit.imp.a.

FontKit is FreeType for the applications, with the card's fonts (SD:/res/fonts).

**Anti-aliased text in a UIKit application** — one call before the widgets are built:

```
#include "uikit/uikit.h"
#include "fontkit/uikitface.h"
using namespace uikit;

int main (void)
{
    ft_uikit_install ("DejaVu Sans", 13);           // every widget's text from now on
    Root root (400, 200, "Smooth text");
    root.addChild (new Label (12, 12, 376, 24, "FreeType draws this"));
    root.run ();
    return 0;
}
```

**The font manager** — the families installed, a font at a size, text measured (a word processor, a canvas):

```
#include "fontkit/fonts.h"

fnt::init ();
for (int i = 0; i < fnt::count (); i++) ax_putln (fnt::name (i));

int fam = fnt::find ("DejaVu Serif");
fnt::Font *f = fnt::get (fam, 0, 14 * 64);           // style 0 (regular), 14 px in 26.6
int width = fnt::advance (f, 'A');                 // in 26.6 units
```

## 11. PrinterKit — printing

#include "printerkit/printerkit.h" — link lib/printerkit.imp.a.

A program prints in four steps: the Print dialog, a job, its pages, the end. Lengths are points (1/72 inch) from the page's top-left corner; colours are 0xRRGGBB. The pages are recorded: the print service turns them into what the printer takes — or into a PDF file.

```
#include "printerkit/printerkit.h"

PrintSetup s;
print_setup_default (&s);
PrintDialogInfo di = { sizeof di, "My document", 1, 0, 0, 0, 0 };
if (print_dialog (&s, &di)) // the printer, the paper, the pages
{
    PrintJob *j = print_begin (&s, "My document");
    int font = print_font (j, "DejaVu Sans", 0);
    if (print_page (j, 0, 0)) // 0, 0: the paper chosen
    {
        print_text (j, font, 12, 72, 84, "Hello, printer", 0x000000);
        print_line (j, 72, 90, s.paper_w - 72, 90, 0.75f, 0x808080);
    }
    print_end (j); // to the print queue
}
```

Rectangles, paths (lines and curves, filled or stroked) and pictures are drawn the same way (`print_rect`, `print_path_*`, `print_image`).

## 12. Adding to a kit, creating a kit

**Before writing a helper, look for it in the kits.** If two programs could use it, it belongs to a kit.

### Adding a function to a kit

1. **Declare** it in the kit's header, with a comment that says what it does.
2. **Write its code** in the kit's source (for SystemKit, NetKit and `filekit/fsutil.h`: the `.inc` beside the header).
3. **Build**: the kit's table (`<kit>.abi`) gets the new name at its end. Commit the `.abi`. A name is never removed nor renamed: a function that is no longer needed keeps a body.
4. **Raise the package's version** (`tools/pkg/versions.ini`: `1.<the table's size>.0`) and what the applications need (`needs = <kit> >= 1.<size>` in `tools/pkg/packages.ini`).
5. **Document** it: its comment in the header is its documentation — run `python tools/docgen/kitdocs.py` (the kit's reference follows), add an example here if it deserves one, then `python docs/build_docs.py`.

### Creating a kit

When a domain has no kit (SystemKit and NetKit are the models — small, with no dependency):

- a folder `user/Kits/<kit>/`: **one header a program includes**, `<kit>/<kit>.h` — it may bring a header per subject, each declaring its functions (`XK_API int f (...);`) with a `.inc` beside it for the code — and one source `<kit>.cpp` that compiles the code into the library;
- its rules in `user/Makefile` (copy SystemKit's block): the library `lib/<kit>.so`, its import archives `lib/<kit>.imp.a` (C++) and `lib/<kit>.imp_c.a` (C);
- its package in `tools/pkg/packages.ini` (`required = 1`, `files = lib/<kit>.so lib/<kit>.bi` — the `.bi` is what BASIC reads of it, made by the build: *From BASIC* above).

The header of a kit a C program may use is written in C.

### 13. Quick reference

| I want to...                         | Kit        | Call                                             |
|--------------------------------------|------------|--------------------------------------------------|
| read or write a file                 | AppKit     | kapi_open, kapi_read, kapi_save_file             |
| load a whole file in memory          | FileKit    | fk_load, fk_save                                 |
| copy or remove a folder              | FileKit    | fk_copy, fk_remove                               |
| build a path                         | FileKit    | fs_join, fk_path_join                            |
| read or write a ZIP                  | FileKit    | fk_zip_open, fk_zipw_create                      |
| print to the console                 | AppKit     | ax_puts, ax_putln                                |
| read an <code>.ini</code> file       | AppKit     | app_ini_load, app_ini_get                        |
| start another program                | AppKit     | lx_launch, lx_open                               |
| open a window with widgets           | UIKit      | Root, Label, Button...                           |
| ask the user (message, file, colour) | UIKit      | uk_messagebox, uk_file_open, uk_color_dialog     |
| load an icon                         | UIKit      | ui::icon_load                                    |
| show a notification                  | SystemKit  | notify, notify_action                            |
| copy / paste                         | SystemKit  | clip_set_text, clip_get_text                     |
| move a file to the trash             | SystemKit  | trash_move                                       |
| open a file with its application     | SystemKit  | fa_open                                          |
| fetch a web page                     | NetKit     | http_get, HttpClient                             |
| reach an FTP server                  | NetKit     | ftpfs_login, then FTP: paths                     |
| load or save a picture               | ImageKit   | ik_load, ik_save                                 |
| resize or turn a picture             | ImageKit   | ik_scale, ik_rotate                              |
| play a sound file                    | AudioKit   | ak_play                                          |
| play a note or an effect             | AudioKit   | ak_note_on, ak_fm_start                          |
| send samples to the output           | AudioKit   | ak_out_open, ak_out_write                        |
| draw smooth text                     | FontKit    | ft_uikit_install, fnt::get                       |
| print                                | PrinterKit | print_dialog, print_begin, print_page, print_end |