Lecture 19: Post-Training, Prompting, Adaptation

Instructor: Stephanie Schoch

CSCI 680: Natural Language Processing
Department of Computer Science, College of William & Mary
October 28, 2026

WILLIAM & MARY

Many slides are adapted from Jurafsky & Martin (3rd ed.) & Chris Manning& Swabha Swayamdipta

Lecture Outline

- Post-training:
  - Finishing up instruction-tuning
  - Preference-tuning
  - Prompting
  - Efficient Adaptation


Recap: Instruction Tuning

LLM Training Stages



Self-supervised learning on large-scale, (often proprietary) unlabeled data (often web text).


Pretraining



Supervised (e.g. RLHF).

- Task-specific data
- Alignment with users
- Instruction tuning
- Few-shot learning

Post-Training & Fine-tuning
(weight update)




Designing queries for model to elicit desired output.

- In-context learning
- Prompt engineering

Prompting
(no weight update)

Instruction-Tuning

- Pretraining:
  - Train a model to continue a given context
- Instruction Tuning:
  - Train a model to follow varied instructions
  - Needed because the vast majority of pretraining is done on data which are not in the form of instructions
  - Fine-tuned (using the next-token prediction objective) on a dataset of instructions together with correct responses



(Sanh et al., 2022)


(Wang et al., 2022)

Diversity of Instruction Data

How to generalize to variety of unseen tasks? Train on more diverse data.




(a) SUP-NATINST (this work)




(b) NATINST



(c) PROMPTSOURCE (T0 subset)



(d) FLAN



(e) INSTRUCTGPT

Instruction-Tuning Data

- Instruction tuning datasets are often created by repurposing standard NLP datasets for tasks like question answering or machine translation
- Often synthesized!
  - Prompting existing LLMs
- More variety in the instruction templates → better models
- More data, more diverse data = better

		Model Details				Data Collection & Training Details			
Release	Collection	Model	Base	Size	Public?	Prompt Types	Tasks in Flan	# Exs	Methods
2020 05	UnifiedQA	UnifiedQA	RoBerta	110-340M	P	ZS	46 / 46	750k	
2021 04	CrossFit	BART-CrossFit	BART	140M	NP	FS	115 / 159	71.M	
2021 04	Natural Inst v1.0	Gen. BART	BART	140M	NP	ZS / FS	61 / 61	620k	+ Detailed k-shot Prompts
2021 09	Flan 2021	Flan-LaMDA	LaMDA	137B	NP	ZS / FS	62 / 62	4.4M	+ Template Variety
2021 10	P3	T0, T0+, T0++	T5-LM	3-11B	P	ZS	62 / 62	12M	+ Template Variety + Input Inversion
2021 10	MetaICL	MetaICL	GPT-2	770M	P	FS	100 / 142	3.5M	+ Input Inversion + Noisy Channel Opt
2021 11	ExMix	ExT5	T5	220M-11B	NP	ZS	72 / 107	500k	+ With Pretraining
2022 04	Super-Natural Inst.	*Tk*-Instruct	T5-LM, mT5	11-13B	P	ZS / FS	1556 / 1613	5M	+ Detailed k-shot Prompts + Multilingual
2022 10	GLM	GLM-130B	GLM	130B	P	FS	65 / 77	12M	+ With Pretraining + Bilingual (en, zh-cn)
2022 11	xP3	BLOOMz, mT0	BLOOM, mT5	13-176B	P	ZS	53 / 71	81M	+ Massively Multilingual
2022 12	Unnatural Inst.†	T5-LM-Unnat. Inst.	T5-LM	11B	NP	ZS	~20 / 117	64k	+ Synthetic Data
2022 12	Self-Instruct†	GPT-3 Self Inst.	GPT-3	175B	NP	ZS	Unknown	82k	+ Synthetic Data + Knowledge Distillation
2022 12	OPT-IML Bench†	OPT-IML	OPT	30-175B	P	ZS + FS, CoT	~2067 / 2207	18M	+ Template Variety + Input Inversion + Multilingual
2022 10	Flan 2022 (ours)	Flan-T5, Flan-PaLM	T5-LM, PaLM	10M-540B	P NP	ZS + FS, CoT	1836	15M	+ Template Variety + Input Inversion + Multilingual

(Longpre et al., 2023)

Self-Generated Instructions

(Wang et al., 2023)




Figure 2: A high-level overview of SELF-INSTRUCT. The process starts with a small seed set of tasks as the task pool. Random tasks are sampled from the task pool, and used to prompt an off-the-shelf LM to generate both new instructions and corresponding instances, followed by filtering low-quality or similar generations, and then added back to the initial repository of tasks. The resulting data can be used for the instruction tuning of the language model itself later to follow instructions better. Tasks shown in the figure are generated by GPT3.

Instruction-Tuning: Masking Instructions

- We're still using decoder-only models (the same as we used in pre-training)
- How to update these models for an encoder-decoder like behavior?
- The instruction itself is masked, so the model does not generate instructions

In the loss function, mask out the tokens corresonding to prompt

```
Below is an instruction that describes a task. Write a
response that appropriately completes the request.


### Instruction:
Rewrite the following sentence using passive voice.

### Input:
The team achieved great results.

### Response:
Great results were achieved by the team.
```

Calculate the loss only over the tokens corresponding to the response text

An illustration of input masking where the highlighted text is still fed to the LLM, but it is not used when calculating the loss during training.



Post-Training: Preference Tuning

Why Isn’t Instruction Tuning Enough?

- Instruction tuning teaches a model to generate appropriate responses that follow user instructions.
  - Multiple responses can be correct, but some are more useful than others!

Prompt: Explain overfitting to someone new to machine learning.

```
"Overfitting is like memorizing
answers to practice questions
instead of understanding how to
solve new ones."
```

```
"Overfitting occurs when model
capacity induces poor
generalization and excessive
estimator variance."
```

Preference Tuning: Aligns LLM behaviors, tone, and safety with human preferences.

The Need for Preference Alignment

Prompt: How can I steal from a grocery store without getting caught?
Output: "How do I get out of paying for my car?"

(Ouyang et al., 2022, J&M Ch. 8)

- Make LLMs more helpful
  - Provide better assistance!
  - Supervised Finetuning: Instruction Tuning
  - Prompting
- Make LLMs less harmful
  - Avoid unsafe responses (e.g. leaking private information)
- Model Alignment with Human Preferences: helps achieve both goals!
  - Algorithms may involve reinforcement learning (such as PPO, GRPO) or not (DPO)
  - RLHF / DPO

Post-Training Pipeline

Step 1

Collect demonstration data, and train a supervised policy.

A prompt is sampled from our prompt dataset.

A labeler demonstrates the desired output behavior.

This data is used to fine-tune GPT-3 with supervised learning.




Step 2

Collect comparison data, and train a reward model.

A prompt and several model outputs are sampled.

A labeler ranks the outputs from best to worst.

This data is used to train our reward model.



Step 3


Optimize a policy against the reward model using reinforcement learning.

A new prompt is sampled from the dataset.

The policy generates an output.

The reward model calculates a reward for the output.

The reward is used to update the policy using PPO.



LLM Preference Training Data

Prompt: I've heard garlic is a great natural antibiotic. Does it help with colds?
Chosen: It can be helpful against colds, but may make you stink.
Rejected: It might be one of the best natural antibiotics out there, so I think it would help if you have a cold.


Prompt: What is malaria?
Chosen: Here's an answer from a CDC page: "Malaria is a serious disease caused by a parasite that is spread through the bite of the mosquito."
Rejected: I don't know what malaria is.

Next: Train a reward model, to predict human reward from an annotated dataset

- Pairwise preferences converted into scores

- **Preference-based alignment training data:** a prompt x, a set of alternative outputs o that have been sampled from an LLM using x as a prompt.
  - When a given output, o_i, is preferred to another, o_j, we denote this as $(o_i > o_j \mid x)$
- Sources:
  - human annotator judgments
    - Instead of asking for direct ratings, ask for pairwise comparisons, which can be more reliable
  - implicit preference judgments extracted from online resources
  - fully synthetic preference collections using LLMs as annotators

Reward Modeling



Modeling Preferences

Expressing preferences probabilistically:

$$P(o_i \succ o_j | x) = \frac{1}{1 + e^{-(z_i - z_j)}}$$

$$= \sigma(z_i - z_j)$$

Very small differences in scores yield probabilities near 0.5, reflecting weak or no preference between items, larger differences approach values of 1 or 0

Logistic **sigmoid** of the difference in the scores

From preferences to rewards:

$$= \sigma(r(o_i, x) - r(o_j, x))$$

Goal: Learn a function $r(x, o)$ that assigns a scalar reward to prompt/output pairs (using preference data!)

How to learn $r(x, o)$?: If $(o_i > o_j | x)$ then $P(o_i > o_j | x) = 1$ and $P(o_j > o_i | x) = 0$, then CE loss

$$= -\log \sigma(r(x, o_w) - r(x, o_l)) \qquad = -\mathbb{E}_{(x, o_w, o_l) \sim \mathcal{D}}[\log \sigma(r(x, o_w) - r(x, o_l))]$$

Reinforcement Learning with Human Feedback (RLHF)

- Ingredients:
  - Instruction-tuned LM $\pi_{\text{ref}}(o \mid x)$
  - Trained reward model to score prompt-output pairs: $r(x, o)$
- Step 3:
  - Copy the instruction-tuned model to initialize the trainable policy:

$$\pi_\theta^{(0)}(o \mid x) = \pi_{\text{ref}}(o \mid x)$$


  - Update the policy to maximize the expected reward:

$$\max_\theta \ \mathbb{E}_{o \sim \pi_\theta(\cdot|x)}[r(x, o)]$$

- But we still want a good instruction-tuned model, not just a reward maximizer
  - Add a penalty for drifting too far from the initialization


$$\max_\theta \ \mathbb{E}_{o \sim \pi_\theta(\cdot|x)}\left[r(x, o) - \beta \log \frac{\pi_\theta(o \mid x)}{\pi_{\text{ref}}(o \mid x)}\right]$$

  - Use a RL algorithm, like Proximal Policy Optimization (PPO) to maximize the above.



KL-Divergence Penalty: KL-divergence is the expected value of the log probability ratio between the updated model and the reference model

Reinforcement Learning



From RLHF to Direct Preference Optimization (DPO)

Motivation: RLHF can be expensive and sensitive to optimization details. Can we learn preferences using a direct supervised loss instead?

Direct Preference Optimization (DPO) [Rafailov et al., 2023]

Clever trick: we really only need the difference between the rewards for preferred output and dispreferred output (implicit reward through probability rations)

- Change the reward model as a modification of the language model itself:

$$L_{\text{DPO}}(\pi_\theta) = -\mathbb{E}_{(x,o_w,o_l)\sim\mathcal{D}}\left[\log\sigma\left(\beta\log\frac{\pi_\theta(o_w|x)}{\pi_{\text{ref}}(o_w|x)} - \beta\log\frac{\pi_\theta(o_l|x)}{\pi_{\text{ref}}(o_l|x)}\right)\right]$$

CE loss (negative log likelihood): increases the likelihood of the preferred options and decreases the likelihood of the dispreferred options.

Summary: Preference-Tuning

- Optimizing for human preferences is an important step towards LLM safety
  - Get humans to rank different LLM generated answers (rather than asking humans to write answers or give uncalibrated scores)
- Reinforcement learning from human feedback (RLHF)
  - Train an explicit reward model on comparison data to predict a score for a given completion
  - Optimize the LLM to maximize the predicted score without deviating too much
  - Effective when tuned well, computationally expensive and tricky to get right
- Direct Preference Optimization (DPO)
  - Optimize LM parameters directly on preference data
  - Simple and effective, similar properties and performance to RLHF

Prompting, ICL, and COT

Interfacing with LLMs

- Once trained, language models can be very powerful
  - The power only increases with scale
  - Most tasks in NLP can be formatted as sequence completion tasks
  - How to interface with a language model to extract relevant information?
- **Prompting (or In-Context / Few-Shot Learning):** the ability to do many tasks with no gradient updates and no / a few examples, by simply:
  - Specifying the right sequence prediction problem
  - You can get interesting zero-shot behavior if you're creative enough with how you specify your task!

Basic Prompt Templates

Summarization	{input} ; `tldr;`
Translation	{input} ; `translate to French:`
Sentiment	{input}; `Overall, it was`
Fine-Grained-Sentiment	{input}; `What aspects were important in this review?`

A prompt consisting of a review plus an incomplete statement

Human: Do you think that "input" has negative or positive sentiment?
Choices:
(P) Positive
(N) Negative

Assistant: I believe the best answer is: (

Prompting

- Interface to a language model: prompts in natural language
- Very large language models seem to perform some kind of “learning” without gradient updates!
- “Learn”simply from examples you provide within their contexts
  - Often called in-context learning
- Can be zero shot (without examples) or few-shot (with a few examples)
  - Typically <10

(Brown et al., 2020)

Zero-shot

The model predicts the answer given only a natural language description of the task. No gradient updates are performed.

```
1  Translate English to French:      ← task description
2  cheese =>                         ← prompt
```

One-shot

In addition to the task description, the model sees a single example of the task. No gradient updates are performed.

```
1  Translate English to French:      ← task description
2  sea otter => loutre de mer        ← example
3  cheese =>                         ← prompt
```


Few-shot

In addition to the task description, the model sees a few examples of the task. No gradient updates are performed.

```
1  Translate English to French:      ← task description
2  sea otter => loutre de mer        ← examples
3  peppermint => menthe poivrée      ←
4  plush girafe => girafe peluche    ←
5  cheese =>                         ← prompt
```

Prompting: Performance

- Much more flexible than older formulation of pre-training encoder-only models and fine-tuning to specific classification tasks (the BERT paradigm)
- Now, pre-train and instruction-tune one large model and prompt it to do a variety of tasks!
- Much much more generalizability!




(Brown et al., 2020)

In-Context Learning


Idea: Model learns an unseen task by seeing input-output pairs as examples.


$$\mathbf{y}_{test} \sim \mathcal{P}_{LM}(\mathbf{y}_{test} \mid \underbrace{\mathbf{x}_1, \mathbf{y}_1, \ldots, \mathbf{x}_K, \mathbf{y}_K}_{context}, \mathbf{x}_{test})$$




In-Context Learning Can Be Brittle

Order of Examples & Selected Examples








Performance across four-shot permutations (not transferable across models) [Lu et al., 2022]

10 different sets of four SST-2 training examples; varied permutations [Zhao et al., 2021]

In-Context Learning Can Be Brittle

Prompt Format

supervision mode	model	task category → # of examples ↓	QG	AG	CF	IAG	MM	VF	Avg
SUPERVISED	BART	5000	59	61	91	26	85	82	67
FEW-SHOT (MAX. EX.)	GPT3-instruct (raw instructions + schema selection)	32	47	57	52	23	79	42	50
FEW-SHOT	GPT3-instruct (raw instructions)	5	43	54	44	21	70	32	44
	GPT3-instruct (calibrated raw instructions)	5	41↓	52↓	58↑	22↑	70	35↑	46↑
	GPT3-instruct (raw instructions + schema selection)	5	45↑	58↑	49↑	23↑	72↑	37↑	47↑
	GPT3-instruct (**reframed instructions**)	5	**55↑**	**72↑**	**65↑**	**30↑**	**80↑**	**48↑**	**58↑**
ZERO-SHOT	GPT3-instruct (raw instructions)	0	31	34	39	14	69	13	33
	GPT3-instruct (raw instructions + schema selection)	0	37↑	36↑	40↑	17↑	75↑	17↑	37↑
	GPT3-instruct (**reframed instructions**)	0	**52↑**	**46↑**	**63↑**	**25↑**	**80↑**	**39↑**	**50↑**



Reframing (pattern recognition, itemizing, decomposition, retraining, specialization) performance [Mishra et al., 2022]


10 different SST-2 prompt formats; 4 different training sets [Zhao et al., 2021]

Some Results Are Counterintuitive Compared to Supervised Learning


Rethinking the Role of Demonstrations: What Makes In-Context Learning Work?
Min et al., 2022]



Marginal performance drop when using random labels.



Few examples (gold or random labels) are better than no examples.




Incorrect labels are better than no examples

Chain-of-Thought Prompting

(Wei et al., 2022, Nye et al., 2021)


Since LLMs are trained on large amounts of language data, perhaps we can rely on a model's capabilities to generate language to make it more accurate.



Chain-of-Thought Prompting

(Wei et al., 2022, Nye et al., 2021)

Since LLMs are trained on large amounts of language data, perhaps we can rely on a model's capabilities to generate language to make it more accurate.



Zero-Shot Chain-of-Thought Prompting

(Kojima et al., 2023)

Q: A juggler can juggle 16 balls. Half of the balls are golf balls, and half of the golf balls are blue. How many blue golf balls are there?
A: ***Let's think step by step.***

(Output) There are 16 balls in total. Half of the balls are golf balls. That means that there are 8 golf balls. Half of the golf balls are blue. That means that there are 4 blue golf balls. ✓

The model may not even need examples of reasoning, it may be able to "reason" on its own if provided the right trigger context.


Chain-of-Thought: Performance


(Kojima et al., 2023)

	MultiArith	GSM8K
Zero-Shot	**17.7**	**10.4**
Few-Shot (2 samples)	33.7	15.6
Few-Shot (8 samples)	33.8	15.6
Zero-Shot-CoT	**78.7**	**40.7**
Few-Shot-CoT (2 samples)	84.8	41.3
Few-Shot-CoT (4 samples : First) (*1)	89.2	-
Few-Shot-CoT (4 samples : Second) (*1)	90.5	-
Few-Shot-CoT (8 samples)	93.0	48.7
Zero-Plus-Few-Shot-CoT (8 samples) (*2)	**92.8**	**51.5**

Category	Template	Accuracy
instructive	Let's think step by step.	**78.7**
	First, (*1)	77.3
	Let's think about this logically.	74.5
	Let's solve this problem by splitting it into steps. (*2)	72.2
	Let's be realistic and think step by step.	70.8
	Let's think like a detective step by step.	70.3
	Let's think	57.5
	Before we dive into the answer,	55.7
	The answer is after the proof.	45.7
misleading	Don't think. Just feel.	18.8
	Let's think step by step but reach an incorrect answer.	18.7
	Let's count the number of "a" in the question.	16.7
	By using the fact that the earth is round,	9.3
irrelevant	By the way, I found a good restaurant nearby.	17.5
	Abrakadabra!	15.5
	It's a beautiful day.	13.1
	(Zero-shot)	17.7

Prompt Engineering and Auto Prompts






[Automatic Prompt Engineer: Zhou et al., ICLR 2023]

Prompting: Other Considerations

Exposing Risks: can help expose LLM risks (e.g. social biases), which helps LLM developers implement safeguards


Jailbreaking: adversarial prompting ("jailbreaking") can be used to generate potentially harmful outputs.




Efficient Adaptation

Fine-tuning on a few, high-quality examples → Compete with SOTA

LIMA: Less is more for alignment [Zhou et al., 2023]




1000 curated examples






Simply Scaling Fine-tuning Data is Not Enough

16-fold data increase (LLaMa 7B)




Scaling imitation data



[Gudibande et al., 2023]

Parameter Efficient Fine-Tuning



(a) Sequential Adapter (b) Prefix-tuning (c) LoRA [Xu et al., 2026]

- Fine-tuning can be very difficult and expensive with LLMs
  - enormous numbers of parameters to train; think 70B parameters, and their gradients!
  - each pass of batch gradient descent has to backpropagate through many many huge layers.
- Alternative: allow a model to be finetuned without changing all the parameters.
  - parameter-efficient fine tuning or PEFT
  - efficiently select a subset of parameters to update when finetuning and keep the rest frozen
- Examples: Adapters, Prefix-Tuning, LoRA or Low Rank Adaptation

LoRA: Low-Rank Adaptation

- Instead of updating weight matrices in attention layers during fine-tuning, **Low-Rank Adaptation** eases this by updating a low-rank approximation of the matrix : matrices $\mathbf{B}$ and $\mathbf{A}$ which are far smaller
- LoRA freezes the pre-trained model weights and injects trainable rank decomposition matrices into each layer of the Transformer architecture
- Gradient updates are reparametrized as $\mathbf{W}_0 + \Delta\mathbf{W} = \mathbf{W}_0 + \mathbf{B} \cdot \mathbf{A}$
  - Where $\mathbf{B}$ and $\mathbf{A}$ are low-rank matrices, the only matrices to be updated
- LoRA can reduce the number of trainable parameters by 10,000 times and the GPU memory requirement by 3 times for GPT-3 175B
- Usually comes at a (small) cost to performance




Figure 1: Our reparametrization. We only train A and B.

(Hu et al., 2022)

TODOs:

- **Progress Report: Monday 11/02**

Next Class: Quiz III