Lecture 22: Robustness & Fairness

Instructor: Stephanie Schoch

CSCI 680: Natural Language Processing
Department of Computer Science, College of William & Mary
November 11, 2026


WILLIAM & MARY

Lecture Outline

- Watermarking
- Fairness
- Prompt Sensitivity
- Adversarial Robustness

Recap: Generated Text & Watermarking

Watermarking



- **Watermark:** "a hidden pattern in text that is imperceptible to humans, while making the text algorithmically identifiable as synthetic"
- **Goal:** Embed an invisible statistical signature into LLM-generated text to distinguish watermarked outputs from ordinary text.
- **Green tokens:** The model is encouraged to select tokens from a pseudorandomly chosen subset of its vocabulary.

How Watermarking Works

Algorithm 2 Text Generation with Soft Red List

Input: prompt, $s^{(-N_p)} \cdots s^{(-1)}$
green list size, $\gamma \in (0, 1)$
hardness parameter, $\delta > 0$

for $t = 0, 1, \cdots$ **do**

1. Apply the language model to prior tokens $s^{(-N_p)} \cdots s^{(t-1)}$ to get a logit vector $l^{(t)}$ over the vocabulary.
2. Compute a hash of token $s^{(t-1)}$, and use it to seed a random number generator.
3. Using this random number generator, randomly partition the vocabulary into a "green list" G of size $\gamma|V|$, and a "red list" R of size $(1-\gamma)|V|$.
4. Add δ to each green list logit. Apply the softmax operator to these modified logits to get a probability distribution over the vocabulary.

$$\hat{p}_k^{(t)} = \begin{cases} \frac{\exp(l_k^{(t)}+\delta)}{\sum_{i\in R}\exp(l_i^{(t)})+\sum_{i\in G}\exp(l_i^{(t)}+\delta)}, & k \in G \\ \frac{\exp(l_k^{(t)})}{\sum_{i\in R}\exp(l_i^{(t)})+\sum_{i\in G}\exp(l_i^{(t)}+\delta)}, & k \in R. \end{cases}$$

5. Sample the next token, $s^{(t)}$, using the watermarked distribution $\hat{p}^{(t)}$.

end for

Watermarking Using Red & Green Lists


- **Generate logits:** Calculate raw scores for each possible next token.
- **Partition vocabulary:** Hash the previous token to pseudorandomly divide the vocabulary into green and red lists; (γ) = green list proportion
- **Bias green tokens:** Add a positive bias ($\boldsymbol{\delta}$) to green-token logits, increasing their probability of selection.
- **Sample and repeat:** Sample the next token from the modified probability distribution and repeat for each generated token.


Statistical Watermark Detection

$$z = (|s|_G - \gamma T)/\sqrt{T\gamma(1-\gamma)}$$

(how far the observed green-token count deviates from its expected value, in units of standard deviations)

Frontier Models & EU AI Act's Article 50(2)
Code of Practice on Transparency of AI-Generated Content





- EU AI Act requires generative AI providers to make generated text identifiable in a machine-readable way
  - OpenAI and Claude both voluntarily signed commitment
- Shorter text (or more constrained language): harder to detect
  - Mathematics rates lower than psychology: less flexible word choice
- Editing (replacing tokens) weakens detection)

Fairness

Representational Harms & Performance Disparities in LLMs

- A **performance disparity** indicates that the model performs better for some groups and worse for others.
- **Social biases** are systematic associations of some concept (e.g. science) with some groups (e.g. men) over others (e.g. women).
- **Stereotypes** are a specific prevalent form of social bias where an association is widely held, oversimplified, and generally fixed.
- Solutions?
  - Data Quality Filtering
  - Preference Tuning

Implicit Reasoning Biases in Persona-Assigned LLMs [Gupta et al., 2024]




Figure 1: Deep-rooted biases in LLMs. While ChatGPT-3.5[2] argues (when asked directly) that disability has nothing to do with the math reasoning ability (a), it expresses inability to answer math questions citing the disability when asked to adopt the persona of a physically-disabled person (b), resulting in an inferior performance on 24 reasoning tasks (avg. relative drop of 33% (c)). Note that, ChatGPT-3.5 answers this question correctly when asked to adopt an able-bodied person's persona.

Representational Harms & Performance Disparities in LLMs

[Pan et al., 2025]


English Variety	BoolQ Accuracy (%)			Count	SciQ Accuracy (%)			Count	MMLU Accuracy (%)			Count
	Gemma 2B	Mistral 7B	GPT4o-mini		Gemma 2B	Mistral 7B	GPT4o-mini		Gemma 2B	Mistral 7B	GPT4o-mini	
Standard American English	71.3	85.4	87.7	9348	94.3	96.6	97.7	11647	34.1	61.3	71.5	11672
Chicano English	72.0 (+0.7)	84.5 (-0.9)	87.2 (-0.5)	3656	93.8 (-0.5)	96.6 (0.0)	97.6 (-0.1)	4325	32.9 (-1.2)	56.9 (-4.4)	65.4 (-6.1)	6772
Appalachian English	70.9 (-0.4)	83.2 (-2.2)	85.7 (-2.0)	5725	93.4 (-0.9)	96.5 (-0.1)	97.2 (-0.5)	9842	34.9 (+0.8)	59.6 (-1.7)	68.7 (-2.8)	9776
Southern English	69.2 (-2.1)	83.3 (-2.1)	85.8 (-1.9)	8280	93.5 (-0.8)	96.3 (-0.3)	97.2 (-0.5)	11351	34.0 (-0.1)	59.5 (-1.8)	69.8 (-1.7)	11193
African American English	67.7 (-3.6)	82.6 (-2.8)	85.8 (-1.9)	9077	93.3 (-1.0)	96.1 (-0.5)	97.0 (-0.7)	11445	34.2 (+0.1)	59.5 (-1.8)	69.2 (-2.3)	11182
Indian English	68.1 (-3.2)	81.2 (-4.2)	85.4 (-2.3)	9321	92.7 (-1.6)	95.8 (-0.8)	96.5 (-1.2)	11631	34.7 (+0.6)	59.4 (-1.9)	68.8 (-2.7)	11554
Singaporean English	66.5 (-4.8)	79.8 (-5.6)	84.6 (-3.1)	9323	91.7 (-2.6)	94.7 (-1.9)	96.1 (-1.6)	11642	34.1 (0.0)	58.5 (-2.8)	68.7 (-2.8)	11612

Table 1: Performance comparison across English varieties with unperturbed questions excluded. In nearly all cases, performance is worse for non-SAE varieties of English.

English Variety	BoolQ Accuracy (%)			SciQ Accuracy (%)			MMLU Accuracy (%)		
	Gemma 2B	Mistral 7B	GPT4o-mini	Gemma 2B	Mistral 7B	GPT4o-mini	Gemma 2B	Mistral 7B	GPT4o-mini
Standard American English	100	100	100	100	100	100	100	100	100
Chicano English	93.9 (-6.1)	95.6 (-4.4)	96.7 (-3.3)	99.2 (-0.8)	99.6 (-0.4)	99.5 (-0.5)	89.3 (-10.7)	92.9 (-7.1)	95.2 (-4.8)
Appalachian English	92.0 (-8.0)	93.6 (-6.4)	94.8 (-5.2)	98.1 (-1.9)	99.0 (-1.0)	99.2 (-0.8)	86.8 (-13.2)	93.0 (-7.0)	93.8 (-6.2)
Southern English	90.1 (-9.9)	93.1 (-6.9)	94.8 (-5.2)	98.4 (-1.6)	99.1 (-0.9)	98.9 (-1.1)	83.1 (-16.9)	92.6 (-7.4)	92.4 (-7.6)
African American English	85.9 (-14.1)	91.9 (-8.1)	95.0 (-5.0)	98.2 (-1.8)	99.1 (-0.9)	98.8 (-1.2)	84.4 (-15.6)	92.3 (-7.7)	92.3 (-7.7)
Indian English	86.9 (-13.1)	90.2 (-9.8)	93.6 (-6.4)	97.5 (-2.5)	98.4 (-1.6)	98.5 (-1.5)	81.3 (-18.7)	91.2 (-8.8)	90.8 (-9.2)
Singaporean English	83.3 (-16.7)	88.2 (-11.8)	92.3 (-7.7)	96.4 (-3.6)	98.0 (-2.0)	97.4 (-2.6)	78.4 (-21.6)	89.9 (-10.1)	88.8 (-11.2)

Table 2: Performance comparison across English varieties with unperturbed questions excluded, conditioned on correct answers in Standard American English. In all cases, performance is worse for non-SAE varieties of English.

Multilingual Performance Disparities



[Agrawal et al., 2024]

“Needle-in-a-haystack” tasks: retrieving information from one or more target sentences embedded in a long document

Language	ISO 639-3 Code	Resource Level	Language Family	Script
English	eng	Level 5	Indo-European	Latin
Vietnamese	vie	Level 4	Austro-Asiatic	Latin
Indonesian	ind	Level 3	Austronesian	Latin
Swahili	swa	Level 2	Niger-Congo	Latin
Somali	som	Level 1	Afro-Asiatic	Latin

Prompt Sensitivity

Prompt Sensitivity


Prompt sensitivity: when subtle changes to prompts cause divergences in outputs and performance

- ***Sensitivity to superficial formatting:*** LLMs can rely on spurious features such as punctuation, whitespace, and prompt templates rather than purely on semantic meaning
- ***Biases inherited from pretraining:*** LLMs develop preferences for certain output tokens based on their frequency in pretraining data
- ***Sensitivity to in-context example ordering***: LLMs implicitly learn task behavior from demonstrations, but the order of examples can significantly change the inferred behavior.
- ***Position-dependent use of context:*** LLMs do not attend to or effectively use all parts of a long prompt equally (e.g. “lost in the middle”)

Review: In-Context Learning


Idea: Model learns an unseen task by seeing input-output pairs as examples.

$$\mathbf{y}_{test} \sim \mathcal{P}_{LM}(\mathbf{y}_{test} \mid \underbrace{\mathbf{x}_1, \mathbf{y}_1, \ldots, \mathbf{x}_K, \mathbf{y}_K}_{context}, \mathbf{x}_{test})$$




In-Context Learning Can Be Brittle


Order of Examples & Selected Examples & Prompt Format



Performance across four-shot permutations (not transferable across models) [Lu et al., 2022]



10 different sets of four SST-2 training examples; varied permutations [Zhao et al., 2021]




10 different SST-2 prompt formats; 4 different training sets [Zhao et al., 2021]

Some Results Are Counterintuitive Compared to Supervised Learning


Rethinking the Role of Demonstrations: What Makes In-Context Learning Work?
Min et al., 2022]



Marginal performance drop when using random labels.



Few examples (gold or random labels) are better than no examples.




Incorrect labels are better than no examples

Chain-of-Thought Prompting

(Wei et al., 2022, Nye et al., 2021)


Since LLMs are trained on large amounts of language data, perhaps we can rely on a model's capabilities to generate language to make it more accurate.



Chain-of-Thought Prompting

(Wei et al., 2022, Nye et al., 2021)

Since LLMs are trained on large amounts of language data, perhaps we can rely on a model's capabilities to generate language to make it more accurate.



Zero-Shot Chain-of-Thought Prompting

(Kojima et al., 2023)

Q: A juggler can juggle 16 balls. Half of the balls are golf balls, and half of the golf balls are blue. How many blue golf balls are there?
A: ***Let's think step by step.***

(Output) There are 16 balls in total. Half of the balls are golf balls. That means that there are 8 golf balls. Half of the golf balls are blue. That means that there are 4 blue golf balls. ✓

The model may not even need examples of reasoning, it may be able to "reason" on its own if provided the right trigger context.

Chain-of-Thought: Performance

(Kojima et al., 2023)

	MultiArith	GSM8K
Zero-Shot	**17.7**	**10.4**
Few-Shot (2 samples)	33.7	15.6
Few-Shot (8 samples)	33.8	15.6
Zero-Shot-CoT	**78.7**	**40.7**
Few-Shot-CoT (2 samples)	84.8	41.3
Few-Shot-CoT (4 samples : First) (*1)	89.2	-
Few-Shot-CoT (4 samples : Second) (*1)	90.5	-
Few-Shot-CoT (8 samples)	93.0	48.7
Zero-Plus-Few-Shot-CoT (8 samples) (*2)	**92.8**	**51.5**


Category	Template	Accuracy
instructive	Let's think step by step.	**78.7**
	First, (*1)	77.3
	Let's think about this logically.	74.5
	Let's solve this problem by splitting it into steps. (*2)	72.2
	Let's be realistic and think step by step.	70.8
	Let's think like a detective step by step.	70.3
	Let's think	57.5
	Before we dive into the answer,	55.7
	The answer is after the proof.	45.7
misleading	Don't think. Just feel.	18.8
	Let's think step by step but reach an incorrect answer.	18.7
	Let's count the number of "a" in the question.	16.7
	By using the fact that the earth is round,	9.3
irrelevant	By the way, I found a good restaurant nearby.	17.5
	Abrakadabra!	15.5
	It's a beautiful day.	13.1
	(Zero-shot)	17.7

Prompt Sensitivity


(Lu et al., 2024)

Prompt variations:


prompt	text
base_a	I'm glad I saw anybody. {target}
base_b	SENTENCE: I'm glad I saw anybody. **QUESTION: Is this (0) unacceptable, or (1) acceptable?** ANSWER: {target}
zero_a	I'm glad I saw anybody. **The answer is 0.** {target}
zero_b	SENTENCE: I'm glad I saw anybody. **The answer is 0.** ANSWER: {target}
CFP	**Bob said,** "I'm glad I saw anybody." QUESTION: Is this (0) unacceptable, or (1) acceptable **in Bob's opinion**? ANSWER: {target}
CoT	SENTENCE: I'm glad I saw anybody. QUESTION: Is this (0) unacceptable, or (1) acceptable? ANSWER: **Let's think step by step.** This sentence is ungrammatical because "anybody" is used as the object in an affirmative clause. So the answer is {target}
APE	**INSTRUCTION: determine whether each sentence was (1) acceptable or (0) unacceptable based on its structure and grammar.** INPUT: I'm glad I saw anybody. OUTPUT: {target}
GKP	**KNOWLEDGE: Electronic maps are the modern version of paper atlas.** INPUT: Google Maps and other highway and street GPS services have replaced what? OPTIONS: (0) united states, (1) mexico, (2) countryside, (3) atlas, (4) oceans OUTPUT: {target}




Accuracy vs. Sensitivity:



Prompt Engineering and Auto Prompts





[Automatic Prompt Engineer: Zhou et al., ICLR 2023]

Why are LLMs sensitive to prompts?

- Small formatting changes can alter tokenization
  - Changing whitespace, punctuation, or spelling can change the number and identity of input tokens [Wegmann et al., 2025]
- **Induction heads:** a special type of attention head or circuit that learns to recognize token patterns & predict their continuations
  - May be a primary mechanism underlying ICL [Olsson et al., 2022]
  - ICL partly relies on token-pattern matching. Changing surface features can change which patterns are recognized and copied.
    - So surface structure could affect behavior even when semantic content stays constant
- **Position embeddings:** Attention is influenced by position, not just relevance. Learned attention patterns can systematically favor certain positions in the context.
  - So different formatting can shift where information appears and how strongly it is used. [Hsieh et al., 2024]

Adversarial Robustness

Training Data Extraction From Pre-trained Language Models

[Ishihara, 2023]




Figure 2: The procedure of training data extraction attacks and possible defenses.

Training Data: Privacy & Memorization

- LLMs can (inadvertently) leak private data
  - Users find it acceptable to overshare with LLMs
- **Jailbreaking:** prompting a language model to make it reveal unsafe / private information

Privacy Ripple Effects from Adding or Removing Personal Information in Language Model Training [Borkar et al., 2025]





Figure 1: We explore a phenomenon we call *assisted memorization*, where unique PII that appeared earlier in the training at step $i-1$ and was not extracted at that step becomes extractable at a later step i, after fine-tuning on *other* PII.


Prompting & Jailbreaking

Jailbreaking: adversarial prompting ("jailbreaking") can be used to generate potentially harmful outputs.



Aligned LLMs are not Adversarially Aligned

[Zou et al., 2023]



TODOs:

- **Homework 3 Due: 11/20**

Next Class: Paper Discussion II