# Prediction of passenger density in underground Systems

Andreas Jahn Kassel University Wilhelmhöher Allee 73 Kassel, Germany andreas.jahn@unikassel.de Stephan Sigg ?Institute? ?P.O. Box 1212? Göttingen, Germany stephan.sigg@udo.edu Klaus David Kassel University Wilhelmhöher Allee 73 Kassel, Germany david@uni-kassel.de

#### **ABSTRACT**

This paper provides a provides a comparison between several prediction accounts in the area of the underground stations.

## 1. INTRODUCTION

Underground transportation systems are big energy consumers and have significant impacts on energy consumptions at a regional scale [2]. Approximately 30% of the required energy is needed for operating the metro stations and surroundings, such as ventilation, vertical transportation and lighting [1].

To realize energy saving in this area already an intelligent control system for metro stations was developed. The control system is adaptive on the basis of environmental factor forecasts and occupancy flow patterns [3].

Changing the parameter doesn't have an immediate effect. Therefore it would the number of passenger needs to be predicted.

This paper focuses the prediction of number of passenger in the station.

## 1.1 Dataset

Metro Statio Passeig de Gracia (PdG) Line 3.

Data are gathered via CCTV. The images are processed. Out of each image the number of passenger is gathered. In this way a database was filled which contains for each data set the time, location and value.

## 2. STATE OF THE ART

State of the art

## 3. RESULTS

Results

#### 4. CONCLUSION

Conclusion

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

Copyright 20XX ACM X-XXXXX-XX-X/XX/XX ...\$15.00.

#### 5. ACKNOWLEDGEMENTS

This work was partially funded by the EU-FP7 project "Sustainable Energy mAnageMent 4(for) Underground Systems" (SEAM4US, FP7-ICT, EEB-ICT-2011.6.4). The authors would like to acknowledge the contributions of their colleagues.

#### 6. REFERENCES

- [1]
- [2] Richard Anderson, Rory Maxwell, and Nigel G. Harris. Maximizing the potential for metros to reduce energy consumption and deliver low-carbon transportation in cities. *MetroRail Asia*, *Delhi*, pages 1–13, 2009.
- [3] Hongliang Guo and Alfons H. Salden. Intelligent control for sustainable energy management in underground stations. In Jean-Louis Ferrier, Oleg Yu Gusikhin, Kurosh Madani, and Jurek Z. Sasiadek, editors, *ICINCO* 2, pages 566–571. SciTePress, 2013.