

# Mode of transportation and ground property detection using accelerometer and gyroscope data from a Smartphone

Theodor Moeser Sebastian Klamt E-mail: theodor.moeser@stud.uni-goettingen.de,  
sebastian.klamt@stud.uni-goettingen.de

**Abstract**—The abstract goes here.



## 1 PROJECT DESCRIPTION

THE goal of our project is to gather various information from the gait of a person using the accelerometer and gyroscope of a normal Smartphone. Foremost the aim is to identify persons by their gait as well as their way of carrying the phone. The different ways of carrying the phone will be classified by the piece of clothing the phone is stored in like different trousers pockets and jacket pocket as it has been done before in various papers like [7]. Also we want to differentiate the mode of their gait to get information about whether a person is standing still, walking or running, as well as on a flat surface, uphill or downhill. There are papers like [8] already using not only flat surfaces but more interesting and usual settings like ways including stairs and corners in hallways. Therefore a focus of this project will be to gather information about the quality of the underground the person is walking on, deciding if it is hard ground (beton/asphalt) or soft ground (grass/dirt/mulch).

To gather the necessary data we will use an app on a Samsung Galaxy S3 smartphone programmed in Python using the cross-platform python framework Kivy. The rate of measurement is about 40 measurements per Second. The accelerometer used in the Samsung Galaxy S3 is the LSM330DLC. The data will consist of a list of timestamps and the according values for the accelerometer and gyroscope values in three dimensions. Since the smartphone can not provide a realtime environment for measurements the measured values will be slightly irregular.

## ACKNOWLEDGMENTS

The authors would like to thank...

## 2 RELATED WORK

THERE has been a lot of work on human gait recognition. There are two main approaches to identify a person or a persons gender via human gait recognition: First there is the "outer" approach where fixed sensors

(mostly cameras) are used to gather the necessary information to compute the gait and thereby identify a person [video ]. These were called vision-based by Gafurov [gaitauth2 ]. Secondly there is the "inner" approach called sensor-based by Gafurov where sensors (mostly accelerometers and gyroscopes) are carried by the person which is to be identified.

As we plan to identify persons using a smartphone app our approach would be a "sensor-based" gait recognition. There has been done work using more of the typical sensors of a modern day smartphone like GPS to differentiate between different modes of transport like walking or driving with a car [transmode ].

While there seems to be little to no work on groundtype recognition via gait differences there has been studies analysing the impact a backpack weighting 4kg does on the ability of a classifier trained on persons not carrying such [gaitauth ]. That particular paper [gaitauth ] also uses sensors placed in the persons pocket. Another paper by Gafurov [gaitauth2 ] uses accelerometer data to identify a person by their gait but this time via an sensor strapped on the leg near the ankle. The use of a gyroscope is claimed to be first used in [gait ] using a wii-remote controll featuring similiar measurement frequencies of 50Hz like while the other papers had frequencies well over 100Hz. Also [gait ] does generate data not only walking a straight hallway but walking with distorted speed or walking in different directions with stops inbetween, while [gaitauth ][gaitauth2 ] left out data right after the start of a walk defining it as "not characteristic". In paper [unobbiom ] motion sensors are used in combination with voice recognition to authenticate users of smartphones or other mobile devices. The data was collected using 3D accelerometer data with a sensor in a hip pocket, a jacket pocket and a suitcase. The used learning algorithm was to store the training data and calculate a similarity score based on the difference in the forier transformation or the correlation between training and test data. Another approach on gait authentication can be seen in [hidmark ] they rely entirely on acclerometer data collected with a phone in a poach

attached to the side of the hip of the participants. The participants walked on a clearly defined path through a hallway so there was no random influence of the ground properties. The algorithm used for classification was a Hidden Markov Model. Another possible application for gait analysis is the medical evaluation of diseases that lead to a change in gait like a dropped foot [dfoot]. There are also previous works on locating a device worn on the body by accelerometer data [devloc] [devlocw]. But in [devloc] instead of locating the device on a walking subject, the motion during different everyday tasks was used for this purpose.

to generate enough cycles to classify with reasonable precision.

## 4 DATA - DATA AND PLANS FOR FEATURE EXTRACTION

## 3 DATA - GATHERING AND SETUP

TO be able to use machine learning methods one has to gather some amount of data. For that we used a Samsung S3 Smartphone and an application written on it in python via the cross-platform python framework Kivy. The application measures three dimensional gyroscope data as well as three dimensional accelerometer data and adds a timestamp. Our project has different aims of classification which we did not tempt to do all at once.

- We aim to differentiate the type of ground as well as what kind of slope is existent. For that we measured data on natural and asphalt ground with each a downward an upward as well as even ground. For this we have put the Samsung S3 Smartphone into the left trousers pocket with the screen facing the leg and the rest being orientated upside down. The measuring for that took place at a slope in the experimental botanic garden of Gttingen of approximated length of 140 meters and slope of 10%. As the path was asphalted ground we used the natural ground right next to the path to get natural ground slope samples with the same slope. For the even natural ground we walked a line of about 50m in the front yard of the Institute for Computer-Science. For the even asphalted ground we decided to take the left-pocket data of the following classes.  
To gather enough data we walked these a number of times (see section: Data - Data).
- An other aim is to differentiate if the phone is in the left or right trousers pocket or in the left jacket pocket, as well as if the zipper of the jacket is open or not. For this we walked around the central campus of Gttingen resulting in 1.4 kilometer of walk per class on mostly even ground.
- We also aim to differentiate between persons carrying the device for which both authors did all the above exmeriments.

As [gaitauth2] differentiated persons using only three gait-cycles (omitting the first two as they were deemed degenerated due to the high noise factor of starting ones gait) our amount of data should suffice