SAFETY DATA SHEET

SECTION 1 – PRODUCT IDENTIFICATION

TRADE NAME: McCabe Gas Level Indicator Paste

GENERIC NAME: None

CHEMICAL FORMULA

MOLECULAR WEIGHT

Not applicable to mixtures

Not applicable to mixtures

SDS NUMBER: 02 Prepared: September 8, 1998

03 Revised: July 6, 2016

MANUFACTURER'S

NAME:

ADDRESS:

MANUFACTURER'S 771 Clark Road

Danville, VT 05828

McCabe and Sons, Inc.

MANUFACTURER'S

PHONE: (802) 748-6840

EMERGENCY PHONE: (802) 748-6840 MANUFACTURER'S FAX: (802) 748-6841

SECTION 2 – HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

No known OSHA hazards

GHS Classification

Acute Toxicity, Oral (Category 4)
Acute Toxicity, Inhalation (Category 4)
Skin Irritation (Category 3)
Eye Irritation (Category 2B)
Acute aquatic toxicity (Category 1)

GHS Label Elements, including precautionary statements

Pictogram



Signal Word Warning

Hazard Statement(s)

H316 May be harmful if swallowed

H320 Causes eye irritation H400 Very toxic to aquatic life

Precautionary Statement(s)

P273 Avoid release to the environment

P305 + P351 + P338 IF IN EYES: rinse cautiously with water for several minutes. Remove contact

lenses, if present, and easy to do. Continue rinsing.

HMIS (U.S.A.) RATINGS:

Health Hazard: 0 Fire Hazard: 0 Physical Hazards: 1 Personal Protection: E

Potential Health Effects

Inhalation Zinc Oxide may cause irritation to the respiratory tract. Symptoms may include coughing

and shortness of breath. Inhalation of fumes can cause metal fume fever, a flu-like illness lasting 24 to 48 hours with symptoms including chills, fever, muscle ache, dryness of the

throat and headache.

Ingestion Swallowing large amounts of material may cause irritation to the gastrointestinal tract.

Slightly toxic. May cause nausea.

Skin Repeated or prolonged contact with skin may cause dermatitis.

Eyes May be mildly irritating to the eyes.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: None

CAS No.	<u>EINECS</u>	<u>Chemical Name</u>	<u>%</u>	OSHA PEL	Classified Hazardous by OSHA *
1314-13-2	215-222-5	Zinc Oxide	60-70	5 mg/m ³ 8-hr TWA F&R 15 mg/m ³ 8-hr TWA D	Yes
25322-69-4	200-338-0	Polypropylene Glycol (ARCOL PPG-2025)	30-40	N/A	No
		D = Total Dust I	R = Respi	rable $F = Fume$	

^{*} OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SECTION 4 – First Aid Measures

Emergency and First Aid Procedures:

Eyes: Flush with water immediately for 15 minutes and call a physician if irritation persists.

Inhalation: Remove to fresh air. Get medical attention if breathing is difficult.

Ingestion: Call the local poison control center and physician immediately.

Skin: Flush with water immediately for 15 minutes and call a physician if irritation persists.

Hazards Persons with a pre-existing circulatory or respiratory disease may be susceptible to the

(Acute/Chronic): effects of this product.

SECTION 5 – FIREFIGHTING MEASURES

Flash Point (Method Used) 390 – 495°Fahrenheit (COC)

Autoignition Temperature: N/A

LEL Flammable Limits (Components):

UEL

Not Flammable

Zinc Oxide

Conditions of Flammability: Not flammable or combustible

Suitable Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical, or carbon

dioxide.

Special Protective Equipment for

Firefighters:

Wear self-contained breathing apparatus for fire-fighting if

necessary

Hazardous Combustion Products: Hazardous decomposition products formed under fire conditions.

Zinc/zinc oxides.

Polypropylene Glycol

Conditions of Flammability: Not flammable or combustible

Suitable Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical, or carbon

dioxide.

Special Protective Equipment for

Firefighters:

Wear self-contained breathing apparatus for fire-fighting if

necessary

Hazardous Combustion Products: Hazardous decomposition products formed under fire conditions.

Carbon oxides.

NFPA (U.S.A.) RATINGS:

Health: 0 Flammability: 1 Reactivity: 0 Specific Hazard:

SECTION 6 – Accidental Release Measures

Consider use of respirators and personal protective equipment in extreme **Personal precautions:**

cases involving large amounts of the material. Avoid breathing vapors, mist,

or gas. Ventilate area. Evacuate personnel to safe areas.

Environmental precautions Segregate and clean-up to avoid generating dust and vapors. Do not let

product enter drains.

Methods and materials for

containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert

absorbent material and properly dispose.

SECTION 7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes and skin. Keep containers closed and away

from oxidizers. Wash thoroughly after handling.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area.

SECTION 8 – Exposure, Personal Protection

Components with workplace control parameters

Component	CAS NO.	Value	Control Parameters	Basis
Zinc Oxide	xide 1314-13-2 TWA 10 mg/r		$10 \text{ mg/m}^3 \text{ D}$	USA, ACGIH Threshold Limit Value (TLV)
			$2 \text{ mg/m}^3 \text{ F}$	USA, ACGIH Threshold Limit Value (TLV)
Remarks	Metal fume f	fever		
		STEL	10 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
	Metal fume f	fever		
		TWA	5 mg/m3	USA Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	15 mg/m3	USA Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		STEL	10 mg/m ³	USA OSHA – Table Z-1 Limits for Air Contaminants – 1910.1000
		TWA	5 mg/m3	USA NIOSH Recommended Exposure Limit
		ST	10 mg/m^3	USA NIOSH Recommended Exposure Limit
		C	15 mg/m3	USA NIOSH Recommended Exposure Limit
Propylene Glycol	25322-69-4	TWA	10 mg/m ³	USA, Workplace Environmental Exposure Levels (WEEL)

D = Total Dust; F = Fume

Personal Protective Equipment

Respiratory Protection: Consider using a NIOSH-approved respirator when handling large

quantities of this material or if vapors are present above the TLV

Hand Protection: Impervious gloves are usually not required.

Skin Protection: Impervious body coverings are usually not required.

Eye Protection: Safety glasses with side shields, chemical goggles.

Work/Hygienic Practices: Avoid breathing vapor. Wear long-sleeved shirt, trousers and safety shoes.

Appropriate Engineering Controls

Ventilation: Recommended to keep below TLVs

Local Exhaust: Recommended to keep below TLVs

Spec And Other: N/A

SECTION 9 – Physical and Chemical Properties

Appearance and Odor Light purplish blue paste **Specific Gravity:** 1.7

with no odor

Boiling Point: Greater than 450°F **Melting Point:** No information found

Specific Gravity: 2.1 **Vapor Pressure:** Less than 0.01

(mm Hg.)

Solubility in Water: Partial Evaporation Rate: No information found

(Butyl Acetate = 1)

Flash Point (Method 390 – 495 Fahrenheit % Volatiles by Volume No information found

Used): (COC)

Autoignition N/A **Viscosity** Unknown

Temperature:

SECTION 10 – Stability and Reactivity

Chemical Stability: Stable under ordinary conditions of use and storage.

Conditions to Avoid: High temperatures and incompatibles.

Incompatible Materials: Oxidizers. Zinc oxide dust may react violently with aluminum and

magnesium powders and chlorinated rubber on heating.

Hazardous Decomposition Carbon dioxide and carbon monoxide. When heated to very high

Products: temperatures, zinc oxide sublimes to produce zinc oxide fume.

Possibility of Hazardous Reactions: None known to occur.

SECTION 11 – Toxicological Information

This product has not been tested as a whole. Individual components are listed:

Acute Toxicity:

Oral LD50 Zinc Oxide: LD 50 (oral – mouse (mg/kg)) 7,950

LD 50 (oral – rat (ul/kg)) 5,530 LD 50 (oral – rabbit (mg/kg)) 2,200

LD 50 (oral – rabbit (liig/kg)) 2,200 LD 50 (oral – guinea pig (mg/kg)) 2,200

Polypropylene Glycol LD 50 (oral – rat (mg/kg)) 9,760

LD 50 (oral – rat (mg/kg)) 3,750 LD 50 (oral – rat (mg/kg)) >2 gm/kg

LD 50 (oral – rat (mg/kg)) 14,800 LD 50 (oral – rat (mg/kg)) 5,840 LD 50 (oral – rat (mg/kg)) 2,410

LD 50 (oral – rat (mg/kg)) 5,840 LD 50 (oral – rat (mg/kg)) 4,190 LD 50 (oral – rat (mg/kg)) 2,130

LD 50 (oral – rat (mg/kg)) 7,250 LD 50 (oral – rat (mg/kg)) 10,334 LD 50 (oral – rat (mg/kg)) 9,760

LD 50 (oral – rat (ul/kg)) 33,600 LD 50 (oral – rat (gm/kg)) >15

LD 50 (oral – rat (ul/kg)) 56,600

Inhalation LC50 Zinc Oxide LC50 (inhalation – mouse (mg/m3)) 2,000

Dermal LD50	Zinc Oxide	No data available				
	Polypropylene Gl	lycol LC50 (skin – rabbit (ml/kg)) 20 LC50 (skin – rabbit (gm/kg)) 10 LC50 (skin – rabbit (gm/kg)) 30 LC50 (skin – rabbit (ml/kg)) 20 LC50 (skin – rabbit (ml/kg)) 20 LC50 (skin – rabbit (ml/kg)) 20				
Skin corrosion/irritation	Zinc Oxide	Skin – rabbit – Mild skin irritation – 24 h				
Respiratory or skin sensitization	No data available					
Germ cell mutagenicity	Zinc Oxide	Genotoxicity in vitro – Hamster – Embryo Unscheduled DNA synthesis Genotoxicity in vitro – Hamster – Embryo Morphological transformation Genotoxicity in vitro – Hamster – Embryo Sister chromatid exchange Genotoxicity in vitro – guinea pig – inhalation				
Carcinogenicity (whole product)		Unscheduled DNA synthesis				
IARC	_	this product present at levels greater than or equal to 0.1% obable, possible, or confirmed human carcinogen by IARC.				
ACGIH	No component of	this product present at levels greater than or equal to 0.1%				
NTP	No component of	carcinogen or potential carcinogen by ACGIH. This product present at levels greater than or equal to 0.1%				
OSHA	is identified as a known or anticipated carcinogen by NTP No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA					
Reproductive toxicity	(whole product)	No data available				
Teratogenicity	Zinc Oxide	Developmental Toxicity – rat – oral Specific Developmental Abnormalities: Homeostasis Effects on Newborn: Stillbirth. Effects on Newborn: Growth statistics (e.g. Reduced weight gain)				
Specific target organ Toxicity - Single exposure	(whole product)	No data available				
Specific target organ Toxicity - Repeated exposur		No data available				
Aspiration Hazard	(whole product)	No data available				

Signs and Symptoms of Exposure

Zinc oxide dust or fume can irritate the respiratory tract. Prolonged skin contact can produce a severe dermatitis called oxide pox. Exposure to high levels of dust or fume can cause metallic taste, marked thirst, coughing, fatigue, weakness, muscular pain, and nausea followed by fever and chills. Severe overexposure may result in bronchitis or pneumonia with a bluish tint to the skin., prolonged or repeated exposure can cause:, Reversible liver enzyme abnormalities., Diarrhea.

Synergistic effects No data available

Additional Information

RTECS: Zinc Oxide: ZH4810000 Propylene Glycol: TR5250000

SECTION 12 – Ecological Information

Toxicity:

Zinc Oxide

Toxicity to Fish LC50 – Oncorhynchus mykiss (rainbow trout) – 1.1 mg/l – 96 hr

Toxicity to Daphnia and other aquatic invertebrates

EC50 – Daphnia magna (water flea) – 0.098 mg/l – 48 hr

Polypropylene Glycol

Toxicity to Fish LC50 – Oncorhynchus mykiss (rainbow trout) – 10,000 mg/l – 96 hr

Toxicity to Daphnia and other aquatic invertebrates

No data available

Persistence and Degradability No data available

Bioaccumulative potential No data available

Mobility in soil No data available

PBT and vPvB assessment No data available

Other adverse effects No data available

SECTION 13 – Disposal Considerations

Product Offer surplus and non-recyclable solutions to a licensed disposal company

Contaminated packaging Dispose of as unused product in accordance with federal, state and local

requirements. Sanitary landfill, incineration at permitted facility.

EPA Hazardous Waste ID

Number

None

SECTION 14 – Transport Information

DOT (US)

Not regulated. Not dangerous goods.

IMDG

Not dangerous goods.

IATA

Not dangerous goods.

SECTION 15 – Regulatory Information

US Federal Regulations

FDA – Zinc oxide as a nutrient and dietary supplement (food additive) has been determined to be "Generally Recognized as Safe" (GRAS) by the FDA

A: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A) or (40 CFR 302.4). Zinc oxide is subject to reporting levels established by SARA Section 313 (40 CFR 372.65).

Acute Health: Yes Chronic Health: No Fire: No Pressure: No Reactivity: No

State Regulations

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	IL	MA	MN	NJ	PA	RI
Zinc oxide	1314-13-2	Yes						
Polypropylene glycol	25322-69-4	No	No	No	Yes	No	No	No

C: Component Analysis - Inventory

Component	CAS	TSCA 8(b)	TSCA 8(d)	DSL	NDSL	WHMIS	EINECS	RCRA
Zinc oxide	1314-13-2	Yes	No	Yes	Yes	Not Controlled	215-222-5	No
Polypropylene glycol	25322-69-4	Yes	No	Yes	Yes	Not Controlled	500-039-8	No

Chemical Weapons Convention: Yes TSCA 12(b): No CDTA: No

California Prop. 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

WHMIS

This SDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all information required by the CPR.

SECTION 16 – Other Information

Label Hazard Warning:

WARNING! MAY IRRITATE RESPIRATORY TRACT.

Label Precautions:

Avoid breathing dust or vapor. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Label First Aid:

If inhaled, remove to fresh air. Get medical attention for any breathing difficulty.

Product Use:

Used to gauge/measure certain petroleum and chemical products.

Revision Information:

Updated Sections 1, 3, 8, and 16 in accordance with the Globally Harmonized System of Classification and Labeling of Chemicals

Date of Preparation: September 8, 1998 Date of Last Revision: July 6, 2016

Disclaimer

This information is provided in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained individual using this product. Individuals receiving this information must exercise their judgment in determining its appropriate use. McCabe and Sons, Inc. makes no representations or warranties, either express or limited, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly, McCabe and Sons, Inc. will not be responsible for damages resulting from use of or reliance upon this information.