


Chapter 7: Synchronization Examples





Chapter 7: Synchronization Examples

- Explain the bounded-buffer, readers-writers, and dining philosophers synchronization problems.
- Describe the tools used by Linux and Windows to solve synchronization problems.
- Illustrate how POSIX and Java can be used to solve process synchronization problems.





Classical Problems of Synchronization

- Classical problems used to test newly-proposed synchronization schemes
 - Bounded-Buffer Problem
 - Readers and Writers Problem
 - Dining-Philosophers Problem





Bounded-Buffer Problem

- n buffers, each can hold one item
- Semaphore **mutex** initialized to the value 1
- Semaphore **full** initialized to the value 0
- Semaphore **empty** initialized to the value n





Bounded Buffer Problem (Cont.)

- The structure of the producer process

```
while (true) {  
    ...  
    /* produce an item in next_produced */  
    ...  
    wait(empty);  
    wait(mutex);  
    ...  
    /* add next produced to the buffer */  
    ...  
    signal(mutex);  
    signal(full);  
}
```





Bounded Buffer Problem (Cont.)

- The structure of the consumer process

```
while (true) {  
    wait(full);  
    wait(mutex);  
    ...  
    /* remove an item from buffer to next_consumed */  
    ...  
    signal(mutex);  
    signal(empty);  
    ...  
    /* consume the item in next consumed */  
    ...  
}
```





Readers-Writers Problem

- A data set is shared among a number of concurrent processes
 - **Readers** – only read the data set; they do **not** perform any updates
 - **Writers** – can both read and write
- Problem – allow multiple readers to read at the same time
 - Only one single writer can access the shared data at the same time
- Several variations of how readers and writers are considered – all involve some form of priorities
- Shared Data
 - Data set
 - Semaphore **rw_mutex** initialized to 1
 - Semaphore **mutex** initialized to 1
 - Integer **read_count** initialized to 0





Readers-Writers Problem (Cont.)

- The structure of a writer process

```
while (true) {  
    wait(rw_mutex);  
  
    ...  
    /* writing is performed */  
    ...  
    signal(rw_mutex);  
}
```





Readers-Writers Problem (Cont.)

- The structure of a reader process

```
while (true){
    wait(mutex);
    read_count++;
    if (read_count == 1)
        wait(rw_mutex);
    signal(mutex);

    ...
    /* reading is performed */
    ...

    wait(mutex);
    read_count--;
    if (read_count == 0)
        signal(rw_mutex);
    signal(mutex);
}
```






Readers-Writers Problem Variations

- **First** variation – no reader kept waiting unless writer has permission to use shared object
- **Second** variation – once writer is ready, it performs the write ASAP
- Both may have starvation leading to even more variations
- Problem is solved on some systems by kernel providing reader-writer locks





Dining-Philosophers Problem



- Philosophers spend their lives alternating thinking and eating
- Don't interact with their neighbors, occasionally try to pick up 2 chopsticks (one at a time) to eat from bowl
 - Need both to eat, then release both when done
- In the case of 5 philosophers
 - Shared data
 - ▶ Bowl of rice (data set)
 - ▶ Semaphore **chopstick** [5] initialized to 1






Dining-Philosophers Problem Algorithm

- Semaphore Solution
- The structure of Philosopher *i*:

```
while (true){  
    wait (chopstick[i] );  
    wait (chopstick[ (i + 1) % 5] );  
  
    /* eat for awhile */  
  
    signal (chopstick[i] );  
    signal (chopstick[ (i + 1) % 5] );  
  
    /* think for awhile */  
  
}
```

- What is the problem with this algorithm?





Monitor Solution to Dining Philosophers

```
monitor DiningPhilosophers
{
    enum { THINKING; HUNGRY, EATING} state [5] ;
    condition self [5];

    void pickup (int i) {
        state[i] = HUNGRY;
        test(i);
        if (state[i] != EATING) self[i].wait;
    }

    void putdown (int i) {
        state[i] = THINKING;
        // test left and right neighbors
        test((i + 4) % 5);
        test((i + 1) % 5);
    }
}
```






Solution to Dining Philosophers (Cont.)

```
void test (int i) {
    if ((state[(i + 4) % 5] != EATING) &&
        (state[i] == HUNGRY) &&
        (state[(i + 1) % 5] != EATING) ) {
        state[i] = EATING ;
        self[i].signal () ;
    }
}

initialization_code() {
    for (int i = 0; i < 5; i++)
        state[i] = THINKING;
}
}
```





Solution to Dining Philosophers (Cont.)

- Each philosopher i invokes the operations **pickup()** and **putdown()** in the following sequence:

```
DiningPhilosophers.pickup(i);
```

```
/** EAT **/
```

```
DiningPhilosophers.putdown(i);
```

- No deadlock, but starvation is possible





Kernel Synchronization - Windows


- Uses interrupt masks to protect access to global resources on uniprocessor systems
- Uses **spinlocks** on multiprocessor systems
 - Spinlocking-thread will never be preempted
- Also provides **dispatcher objects** user-land which may act mutexes, semaphores, events, and timers
 - **Events**
 - ▶ An event acts much like a condition variable
 - Timers notify one or more thread when time expired
 - Dispatcher objects either **signaled-state** (object available) or **non-signaled state** (thread will block)





Kernel Synchronization - Windows

- Mutex dispatcher object





Linux Synchronization

- ❑ Linux:
 - ❑ Prior to kernel Version 2.6, disables interrupts to implement short critical sections
 - ❑ Version 2.6 and later, fully preemptive
- ❑ Linux provides:
 - ❑ Semaphores
 - ❑ atomic integers
 - ❑ spinlocks
 - ❑ reader-writer versions of both
- ❑ On single-cpu system, spinlocks replaced by enabling and disabling kernel preemption





Linux Synchronization

- Atomic variables

`atomic_t` is the type for atomic integer

- Consider the variables

```
atomic_t counter;  
int value;
```

<i>Atomic Operation</i>	<i>Effect</i>
<code>atomic_set(&counter,5);</code>	<code>counter = 5</code>
<code>atomic_add(10,&counter);</code>	<code>counter = counter + 10</code>
<code>atomic_sub(4,&counter);</code>	<code>counter = counter - 4</code>
<code>atomic_inc(&counter);</code>	<code>counter = counter + 1</code>
<code>value = atomic_read(&counter);</code>	<code>value = 12</code>





POSIX Synchronization

- POSIX API provides
 - mutex locks
 - semaphores
 - condition variable
- Widely used on UNIX, Linux, and macOS





POSIX Mutex Locks

- Creating and initializing the lock

```
#include <pthread.h>

pthread_mutex_t mutex;

/* create and initialize the mutex lock */
pthread_mutex_init(&mutex, NULL);
```

- Acquiring and releasing the lock

```
/* acquire the mutex lock */
pthread_mutex_lock(&mutex);

/* critical section */

/* release the mutex lock */
pthread_mutex_unlock(&mutex);
```





POSIX Semaphores

- ❑ POSIX provides two versions – **named** and **unnamed**.
- ❑ Named semaphores can be used by unrelated processes, unnamed cannot.





POSIX Named Semaphores

- Creating and initializing the semaphore:

```
#include <semaphore.h>
sem_t *sem;

/* Create the semaphore and initialize it to 1 */
sem = sem_open("SEM", O_CREAT, 0666, 1);
```

- Another process can access the semaphore by referring to its name **SEM**.
- Acquiring and releasing the semaphore:

```
/* acquire the semaphore */
sem_wait(sem);

/* critical section */

/* release the semaphore */
sem_post(sem);
```





POSIX Unnamed Semaphores

- Creating and initializing the semaphore:

```
#include <semaphore.h>
sem_t sem;

/* Create the semaphore and initialize it to 1 */
sem_init(&sem, 0, 1);
```

- Acquiring and releasing the semaphore:

```
/* acquire the semaphore */
sem_wait(&sem);

/* critical section */

/* release the semaphore */
sem_post(&sem);
```





POSIX Condition Variables

- Since POSIX is typically used in C/C++ and these languages do not provide a monitor, POSIX condition variables are associated with a POSIX mutex lock to provide mutual exclusion: Creating and initializing the condition variable:

```
pthread_mutex_t mutex;  
pthread_cond_t cond_var;
```

```
pthread_mutex_init(&mutex, NULL);  
pthread_cond_init(&cond_var, NULL);
```





POSIX Condition Variables

- Thread waiting for the condition `a == b` to become true:

```
pthread_mutex_lock(&mutex);  
while (a != b)  
    pthread_cond_wait(&cond_var, &mutex);  
  
pthread_mutex_unlock(&mutex);
```

- Thread signaling another thread waiting on the condition variable:

```
pthread_mutex_lock(&mutex);  
a = b;  
pthread_cond_signal(&cond_var);  
pthread_mutex_unlock(&mutex);
```



End of Chapter 7

