

GTEEx summary statistics database

Gao Wang

Last updated: June 24, 2015

1 Databases

1.1 Multi-tissue summary stats

Summary statistics from the GTEEx v6 analysis are stored in `MatrixEQTLSumStats.h5` (130GB, in HDF5 format). It contains 38,933 genes (less than previous version!); each gene has several summary statistics matrix of dimension $N_{cisSNPs} \times N_{tissues}$. For this release $N_{tissues} = 44$. For `MatrixEQTL` the summary statistics are $\hat{\beta}$, T -stat and P -value.

`MatrixEQTLSumStats.h5`

```
/ENSG000000008735.10 'MatrixEQTL summary statistics of GTEEx Release 2015.04.15'  
/ENSG000000008735.10/beta (5636, 44)  
/ENSG000000008735.10/p-value (5636, 44)  
/ENSG000000008735.10/t-stat (5636, 44)  
/ENSG000000008735.10/rownames (5636,)  
/ENSG000000008735.10/colnames (44,)  
...
```

A special table in `MatrixEQTLSumStats.h5` is called `max`, which is the data for the “best” gene-snp pair identified per gene as the snp pair having maximum $\text{abs}(t\text{-stat})$ across all snps and all tissues and there is no missing data for any tissue. It contains 16,069 gene-snp pairs. For portability the data also is stored separately in `MatrixEQTLSumStats.Max.h5` (15MB, in HDF5 format).

`MatrixEQTLSumStats.Max.h5`

```
/max (Group) 'max'  
/max/beta (16069, 44)  
/max/p-value (16069, 44)  
/max/t-stat (16069, 44)  
/max/rownames (16069,)  
/max/colnames (44,)
```

1.2 Meta-database

Unfortunately GTEEx names *cis*SNP by their genomic coordinate in Human Genome Assembly hg19 (b37), not by rsID. To make it possible to search with rsID I created another database `snp-gene.db` (1.3GB, in SQLite format).

snp-gene.db		
3_52771872_C_T_b37	rs59638016	ENSG00000016864.12,ENSG00000055955.11,ENSG00000055957.6 ...
3_52774530_C_T_b37	rs2159644	ENSG00000016864.12,ENSG00000055955.11,ENSG00000055957.6 ...
3_52774835_AT_A_b37	rs35270761,rs397785457	ENSG00000016864.12,ENSG00000055955.11,ENSG00000055957.6 ...
...		

The 3 columns are

- SNP name in GTEx convention
- rsID
- cis-genes, *i.e.*, genes whose TSS is within 100,000bp up/down-stream of the SNP.

This database will be used prior to searching the summary statistics.



Note

- There may be multiple rsID associated with the same coordinate. Indeed such records exists in dbSNP 144, and eventually these rsIDs should merge into one name (as always have happened in history).
- There are 10,297,646 SNPs in total in this dataset. 9,794,339 of them (95.1%) has rsID in dbSNP 144.

2 Queries

I provide a simple R script SumstatQuery.R to make queries on this dataset. It has:

- A function that lists for given rsID the GTEx SNP ID and all its cis-genes.
- A function that loads sumstats data given gene name and GTEx SNP ID.

To use the script, RSQLite and rhdf5 should be installed, *e.g.*,

R

```
install.packages('RSQLite')
source("http://bioconductor.org/biocLite.R")
biocLite("rhdf5")
```

2.1 Get GTEx SNP ID given rsID

For example to get information for gene ENSG00000171960.6 and SNP rs6600419:

R

```
source('/project/mstephens/gtex/scripts/SumstatQuery.R')
##
# Look up GTEx SNP ID
##
ShowSNP('rs6600419', '/project/mstephens/gtex/analysis/april2015/query/snp-gene.db')
```

```
## GTE SNP ID: 1_43124701_A_G_b37
## cisGenes: ENSG00000065978.13,ENSG00000164007.6,ENSG00000171960.6,ENSG00000200254.1,ENSG00000234917.1,ENSG00000236180.2
##
# Load data for given gene
##
dat <- GetSS('ENSG00000171960.6', '/project/mstephens/gtex/analysis/april2015/query/MatrixEQTLSumStats.h5')
print(names(dat))
## [1] "beta" "p-value" "t-stat" "z-score"
##
# Output information for the SNP of interest
##
print(dat$`p-value`["1_43124701_A_G_b37", ])
##
## Adipose_Subcutaneous Adipose_Visceral_Omentum
## 1.632499e-01 3.462833e-02
## Adrenal_Gland Artery_Aorta
## 8.168959e-01 5.600338e-01
## Artery_Coronary Artery_Tibial
## 7.659426e-01 7.397466e-01
## Brain_Anterior_cingulate_cortex_BA24 Brain_Caudate_basal_ganglia
## ...
print(dat$`z-score`["1_43124701_A_G_b37", ])
##
## Adipose_Subcutaneous Adipose_Visceral_Omentum
## -1.39422418 -2.11267803
## Adrenal_Gland Artery_Aorta
## -0.23153929 0.58279135
## Artery_Coronary Artery_Tibial
## 0.29768626 0.33218889
## Brain_Anterior_cingulate_cortex_BA24 Brain_Caudate_basal_ganglia
## ...
###
# Load the best gene-snp data
###
dat <- GetSS('max', '/project/mstephens/gtex/analysis/april2015/query/MatrixEQTLSumStats.Max.h5')
print(dat$`p-value`[1, ])
print(dat$`z-score`[1, ])
```

For MatrixEQTLSumStats.h5, for given rsID you first search the GTEx SNP ID via ShowSNP, then load the cisGene of interest via GetSS and extract information using the GTEx SNP ID as the row name key.



Note

If R complains the given row name does not exist, try to flip the DNA strand in the GTEx SNP ID and search again. For example, instead of searching for 1_43124701_A_G_b37 you search for 1_43124701_T_C_b37.

The best gene-snp data can be loaded to memory, via GetSS('max', 'MatrixEQTLSumStats.h5'), or the portable version GetSS('max', 'MatrixEQTLSumStats.Max.h5')