



API design

January 2018

Hadley Wickham
[@hadleywickham](#)
Chief Scientist, RStudio



The API defines how you
interact with code



The surface, not
the internals

Case study

What makes base R functions hard to learn?

strsplit(x, split, ...)

grep(pattern, x, value = FALSE, ...)

grepl(pattern, x, ...)

sub(pattern, replacement, x, ...)

gsub(pattern, replacement, x, ...)

regexpr(pattern, text, ...)

gregexpr(pattern, text, ...)

regexec(pattern, text, ...)

subset(x, start, stop)


nchar(x, type, ...)

A few issues

Names: Function names have no common theme, and no common prefix. Names are concise at expense of expressiveness. Sometimes text, sometimes x.

Pipeability: Argument names & order are not consistent, and data isn't the first argument. Can't feed output of `grepexpr()` into `substr()`

Type stability: `grep()` is not type stable: can return string or integer. Can't feed output of `grepexpr()` into `substr()`



Each individual problem is small

“Each [function] is perfect the way
it is ... and it can use a little
improvement.”

—*Shunryu Suzuki*

Carefully
contemplate names

“A rose by any other name
would smell as sweet.”
— *Shakespeare*



“A **function** by any other name
would **not** smell as sweet.”

— *Hadley*



Principle:

Use prefixes to group
related functions together

stringr uses consistent prefixes

`str_split()`

`str_detect()`

`str_locate()`

`str_replace()`

Uses suffixes for variations on a theme

`str_locate_all()`

`str_replace_all()`

Principle:

Whenever you can give something an informative name, you should

stringr uses evocative verbs

`str_split()`

`str_detect()`

`str_locate()`

`str_subset()`

`str_extract()`

`str_replace()`

But good verbs don't always exist

`str_to_lower()`

`str_to_upper()`

General advice

Be consistent!

Function names should be generally be verbs.

Prefer specific to general; concrete to abstract.

Avoid short names; err on the side of expressiveness.

Avoid names that differ in UK/US dialects.

Avoid names used in base R, or by similar packages.

You might get it wrong the first time

Your turn

Brainstorm functions that violate these principles
(particularly within the tidyverse!)

Plan for pipes

Why is the pipe useful?

```
library(dplyr)
by_dest <- group_by(flights, dest)
dest_delay <- summarise(by_dest,
  delay = mean(dep_delay, na.rm = TRUE),
  n = n()
)
big_dest <- filter(dest_delay, n > 100)
arrange(big_dest, desc(delay))
```

But naming is hard work

```
foo <- group_by(flights, dest)
foo <- summarise(foo,
  delay = mean(dep_delay, na.rm = TRUE),
  n = n()
)
foo <- filter(foo, n > 100)
arrange(foo, desc(delay))
```


But naming is hard work

```
foo1 <- group_by(flights, dest)
foo2 <- summarise(foo1,
  delay = mean(dep_delay, na.rm = TRUE),
  n = n()
)
foo3 <- filter(foo2, n > 100)
arrange(foo2, desc(delay))
```

Alternatively, you *could* nest function calls







```
arrange(  
  filter(  
    summarise(  
      group_by(flights, dest),  
      delay = mean(dep_delay, na.rm = TRUE),  
      n = n()  
    ),  
    n > 100  
  ),  
  desc(delay)  
)
```

magrittr provides a third option

0% > 0%

No intermediaries; read from left-to-right

```
flights %>%  
  group_by(dest) %>%  
  summarise(  
    delay = mean(dep_delay, na.rm = TRUE),  
    n = n()  
  ) %>%  
  filter(n > 100) %>%  
  arrange(desc(delay))
```


	Read left-to-right	Can omit intermediate names	Non-linear
$y \leftarrow f(x)$ $g(y)$			
$g(f(x))$			
$x \%>\%$ $f() \%>\%$ $g()$			

Principle:

Data arguments should
come first

Most arguments fall in one of two classes

Data	Details
Required	Optional
Core data	Additional options
Often vectorised	
Often called x or data	

Your turn

Which are the data arguments in `grepl()`?

Which are the details?

Which are the data arguments in `strsplit()`?

Which are the details?

Which are the data arguments in `substr()`?

Which are the details?

And consistent argument order + names

```
str_split(string, pattern)
```

```
str_detect(string, pattern)
```

```
str_locate(string, pattern)
```

```
str_replace(string, pattern, replacement)
```

Principle:

Match outputs and inputs

Your turn

How does `regexpr()` return location of match?

How does `gregexpr()` return location?

How does `substr()` take locations?

What's difference between `substr()` and `substring()`

Output of `regexpr()` not compatible with `substr()`

```
x <- c("bbaab", "bbb", "bbaaba")  
regexpr("a+", x)
```

```
loc <- regexpr("a", x)  
substr(x, loc, loc + attr(loc, "match.length"))
```

```
# And only works because this returns ""  
substr(x, -1, -2)
```

Equivalent stringr code is much simpler

```
library(stringr)
```

```
x <- c("bbaab", "bbb", "bbaaba")
```

```
str_sub(x, str_locate(x, "a+"))
```


This work is licensed under the
Creative Commons Attribution-Noncommercial 3.0
United States License.

To view a copy of this license, visit
<http://creativecommons.org/licenses/by-nc/3.0/us/>