

10.24.0.0/24

Direction	θ	width	breadth
1° 10.24.0.0	10.24.0.1	.67	.63
2° 10.24.0.64	.65	.94	.95
3° 10.24.0.96	.97	.110	.111
4° 10.24.0.112	.113	.126	.127
5° 10.24.0.128	.129	.130	.131
6° 10.24.0.132	.133	.134	.135

```
PC1> ip 10.24.0.2 255.255.255.192 10.24.0.1
Checking for duplicate address...
PC1 : 10.24.0.2 255.255.255.192 gateway 10.24.0.1
```

```
PC1> save
Saving startup configuration to startup.vpc
. done
```

```
PC1> show i
```

```
NAME           : PC1[1]
LINK-LOCAL SCOPE : fe80::250:79ff:fe66:6800/64
GLOBAL SCOPE    :
ROUTER LINK-LAYER :
MAC             : 00:50:79:66:68:00
LPORT           : 10028
RHOST:PORT      : 127.0.0.1:10029
MTU:            : 1500
```

```
PC1> show ip
```

```
NAME           : PC1[1]
IP/MASK         : 10.24.0.2/26
GATEWAY         : 10.24.0.1
DNS             :
MAC             : 00:50:79:66:68:00
LPORT           : 10028
RHOST:PORT      : 127.0.0.1:10029
MTU:            : 1500
```

```
PC1> █
```

```
PC2> ip 10.24.0.66 255.255.255.224 10.24.0.65
Checking for duplicate address...
PC1 : 10.24.0.66 255.255.255.224 gateway 10.24.0.65

PC2> save
Saving startup configuration to startup.vpc
. done

PC2> show ip

NAME       : PC2[1]
IP/MASK     : 10.24.0.66/27
GATEWAY     : 10.24.0.65
DNS         :
MAC         : 00:50:79:66:68:01
LPORT      : 10030
RHOST:PORT  : 127.0.0.1:10031
MTU         : 1500

PC2> █
```

```
PC3> ip 10.24.0.98 255.255.255.240 10.24.0.97
Checking for duplicate address...
PC1 : 10.24.0.98 255.255.255.240 gateway 10.24.0.97
```

```
PC3> save
Saving startup configuration to startup.vpc
. done
```

```
PC3> show i
```

```
NAME           : PC3[1]
LINK-LOCAL SCOPE : fe80::250:79ff:fe66:6802/64
GLOBAL SCOPE    :
ROUTER LINK-LAYER :
MAC            : 00:50:79:66:68:02
LPORT          : 10032
RHOST:PORT      : 127.0.0.1:10033
MTU:            : 1500
```

```
PC3> show ip
```

```
NAME           : PC3[1]
IP/MASK         : 10.24.0.98/28
GATEWAY         : 10.24.0.97
DNS             :
MAC            : 00:50:79:66:68:02
LPORT          : 10032
RHOST:PORT      : 127.0.0.1:10033
MTU:            : 1500
```

```
PC3> █
```

```

PC4> ip 10.24.0.114 255.255.255.240 10.24.0.113
Checking for duplicate address...
PC1 : 10.24.0.114 255.255.255.240 gateway 10.24.0.113

PC4> save
Saving startup configuration to startup.vpc
. done

PC4> show ip

NAME       : PC4[1]
IP/MASK     : 10.24.0.114/28
GATEWAY     : 10.24.0.113
DNS         :
MAC         : 00:50:79:66:68:03
LPORT      : 10034
RHOST:PORT  : 127.0.0.1:10035
MTU         : 1500

PC4>

```

```

R1-00056024#show ip interface brief
Interface      IP-Address      OK? Method Status      Protocol
FastEthernet0/0 10.24.0.1       YES manual up          up
FastEthernet0/1 10.24.0.65      YES manual up          up
FastEthernet1/0 10.24.0.129     YES manual up          up
R1-00056024#

```

```

R2-00056024#show ip interface brief
Interface      IP-Address      OK? Method Status      Protocol
FastEthernet0/0 10.24.0.97      YES manual up          up
FastEthernet0/1 10.24.0.130     YES manual up          up
FastEthernet1/0 10.24.0.133     YES manual up          up
R2-00056024#

```

```

R3-00056024#show ip interface brief
Interface      IP-Address      OK? Method Status      Protocol
FastEthernet0/0 10.24.0.113     YES manual up          up
FastEthernet0/1 10.24.0.134     YES manual up          up
FastEthernet1/0 unassigned      YES manual up          up
R3-00056024#

```

```
R1-00056024#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 6 subnets, 4 masks
C       10.24.0.0/26 is directly connected, FastEthernet0/0
C       10.24.0.64/27 is directly connected, FastEthernet0/1
S       10.24.0.112/28 [1/0] via 10.24.0.130
S       10.24.0.96/28 [1/0] via 10.24.0.130
C       10.24.0.128/30 is directly connected, FastEthernet1/0
S       10.24.0.132/30 [1/0] via 10.24.0.130
R1-00056024#
```

```
R2-00056024#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 6 subnets, 4 masks
S       10.24.0.0/26 [1/0] via 10.24.0.129
S       10.24.0.64/27 [1/0] via 10.24.0.129
S       10.24.0.112/28 [1/0] via 10.24.0.134
C       10.24.0.96/28 is directly connected, FastEthernet0/0
C       10.24.0.128/30 is directly connected, FastEthernet0/1
C       10.24.0.132/30 is directly connected, FastEthernet1/0
R2-00056024#
```

```

[OK]
R3-00056024#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 6 subnets, 4 masks
S       10.24.0.0/26 [1/0] via 10.24.0.133
S       10.24.0.64/27 [1/0] via 10.24.0.133
C       10.24.0.112/28 is directly connected, FastEthernet0/0
S       10.24.0.96/28 [1/0] via 10.24.0.133
S       10.24.0.128/30 [1/0] via 10.24.0.133
C       10.24.0.132/30 is directly connected, FastEthernet0/1
R3-00056024#

```

```

100 PC1> trace 10.24.0.114
trace to 10.24.0.114, 8 hops max, press Ctrl+C to stop
 1  10.24.0.1  16.286 ms  11.415 ms  16.063 ms
 2    *10.24.0.130  46.329 ms  46.850 ms
 3    *10.24.0.134  76.744 ms  75.474 ms
 4    **10.24.0.114  92.523 ms (ICMP type:3, code:3, Destination port unreachable)
PC
PC

```

Ejercicio dinámico

Carnet: 00056024

A: 00

B: 24

192.24.0.0/24

6°-10° 22-23 32-2 = 130 → mm mm mm 1111100
22-23 23 9.8546 252

Dirección	1°	Suma	broadcast
1° 192.24.0.0	192.24.0.1	192.24.0.62	192.24.0.63
2° .64	.65	.94	.95
3° .96	.97	.126	.127
4° .128	.129	.158	.159
5° .160	.161	.190	.191
6° .192	.193	.222	.223
7° .224	.225	.254	.255
8° .256	.257	.286	.287
9° .288	.289	.320	.321
10° .320	.321	.352	.353
	.352		

1° R5 F010 192.24.0.1
PC1 E10 192.24.0.2
2° R2 F010 192.24.0.65
PC2 E10 192.24.0.66
3° R3 F010 192.24.0.97
PC3 E10 192.24.0.98
4° R1 F010 192.24.0.129
PC4 E10 192.24.0.130
5° R4 F010 192.24.0.161
PC5 E10 192.24.0.162
6° R1 F010 192.24.0.193
R2 F010 192.24.0.194
7° R1 E10 192.24.0.157
R3 F010 192.24.0.158
R2 F010 192.24.0.159

```

PC1> ip 192.24.0.2 255.255.255.192 192.24.0.1
Checking for duplicate address...
PC1 : 192.24.0.2 255.255.255.192 gateway 192.24.0.1

PC1> save
Saving startup configuration to startup.vpc
. done

PC1> show ip

NAME          : PC1[1]
IP/MASK       : 192.24.0.2/26
GATEWAY       : 192.24.0.1
DNS           :
MAC           : 00:50:79:66:68:00
LPORT        : 10050
RHOST:PORT    : 127.0.0.1:10051
MTU           : 1500

PC1>

```



```
PC2> ip 192.24.0.66 255.255.255.224 192.24.0.65
Checking for duplicate address...
PC1 : 192.24.0.66 255.255.255.224 gateway 192.24.0.65

PC2> save
Saving startup configuration to startup.vpc
. done

PC2> show ip

NAME          : PC2[1]
IP/MASK        : 192.24.0.66/27
GATEWAY        : 192.24.0.65
DNS            :
MAC            : 00:50:79:66:68:01
LPORT         : 10054
RHOST:PORT     : 127.0.0.1:10055
MTU:           : 1500

PC2> █
```

```
PC3> ip 192.24.0.98 255.255.255.224 192.24.0.97
Checking for duplicate address...
PC1 : 192.24.0.98 255.255.255.224 gateway 192.24.0.97

PC3> save
Saving startup configuration to startup.vpc
. done

PC3> show ip

NAME          : PC3[1]
IP/MASK        : 192.24.0.98/27
GATEWAY        : 192.24.0.97
DNS            :
MAC            : 00:50:79:66:68:02
LPORT         : 10052
RHOST:PORT     : 127.0.0.1:10053
MTU:           : 1500

PC3> █
```

```
PC4> ip 192.24.0.130 255.255.255.240 192.24.0.129
Checking for duplicate address...
PC1 : 192.24.0.130 255.255.255.240 gateway 192.24.0.129

PC4> save
Saving startup configuration to startup.vpc
. done

PC4> show ip

NAME       : PC4[1]
IP/MASK    : 192.24.0.130/28
GATEWAY    : 192.24.0.129
DNS        :
MAC        : 00:50:79:66:68:03
LPORT      : 10056
RHOST:PORT : 127.0.0.1:10057
MTU        : 1500

PC4> █
```

```
PC5> ip 192.24.0.146 255.255.255.248 192.24.0.145
Checking for duplicate address...
PC1 : 192.24.0.146 255.255.255.248 gateway 192.24.0.145

PC5> save
Saving startup configuration to startup.vpc
. done

PC5> show ip

NAME       : PC5[1]
IP/MASK    : 192.24.0.146/29
GATEWAY    : 192.24.0.145
DNS        :
MAC        : 00:50:79:66:68:04
LPORT      : 10058
RHOST:PORT : 127.0.0.1:10059
MTU        : 1500

PC5> █
```

```
R1-00056024#show ip interface brief
Interface                IP-Address      OK? Method Status      Protocol
FastEthernet0/0          192.24.0.129    YES manual up          up
FastEthernet0/1          192.24.0.153    YES manual up          up
FastEthernet1/0          192.24.0.157    YES manual up          up
R1-00056024#
```

```
[OK]
R2-00056024#show ip interface brief
Interface                IP-Address      OK? Method Status      Protocol
FastEthernet0/0          192.24.0.65     YES manual up          up
FastEthernet0/1          192.24.0.154    YES manual up          up
FastEthernet1/0          192.24.0.161    YES manual up          up
R2-00056024#
```

```
[OK]
R3-00056024#show ip interface brief
Interface                IP-Address      OK? Method Status      Protocol
FastEthernet0/0          192.24.0.97     YES manual up          up
FastEthernet0/1          192.24.0.158    YES manual up          up
FastEthernet1/0          192.24.0.165    YES manual up          up
R3-00056024#
```

```
R4-00056024#show ip interface brief
Interface                IP-Address      OK? Method Status      Protocol
FastEthernet0/0          192.24.0.145    YES manual up          up
FastEthernet0/1          192.24.0.166    YES manual up          up
FastEthernet1/0          192.24.0.169    YES manual up          up
R4-00056024#
```

```
[OK]
R5-00056024#show ip interface brief
Interface                IP-Address      OK? Method Status      Protocol
FastEthernet0/0          192.24.0.1      YES manual up          up
FastEthernet0/1          192.24.0.162    YES manual up          up
FastEthernet1/0          192.24.0.170    YES manual up          up
R5-00056024#
```

```
R1-00056024#show ip route
```

```
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
```

```
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
```

```
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
```

```
E1 - OSPF external type 1, E2 - OSPF external type 2
```

```
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
```

```
ia - IS-IS inter area, * - candidate default, U - per-user static route
```

```
o - ODR, P - periodic downloaded static route
```

```
Gateway of last resort is not set
```

```
192.24.0.0/24 is variably subnetted, 10 subnets, 5 masks
```

```
C 192.24.0.152/30 is directly connected, FastEthernet0/1
```

```
C 192.24.0.156/30 is directly connected, FastEthernet1/0
```

```
O 192.24.0.144/29 [110/12] via 192.24.0.158, 00:01:51, FastEthernet1/0
```

```
C 192.24.0.128/28 is directly connected, FastEthernet0/0
```

```
O 192.24.0.168/30 [110/3] via 192.24.0.158, 00:01:29, FastEthernet1/0
```

```
O 192.24.0.160/30 [110/11] via 192.24.0.154, 00:04:53, FastEthernet0/1
```

```
O 192.24.0.164/30 [110/2] via 192.24.0.158, 00:03:29, FastEthernet1/0
```

```
O 192.24.0.64/27 [110/20] via 192.24.0.154, 00:05:05, FastEthernet0/1
```

```
O 192.24.0.96/27 [110/11] via 192.24.0.158, 00:03:39, FastEthernet1/0
```

```
O 192.24.0.0/26 [110/13] via 192.24.0.158, 00:00:06, FastEthernet1/0
```

```
R1-00056024#
```

```
R2-00056024#show ip route
```

```
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
```

```
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
```

```
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
```

```
E1 - OSPF external type 1, E2 - OSPF external type 2
```

```
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
```

```
ia - IS-IS inter area, * - candidate default, U - per-user static route
```

```
o - ODR, P - periodic downloaded static route
```

```
Gateway of last resort is not set
```

```
192.24.0.0/24 is variably subnetted, 10 subnets, 5 masks
```

```
C 192.24.0.152/30 is directly connected, FastEthernet0/1
```

```
O 192.24.0.156/30 [110/11] via 192.24.0.153, 00:05:22, FastEthernet0/1
```

```
O 192.24.0.144/29 [110/12] via 192.24.0.162, 00:00:28, FastEthernet1/0
```

```
O 192.24.0.128/28 [110/20] via 192.24.0.153, 00:05:22, FastEthernet0/1
```

```
O 192.24.0.168/30 [110/2] via 192.24.0.162, 00:00:28, FastEthernet1/0
```

```
C 192.24.0.160/30 is directly connected, FastEthernet1/0
```

```
O 192.24.0.164/30 [110/12] via 192.24.0.162, 00:00:30, FastEthernet1/0
```

```
[110/12] via 192.24.0.153, 00:03:52, FastEthernet0/1
```

```
C 192.24.0.64/27 is directly connected, FastEthernet0/0
```

```
O 192.24.0.96/27 [110/21] via 192.24.0.153, 00:03:52, FastEthernet0/1
```

```
O 192.24.0.0/26 [110/11] via 192.24.0.162, 00:00:50, FastEthernet1/0
```

```
R2-00056024#
```

```
R3-00056024#show ip route
```

```
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2  
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2  
ia - IS-IS inter area, * - candidate default, U - per-user static route  
o - ODR, P - periodic downloaded static route
```

```
Gateway of last resort is not set
```

```
192.24.0.0/24 is variably subnetted, 10 subnets, 5 masks  
O    192.24.0.152/30 [110/20] via 192.24.0.157, 00:04:24, FastEthernet0/1  
C    192.24.0.156/30 is directly connected, FastEthernet0/1  
O    192.24.0.144/29 [110/11] via 192.24.0.166, 00:02:40, FastEthernet1/0  
O    192.24.0.128/28 [110/20] via 192.24.0.157, 00:04:24, FastEthernet0/1  
O    192.24.0.168/30 [110/2] via 192.24.0.166, 00:02:18, FastEthernet1/0  
O    192.24.0.160/30 [110/12] via 192.24.0.166, 00:00:54, FastEthernet1/0  
C    192.24.0.164/30 is directly connected, FastEthernet1/0  
O    192.24.0.64/27 [110/22] via 192.24.0.166, 00:00:56, FastEthernet1/0  
C    192.24.0.96/27 is directly connected, FastEthernet0/0  
O    192.24.0.0/26 [110/12] via 192.24.0.166, 00:00:56, FastEthernet1/0
```

```
R3-00056024#
```

```
R4-00056024#show ip route
```

```
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2  
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2  
ia - IS-IS inter area, * - candidate default, U - per-user static route  
o - ODR, P - periodic downloaded static route
```

```
Gateway of last resort is not set
```

```
192.24.0.0/24 is variably subnetted, 10 subnets, 5 masks  
O    192.24.0.152/30 [110/21] via 192.24.0.170, 00:01:11, FastEthernet1/0  
O    192.24.0.156/30 [110/20] via 192.24.0.165, 00:02:48, FastEthernet0/1  
C    192.24.0.144/29 is directly connected, FastEthernet0/0  
O    192.24.0.128/28 [110/30] via 192.24.0.165, 00:02:48, FastEthernet0/1  
C    192.24.0.168/30 is directly connected, FastEthernet1/0  
O    192.24.0.160/30 [110/11] via 192.24.0.170, 00:01:11, FastEthernet1/0  
C    192.24.0.164/30 is directly connected, FastEthernet0/1  
O    192.24.0.64/27 [110/21] via 192.24.0.170, 00:01:13, FastEthernet1/0  
O    192.24.0.96/27 [110/20] via 192.24.0.165, 00:02:50, FastEthernet0/1  
O    192.24.0.0/26 [110/11] via 192.24.0.170, 00:01:13, FastEthernet1/0
```

```
R4-00056024#
```

```
R5-00056024#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route
```

Gateway of last resort is not set

```
192.24.0.0/24 is variably subnetted, 10 subnets, 5 masks
O    192.24.0.152/30 [110/20] via 192.24.0.161, 00:01:39, FastEthernet0/1
O    192.24.0.156/30 [110/21] via 192.24.0.169, 00:01:29, FastEthernet1/0
      [110/21] via 192.24.0.161, 00:01:39, FastEthernet0/1
O    192.24.0.144/29 [110/11] via 192.24.0.169, 00:01:29, FastEthernet1/0
O    192.24.0.128/28 [110/30] via 192.24.0.161, 00:01:39, FastEthernet0/1
C    192.24.0.168/30 is directly connected, FastEthernet1/0
C    192.24.0.160/30 is directly connected, FastEthernet0/1
O    192.24.0.164/30 [110/11] via 192.24.0.169, 00:01:31, FastEthernet1/0
O    192.24.0.64/27 [110/20] via 192.24.0.161, 00:01:41, FastEthernet0/1
O    192.24.0.96/27 [110/21] via 192.24.0.169, 00:01:31, FastEthernet1/0
C    192.24.0.0/26 is directly connected, FastEthernet0/0
R5-00056024#
```

```
PC5> trace 192.24.0.66
trace to 192.24.0.66, 8 hops max, press Ctrl+C to stop
 1  192.24.0.145    15.548 ms  15.006 ms  15.811 ms
 2  192.24.0.170    46.642 ms  45.913 ms  46.053 ms
 3  192.24.0.161    76.391 ms  75.698 ms  75.477 ms
 4  **192.24.0.66   90.339 ms (ICMP type:3, code:3, Destination port unreachable)
PC5>
```

Ejercicio híbrido
 Carnet: 00056024
 A: 00
 B: 24
 172.16.24.0/24

Handwritten notes at the top: $6^{\circ} - 1^{\circ} = 5^{\circ}$, $2^{\circ} - 2^{\circ} = 0^{\circ}$, $3^{\circ} - 2^{\circ} = 1^{\circ}$, $4^{\circ} - 3^{\circ} = 1^{\circ}$, $5^{\circ} - 4^{\circ} = 1^{\circ}$, $6^{\circ} - 5^{\circ} = 1^{\circ}$, $7^{\circ} - 6^{\circ} = 1^{\circ}$, $8^{\circ} - 7^{\circ} = 1^{\circ}$, $9^{\circ} - 8^{\circ} = 1^{\circ}$, $10^{\circ} - 9^{\circ} = 1^{\circ}$, $11^{\circ} - 10^{\circ} = 1^{\circ}$.
 $2^{\circ} - 2^{\circ} = 0^{\circ}$
 $3^{\circ} - 2^{\circ} = 1^{\circ}$
 $4^{\circ} - 3^{\circ} = 1^{\circ}$
 $5^{\circ} - 4^{\circ} = 1^{\circ}$
 $6^{\circ} - 5^{\circ} = 1^{\circ}$
 $7^{\circ} - 6^{\circ} = 1^{\circ}$
 $8^{\circ} - 7^{\circ} = 1^{\circ}$
 $9^{\circ} - 8^{\circ} = 1^{\circ}$
 $10^{\circ} - 9^{\circ} = 1^{\circ}$
 $11^{\circ} - 10^{\circ} = 1^{\circ}$

Orden	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°
1°	172.16.24.0	172.16.24.1	172.16.24.2	172.16.24.3							
2°	.64	.65	.99	.95							
3°	.96	.97	.126	.177							
4°	.178	.179	.142	.143							
5°	.194	.195	.150	.151							
6°	.152	.153	.154	.155							
7°	.156	.157	.158	.159							
8°	.160	.161	.162	.163							
9°	.164	.165	.166	.167							
10°	.168	.169	.170	.171							
11°	.172	.173	.174	.175							

Orden	1°	2°	3°	4°	5°	6°	7°
1°	R5 R010 .1	PC1 R10 .2					
2°	R2 R010 .65	PC2 R10 .86					
3°	R3 R010 .97	PC3 R10 .98					
4°	R1 R010 .129	PC4 R10 .170					
5°	R4 R010 .195	PC5 R10 .146					
6°	R1 R010 .153	R2 R010 .154					
7°	R1 R110 .157	R3 R010 .158					

PC1> show ip

```
NAME       : PC1[1]
IP/MASK    : 172.16.24.2/26
GATEWAY    : 172.16.24.1
DNS        :
MAC        : 00:50:79:66:68:00
LPORT     : 10056
RHOST:PORT : 127.0.0.1:10057
MTU       : 1500
```

PC1> █

```
PC2> show ip
```

```
NAME       : PC2[1]  
IP/MASK    : 172.16.24.66/27  
GATEWAY    : 172.16.24.65  
DNS        :  
MAC        : 00:50:79:66:68:01  
LPORT      : 10058  
RHOST:PORT : 127.0.0.1:10059  
MTU        : 1500
```

```
PC2> █
```

```
PC4> show ip
```

```
s S NAME       : PC4[1]  
s n IP/MASK    : 172.16.24.98/28  
ute GATEWAY    : 172.16.24.97  
s l DNS        :  
ro  MAC        : 00:50:79:66:68:03  
    LPORT      : 10062  
    RHOST:PORT : 127.0.0.1:10063  
    MTU        : 1500
```

```
er ) PC4> █
```