



FreeRTOS V9.0.0rc1 is now available for download and comment.



Sponsored Links







1 von 3 01.03.2016 09:42

Home FreeRTOS Books and Manuals ■ FreeRTOS <u>■ About FreeRTOS</u> <u>■ Features / Getting Started...</u> ■ More Advanced... ■ Demo Projects ■ Supported Devices & Demos ■ API Reference PDF Reference Manual <u>■ Task Creation</u> **±** Task Control <u>■ Task Utilities</u> ■ RTOS Kernel Control ■ <u>Direct To Task Notifications</u> **■** FreeRTOS-MPU Specific ■ Queues uxQueueMessagesWaiting() uxQueueMessagesWaitingFromISR() uxQueueSpacesAvailable() xQueueCreate() vQueueDelete() xQueueReset() xQueueSend() xQueueSendToBack() xQueueSendToFront() xQueueReceive() xQueueOverwrite() xQueueOverwriteFromISR() xQueuePeek() xQueuePeekFromISR() xQueueSendFromISR() xQueueSendToBackFromISR() xQueueSendToFrontFromISR() xQueueReceiveFromISR() vQueueAddToRegistry() vQueueUnregisterQueue() xQueuelsQueueFullFromISR()

xQueuelsQueueEmptyFromISR() ■ Queue Sets

■ Semaphore / Mutexes ■ Software Timers

<u> Co-routines</u>

⊞ Contact, Support, Advertising <u>★ FreeRTOS Interactive!</u>

FreeRTOS+ Lab Projects

FreeRTOS+TCP:

Thread safe TCP/IP stack
FreeRTOS+FAT:

Thread aware file system

FreeRTOS+ Ecosystem

Internet of Things:

Fail Safe File System:

Ensures data inte

InterNiche TCP/IP: Low cost pre-ported libraries

FreeRTOS BSPs:

FAT SL File System:

UDP/IP: Thread aware UDP stack

Trace & Visualisation:

alyzer for FreeRTOS

CI I:

Command line interface
WolfSSL SSL / TLS:

Networking security protocols

Safety: TUV certified RTOS

RTOS Training:

Delivered online or on-site

10:

read(), write(), ioctl() interface

Google^m Custom Search Search

xQueueReceive

[Queue Management]

```
queue. h
```

```
BaseType_t xQueueReceive(
                              QueueHandle_t xQueue,
                               void *pvBuffer.
                              TickType_t xTicksToWait
```

This is a macro that calls the xQueueGenericReceive() function.

Receive an item from a queue. The item is received by copy so a buffer of adequate size must be provided. The number of bytes copied into the buffer was defined when the queue was created.

This function must not be used in an interrupt service routine. See xQueueReceiveFromISR for an alternative that can.

Parameters:

xQueue The handle to the gueue from which the item is to be received pvBuffer Pointer to the buffer into which the received item will be copied

xTicksToWait The maximum amount of time the task should block waiting for an item to receive should the queue be empty at the time of the call. Setting xTicksToWait to 0 will cause the function to return immediately if the queue is empty. The time is defined in tick periods so the constant portTICK_PERIOD_MS should be used to convert to real time if this is

> If INCLUDE_vTaskSuspend is set to '1' then specifying the block time as portMAX DELAY will cause the task to block indefinitely (without a

Returns:

pdTRUE if an item was successfully received from the queue, otherwise pdFALSE.

Example usage:

```
struct AMessage
    char ucMessageID;
    char ucData[ 20 ];
QueueHandle t xQueue;
// Task to create a queue and post a value.
void vATask( void *pvParameters )
struct AMessage *pxMessage;
    // Create a queue capable of containing 10 pointers to AMessage structures. // These should be passed by pointer as they contain a lot of data.
    xQueue = xQueueCreate( 10, sizeof( struct AMessage * ) );
if( xQueue == 0 )
         // Failed to create the queue.
    }
    // Send a pointer to a struct AMessage object. Don't block if the
   // queue is already full.
pxMessage = & xMessage;
    xQueueSend( xQueue, ( void * ) &pxMessage, ( TickType_t ) 0 );
        // ... Rest of task code.
// Task to receive from the queue.
void vADifferentTask( void *pvParameters )
struct AMessage *pxRxedMessage;
    if( xQueue != 0 )
         // Receive a message on the created queue. Block for 10 ticks if a
        // message is not immediately available. if( xQueueReceive( xQueue, &( pxRxedMessage ), ( TickType_t ) 10 ) )
               / pcRxedMessage now points to the struct AMessage variable posted
   }
        // ... Rest of task code.
```



















2 von 3 01.03.2016 09:42 [Back to the top] [About FreeRTOS] [Sitemap] [Report an error on this page]

Copyright (C) 2004-2010 Richard Barry. Copyright (C) 2010-2016 Real Time Engineers Ltd.

Any and all data, files, source code, thml content and documentation included in the FreeRTOSTM distribution or available on this site are the exclusive property of Real Time Engineers Ltd. See the files license.tx (included in the distribution) and this copyright notice for more information. FreeRTOSTM and FreeRTOS.orgTM are trade marks of Real Time Engineers Ltd.

3 von 3 01.03.2016 09:42