

03_geocode

May 30, 2019

1 Geocode

Mapping the H2A visa work sites

```
[73]: import os
import csv
import time
import random
import calculate
import numpy as np
import pandas as pd
import timeout_decorator
from geopy import Location
from geopy.geocoders import Bing
```

```
[74]: import warnings
warnings.filterwarnings("ignore")
```

Read in all the visas

```
[75]: df = pd.concat([
    pd.read_csv("./output/transformed_master_cases.csv"),
    pd.read_csv("./output/transformed_sub_cases.csv"),
])
```

Join

Extract the distinct locations

```
[76]: locations = df.groupby(['city', 'state']).size().reset_index().
    →rename(columns={0: "count"})
```

Double group by

Read in previously geocoded locations

```
[77]: geocoded = pd.read_csv("./output/geocoded.csv")
```

```
[78]: geocode_cache = dict(
    (d['key'], d) for i, d in geocoded.iterrows()
)
```

Identify how many remain unmapped

```
[79]: df['key'] = df.apply(lambda x: "{}, {}".format(x.city, x.state), axis=1)
```

```
[80]: not_geocoded = df[~df.key.isin(geocoded.key)]
```

```
[81]: print "{:}, of {:}, geocoded ({}%)".format(
        len(df) - len(not_geocoded),
        len(df),
        calculate.percentage(len(df) - len(not_geocoded), len(df))
    )
```

83,087 of 83,088 geocoded (99.9987964568%)

Extract the unmapped locations

```
[82]: unmapped = not_geocoded.groupby(['key']).size().reset_index().rename(columns={0:
        → "count"})
```

```
[83]: df_list = list(unmapped.iterrows())
```

```
[84]: random.shuffle(df_list)
```

Try to geocode them

```
[85]: @timeout_decorator.timeout(10)
def bingit(key):
    bing = Bing(os.getenv("BING_API_KEY"), timeout=10)
    address = "{}, United States".format(key)
    print "Geocoding {}".format(address)
    try:
        geocode_cache[key]
        print "Already mapped"
        return
    except KeyError:
        pass

    result = bing.geocode(address, exactly_one=False)
    if not result:
        return
    first_result = result[0]

    print "Mapped to {}".format(first_result)
    geocode_cache[key] = first_result
    time.sleep(0.5)
```

```
[86]: for i, row in df_list:
        try:
            bingit(row.key)
        except:
            print "TIMEOUT"
            continue
```

Geocoding Juniata, NE, United States

Mapped to Juniata, NE, United States

Merged the newly geocoded locations with the old ones

```
[87]: def transform_geocode(key, value):
        if isinstance(value, pd.Series):
            return [key, value['geocoder_address'], value['lat'], value['lng'],
                    ↪value['geocoder_type']]
        return [key, value.address, value.latitude, value.longitude, "bing"]
```

```
[88]: rows = [transform_geocode(k, v) for k, v in geocode_cache.items()]
```

```
[89]: rows.sort(key=lambda x:x[0])
```

Save the geocoded locations

```
[90]: with open("./output/geocoded.csv", 'w') as f:
        w = csv.writer(f)
        w.writerow(["key", "geocoder_address", "lat", "lng", "geocoder_type"])
        w.writerows(rows)
```

Merge geocoded points onto cases

```
[91]: mapped = pd.read_csv("./output/geocoded.csv")
```

```
[92]: def create_key(row):
        # Skip any nulls
        if row.city in [np.NaN, 'nan', '']:
            return ''
        elif row.state in [np.NaN, 'nan', '']:
            return ''
        else:
            return "{}, {}".format(row.city, row.state)
```

```
[93]: def add_points(name):
        df = pd.read_csv("./output/transformed_{}.csv".format(name))
        df['key'] = df.apply(create_key, axis=1)
        mapped_df = df.merge(mapped, on=["key"], how="left")
        mapped_df.drop('key', axis=1, inplace=True)
        mapped_df.to_csv("./output/geocoded_{}.csv".format(name), index=False,
            ↪encoding="utf-8")
```

```
[94]: add_points("master_cases")
```

```
[95]: add_points("sub_cases")
```

```
[96]: add_points("all_cases")
```