

PMorph: A Task-Specialized Robot Manipulator Morphology Optimizer

Stephen Gillet¹

Abstract—This paper seeks to address the overactuation, energy-inefficiency, and lack of task specialization seen in manufacturing from the current suite of generalized robotic manipulators. The approach involves specifying a task in a MuJoCo simulated environment and then using a PPO agent to optimize the morphology for that environment given a reward function. The morphological elements to be optimized include the number of links, the lengths of each link, and the type of joints involved. The reward function is tuned to weigh energy cost, end effector movement, end effector accuracy, manipulability measures, number of links, and task completion. PPO is ideal for this task because it can efficiently optimize over the continuous action space that is morphology, resulting in a robot that is more simple, efficient, and capable than those commonly used in industry today.

I. INTRODUCTION

Imagine a factory where every employee has to be trained on and work every job in the plant. Imagine how inefficient that would be. Every employee would have general knowledge and ability, but no one would have a chance to specialize and become very good at any particular job. This is exactly the state of robotics in manufacturing today where high costs and lack of tailorability are some of the most cited problems for the adoption of robotics [1][2]. To make matters worse [3] and [4] show that most manipulators are overactuated, less cost-efficient, and less effective for most tasks they are used in today.

This paper seeks to address these issues by using a PPO agent to optimize the morphology of a robotic manipulator to the particular task it is being used for. This ensures that the robot is as simple, efficient, and capable as possible for its particular job while still allowing the user to specify the level of robustness by tuning the reward function.

PPO was chosen for its ability to explore the continuous action space that is morphology and it has been shown to do so efficiently and robustly [5]. The core method is to use `stable_baselines3` PPO implementation to iterate on the design parameters (number of links, joint types (X, Y, Z hinge, and Z actuation), and link lengths), use MuJoCo to simulate that iteration on a simple task using RRTConnect and damped least squares (DLS) inverse kinematics (IK) for the path planning, feed the results (success, efficiency, and manipulability index) back into the PPO model. RRTConnect was chosen for simplicity and it has been shown to be faster than other methods [6] which enables faster and more robust training. DLS IK was chosen for a similar reason, it has

been shown to be robust especially in situations where the target position is out of reach [7] which is inevitable when exploring morphologies, some of which will be too small or otherwise poorly suited to the task as the agent learns.

The evaluation signals will be successful path planning, path length, energy cost, and manipulability index. The manipulability index is a measure of a manipulators ability to arbitrarily change the position and orientation of the end effector at a particular point, borrowed from [8]. The tasks will be kept simple but varied in ways to test different types of movements like moving near the base, moving from near to far, different elevations, more linear movements, and different obstacle constraints. One might imagine that a lot of pick and place tasks are mostly linear and so might largely be done by linear actuators more efficiently for example.

The research questions to be answered: Can PPO be used to generate more efficient morphologies? Can morphologies be generated for tasks that generalized manipulators cannot do or cannot perform well? Can more simple morphologies (less DOF) be generated that can perform the same tasks with similar levels of accuracy?

II. RELATED WORK

Most of the research in this area codesigns morphology and control of atomic, modular robots. [9] shows that PPO can be used to generate freeform morphologies optimized for locomotion tasks from a set of atomic modules. [10] shows that reinforcement learning can be used to co-optimize morphology and control for a modular robot that outperforms optimizing motion on a fixed morphology in a simulated environment. [11] also uses reinforcement learning to co-optimize with the addition of a pretrained foundation model to accelerate the training process and improve results.

Most pertinent to this paper, [12] shows that PPO and A3C can be used to generate optimal morphologies that improve performance of reconfigurable robots, [13] uses DDQN to co-optimize morphology and control for modular robotic manipulators, and [14] uses soft actor critic for co-optimization showing that the approach resulted in drastically less design prototypes. This background motivates the approach of this paper which is going to use simple controllers and similar reinforcement learning techniques to maximize morphological potential. FANUC 6-DOF series of manipulators are the most commonly used in industry today [15][16] and so their morphology will be used as a baseline for comparison. Given the same environment, task, and controllers which morphologies will perform better?

^{*}This work was not supported by any organization

¹Stephen Gillet is a Master's student with the Robotic Program, University of Colorado Boulder, Boulder, CO 80309, U.S.A. stgi5837@colorado.edu

III. MATH

Before you begin to format your paper, first write and save the content as a separate text file. Keep your text and graphic files separate until after the text has been formatted and styled. Do not use hard tabs, and limit use of hard returns to only one return at the end of a paragraph. Do not add any kind of pagination anywhere in the paper. Do not number text heads-the template will do that for you.

Finally, complete content and organizational editing before formatting. Please take note of the following items when proofreading spelling and grammar:

A. Abbreviations and Acronyms

Define abbreviations and acronyms the first time they are used in the text, even after they have been defined in the abstract. Abbreviations such as IEEE, SI, MKS, CGS, sc, dc, and rms do not have to be defined. Do not use abbreviations in the title or heads unless they are unavoidable.

B. Units

- Use either SI (MKS) or CGS as primary units. (SI units are encouraged.) English units may be used as secondary units (in parentheses). An exception would be the use of English units as identifiers in trade, such as "3.5-inch disk drive".
- Avoid combining SI and CGS units, such as current in amperes and magnetic field in oersteds. This often leads to confusion because equations do not balance dimensionally. If you must use mixed units, clearly state the units for each quantity that you use in an equation.
- Do not mix complete spellings and abbreviations of units: Wb/m or "webers per square meter", not "webers/m²". Spell out units when they appear in text: ". . . a few henries", not ". . . a few H".
- Use a zero before decimal points: "0.25", not ".25". Use "cm³", not "cc". (bullet list)

C. Equations

The equations are an exception to the prescribed specifications of this template. You will need to determine whether or not your equation should be typed using either the Times New Roman or the Symbol font (please no other font). To create multileveled equations, it may be necessary to treat the equation as a graphic and insert it into the text after your paper is styled. Number equations consecutively. Equation numbers, within parentheses, are to position flush right, as in (1), using a right tab stop. To make your equations more compact, you may use the solidus (/), the exp function, or appropriate exponents. Italicize Roman symbols for quantities and variables, but not Greek symbols. Use a long dash rather than a hyphen for a minus sign. Punctuate equations with commas or periods when they are part of a sentence, as in

$$\alpha + \beta = \chi \quad (1)$$

Note that the equation is centered using a center tab stop. Be sure that the symbols in your equation have been defined

before or immediately following the equation. Use "(1)", not "Eq. (1)" or "equation (1)", except at the beginning of a sentence: "Equation (1) is . . ."

D. Some Common Mistakes

- The word "data" is plural, not singular.
- The subscript for the permeability of vacuum μ_0 , and other common scientific constants, is zero with subscript formatting, not a lowercase letter "o".
- In American English, commas, semi-/colons, periods, question and exclamation marks are located within quotation marks only when a complete thought or name is cited, such as a title or full quotation. When quotation marks are used, instead of a bold or italic typeface, to highlight a word or phrase, punctuation should appear outside of the quotation marks. A parenthetical phrase or statement at the end of a sentence is punctuated outside of the closing parenthesis (like this). (A parenthetical sentence is punctuated within the parentheses.)
- A graph within a graph is an "inset", not an "insert". The word alternatively is preferred to the word "alternately" (unless you really mean something that alternates).
- Do not use the word "essentially" to mean "approximately" or "effectively".
- In your paper title, if the words "that uses" can accurately replace the word "using", capitalize the "u"; if not, keep using lower-cased.
- Be aware of the different meanings of the homophones "affect" and "effect", "complement" and "compliment", "discreet" and "discrete", "principal" and "principle".
- Do not confuse "imply" and "infer".
- The prefix "non" is not a word; it should be joined to the word it modifies, usually without a hyphen.
- There is no period after the "et" in the Latin abbreviation "et al."
- The abbreviation "i.e." means "that is", and the abbreviation "e.g." means "for example".

IV. USING THE TEMPLATE

Use this sample document as your LaTeX source file to create your document. Save this file as **root.tex**. You have to make sure to use the cls file that came with this distribution. If you use a different style file, you cannot expect to get required margins. Note also that when you are creating your out PDF file, the source file is only part of the equation. *Your $\TeX \rightarrow \text{PDF}$ filter determines the output file size. Even if you make all the specifications to output a letter file in the source - if your filter is set to produce A4, you will only get A4 output.*

It is impossible to account for all possible situation, one would encounter using $\TeX$. If you are using multiple $\TeX$ files you must make sure that the "MAIN" source file is called root.tex - this is particularly important if your conference is using PaperPlaza's built in $\TeX$ to PDF conversion tool.

A. Headings, etc

Text heads organize the topics on a relational, hierarchical basis. For example, the paper title is the primary text head because all subsequent material relates and elaborates on this one topic. If there are two or more sub-topics, the next level head (uppercase Roman numerals) should be used and, conversely, if there are not at least two sub-topics, then no subheads should be introduced. Styles named "Heading 1", "Heading 2", "Heading 3", and "Heading 4" are prescribed.

B. Figures and Tables

Positioning Figures and Tables: Place figures and tables at the top and bottom of columns. Avoid placing them in the middle of columns. Large figures and tables may span across both columns. Figure captions should be below the figures; table heads should appear above the tables. Insert figures and tables after they are cited in the text. Use the abbreviation "Fig. 1", even at the beginning of a sentence.

TABLE I
AN EXAMPLE OF A TABLE

One	Two
Three	Four

We suggest that you use a text box to insert a graphic (which is ideally a 300 dpi TIFF or EPS file, with all fonts embedded) because, in an document, this method is somewhat more stable than directly inserting a picture.

Fig. 1. Inductance of oscillation winding on amorphous magnetic core versus DC bias magnetic field

Figure Labels: Use 8 point Times New Roman for Figure labels. Use words rather than symbols or abbreviations when writing Figure axis labels to avoid confusing the reader. As an example, write the quantity "Magnetization", or "Magnetization, M", not just "M". If including units in the label, present them within parentheses. Do not label axes only with units. In the example, write "Magnetization (A/m)" or "Magnetization A[m(1)]", not just "A/m". Do not label axes with a ratio of quantities and units. For example, write "Temperature (K)", not "Temperature/K."

V. CONCLUSIONS

A conclusion section is not required. Although a conclusion may review the main points of the paper, do not replicate the abstract as the conclusion. A conclusion might elaborate on the importance of the work or suggest applications and extensions.

APPENDIX

Appendixes should appear before the acknowledgment.

ACKNOWLEDGMENT

The preferred spelling of the word "acknowledgment" in America is without an "e" after the "g". Avoid the stilted expression, "One of us (R. B. G.) thanks . . ." Instead, try "R. B. G. thanks". Put sponsor acknowledgments in the unnumbered footnote on the first page.

References are important to the reader; therefore, each citation must be complete and correct. If at all possible, references should be commonly available publications.

REFERENCES

- [1] McKinsey and Company, "Industrial robotics: Insights into the sector's future growth dynamics," McKinsey and Company, Tech. Rep., 2019. [Online]. Available: <https://www.mckinsey.com/business-functions/operations/our-insights/industrial-robotics-insights-into-the-sectors-future-growth-dynamics>
- [2] R. V. Patel, "Opportunities and challenges for adoption of robotics in packaging industry: A review," *IOSR Journal of Engineering*, vol. 14, no. 1, pp. 32–38, Jan 2024, available: https://www.iosrjen.org/Papers/vol14_issue1/E1401013238.pdf.
- [3] M. Russo, L. Raimondi, X. Dong, and D. Axinte, "Task-oriented optimal dimensional synthesis of robotic manipulators with limited mobility," *Robotics and Computer-Integrated Manufacturing*, vol. 69, p. 102098, 2021.
- [4] B. He, S. Wang, and Y. Liu, "Underactuated robotics: A review," *International Journal of Advanced Robotic Systems*, vol. 16, no. 4, pp. 1–14, 2019.
- [5] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov, "Proximal policy optimization algorithms," arXiv:1707.06347, 2017.
- [6] J. J. Kuffner and S. M. LaValle, "Rrt-connect: An efficient approach to single-query path planning," in *Proceedings 2000 ICRA. Millennium Conference. IEEE International Conference on Robotics and Automation. Symposia Proceedings (Cat. No.00CH37065)*, vol. 2, 2000, pp. 995–1001 vol.2.
- [7] S. R. Buss, "Introduction to inverse kinematics with jacobian transpose, pseudoinverse and damped least squares methods," *IEEE Journal of Robotics and Automation*, vol. 17, no. 1–19, p. 16, 2004.
- [8] T. Yoshikawa, "Manipulability of robotic mechanisms," *The International Journal of Robotics Research*, vol. 4, no. 2, pp. 3–9, 1985.
- [9] J. Bhatia *et al.*, "Reinforcement learning for freeform robot design," arXiv:2310.05670, 2023.
- [10] B. Tjanaka *et al.*, "Co-optimization of morphology and behavior of modular robots via hierarchical deep reinforcement learning," in *Robotics: Science and Systems (RSS)*, 2023.
- [11] A. Spielberg *et al.*, "Accelerated co-design of robots through morphological pretraining," arXiv:2502.10862, 2025.
- [12] M. Kalimuthu, A. A. Hayat, T. Pathmakumar, M. R. Elara, and K. L. Wood, "A deep reinforcement learning approach to optimal morphologies generation in reconfigurable tiling robots," *Mathematics*, vol. 11, no. 18, p. 3893, 2023.
- [13] Z. Ding, H. Tang, H. Wan, C. Zhang, and R. Sun, "A modular robotic arm configuration design method based on double dqn with prioritized experience replay," *Symmetry*, vol. 16, no. 6, p. 714, 2024. [Online]. Available: <https://www.mdpi.com/2073-8994/16/6/714>
- [14] K. S. Luck, H. B. Amor, R. Calandra, and J. Peters, "Data-efficient co-adaptation of morphology and behaviour with deep reinforcement learning," in *Conference on Robot Learning (CoRL)*, 2019.
- [15] PatentPC, "Top robotics vendors by market share and installations," Sep 2025. [Online]. Available: <https://patentpc.com/blog/top-robotics-vendors-by-market-share-installations>
- [16] Standard Bots, "Fanuc robot prices: Cost, models, and buying insights in 2025," 2025. [Online]. Available: <https://standardbots.com/blog/fanuc-robot-price>