

Week-14-Structures and Unions: Attempt review | REC-CIS - Personal - Microsoft Edge

Not secure | www.rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159139&cmid=405

REC-CIS

Question 2  
Correct  
Flag question

You are given  $n$  triangles, specifically, their sides  $a_i$ ,  $b_i$  and  $c_i$ . Print them in the same style but sorted by their areas from the smallest one to the largest one. It is guaranteed that all the areas are different.

The best way to calculate a volume of the triangle with sides  $a$ ,  $b$  and  $c$  is Heron's formula:

$$S = \sqrt{p(p-a)(p-b)(p-c)} \text{ where } p = (a+b+c)/2.$$

Input Format

First line of each test file contains a single integer  $n$ .  $n$  lines follow with  $a_i$ ,  $b_i$  and  $c_i$  on each separated by single spaces.

Constraints

$1 \leq n \leq 100$   
 $1 \leq a_i, b_i, c_i \leq 70$   
 $a_i + b_i > c_i$ ,  $a_i + c_i > b_i$  and  $b_i + c_i > a_i$

Output Format

Print exactly  $n$  lines. On each line print 3 integers separated by single spaces, which are  $a_i$ ,  $b_i$  and  $c_i$  of the corresponding triangle.

Sample Input 0

```
3
7 24 25
5 12 13
3 4 5
```

Sample Output 0

```
3 4 5
5 12 13
7 24 25
```

Week-14-Structures and Unions: Attempt review | REC-CIS - Personal - Microsoft Edge

Not secure | www.rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159139&cmid=405

REC-CIS

Explanation 0

The first box is really low, only 5 feet tall, so it can pass through the tunnel and its volume is  $5 \times 5 \times 5 = 125$ .

The second box is sufficiently low, its volume is  $1 \times 2 \times 4 = 80$ .

The third box is exactly 47 feet tall, so it cannot pass. The same can be said about the fourth box.

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int a;
5     scanf("%d", &a);
6     for(int i=0; i<a; i++) {
7         int l, w, h;
8         scanf("%d %d %d", &l, &w, &h);
9         if(h>47) {
10             printf("%d\n", l*w*h);
11         }
12     }
13     return 0;
14 }
15 }
```

|   | Input   | Expected | Got |   |
|---|---------|----------|-----|---|
| ✓ | 4       | 125      | 125 | ✓ |
|   | 5 5 5   | 80       | 80  |   |
|   | 1 2 40  |          |     |   |
|   | 10 5 41 |          |     |   |
|   | 7 2 42  |          |     |   |

Passed all tests! ✓

Week-14-Structures and Unions: Attempt review | REC-CIS - Personal - Microsoft Edge

Not secure | www.rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159139&cmid=405

REC-CIS

Quiz navigation

12

Show one page at a time

Finish review

Status: Finished

Started: Monday, 13 January 2025, 10:49 PM

Completed: Monday, 13 January 2025, 11:07 PM

Duration: 18 mins

Question 1

Correct

Flag question

You are transporting some boxes through a tunnel, where each box is a parallelepiped, and is characterized by its length, width and height.

The height of the tunnel **47** feet and the width can be assumed to be infinite. A box can be carried through the tunnel only if its height is strictly less than the tunnel's height. Find the volume of each box that can be successfully transported to the other end of the tunnel. Note: Boxes cannot be rotated.

Input Format

The first line contains a single integer  $n$ , denoting the number of boxes.

$n$  lines follow with three integers on each separated by single spaces - **length**, **width** and **height**, which are length, width and height in feet of the  $i$ -th box.

Constraints

$1 \leq n \leq 100$

$1 \leq \text{length}, \text{width}, \text{height} \leq 100$

Output Format

For every box from the input which has a height less than **47** feet, print its volume in a separate line.

Sample Input 0

```
4
5 5 5
1 2 40
10 5 41
7 2 42
```

Week-14-Structures and Unions: Attempt review | REC-CIS - Personal - Microsoft Edge

Not secure | www.rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=159139&cmid=405

REC-CIS

Explanation 0

The square of the first triangle is **84**. The square of the second triangle is **30**. The square of the third triangle is **6**. So the sorted order is the reverse one.

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <math.h>
4 int cmp(const void*a,const void*b) {
5     return(*(int*)a-*(int*)b);
6 }
7 int main()
8 {
9     int a;
10    scanf("%d",&a);
11    int b[a][3];
12    int c[a],d[a];
13    for(int i=0;i<a;i++) {
14        scanf("%d %d %d",&b[i][0],&b[i][1],&b[i][2]);
15        int p=(b[i][0]*b[i][1]+b[i][1]*b[i][2]);
16        c[i]=sqrt((p*(p-b[i][0])*(p-b[i][1])*(p-b[i][2])));
17        d[i]=c[i];
18    }
19    qsort(d,a,sizeof(int),cmp);
20    for(int i=0;i<a;i++) {
21        for(int j=0;j<a;j++) {
22            if (d[i]==c[j]) {
23                printf("%d %d %d\n",b[j][0],b[j][1],b[j][2]);
24                break;
25            }
26        }
27    }
28 }
29
30
```

|   | Input   | Expected | Got     |   |
|---|---------|----------|---------|---|
| ✓ | 3       | 3 4 5    | 3 4 5   | ✓ |
| ✓ | 7 24 25 | 5 12 13  | 5 12 13 |   |
| ✓ | 5 12 13 | 7 24 25  | 7 24 25 |   |
| ✓ | 3 4 5   |          |         |   |

Passed all tests! ✓