

# CS 241: Systems Programming

## Lecture 29. Static Libraries

Fall 2019

Prof. Stephen Checkoway

# Announcement

Homework 5 *Regular Expressions* is now available

- Due Sunday 2019-11-24 at 23:59

# Code reuse is good!

Why?

# Multiple forms of code reuse

## Source code reuse

- Distribute source code that can be included in many programs

## Binary code reuse

- Distribute binary code that can be linked into programs
- Static libraries: code linked in at link time
- Dynamic libraries: code linked in at run time

# Static libraries ("archives")

Nothing more than a collection of object files (.o) bundled together

A "foo" library composed of object files a.o, b.o, ..., z.o

- ▶ Traditionally named `libfoo.a`
- ▶ Compile object files as normal, e.g.,  
`$ clang -c -o a.o a.c`
- ▶ Put them in an archive:  
`$ ar crs libfoo.a a.o b.o ... z`

We can link our programs with the archive, e.g.,

- ▶ `$ clang -o prog1 prog1.o libfoo.a`
- ▶ `$ clang -o prog2 prog2.o libfoo.a`

# ar(1)

ar is the archive utility

- It can create archives of arbitrary files
- It can add files to or update files in an archive
- It can delete or extract files from an archive

```
$ ar crs libfoo.a a.o b.o ... z
```

- c — create an archive
- r — add (with replacement) files to the archive
- s — create a symbol table

# An archive Makefile rule

Because ar is designed to update archives, it's easiest to just delete and recreate it

```
libfoo.o: a.o b.o c.o  
    $(RM) $@  
    $(AR) crs $^
```

# Linking with static libraries

The linker (which we usually invoke via the compiler driver clang or gcc) only includes object files from an archive which are "needed"

For example,

- ▶ `a.c` defines `void fun1(void);`
- ▶ `b.c` defines `void fun2(void);`
- ▶ `c.c` defines `int blah;`
- ▶ `libfoo.a` contains `a.o`, `b.o`, and `c.o`
- ▶ If the program uses `fun1()` and `blah` but not `fun2()` in its `main.c` then  
\$ `clang -o prog main.o libfoo.a`  
is essentially  
\$ `clang -o prog main.o a.o c.o`



# Symbols

Symbols have

- a name — the identifier used in the program); and
- a value — an offset into a section (.text, .data, .bss, etc.)

```
$ readelf -s maze.o
```

Symbol table '.symtab' contains 59 entries:

Num:	Value	Size	Type	Bind	Vis	Ndx	Name
45:	00000000000000000000	0	NOTYPE	GLOBAL	DEFAULT	UND	free
46:	00000000000000000000	0	NOTYPE	GLOBAL	DEFAULT	UND	malloc
47:	000000000000000005e0	135	FUNC	GLOBAL	DEFAULT	2	maze_free
48:	00000000000000000700	143	FUNC	GLOBAL	DEFAULT	2	maze_get_cols

# Symbols

Symbols have

- a name — the identifier used in the program); and
- a value — an offset into a section (.text, .data, .bss, etc.)

UND is undefined  
2 is .text (in this case)

```
$ readelf -s maze.o
```

Symbol table '.symtab' contains 59 entries:

Num:	Value	Size	Type	Bind	Vis	Ndx	Name
45:	000000000000000000	0	NOTYPE	GLOBAL	DEFAULT	UND	free
46:	000000000000000000	0	NOTYPE	GLOBAL	DEFAULT	UND	malloc
47:	0000000000000005e0	135	FUNC	GLOBAL	DEFAULT	2	maze_free
48:	000000000000000700	143	FUNC	GLOBAL	DEFAULT	2	maze_get_cols

# Defined/undefined symbols

Defined symbols have a value relative to a section in the object file (or binary)

Undefined symbols are references to symbols defined in other object files (or dynamic libraries)

# Archive symbol table

Maps symbols to object files inside the archive

Created using the `s` option to `ar(1)` or the `ranlib(1)` tool

# Linking with static libraries

The linker maintains a list of currently undefined symbols, initially empty

For each input files (objects and archives) from left-to-right

- If it's an object file, add the contents and symbols to the program
  - Remove defined symbols from the undefined symbol list
  - Add new undefined symbols to the undefined symbol list
- If it's an archive, perform the following until no new object files are added
  - If any object file in the archive defines a symbol in the undefined symbol list, add the object file from the archive as above

Linkers add object files from archives that define currently undefined symbols in a loop.

`libex.a` contains `a.o` and `b.o`.

`prog` is linked as

```
$ gcc -o prog foo.o bar.o libex.a
```

	a.o	b.o	foo.o	bar.o
Defined symbols	fun1	fun2 bar	main foo	bar
Undefined symbols	malloc free bar		bar fun1	

Which object files are linked into `prog`?

A. `foo.o`, `bar.o`, `a.o`, and `b.o`

D. `foo.o`, `a.o`, and `b.o`

B. `foo.o`, `bar.o`, and `a.o`

E. `foo.o`, and `bar.o`

C. `foo.o`, `bar.o`, and `b.o`

Duplicate symbols are an error.

libex.a contains a.o and b.o.

libbar.a contains bar.o.

prog is linked as

```
$ gcc -o prog foo.o libex.a \
    libbar.a
```

	a.o	b.o	foo.o	bar.o
Defined symbols	fun1	fun2 bar	main foo	bar
Undefined symbols	malloc free bar		bar fun1	

Which object files are linked into prog?

A. foo.o, bar.o, a.o, and b.o

D. foo.o, a.o, and b.o

B. foo.o, bar.o, and a.o

E. Duplicate symbol error

C. foo.o, bar.o, and b.o

Duplicate symbols are an error.

libex.a contains a.o and b.o.

libbar.a contains bar.o.

prog is linked as

```
$ gcc -o prog foo.o libex.a bar.o
```

	a.o	b.o	foo.o	bar.o
Defined symbols	fun1	fun2 bar	main foo	bar
Undefined symbols	malloc free bar		bar fun1	

Which object files are linked into prog?

A. foo.o, bar.o, a.o, and b.o

D. foo.o, a.o, and b.o

B. foo.o, bar.o, and a.o

E. Duplicate symbol error

C. foo.o, bar.o, and b.o



# Moral of the story

Specify your static libraries at the end of the link line

# Dynamic libraries

Dynamic libraries are produced by the (program) linker and are combined at run time by the loader (dynamic linker)

We'll talk more about them next time!

# In-class exercise

<https://checkoway.net/teaching/cs241/2019-fall/exercises/Lecture-29.html>

Grab a laptop and a partner and try to get as much of that done as you can!