CS 241: Systems Programming Lecture 12. Bits and Bytes 1

Fall 2019 Prof. Stephen Checkoway

Computers use binary

Everything in a computer is stored and manipulated as a collection of bits

The bits mean something only in how they are used, not what they are

Example with 32-bits: 01000011010100110100001101001001

- As a integer: 1129530185
- As a (single-precision) floating point number: 211.262833
- As a sequence of four ASCII characters: CSCI
- As 32-bit x86 instructions:

```
inc ebx
push ebx
inc ebx
dec ecx
```

Given a decimal (base 10) number 1253₁₀

► 3 ones (10°)

- ► 3 ones (10°)
- ► 5 tens (10¹)

- ► 3 ones (10°)
- ► 5 tens (10¹)
- ► 2 hundreds (10²)

- ► 3 ones (10°)
- ► 5 tens (10¹)
- 2 hundreds (10²)
- ► 1 thousand (10³)

```
10<sup>3</sup> 10<sup>2</sup> 10<sup>1</sup> 10<sup>0</sup>
1 2 5 3
```

Only uses the digits 0-7

In C, literal starts with leading 0

Only uses the digits 0-7

In C, literal starts with leading 0

Given a octal (base 8) number 02345

- ► 5 ones (8°)
- ► 4 eights (8¹)
- 3 sixty-fours (8²)
- 2 five hundred twelves (83)

Only uses the digits 0-7

In C, literal starts with leading 0

Given a octal (base 8) number 02345

- ► 5 ones (8°)
- ► 4 eights (8¹)
- 3 sixty-fours (8²)
- 2 five hundred twelves (83)
 - 83828180345

Single place has values of 0-15

- ► Need digits larger than 9. Use A=10, B=11, ..., F=15
- In C, starts with a leading 0x or 0x

Single place has values of 0-15

- ► Need digits larger than 9. Use A=10, B=11, ..., F=15
- In C, starts with a leading 0x or 0x

Given a hexadecimal (base 16) number 0x04E5

- ► 5 ones (16°)
- ► 14 sixteens (16¹)
- 4 two hundred fifty-sixes (16²)
- ► 0 four thousand ninety-sixes (16³)

Single place has values of 0-15

- ► Need digits larger than 9. Use A=10, B=11, ..., F=15
- In C, starts with a leading 0x or 0x

Given a hexadecimal (base 16) number 0x04E5

- ► 5 ones (16°)
- ► 14 sixteens (16¹)
- 4 two hundred fifty-sixes (16²)
- ► 0 four thousand ninety-sixes (16³)
 - 16³ 16² 16¹ 16⁰

Single place has values of 0-15

- ► Need digits larger than 9. Use A=10, B=11, ..., F=15
- In C, starts with a leading 0x or 0x

Given a hexadecimal (base 16) number 0x04E5

- ► 5 ones (16°)
- ► 14 sixteens (16¹)
- 4 two hundred fifty-sixes (16²)
- ► 0 four thousand ninety-sixes (16³)

```
16<sup>3</sup>
16<sup>2</sup>
16<sup>1</sup>
16<sup>0</sup>
5
```

Only uses the digits 0 and 1

Only uses the digits 0 and 1

Given a binary number 0b000010011100101

```
► 1 2<sup>0</sup>, 0 2<sup>1</sup>, 1 2<sup>2</sup>, 0 2<sup>3</sup>
```

- ► 0 2⁴, 1 2⁵, 1 2⁶, 1 2⁷
- ► 0 28, 0 29, 1 2¹⁰, 0 2¹¹
- ► 0 2¹², 0 2¹³, 0 2¹⁴, 0 2¹⁵

Only uses the digits 0 and 1

Given a binary number 0b000010011100101

```
1 20, 0 21, 1 22, 0 23
0 24, 1 25, 1 26, 1 27
0 28, 0 29, 1 210, 0 211
0 212, 0 213, 0 214, 0 215
```

```
215..12 211..8 27..4 23..0
```

Only uses the digits 0 and 1

Given a binary number 0b000010011100101

```
1 20, 0 21, 1 22, 0 23
0 24, 1 25, 1 26, 1 27
0 28, 0 29, 1 210, 0 211
0 212, 0 213, 0 214, 0 215
215..12 211..8 27..4 23..0
0 0 0 0 0 1 1 1 0 0 1 0 1
```

```
\mathbf{1253} = 1*10^3 + 2*10^2 + 5*10^1 + 3*10^0 = 1253
```

```
► 1253 = 1*10^3 + 2*10^2 + 5*10^1 + 3*10^0 = 1253

► 02345 = 2*8^3 + 3*8^2 + 4*8^1 + 5*8^0 = 1253
```

```
► 1253 = 1*10^3 + 2*10^2 + 5*10^1 + 3*10^0 = 1253

► 02345 = 2*8^3 + 3*8^2 + 4*8^1 + 5*8^0 = 1253

► 0x04E5 = 0*16^3 + 4*16^2 + 14*16^1 + 5*16^0 = 1253
```

Multiply and sum up the digit * baseposition value

```
► 1253 = 1*10^3 + 2*10^2 + 5*10^1 + 3*10^0 = 1253

► 02345 = 2*8^3 + 3*8^2 + 4*8^1 + 5*8^0 = 1253

► 0x04E5 = 0*16^3 + 4*16^2 + 14*16^1 + 5*16^0 = 1253
```

 $blue{-}0b0000010011100101 = 1253$

Convert the octal value 031 to decimal

- A. 7
- B. 25
- C. 31
- D. 49
- E. 248

Hex	Binary	Hex	Binary
0	0000	8	1000
1	0001	9	1001
2	0010	A	1010
3	0011	В	1011
4	0100	C	1100
5	0101	D	1101
6	0110	E	1110
7	0111	F	1111

Just group digits by 4s starting with LSB

Hex	Binary	Hex	Binary
0	0000	8	1000
1	0001	9	1001
2	0010	A	1010
3	0011	В	1011
4	0100	C	1100
5	0101	D	1101
6	0110	E	1110
7	0111	F	1111

Just group digits by 4s starting with LSB

b 0b000010011100101

Hex	Binary	Hex	Binary
0	0000	8	1000
1	0001	9	1001
2	0010	A	1010
3	0011	В	1011
4	0100	C	1100
5	0101	D	1101
6	0110	Е	1110
7	0111	F	1111

Just group digits by 4s starting with LSB

- ► 0b000010011100101
- ► 0b 0000 0100 1110 0101

Hex	Binary	Hex	Binary
0	0000	8	1000
1	0001	9	1001
2	0010	A	1010
3	0011	В	1011
4	0100	C	1100
5	0101	D	1101
6	0110	E	1110
7	0111	F	1111

Just group digits by 4s starting with LSB

- ► 0b000010011100101
- ► 0b 0000 0100 1110 0101

Each block of 4 bits is 0–15

Hex	Binary	Hex	Binary
0	0000	8	1000
1	0001	9	1001
2	0010	A	1010
3	0011	В	1011
4	0100	C	1100
5	0101	D	1101
6	0110	E	1110
7	0111	F	1111

Just group digits by 4s starting with LSB

- b0b000010011100101
- ► 0b 0000 0100 1110 0101

Each block of 4 bits is 0–15

Replace each with a hex digit

Hex	Binary	Hex	Binary
0	0000	8	1000
1	0001	9	1001
2	0010	A	1010
3	0011	В	1011
4	0100	C	1100
5	0101	D	1101
6	0110	Ε	1110
7	0111	F	1111

Just group digits by 4s starting with LSB

- b0b000010011100101
- ► 0b 0000 0100 1110 0101

Each block of 4 bits is 0–15

- Replace each with a hex digit
- ► 0 4 E 5

Hex	Binary	Hex	Binary
0	0000	8	1000
1	0001	9	1001
2	0010	A	1010
3	0011	В	1011
4	0100	C	1100
5	0101	D	1101
6	0110	E	1110
7	0111	F	1111

Converting binary to hex

Just group digits by 4s starting with LSB

- ► 0b000010011100101
- ► 0b 0000 0100 1110 0101

Each block of 4 bits is 0–15

- Replace each with a hex digit
- ► 0 4 E 5
- ► 0x04E5

Hex	Binary	Hex	Binary
0	0000	8	1000
1	0001	9	1001
2	0010	A	1010
3	0011	В	1011
4	0100	C	1100
5	0101	D	1101
6	0110	E	1110
7	0111	F	1111

Octal	Binary
0	000
1	001
2	010
3	011
4	100
5	101
6	110
7	111

Just group digits by 3s starting with LSB

Octal	Binary
0	000
1	001
2	010
3	011
4	100
5	101
6	110
7	111

Just group digits by 3s starting with LSB

► 0b000010011100101

Octal	Binary
0	000
1	001
2	010
3	011
4	100
5	101
6	110
7	111

Just group digits by 3s starting with LSB

- b 0b000010011100101
- ► 0b 000 000 010 011 100 101

Octal	Binary
0	000
1	001
2	010
3	011
4	100
5	101
6	110
7	111

Just group digits by 3s starting with LSB

- b 0b000010011100101
- ► 0b 000 000 010 011 100 101

Each block of 3 bits is 0–7

Octal	Binary
0	000
1	001
2	010
3	011
4	100
5	101
6	110
7	111

Just group digits by 3s starting with LSB

- b0b000010011100101
- ► 0b 000 000 010 011 100 101

Each block of 3 bits is 0–7

Replace each with a octal digit

Octal	Binary
0	000
1	001
2	010
3	011
4	100
5	101
6	110
7	111

Just group digits by 3s starting with LSB

- b 0b000010011100101
- ► 0b 000 000 010 011 100 101

Each block of 3 bits is 0–7

- Replace each with a octal digit
- ► 0 0 2 3 4 5

Octal	Binary
0	000
1	001
2	010
3	011
4	100
5	101
6	110
7	111

Just group digits by 3s starting with LSB

- b 0b0000010011100101
- ► 0b 000 000 010 011 100 101

Each block of 3 bits is 0–7

- Replace each with a octal digit
- ► 0 0 2 3 4 5
- 0002345 (We prepended a 0 to denote octal)

Octal	Binary
0	000
1	001
2	010
3	011
4	100
5	101
6	110
7	111

Convert the 16-bit binary number 0b11001010_11111110 to hex.

(I added an underscore to separate the two groups of 8 bits to improve readability.)

- A. Oxbeef
- B. 0xCAFE
- C. OxDEAD
- D. 0xFACE
- E. OxFEED

Alternative view of hex/octal

Binary is a pain to read/work with

Consider a 64-bit number

so long it doesn't fit on one line!

Hex (and much less commonly octal) can be viewed as a much more compact way to represent binary numbers

Ox4c40d6b036c547b0

Converting hex/octal to binary

- 1. Take each hexadecimal (or octal) digit
- 2. Convert it into binary
 - 4 places hex (e.g., A becomes 1010)
 - 3 places octal (e.g., 6 becomes 110)
- 3. Group them together from LSB to MSB

Converting between Hex & Octal

- 1. Take hexadecimal number
- 2. Convert to binary
- 3. Regroup in clusters of 3 from LSB
- 4. Generate Octal digits
- 5. Use reverse process for Octal to Hex

Repeatedly divide by 2, recording remainders

Repeatedly divide by 2, recording remainders

Remainders form the binary number from least to most significant

Repeatedly divide by 2, recording remainders

Remainders form the binary number from least to most significant

Repeatedly divide by 2, recording remainders

Remainders form the binary number from least to most significant

$$\rightarrow$$
 39 / 2 = 19 r 1

Repeatedly divide by 2, recording remainders

Remainders form the binary number from least to most significant

- \rightarrow 39 / 2 = 19 r 1
- -19 / 2 = 9 r 1

Repeatedly divide by 2, recording remainders

Remainders form the binary number from least to most significant

- \rightarrow 39 / 2 = 19 r 1
- -19 / 2 = 9 r 1
- \rightarrow 9 / 2 = 4 r 1

Repeatedly divide by 2, recording remainders

Remainders form the binary number from least to most significant

- \rightarrow 39 / 2 = 19 r 1
- -19 / 2 = 9 r 1
- \rightarrow 9 / 2 = 4 r 1
- -4 / 2 = 2 r 0

Repeatedly divide by 2, recording remainders

Remainders form the binary number from least to most significant

- \rightarrow 39 / 2 = 19 r 1
- -19 / 2 = 9 r 1
- \rightarrow 9 / 2 = 4 r 1
- -4 / 2 = 2 r 0
- 2 / 2 = 1 r 0

Repeatedly divide by 2, recording remainders

Remainders form the binary number from least to most significant

- \rightarrow 39 / 2 = 19 r 1
- -19 / 2 = 9 r 1
- \rightarrow 9 / 2 = 4 r 1
- -4 / 2 = 2 r 0
- 2 / 2 = 1 r 0
- 1 / 2 = 0 r 1

Repeatedly divide by 2, recording remainders

Remainders form the binary number from least to most significant

- \rightarrow 39 / 2 = 19 r 1
- -19 / 2 = 9 r 1
- \rightarrow 9 / 2 = 4 r 1
- -4 / 2 = 2 r 0
- 2 / 2 = 1 r 0
- 1 / 2 = 0 r 1
- \rightarrow 39 = 0b100111

In-class exercise

https://checkoway.net/teaching/cs241/2019-fall/exercises/Lecture-12.html

Grab a laptop and a partner and try to get as much of that done as you can!