

Programming Abstractions

Lecture 25: MiniScheme G

Stephen Checkoway

Announcement

Homework 7 is now up on the website

- Use the same groups as before (this time, they should be created already)
- It's due on Dec. 17

Exam 2 is next week

- Monday, Dec. 13: Exam 2 review; come prepared with questions!
- Wednesday, Dec. 15: Exam 2, take home exam

Office hours

- Tomorrow at 13:30–14:30

Example: ((lambda (x y) (+ x y)) 3 5)

Parsing

Parse into an (app-exp **proc** **args**)

```
(app-exp (lambda-exp '(x y)
                     (app-exp (var-exp '+)
                              (list (var-exp 'x)
                                    (var-exp 'y))))
  (list (lit-exp 3)
        (lit-exp 5)))
```

Example: `((lambda (x y) (+ x y)) 3 5)`

Evaluating

```
(app-exp (lambda-exp '(x y)
                     (app-exp (var-exp '+)
                               (list (var-exp 'x)
                                     (var-exp 'y))))
  (list (lit-exp 3) (lit-exp 5)))
```

This is evaluated by calling `apply-proc` with the evaluated procedure and evaluated arguments

The **procedure** evaluates to

```
(closure '(x y)
  (app-exp (var-exp '+)
            (list (var-exp 'x) (var-exp 'y))))
e)
```

The **arguments** evaluate to `'(3 5)`

Example: `((lambda (x y) (+ x y)) 3 5)`

Evaluating

`apply-proc` will evaluate the closure

```
(closure '(x y)
  (app-exp (var-exp '+)
    (list (var-exp 'x) (var-exp 'y))))
e)
```

by calling `eval-exp` on the **body** in the environment $e[x \mapsto 3, y \mapsto 5]$

Since the body is an `app-exp`, it'll evaluate `(var-exp '+)` to get `(prim-proc '+)` and the arguments to get `'(3 5)`

Example 2

Parsing

Example 2

Parsing

What is the result of parsing this?

```
(let ([f (lambda (x) (* 2 x))])  
  (f 6))
```

Example 2

Parsing

What is the result of parsing this?

```
(let ([f (lambda (x) (* 2 x))] )  
      (f 6) )
```

```
(let-exp '(f)  
  (list (lambda-exp  
          '(x)  
          (app-exp (var-exp '*)  
                    (list (lit-exp 2) (var-exp 'x)))) )  
  (app-exp (var-exp 'f)  
            (list (lit-exp 6)))) )
```


Example 2

Evaluating

```
(let-exp ' (f)
  (list (lambda-exp
        ' (x)
        (app-exp (var-exp '*)
                  (list (lit-exp 2) (var-exp 'x))))))
(app-exp (var-exp 'f)
  (list (lit-exp 6))))
```

Evaluate the `let-exp` by extending the current environment `e` with `f` bound to the closure we get by evaluating the `lambda-exp` in environment `e`:

```
(closure ' (x)
  (app-exp (var-exp '*)
    (list (lit-exp 2) (var-exp 'x))))
e)
```

Example 2

Evaluating

With f bound to

```
(closure '(x)
  (app-exp (var-exp '* )
    (list (lit-exp 2) (var-exp 'x)))
  e)
```

we next evaluate the body of the let

```
(app-exp (var-exp 'f) (list (lit-exp 6)))
```

This will evaluate $(\text{var-exp } 'f)$, getting the closure above and evaluate the arguments getting $'(6)$

`apply-proc` will call `eval-exp` on the **body of the closure** and the extended environment $e[x \mapsto 6]$

set ! and begin expressions

MiniScheme G: set! and begin

$EXP \rightarrow$ number
| symbol
| (if $EXP\ EXP\ EXP$)
| (let ($LET-BINDINGS$) EXP)
| (lambda ($PARAMS$) EXP)
| (set! symbol EXP)
| (begin EXP^*)
| ($EXP\ EXP^*$)

$LET-BINDINGS \rightarrow LET-BINDING^*$

$LET-BINDING \rightarrow [\text{symbol } EXP]^*$

$PARAMS \rightarrow \text{symbol}^*$

parse into lit-exp
parse into var-exp
parse into ite-exp
parse into let-exp
parse into lambda-exp
parse into set-exp
parse into begin-exp
parse into app-exp

What is the value of

```
(let ([x 10])  
  (+ x  
     (let ([x 20])  
       x)  
     x))
```

This is the sum of 3 numbers

A. 30

B. 40

C. 50

D. 60

What is the value of

```
(let ([x 10])  
  (+ x  
     (begin  
       (set! x 20)  
       x)  
     x) )
```

This is the sum of 3 numbers

A. 30

B. 40

C. 50

D. 60

Assignments

Assignment expressions are different in nature than the functional parts of MiniScheme

The `set!` expression introduces mutable state into our language

We're going to use a Scheme `box` to model this state

Boxes in Scheme

box is a data type that holds a mutable value

- Constructor: `(box val)`
- Recognizer: `(box? obj)`
- Getter: `(unbox b)`
- Setter: `(set-box! b val)`

Example usage

We can create a box holding the value 275 with

```
(define b (box 275))
```

We can get the value in the box with `(unbox b)`

We can change the value in the box with `(set-box! b 572)`

If we use `(unbox b)` afterward, it'll return 572

This models the way variables work in non-functional languages

What does this code print out (ignoring line breaks) and why?

```
(define (f b)
  (displayln (unbox b))
  (set-box! b (* 2 (unbox b))))
(let ([x (box 5)])
  (f x)
  (f x)
  (displayln (unbox x)))
```

- A. 5 5 5 because each call to f creates a new box (pass by value)
- B. 10 10 5 because f doubles the value in the box b but box x contains 5
- C. 5 10 5 because box b is initialized with value 5 but is doubled by the first call to f
- D. 5 10 20 because b and x point to the same box whose value is doubled twice

Implementing set!

To implement set! in MiniScheme

- Change the environment so that *everything* in the environment is in a box
- When we evaluate a `var-exp`, we'll lookup the variable in the environment, unbox the result, and return it
- When we evaluate a set expression such as `(set! x 23)`, we'll lookup `x` in the environment to get its box and then set the value using `set-box!`

We can do this in four simple steps

Implementing set!

Step 1

We need to box every value in the environment

Find every place you extend the environment and replace each call

`(env syms vals old-env)`

with

`(env syms (map box vals) old-env)`

Implementing set!

Step 2

Do *not* change your env-lookup procedure

Do change the line in eval-exp that evaluates var-exp expressions to

```
[ (var-exp? tree) (unbox (env-lookup e (var-exp-sym tree))) ]
```

At this point, the interpreter should work exactly as it did before you introduced boxes!

Implementing set!

Step 3

Set expressions have the form `(set! sym exp)`

You need a new data type for these, I used `set-exp`

When parsing, put the unparsed symbol (i.e., `'x` rather than `(var-exp 'x)`) into the `set-exp` and the parsed expression `exp`

Implementing set!

Step 4

Inside eval-exp, you'll need some code

```
[ (set-exp? tree)
  (set-box! (env-lookup ...)
            (eval-exp ...)) ]
```

Let's make set! useful!

MiniScheme now has set! but it isn't of much use until we can execute a sequence of expressions like

```
(let ([x 0])  
  (begin  
    (set! x 23)  
    (+ x 5)))
```

In Racket, we don't need the begin, but we do in MiniScheme because our let expressions only have a single expression as a body

Parsing a begin expression

`(begin exp1 exp2 ... expn)`

You need a new data type to hold these

- Since begin creates a sequence of expressions, `begin-exp` is a good name

The expressions in `(begin exp1 exp2 ... expn)` are evaluated in order and the value of the expression is the value that results from evaluating `expn`. How should we implement evaluating all the expressions? Assume we have something like `(let ([exps (begin-exp-exps tree)]) ...)`.

- A. `(map eval-exp exps)`
- B. `(map (λ (exp) (eval-exp exp e)) exps)`
- C. `(foldr (λ (exp acc) (eval-exp exp e)) (void) exps)`
- D. `(foldl (λ (exp acc) (eval-exp exp e)) (void) exps)`
- E. More than one of the above

Evaluating a `begin` expression

```
(begin exp1 exp2 ... expn)
```

Evaluate each expression in turn, returning the final one

- You can create a helper function to do that, or you can use our old friend:
`foldl`
- My code looks something like

```
(foldl (λ (exp acc) (eval-exp exp e)) (void) ...)
```
- `(void)` returns, well, a void value which does nothing