

Lecture 08 – Format string vulnerabilities

Stephen Checkoway
Oberlin College

Goal

- Take control of the program (as usual)
- How?
 - Write4 (write 4 bytes to an arbitrary location)
 - Inject shellcode (or other exploits) into the process

What should we overwrite?

- Saved instruction pointer/return address (rip) on the stack
- Other pointers to code (we'll come back to this)

printf operation

- printf takes a format string and arguments
- printf copies the format string to its output, replacing conversion specifiers with values determined by the arguments
- Arguments are (normally) accessed one at a time, in turn
- Internally, printf keeps a pointer to the next argument to be converted by a conversion specifier
- Example: `printf("value = %d %c", 42, 'm');`
prints: value = 42 m

Common conversion specifiers

%c	Character	%s	String
%d, %i	Integer	%p	Pointer
%u	Unsigned integer	%%	Literal %
%x, %X	Hex	%n	Stores number of characters written
%e, %f,	Double		

printf family

- printf
- fprintf
- sprintf
- snprintf
- asprintf
- dprintf
- vprintf
- vfprintf
- vsprintf
- vsnprintf
- vasprintf
- vdprintf


These slides depict 32-bit x86

Key differences between x86-64 and x86 (for our purposes)

- Registers are 32 bits: eax, ebx, ecx, edx, edi, esi, ebp, esp
- Instruction pointer is 32-bits: eip
- Integers, longs, and pointers are 32 bits (ILP32 data model)
- Calling convention is that all arguments to functions are passed on the stack rather than the first six being passed in registers


The following slides use seip and sebp to mean the saved instruction pointer (eip) and frame pointer (ebp) on the stack

x86-64 is slightly more difficult to exploit due to addresses containing zeros; we'll return to this




The way snprintf() normally works

```
void foo(int w) {
    char buf[500];
    const char *ending = w==1? ":"s";
    sprintf(buf, 500, "Hello %d world%s",
            w, ending);
}
...
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {
    char buf[500];
    const char *ending = w==1? "" :"s";
    sprintf(buf, 500, "Hello %d world%s"
            w, ending);
}
...
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hellow%d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %dworld%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? ":"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




The way snprintf() normally works

```
void foo(int w) {  
    char buf[500];  
    const char *ending = w==1? "" :"s";  
    snprintf(buf, 500, "Hello %d world%s",  
             w, ending);  
}  
...  
foo(5);
```




Now with %n

```
void foo(int w) {  
    char buf[500];  
    int x;  
    snprintf(buf, 500, "Hellow%d world%n",  
             w, &x);  
}  
...  
foo(5);
```




Now with %n

```
void foo(int w) {  
    char buf[500];  
    int x;  
    snprintf(buf, 500, "Hello %d world%n",  
             w, &x);  
}  
...  
foo(5);
```




Now with %n

```
void foo(int w) {  
    char buf[500];  
    int x;  
    snprintf(buf, 500, "Hello %d\u0004world%n",  
             w, &x);  
}  
...  
foo(5);
```




Now with %n

```
void foo(int w) {  
    char buf[500];  
    int x;  
    snprintf(buf, 500, "Hello %d world%n",  
             w, &x);  
}  
...  
foo(5);
```




Now with %n

```
void foo(int w) {  
    char buf[500];  
    int x;  
    snprintf(buf, 500, "Hello %d world%n",  
             w, &x);  
}  
...  
foo(5);
```




Now with %n

```
void foo(int w) {  
    char buf[500];  
    int x;  
    snprintf(buf, 500, "Hello %d world%n",  
             w, &x);  
}  
...  
foo(5);
```




Attacker controlled format string

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("ZZZ%x%x%x%x");
```




Attacker controlled format string

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("ZZZZ%x%x%x%x");
```




Attacker controlled format string

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("ZZZZ%x%x%x%x");
```




Attacker controlled format string

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("ZZZZ%x%x%x%x");
```




Attacker controlled format string

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("ZZZZ%x%x%x%x");
```




Attacker controlled format string

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("ZZZZ%x%x%x%x" );
```




Attacker controlled format string

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("ZZZZ%x%x%x%x");
```




Attacker controlled format string

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("ZZZZ%x%x%x%x");
```




Attacker controlled format string

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("ZZZZ%x%x%x%x");
```




Overwriting seip

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("\xe6\xff\xff\xbf%*x*x*x*x*n");
```




Overwriting seip

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("\xe6\xff\xff\xbf%*x*x*x*x*n");
```




Overwriting seip

```
void foo(const char *evil) {  
    char buf[500];  
    snprintf(buf, 500, evil);  
}  
...  
foo("\xe6\xff\xff\xbf%*x*x*x*x%n");
```




Overwriting seip

```
void foo(const char *evil) {  
    char buf[500];  
    sprintf(buf, 500, evil);  
}  
...  
foo("\xe6\xff\xff\xbf%*%*%*%*n");
```



Overwriting seip

```
void foo(const char *evil) {  
    char buf[500];  
    sprintf(buf, 500, evil);  
}  
...  
foo("\xe6\xff\xff\xbf%*%*%*%*n");
```



Picking the bytes to write

- Use `%{len}x` to control the length of the output
 - E.g., `%100x` will write the next argument in hexadecimal using 100 characters
 - Note that smaller lengths than are required to print the number are ignored! E.g., `%2x` for the number `0x12345678` will still print 8 characters
- Use `%hn` to write just the least-significant byte of the length
 - I.e., it'll write the length modulo 256 to the byte in memory pointed to by the next argument

Almost putting it all together

```
evil = "<address>zzzz"  
      "<address+1>zzzz"  
      "<address+2>zzzz"  
      "<address+3>"  
      "%8x%8x...%8x"  
      "%<len>x%hhn"  
      "%<len>x%hhn"  
      "%<len>x%hhn"  
      "%<len>x%hhn";
```

By carefully picking the len values, one can write an arbitrary 4 bytes to an arbitrary address

Each address (which cannot contain 0 bytes!) is written to the buffer in little endian, separated by 4 arbitrary characters (I selected Z)

The %8x move the next argument pointer up the stack until it reaches 4 bytes below the buffer, writing 8 bytes each time

%<len>x will write the next argument in len bytes

%hhn will use the next argument, <address>, to store the length so far modulo 256 at address, this repeats for address+1, address+2, and address+3

Misaligned buf

- If buf is not 4-byte aligned, prepend 1, 2, or 3 characters to evil

x86 is great and all, but what about x86-64?

Bad news: Unlike 32-bit addresses, every x86-64 address you encounter contains 0 bytes

E.g., Here are some address ranges from the cat program

- stack addresses: 0x~~0000~~7fffffffde000–0x~~0000~~7fffffff000
- code addresses: 0x~~0000~~55555556000–0x~~0000~~5555555b000
- heap addresses: 0x~~0000~~55555560000–0x~~0000~~55555581000

We can't write addresses and then use them 😞

Sometimes we can make use of addresses already on the stack

Sometimes we can arrange for addresses to appear on the stack

- Only string operations like `strcpy()`/`strcat()` are the ones that cannot have 0 bytes
- Others, like `fgets()`, and `getline()` don't care about 0 bytes and only care about newline bytes (`0x0A`)
- Files read from disk, either using `read()` or `fread()` happily work with binary data and so can contain 0 bytes

One exploitation option

If the target program reads from an attacker-controlled file into a stack buffer, the attacker can put addresses in the file and they'll appear on the stack

An attacker-controlled format string (which could be from the same file or something else entirely) can use those addresses along with %hn to write bytes to memory at those addresses

More complicated exploits are possible making use of existing addresses on the stack without introducing new ones

Further simplifications

Conversion specifiers (like %d, %16lx, or %hhn) can reference arguments out of order with the syntax %{arg_num}\$d

E.g., %35\$16lx means to take argument 35 as a long (so 8 bytes on x86-64) and print it in 16 hexadecimal characters

We can use that to selectively print out words on the stack (this is *really* worth remembering)

%10\$231c will take the 10th argument and print it as a character in 231 bytes

This can often be easier to use than doing a bunch of %16lx to move the next argument pointer up the stack while writing 16 bytes each time

Advantages of format string exploits

No need to smash the stack (targeted write)

Avoids defenses such as stack canaries!

- Stack canary is a random word pushed onto the stack that is checked before the function returns


They can be used to read arbitrary locations on the stack (again, remember this!)

Stack Canaries

```
int bar(char *);  
char foo(void) {  
    char buf[100];  
    bar(buf);  
    return buf[0];  
}  
foo:  
    sub    rsp, 120  
    mov    rax, QWORD PTR fs:40  
    mov    QWORD PTR [rsp+104], rax  
    xor    eax, eax  
    mov    rdi, rsp  
    call   bar  
    movzx  eax, BYTE PTR [rsp]  
    mov    rdx, QWORD PTR [rsp+104]  
    sub    rdx, QWORD PTR fs:40  
    jne    .L5  
    add    rsp, 120  
    ret  
.L5:  
    call   __stack_chk_fail
```

fs is a segment register which, on x86-64 is essentially just a (complicated) pointer

fs:40 means take the value 40 bytes from the start of the fs segment



Disadvantages of format string exploits

Format string vulnerabilities are *very* easy for the compiler to spot and warn about which makes them comparatively rare relative to other vulnerabilities

- \$ gcc -Wformat=2 f.c
f.c: In function ‘main’:
f.c:5: warning: format not a string literal and no format arguments

x86-64 makes format string exploits tricky to write, especially if you don't have the ability to put arbitrary data containing 0s on the stack

What else can we overwrite?

- Function pointers
- C++ vtables
- Global offset table (GOT)

Function pointers

```
#include <stdlib.h>
#include <stdio.h>

int compare(const void *a,
            const void *b) {
    const int *x = a;
    const int *y = b;
    return *x - *y;
}

int main() {
    int i;
    int arr[6] = {2, 1, 5, 13, 8, 4};
    qsort(arr, 6, 4, compare);
    for (i = 0; i < 6; ++i)
        printf("%d ", arr[i]);
    putchar('\n');
    return 0;
}
```

```
main:
...
    mov    rbx, rsp
    lea    rcx, compare[rip]
    mov    edx, 4
    mov    esi, 6
    mov    rdi, rbx
    call   qsort@PLT
...
qsort:
```

```
...
    call  rax
...
...
```

C++ Virtual function tables (vtable)

```
struct Foo {  
    Foo() {}  
    virtual ~Foo() {}  
    virtual void fun1() {}  
    virtual void fun2() {}  
};  
  
void bar(Foo &f) {  
    f.fun1();  
    f.fun2();  
}  
  
int main() {  
    Foo f;  
    bar(f);  
}
```

```
_Z3barR3Foo:  
    push    rbx  
    mov     rbx, rdi          // rbx = this  
    mov     rax, QWORD PTR [rdi] // rax = this->vptr  
    call    QWORD PTR [rax+16]  // call Foo::fun1(this)  
    mov     rax, QWORD PTR [rbx] // rax = this->vptr  
    mov     rdi, rbx           // rdi = this  
    call    QWORD PTR [rax+24]  // call Foo::fun2(this)  
    pop    rbx  
    ret
```

vptr points to vtable + 16

```
_ZTV3Foo:  
    .quad 0  
    .quad _ZTI3Foo  
    .quad _ZN3FooD1Ev  
    .quad _ZN3FooD0Ev  
    .quad _ZN3Foo4fun1Ev  
    .quad _ZN3Foo4fun2Ev  
  
// Demangled  
vtable for Foo:  
    .quad 0  
    .quad typeinfo for Foo  
    .quad Foo::~Foo()  
    .quad Foo::~Foo()  
    .quad Foo::fun1()  
    .quad Foo::fun2()
```

```
main:  
    sub    rsp, 24  
    lea    rax, vtable for Foo[rip+16]  
    mov    QWORD PTR [rsp+8], rax  
    lea    rdi, [rsp+8]  
    call   _Z3barR3Foo  
    mov    eax, 0  
    add    rsp, 24  
    ret
```

Stores the address of vtable + 16 in the vptr of the Foo object (which here is at rsp + 8)

Global Offset Table (GOT)

- Contains pointers to code and data in shared libraries
- Library functions aren't called directly; stub in the Procedure Linkage Table (PLT) called
- E.g., call exit -> call exit@plt
- exit@plt looks up the address of exit in the GOT and jumps to it (not the whole story)
- Overwrite function pointer in GOT