CSCI 210: Computer Organization Lecture 2: Assembly Language

Stephen Checkoway

Oberlin College

Feb 21, 2022

Slides by Cynthia Taylor

Announcements

- Problem set 0 due this Friday at 23:59
 - Access it via Gradescope (link on course website)


Selection	High Level Language	Assembly	Machine Language
Α	3	2	1
В	3	1	2
С	2	1	2
D	1	2	2
E	None of the above		


What Your CPU Understands

Electricity


Ones and zeros

Problem: People don't like writing programs in ones and zeros





Machine Interpretation



```
temp = v[k];

v[k] = v[k+1];

v[k+1] = temp;


Iw $15, 0($2)

Iw $16, 4($2)

sw $16, 0($2)

sw $15, 4($2)
```


Machine Interpretation



```
temp = v[k];
v[k] = v[k+1];
v[k+1] = temp;
```

```
Iw $15, 0($2)
Iw $16, 4($2)
sw $16, 0($2)
sw $15, 4($2)
```

Machine Interpretation




```
temp = v[k];

v[k] = v[k+1];

v[k+1] = temp;
```

Iw \$15, 0(\$2) Iw \$16, 4(\$2) sw \$16, 0(\$2) sw \$15, 4(\$2)

Machine Interpretation



Machine Interpretation


Machine Language

- Actual operations built into hardware.
 - Translated to electrical impulses

− 1: voltage > .5 V

0: voltage < .5V

 Provides direct access to CPU components.



CPU

- Central Processing Unit, or "chip"
- Performs operations by executing instructions

- Contains
 - Mechanism to perform arithmetic operations
 - Small amount of memory to hold inputs and outputs for these instructions

Registers

• (Very) Small amount of memory inside the CPU


Data is put into a register before it is used in an instruction

Manipulated data is then stored back in main memory.

Typical Machine Language Operations

- Load a word from memory into a register
- Store the contents of a register into a memory word
- Compute the sum (or difference) of two registers, store the result in a register
- Change which instruction runs next
- Change which instruction runs next based on a register value

Instruction Set Architecture (ISA)



- Abstracts from hardware (voltages) to machine language (1s & 0s)
- Encompasses all the information necessary to write a machine language program, including instructions, registers, memory access, ...
- The definition (specification) of the machine language for a particular CPU

Examples of ISAs

Intel x86, x86_64


MIPS

• ARM: A32 (32-bit ARM), A64 (64-bit ARM), T32 (Thumb)

Power ISA (PowerPC)

Which of the following statement is generally true about ISAs?

Select	Statement		
A	Many models of processors support exactly one ISA.		
В	An ISA is unique to one model of processor.		
С	Every processor supports multiple ISAs.		
D	Each processor manufacturer has its own unique ISA.		
E	None of the above		



```
temp = v[k];
v[k] = v[k+1];
v[k+1] = temp;
```

```
Iw $15, 0($2)
Iw $16, 4($2)
sw $16, 0($2)
sw $15, 4($2)
```

Machine Interpretation

Assembly Language

- Abstraction of machine language
 - From 1s & 0s to symbolic names


 Allows direct access to architectural features (registers, memory)

- Symbolic names are used for
 - operations (mnemonics)
 - memory locations (variables, branch labels)

C code
$$x = 4;$$

$$y = 5;$$

$$x = x + y;$$



10101100011000100000000000000100

Machine Interpretation

What are some advantages to a high-level language?



Rear Admiral Grace Hopper

- Invented the compiler
- Conceptualized machineindependent programming languages.
- Popularized term "debugging"

A single program written in a high-level language can be compiled into _____ assembly language programs

A. Exactly one

B. Multiple

C. At most three

A single program written in assembly can be assembled into ____ machine language programs


A. Exactly one

B. Multiple

C. At most two


High-level language program (in C)

```
swap (int v[], int k)
(int temp;
    temp = v[k];
    v[k] = v[k+1];
    v[k+1] = temp;
)
```



Assembly language program (for MIPS)

```
swap: sll $2, $5, 2
add $2, $4, $2
lw $15, 0($2)
lw $16, 4($2)
sw $16, 0($2)
sw $15, 4($2)
jr $31
```



Machine (object, binary) code (for MIPS)

```
000000 00000 00101 000100001000000
000000 00100 00010 000100000100000
```

. . .

Reading

- Next lecture: Hardware!
 - Sections 1.5

Problem set 0 due Friday at 23:59