



What's Cooking

All Eatable

CS 412 : Introduction to Machine Learning

He Huang, Ye Liu, Lichao Sun
Zhu Wang, Congying Xia, Fan Zhu

Apr 27, 2017

Project Description

- Kaggle
- Goal
 - use recipe ingredients to predict the cuisine
- Data
 - Training data
 - 39774 recipes and 20 kinds of cuisines
 - Recipe id
 - type of cuisine
 - list of ingredients of each
 - Testing data
 - Recipe id
 - list of ingredients of each



Introduction

 This image cannot currently be displayed.


Italian (7838)

Mexican (6438)

Southern_US (4320)

Introduction

- Using K-means Clusters to visualize training dataset
 - Tf-idf : each term in gradients and cuisine as documents
 - PCA: reduced to 2-Dimensions
 - K-means cluster: $k = 5$
 - Size of bubbles: Jaccard Similarity(one v.s the other cuisines in its cluster)

 This image cannot currently be displayed.

Introduction

➤ Ingredients frequency more than 1000



Introduction

➤ Data representation

➤ Focus on *Italian* cuisine to show its ingredient network

➤ After removing stop-words, numbers and stemming



Methods


➤ Random Forest

➤ Naïve Bayes

➤ SVM


➤ LDA

➤ Neural Network


 This image cannot currently be displayed.

Random Forest

- Number of trees
 - Higher number of trees
 - Better performance
 - Lower speed




- Max_features
 - Sqrt -> $\sqrt{n_features}$
 - Log2 -> $\log_2(n_features)$
 - None -> $n_features$



Random Forest


➤ Min samples leaf

- The minimum number of samples required to split an internal node



➤ max_depth

- The maximum depth of the tree.
- If None, then nodes are expanded until all leaves are pure or until all leaves contain less than min_samples_split sample



Naïve Bayes

 This image cannot currently be displayed.

Using 5-fold cross-validation to tune smoothing parameter α , we got $\alpha=0.125$ to build model.

There are 20 classes and the areas of ROC curves are around 0.89 to 0.99.


	Accuracy	F-score(micro)	F-score(macro)
Train	0.826601	0.826601	0.788229
Test	0.762946	0.762946	0.685015

Linear SVM

➤ max_iter

➤ The maximum number of iterations to be run

Max_Iter	Train	Test
5	0.874827153	0.751194368
10	0.904431175	0.758109127
100	0.933312382	0.764018104
1000	0.933123821	0.764395273



Linear SVM

➤ C: Penalty parameter C of the error term.


C	Train	Test
0.5	0.9221873	0.7738245
1	0.9331238	0.7643952
2	0.9403834	0.7523259

➤ Loss: 'hinge' or 'squared_hinge'

loss	Train	Test
hing	0.9085167	0.7725672
squared_hing	0.9331238	0.7643953


Linear SVM

➤ Roc Curve



Latent Dirichlet Allocation


Unsupervised learning



- Randomly generate the topic distribution θ_i of document i from dirichlet distribution with α
- Randomly sample the topic of word j in the document i $z_{i,j}$ from the topic polynomial distribution θ_i
- Dirichlet distribution with β to randomly generate the vocabulary distribution $\varphi_{z_{i,j}}$ of topic $z_{i,j}$
- From vocabulary with polynomial distribution $\varphi_{z_{i,j}}$ to randomly sample the final word $w_{i,j}$

LDA

➤ Most probable words in four of the topics:



Topic 0	Topic 5	Topic 9	Topic 14
Sour cream	salt	salt	butter
Chili powder	All-purpose flour	Garlic cloves	salt
salsa	Baking powder	Cooking spray	eggs
Black beans	sugar	Olive oil	sugar
Flour tortillas	Large eggs	Chopped onion	milk

LDA

➤ Most probable words in four of the topics:

 This image cannot currently be displayed.

LDA


➤ Most probable topics in five of the docs:



LDA + KNN

➤ Unsupervised -> Supervised

Neural Network

 This image cannot currently be displayed.

4th hidden Layer

3rd hidden Layer

2nd hidden Layer


1st hidden Layer

 This image cannot currently be displayed.

Results of Neural Network

Batch-norm with Dropout

	Accuracy	Loss
Train	0.987010	0.043150
Test	0.789090	1.269093

 This image cannot currently be displayed.

Results of Neural Network

No Batch-norm but
with Dropout

	Accuracy	Loss
Train	0.780003	0.726374
Test	0.741327	0.855012

 This image cannot currently be displayed.

Results of Neural Network

Batch-norm without Dropout

	Accuracy	Loss
Train	0.999609	0.001691
Test	0.754651	1.096316

 This image cannot currently be displayed.


Comparison on the effects of Batch-norm and Dropout

Batch Normalization	Dropout	Train Accuracy	Test Accuracy
Yes	Yes	0.987010	0.789090
No	Yes	0.780003	0.741327
Yes	No	0.999609	0.754651
No	No	0.999497	0.746858

Batch-norm:
faster convergence

Dropout:
reduce over-fitting

Comparison



Fin

Thank you for your Attention