

Object Meets Function

The Power of HoF

Steven Lolong

`steven.lolong(at)uni-tuebingen.de`

**Programming Language Research Group
Tuebingen University**

Nov. 23, 2022



The Power of HoF

- 1 Map
- 2 Filter

- 3 Fold
- 4 Zip



Mapping [Functor]

Borrow the concept from category theory

A **Functor** is a mapping between categories.

A **Category** is a collection of "object" that are linked by "arrow".

One of a good resources: **Bartosz Milewski. Category Theory for Programmers.**

A functor is simply a container. Given a container, and a function which works on the elements, we can apply that function to each element (wiki.haskell.org).



Mapping [Functor]

fmap : **(object-A) (fArrow) => object-B**

object-A the source object.

fArrow the function that will map the data of source object (object-A) to become a new data of target object (object-B).

object-B the target object.



Mapping [Functor]

Let's do it!

```
1 def fMap(dList: List[Int])(f0ptr:(Int) => Int) : List[Int] =  
    dList match  
2   case Nil => Nil  
3   case (x :: xs) => f0ptr(x) :: fMap(xs)(f0ptr)  
4  
5 val exList = List(1,2,3,4,5)  
6  
7 fMap(exList)((a) => a + 2)
```

Listing: FMap - Example1



Mapping [Functor]

Let's do it!

How about if the object's type is varied.



Mapping [Functor]

Let's do it!

```
1 def fMapTP1 [A](dList: List[A]) (fOptpr: A => A) : List[A] =  
    dList match  
2   case Nil => Nil  
3   case (x :: xs) => fOptpr(x) :: fMapTP1(xs)(fOptpr)
```

Listing: FMap - Example2



Mapping [Functor]

Let's do it!

How about if the source object's type is different with the target object's type.



Mapping [Functor]

Let's do it!

```
1 def fMapTP [A,B](dList: List[A]) (fOptr: A => B) : List[B] =  
  dList match  
2   case Nil => Nil  
3   case (x :: xs) => fOptr(x) :: fMapTP(xs)(fOptr)
```

Listing: FMap - Example3



Filter

Select a specific member in the object that satisfies the rule.



Filter

filter:(**object-A**)(fRule: Boolean) => **object-B**



Filter

```
1 def filter (dList: List[Int])(fFilter: Int => Boolean) :  
  List[Int] = dList match  
2   case Nil => Nil  
3   case (x :: xs) => fFilter(x) match  
4     case true => x :: filter(xs)(fFilter)  
5     case false => filter(xs)(fFilter)  
6  
7 val exList = List(1,2,3,4,5,6)  
8  
9 val dEven = filter(exList)((a) => (a % 2) match  
10   case 0 => true  
11   case _ => false)
```

Listing: Filter - Example1



Filter

```
1 def filterTP [A](dList: List[A]) (fFilter: (A) => Boolean) :  
  List[A] = dList match  
2   case Nil => Nil  
3   case (x :: xs) => fFilter(x) match  
4     case true => x :: filterTP(xs)(fFilter)  
5     case false => filterTP(xs)(fFilter)
```

Listing: Filter - Example2



Fold

Fold (Reduce) is a family of higher order functions that process a data structure in some order and build a return value.



Fold

Right

foldr: **(object-A)(reducer: A => B) => object-B**



Fold

Right

```
1 def rFold(dList: List[Int])(dIdent: Int)(f: (a:Int, b:Int) =  
  > Int) : Int = dList match  
2   case Nil => dIdent  
3   case (x :: xs) => f(x, rFold(xs)(dIdent)(f))  
4  
5 val exList = List(1,2,3,4,5)  
6  
7 rFold(exList)(0)(_ + _)
```

Listing: Foldr - Example1



Fold

Right

```
1 def rFoldTV1 [A](dList: List[A])(dIdent: A) (f: (A, A) => A)
   : A = dList match
2   case Nil => dIdent
3   case (x :: xs) => f(x, rFoldTV1(xs)(dIdent)(f))
```

Listing: Foldr - Example2



Fold

Right

```
1 def rFoldTV2 [A,B](dList: List[A])(dIdent: B) (f: (A, B) =>
   B) : B = dList match
2   case Nil => dIdent
3   case (x :: xs) => f(x, rFoldTV2(xs)(dIdent)(f))
```

Listing: Foldr - Example3



Fold

Left

```
1 def lFold(dList : List[Int])(accu: Int)(f: (Int, Int) =>
  Int) : Int = dList match
2   case Nil => accu
3   case (x :: xs) => lFold (xs) (f(x, accu)) (f)
4
5 val exList = List(1,2,3,4)
6
7 lFold (exList)(0)(_ + _)
8
9 // Build factorial function base on lFold
10 val factorialFunc = (a: Int) => a match
11   case x if x <= 1 => 1
12   case _ => lFold(List.range(1,(a + 1)))(1)(_ * _)
```

Listing: Foldl - Example1



Fold

Left

```
1  case x if x <= 1 => 1
2  case _ => lFold(List.range(1,(a + 1)))(1)(_ * _)
```

Listing: Foldl - Example2



Fold

Left

```
1 def lFoldTV1[A](dList: List[A])(accu1: A)(f: (A,A) => A) : A
   = dList match
2   case Nil => accu1
3   case (x :: xs) => lFoldTV1(xs)(f(accu1,x))(f)
```

Listing: Foldl - Example3



Zip

Zip is a function that combines two objects into one.



Fold

Left

```
1 def zipIt[A,B](a: List[A])(b: List[B]) : List[(A,B)] = (a,b)
   match
2   case (Nil, _) => Nil
3   case (_, Nil) => Nil
4   case ((x :: xs), (y :: ys)) => (x,y) :: zipIt(xs)(ys)
5
6 val listA = List.range(1,5)
7 val listB = List.range(4,7)
8
9 zipIt[Int,Int] (listA)(listB)
10
11
12 zipIt (listA)(listB)
```

Listing: Zip - Example1

