Web Programming with The Laravel Framework

#4 - Model-View-Controller (MVC)

Steven Lolong

steven.lolong@uni-tuebingen.de

Programming Language Research Group
Tuebingen University

4 May 2022



Spaghetti Code

Spaghetti Code means mix all code in one page

```
<?php
  session_start();
 // act as persistence
  $uName = "gerald";
  // this is hash of "007" using md5;
  $uPass = "9e94b15ed312fa42232fd87a55db0d39";
  if(isset($_SESSION['login']) && ($_SESSION['login'] == true)
      ) {
    if(isset($_POST['logout'])){
9
      session_destroy();
10
      header('Location: #');
    }else{
12
    ?>
  <html>
    <head>
      <title>Welcome</title>
    </head>
```

Listing: Form in login page - mvc/spaghetti.php

Eberhard Karls
UNIVERSITÄT
TÜBINGEN

Spaghetti Code (cont.)

```
<body>
18
    < h2 > Welcome < / h2 >
19
20
    <form action="#" method="post" target="_self">
      <fieldset>
21
22
         <legend>User</legend>
         <input type="hidden" name="logout">
23.
         <input type="submit" value="Logout">
24
      </fieldset>
25
    </form>
26
    </body>
  </html>
  <?php
30
  }else{
    if(isset($_POST["uName"]) && isset($_POST["uPassw"])){
      if(($_POST["uName"] == $uName) && (md5($_POST["uPassw"])
       == $uPass)){
         $_SESSION['login'] = true;
34
```

Listing: Form in login page - mvc/spaghetti.php



Spaghetti Code (cont.)

```
header("Location: #");
35
36
37
    ?>
38
39
  <html>
    <head>
41
      <title>Login</title>
42
    </head>
43
    <body>
    <h2>The Witcher</h2>
45
    <form action="#" method="post" target="_self">
46
      <fieldset>
47
         <legend>Login</legend>
         <label for="uNameId">Username:</label>
         <input type="text" id="uNameId" name="uName"><br><br>
         <label for="passwId">Password:</label>
```

Listing: Form in login page - mvc/spaghetti.php



Spaghetti Code (cont.)

Listing: Form in login page - mvc/spaghetti.php



5/13


MVC

MVC, is a pattern in software design that split the code and group it into:

- Model (M), business logic and manages data.
- View (V), handles layout and display.
- **Controller**, routes commands to the model and view parts.



How it works





How it works

- Request from user, ex. sending information view web-form, triger view link or address to controller.
- 2 Processing data in controller.
- 3 C-Request, it can be get or update data.
- 4 M-Process, processing C-Request in model.
- M-Response, sending information to controller.
- 6 C-Process, processing information.
- 7 C-Update, update view.
- 8 V-Response, display UI to user.



MVC 00000000

Splitting the Code

Let's design the application using the MVC pattern by splitting the code *mvc/spaghetti.php* into:

- 1 controller.php
- 2 model.php
- 3 view_login.html
- view_logged_in.html



Controller

```
<?php
  require_once "model.php";
if(isset($_SESSION['login']) && ($_SESSION['login'] == true)
      ) {
    if(isset($_POST['logout'])){
      session_destroy();
      header('Location: #');
    }else{
7
8
      $uNameLogin = "Gerald";
      require_once "view_logged_in.html";
9
  }else{
    if(isset($_POST["uName"]) && isset($_POST["uPassw"])){
12
      if(checkUser($_POST["uName"], $_POST["uPassw"])){
13
        $_SESSION['login'] = true;
14
        header("Location: #");
15
16
    require_once "view_login.html";
19
20
```

UNIVERSITA TÜBINGEN

10 / 13

Listing: controller - mvc/controller.php

Model

```
<?php
  session_start();
  function checkUser($uname, $upass){
    // act as persistence
    $uName = "gerald";
    // this is hash of "007" using md5;
    $uPass = "9e94b15ed312fa42232fd87a55db0d39";
8
9
    $check = false;
10
    if((\$uname == \$uName) \&\& (md5(\$upass) == \$uPass)){}
12
      $check = true;
13
14
    return $check;
  ?>
```

Listing: model - mvc/model.php



View - Login

```
<ht.ml>
  <head>
    <title>Login</title>
  </head>
  <body>
    <h2>The Witcher</h2>
8
9
    <form action="#" method="post" target="_self">
      <fieldset>
10
11
        <legend>Login</legend>
        <label for="uNameId">Username:</label>
12
        <input type="text" id="uNameId" name="uName"><br><br>
13
        <label for="passwId">Password:</label>
14
15
        <input type="password" id="passwId" name="uPassw"><br>
        <input type="submit" value="Login">
16
      </fieldset>
    </form>
18
  </body>
20
  </html>
```

Listing: view – mvc/view login.php



View - Logged In

```
<html>
  <head>
    <title>Welcome</title>
  </head>
6
  <body>
    <h2>Welcome,
8
      <?php echo $uNameLogin ; ?>
9
    </h2>
10
    <form action="#" method="post" target="_self">
      <fieldset>
12
         <legend>User</legend>
13
         <input type="hidden" name="logout">
14
         <input type="submit" value="Logout">
      </fieldset>
16
    </form>
  </body>
19
  </html>
```

Listing: view - mvc/view logged in.php

Eberhard Karls Universität Tübingen