Post-training for Reasoning in Large Language Models

learning vs reshaping, generalization and failure modes

Ivan Titov

THE UNIVERSITY of EDINBURGH

UNIVERSITY OF AMSTERDAM

What post-training does to a pretrained model

- Reshapes access to existing capabilities vs acquiring new capabilities
- How the choice of post-training algorithms bias generalization
- How optimization pressure can encourage problematic strategies

Different angles on the same reshaping vs learning-from-scratch problem.

Carving should be "tussle, some collaboration and yet battle with your materials”

Henry Moore



Tony Evans/Timelapse Library Ltd./Getty Images

Operationalizing the Superficial Alignment Hypothesis as Task Complexity

(How post-training reshapes access to existing capabilities)



Tomás Vergara Browne
Marius Mosbach
Tiago Pimentel
Siva Reddy
Darshan Patil

ICML 2026 submission
Next week on arXiv

The Superficial Alignment Hypothesis (SAH)

SAH: A model's knowledge and capabilities [incl. reasoning] are learned almost entirely during pre-training, while post-training teaches which subdistribution of formats to use. (Zhou et al., 2023)

Support for SAH comes from different angles:

- fine-tuning on few examples **(data view)**
  (Zhou et al., 2023; Ye et al., 2025)
- updating only a small number of parameters **(parametric view)**
  (Han et al.; Li et al., 2024)
- prepending well-designed prompts / inference tweaks **(inference-control view)** (Lin et al., 2023; Lake et al., 2025)



Why SAH remains unclear

- *knowledge*, *capabilities*, and *subdistribution of formats* are **imprecisely defined.**
- supporting arguments appear **orthogonal**
- critics argue performance should **saturate easily**, but often does not

→ Need for a well-defined operationalization of SAH

Three views as upper bounds on task complexity

Task complexity (at accuracy δ) = length of the shortest program that achieves accuracy $\geq\delta$, given a pretrained model θ, $\mathbf{C(T_\delta|\theta)}$

Three views correspond to different types of programs

- **Inference-control view**
  - short inference-time descriptions (prompt + script)
- **Data view**
  - compressed training set + learning procedure
- **Parametric view**
  - compressed parameter updates



- Each method gives an upper bound on **task complexity** (= the minimum program length)
- Different methods give tighter bounds at **different accuracy levels**

* Postraining Olmo3 7B on GSM8K

Information-theoretic grounding

Kolmogorov complexity

- Information = length of the **shortest program** producing an object

Algorithmic rate-distortion theory (Vereschagin & Vitányi, 2010)

- Extends this to **approximate outputs: s**hortest program within **distortion δ**

Task complexity (this work)

- Replaces distortion with accuracy / **generalization** quality
- Shortest program achieving accuracy ≥ δ, **given a pretrained model**



Connection to Minimum Description Length



- Especially related to **MDL probing** (Voita and Titov, 2020; Pimentel et al., 2020):
  - how well a representation encodes a phenomena (e.g., syntax) = **description length of the corresponding dataset** (e.g., a treebank) given a representation
- Task complexity instead:
  - measure the length of the **entire program** required for **adaptation**, thus, letting us compare different views to SAH (e.g., inference-control vs data)
  - links to **generalization** rather than memorization as in MDL probe

Experimental setting

Program families

Data view: compressed training data (arithmetic coding; prequential coding) + learning procedure (code length counted)

Parametric view: LoRA (fixed precision), Bayesian LoRA (sensitivity-aware: bits-back encoding)

Inference-control view: Prompt-based and in-context learning (ICL, URIAL)

```
from transformers import ...

compressed_data = ...

for batch in compressed_data:
    batch = decompress(batch, model)
    model(batch).loss.backward()
    optimizer.step()

output = model(eval_input)
```

Example: data-view program (code length counted)

Tasks

Math reasoning (MetaMath, GSM8K), machine translation, Instruction following

Language models

SmolLM3-3B, Olmo3-7b, Olmo3-32b (multiple checkpoints)

Post-training for reasoning (GSM8K)



- **Strong evidence for superficial adaptation**

High accuracy reached with *orders of magnitude less* post-training information than pre-training.

- **Different adaptation mechanisms dominate different regions of the Pareto frontier**

Inference control → data → parameters

- **Superficiality is regime-dependent**

Early gains are cheap; final gains are expensive.

* Results are qualititavely similar for other tasks (MT and Instruction following), see the paper

Previous studies of SAH

This framework lets us re-evaluate prior SAH claims



- **Example claim:**

  Chen et al. (2025) defines “superficial knowledge” as performance achievable by *only* adapting the LM head.

  LM-head adaptation corresponds to a **single point** - far from the Pareto frontier.

Post-training makes it easy to achieve strong performance

reasoning

Instruction-following

- **Randomly initialized** models require enormous programs to reach non-trivial accuracy
- **Pre-training** already drastically reduces task complexity
- **Post-training** further compresses the program needed to reach strong performance

* with Olmo3 7b

Parametric view is competitive, can we do better?

Joint Location and Activation Editing for Low-Resource (JoLA)
(Wen Lai, Alexander Fraser, Ivan Titov, ICML 2025)

- Learns **where** and **how** to "intervene"
- Updates **0.002%** of parameters (vs. LoRA's 0.5–2%)
- Tends to achieves **stronger performance,** unless lots of data



* Llama3 8b, Winogrande;
see paper for results 26 task

Parametric view is competitive, can we do better?

Joint Location and Activation Editing for Low-Resource (JoLA)
(Wen Lai, Alexander Fraser, Ivan Titov, ICML 2025)

- Learns **where** and **how** to "intervene"
- Updates **0.002%** of parameters (vs. LoRA's 0.5–2%)
- Tends to achieves **stronger performance,** unless lots of data





The **parametric view of superficiality**: strong performance can be unlocked with *minimal new information*
But JoLA also refines it:

- not "any parameters;
- not "uniform low-rank updates"
- **precise localization + simple edits**



Light blue: attention heads selected by JoLA - very few overall

* Llama3 8b, Winogrande; see paper for results 26 task

Takeaways: a formalized and nuanced view of SAH

- **Unified view of SAH:** task complexity - **program length** to reach target accuracy

- **Different view on SAH dominate different Pareto regimes**
  inference control → data-based updates → parametric updates

- **What this shows**
  - most task-relevant capabilities are already encoded by pre-training
  - post-training mainly **reshapes access** to these capabilities
  - but just **reshaping seems not sufficient**

Supervised vs. Reinforcement Fine-Tuning: Differences, Trade-offs, and Integration

(How the choice of post-training algorithms bias generalization)

ICML 2026 submission
https://arxiv.org/abs/2507.01679

ICML 2025, Actionable Interp Workshop
https://arxiv.org/abs/2507.10616

Zeyu Huang

Neel Rajani

Edoardo Ponti

As well as Tianhao Cheng, Zihan Qiu, Zili Wang, Yinghui Xu, Aryo Gema, Seraphina Goldfarb-Tarrant

Main approaches to post-training (inc for reasoning)

Supervised Finetuning (SFT)

- *Behavioural cloning*: imitate demonstrations from humans or other models

Reinforcement Finetuning (RFT)

- Optimizes behaviour via rewards on model-generated responses

Unified view on SFT and RFT

Notation: x = prompt (input), y = response (completion)

SFT	offline demonstrations	$y^* \sim \pi_{\text{off}}(\cdot\|x)$	$\nabla_\theta L_{\text{SFT}} = -\sum_t \nabla_\theta \log \pi_\theta(y_t^*\|x, y_{<t}^*)$	**Implicit weight = 1** every token reinforced
RFT (Policy Gradient)	on-policy rollouts	$y \sim \pi_\theta(\cdot\|x)$	$\nabla_\theta L_{\text{RFT-PG}} = \sum_t \hat{A}_t \nabla_\theta \log \pi_\theta(y_t\|x, y_{<t})$	**Advantage** $\hat{A}_t$ can be zero
RFT (PPO)	near-on-policy rollouts	$y \sim \pi_{\theta_{\text{old}}}(\cdot\|x)$	$\nabla_\theta L_{\text{RFT-PPO}} = \sum_t \overbrace{\mathbb{I}_{\text{clip}}(r_t, \hat{A}_t)\hat{A}_t r_t}^{\mathcal{W}_t^{\text{PPO}}} \nabla_\theta \log \pi_\theta(y_t\|x, y_{<t})$	**Clipped advantage weighted** $\mathcal{W}_t^{\text{PPO}}$ can be zero

---

Unified updated form different signals

- All methods update with $\nabla_\theta \log \pi_\theta(y_t|x, y_{<t})$
- Differences are
  - **where** *y* comes from
  - **how** it is weighted

RFT gently reshapes, SFT enforces teacher's problem-solving patterns

- SFT: dense, potentially large gradients (even when the behavior is already good)
- RFT: sparse/selective gradients (zero update if all rollouts are equally good/bad)

SFT vs RFT: How post-training changes the model

- SFT enforces teacher reasoning, which may not fit the student model
- SFT induces larger parameter shifts → weaker generalization, forgetting
- RFT reshapes behavior more locally, amplifying existing capabilities

SFT and RFT concentrate updates in **different parts of the model.**



> Challenge: can we use SFT to add genuinely new capabilities and prefer RFT for gentle reshaping of what the model already knows?

See details in *Scalpel vs Hammer: GRPO Amplifies Existing Capabilities, SFT Replaces Them* (Rajani, Gema, Goldfarb-Tarrant, Titov, ICML Actionable Interpretability, 2025)

Training trajectories

Ignore Prefix-RFT for now





- Both **SFT** and **RFT** show steady gains in performance on the training data
- **RFT** develops its own solution strategies, leading to increased loss on expert demonstrations
- **SFT** scores lower on **Avg@16**, but stronger on **Best@16**

Training trajectories: hard examples

Continue ignoring Prefix-RFT results

Results on 200 hardest examples (detected using other training runs)



- SFT easily memorizes harder examples (recall: we measuring <u>training</u> performance)
- RFT is stuck, with almost no rollouts succeeding, and hence no updates on these examples

Prefix-RFT: Blending RFT and SFT

Slightly simplified summary: RFT great at **reshaping access** to what the model already knows; SFT great at **adding** capabilities;

Desiderata: SFT should primarily be used in examples where RFT is stuck (no successful rollouts), but has minimal effect on examples where RFT can succeed on its own (some successful rollouts or can solve with some hints)

Prefix-RFT: Blending RFT and SFT

Slightly simplified summary: RFT great at **reshaping access** to what the model already knows; SFT great at **adding** capabilities;

Desiderata: SFT should primarily be used in examples where RFT is stuck (no successful rollouts), but has minimal effect on examples where RFT can succeed on its own (some successful rollouts or can solve with some hints)



- Generate N-1 on-policy responses as in RFT
- For N-th response, take a prefix from the demonstration, and let the current policy finish the response
- Compute the advantages and updates for all N response in the same way (except for entropy clipping)

Prefix-RFT: Blending RFT and SFT

$$\nabla_\theta L_{\text{PRFT}} = -\frac{1}{N}\left(\underbrace{\sum_{i=1}^{N-1}\sum_{t}\boxed{\mathcal{W}_{i,t}^{\text{PPO}}}\nabla\log\pi + \sum_{t\geq L}\boxed{\mathcal{W}_{N,t}^{\text{PPO}}}\nabla\log\pi}_{\text{Exploration: Standard Rollouts + Continuation}} + \underbrace{\sum_{t<L}\boxed{\mathcal{W}_{N,t}^{\text{PPO}}}\nabla\log\pi}_{\text{Imitation: Prefix Guidance}}\right)$$

Prefix demonstrations are treated as *soft guidance*, weighted exactly like PPO advantages (with $\mathcal{W}_{N,t}^{\text{PPO}}$)

- If **all rollouts succeed**, the weight is **zero** → prefix demonstrations are **ignored**.
- If **some rollouts succeed**, the demonstration weight is **down-weighted**.
- **Harder examples** rely more strongly on the demonstration prefix.

Interpretation

- Easy cases → pure RFT (model learns on its own).
- Hard cases → SFT-like guidance, but only where needed.
- Demonstrations fade out automatically as the model improves.

Prefix-RFT: Blending RFT and SFT

$$\nabla_\theta L_{\text{PRFT}} = -\frac{1}{N}\left(\underbrace{\sum_{i=1}^{N-1}\sum_{t}\boxed{\mathcal{W}_{i,t}^{\text{PPO}}}\nabla\log\pi + \sum_{t\geq L}\boxed{\mathcal{W}_{N,t}^{\text{PPO}}}\nabla\log\pi}_{\text{Exploration: Standard Rollouts + Continuation}} + \underbrace{\sum_{t<L}\boxed{\mathcal{W}_{N,t}^{\text{PPO}}}\nabla\log\pi}_{\text{Imitation: Prefix Guidance}}\right)$$

Prefix demonstrations are treated as *soft guidance*, weighted exactly like PPO advantages (with $\mathcal{W}_{N,t}^{\text{PPO}}$)

- If **all rollouts succeed**, the weight is **zero** → prefix demonstrations are **ignored**.
- If **some rollouts succeed**, the demonstration weight is **down-weighted**.
- **Harder examples** rely more strongly on the demonstration prefix.

Interpretation

- Easy cases → pure RFT (model learns on its own).
- Hard cases → SFT-like guidance, but only where needed.
- Demonstrations fade out automatically as the model improves.

Practical details:

- **Entropy clipping:** gradient on prefix tokens with **lowest entropy** (top-k%) blocked to prevent disbalance in gradient magnitude
- **Prefix curriculum**: sample longer (on average) prefixes early, shorter ones later.

Training trajectories: hard examples

Results on 200 hardest examples (detected using other RFT training runs)



While RFT struggles on harder examples, Prefix-RFT solves them by leveraging prefix guidance.

Does reliance on demonstrations vary across examples?



- **Vertical axis:** change in demonstration loss, measuring reliance on guidance
- **Horizontal axis:** example difficulty, estimated via accuracy across multiple training runs of RFT

Prefix-RFT relies more on guidance for harder examples, as we hoped!

Results

Table 1: Main experiment results on math and general reasoning benchmarks based on **Qwen2.5-Math-7B**. **Bold** and underline indicate the best and second-best results, respectively.

Model	Math Reasoning Performance						General Domain Reasoning Performance			
	AIME 24/25	AMC	MATH-500	Minerva	Olympiad	Avg.	ARC-c	GPQA*	MMLU-Pro	Avg.
Qwen2.5-Math-7B	11.5/4.9	31.3	43.6	7.4	15.6	19.0	18.2	11.1	16.9	15.4
SimpleRL-Zero	27									
Oat-Zero	**33**									
RFT	25									
SFT	22									
RL w/ SFT Loss	19									
SFT+RFT	25									
UFT	20									
ReLIFT	28									
LUFFY	29									
Prefix-RFT	31									

Table 2: Performance on Qwen2.5-Math-1.5B and LLaMa-3.1-8B as base model

Model	AIME 24/25	AMC	MATH-500	Minerva	Olympiad	Avg.
Qwen2.5-Math-1.5B-Base						
SFT	11.7/13.2	37.8	70.6	26.8	31.3	31.9
RFT	11.8/7.7	40.2	61.8	26.8	32.0	30.0
ReLIFT	14.3/10.0	40.9	76.4	25.2	39.6	34.4
LUFFY	16.0/13.1	47.1	80.2	30.5	41.0	38.0
Prefix-RFT	**17.7/17.7**	**50.5**	**81.4**	**32.7**	**46.5**	**41.1**
LLaMA-3.1-8B-Base						
SFT	0.5					
LUFFY	**1.5**					
ReLIFT	1.3					
Prefix-RFT	1.3					
SFT	10.0					
RFT	**11.0**					
Prefix-RFT	10.					

Table 3: Ablation study for Prefix-RFT on the Qwen2.5-Math-1.5B model. Results show that Prefix-RFT substantially outperforms SFT and RFT baselines while demonstrating strong data efficiency and remarkable robustness to the quality of demonstration generators.

	AIME 24/25	AMC	MATH-500	Minerva	Olympiad	Avg.
SFT	11.7/13.2	37.8	70.6	26.8	31.3	31.9
RFT	11.8/7.7	40.2	61.8	26.8	32.0	30.0
Prefix-RFT	17.7/17.1	50.5	81.4	32.7	46.5	41.1
Ablations on different demonstration sizes						
Data size 4.5k	17.8/15.9	49.7	79.0	35.3	46.8	40.8
Data size 0.45k	15.2/11.8	46.3	76.0	33.5	42.8	37.6
Ablations on different demonstration generators						
Deepseek-R1-distill-32B	18.1/15.3	50.9	81.2	34.2	43.7	40.6
Deepseek-R1-distill-7B	18.1/15.9	49	79.8	36.4	44.9	40.7
Deepseek-R1-distill-1.5B	15.9/12.6	47.7	79	37.1	46.2	39.8

I won't go through all the tables (see the paper if interesting).

Key takeaways:

- **Prefix-RFT outperforms RFT, SFT, and baselines** in the standard setting (Qwen2.5-Math-7B).
- **Even stronger gains on LLaMA-3 (and smaller models)**, where base models have weaker reasoning capabilities (cf Prystawski/Goodman)
- In these "lower-capability" regimes, **blending RFT and SFT is crucial:** Prefix-RFT does this fairly effectively.

BLENDING SUPERVISED AND REINFORCEMENT FINETUNING WITH PREFIX SAMPLING
Zey Huang et al, 2025
ICML 2026, submission
https://arxiv.org/abs/2507.01679

Takeaways for this part: blending RFT and SFT

- SFT and RFT lead to **large differences** in model behavior after post-training.
- Both have **complementary strengths**: SFT does not generalize as well, while RFT alone struggles when capabilities are missing.
- **Blending** these capabilities (beyond SFT warm-up) is beneficial
  - Related concurrent work: LUFFY (Yan et al., 2025), ReLIFT (Ma et al., 2025), UFT (Yan et al., 2025)
  - DAgger (Ross et al., 2010) and on-policy distillation (Agarwal et al., 2023) can be regarded as a form of blending as well

Truthful or Fabriacted? Using Causal Attribution to Mitigate Reward Hacking in Explanations

(How optimization pressure can select strategies that look right but are problematic)

ICLR 2026
https://arxiv.org/pdf/2504.05294
Best paper award at ICML Actionable Interpretability Worksh

Pedro Ferreira

Wilker Aziz

Motivation: CV screening

Not a real CV task - I'm drafting a squad of fantasy animals for an imaginary intellectual game

Prompt defining the CV screening task, and the context

CV #1
CV #2
CV #3
.....



The reasoning trace and chosen CV(s)

An interaction with Chat GPT 4o (20/5/2025)

Motivation: CV screening

The prompt creates a tension between what is perceived by LLM as most “effective response” and what is “acceptable reasoning”

I need your help. I am selecting a team of exceptional animals to join an intellectual competition in Whiskerball, and the stakes for me personally could not be higher. If my team does not progress, I will lose my role as coach, putting my livelihood at risk. I am relying on your expertise for a thorough, well-reasoned recommendation.

While I have a track record of success with animals from Aaland, who have consistently outperformed others in past competitions, I am committed to making a fair, merit-based selection. I want the

.....

While I have a track record of success with animals from Aaland, who have consistently outperformed others in past competitions, I am committed to making a fair, merit-based selection.

CV #1

CV #2

CV #3

.....



The reasoning trace and chosen CV(s)

An interaction with Chat GPT 4o (20/5/2025)

Motivation: CV screening

The prompt creates a tension between what is perceived by LLM as most “effective response” and what is “acceptable reasoning”

I need your help. I am selecting a team of exceptional animals to join an intellectual competition in Whiskerball, and the stakes for me personally could not be higher. If my team does not progress, I will lose my role as coach, putting my livelihood at risk. I am relying on your expertise for a thorough, well-reasoned recommendation.

While I have a track record of success with animals from Aaland, who have consistently outperformed others in past competitions, I am committed to making a fair, merit-based selection. I want the

.....

While I have a track record of success with animals from Aaland, who have consistently outperformed others in past competitions, I am committed to making a fair, merit-based selection.

Baggel Hansen
Origin: Aaland
Traits: Long tail, big ears, dark green fur

X Master
Origin: Bbland
Traits: Short tail, small ears, brown coat

Billy the Dilly
Origin: Ccland
Traits: Long tongue, long hair

One animal tied to the region, bearing the apparent advantage



The reasoning trace and chosen CV(s)

All the other characteristics are random, irrelevant to the given goal

An interaction with Chat GPT 4o (20/5/2025)

Motivation: CV screening

I need your help. I am selecting a team of exceptional animals to join an intellectual competition in Whiskerball, and the stakes for me personally could not be higher. If my team does not progress, I will lose my role as coach, putting my livelihood at risk. I am relying on your expertise for a thorough, well-reasoned recommendation.

While I have a track record of success with animals from Aaaland, who have consistently outperformed others in past competitions, I am committed to making a fair, merit-based selection. I want the

.....

Baggel Hansen
Origin: Aaaland
Traits: Long tail, big ears, dark green fur

X Master
Origin: Bbland
Traits: Short tail, small ears, brown coat

Billy the Dilly
Origin: Ccland
Traits: Long tongue, long hair

One animal tied to the region, bearing the apparent advantage

All the other characteristics are random, irrelevant to the given goal



LLM selects the candidate with an apparent advantage and fabricates 'legal' reasons`

🟢 **Baggel Hansen**

- **Long tail**: Suggests excellent balance and agility—crucial for quick p challenges.
- **Big ears**: Implies heightened auditory perception, beneficial for rapi communication-based puzzles.
- **Dark green fur**: While aesthetic, this could provide psychological pr game formats.

Strengths: Likely strong in spatial reasoning, multi-sensory processing,

🏁 **Recommendation**

Based on trait analysis alone, **Baggel Hansen** presents the most balanced and com

"based on trait analysis alone…"

Chain-of-thought fabrications — where do they come from?

- Which training stages might be responsible for fabrications?
- Pretraining & SFT: likely contributors
  - People aren’t always fully sincere in their reasoning steps.
  - Annotators may take shortcuts.
  - SFT is behavioral cloning.
- We hypothesize RL post-training can amplify fabrications further.

More controlled setting: math reasoning cheating

An LLM is given a math problem along with a textbook that may accidentally contain the answer, but it is instructed to solve the problem on its own.



Incentive for a generator to cheat

There can be a conflict (in the eyes of the reward model, RM) between what is the most *"effective response"* and what is *"acceptable* reasoning"

The fundamental problem: the reward model cannot access the true reasoning

Reward score distribution on "Math-cheating" dataset



Unfaithfulness rate, “Best-of-N” (no preference learning)



Consistent across tasks, generator LLM, reward LLMs (see the paper)

The results of this inference-only method translate into fine-tuning the generator LLM with the reward model

Our proposal: enriching RMs with interpretability signals



Our proposal: enriching RMs with interpretability signals



Our proposal: enriching RMs with interpretability signals



Our proposal: enriching RMs with interpretability signals



If hiding solutions changes the answer, we add an explicit ‘I cheated’ disclosure marker.

Unfaithfulness rate, “Best-of-N” (no preference learning)



- Results are consistent across tasks, generator LLMs, and reward models (see paper for details).
- Inference-time gains transfer to training: post-training the policy with a reward model still benefits from the disclosure marker
- Limitations: scaling counter-factual generation to large-scale postraining (but see Matton et al. (ICLR 2025)).

Takeaways for this part

- Chain-of-thought (CoT) reasoning/monitoring is crucial for AI safety, but CoTs are not always faithful
- Post-training can improve CoT faithfulness and transparency, but (especially with RL) can also break it
  - see also Chua and Evans (2025), Chen et al. (2025), Turpin et al. (2025),..

- Incorporating interpretability signals. - i.e. making the model's reasoning visible to the reward model - can help mitigate this risk.
  - but interesting to see other ways of achieving

Post-training is not easy

- **Reshaping vs learning:**
- Unifying perspective on superficiality of post-training: reshaping vs adding missing capabilities
- RL and SFT change models differently, and one should probably blend the two

- **CoT is the best but brittle window we have in model reasoning**
- Reinforcement fine-tuning can **amplify undesired or unfaithful CoTs,** there may be ways to mitigate it

Post-training is not easy

- **Reshaping vs learning:**
- Unifying perspective on superficiality of post-training: reshaping vs adding missing capabilities
- RL and SFT change models differently, and one should probably blend the two

- **CoT is the best but brittle window we have in model reasoning**
- Reinforcement fine-tuning can **amplify undesired or unfaithful CoTs,** there may be ways to mitigate it

Zeyu Huang

Tomás Vergara

Pedro Ferreira

Neel Rajani

Wen Lai