

TEACHING AND ANSWER GUIDANCE

BBQ Carry-All teacher guide

Read the answer as evidence of reasoning, with room for defensible alternatives.

Purpose

Use this workbook beside the existing course. The student reads, reasons and records evidence on paper while you supply demonstrations, actual school procedures and current task instructions. The activities are formative; this guide does not establish a new marking scheme.

Print and prepare

The student book contains 50 A4 pages, including the cover, contents and original plan. Print double-sided on the long edge for 25 sheets. Check the first duplex copy before a class run. No physical test print is claimed in the production record.

Authority and practical readiness

Use the unchanged original plan and written dimensions. Confirm current assessment dates and marks separately from retained historical records. Supply the applicable school SOPs, approved material/cutting information and relevant product or manufacturer instructions. Paper completion is not permission to operate equipment.

Using the answers

The answer guidance is keyed to the student page and prompt. Multiple-choice responses have one best answer; the explanations address the underlying reasoning. For open tasks, judge the stated evidence and reasoning, accepting valid alternatives. Do not require students to copy an indicative model word for word.

Teacher judgement

Check that photographs or records show the student's own actual work. A missing observation is a limitation to discuss, not a reason to invent a result. Illustrative artwork teaches recognition and comparison; it is not a construction plan or proof of safe performance.

PREPARATION AND TEACHING NOTES

Teaching modules 1–5

Prepare the actual source, sample or procedure before the linked lesson.

Module 1 • Brief, plans and workshop safety • pp. 4–7

Display the original drawing alongside an enlarged handle detail. Have students follow the extension lines: 178 mm is between rounded-end centres, not the total slot opening. Use the actual school SWMS to connect a hazard with possible harm and an effective control. Before cutting, check each student's source, component orientation, dimensions and unresolved questions; paper completion does not authorise practical work.

Module 2 • Materials, culture and responsible use • pp. 8–11

Prepare pine and plywood samples with visible end grain/layers plus stock containing a safely observable defect. Ask why each suits its component rather than teaching plywood as simply inferior timber. Introduce the supplied museum-linked Nyoongar kodj example with its attribution and bounded context. Check proposed component layouts for sound material, avoidable waste and justified source claims before students commit the actual stock.

Module 3 • Required construction and comparative joints • pp. 12–15

Use separate labelled box-pin, dovetail, rebate and housing samples or accurate images. Keep the first two visibly marked comparison knowledge and connect the required features to the unchanged working drawing. Ask students to explain how the removed material changes mating surfaces and alignment. Check the planned project joint and its written dimensions before marking; a stronger-looking comparison never authorises a substitute construction.

Module 4 • Accurate marking and hand-tool control • pp. 16–19

Prepare static examples of a reliable reference face/edge, paired component marks, clear waste marking and a mismatched datum. Demonstrate only the school's approved hand-tool method with its required support and control. Ask students to locate the cause of a repeating error before suggesting removal. Check datum consistency, actual marked relationships and waste side before the authorised cut, then preserve evidence of any approved correction.

Module 5 • Rebates, housings and dry assembly • pp. 20–23

Provide a base rebate sample, a housing sample and an approved dry assembly that makes their different functions visible. Compare an even seat with a hypothetical local obstruction; students should not assume every tight fit needs a wider recess. Before adhesive, inspect the whole structure for base seating, divider/handle location, closure, square and flatness. Diagnose the cause and approve a correction before students remove more material.

PREPARATION AND TEACHING NOTES

Teaching modules 6–10

Prepare the actual source, sample or procedure before the linked lesson.

Module 6 • Handle design, drawing and shaping • pp. 24–27

Prepare the original handle detail, aligned orthogonal views and a teacher-verified template. Revisit the 178 mm centre-to-centre dimension so students do not copy a resized print or label it as the overall opening. Discuss grip access, smooth edges and remaining material within the approved form. Check the drawing, template identity, orientation and written dimensions before any teacher-approved shaping operation.

Module 7 • Adhesive assembly and workshop care • pp. 28–31

Supply the actual approved adhesive label/SDS, a comparison product's reliable information where available, and the planned clamps/packing. Students compare suitability and requirements rather than ranking products by an unsupported strength claim. Rehearse the dry assembly and check clamp placement, square, access and clean-up arrangements before adhesive is issued. Use the tool-function map to check safe storage and fault reporting, not to infer unauthorised operation.

Module 8 • Handling, sequencing and surface preparation • pp. 32–35

Arrange a safe handover scenario using supported components and the school-approved handling process. Establish individual roles for the teacher-authorised collaborative task and require each student to identify what they made, checked and communicated. Use raking light and prepared sample surfaces to reveal scratches or glue residue. Check readiness and the next authorised step at handover; a completed role list alone proves neither workmanship nor safe sequencing.

Module 9 • Finish and final workmanship • pp. 36–39

Have the actual approved finish label/SDS and representative prepared/finished samples ready. Teach students to connect product choice with intended use and maintenance, then separate observed defects from possible causes. Confirm product-specific application, storage and waste arrangements locally. Inspect surface readiness and preserved edges before coating, and final fit/function as well as appearance afterwards; do not invent standard coat counts, drying times or a food-contact claim.

Module 10 • Evidence, problem solving and evaluation • pp. 40–43

Prepare one vague and one evidence-linked caption plus a hypothetical defect with more than one plausible cause. Require students to name the observation, checking source and approved response before claiming a diagnosis. Use PMI to examine function, workmanship, material use and process, with a defensible interesting point rather than compulsory praise. Check genuine evidence references, current hand-in requirements and a verified saved/exported copy before final submission.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 1 answers • 1

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 6 • The printed picture looks shorter than 400 mm. Explain why this is not evidence that the overall length has changed.

Printing, page fitting and screen zoom can change the displayed size. The written 400 mm overall dimension remains the source specification; students must not scale the drawing. A revised teacher-issued drawing or explicit teacher direction would be needed to establish an authorised change.

Student page 7 • 1. Which statement is an observable success criterion?

C. It identifies a specific feature and an observable relationship. The other statements are unsupported, comparative or unrelated to demonstrated function.

Student page 7 • 2. A dimension seems different after the page is printed smaller. What controls manufacture?

B. Written dimensions and their referenced features control the work; print or screen scale can change the apparent size.

Student page 7 • 3. Which SWMS entry best connects a control with its hazard?

D. It connects unstable work with a stage-specific physical control. The other options do not identify a usable control.

Student page 7 • Choose material handling, joint work or finishing. Identify one hazard, the possible harm and a relevant control to confirm with your teacher.

Accept a coherent stage–hazard–harm–control chain. Examples: awkward stock could strike someone, so assess the route and use the teacher-directed handling procedure; unstable joint work could slip, so use approved workholding; finish exposure requires product-specific controls from label/SDS and school procedures. Do not reward invented operating instructions.

Student page 44 • In your own words, describe the Carry-All's purpose and the required construction. Name the controlling source.

Expected: a practical timber carry-all/tray with handle and dividers; rebate-butt corners and housings where shown; original Carry-All Working Drawing and teacher directions as authority. Accept concise wording that recognises function and source control. Alternative box-pin/dovetail construction is not accepted.

Student page 44 • Set three observable criteria.

Accept three relevant observable criteria with feasible teacher-approved checks: complete joint seating, even base support, correct internal-part alignment, smooth handle edges, consistent finish or traceable stage evidence. Criteria must not invent tolerances, loads or formal marks. Vague “looks good” without a check needs refinement.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 1 answers • 2

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 44 • Record one requirement or decision that needs teacher confirmation before work proceeds.

Accept a real unresolved source, practical process, specification or approval question. The student should name the uncertainty and relevant stage. If nothing is currently unresolved, record the verified source and next hold point; do not invent a gap solely to fill the space.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 2 answers • 1

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 10 • Decide what each piece needs

Split: do not allocate that damaged area without teacher assessment; revise the layout or seek alternative stock. Sound useful off-cut: identify, protect and store for the approved purpose. Separating plywood edge: report and seek a suitable base/teacher decision; do not force defective sheet into the assembly.

Student page 10 • Write one specific piece of evidence that would support the claim “my layout reduced avoidable waste”.

Accept an annotated actual layout showing a defect avoided, several verified parts allocated efficiently, a useful off-cut retained, or a prevented recut. It must identify an observable decision and result, not merely repeat the claim. Hypothetical evidence must be labelled as such.

Student page 11 • 1. Why inspect the edges of the plywood as well as its faces?

A. Layer separation and edge damage can affect base condition and fit. Neither colour nor thickness establishes sustainability or water resistance.

Student page 11 • 2. Which statement treats First Nations knowledge respectfully?

C. It identifies a bounded source and acknowledges diversity. Public visibility alone is not permission to copy cultural expression.

Student page 11 • 3. What is the strongest basis for a sustainability claim?

B. Source evidence and observable practice can support a claim; appearance, price or one defect check cannot establish responsible sourcing.

Student page 11 • Sequence puzzle: A Store useful off-cuts; B Check requirements; C Inspect stock; D Propose and verify the layout. Write the most sensible order and explain why A comes after D.

B–C–D–A. Establish requirements, inspect available material, plan/verify the allocation, then identify and store genuine remaining off-cuts. Their usefulness depends on knowing what the full approved project still needs. Accept discussion that inspection and layout may iterate.

Student page 45 • Verified cutting-information record

The teacher checks the record against the original drawing and actual approved component schedule. It must identify the drawing's 12 mm pine components and 3 mm plywood base where applicable, record only verified sizes/quantities, and flag missing information. Do not treat the number of table rows as the number of required parts.

Student page 45 • Explain one decision about grain, defects or component placement. How does it protect quality and reduce avoidable waste?

Accept a specific proposed or observed layout decision, such as avoiding a split within the required part, allocating an inflexible larger component before smaller ones, or retaining a sound useful off-cut. Link the decision to component suitability and material use. Teacher approval is needed for stock near defects.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 2 answers • 2

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 45 • Investigate one First Nations timber-working tool using a teacher-approved, community-attributed public source. Record: source/authority; Nation or community and Country if supplied; tool/material; action and purpose; ICIP sharing limits; and one respectful Carry-All material-use lesson.

Require a specific, accurately attributed investigation, not a general sustainability statement. Check the source title/location and authority; Nation/community and Country where supplied; the named tool, its material, action and purpose; and the source-specific limits on sharing or reproduction. Accept a respectful Carry-All connection such as thoughtful material selection, repair or avoiding waste when supported by the source, without copying a cultural object or design. Public access is not permission to reproduce. Record absent details as not supplied or Teacher to confirm; do not invent Country, endorsement or permissions, or generalise one community example to all First Nations peoples.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 3 answers

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 14 • Explain how a housing helps locate a divider, then name a check that would reveal a housing on the wrong face.

The housing shoulders locate the divider laterally and its depth surface supports the seated edge. A dry fit compared with the original drawing and inside/reference marks shows whether the divider enters the correct face and aligns with matching components. Accept an accurate annotated explanation; do not accept appearance alone.

Student page 15 • 1. Which construction controls this Carry-All project?

B. The original working drawing and teacher-authorised pathway require rebate-and-housing construction. Box-pin and dovetail joints are comparison theory only.

Student page 15 • 2. What distinguishes a dovetail from a box-pin joint?

C. Sloping tails and matching pins distinguish a dovetail; a box-pin comparison has rectangular alternating pins and spaces. This recognition does not authorise either joint on the project.

Student page 15 • 3. A rebate fits neatly but was formed on the wrong face. What follows?

A. A feature must meet the required form, position and orientation. Stop and seek a teacher-approved diagnosis before any alteration.

Student page 15 • A classmate says, “The dovetail looks stronger, so I will use it on my Carry-All.” Write a reasoned reply.

Explain that the dovetail is useful comparative knowledge but the authorised Carry-All must follow the original rebate-and-housing drawing. Appearance or a general strength claim cannot change required construction. The next step is to identify the required corner on the plan and discuss any uncertainty with the teacher before marking stock.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 4 answers

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 18 • Match the observation to the check. Use each check once.

Answers in order: B, C, A. B checks the datum/tool setting for a shared error; C checks accumulated error from dependent marks; A checks orientation and inside/outside reference marks.

Student page 18 • Why should this check happen before cutting rather than after a dry fit?

An incorrect mark can be corrected before material is removed. Cutting from it may create an undersized part, misplaced recess or reversed component that requires teacher-directed repair or replacement and wastes material. A later dry fit remains important but cannot restore removed timber.

Student page 19 • 1. What is the chief benefit of a verified common datum?

D. Independent positions from the verified reference reduce accumulated marking error. The datum still needs checking and does not replace other controls.

Student page 19 • 2. The saw begins binding and leaving its intended path. What is the appropriate response?

B. Binding/wandering signals a problem in the setup or operation. More force can increase damage and reduce control.

Student page 19 • 3. Why remove only small amounts during an approved fitting correction?

A. Material removal is irreversible; small checked adjustments help avoid turning a tight fit into a loose one. Diagnosis and approval still matter.

Student page 19 • Explain how a loose housing could result from trying to fix a tight fit without diagnosing its cause.

If a local high spot, wrong orientation or angled entry causes binding, enlarging the entire housing removes sound material unnecessarily. The part may then move or misalign. A correct response identifies contact and orientation before a small approved correction.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 5 answers

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 22 • Why would immediately trimming the plywood be a weak diagnosis? Name one useful check first.

It assumes the base is the cause without testing alternatives and may permanently undersize sound material. Valid first checks include correct orientation, debris/high spots on support surfaces, rebate continuity, full joint seating or plywood damage, checked against the drawing with teacher guidance.

Student page 23 • 1. What does a rebate's depth surface primarily do for the base?

C. The depth surface supports the base while the shoulder helps locate its edge. The rebate does not replace all other structural relationships.

Student page 23 • 2. Why must matching housings be checked across the assembly?

A. Matching positions, reference faces and orientation allow internal parts to seat without twisting. The original drawing determines each required feature.

Student page 23 • 3. Which observation means a dry assembly needs investigation?

D. Requiring distortion is evidence of a mismatch, not a successful fit. Stop and diagnose under teacher guidance before adhesive.

Student page 23 • The corners appear square from above, but the assembly rocks on a flat surface. Explain what another view or check could reveal.

A view from above alone may miss twist, an uneven seat or a protruding/mis-seated component. Inspect from several viewpoints and use the teacher-approved reference surface and checks. Identify which contact changes; do not assume that squareness eliminates all distortion.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 6 answers • 1

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 26 • Why is “I measured the entire opening and got 178 mm” not the right verification of this dimension?

It measures a different feature. The original 178 mm dimension runs between the centres of the rounded ends; the overall opening includes the curved ends beyond those centres. Students should trace the extension lines and check the teacher-verified template rather than infer a new total manufacturing dimension.

Student page 27 • 1. What does the handle view’s 178 mm dimension describe?

C. The extension lines reference the centres of the rounded ends. It is not the total outside opening length.

Student page 27 • 2. What is the strongest reason to use centre marks during template transfer?

A. Centre/reference marks help locate and compare the intended shape, while size, identity and orientation still require verification.

Student page 27 • 3. One side of the opening is accidentally over-cut. What should happen next?

B. Further removal cannot restore the missing material and may weaken the panel. Diagnosis and an approved response come first.

Student page 27 • Explain why a comfortable-looking handle photograph cannot prove that the completed Carry-All is safe and functional.

A photograph cannot establish smooth touch surfaces, sound timber, secure housing connections, verified shape, alignment or behaviour in the teacher-directed functional check. It supports visual evidence but must be combined with appropriate inspection and original-plan comparison; no unapproved load test is justified.

Student page 47 • Sketch the handle panel’s front view. Show the centre line, rounded slot ends and the 178 mm centre-to-centre dimension with extension lines. This is a communication sketch, not a full-size cutting template.

Expected evidence: recognisable front view of the handle panel and slot, meaningful centre line, correctly directed extension lines from rounded-end centres, and 178 mm between those centres. No inferred total opening length or invented setting. Proportions can be approximate in the communication sketch; the original drawing controls manufacture.

Student page 47 • Explain how you would verify and align a full-size template before it reaches the timber.

Check the template against written drawing information and teacher directions, including centre marks, symmetry, orientation and the referenced 178 mm distance. Do not assume print scale is correct. Align the verified template with the component’s approved reference faces/edges and obtain the teacher checkpoint before transfer.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 6 answers • 2

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 47 • What will you inspect to judge handle comfort while preserving the approved form?

Check accessible edges for splinters, roughness and pressure points; inspect smooth transitions, approved clearance, alignment and secure housing fit. Comfort is checked within the approved design, without enlarging the slot or claiming one size suits everyone. Practical tests remain teacher-directed.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 7 answers • 1

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 28 • Map the approved tools: name one for each category, its material-specific job and one applicable control.

For each listed category, identify a tool or equipment example actually approved for this project. Explain its Carry-All function and why it suits the relevant material, then name one applicable setup, maintenance or safety control from the school procedure or instruction. A tool may serve several functions if the explanation is sound. Where a category is unavailable or not approved, record the teacher-confirmed alternative or that it is not applicable; do not invent equipment or permission to operate. The two tables together must address marking out, cutting, shaping/forming, machining, detailing, finishing and assembly.

Student page 29 • Complete the tool map. Identification does not authorise operation; confirm unavailable categories with your teacher.

For each listed category, identify a tool or equipment example actually approved for this project. Explain its Carry-All function and why it suits the relevant material, then name one applicable setup, maintenance or safety control from the school procedure or instruction. A tool may serve several functions if the explanation is sound. Where a category is unavailable or not approved, record the teacher-confirmed alternative or that it is not applicable; do not invent equipment or permission to operate. The two tables together must address marking out, cutting, shaping/forming, machining, detailing, finishing and assembly.

Student page 30 • Compare two actual teacher-approved products using current technical information, SDS and dated price evidence. Record missing information for teacher confirmation.

Identify each approved product and current technical/SDS sources, plus dated cost and package quantity for a fair price comparison. Record supported material suitability, strength and gap-filling limits, working/curing time and assembly conditions, shelf life/storage, hazards and controls, and clean-up/disposal. Keep unavailable information marked not supplied or Teacher to confirm. Do not invent product values, prices, ratios, PPE or disposal rules. The reasoned choice must suit the joint, pine/plywood and authorised school process; teacher approval remains required before use.

Student page 30 • Which candidate is better supported for this project, or what evidence is still needed? Explain your decision.

Accept a reasoned comparison tied to pine/plywood, fit requirements, intended use and the school's authorised process. If evidence is incomplete, the correct decision is to identify the gap and seek confirmation, not choose by brand recognition or fill in generic instructions.

Student page 31 • 1. What makes an adhesive comparison defensible?

D. The comparison needs product-specific evidence and the teacher's authorised process. Familiarity and generic timing do not establish suitability.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 7 answers • 2

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 31 • 2. What is the purpose of a clamp pad?

B. A pad protects the pine surface; it does not justify excessive pressure or repair incorrect fit.

Student page 31 • 3. A tool has an obviously loose part. What should the student do?

A. Faulty equipment needs a teacher-directed response. Testing or repairing it without authorisation may create further risk.

Student page 31 • A dry-fit corner only closes with heavy clamp pressure.**Explain why applying adhesive now would be poor problem-solving.**

The pressure may conceal a high spot, wrong orientation or another mismatch, and can introduce bow, twist or damage. The assembly has not demonstrated a sound dry fit. Diagnose and obtain an approved correction, then repeat the full dry fit before adhesive.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 8 answers • 1

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 34 • Plan your authorised shared task

Expected evidence: a real teacher-authorised component/template/test-piece task, named individual contributions within their authority, controlling source/criterion and a checked handover. Suitable checks include identity, written size relationship, orientation, condition and readiness. Teacher observation is distinct from student claims.

Student page 34 • Sequence puzzle: A apply finish; B approved surface check; C complete dry fit; D adhesive assembly and required waiting. Give the order and explain one dependency.

C–D–B–A. Dry fitting verifies the full assembly before adhesive; required product-specific waiting and sound assembly precede final surface readiness; the approved surface check precedes finish. Local details and actual SWMS remain teacher-controlled.

Student page 35 • 1. What should be assessed before moving long stock?

C. Safe handling depends on the actual load and surroundings, not a strength claim or speed.

Student page 35 • 2. What makes a production handover traceable?

B. The record connects an individual action with verified output passed to the next stage.

Student page 35 • 3. Why inspect between abrasive stages?

A. Progressive preparation depends on the observed surface and shape. Later abrasives or finish do not automatically erase earlier faults.

Student page 35 • A pale patch remains near an adhesive joint after preparation. What information should guide the next step?

Identify the condition and possible adhesive contamination; check under suitable light and seek the approved correction. Use the selected finish's requirements and teacher guidance. Do not add product, sand heavily or claim the patch is harmless without diagnosis.

Student page 46 • Stage-specific risk and control record

Expected entries connect real stage-specific hazards with possible harm, suitable approved controls and a check before progression. Examples may concern unstable material, adhesive exposure or finish contamination/handling; product-specific controls must come from actual information and the local school process. The teacher supplies required risk-rating conventions and authorisations.

Student page 46 • Describe a changed condition that would require you to stop and review this plan. Who needs to be involved?

Accept a meaningful change such as damaged equipment, unstable workholding, a new material defect, unclear fit or an unavailable approved process. The student stops, reports to the teacher and revises the relevant plan/control with approval before resuming.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 8 answers • 2

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

**Student page 46 • Teacher record —
agreed stage, required check and
decision to proceed or revise:**

Reserved for the teacher's actual observation and decision. The student must not prefill approval or imply a sign-off from this model answer.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 9 answers • 1

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 38 • Plan an inspection before changing the surface.

Pale area: inspect for adhesive contamination, preparation differences and product compatibility. Roughness: check dust/contamination, previous surface condition and application record. Run: check observed coverage and product-specific application information. All remain hypotheses until checked; corrections and waiting requirements must come from teacher/product directions.

Student page 38 • Why would applying more finish to every fault be an unreliable response?

Different causes need different approved responses. Additional finish may conceal or worsen contamination, runs or preparation faults and may conflict with required timing. Diagnose the observed condition and consult the selected product information before further work.

Student page 39 • 1. Where should the actual recoating requirement come from?

B. Recoating depends on the actual finish and conditions. This workbook provides no universal time or coat count.

Student page 39 • 2. What does a finish test piece help establish?

D. A representative test supports judgements about appearance and compatibility. It does not prove unrelated safety or structural claims.

Student page 39 • 3. Which final judgement has the strongest evidence?

A. It connects named functional/workmanship criteria to observed checks. The other statements overgeneralise from opinion or appearance.

Student page 39 • Describe two things to keep comparable between a finish test piece and the Carry-All, and explain why.

Accept material type/condition, surface preparation, approved finish/system and relevant application conditions. Comparable inputs make the test result more useful for predicting appearance or revealing problems. A test on unrelated material or rough preparation may mislead.

Student page 49 • Actual approved system

Entries must refer to the actual teacher-approved finish and current label/technical/SDS information. Record representative test preparation, observed appearance/compatibility and the teacher's decision. Timings, coats, controls and disposal details remain product/local-process specific. Teacher to confirm any missing requirement.

Student page 49 • Describe the surface check completed before finish. Include one internal or less visible area.

Accept actual evidence of scratches, grain, adhesive contamination, dust and preserved form. Internal areas could include the base, divider intersections, handle opening or corners. Explain the result and any approved response before finishing.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 9 answers • 2

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 49 • Name one finishing-stage observation and the information that guided your next decision.

Accept a real observation such as consistent coverage, roughness, a run, missed area or unexpected test reaction, linked to current product directions and teacher guidance. It must not invent a correction recipe or claim a waiting period without the actual source.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 10 answers • 1

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 42 • Find the evidence in the stronger model.

Stage: adhesive assembly after the teacher-approved dry fit. Action: assembled required joints and held them in the approved clamp arrangement. Check: corner seating and internal-part alignment before the adhesive set. Result: parts remained in position. Equivalent accurate wording is valid.

Student page 42 • Write a caption for one genuine stage of your Carry-All. Include the stage, action, check and observed result.

Accept a truthful specific caption identifying all four elements with a traceable image/page reference where available. If no practical stage has occurred, the student may draft a clearly labelled example and replace it later; do not treat an imagined event as completed work.

Student page 43 • 1. Which caption is most traceable?

C. It identifies the stage, symptom, check and response; it can be connected with a specific piece of evidence.

Student page 43 • 2. What belongs in the Interesting part of a PMI?

A. Interesting captures meaningful learning or a comparison that is neither simply a strength nor a weakness.

Student page 43 • 3. What remains important in both hand and industrial production?

D. Production methods can differ, but source control, safety and quality remain necessary. Repeatability does not make checking redundant.

Student page 43 • A student repeatedly lost track of component orientation. Propose one practical improvement and explain what evidence would show it helped.

A valid improvement could be an earlier consistent identification/reference-mark system and a checked handover before each operation. Evidence could compare labelled components with the drawing and record fewer orientation mismatches at later dry fits. Accept other specific approved changes with a credible checking method; avoid “be perfect” or unverified claims.

Student page 48 • Evidence reference / stage: identify a real image, sketch or page. State the action, check and result it shows.

A truthful record names the evidence location, practical stage, student action, relevant criterion/check and observed result. Accept an annotated sketch where photography is unavailable. A supplied illustration cannot be presented as the student’s work.

Student page 48 • One actual correction or diagnostic decision

Expected: a specific symptom, a cause treated as a hypothesis until checked, an approved response, and a repeat check. If no correction was needed, record a real diagnostic check and the decision to retain the work. Do not invent an error or claim that a hypothetical scenario actually occurred.

ANSWERS AND ACCEPTABLE EVIDENCE

Module 10 answers • 2

Use the linked student-page prompts and accept sound alternative reasoning for open tasks.

Student page 48 • Teacher-authorised collaborative production handover

Expected: a genuine authorised component, template, test piece or repeatable detail, the student's distinct contribution, a receiving check of identity/condition/readiness, and actual teacher observation where required. Helping carry stock alone is not evidence of the specified production task; record the real work completed.

Student page 50 • PLUS — What meets the brief? Name one feature, why it matters and the evidence that supports the judgement.

Accept a specific success in function, alignment, required joints, stable base, comfortable edges, finish, safe process or responsible material use. It needs a traceable observation, measurement or process record; unsupported praise is insufficient.

Student page 50 • MINUS — What limitation remains? Explain its effect and the evidence for the likely cause.

Accept an honest bounded limitation with effect on function, appearance, safety, efficiency or evidence. Distinguish a verified cause from a hypothesis. A student may identify a process limitation if the finished object has no obvious fault; do not require an invented defect.

Student page 50 • INTERESTING — What did this project reveal about materials, accuracy, collaboration or hand and industrial production?

Accept a meaningful insight grounded in the student's work or a clearly identified comparison. Examples include error propagation, value of dry fitting, grain behaviour, a checked handover, or how jigs support repeatability while still needing quality checks.

Student page 50 • NEXT TIME — Propose one achievable improvement. Explain which earlier decision would change and how you would check the result.

Accept one cause-linked practical improvement within teacher-approved work: an earlier reference check, clearer labels, more deliberate trial practice, stronger evidence timing or better handover. Explain a realistic measure/observation of improvement rather than promising perfection.

SOURCE RECORD

Sources and teaching limits

Keep this guide with the corresponding student edition.

Companion course: <https://stevencowell.github.io/Yr-9-Carry-All/> . Prepared from the course materials available on 11 September 2026. Use the original project drawing and current teacher-issued instructions for practical work. Generated editorial pictures are labelled illustrations. Check the guided course for subsequent teacher additions.

Teacher to confirm: the current assessment notification, due dates, required approvals and any project-specific changes. Retained source task records from earlier years are evidence of their own editions and must not be silently presented as current.