

Bedside Table Teacher Guide

Use with the guided course

This 50-page A4 workbook is a paper companion to the Bedside Table guided course: ten modules, 60 named theory sections and authentic project folio work. Read the relevant module as the teacher introduces it; use current classroom instructions for practical approval, timing and submission.

Print at A4, actual size, double-sided on the long edge: 25 sheets. The editable Word edition contains the same teaching, tasks and response areas. Editing can change pagination, so check it again before printing.

The workbook selects three source multiple-choice questions per module: 30 of the website's 120 questions. All selected question wording, option order and answers are preserved. The other 90 multiple-choice questions and 40 website written checks remain available online. Workbook written applications are formative adaptations with model reasoning in this guide.

Original plan and teacher-confirmed variations

The supplied original is the single A3 Occasional Table drawing by A. Sarina, dated 23/09/16. It is reproduced as a complete rotated sheet on student page 43. It shows straight aprons and no drawer or shelf. Website discussion of a curved front apron and storage is retained as conditional learning: confirm an approved variation before manufacture; storage evidence may be not applicable.

The drawing controls dimensions. The 600 mm vertical dimension terminates at the underside-of-top/leg datum; it must not be treated as an overall finished height. Its top note specifies biscuit joining three 150 × 25 × 500 boards, while the finished top outline is 500 × 400. Distinguish stock from finished dimensions, and confirm any allowance or missing detail rather than inventing it.

The website describes a school-selected 2027 Year 10 pathway with early use of the 2025 syllabus, and separately retains a 2026 formal assessment record. This booklet does not issue a replacement assessment notice or transfer historical dates, marks or conditions. The teacher confirms the current task and evidence requirements.

Practical teaching and assessment of responses

All machinery photographs show recognition references at rest. They do not specify operating settings, blade clearance, guarding or authorisation. Use the current workshop SOP, teacher demonstration and approved work holding. Chemical controls and drying or curing times come from the actual finish label and current SDS. Stop and obtain teacher direction when information conflicts or is incomplete.

Credit defensible alternative reasoning supported by the taught concepts. For open tasks, look for a specific observation, an explanation of its significance and a justified next decision. Do not require an invented practical result, unsafe test or one predetermined visual design. Distinguish a teacher sign-off from a student self-check.

The example photographs and generated illustrations explain a concept; they are not student work. Each image appears only once within each student edition. Reused images retain their provenance from Steve's other course booklets. Students must use their own evidence and truthful captions in their folio.

Student page 3

Name two success criteria and state a different observation you could use to check each one.

Accept specific pairs such as stability checked on the teacher-approved flat reference, and joint accuracy checked by shoulder closure and alignment. Appearance alone cannot prove structural stability. The evidence must relate directly to the criterion.

Student page 4

A marked set has four matching lengths but one reversed taper. Explain which check was missed.

Length alone was checked. The maker also needed to arrange the labelled legs in assembly orientation and compare datum faces, taper direction, joint faces and waste sides against the drawing before cutting.

Student page 5

1. The plan is displayed smaller on your screen than it was when it was drawn. Which information should control the table dimensions?

B. The written dimensions and notes on the drawing

Written dimensions remain authoritative even if the drawing has been enlarged or reduced.

Source: Module 1 knowledge checks

2. A broad curved front apron looks attractive but takes longer to machine and may create weak short grain. What is the strongest design decision?

C. Compare appearance, strength, function, time and manufacturability before deciding

A justified decision compares competing criteria and chooses the best overall balance.

Source: Module 1 knowledge checks

3. Which action best prevents parallax error when reading a steel rule?

B. Place your eye directly above the graduation being read

Looking directly above the graduation removes the angled viewing error.

Source: Module 1 knowledge checks

Explain a mark-out routine that would prevent a mortise being placed on the wrong face of a leg. Include your reference surfaces, labels and the check before cutting.

Use prepared face side/edge and a common datum end; arrange the four legs in their intended positions; label front/rear and left/right, visible faces, mortise face, taper and waste. Mark from the drawing, compare the set and seek the relevant teacher check before irreversible cutting. Credit a clear sequence and the reason for each control.

Student page 6

Sketch one leg blank. Label its face side, face edge, datum end, component position and the waste side of a proposed taper.

Look for distinguishable adjacent reference surfaces, a common reference end, a leg position and clearly separated retained timber/waste. Taper location and orientation must be checked against the actual plan; this sketch is mark-out evidence, not permission to invent a taper.

Explain one check that must happen before the first cut.

Accept a specific check of drawing dimension, datum, joint/taper face, matched-set orientation or waste side, with a consequence of getting it wrong.

Student page 7

Why is “one attractive face” insufficient evidence that a board suits a tapered leg?

The full blank must be sound and large enough after preparation. Grain changes, splits, knots or distortion can remain on other faces or at the joint/taper. The finished component’s position determines whether the board is suitable.

Student page 8

Explain why a marking gauge cannot compensate for an unreliable reference edge.

It repeats the distance from whichever edge the stock follows. If that edge is bowed, rough or incorrectly selected, the repeated line may be consistently wrong. Prepare and verify the reference before marking the final requirement.

Student page 9

1. Why are rough-cut timber blanks often prepared slightly oversize before final dressing?

B. To allow saw marks, damaged ends and distortion to be removed while reaching the finished size

The oversize allowance gives room to remove defects and produce flat, square surfaces at the required finished size.

Source: Module 2 knowledge checks

2. Why does the FEWTEL sequence begin by establishing a flat face and a square edge?

A. Because the remaining surfaces need reliable references

A flat face and square edge become the references from which the remaining surfaces are made parallel, square and correctly sized.

Source: Module 2 knowledge checks

3. What is the strongest reason for labelling prepared bedside-table components?

B. It preserves component identity, orientation, datum faces and matched relationships through later processes

Clear labels protect identity and orientation through joinery, shaping and assembly.

Source: Module 2 knowledge checks

A prepared leg twists slightly before joinery is marked. Explain the next decision and why it must happen now.

Stop at the preparation hold point. Recheck the actual component, datums and available size; the teacher determines whether it can be corrected while retaining the specified dimensions or should be replaced. Marking joints first would commit the twist and unreliable references to later stages.

Student page 10

Record two other details that must be settled before a cutting list becomes a cutting instruction.

Table guidance: top row records three 150 × 25 × 500 stock boards and the 500 × 400 finished top, with preparation and biscuit-joint allowances confirmed by the teacher. Legs row identifies four legs and transfers the actual drawn dimensions, taper and joint information without treating the 600 underside-of-top datum as overall height. Rails row distinguishes each position and transfers its drawn length, shoulder and joint requirements; do not infer a curved apron from this straight-apron drawing. The preparation column records actual teacher decisions rather than invented allowances. Accept actual timber allocation, finished versus rough dimensions, approved allowances, component orientation, joint allowances, defects and approval of any variation. Values must come from the original drawing or the teacher, not guessed from image proportions.

Student page 11

Name one material observation and one process observation worth recording from a mortiser test piece.

Material: whether the timber holds the required form without unacceptable splitting, crushing or tear-out. Process: accuracy, surface quality, control or waste against the required mortise and approved method. A fair comparison uses similar prepared material and teacher-authorised conditions.

Student page 12

Why should the final reference line remain visible after rough shaping?

It provides a reliable boundary for controlled refinement and comparison. Cutting away the line loses the reference and may remove required timber; a taper or curve cannot be made correct by sanding an over-cut area.

Student page 13

1. Which plan gives the fairest evidence about both material suitability and the effectiveness of a mortising tool, equipment and process?

A. Use matching offcuts of the same prepared timber and the same target mortise, follow teacher-approved options or criteria, and record each result

Keeping the material and target constant makes the comparison fair; the recorded result can show whether the timber is suitable and whether the selected process is effective.

Source: Module 3 knowledge checks

2. Why should the finished line remain visible after the bandsaw cut?

A. So the component can be refined accurately to final size

Leaving the line provides a reliable boundary for controlled final refinement.

Source: Module 3 knowledge checks

3. What does full shoulder contact in a mortise-and-tenon joint mainly help to provide?

A. Location, alignment and a neat closed joint

Full shoulder contact helps locate the parts and supports alignment and appearance.

Source: Module 3 knowledge checks

A tenon feels tight but its shoulder stays open. Explain what should be inspected before any correction.

Stop the fit and inspect cheeks, shoulder accuracy, mortise depth/position and any obstruction against the drawing. Identify whether binding prevents full seating or the shoulder itself is inaccurate. Obtain the appropriate teacher direction; do not hammer the joint or randomly remove material from every surface.

Student page 14

Plan the comparison. If only one method is authorised, state the success criteria you would check instead.

Table guidance: prepared timber and target row keeps material condition, preparation and required mortise comparable. Material response row records tear-out, splitting and surface quality as actual observations. Accuracy, control and waste row compares the marked target, resulting fit, controlled process and waste, without substituting speed for quality. If only one method is approved, mark the other method not applicable and check that result against the same criteria. Identify comparable prepared material, the same target and authorised methods; distinguish material suitability from process effectiveness. If there is one approved method, compare its test-piece result against agreed criteria rather than inventing a second process.

State the hold point before the project component is machined.

The teacher checks the relevant setup/test result and the student verifies component identity, datums, joint position, orientation and waste. Record the observed result before selecting the project method.

Student page 15

Give one reason to rehearse the clamp positions as well as the assembly order.

A clamp may block another joint, prevent measuring access or apply pressure in a distorting direction. Rehearsal verifies fit, access and protective pads while there is no adhesive working-time pressure.

Student page 16

Why should a “diagonals match” note include at least one other observation?

Matching diagonal readings must be interpreted with consistent measurement references and the intended rectangular shape. Closed shoulders, alignment, corner checks and freedom from twist provide other evidence that the actual frame is sound and correctly assembled.

Student page 17

1. Why should a complete dry fit occur before adhesive is opened?

A. To confirm fit, sequence, clamp access and measurements while correction is still easy
Dry fitting verifies the method and exposes faults before the glue-up becomes time-critical.

Source: Module 4 knowledge checks

2. Why are clamp pads used on finished timber surfaces?

A. To spread pressure and prevent jaw marks or bruising
Pads distribute pressure and reduce surface damage.

Source: Module 4 knowledge checks

3. After the frame has been clamped, what should be checked before it is left to cure?

B. Joint closure, frame diagonals, flush references, clamp stability and squeeze-out management
These checks confirm alignment, squareness and controlled adhesive work before curing.

Source: Module 4 knowledge checks

A dry-fitted frame has equal diagonals and closed shoulders, but rocks on a checked flat support. Explain why it still needs investigation before glue-up.

Equal diagonals and closed shoulders do not establish that all reference points lie in one plane. Rocking on a verified flat support may indicate twist, component alignment or an unsuitable support/contact condition. Identify the actual contact and alignment before correcting; do not cut a leg to hide an unexplained cause. Recheck the complete dry fit and obtain teacher direction before glue-up.

Student page 18

Draw a simple rectangular frame seen from above. Mark the four corner references and both diagonal measurement paths.

A clear top-view rectangle with two corner-to-opposite-corner paths crossing inside, each connected to consistent references. It is a measurement sketch, not a construction plan. Do not draw separate paths that compare different edges or arbitrary points.

Another practice frame reads 508 mm and 501 mm. After adjustment both diagonals read 501 mm, but one shoulder opens. Calculate the original difference and explain whether the frame is ready for adhesive.

The original difference is 7 mm. The frame is not ready: an open shoulder is an unresolved joint/alignment problem even if diagonal readings now match. Diagnose the component, joint or clamp cause with teacher direction and achieve the required closure and alignment together. These practice values supply no project tolerance.

What would a useful follow-up record show after an approved correction?

New actual readings plus shoulder closure/alignment or twist observations, the correction made, and whether the result met the agreed criteria. It must show the outcome rather than only the action.

Student page 19

What should the storage folio record contain when your approved version has no storage feature?

State that the feature is not applicable and cite the approved plan or teacher-confirmed version. Do not invent a drawer, make up hardware tests or leave an unexplained empty record. Continue evidence for the actual table components.

Student page 20

A drawer rubs at one rear corner. Why would planing every edge be a poor first response?

It removes good material without identifying the cause. Locate the contact and check opening geometry, component squareness, hardware alignment and proud fixings. Correct the confirmed cause with teacher direction, then retest the full movement.

Student page 21

1. What controls whether the bedside table includes a drawer, shelf or other storage component?

B. The approved plan and teacher-approved variation

The approved design controls what is built and how it is checked.

Source: Module 5 knowledge checks

2. What is the strongest method for aligning a visible drawer front or approved storage face?

A. Reference it to the actual opening and approved reveals, support it in position, then mark fixing locations

This controls position and reveals before holes are committed.

Source: Module 5 knowledge checks

3. How can the approved finish system affect storage-component fit?

A. Coating build can reduce a small clearance, so preparation and test fitting must follow the approved sequence

Controlled preparation and the approved finishing sequence help prevent post-finish binding.

Source: Module 5 knowledge checks

Explain how you would distinguish a problem in an opening from a problem in the moving component or hardware.

Measure and inspect the actual opening at multiple positions; check the component's size, squareness and alignment; observe where binding begins through the full travel; inspect hardware parallelism and proud fixings. Compare evidence before making one approved adjustment. Accept a coherent diagnostic sequence; do not infer fixed clearance values.

Student page 22

Choose the full-travel or uneven-front-gap row. Explain how its result would guide an approved adjustment and the final retest.

Table guidance: resistance at one point may indicate a local contact or projecting fixing; locate it and inspect before adjusting. Resistance through full travel may indicate overall fit or misaligned guides; compare actual opening and component dimensions and check the approved hardware alignment. An uneven front gap may indicate alignment, squareness or face-position error; compare the opening, references and fixing positions. These are possible causes requiring evidence, not diagnoses from the symptom alone. A strong response links observed position/pattern to a plausible cause, proposes a check that distinguishes it from other causes and limits removal or adjustment to the confirmed problem. Retest full travel, alignment and clearances. Do not award certainty for a cause chosen without evidence.

If your table has no drawer, name a fitting check that still applies to its top or frame.

Accept reliable reference faces, actual opening/component measurements, dry fit, alignment, correct support, clearance where required or secure fixings. State the actual component; do not add storage to the approved plan.

Student page 23

Explain how a solid top can remain secure while allowing movement. Name the direction of greatest movement and the authority for the fixing detail.

Seasonal moisture change produces most dimensional movement across the grain. The approved fixing detail locates the top securely while accommodating that movement; it is not random looseness. The plan and teacher direction determine the method, with the actual grain orientation checked.

Source: Module 6, section 1; Module 6, section 2; Module 6, section 3

Student page 24

One corner is high and a fixing feels loose. Name two checks you would make before adding force, and explain one possible consequence of overtightening.

Accept checks for debris or dried glue, a proud joint or displaced hardware, frame twist on a flat reference, and top distortion using the directed method. Tightening harder can crush fibres, strip a hole, distort hardware, stress the frame or restrict movement. A strong answer separates a symptom from a verified cause.

Source: Module 6, section 4; Module 6, section 5; Module 6, section 6

Student page 25

Across which direction does a solid timber top normally show the greatest seasonal movement?

A. Across the grain, as its moisture content changes

Solid timber expands and contracts mainly across the grain.

Source: Module 6 knowledge checks

One corner of the top sits high during a trial fit. What is the best first response?

A. Check for debris, proud joints or hardware, frame twist and top distortion before forcing it down
These checks separate contamination, frame geometry, hardware and timber shape.

Source: Module 6 knowledge checks

What is the strongest hold point before the top and hardware move to final finishing?

A. Teacher-approved checks confirm alignment, stability, safe hardware, operation and movement allowance

This protects function, safety and material movement before finishing.

Source: Module 6 knowledge checks

A classmate proposes pulling a high top corner down with one screw. Explain the problem with this proposal and describe a short diagnostic sequence before the pre-finish hold point.

Pulling the corner down can store stress, distort the frame, damage the top or remove movement allowance. Check a reliable flat reference, frame stability/twist, debris and proud joints or hardware, then inspect the top separately. Correct only the confirmed cause under teacher direction and retest contact, position, stability, safe hardware and movement allowance before finishing.

Source: Module 6, section 1; Module 6, section 2; Module 6, section 3; Module 6, section 4; Module 6, section 5; Module 6, section 6

Student page 26

A different trial fit still rocks after debris is removed. Write a cause → check → approved action → retest sequence. Explain why the loose-board image cannot prove which correction the actual table needs.

Accept a coherent sequence that tests remaining causes such as frame twist, a proud joint, top distortion or hardware seating using reliable references. The action must address the confirmed cause, with teacher advice before altering geometry, followed by the same contact/stability/alignment check and movement check. The generic image supplies no measurements or observations of the actual top, frame or fixings and therefore cannot determine the correction.

Source: Module 6, section 1; Module 6, section 2; Module 6, section 5; Module 6, section 6

Student page 27

The face looks smooth, but one deep cross-grain scratch remains. Explain why changing straight to finer paper may fail and how you would protect the approved shape.

Fine abrasive may polish the surrounding surface without removing the deeper previous scratch. Stay within the directed sequence, inspect the current pattern, work with the grain and use suitable support to distribute pressure. Avoid a local hollow or rounded edge; obtain teacher advice if removal would change geometry.

Source: Module 7, section 1; Module 7, section 2; Module 7, section 3

Student page 28

A pale patch appears beside a joint on a trial finish. Explain one likely cause, one check and the boundary at which you should seek teacher advice.

Residual glue may have altered absorption, but the image or pale patch alone does not establish the cause. Inspect the location/history and test the proposed compatible treatment on matching scrap where directed. Seek advice before a repair changes a joint, taper, profile or significant sound material; do not hide a structural gap with filler.

Source: Module 7, section 4; Module 7, section 5; Module 7, section 6

Student page 29

Why should dried glue be removed before normal finish sanding?

A. It can block finish absorption and appear as a pale patch

Glue contamination can prevent even wetting or penetration and remain visible.

Source: Module 7 knowledge checks

Why should each grit remove the scratches from the previous grit?

A. Otherwise deep scratches may remain visible after finishing

The sequence progressively replaces deep scratches with finer ones.

Source: Module 7 knowledge checks

Why are raking light and touch useful during final surface inspection?

A. They reveal scratches, glue, dents, ripples and sharp transitions that may be missed under normal viewing

Together they reveal subtle surface faults before coating highlights them.

Source: Module 7 knowledge checks

Plan a pre-finish inspection route for your approved table. Explain how you would distinguish a surface defect from a structural fault and prevent new dust contamination after correction.

A systematic route includes top, every leg, rails/apron, joints, edges and underside, with raking light from more than one direction and gentle clean touch. Scratches or glue residue may be surface issues; movement, splits or open joints need structural diagnosis and teacher advice. Use controlled approved correction, repeat the inspection, remove dust using workshop procedures and protect the clean table from active sanding.

Source: Module 7, section 1; Module 7, section 2; Module 7, section 3; Module 7, section 4; Module 7, section 5; Module 7, section 6

Student page 30

Complete the table. Then explain how you would verify one approved surface correction and prepare a clean handover for finishing.

Open joint with movement: structural; stop for teacher assessment, do not hide it with filler or sanding. Glue-like patch: suspected surface contamination; inspect/history and compatible trial, avoiding damage to the joint. Rounded shoulder: shape/geometry fault; teacher advice before further removal. Verification should repeat raking-light/touch checks over the full affected surface, confirm the intended shape remains, remove dust by approved procedures and protect from active sanding before the pre-finish hold point.

Source: Module 7, section 1; Module 7, section 2; Module 7, section 3; Module 7, section 4; Module 7, section 5; Module 7, section 6

Student page 31

Explain why a trial piece must match the table's preparation and why a touch-dry coat is not enough evidence that the table is ready for use.

Different sanding or contamination can change absorption and appearance, so the trial needs the same timber preparation and approved finish system. Touch-dry describes an early stage; hardness and service resistance may still be developing. Use exact product instructions, conditions and teacher confirmation for handling or use.

Source: Module 8, section 1; Module 8, section 2; Module 8, section 3

Student page 32

Give one control that reduces exposure before PPE is relied on. Explain why ordinary workshop gloves and an old SDS are insufficient for choosing the finish procedure.

Accept a teacher-approved lower-risk system, designated controlled area or effective extraction matching the product. Glove resistance depends on material and the exact chemical, while an old or different-product SDS may give unsuitable information. Use the current exact-product label/SDS and school procedure; PPE does not remove the hazard.

Source: Module 8, section 4; Module 8, section 5; Module 8, section 6

Student page 33

What should be checked before opening a finishing product?

A. The exact label, intended use, hazards, precautions and current SDS

The exact product information is required before handling begins.

Source: Module 8 knowledge checks

Why is PPE placed near the bottom of the hierarchy of controls?

A. It depends on correct selection, fit and use and does not remove the hazard

PPE reduces exposure but does not eliminate the source and relies on consistent use.

Source: Module 8 knowledge checks

What is the main difference between drying and curing?

A. Drying is an early handling stage; curing is the longer development of hardness and resistance. The distinction explains why apparently dry coating may still mark or stick.

Source: Module 8 knowledge checks

A classmate wants to use a similar-looking finish, wear general workshop gloves and pack the table as soon as it feels dry. Explain three decisions that must change before this plan is suitable.

Use only the teacher-approved exact finish system and read its label/current SDS rather than substituting by appearance. Determine product-specific controls and glove compatibility through the SDS and school procedure; general gloves are not sufficient evidence. Protect the coat and follow the specified drying/curing and handling requirements with teacher confirmation before packing. Accept equivalent source-consistent reasoning without invented times or product prescriptions.

Source: Module 8, section 1; Module 8, section 2; Module 8, section 3; Module 8, section 4; Module 8, section 5; Module 8, section 6

Student page 34

Complete the reading record with source references or “Teacher to confirm”. Explain how one planned control reduces exposure and how one handling or waste decision avoids damage or unnecessary waste.

Answers depend on the actual teacher-supplied product and current SDS; verify every recorded requirement against those documents and the school procedure. Accept “Teacher to confirm” for unavailable information. A control explanation should connect the hazard/exposure to an appropriate directed control rather than relying on PPE alone. Handling/waste reasoning may connect sufficient cure to avoiding surface damage/rework, planned quantity to less waste, or segregated contaminated materials to the directed safe disposal route. Do not award an invented product, glove, drying time or disposal rule as a factual answer.

Source: Module 8, section 1; Module 8, section 3; Module 8, section 4; Module 8, section 5; Module 8, section 6

Student page 35

Choose one quality criterion for your table. State the evidence that would test it and one thing a photograph alone could not prove.

Accept a source-consistent criterion such as stable contact on a known flat surface, top alignment or joint closure. Evidence must connect to the criterion: observed stability test plus record, reference measurements or suitable detail photographs. A photograph alone cannot prove all structural strength, movement allowance, actual dimensions or every hidden joint. No invented result is required.

Source: Module 9, section 1; Module 9, section 2; Module 9, section 3

Student page 36

Explain how you would choose between two similar photographs for the folio and what you would check before leaving the device.

Keep the sharper, better-lit, more informative image that proves the relevant criterion and remove repetition from the selected evidence set. Add an accurate caption, retain useful development evidence and download the folio ZIP backup; check that the expected work is present and exports open before changing devices or clearing browser data.

Source: Module 9, section 4; Module 9, section 5; Module 9, section 6

Student page 37

Which portfolio item provides the strongest manufacturing evidence?

A. One labelled photo showing the component, template comparison, quality result and date

A labelled, contextual photo can prove the stage, process and result.

Source: Module 9 knowledge checks

What should a strong photograph caption include?

A. The stage, process or decision, evidence and outcome

These elements make the evidence traceable and meaningful.

Source: Module 9 knowledge checks

Which improvement is most specific?

B. Mark matching components from one datum and compare the dry-fitted frame diagonals before glue-up

This action directly addresses component alignment and adds a measurable check.

Source: Module 9 knowledge checks

Write an evaluation of one genuine feature of your work so far: state the criterion, the evidence, your judgement and one realistic improvement. If work is not yet available, clearly label a hypothetical example.

Assess the connection among criterion, evidence, judgement and cause-linked improvement, not whether the student claims success. A suitable example identifies a specific quality requirement, cites an actual observation or clearly hypothetical result, acknowledges a limitation and proposes a repeatable method. Generic praise, invented measurements presented as actual, or an improvement unrelated to the cause is insufficient.

Source: Module 9, section 1; Module 9, section 2; Module 9, section 3; Module 9, section 4; Module 9, section 5; Module 9, section 6

Student page 38

Rewrite this hypothetical caption: “My table looks great, so it is completely accurate.” Choose two records from the table above and explain what each proves. Finish with one realistic evaluation statement and one improvement; label any imagined result as hypothetical.

A suitable response replaces praise with a specific feature/stage and supported observation, selects complementary evidence rather than duplicate photographs, and recognises each record’s limits. For example, an overall image can show top/frame alignment while a recorded check supports observed stability on a known reference. Evaluation should state criterion, evidence and judgement, with a specific cause-linked improvement. Hypothetical results must be labelled; do not require a particular result or accept invented measurements as actual evidence.

Source: Module 9, section 1; Module 9, section 2; Module 9, section 3; Module 9, section 4; Module 9, section 5; Module 9, section 6

Student page 39

A table rocks during the final presentation. Explain how you would confirm the cause and protect the finished work before deciding on a correction.

Recheck on a verified flat/level reference and inspect for debris, uneven contact, twist or a racked frame rather than assuming one long leg. Protect nearby finish and use only the least invasive approved action for the confirmed cause. Seek teacher advice before structural or geometry changes, and retest using the original check.

Source: Module 10, section 1; Module 10, section 2; Module 10, section 3

Student page 40

Write one precise practice you would transfer to another timber project, then name one handover check for the workshop and one for your digital evidence.

Accept a specific process linked to a benefit, for example mark matching parts from one datum to reduce variation. Workshop check may be returned tools, clear access routes, directed waste sorting or reporting damage. Evidence check must verify the downloaded final files/folio backup open and contain the expected authentic work. Vague statements alone are insufficient.

Source: Module 10, section 4; Module 10, section 5; Module 10, section 6

Student page 41

Which final-work priority is strongest?

A. Safety and function before cosmetic extras

Safety, structure and function are the essential requirements.

Source: Module 10 knowledge checks

What does “least invasive correction” mean?

A. Restore the requirement while changing or removing the least sound material

A least invasive action corrects the verified cause with minimal collateral change. In the preserved source option, “the least sound material” means the smallest amount of sound timber: minimise removal of good material. It does not mean selecting the poorest-quality timber.

Source: Module 10 knowledge checks

What completes a professional workshop handover?

A. Tools returned, waste separated, chemicals secured, faults reported and access paths clear
These actions protect the next user and make problems visible.

Source: Module 10 knowledge checks

Write a brief care and handover note for the table. Include safe lifting, finish-compatible cleaning, the response to later instability and one responsibility for the shared workshop.

Support the frame when lifting; do not drag or lift only from the top. Use the teacher/manufacturer-approved cleaning method for the finish, protecting from heat, moisture and unsuitable chemicals. Remove an unstable table from use until appropriately assessed and repaired. Include a relevant workshop responsibility such as returning checked tools, sorting waste, clearing access or reporting faults. No invented load rating or chemical recipe is expected.

Source: Module 10, section 1; Module 10, section 2; Module 10, section 3; Module 10, section 4; Module 10, section 5; Module 10, section 6

Student page 42

Complete the handover table. Then write one precise future practice that would prevent an issue shown here or encountered in your own project, explaining its benefit.

Access route: identify the loose timber obstruction and arrange its removal/storage under workshop direction, leaving the route clear. Tools/waste: return checked equipment, report damage and sort waste by approved routes. Project: support/store/transport in the directed position and protect the finish. Digital evidence: download and open the required exports/folio backup to verify content. The future practice must be repeatable and explain a benefit, such as a route-and-bench check before departure preventing trip hazards. Accept another genuine source-consistent improvement; do not infer every unseen hazard from the picture.

Source: Module 10, section 3; Module 10, section 4; Module 10, section 5; Module 10, section 6

Student page 44

Choose one pictured tool or item. Name its job in an approved task and one check required before use.

A sound response links the item to a source-supported task and a relevant check: square/reference condition; mallet/appropriate striking task and sound tool; glasses/fit and condition; biscuit joiner/teacher-approved method, registration and required SOP. No machine operation or setting is authorised by this activity.

Source: Project folio

Student page 45

State the intended user, purpose and two success criteria for your table.

Specify an actual user/use and assessable criteria such as stable support, suitable proportions, sound joints, safe edges or satisfactory approved finish. Avoid an unsupported numerical load or invented assessment condition.

Source: Project folio

Concept A / sketch and annotate one choice that the teacher permits you to explore.

A recognisable, labelled design idea within the authorised project. Notes explain a genuine choice and its effect on function, strength, appearance or manufacture. Any curved apron or storage requires a confirmed variation.

Source: Project folio

Concept B / show a meaningful alternative and name its main trade-off.

The second idea must differ in a meaningful approved aspect. Its annotation identifies both a benefit and a consequence; decorative changes must not weaken the structure or conflict with the drawing.

Source: Project folio

Which idea best meets your criteria, and what needs teacher confirmation before manufacture?

Justify using the stated criteria, compare both options and identify approval or drawing information still needed. Aesthetic preference may be valid when balanced with function, structure and realistic manufacture.

Source: Project folio

Student page 46

Complete a cutting list for the components you will make.

Entries must correspond to the approved version, with quantities, actual allocated material, finished requirements and the source of dimensions. Distinguish stock from finished size and identify teacher-confirmed allowances. Do not invent omitted drawer dimensions or timber species.

Source: Project folio

Draw one component showing its datum faces, grain, identity, joint location and waste marks.

A specific component with clear reference faces/end, grain orientation, location/identity and required joint/waste marks. Joint and taper locations need to agree with the drawing or a confirmed variation.

Source: Project folio

Explain one inspection or grain-placement decision that affected your cutting list.

Name an observed condition or arrangement, its proposed position and consequence for the finished part. Explain why repositioning, allowance or replacement was chosen and record teacher direction where necessary.

Source: Project folio

Student page 47

Record your process, result and next decision.

Entries describe real work, the selected process and a specific observed result. Useful records separate actions from outcomes and show the reason for a next step. They must not copy the hypothetical examples as actual student results.

Source: Project folio

Choose one entry. Identify the hazard, possible harm and controls used, including teacher/SOP direction.

A credible hazard-to-harm chain with task-specific controls. Higher-level controls and work holding/guarding/extraction should be considered before reliance on PPE. Record actual authorisation; the workbook is not a practical licence.

Source: Project folio

Name the test-piece or dry-fit evidence that helped you decide to continue.

Identify the actual test or dry fit, comparable material where applicable, observed joint/material/process result and the relevant teacher hold point. Do not claim a satisfactory fit from appearance alone.

Source: Project folio

Student page 48

Add or sketch your own checkpoint evidence. Label the feature, reference and stage it shows.

Use authentic project evidence: a labelled sketch or an attached photograph of a meaningful checkpoint. It should identify what is being checked, the relevant reference and the stage. A borrowed or generated picture is not student evidence.

Source: Project folio

Write a caption: what was checked, what did you observe and what does that result show?

A useful caption links the specific check to the visible/recorded result and a justified claim. It does not claim unseen performance, full structural strength or teacher approval from one image.

Source: Project folio

Record the relevant assembly evidence.

Frame evidence should combine joint closure with squareness/alignment and twist checks. Top evidence records its approved fixing and allowance for movement. Storage records actual approved function or clearly explains non-applicability with the plan reference.

Source: Project folio

What remains to be checked before the next stage?

Identify a genuine unresolved feature, the evidence needed and who must confirm it. An honest limit is stronger than ticking a check that has not occurred.

Source: Project folio

Student page 49

Judge the finished table against your brief.

Each judgement needs relevant evidence and a proportionate improvement. Criteria may be adapted to the actual brief. Stability and approved use checks remain teacher-directed; do not invent load tests. Credit honest limitations and a clear distinction between observed result and proposed action.

Source: Project folio

Explain one real problem using problem → likely cause → approved action → result.

Describe a specific problem and evidence for its likely cause, the correction actually used, and the observed outcome. If unresolved, record that clearly and identify the next authorised check. Do not substitute a generic claim that everything went well.

Source: Project folio

Which evidence best supports your strongest judgement? Explain why.

Select a relevant photo, measurement, drawing, test or recorded observation and explain the claim it can support. A pleasing finished-product image alone does not prove every quality criterion.

Source: Project folio

Student page 50

Check your actual submission and workshop handover.

Record actual evidence locations and unfinished actions. Verify current teacher instructions; do not import the old 2026 task dates or marks. Include approved changes, authentic process and quality evidence, relevant finish information and responsible workshop handover.

Source: Project folio

Write care advice suitable for the actual finish and table version. Name the source you used.

Use the actual approved product and teacher instructions. Advice should address handling and ordinary use, avoiding premature use during curing, and reporting looseness or damage. No invented cleaner, chemical, recoating interval or repair method.

Source: Project folio

Name one skill you will transfer to a future project. Explain what you would do differently and why.

A specific transferable skill such as common datums, controlled trial comparisons, diagnostic dry fitting, restrained adjustments or evidence-based evaluation. Explain a concrete future action and how it responds to this project's evidence.

Source: Project folio

Current matching course: <https://stevencowell.github.io/bedside-table-guided-course/> . Access the complete module questions, presentations, videos, folio and teacher resources through that course.

Source control: website snapshot aa2c49deaf5d0a72d6b42ff74d315941a4c4e94d, checked 12 September 2026. Original Occasional Table plan, course module text and question data, folio, source notes and labelled teacher/assessment resources are retained in the workbook evidence record.

Original plan reproduction is a construction reference; generated and reused concept figures have no dimensional authority.