

Disc sander (fixed)

Safe operating procedure (SOP)

SANDER, DISC (FIXED) < = 390MM DISC

DO NOT use this equipment unless a teacher has demonstrated its safe operation, you have passed a safety test, your teacher has given permission and observed you using it safely.

Compulsory PPE			As needed PPE		
					
Face and eye protection	No loose clothing	Enclosed leather shoes	Hearing protection	Dust mask	Hair restraint
Risks					
❗ Eye injuries	❗ Abrasions	❗ Burns	❗ Entanglement	❗ Dust inhalation	
Prohibited					
❗ Removing guards		❗ Sharpening tools		❗ Sanding metal	



Usage controls			
	7–8	9–10	11–12
Typical tasks	✓ Sanding end grain to a squared line	✓ Rounding a corner	✓ Sanding mitres to a line
Controls	✓ Maximum width: 140 mm ✓ Minimum thickness: 10 mm ✓ Maximum thickness: 70 mm ✓ Minimum length: 100 mm ✓ Maximum length: 450 mm	✓ Maximum width: 140 mm ✓ Minimum thickness: 3 mm ✓ Maximum thickness: 100 mm ✓ Minimum length: 100 mm ✓ Maximum length: 1000 mm	✓ Maximum width: 140 mm ✓ Minimum thickness: 3 mm ✓ Maximum thickness: 150 mm ✓ Minimum length: 100 mm ✓ Maximum length: 1000 mm
	✓ Teacher permission/approval required ✓ Only one student to use disc sander at a time ✓ Only one student within machine zone ✓ All guards in place and adjusted correctly ✓ Use of mitre gauge wherever possible ✓ Minimum separation of hands and disc: 50 mm ✓ Work kept flat on table at all times ✓ Use of mitre gauge	✓ Max gap between disc and table: 2 mm ✓ Abrasive to be securely fixed to disc ✓ Abrasive to be cleaned regularly ✓ Worn or torn abrasive to be replaced ✓ Dust extraction must be connected and turned on ✓ Disc sander must be electrically isolated when not in use	

Safe operating instructions	
Pre-start checks	✓ Locate and ensure you are familiar with the ON/OFF control and E-Stop (if fitted) ✓ Ensure disc sander is electrically isolated before making any adjustments ✓ Immediately report unsafe or faulty equipment to the teacher
Operational checks	✓ Ensure all guards are in place and adjusted correctly ✓ Check abrasive for damage or excessive wear ✓ Check that abrasive disc is securely fixed to the metal disc ✓ Adjust the angle of the table if required ✓ Hold the workpiece securely in both hands
Workpiece sizes checks	✓ Ensure the size of the workpiece is correct for the year group
Sanding timber checks	✓ Wear all appropriate PPE as identified above ✓ Beware of clothing or entanglement in the abrasive disc ✓ Do not force the timber into the disc ✓ Keep the timber flat on the table at all times ✓ Before making adjustments or cleaning accumulated dust, switch off the disc sander and bring it to a stop ✓ Never leave the disc sander while it is running
Clean-up checks	✓ Switch off the disc sander ✓ Leave the disc sander in a safe, clean and tidy state