Chapter 27
Reports

The Rubrik CDM web UI provides a reports summary and a gallery of reports. The gallery includes default reports and custom reports created from templates.

The Reports section of the Rubrik CDM web UI offers two views: a Summary view and a Gallery view.

The Summary view provides a graphical representation of the current status of various tasks, divided into cards. Each card contains a link to a report with more details.

The Gallery view displays both default and custom reports. Any of the default reports can be used as templates to create customized reports with different fields and graphs, as well as custom filtering along several different dimensions.

Summary view

The Reports Summary page provides a high-level view of statistics for key areas of the Rubrik cluster. The statistics are collected from the default reports.

Statistics	Description
Daily Protection Tasks by Status	Indicates the number of protection tasks that succeeded, the number that were canceled, and the number that failed. Links to the Protection Tasks Details report.
Local Snapshot Storage	Shows a time series graph of storage used on a daily basis. Links to the System Capacity report.
SLA Compliance	Shows the number of objects in compliance and the number of objects out of compliance. Links to the SLA Compliance Summary report.
System Capacity	Summarizes the amount of storage used and estimates how long it will take to reach full capacity at the current rate. Links to the System Capacity report.
Weekly Protection Tasks by SLA Domain	Summarizes the status (Successful, Failed, or Canceled) of each protection task associated with a given SLA Domain. Links to the Protection Tasks Summary report.

Viewing report summary information

View the summary information on the Reports Summary page.

Procedure

1. Log in to the Rubrik CDM web UI.
2. On the left-side menu, select **Reports** > **Summary**.
   Rubrik CDM displays summary information collected from the default reports.
3. Click **View Report** in any individual tile.

Result

The report summary information appears.

Displaying a report

Use the Rubrik CDM web UI to display default and custom reports.

Procedure

1. Log in to the Rubrik CDM web UI.
2. On the left-side menu, select **Reports** > **Gallery**.
   A list of all available reports appears.
3. Optional: To search the list, type a string into the **Search by Name** field.
   - To filter the list by template, select a template type from the **Filter Template** menu.
   - To filter the list by type, select Default or Custom from the **Filter Type** menu.
4. Click the name of a report.
   The selected report appears.

Result

The Gallery view includes eight default reports. Each report consists of two charts and a information. The information in the reports is refreshed every hour.

Default reports

The Gallery view includes eight default reports. Each report consists of two charts and a table of information. The information in the reports is refreshed every hour.

Report name	Description
SLA Compliance Summary	Summarizes information about compliance with the policies set forth in each SLA Domain. The compliance calculation includes on-demand snapshots. **Note:** The report depends on the time range selected. Objects may appear out-of-compliance if they have missed snapshots in the specified time range.
Object Backup Task Summary	Provides information about scheduled backup tasks that are triggered by an SLA protection policy. The report does not include information about on-demand backup tasks. Information includes the total number of daily expected backup tasks for each object along with the number of successful, failed, canceled and missed tasks. **Note:** This report does not include information for the current day.
Object Indexing Summary	Provides the indexing status for the latest local snapshot, the time stamp of the latest successfully indexed snapshot, and the number of indexed local snapshots. Includes charts that display the indexing summary by SLA Domain, and the indexing summary by object name.

Report name	Description
Protection Tasks Summary	Displays the weekly number of backup and replication tasks by status, the status of weekly tasks by SLA Domain, and a summary table with more detailed information.
Protection Tasks Details	Displays the daily number of protection tasks by status, daily failed tasks by object name, and a summary table with more detailed information.
Recovery Tasks Details	Displays the total number of recovery tasks in the last month, the number of recovery tasks by status, a chart of failed recovery tasks sorted by object name, and a summary table with more detailed information.
Object Protection Summary	Displays the storage usage of each SLA Domain, the level of SLA compliance by SLA Domain, and a summary table with more detailed information.
Capacity Over Time	Displays the average storage used on the Rubrik cluster for the current month and the three previous months. The report is refreshed every hour. The average monthly storage is calculated by taking the average of the storage values for each day in the month. The storage value for a given day is calculated by taking the average of the storage used at four sampling points in that day. The report also includes a summary table with more detailed information.
System Capacity	Displays the usage of local storage by SLA Domain, the usage growth over time by SLA Domain, and a summary table with more detailed information.

Custom reports

Each default report can be used as a template for creating customized reports. Customized reports include two charts, a table, and optional filters.

For each chart, select an attribute and a measure, and the type of chart used to visualize the data (such as a donut chart, vertical chart, horizontal chart, or line chart). For the table, select any combination of measures and attributes as column headings.

A measure is something that can be counted or calculated; for example, the number of successful tasks, or the effective throughput.

An attribute is a characteristic of the data that does not change; for example, the name or location of an object.

Object logical size

The Rubrik cluster reports the logical size of the latest snapshot of an object. The object logical size definition depends on the object type.

Object type	Definition of logical size
VMware virtual machine	The full provisioned size of the virtual machine disks as reported by VMware. The reported size is not reduced by the amount of unused disk space.
Nutanix virtual machine	The full provisioned size of the virtual disks. The reported size is not reduced by the amount of unused disk space.
HyperV virtual machine	The size of the VHD or VHDX file stored as a sparse file. The reported size does not represent the actual size of the guest OS; it is only the physical size of the VHDX file on the host.
Cloud Native virtual machine	The current capacity of all the EBS volumes that are attached to the Amazon EC2 instance.
Fileset	The aggregate size of data volumes used for storing the file system hierarchy. The logical size of the fileset object is proportional to the sum of the sizes of all the files in the filesystem reported by the host, plus an additional 4096 bytes per directory.
MS SQL database	For snapshots, the sum of the sizes of all database files as shown in the host file systems. Database files have .mdf, .ldf, or .ndf extensions. For log backups, logical size is the actual log backup file size as computed by the Backup Log command of the SQL Server.

Types of charts

Charts provide a graphical representation of the data gathered in a report.

Chart Type	Description
Donut	A ring shape with the length of the arcs proportional to the percentage of the total.
Vertical	A chart that displays vertical bars with the length of the bars proportional to the value.
Horizontal	A chart that displays horizontal bars with the length of the bars proportional to the value.
Line	A chart that displays a series of data points connected by line segments.
Stacked Vertical	A vertical chart where the bars have individual segments with lengths proportional to the percentage of the total value of each bar.
Stacked Horizontal	A horizontal chart where the bars have individual segments with lengths proportional to the percentage of the total value of each bar.

Chart measures for custom reports

Information about the measures available for custom report charts. Each chart corresponds to a single measure.

Chart	Measure Description	Default report templates with this measure
Archival Snapshot Lag	Integer representing the difference between ingested snapshots and snapshots successfully transferred to the archival location.	• SLA Compliance Summary • Object Protection Summary
Archive Data Reduction	The percentage of reduction in total data size of the archive.	• System Capacity • Capacity Over Time • Object Protection Summary
Archive Dedup Ratio	The deduplication ratio achieved by the archive.	• System Capacity • Capacity Over Time • Object Protection Summary
Archive Effective Data Transferred	Total amount of data transferred by the task.	• System Capacity • Capacity Over Time • Object Protection Summary
Archive Effective Logical Data	Total size of protected data calculated on the basis of full backups instead of incremental differences.	• System Capacity • Capacity Over Time • Object Protection Summary
Archive Logical Data Reduction	The percentage of reduction in the size of the backup calculated on the basis of full backups instead of incremental differences.	• System Capacity • Capacity Over Time • Object Protection Summary
Archive Logical Dedup Ratio	The deduplication ratio calculated on the basis of full backups instead of incremental differences.	• System Capacity • Capacity Over Time • Object Protection Summary
Archive Storage	Amount of cluster storage used by archived snapshots.	• System Capacity • Capacity Over Time • Object Protection Summary
Archive Storage Growth	Amount of cluster storage used by archives in a specified time period.	• System Capacity • Capacity Over Time • Object Protection Summary
Average Duration	Average task duration.	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details

Chart	Measure Description	Default report templates with this measure
Canceled Tasks	Number of canceled tasks.	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details • Object Backup Task Summary
Compliance Count by Status	Object count by compliance status. Objects can be out of compliance or in compliance.	• SLA Compliance Summary • Object Protection Summary
Data Reduction	The percentage of reduction in total data size of the backup, calculated after deduplication and compression.	• Protection Tasks Summary • Protection Tasks Details
Data Stored	Total storage used by objects over the target time period, including expired and purged snapshots, after deduplication and compression.	• Protection Tasks Summary • Protection Tasks Details
Data Transferred	The sum of the data transferred for each active snapshot (both policy-based and on-demand). The data transfer size of expired snapshots is not counted towards this value. The size of the data transferred is measured before deduplication, compression, and global linking.	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details
Data Transferred vs Stored	The ratio of data transferred over the network compared to the amount of data stored on the Rubrik cluster.	• Protection Tasks Summary • Protection Tasks Details
Dedup Ratio	The ratio of data transferred to data stored, expressed as a fraction.	• Protection Tasks Summary • Protection Tasks Details
Effective Throughput	The ratio of the number of bytes received during a backup divided by the length of time for the backup.	• Protection Tasks Summary • Protection Tasks Details
Expected Tasks	Number of expected tasks, based on the snapshot schedule defined in the SLA Domain.	• Object Backup Task Summary
Failed tasks	Number of failed tasks.	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details • Object Backup Task Summary

Chart	Measure Description	Default report templates with this measure
In Compliance	A Boolean with a value of Yes when the object is SLA compliant and a value of No otherwise.	• SLA Compliance Summary • Object Protection Summary
Local CDP Health	The percentage of time a particular virtual machine has been in a healthy CDP state. The percentage is calculated from the ratio of time healthy to total time enabled. CDP is considered healthy when the status is Active. CDP is considered enabled when the status is Active, Failed, or Taking Snapshot (when the snapshot is taken immediately following a failure).	• SLA Compliance Summary • Object Protection Summary
Local CDP Log Storage	The amount of disk space consumed on the local Rubrik cluster by CDP logs. For a custom report based on Capacity Over Time, Local CDP Log Storage is summed over all virtual machines for the specified time period.	• Object Protection Summary • Capacity Over Time • System Capacity
Local CDP Throughput	The local network bandwidth consumed by CDP per virtual machine. For a custom report based on Capacity Over Time, Local CDP Throughput is summed over all virtual machines for the specified time period. Units are bps (bits per second).	• Object Protection Summary • Capacity Over Time • System Capacity
Local Data Reduction	The percentage of reduction in total data size of the backup.	• System Capacity • Capacity Over Time • Object Protection Summary
Local Data Transferred	The sum of the data transferred for each active snapshot, both policy based and on demand. The data transfer size of expired snapshots is not counted towards this value. The size of the data transferred is measured before deduplication, compression, and global linking.	• System Capacity • Capacity Over Time • Object Protection Summary
Local Dedup Ratio	The ratio of data transferred to data stored, expressed as a fraction.	• System Capacity • Capacity Over Time • Object Protection Summary
Local Effective Logical Data	Total size of protected data calculated on the basis of full	• System Capacity

Chart	Measure Description	Default report templates with this measure
	backups instead of incremental differences.	• Capacity Over Time • Object Protection Summary
Local Effective Storage	Calculation of the equitable allocation of deduplicated data assigned to individual snapshots. This enables a fair distribution between objects. For example, a system that includes duplicate data from five objects with the same size and the same data overlap reduces storage to a total of a combined 10 GB. This data contributes 2 GB to the total Local Effective Storage for each object (10 GB ÷ 5 = 2 GB).	• System Capacity • Capacity Over Time • Object Protection Summary
Local Logical Data Reduction	The percentage of reduction in the size of the backup calculated on the basis of full backups instead of incremental differences.	• System Capacity • Capacity Over Time • Object Protection Summary
Local Logical Dedup Ratio	The deduplication ratio calculated on the basis of full backups instead of incremental differences.	• System Capacity • Capacity Over Time • Object Protection Summary
Local Metered Data	For a protected object, the amount of data transferred from the data source to the Rubrik cluster between two points in time.	• System Capacity • Capacity Over Time • Object Protection Summary
Local Protected Data	The sum total of data protected, including full and incremental backups, before the application of deduplication and other efficiencies	• System Capacity • Capacity Over Time • Object Protection Summary
Local Snapshot Count by Index Status	Total number of local snapshots for all index statuses (indexed, unindexed, and pending).	• Object Indexing Summary
Local Snapshots Indexed	Number of local snapshots that were indexed successfully.	• Object Indexing Summary
Local Snapshots Pending For Indexing	Number of local snapshots that are in the process of being indexed.	• Object Indexing Summary
Local Snapshots Unindexed	Number of local snapshots that are not indexed because indexing failed.	• Object Indexing Summary

Chart	Measure Description	Default report templates with this measure
Local Storage	Amount of Rubrik cluster storage currently in use.	• SLA Compliance Summary • Capacity Over Time • Object Protection Summary
Local Storage Growth	Amount of Rubrik cluster storage used in a specified time period.	• SLA Compliance Summary • Capacity Over Time • Object Protection Summary
Logical Data Protected	The total logical size of the protected object for all active snapshots, both policy based and on demand.	• Protection Tasks Summary • Protection Tasks Details
Logical Data Reduction	The ratio of logical data protected to data stored, expressed as a percentage.	• Protection Tasks Summary • Protection Tasks Details
Logical Dedup Ratio	The ratio of logical data protected to data stored, expressed as a fraction.	• Protection Tasks Summary • Protection Tasks Details
Missed Objects	Number of files and folders that failed to back up.	• Protection Tasks Summary • Protection Tasks Details
Missed Tasks	Number of tasks that should have been scheduled in a calendar day according to the SLA, but were not.	• Object Backup Task Summary
Object Count	Total number of objects.	• Recovery Task Details • SLA Compliance Summary • Object Protection Summary
Object Logical Size	The logical size of the most recent unexpired snapshot.	• Object Protection Summary • Capacity Over Time • System Capacity
Out of Compliance	A Boolean with a value of No when the object is SLA compliant and a value of Yes otherwise.	• SLA Compliance Summary • Object Protection Summary
Provisioned Size	Total size allocated to the object at creation or modification. For example, if a database or virtual machine is created with 100 GB of size, the provisioned size is 100 GB, regardless of the data consumed within the object.	• System Capacity • Capacity Over Time • Object Protection Summary
Replica Storage	Amount of cluster storage used by replicas.	• SLA Compliance Summary • Capacity Over Time • Object Protection Summary

Chart	Measure Description	Default report templates with this measure
Replica Storage Growth	Amount of cluster storage used by replicas in a specified time period.	• SLA Compliance Summary • Capacity Over Time • Object Protection Summary
Snapshot Count by Data Location	A stack chart of local, replica, and archive snapshot counts.	• SLA Compliance Summary • Object Protection Summary
Storage Growth by Data Location	A stack chart of storage growth for local, replica, and archive snapshots.	• System Capacity • Object Protection Summary
Successful Tasks	Number of successful tasks.	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details • Object Backup Task Summary
Task Count	Total number of tasks.	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details
Task Count by Status	The number of successful, canceled, and failed tasks.	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details
Total Files Transferred	Total number of files ingested by the Rubrik cluster.	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details
Total Storage by Data Location	A stack chart of local, replica, and archive physical storage consumed.	• System Capacity • Object Protection Summary
Used Size	Actual amount of data consumed by an object at its source. For example, if an object is provisioned with 100 GB of disk space but only 10 GB of data has been written to the disk, 10 GB is the Used Size. For hypervisor workloads, Used Size is considered to be written blocks as reported by the hypervisor. Written blocks might be higher than what the guest OS reports due to provisioning type or deleted but not reclaimed allocated blocks.	• System Capacity • Capacity Over Time • Object Protection Summary

Related reference

Chart measures for custom reports

Information about the measures available for custom report charts. Each chart corresponds to a single measure.

Types of charts
Charts provide a graphical representation of the data gathered in a report.

Chart attributes

The attributes available for custom report charts. Each chart has one attribute.

Attribute	Description	Reports with this attribute
Cluster Location	Specifies whether the cluster is local or remote.	All, except Capacity Over Time and Object Backup Task Summary
Compliance Status	Restricts the report to information about compliant, non-compliant, or unprotected elements.	• SLA Compliance • Object Protection Summary
Day	Day the task ran.	• Capacity Over Time • Object Backup Task Summary
Latest Local Snapshot Index Status	The indexing status for the most recent local snapshot (Success, Failed, or Pending).	Object Indexing Summary
Local CDP Status	Displays one of the following statuses: • Not Enabled – The CDP-enabled SLA Domain has not been assigned to a virtual machine. • Pending – A CDP-enabled SLA Domain is assigned, but the system is waiting for the CDP filter to be installed, or for the storage policy to be assigned, or for a successful initial snapshot. Local CDP Status is also set to Pending when disks are added or removed. • Taking Snapshot – In the process of taking a snapshot. If the snapshot is successful, the status changes to Active. • Active – CDP is running successfully. • Failed – CDP failed or a snapshot failed. CDP can fail if it has problems handling large bursts of incoming data, or maintaining its logs, for example.	• SLA Compliance • System Capacity • Object Protection Summary
Location	The definition of location varies by object: • Virtual machines – The IPv4 address or FQDN of the vCenter Server. • SQL Server DBs – The FQDN of the Window Server and the SQL Server instance.	All, except Capacity Over Time

Attribute	Description	Reports with this attribute
	• Linux & Unix Hosts – The IPv4 address or FQDN of the Linux or Unix host. • Windows Hosts – The IPv4 address or FQDN of the Windows host. • Nutanix Cluster – The name of the cluster. • Hyper-V Cluster – The name of the cluster. • Managed Volume – The name of the volume.	
Month	Month the task ran.	Capacity Over Time
Object Index Type	Indicates whether the object is Indexable, Unindexable, or Unprotected.	Object Indexing Summary
Object Name	The name of the object that is the subject of the task.	All, except Capacity Over Time
Object Type	Restricts the report to information about objects of the specified types. Supported object types are: • Virtual Machine • Linux & Unix Fileset • Windows Fileset • SQL Server DB • Nutanix Cluster • Hyper-V Cluster • Managed Volumes	All, except Capacity Over Time
Quarter	Quarter the task ran.	Capacity Over Time
SLA Domain	Entry is one of the following: • The name of the SLA Domain that protects the object. • Unprotected • Click on the name of the SLA Domain to manage the domain.	All, except Capacity Over Time
Task Status	Icon representing the state of the task at the time of the entry. The status can be: • Succeeded • Failed • Canceled	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details
Task Type	Restricts the report to information about tasks of the specified types. Supported task types are: • Backup • Archival	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details

Attribute	Description	Reports with this attribute
	• Replication	

Table measures

In addition to charts, reports feature a data table that can be customized with specific measures.

Measure	Default Report Template
Archival Object Count	• SLA Compliance Summary • Object Backup Task Summary • Object Indexing Summary • Protection Tasks Summary • Object Protection Summary • Capacity Over Time • System Capacity
Archival Snapshot Lag	• SLA Compliance Summary • Object Protection Summary
Archive Data Reduction	• Object Protection Summary • Capacity Over Time • System Capacity
Archive Dedup Ratio	• Object Protection Summary • Capacity Over Time • System Capacity
Archive Effective Data Transferred	• Object Protection Summary • Capacity Over Time • System Capacity
Archive Effective Logical Data	• Object Protection Summary • Capacity Over Time • System Capacity
Archive Logical Data Reduction	• Object Protection Summary • Capacity Over Time • System Capacity
Archive Logical Dedup Ratio	• Object Protection Summary • Capacity Over Time • System Capacity
Archive Storage	• Object Protection Summary • Capacity Over Time • System Capacity
Archive Storage Growth	• Object Protection Summary • Capacity Over Time • System Capacity

Measure	Default Report Template
Archived On Demand Snapshots	• SLA Compliance Summary • Object Indexing Summary
Archived SLA Snapshots	• SLA Compliance Summary • Object Indexing Summary • Object Protection Summary
Archived Snapshots	• SLA Compliance Summary • Object Indexing Summary • Object Protection Summary
Average Duration	• Protection Tasks Summary
Canceled Tasks	• Protection Tasks Summary
Data Reduction	• Protection Tasks Summary • Protection Tasks Details
Data Stored	• Protection Tasks Summary • Protection Tasks Details
Data Transferred	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details
Data Transferred vs Stored	• Protection Tasks Summary
Dedup Ratio	• Protection Tasks Summary • Protection Tasks Details
Duration	• Protection Tasks Details • Recovery Task Details
Effective Throughput	• Protection Tasks Summary • Protection Tasks Details
End Time	• Protection Tasks Details • Recovery Task Details
Failed Tasks	• Protection Tasks Summary
In Compliance	• SLA Compliance Summary • Object Protection Summary
Latest Archived Snapshot	• SLA Compliance Summary • Object Indexing Summary
Latest Local Indexed Snapshot	• Object Indexing Summary
Latest Local Snapshot	• SLA Compliance Summary • Object Indexing Summary

Measure	Default Report Template
	• Object Protection Summary
Local Data Reduction	• Object Protection Summary • Capacity Over Time • System Capacity
Local Data Transferred	• Object Protection Summary • Capacity Over Time • System Capacity
Local Dedup Ratio	• System Capacity • Capacity Over Time • Object Protection Summary
Local Effective Logical Data	• System Capacity • Capacity Over Time • Object Protection Summary
Local Logical Data Reduction	• System Capacity • Capacity Over Time • Object Protection Summary
Local Logical Dedup Ratio	• System Capacity • Capacity Over Time • Object Protection Summary
Local On Demand Snapshots	• SLA Compliance Summary • Object Indexing Summary
Local SLA Snapshots	• SLA Compliance Summary • Object Indexing Summary
Local Snapshots	• SLA Compliance Summary • Object Indexing Summary • Object Protection Summary
Local Snapshots Indexed	• Object Indexing Summary
Local Snapshots Pending For Indexing	• Object Indexing Summary
Local Snapshots Unindexed	• Object Indexing Summary
Local Storage	• System Capacity • Capacity Over Time • Object Protection Summary
Local Storage Growth	• System Capacity • Capacity Over Time • Object Protection Summary

Measure	Default Report Template
Logical Data Protected	• Protection Tasks Summary • Protection Tasks Details
Logical Data Reduction	• Protection Tasks Summary • Protection Tasks Details
Logical Dedup Ratio	• Protection Tasks Summary • Protection Tasks Details
Long Running Tasks	• Object Backup Task Summary
Missed Objects	• Protection Tasks Summary • Protection Tasks Details
Missed Snapshots	• SLA Compliance Summary • Object Protection Summary
Object Count	• Object Backup Task Summary • Object Indexing Summary • Capacity Over Time • System Capacity
Object Logical Size	• System Capacity • Capacity Over Time • Object Protection Summary
On Time Tasks	• Object Backup Task Summary
Out of Compliance	• SLA Compliance Summary • Object Protection Summary
Protected On	• SLA Compliance Summary • Object Backup Task Summary • Object Indexing Summary • Object Protection Summary • System Capacity
Queued Time	• Protection Tasks Details • Recovery Task Details
Replicated Snapshots	• SLA Compliance Summary • Object Indexing Summary
Replica Storage	• System Capacity • Capacity Over Time • Object Protection Summary
Replica Storage Growth	• System Capacity • Capacity Over Time • Object Protection Summary

Measure	Default Report Template
Start Time	• Protection Tasks Details • Recovery Task Details
Successful Tasks	• Protection Tasks Summary
Task Count	• Protection Tasks Summary • Object Backup Task Summary
Task Count by Status	• Protection Tasks Summary
Total Files Transferred	• Protection Tasks Summary • Protection Tasks Details • Recovery Task Details
Total Snapshots	• SLA Compliance Summary • Object Indexing Summary • Object Protection Summary

Table attributes

In addition to charts, reports feature a data table that can be customized with specific attributes.

Attribute	Default Report Template
Archival Target	All except Protection Tasks Summary
Cluster Location	All
Compliance Status	• SLA Compliance • Object Protection Summary
Current Task Status	Object Backup Task Summary
Day	• Protection Tasks Summary • Capacity Over Time
Direct Archive	All
Failure Reason	Recovery Task Details
Hour	Protection Tasks Summary
Last Successful Task	Object Backup Task Summary
Latest Local Snapshot Index Status	Object Indexing Summary
Location	All
Month	• Protection Tasks Summary • Capacity Over Time
Object Index Type	Object Indexing Summary
Object Name	All
Object Type	All

Attribute	Default Report Template
Organization	• SLA Compliance • Object Indexing Summary • Object Protection Summary • Capacity Over Time • System Capacity
Quarter	• Protection Tasks Summary • Capacity Over Time
Recovery Point	Recovery Task Details
Recovery Point Type	Recovery Task Details
Replication Source	All
Replication Target	All
SLA Domain	All
Snapshot Consistency	Protection Tasks Details
Task Status	• Protection Tasks Summary • Protection Tasks Details • Recovery Task Details
Task Type	• Protection Tasks Details • Recovery Task Details
Username	Recovery Task Details
Year	Protection Tasks Summary

Report filters

Filters restrict the content that appears in a report.

Filter	Description	Reports with this filter
Archival Compliance Status	Restricts the report to archival objects with one of these statuses: • In Compliance • Out of Compliance • Unprotected	SLA Compliance Summary
Replication Compliance Status	Restricts the report to replication objects with one of these statuses: • In Compliance • Out of Compliance • Unprotected	SLA Compliance Summary
Cluster Location	Restricts the report to information from local or remote clusters.	All, except Object Backup Task Summary
Compliance Status	Restricts the report to objects with one of these statuses:	SLA Compliance Summary

Filter	Description	Reports with this filter
	• In Compliance • Out of Compliance.	
Date	Restricts the report information to a selected date range. Supported ranges are: • Past 24 Hours • Past 7 Days • Past 30 Days • Past Year • Custom Range, which is a start date to an end date.	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details • Capacity Over Time
Location	Restricts the report to information from specified locations. The definition of location varies by object: • Virtual machines – The IPv4 address or FQDN of the vCenter Server. • SQL Server DBs – The FQDN of the Window Server and the SQL Server instance. • Linux & Unix Hosts – The IPv4 address or FQDN of the Linux or Unix host. • Windows Hosts – The IPv4 address or FQDN of the Windows host. • Nutanix Cluster – The name of the cluster. • Hyper-V Cluster – The name of the cluster. • Managed Volume – The name of the volume. Search for specific locations by typing a portion of the name of a location in **Search by Name**. To add a location, click **Add** next to the entry for the location.	All, except Object Task Backup Summary
Object Index Type	Restricts the report to information about objects of the specified index type. Index types include: • Indexable • Unindexable • Unprotected	Object Indexing Summary
Object Name	Restricts the report to information from selected objects. Search for specific objects by typing a portion of the object name in **Search by Name**.	All, except Object Task Backup Summary

Filter	Description	Reports with this filter
	To add an object, click **Add** next to the entry for the object.	
Object Type	Restricts the report to information about the specified object types: • VMware Virtual Machines • Linux & Unix Filesets • Windows Filesets • SQL Server DBs • Nutanix Cluster • Hyper-V Cluster • Managed Volumes	All
Range	Restricts the report to information from the selected time range or number of snapshots: • Past 24 Hours • Past 7 Days • Past 30 Days • Past 90 Days • Past 365 Days • Last Snapshot • Last 2 Snapshots • Last 3 Snapshots • Start of Protection (Default)	SLA Compliance Summary
SLA Domain	Filters tasks by the selected SLA Domain. Search for specific SLA Domains by typing a portion of the name of an SLA Domain in **Search by Name**.	All
Task Status	Restricts the report to information about tasks in the selected statuses: • Succeeded • Canceled • Failed	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details
Task Types	Restricts the report to information about tasks of the specified types. Supported task types are: • Backup • Archival • Replication	• Protection Tasks Summary • Protection Tasks Details • Recovery Tasks Details • Object Protection Summary

Creating a custom report

Assign the attributes and measures that will appear in the custom report.

Procedure

1. Log in to the Rubrik CDM web UI.

2. On the left-side menu, select **Reports** > **Gallery**.
   A list of all available reports appears.
3. From the Gallery, click **Create Report** in the top right corner.
4. Enter a name for the report.
5. Select one of the default reports as a report template, then click **Next**.
6. Configure the top left chart by assigning a chart name, then choose the attribute and the measure that will appear in the chart.
7. Choose the chart type, then click **Next**.
8. Repeat step 6 and step 7 for the top-right chart.
9. Select all the attributes and measures that should appear in the table for the report, then click **Next**.
10. In the left column, select a filter type.
11. From the right-side list, select entries to add to the menu for the selected filter type, then click **Finish**.

Result

The customized report appears.

Creating a Daily Capacity Over Time report

Use the default Capacity Over Time report to create a custom Daily Capacity Over Time report.

Context

Change each chart's attribute from Month to Day to see the daily amounts of local data transferred and storage used. Include the SLA Domain and Object Name attributes in the table to provide an additional level of sorting. Limit the report data to the last seven days and limit the SLA Domains to a select group.

Procedure

1. Log in to the Rubrik CDM web UI.
2. On the left-side menu, select **Reports** > **Gallery**.
   A list of all available reports appears.
3. From the Gallery, click **Create Report** in the top right corner.
   The Name & Template pane of the Create Report wizard appears.
4. Enter a name for the report, such as Daily Capacity Over Time.
5. Select **Capacity Over Time** as the report template, then click **Next**.
   The Top Left Chart pane appears.
6. Keep the chart name as **Local Data Transferred**, choose **Day** for the attribute, and keep **Local Data Transferred** as the measure.

   Alternatively, choose a different measure and change the name of the chart to match.
7. Choose **Vertical** or **Line** for the chart type, then click **Next**.
   The Top Right Chart pane appears.
8. Keep the chart name as **Total Capacity**, choose **Day** for the attribute, and keep **Local Storage** for the measure.

   Alternatively, choose a different measure and change the name of the chart to match.
9. Choose **Vertical** or **Line** for the chart type, then click **Next**.

   The Table pane appears.
10. Select all the attributes and measures that should appear in the table for the report, then click **Next**.
    Clear **Month**, then select **Day**, **SLA Domain** and **Object Name** in addition to the other default choices already selected
    The Filter pane appears.
11. In the left column, select the **Date** filter.

12. In the right column, select **Past 7 Days** to limit the data in the report to the past seven days.
13. In the left column, select **SLA Domain**.
14. In the right column, select the SLA Domains to include in the report.
15. Click **Finish**.

Result

The customized report, Daily Capacity Over Time, appears.

Modifying a custom report

Edit existing custom reports to change attributes, measures, and charts as necessary.

Procedure

1. Log in to the Rubrik CDM web UI.
2. On the left-side menu of the web UI, click **Reports** > **Gallery**.
   A list of all available reports appears.
3. Optional: To search the list, type a string in the **Search by Name** field.
4. From the Gallery, click the name of a custom report.
5. Open the ellipsis menu and select **Edit Report**.
6. Select options for the charts, data table, and filters, then click **Update**.

Result

The report is updated with the new information.

Transaction log metadata retention

The retention time for metadata about jobs that protect database transaction logs is 30 days by default.

Reports are constructed from metadata about the jobs the Rubrik cluster performs. The Rubrik cluster stores metadata in an internal database. The metadata retention time for jobs other than protection jobs for database transaction logs is one year. Metadata for jobs that protect database transaction jobs can become voluminous for highly active databases. The retention time of metadata for these jobs can be changed from the initial default of 30 days.

Changing transaction log metadata retention

Change the retention time of metadata for jobs that protect database transaction logs by making an API call.

Procedure

1. Log in to the web UI.
2. Open the account menu in the upper right corner and select **API Token Manager**.
3. On the API Token Manager page, click **+**.
4. Complete the Duration and tag fields and click **Generate**.
5. Click **Copy**.
6. Paste the token in a scratch file.
7. In a new browser window, navigate to `https://cluster_address/docs/v1/playground`.
   Replace *cluster_address* with the hostname or IPv4 address of the Rubrik cluster.
   The Rubrik REST API Explorer page appears.

8. Click **Authorize**.
   The authorization dialog appears.
9. Paste the token into the value field and click **Authorize**.
   The authorization dialog closes.
10. Click **/reports**.
    A list of API endpoints for reports appear.
11. Click **PATCH /report/config**.
12. Click **Try it out**.
    A text field for the `new_values` object that contains the new configuration values appears.
13. Type a new value for the `"cleanupReportJobInstanceForLogJobs"` parameter after the `:` character.

    The value specifies the retention period in days. The default value is 30.
14. Click **Execute**.
    The page updates with a response code for the API call. A response code of 200 indicates a successful API call.

Result

Metadata for jobs to protect database transaction logs are retained for the specified number of days.

Exporting a report data table

Export a CSV-formatted version of a report data table to the computer that is running the web browser.

Procedure

1. Log in to the Rubrik CDM web UI.
2. On the left-side menu of the web UI, click **Reports** > **Gallery**.
   A list of all available reports appears.
3. Optional: To search the list, type a string into the Search by Name field.
4. Click the name of a report.
5. At the top of the report, click **CSV**.

   Depending on the Download settings of the web browser, one of the following occurs:

   - The browser downloads the report to the default download folder.
   - The browser opens a Save As dialog box.
6. (Save As dialog box) Select a location on the computer that is running the web browser.
7. (Save As dialog box) Click **Save**.

Result

The browser downloads the CSV table to the selected location.

Report schedules

The Rubrik cluster can send reports to a list of email recipients according to a set schedule.

The schedule can specify daily reports and monthly reports based on specified requirements.

Scheduling reports

Schedule a report to specify times for the Rubrik cluster to send an HTML email containing the report charts and the first 100 lines of the report table. The email includes all data from the report table in an attached CSV file.

Procedure

1. Log in to the Rubrik CDM web UI.
2. On the left-side menu of the web UI, click **Reports** > **Gallery**.
   A list of all available reports appears.
3. Optional: To search the list, type a string into the **Search by Name** field.
4. Click the name of a report.
5. At the top of the report, click **Schedule**.
   The Schedule Report dialog box appears.
6. In **Email Address**, type a valid email address. To specify multiple recipients, use commas to separate each address.
7. Optional: Clear the **CSV** box to omit the CSV file of report data from the report emails.
   - For daily emails, click **Every Day at** and select the time of day when. For example, select 8:00 AM to send an email to each designated recipient every day at 8:00 AM.
   - To send emails on specific days of the week, click **Every Week on** and select the days of the week.

     For example, select Monday and Thursday. More than one day of the week can be selected.
   - For monthly emails, select the date of the month and the time of day when emails should be sent.

     For example, select the 15th of the month at 12:00 AM. Only one date can be selected.
8. Optional: To add another schedule, click **+**.
9. Click **Schedule** after the last schedule has been entered.

Result

The Rubrik cluster sends reports to the listed email addresses according to the specified schedule.

Changing ownership of a scheduled report email subscription

When a user who owns the subscription to a scheduled report can no longer access the Rubrik cluster, the cluster administrator can assume ownership of the subscription.

Procedure

1. Log in to the Rubrik CDM web UI as a user with administrative privileges over the cluster.
2. On the left-side menu of the web UI, select **Reports** > **Gallery**.
   A list of all available reports appears.
3. Optional: To search the list, type a string into the "Search by Name" field.
4. Click the name of a report.
5. At the top of the report, click **Schedule**.
   The Schedule Report dialog box appears.
6. Click the **Owned By menu**.
7. Select the current user.
8. Click **Schedule**.

Result

The assigned user is now the owner of the subscription.

Changing a report schedule

Modify a report subscription to change the recipient email address and to change the subscription frequency and time.

Procedure

1. Log in to the Rubrik CDM web UI.
2. On the left-side menu of the web UI, click **Reports** > **Gallery**.
3. Optional: To search the list, type a string into the **Search by Name** field.
4. Click the name of a report.
5. At the top of the report, click **Schedule**.
   The Schedule Report pane appears.
6. Make changes to the information in the dialog box.
7. Click **Schedule**.

Result

The Rubrik cluster sends report emails to the recipients listed at the frequency specified in the modified schedule.

Removing report schedules

Remove a report subscription to stop the Rubrik cluster from sending the report by email.

Procedure

1. Log in to the Rubrik CDM web UI.
2. On the left-side menu of the web UI, click **Reports** > **Gallery**.
   A list of the reports available on the cluster appears.
3. Optional: To search the list, type a string into the **Search by Name** field.
4. Click the name of a report.
5. At the top of the report, click **Schedule**.
   The Schedule Report pane appears.
6. Click **X** to delete the schedule from the Schedule Report pane.
7. Click **Schedule** to confirm changes and return to the report.

Result

The Rubrik cluster removes the report scheduling information.