LEOPACK



cicmsvpnsmap

Conducting **I**nner **C**ore and **M**antle **S**olution **V**ector:
Perturbation and **N**ew **S**patial **M**esh **A**daption **P**rogram

Steven J. Gibbons, Oslo

Original document: November 21^{st}, 2001. Updated: October 30^{th}, 2022.

1 cicmsvpnsmap

Conducting **I**nner **C**ore and **M**antle **S**olution **V**ector: **P**erturbation and **N**ew **S**patial **M**esh **A**daption **P**rogram

Essentially identical to cicsvpnsmap but has one extra line in the input file containing the numbers `RCM  NRCM  ISPCM` (see example).

1.1 Subprograms required for cicmsvpnsmap

SUBS subroutines

```
hmfrd.f svfrd.f xarrrd.f hminda.f esnaas.f zcpaas.f
zcpaa2.f svrint.f hmfwt.f xarrwt.f svfwt.f fopen.f
fclose.f gfdcfd.f fnamer.f matop.f
```

SUBS integer function

```
indfun.f
```

BLAS integer function

```
idamax.f
```

BLAS subroutines

```
dgemv.f dgemm.f dtrsm.f dswap.f dger.f  dscal.f
dtrmm.f dtrmv.f
```

LAPACK subroutines

```
xerbla.f dgetrf.f dgetri.f dgetf2.f dlaswp.f dtrtri.f
dtrti2.f
```

LAPACK integer function

```
ilaenv.f
```

LAPACK logical function

```
lsame.f
```

The input file is as follows:

```
condic_case1.intsv                  : Harmonics file
condic_case1.vecsv                  : Vector file
condic_case1.xarrv                  : Radial grid nodes
condic_case1.intsm                  : Harmonics file
condic_case1.vecsm                  : Vector file
condic_case1.xarrm                  : Radial grid nodes
example_aOUTPUT                     : Filename stem
 40  2  20  3   4     4     0.00001  : NRVNW ISPV NRICNW ISPIC IFORMF NNDS DMAG
 2.0    15    3                     : RCM   NRCM  ISPCM  *** (THIS LINE IS DIFFE
 36    36    36   36    36          : LH1   LH2   LH3   LH4   LH5
 1    2   4    20                   : ISV ISM MINC MMAX
```

References