

ECE 266 Lab2 Design Review


Mingjie Ma Chengming Li


University of California, San Diego, La Jolla, CA, USA




Schematic

Dummy Devices for M12 and M13: Top+bottom(DGS are shorted to VSS): 4fin * 12m * 1u Left+Right(D-Itail, GS are shorted to VSS): 4fin * 4m *1u









Comparator Layout

Common Centroid Pattern

ABBA

BAAB

After dummy devices


(D:2 fingers; d: 1fingers)

DDDDDD

DABBAD

DBAABD

DDDDDD





Schematic


Dummy Devices for M17 and M18:


*Top Bottom(DGS - VDD): 1fin * 8m * 400n


2fin * 12m * 400n

Left+Right(GS- VDD, D- FNS/FPS): 1fin * 8m *400n

2fin * 4m * 400n









Comparator Layout

Common Centroid Pattern

ABBA

BAAB

After dummy devices


(D:2 fingers; d: 1fingers)

DDddDDddDD

DAddBBddAD


DBddAAddBD

DDddDDddDD






Top Level Layout





Comparator Layout





RCX Cap Table

†ó comparator_core ×									
No.	Layout Net	Source Net	C Total (F)	CC Total (F)	C+CC Total (F)				
1	VSS	VSS	5.99226E-15	9.00221E-15	1.49945E-14				
2	2	ITAIL	1.12065E-15	1.24908E-14	1.36114E-14				
3	3	FN	1.21612E-15	8.82237E-15	1.00385E-14				
4	VDD	VDD	5.92345E-15	3.71678E-15	9.64023E-15				
5	5	FP	1.31827E-15	8.70704E-15	1.00253E-14				
6	6	FNS	6.53515E-16	4.29652E-15	4.95004E-15				
7	7	FPS	6.66487E-16	3.85037E-15	4.51685E-15				
8	CP	CP	1.01519E-15	5.83630E-15	6.85149E-15				
9	CN	CN	1.01645E-15	5.74597E-15	6.76243E-15				
10	INN	INN	7.40995E-16	4.71160E-15	5.45260E-15				
11	INP	INP	7.11225E-16	4.76377E-15	5.47499E-15				
12	CLK	CLK	6.39664E-16	1.82970E-15	2.46937E-15				
13	CLKB	CLKB	6.13752E-16	9.68238E-16	1.58199E-15				

Source Net	C+CC (F)	Difference(%)
FP	10.0253f	
FN	10.0385f	0.13
CP	6.85f	
CN	6.76f	1.31
INP	5.475f	
INN	5.452f	2.3




Extracted Simulation(Offset) – Process Corners

Detail 🔽 🔾		™ ▼ Mepla	ice 🔽	2 🗹 💌			1 🔘 🥞 🛚		
	Parameter						TT	FF	SS
	crn65gplus_2d5						tt_lvt	ff_lvt	ss_lvt
	crn65gplus_2d5						tt	ff	SS
	temperature						27	27	27
Test	Output	Spec	Weight	Pass/Fail	Min	Max	TT	FF	SS
Lab2_combine:comp_off_TB:2	/INN							<u>_</u>	<u>~</u>
Lab2_combine:comp_off_TB:2	/INP						<u></u>	<u>~</u>	<u></u>
Lab2_combine:comp_off_TB:2	/OUT						<u>L</u>	<u>~</u>	<u>~</u>
Lab2_combine:comp_off_TB:2	/CLK						<u>L</u>	<u></u>	<u></u>
Lab2_combine:comp_off_TB:2	/I0/CNb						<u>L</u>	<u></u>	<u>L</u>
Lab2_combine:comp_off_TB:2	/I0/CPb						<u>L</u>	<u> </u>	<u>L</u>
Lab2_combine:comp_off_TB:2	/10/VDD						<u>L</u>	<u></u>	<u>L</u>
.ab2_combine:comp_off_TB:2	Pwr				1.218u	3.017u	1.512u	3.017u	1.218u
.ab2_combine:comp_off_TB:2	/OFF						<u>L</u>	<u></u>	<u></u>
Lab2_combine:comp_off_TB:2	offset				89.51u	697u	533.9u	89.51u	697u

Test Corners	TT	FF	SS
#1 Iteration	5.545m	6.725m	4.428m
#2 Iteration	533.9u	89.51u	697u



Extracted Simulation(Offset) - Mismatch






Extracted Simulation(Tpd) – Process Corners

	Parameter						TT	FF	SS
	crn65gplus_2d5						tt_lvt	ff_lvt	ss_lvt
	crn65gplus_2d5						tt	ff	SS
	temperature						27	27	27
Test	Output	Spec	Weight	Pass/Fail	Min	Max	TT	FF	SS
			1						
Lab2_combine:comp_tpd_TB:4	/INN						<u>L</u>	<u></u>	<u>L</u>
Lab2_combine:comp_tpd_TB:4	/INP						<u></u>	<u></u>	<u>L</u>
Lab2_combine:comp_tpd_TB:4	/OUT						<u></u>	<u></u>	<u>L</u>
Lab2_combine:comp_tpd_TB:4	/CLK						<u></u>	<u></u>	<u>L</u>
Lab2_combine:comp_tpd_TB:4	/I0/CNb						<u></u>	<u></u>	<u>L</u>
Lab2_combine:comp_tpd_TB:4	/10/CPb						<u></u>	<u></u>	<u>Ľ</u>
Lab2_combine:comp_tpd_TB:4	/10/VDD						<u></u>	<u></u>	<u>L</u>
Lab2_combine:comp_tpd_TB:4	Pwr				1.056u	2.921u	1.273u	2.921u	1.056u
Lab2_combine:comp_tpd_TB:4	offset						eval err	eval err	eval err
Lab2_combine:comp_tpd_TB:4	tpdr				270.5p	457.6p	322.4p	270.5p	457.6p

Test Corners	TT	FF	SS
Tpd(s)	322.4p	270.5p	457.6p





Extracted Simulation(Tpd) - Mismatch





Appendix - #1 Iteration








Appendix - #2 Iteration







Appendix – Metal Color

