NOAA • AOC • SED N43RF AVAPS DROP LOG Lead Tech: Dana Naeher

Project: Atomic 2020 Mission: _____ Flight ID: 20200514 1

Take Off : 1300 Landing: _____ Flt Dir : Hu/Mc

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	191930259	1	0	1351	MM	AOC	FW	
2	200410813	2	0	1351	MM	AOC	FW	
3	191930255	3	0	1351	MM	AOC	FW	
4	195050506	1	0	1403	MM	AOC	NEW	
5	195110269	2	0	1403	MM	AOC	NEW	
6	200530006	3	0	1403	MM	AOC	NEW	
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								
57								

Drop Station Operator Notes

Charge $$ To Options: AOC, NWS, HFIP, NESDIS, ONR, HRD, IR/SST or HRD ONLY – Do not use funding codes!!!

AVAPS Pre-Flight Check:

- If time-premits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and full Flight ID (example 20110823h2).
- Update the Frequency band allocation as required:
  Band A - W53rd, Band B - N42RF, Band C - N43RF, Band D - N49RF, Band E - not allocated
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights. Verify data is available on Remote AVAPS at the FD Station, then terminate the sonde by selecting **Abort** to cancel the sonde initialization. Verify the AVAPS Data mission folder has been created.
- Verify AVAPS PC Time is correct

NOTE: HRD RESEARCH MAY REQUIRE USING "IR SONDES", WHICH ALSO HAVE SLOW FALL CHUTES. DO NOT SHORTEN THE RIBBON ON THE SLOW FALL CHUTE SONDES.

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater – only if cabin pressure sensor has been fixed and re-calibrated
- Select "begin data collection" and verify good data (including Winds) prior to putting sonde in launch tube
- Cut off about ½ of ribbon, Unwind ribbon and flip the screen, Re-wind ribbon, Use orange tape to make a pocket at end of ribbon
- Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing starboard
- Verify the sonde is actively tracking GPS data prior to launch and no Early Launch detect

NOAA • AOC • SED N43RF AVAPS DROP LOG Lead Tech: Dana Naeher

Project: Atomic 2020 Mission: Wind Cal / Sys Test Flt Flight ID: 20200603I1

Take Off : 1400 Z Landing: _____ Flt Dir : Carpenter

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	191920300	1	Ø	1443	Mac	AOC	no initial launch detect	NO
2	193130667	2	Ø	1442	Mac	AOC	backup sonde to 1st drop	✓
3	192730579	3	Ø	1505	Mac	AOC	2nd tasked drop	✓
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								
57								

Drop Station Operator Notes

Charge $$ To Options: AOC, NWS, HFIP, NESDIS, ONR, HRD, IR/SST or HRD ONLY – Do not use funding codes!!!

AVAPS Pre-Flight Check:

- If time-premits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and full Flight ID (example 20110823h2).
- Update the Frequency band allocation as required:
  Band A - W53rd, Band B - N42RF, Band C - N43RF, Band D - N49RF, Band E - not allocated
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights. Verify data is available on Remote AVAPS at the FD Station, then terminate the sonde by selecting **Abort** to cancel the sonde initialization. Verify the AVAPS Data mission folder has been created.
- Verify AVAPS PC Time is correct

NOTE: HRD RESEARCH MAY REQUIRE USING "IR SONDES", WHICH ALSO HAVE SLOW FALL CHUTES. DO NOT SHORTEN THE RIBBON ON THE SLOW FALL CHUTE SONDES.

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater – only if cabin pressure sensor has been fixed and re-calibrated
- Select "begin data collection" and verify good data (including Winds) prior to putting sonde in launch tube
- Cut off about ½ of ribbon, Unwind ribbon and flip the screen, Re-wind ribbon, Use orange tape to make a pocket at end of ribbon
- Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing starboard
- Verify the sonde is actively tracking GPS data prior to launch and no Early Launch detect

NOAA • AOC • SED N43RF AVAPS DROP LOG Lead Tech: Dana Naeher

Project: Atomic 2020 Mission: TS Cristobal Flight ID: 20200605I1

Take Off : 2000Z Landing: _____ Flt Dir : Carpenter / Holmes

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	192741780	1	Ø	2244	Mac	NWS	Pt1, Good	✓
2	190220016	2	Ø	2255			Pt2, Good	✓
3	192620683	3	Ø	2306			Pt3, Good	✓
4	192741750	4	Ø	2317			Pt4, Good	✓
5	185110400	1	Ø	2328			Pt5, Good	✓
6	192740316	2	Ø	2340			Pt6, Good	✓
7	191640160	3	Ø	2353			Pt7, Good	✓
8	185130789	4	Ø	0006			Pt8, Good	✓
9	191640489	1	Ø	0019			Pt9, Good	✓
10	193130163	2	Ø	0031			Pt10, Good	✓
11	190140100	3	Ø	0042			Pt11, Good	✓
12	192540907	4	-0.8	0051			Pt12, Good	✓
13	192530524	1	Ø	0101			Pt13, Good	✓
14	192620613	2	Ø	0110			Pt14, Good	✓
15	191940441	3	Ø	0120			Pt15, Good	✓
16	192450007	4	-Ø.6	0134			Pt16, Good	✓
17	191820276	1	-0.6	0146			Pt17, Good	✓
18	192741748	2	Ø	0156			Pt18, Good	✓
19	191820276	3	Ø	0209			Pt19, Good	✓
20	191640225	4	Ø	0216			Pt20, Weak GPS	✓
21	192741433	1	Ø	0225	↓	↓	Pt21, Weak GPS	meh
22	192750286	2	Ø	0227	MAC	NWS	Pt21, Weak GPS also B/u to 21	meh
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								
57								

Drop Station Operator Notes

Charge $$ To Options: AOC, NWS, HFIP, NESDIS, ONR, HRD, IR/SST or HRD ONLY – Do not use funding codes!!!

AVAPS Pre-Flight Check:

- If time-premits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and full Flight ID (example 20110823h2).
- Update the Frequency band allocation as required:
  Band A - W53rd, Band B - N42RF, Band C - N43RF, Band D - N49RF, Band E - not allocated
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights. Verify data is available on Remote AVAPS at the FD Station, then terminate the sonde by selecting **Abort** to cancel the sonde initialization. Verify the AVAPS Data mission folder has been created.
- Verify AVAPS PC Time is correct

NOTE: HRD RESEARCH MAY REQUIRE USING "IR SONDES", WHICH ALSO HAVE SLOW FALL CHUTES. DO NOT SHORTEN THE RIBBON ON THE SLOW FALL CHUTE SONDES.

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater – only if cabin pressure sensor has been fixed and re-calibrated
- Select "begin data collection" and verify good data (including Winds) prior to putting sonde in launch tube
- Cut off about ½ of ribbon, Unwind ribbon and flip the screen, Re-wind ribbon, Use orange tape to make a pocket at end of ribbon
- Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing starboard
- Verify the sonde is actively tracking GPS data prior to launch and no Early Launch detect

NOAA • AOC • SED N43RF AVAPS DROP LOG Lead Tech: Dana Naeher

Project: Atomic 2020 Mission: TS Cristobal Flight ID: 2020060611

Take Off : 2000Z Landing: _____ Flt Dir : Carpenter / Holmes

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	192540924	1	-0.7	2143Z	Mac	NWS	IP1	✓
2	191930454	2	-0.5	2155Z			1st midpoint in	✓
3	191640487	3	-0.3	2206Z			1st Center	✓
4	191820266	4	-0.8	2219			1st mid out	✓
5	192521113	1	Ø	2231			1st end pt	✓
6	195020022	2	-0.7	2257			IP2 / NO GPS	X
7	194941097	3	-0.7	2258			IP2 backup	✓
8	192520674	4	-1.0	2308			2nd MID IN	✓
9	194940958	1	-0.3	2320			2nd CTR	✓
10	195020021	2	-0.4	2333			2nd MID OUT	✓
11	195020020	3	-0.5	2344			2nd END PT	✓
12	194491098	4	-0.6	0001			IP3	✓
13	185740067	1	Ø	0013			3rd MID IN	✓
14	191740846	2	Ø	0028			3rd CTR	✓
15	195020019	3	-0.5	0037			3rd MID OUT / NO GPS	X
16	192450958	4	Ø	0038			3rd MID OUT Backup	✓
17	185050754	1	-0.4	0050			3rd END PT	✓
~~18~~	~~191050909~~	~~2~~	~~Ø~~					
19		~~3~~						
20		~~4~~			Mac	NWS		
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								
57								

Drop Station Operator Notes

Charge $$ To Options: AOC, NWS, HFIP, NESDIS, ONR, HRD, IR/SST or HRD ONLY – Do not use funding codes!!!

AVAPS Pre-Flight Check:

- If time-premits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and full Flight ID (example 20110823h2).
- Update the Frequency band allocation as required:
  Band A - W53rd, Band B - N42RF, Band C - N43RF, Band D - N49RF, Band E - not allocated
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights. Verify data is available on Remote AVAPS at the FD Station, then terminate the sonde by selecting **Abort** to cancel the sonde initialization. Verify the AVAPS Data mission folder has been created.
- Verify AVAPS PC Time is correct

NOTE: HRD RESEARCH MAY REQUIRE USING "IR SONDES", WHICH ALSO HAVE SLOW FALL CHUTES. DO NOT SHORTEN THE RIBBON ON THE SLOW FALL CHUTE SONDES.

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater – only if cabin pressure sensor has been fixed and re-calibrated
- Select "begin data collection" and verify good data (including Winds) prior to putting sonde in launch tube
- Cut off about ½ of ribbon, Unwind ribbon and flip the screen, Re-wind ribbon, Use orange tape to make a pocket at end of ribbon
- Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing starboard
- Verify the sonde is actively tracking GPS data prior to launch and no Early Launch detect

NOAA • AOC • SED N43RF AVAPS DROP LOG Lead Tech: Dana Naeher

Project: ~~Atomic 2020~~ Mission: SFMF Cal Flight ID: 20200625I1

Take Off : 2132 Z Landing: _____ Flt Dir : Lundry

Drop # Point # Rcvr # Launch Time Status

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	185150255	1	-1.0	2207	TR	AOC	16K ft.	✓
2	193130635	1	0	2330	TR	AOC	5K ft.	✓
3								
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								
57								

Drop Station Operator Notes

Charge $$ To Options: AOC, NWS, HFIP, NESDIS, ONR, HRD, IR/SST or HRD ONLY – Do not use funding codes!!!

AVAPS Pre-Flight Check:

- If time-premits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and full Flight ID (example 20110823h2).
- Update the Frequency band allocation as required:
  Band A - W53rd, Band B - N42RF, Band C - N43RF, Band D - N49RF, Band E - not allocated
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights. Verify data is available on Remote AVAPS at the FD Station, then terminate the sonde by selecting **Abort** to cancel the sonde initialization. Verify the AVAPS Data mission folder has been created.
- Verify AVAPS PC Time is correct

NOTE: HRD RESEARCH MAY REQUIRE USING "IR SONDES", WHICH ALSO HAVE SLOW FALL CHUTES. DO NOT SHORTEN THE RIBBON ON THE SLOW FALL CHUTE SONDES.

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater – only if cabin pressure sensor has been fixed and re-calibrated
- Select "begin data collection" and verify good data (including Winds) prior to putting sonde in launch tube
- Cut off about ½ of ribbon, Unwind ribbon and flip the screen, Re-wind ribbon, Use orange tape to make a pocket at end of ribbon
- Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing starboard
- Verify the sonde is actively tracking GPS data prior to launch and no Early Launch detect