AVAPS Drop Log

Project: HX 2020 Mission: TS Zeta Flight ID: 20201025N1

Take Off: _____ Landing: _____ Flt Dir: Kacen/Parrott Launcher S/N: 2

32/36

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	201440502	1	Ø	1758	SCP	NWS		✓
2	194920523	2	Ø	1809				✓
3	201430144	3	Ø	1826				✓
4	201440265	4	Ø	1837				✓
5	201420744	1	Ø	1850				✓
6	201520831	2	Ø	1904				✓
7	194820827	3	Ø	1920				✓
8	201440287	4	Ø	1931				✓
9	201430149	1	Ø	1952				✓
10	201450440	2	-0.5	2008			no LD	X
11	195130537	3	Ø	2008			b/u for 10	✓
12	195120788	4	Ø	2022			lost LD / fast	X
13	201520838	1	Ø	2022			b/u for 12	✓
14	200240385	2	Ø	2030				✓
15	201520839	3	Ø	2097			fast	X
16	201440501	4	Ø	2048			b/u for 15	✓
17	201350166	1	Ø	2055				✓
18	195051123	2	Ø	2103				✓
19	201440298	3	Ø	2113				✓
20	201430153	4	-0.4	2123			No LD	X
21	201520836	1	-0.4	2124			B/U for 20	✓
22	194830216	2	Ø	2133				✓
23	201440404	3	Ø	2145				✓
24	201430171	4	Ø	2159				✓
25	194240252	1	Ø	2211				✓
26	194250484	2	Ø	2219				✓
27	201440355	3	Ø	2229				✓
28	201440233	4	Ø	2239				✓
29	201730206	1	Ø	2252				✓
30	201430174	2	Ø	2305				✓
31	201450551	3	Ø	2314				✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	201520330	4	Ø	2326	SCP	NWS		✓
33	194240227	1	Ø	2335				✓
34	201440401	2	Ø	2346				✓
35	201740088	3	Ø	0005				✓
36	201440136	4	Ø	0024				✓
37	~~201740659~~	~~4~~	~~Ø~~				NO DROP	
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricanes 2020 Mission: Zeta Flight ID: 20201026N1

Take Off: 0531Z Landing: _____ Flt Dir: Hathaway Launcher S/N: 2

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	2014 30011	1	-0.2	0549Z	NGU	NWS	Point #1, bad temp at 300 mbar	X
2	2014 505 20	2	-0.3	0605Z			Point #2, fast fall	X
3	2014 50553	3	-0.5	0607Z			Point #2 backup	✓
4	2023 11606	4	+0.2	0622Z			Point #3	✓
5	2023 11588	1	+0.2	0637Z			Point #4	✓
6	2017 40657	2	-0.5	0653Z			Point #5	✓
7	2023 11499	3	+0.4	0710Z			Point #6, noisy winds	✓
8	2023 11603	4	0.0	0722Z			Point #7	✓
9	2023 11550	1	+0.2	0737Z			Point #8	✓
10	202 340243	2	0.0	0750Z			Point #9	✓
11	2030 30526	3	-0.3	0806Z			Point #10	✓
12	2030 30528	4	-0.3	0821Z			Point #11	✓
13	202730016	1	-0.2	0831Z			Point #12	✓
14	2027 30049	2	-0.2	0851Z			Ad hoc sonde	✓
15	2030 30523	3	-0.2	0904Z			Point #13	✓
16	203030515	4	-0.2	0914Z			Point #14	✓
17	202730014	1	-0.2	0928Z			Point #15, no launch detect	X
18	202730050	2	-0.7	0928Z			Point #15 backup	✓
19	2023 11579	3	+0.3	0936Z			Point #16, fast fall	X
20	2027 21726	4	-0.2	0938Z			Point #16 backup	✓
21	2030 30532	1	-0.2	0948Z			Point #17, late winds	X
22	2030 30519	2	-0.2	0949Z			Point #17, backup	✓
23	194410 149	3	+0.3	1000Z			Point #18, fast fall	X
24	2014 30147	4	-0.1	1001Z			Point #18 backup PTH died	X
25	2014 40020	1	-0.1	1014Z			Point #19	✓
26	1943 20259	2	0.0	1030Z			Point #20	✓
27	1943 20249	3	-0.2	1037Z			Point #21	✓
28	202721727	4	-0.1	1054Z			Point #22	✓
29	201440022	1	-0.3	1107Z			Point #23	✓
30	201440359	2	-0.1	1115Z			Point #24	✓
31	2030 30531	3	-0.2	1124Z			Point #25	✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	201440296	4	-0.1	1133Z	NGU	NWS	Point #26	✓
33	203030518	1	0.0	1148Z			Point #27	✓
34	203030514	2	-0.3	1204Z			Point #28, no launch detect	X
35	203040939	3	-0.2	1204Z			Point #28, backup	✓
36	2015 20258	4	-0.2	1213Z			Point #29	✓
37	201430151	1	-0.2	1223Z			Point #30	✓
38	201430169	2	0.0	1231Z			Point #31	✓
39	202730615	3	-0.2	1253Z			Point #32	✓
40	201440259	4	-0.1	1317Z			Point #33	✓
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: _____ Mission: Zeta Flight ID: 20201026N2

Take Off: _____ Landing: _____ Flt Dir: Parrish Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	202 270 599	1	Ø	1759	JEH	NWS		✓
2	201 520 274	2	Ø	1813	^	^		✓
3	201 520 306	3	Ø	1822				✓
4	201 651 060	4	Ø	1833				✓
5	201 440 021	1	Ø	1843				✓
6	203 310 481	2	Ø	1855				✓
7	203 250 051	3	Ø	1906				✓
8	202 270 031	4	Ø	1917				✓
9	202 270 600	1	Ø	1929				✓
10	202 270 032	2	Ø	1942				✓
11	201 520 302	3	Ø	1954				✓
12	201 520 271	4	Ø	2006				✓
13	201 520 288	1	Ø	2023				✓
14	202 260 253	2	Ø	2033				✓
15	201 440 389	3	Ø	2044				✓
16	203 250 052	4	-0.6	2054				✓
17	203 210 093	1	Ø	2105				✓
18	201 520 237	2	Ø	2114				✓
19	201 440 360	3	Ø	2138				✓
20	203 320 224	4	Ø	2146				✓
21	201 440 630	1	Ø	2156				✓
22	201 520 322	2	Ø	2205				✓
23	203 210 177	3	Ø	2215			fast fall?	
24	201 651 034	4	Ø	2218			Backup	✓
25	201 520 234	1	Ø	2225				✓
26	201 520 239	2	Ø	2236				✓
27	201 520 303	5	Ø	2246				✓
28	203 250 054	3	Ø	2252				✓
29	201 520 259	4	Ø	2303			No temp, hum	
30	201 520 280	1	Ø	2305			Backup	✓
31	201 651 053	2	Ø	2314	JEH	NWS		✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	201 520 235	3	Ø	2325	JSH	NWS		✓
33	201 520 236	4	Ø	2335				✓
34	201 520 304	1	Ø	2348				✓
35	201 520 270	2	Ø	—			No bunch detect	
36	201 520 269	3	Ø	2359				✓
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricanes 2020 Mission: Zeta Flight ID: 20201027N1

Take Off: _____ Landing: _____ Flt Dir: Hathaway Launcher S/N: 2

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	201740729	1	0.0	0553Z	N6U	NWS	Point #1	✓
2	2026 20523	2	-0.1	0609Z			Point #2	✓
3	2023 11594	3	0.0	0625Z			Point #3	✓
4	2015 20305	4	-0.4	0642Z			Point #4	✓
5	2022 70654	1	-0.2	0657Z			Point #5	✓
6	2033 20204	2	-0.2	0714Z			Point #6	✓
7	2032 50210	3	0.0	0727Z			Point #7	✓
8	2023 20539	4	0.0	0740Z			Point #8	✓
9	2026 20556	1	-0.1	0753Z			Point #9	✓
10	2033 20201	2	-0.1	0804Z			Point #10	✓
11	202640053	3	-0.1	0815Z			Point #11	✓
12	2023 11573	4	0.0	0826Z			Point #12	✓
13	202630731	1	0.0	0838Z			Point #13	✓
14	202610580	2	+0.1	0850Z			Point #14	✓
15	203310496	3	-0.1	0903Z			Point #15	✓
16	2026 20573	4	0.0	0914Z			Point #16	✓
17	2033 20248	1	0.0	0928Z			Point #17	✓
18	203320249	2	-0.3	0940Z			Point #18	✓
19	202620596	3	+0.1	0951Z			Point #19	✓
20	202640052	4	-0.1	1002Z			Point #20	✓
21	2026 20595	1	0.0	1019Z			Point #21	✓
22	202440386	2	+0.1	1026Z			Point #28	✓
23	2032 50207	3	-0.1	1036Z			Point #27 CPA	✓
24	2022 70542	4	0.0	1058Z			Point #29	✓
25	2032 50057	1	-0.2	1107Z			Point #30	✓
26	2026 20570	2	-0.1	1122Z			Point #31	✓
27	2023 11570	3	0.0	1135Z			Point #32	✓
28	203250209	4	-0.1	1154Z			Point #33	✓
29		1						
30		2						
31		3						

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: 2020 Hurricanes Mission: TS Eta Flight ID: 20201107N1

Take Off: _____ Landing: _____ Flt Dir: Henning Launcher S/N: 2

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	201441187	1	-0.4	0544Z	NGU	NWS	Point #1	✓
2	20231615	2	0.0	0601Z			Point #2	✓
3	2015 20240	3	0.0	0616Z			Point #3	✓
4	20291036 1	4	0.0	0631Z			Point #4	✓
5	201441188	1	-0.1	0646Z			Point #5	✓
6	202610461	2	0.0	0701Z			Point #6	✓
7	202730132	3	0.0	0716Z			Point #7	✓
8	20261 0494	4	0.0	0729Z			Point #8	✓
9	20261 0508	1	0.0	0746Z			Point #9	✓
10	20261 0451	2	+0.1	0759Z			Point #10, messy wind dir	✓
11	20263 0338	3	+0.1	0823Z			Point #11	✓
12	20261 0505	4	0.0	0841Z			Point #12	✓
13	20261 0462	1	0.0	0858Z			Point #13	✓
14	20261 0510	2	-0.1	0916Z			Point #14	✓
15	20261 0454	3	+0.2	0929Z			Point #15	✓
16	20261 0458	4	+0.3	0943Z			Point #16	✓
17	201441163	1	0.0	0956Z			Point #17	✓
18	20261 0459	2	+0.1	1009Z			Point #18	✓
19	202610493	3	0.0	1016Z			Point #19	✓
20	20262 0923	4	+0.2	1030Z			Point #20, no launch detect	✗
21	201441248	1	+0.1	1030Z			Point #20 backup	✓
22	20261 0499	2	0.0	1044Z			Point #21	✓
23	201650999	3	-0.1	1055Z			Point #22	✓
24	202610456	4	+0.1	1101Z			Point #23	✓
25	202640047	1	+0.1	1115Z			Point #24	✓
26	202610455	2	0.0	1124Z			Point #25	✓
27	20261 0504	3	+0.2	1133Z			Point #26	✓
28	20261 0509	4	0.0	1140Z			Point #27	✓
29	202610498	1	+0.1	1153Z			Point #28	✓
30	202530143	2	+0.2	1210Z			Point #29	✓
31	202621470	3	+0.3	1223Z			Point #30	✓

Started ajar diverts →

Ended diverts →

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	2026104 52	4	+0.1	1236Z	NGU	NWS	Point #31, bad winds	✗
33	2029103 77	1	+0.2	1238Z	1	1	Point #31 backup	✓
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricanes 2020 Mission: TS Eta Flight ID: 20201108N1

Take Off: 0531Z Landing: _____ Flt Dir: Henning Launcher S/N: 2

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203310572	1	-0.4	0559Z	NGU	NWS	Point #1	✓
2	202270653	2	-0.3	0612Z			Point #2	✓
3	203440041	3	-0.3	0624Z			Point #3, bad winds	✗
4	203250205	4	-0.3	0626Z			Point #3 backup	✓
5	203310563	1	-0.4	0636Z			Point #4	✓
6	203440035	2	-0.4	0651Z			Point #5	✓
7	203310573	3	-0.4	0703Z			Point #6	✓
8	203310616	4	-0.4	0712Z			Point #7	✓
9	202311595	1	+0.1	0721Z			Point #8, CPA	✓
10	203310575	2	-0.3	0732Z			Point #9	✓
11	203310559	3	-0.2	0742Z			Point #10	✓
12	200730576	4	0.0	0753Z			Point #11, CPA	✓
13	203320199	1	-0.3	0804Z			Point #12, CPA	✓
14	203250208	2	-0.1	0816Z			Point #13, CPA	✓
15	203310574	3	-0.4	0837Z			Point #14, bad winds	✗
16	203240789	4	0.0	0839Z			Point #14 backup	✓
17	202270597	1	-0.1	0851Z			Point #15	✓
18	203240795	2	-0.1	0901Z			Point #16	✓
19	203310625	3	-0.3	0911Z			Point #17	✓
20	202270139	4	0.0	0923Z			Point #18	✓
21	203310571	1	-0.3	0943Z			Point #19	✓
22	203240796	2	0.0	1000Z			Point #20	✓
23	203310562	3	-0.1	1021Z			Point #21	✓
24	201520275	4	-0.2	1034Z			Point #22, no LD	✗
25	202270141	1	0.0	1034Z			Point #22 backup	✓
26	202260256	2	-0.1	1049Z			Point #23	✓
27	202721655	3	+0.1	1102Z			Point #24	✓
28	203520457	4	-0.2	1117Z			Point #25	✓
29	203231092	1	0.0	1133Z			Point #26, no LD	✗
30	203540070	2	-0.3	1133Z			Point #26, backup	✓
31	203520510	3	-0.3	1148Z			Point #27	✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	203540084	4	-0.2	1203Z	NGU	NWS	Point #28	✓
33	203431513	1	-0.2	1219Z	|	|	Point #29	✓
34	203310510	2	-0.1	1233Z	|	|	Point #30	✓
35	203440021	3	-0.3	1248Z	|	|	Point #31	✓
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

= 1235000

AVAPS Drop Log

Project: Hurricanes 2020 Mission: TS Eta Flight ID: 20201110N1

Take Off: _____ Landing: _____ Flt Dir: Henning Launcher S/N: 2

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203030860	1	-0.1	0604Z	NGU	NWS	Point #1	✓
2	203030592	2	-0.2	0624Z			Point #2	✓
3	202270428	3	-0.1	0633Z			Point #3	✓
4	203040089	4	-0.1	0649Z			Point #4	✓
5	203030530	1	-0.3	0657Z			Point #5	✓
6	203310484	2	-0.2	0707Z			Point #6	✓
7	203040327	3	-0.1	0724Z			Point #7	✓
8	203040080	4	-0.2	0738Z			Point #8	✓
9	202270467	1	-0.1	0753Z			Point #9	✓
10	203540091	2	-0.3	0807Z			Point #10	✓
11	203520458	3	-0.3	0822Z			Point #11	✓
12	203440020	4	-0.3	0836Z			Point #12	✓
13	203540087	1	-0.4	0853Z			Point #13	✓
14	203030629	2	-0.1	0909Z			Point #14	✓
15	202251095	3	0.0	0924Z			Point #15	✓
16	203540086	4	-0.3	0939Z			Point #16	✓
17	202270429	1	-0.1	0957Z			Point #17, no PTH	✗
18	203030593	2	-0.1	0958Z			Point #17 backup	✓
19	202251098	3	0.0	1006Z			Point #18	✓
20	202270432	4	-0.1	1018Z			Point #19, no LD	✗
21	203040919	1	-0.1	1018Z			Point #19 backup	✓
22	203030591	2	-0.1	1029Z			Point #20	✓
23	202251094	3	-0.1	1041Z			Point #21	✓
24	202260856	4	-0.1	1057Z			Point #22	✓
25	203040920	1	-0.2	1107Z			Point #23	✓
26	202910374	2	-0.1	1114Z			Point #24	✓
27	202910375	3	0.0	1120Z			Point #25	✓
28	203030863	4	0.0	1126Z			Point #26	✓
29	202270427	1	-0.1	1133Z			Point #27	✓
30	203040921	2	-0.1	1138Z			Point #28	✓
31	202910392	3	+0.1	1149Z			Point #29, fast fall	✗

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	203040024	4	-0.1	1149Z	NFU	NWS	Point #29 backup	✓
33	203030994	1	+0.1	1158Z			Point #30	✓
34	203030864	2	-0.1	1209Z			Point #31	✓
35	202270142	3	-0.1	1224Z			Point #32	✓
36	203040051	4	-0.1	1240Z			Point #33	✓
37	203440023	1	-0.2	1256Z			Point #34	✓
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect