NOAA • AOC • SED N42RF AVAPS DROP LOG Lead Tech: Mike Mascaro

Project: ~~Hurricane 2018~~ Mission: SFMR Cal Flight ID: 20210525H1

Take Off : 2110Z Landing: Flt Dir : Carpenter

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204330610	1	-0.4	2150Z	NGU	SER	Test sonde at 10k	✓
2	204350383	2	0.0	2325Z	1	1	Test sonde at 20k	✓
3								
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								

Drop Station Operator Notes

Charge $$ To Options: AOC, NWS, [redacted], SAT (Special NESDIS/HRD), IR/SST or HRD ONLY – Do not use funding codes!!!

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and full Flight ID (example 20150118I1).
- Update the Frequency band allocation as required:
  Band A - W53rd, Band B - N42RF, Band C - N43RF, Band D - N49RF, Band E - not allocated
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights. Verify data is available on Remote AVAPS at the FD Station, then terminate the sonde by selecting **Abort** to cancel the sonde initialization. Verify the AVAPS Data mission folder has been created.
- Verify AVAPS PC Time is correct
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled between the PCB ears. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Eyewall drop performance is improved when using sondes manufactured after 7/2016
- Perform RH Regeneration on all sondes – this must be done prior to sonde initialization -

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset. The latest AVAPS inserts a default offset value. Adjust if pressure offset is 0.4 mB or greater
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Select "begin data collection" and verify good data (including Winds) prior to putting sonde in launch tube
- Failure to keep good lock on GPS is likely due to the GPS antenna connector on the sonde PCB needing to be rotated away from surface mount components – do this if needed.
- Cut off about ½ of ribbon, loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing starboard
- Verify the sonde is actively tracking GPS data prior to launch and no Early Launch detect

NOAA • AOC • SED N42RF AVAPS DROP LOG

Project: Hurricane 2018 Mission: SFMR Cal Lead Tech: Mike Mascaro

Take Off: 2130Z Landing: Flight ID: 20210527H1

Flt Dir: J. Carpenter / R. Henning

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204521424	1	-1.5	2256	MAC	AOC	Drop 1, 1st buoy pass	✓
2	203150290	2	-0.7	0016	MAC	AOC	Drop 2, buoy pass	Delayed OPS
3	203310630	3	-0.9	1648	MAC	AOC	Drop 3, backup	✓
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								

Drop Station Operator Notes

Charge $$ To Options: AOC, NWS, [redacted], SAT (Special NESDIS/HRD), IR/SST or HRD ONLY – Do not use funding codes!!!

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and full Flight ID (example 20150118I1).
- Update the Frequency band allocation as required:
  Band A - W53rd, Band B - N42RF, Band C - N43RF, Band D - N49RF, Band E - not allocated
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights. Verify data is available on Remote AVAPS at the FD Station, then terminate the sonde by selecting **Abort** to cancel the sonde initialization. Verify the AVAPS Data mission folder has been created.
- Verify AVAPS PC Time is correct
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled between the PCB ears. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Eyewall drop performance is improved when using sondes manufactured after 7/2016
- Perform RH Regeneration on all sondes – this must be done prior to sonde initialization -

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset. The latest AVAPS inserts a default offset value. Adjust if pressure offset is 0.4 mB or greater
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Select "begin data collection" and verify good data (including Winds) prior to putting sonde in launch tube
- Failure to keep good lock on GPS is likely due to the GPS antenna connector on the sonde PCB needing to be rotated away from surface mount components – do this if needed.
- Cut off about ½ of ribbon, loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing starboard
- Verify the sonde is actively tracking GPS data prior to launch and no Early Launch detect

AVAPS Drop Log

Project: HURR 2021 Mission: FISH 1 Flight ID: 20210702H1

Take Off: _____ Landing: _____ Flt Dir: Parrish/Hatch Launcher S/N: 002

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203150500	1	-.4	1609	JW	NNS		✓
2	203240582	2	-.3	1622				✓
3	203240584	3	Ø	1633				✓
4	203431774	4	-.3	1647				✓
5	203310507	5	Ø	1659				✓
6	203520177	6	Ø	1721				✓
7	203310560	7	Ø	1734				✓
8	203240578	8	-.4	—			NO LD	X
9	203431546	1	Ø	1755				✓
10	203240583	2	Ø	1809				✓
11	203431807	3	Ø	1823				✓
12	203240587	4	Ø	1846				✓
13	203310026	5	Ø	1857				✓
? 14	203520171	6	-.3	1910				✓
15	203310025	7	Ø	1919				✓
16	203240589	8	-.5	1932				✓
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: HMT 2021 Mission: ELSA #2 Flight ID: 20210703H1

Take Off: 1535Z Landing: _____ Flt Dir: Ramos / Hatch Launcher S/N: 002

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203241007	1	-.4	1624	JW	NWS		✓
2	203231089	2	-.3	1636				✓
3	203310282	3	-.6	1643				✓
4	203231091	4	-.4	1651				✓
5	203310610	5	Ø	1700				✓
6	203310509	6	Ø	1729				✓
7	202730017	7	-.9	1748	JW			✓
8	203240780	8	-.4	1757	MTD			✓
9	203540090	1	-.4	1807	MTD			✓
10	203250847	2	-.8	1820	MTD			✓
11	203310036	3	-.4	1831	MTD			✓
12	203310027	4	-.4	1843	JW			✓
13	203231075	5	-.4	1857	MD			✓
14	202730129	6	-.4	1930	MD			✓
15	203310029	7	-.4	1942	MD			✓
16	203431548	8	-.7	1954	MD			✓
17	203240578	1	-.7	2005	MD			✓
18	203520171	2	-.7	2017	MD			✓
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurr 2021 Mission: ELSA #3 Flight ID: 2021070

Take Off: 0828z Landing: _____ Flt Dir: _____ Launcher S/N: C07R

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203310032	01	-0.7	1016	NRK	NWS		Y
2	203310166	02	-0.9	1031	NRK			Y
3	200650646	03	-1.0	1058	NRK			Y
4	203540094	04	-1.2	1135	NRK		MP DROP	Y
5	203150667	05	-1.2	1147	NRK		DATA MISSING	N Ecly LD? 103
6	203240788	06	-0.5	1204	CFL		IP #2	Y
7	203540067	07	-0.6	1244	CFL		IPSE	Y
8	203431767	8	-0.7	1257	CFL		MID	Y
9	203240120	1	-0.7	1312	CFL		CTR noisy winds	Y
10	~~203 030 568~~							
~~11~~ 10	203 310 165	2	-.6	1321	CFL		MID	Y
11 ~~12~~	203440 009	3	-1.0	1334	CFL		EPNW	Y
12 ~~13~~	203 240 092	4	-0.5	1354	NRK			Y
13 ~~14~~	203240112	05	-0.5	1407	NRK	NWS	MP	Y
~~14~~ ~~15~~	~~203540082~~	06	-0.6				~~BAD~~	
~~14~~ ~~16~~	203150672	06	-0.5	1420	NRK	NWS	CP	Y
~~15~~ ~~17~~	~~203240109~~	~~07~~	~~-0.8~~				NO DROP	–
~~16~~ ~~18~~								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurr 2021 Mission: ELSA #4 Flight ID: 20210705A1

Take Off: _____ Landing: _____ Flt Dir: _____ Launcher S/N: 002

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	201440734	01	-1.0	0958	NRK	NWS	IP NW	Y
2	203240118	02	-0.9	1040	NRK	NSW	CTR 1	Y
3	200650910	03	-1.0	1101	NRK	NSW	PT2	Y
4	203431805	04	-1.1	1126	NRK	NSW	/ IP #2 NW	Y
5	203431787	05	-0.9	1205	NRK	NSW	W PT2	Y
6	203440012	06	-1.3	1231	NRK	NSW	IP 3 NE	Y
7	203030568	07	-0.9	1256	NRK	NSW	CTR 2	Y
8	203240720	08	-0.3	1313	NRK	NSW	IP3 SW	Y
9	202701144	01	-0.9	1328	NRK	NWS	IP 4	Y
10	203440011	02	-1.0	1353	NRK	NWS	CTR 3	Y
11	203540075	03	-0.8	1419	NRK	NWS	IP 4 NE	Y
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricanes 2021 Mission: SFMR Calibration Flight ID: 20210721 H1

Take Off: _____ Landing: _____ Flt Dir: Carpenter Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	202640069	1	0.0	2258Z	NGU	AOC	Drop 1 @ 15k	✓
2	202630589	2	0.0	0017Z	↓	↓	Drop 2 @ 20k	✓
3								
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricanes 2021 Mission: TS Fred Flight ID: 20210811 #1

Take Off: _____ Landing: _____ Flt Dir: Carpenter Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203350234	1	-0.8	2106Z	NGU	NWS	Point #1, bad winds tumbling	X
2	202630578	2	0.0	2108Z			Point #1 backup	✓
3	203630327	3	0.0	2120Z			Point #2, no LD	X
4	192950666	4	0.0	2120Z			Point #2, backup	✓
5	203350280	5	-0.5	2133Z			Point #3	✓
6	203520172	6	-0.9	2148Z			Point #4	✓
7	203451432	7	0.0	2201Z			Point #5	✓
8	203150289	8	-0.6	2211Z			Point #6	✓
9	202640073	1	0.0	2222Z			Point #7	✓
10	202640033	2	0.0	2233Z			Point #8	✓
11	201730182	3	0.0	2247Z			Point #9	✓
12	192731141	4	-0.5	2302Z			Point #10	✓
13	195110551	5	0.0	2318Z			Point #11	✓
14	193020244	6	-0.6	2341Z			Point #12	✓
15	203640264	7	0.0	0008Z			Point #13	✓
16	192620167	8	0.0	0032Z			Point #14	✓
17	202520289	1	0.0	0041Z			Point #15	✓
18	202620524	2	-0.8	0053Z			Point #16	✓
19	203820184	3	-0.5	0108Z			Point #17	✓
20	202640071	4	0.0	0125Z			Point #18	✓
21	203451353	5	0.0	0142Z			Point #19	✓
22	202640083	6	0.0	0157Z			Point #20	✓
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: HURR 21 Mission: TS/TD FRED Flight ID: 1

Take Off: 0805Z Landing: _____ Flt Dir: Hathaway Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203240046	1	-.6	1002	JW	HRD		✓
2	202440031	2	Ø	1015				✓
3	202640080	3	Ø	1027				✓
4	203350223	4	Ø	1033				✓
5	202640032	5	-.6	1052				✓
6	203810235	6	-.3	1110				✓
7	203810250	7	-.3	1117				✓
8	203350251	8	-.7	1133				✓
9	203810238	1	Ø	1143				✓
10	202640036	2	Ø	1214				✓
11	203630331	3	Ø	1223				✓
12	203630332	4	Ø	1233				✓
13	202620534	5	Ø	1244			14/14	✓
14	202640022	6	Ø	1258	JW	HRD		✓
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricanes 2021 Mission: TS Fred Flight ID: 20210812H2

Take Off: _____ Landing: _____ Flt Dir: Carpenter Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	20231 1639	1	0.0	2128Z	NGU	NWS	IP, inbound,	✓
2	20244 0390	2	0.0	2140Z			MP, IB,	✓
3	20272 1620	3	0.0	2152Z			Center #1	✓
4	20304 0284	4	0.0	2205Z			MP, OB	✓
5	20227 0545	5	0.0	2219Z			EP, OB	✓
6	20272 1616	6	0.0	2259Z			EP, IB, no LD	X
7	20272 1608	7	-0.7	2300Z			EP, IB,	✓
8	20304 0019	8	-0.6	2313Z			MP, IB	✓
9	20272 1606	1	-0.5	2327Z			EP, IB, near center	✓
10	20304 0288	2	-0.5	2340Z			MP, OB	✓
11	20291 0425	3	-1.2	2353Z			EP, OB	✓
12		4						
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: HURR 21 Mission: TD Fred Flight ID: 20210813H1

Take Off: _____ Landing: _____ Flt Dir: Hathaway Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	202910378	1	-.3	0924	JW	NWS		✓
2	202311650	2	-1.5	0934			HIGH OFFSET	✓
3	203040923	3	-.7	0951				✓
4	203040302	4	-.8	1001				✓
5	202910376	5	-.8	1007				✓
6	202910404	6	Ø	1014				✓
7	202910393	7	-.4	1035				✓
8	202721607	8	Ø	1047				✓
9	203310483	1	-.8	1105				✓
10	203040924	2	Ø	1123				✓
11	202721605	3	-.3	1134				✓
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Herr 21 Mission: TD Grace Flight ID: 20210816H1

Take Off: _____ Landing: _____ Flt Dir: Hathaway Launcher S/N: 002

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	192940092	1	-1.2	0859	JW	NWS		✓
2	203040297	2	-.7	0957				✓
3	192540926	3	-.7	1013				✓
4	203040915	4	-.8	1041				✓
5	192540910	5	-.7	1055			Lost GPS at 9700	X
6	192540695	6	-.7	1058			Lost GPS at 9264	X
7	192620333	7	-.6	1103				✓
8	192950650	8	Ø	1117				✓
9	192940174	1	-.9	1128				✓
10	192940112	2	Ø	1156				✓
11	192940593	4	-.8	1206				✓
12	192610953	5	-.6	1216				✓
13	192610973	6	Ø	1227				✓
14	192940586	7	-.6	1238				✓
15	192540954			1257				
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

20210817H1

Project: _____ Mission: _____ Flight ID: _____

Take Off: _____ Landing: _____ Flt Dir: Lundry Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	191930467	1	-.5	0946	JW	NWS		✓
2	202311635	2	Ø	0958				✓
3	192530720	3	-.6	1012				✓
4	192610990	4	-1.1	1022				✓
5	192540946	5	-.9	1035				✓
6	192540720	6	-.7	1108				✓
7	192540954	7	Ø	1122				✓
8	202640081	8	Ø	1142				✓
9	202640074	1	Ø	1153				✓
10	192940016	2	-.5	1225				✓
11	203451371	3	Ø	1246				✓
12	202620548	4	Ø	1251				✓
13	202630409	5	Ø	1309				✓
14	203431523	6	-.4	1318				
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricanes 2021 Mission: Hurricane Grace Flight ID: 20210818H1

Take Off: _____ Landing: _____ Flt Dir: Carpenter Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203520290	1	-0.8	2128Z	NGU	NWS	IP, IB, combo	✓
2	203431514	2	-1.0	2136Z			MP, IB	✓
3	203451374	3	-1.0	2145Z		ONR	QP, IB	✓
4	202630410	4	0.0	2152Z		NWS	Center #1	✓
5	202640068	5	0.0	2201Z		ONR	QP, OB	✓
6	203350226	6	-0.5	2208Z		NWS	MP, OB	✓
7	203350235	7	-1.0	2224Z			EP, OB	✓
8	203440003	8	-0.5	2248Z			EP, IB	✓
9	202610578	1	0.0	2257Z			MP, IB	✓
10	203431524	2	0.0	2304Z		ONR	QP, IB	✓
11	203350260	3	-0.8	2306Z			RMW	✓
12	203451386	4	-0.6	2314Z		NWS	Center #2, combo	✓
13	203420233	5	-0.8	2320Z		ONR	RMW, late 6K winds	✓
14	203631771	6	0.0	2323Z			QP, OB	✓
15	203451383	7	-0.7	2327Z		NWS	MP, OB	✓
16	203451272	8	-0.7	2338Z			EP, OB, combo	✓
17	203431520	1	-0.6	0001Z			EP, IB, combo	✓
18	203451418	2	-0.8	0010Z			MP, IB	✓
19	203520505	3	-0.6	0018Z		ONR	QP, IB	✓
20	202620571	4	0.0	0021Z			RMW	✓
21	202610673	5	0.0	0022Z		NWS	Center #3 CPA	✓
22	203451381	6	-0.8	0026Z		ONR	RMW, no LD	✗
23	203820052	7	0.0	0026Z			" backup	✓
24	203631821	8	-0.5	0029Z		ONR	QP, OB	✓
25	204420101	1	0.0	0037Z		NWS	MP, OB	✓
26	192610976	2	-0.6	0049Z			EP, OB, combo	✓
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricanes 2021 Mission: Hurricane Grace Flight ID: 202108 19H1

Take Off: _____ Landing: _____ Flt Dir: Carpenter Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	1925 40933	1	0.0	2145Z	NGU	NWS	IP, IB, combo	✓
2	1926 20161	2	-0.6	2157Z			MP, IB	✓
3	204420099	3	-1.0	2201Z		ONR	QP, IB	✓
4	204330609	4	-0.6	2206Z		NWS	Center #1 CPA	✓
5	204270036	5	0.0	2210Z		ONR	QP, OB	✓
6	204260859	6	0.0	2219Z		NWS	MP, OB	✓
7	204521426	7	-0.5	2226Z			EP, OB	✓
8	204521397	8	0.0	2248Z		NWS	MP, IB	✓
9	204270034	1	-0.5	2255Z			Center #2 CPA	✓
10	204521387	2	-0.5	2304Z		ONR	QP, OB	✓
11	204260876	3	0.0	2308Z		NWS	MP, OB	✓
12	204241108	4	-0.7	2319Z			EP, OB	✓
13	1929 40309	5	-0.8	2343Z			EP, IB	✓
14	1929 40095	6	-1.0	2357Z			MP, IB	✓
15	204420100	7	-0.6	0003Z		ONR	QP, IB	✓
16	204310006	8	-0.6	0010Z		NWS	Center #3 CPA	✓
17	193120733	1	-0.9	0015Z		ONR	QP, OB	✓
18	204260887	2	0.0	0023Z		NWS	MP, OB	✓
19	204260883	3	-0.5	0037Z			EP, OB	✓
20		4						
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricanes 2021 Mission: TS Henri Flight ID: 20210820H1

Take Off: _____ Landing: _____ Flt Dir: Carpenter Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204260870	1	-0.7	2137Z	NGU	NWS	IP, IB, combo	✓
2	204270040	2	-0.6	2147Z			MP, IB	✓
3	204521425	3	-0.5	2153Z			Center CPA	✓
4	204350537	4	-0.8	2206Z		ONR	QP, OB	✓
5	204420093	5	-0.6	2212Z		NWS	MP, OB	✓
6	204521285	6	-0.5	2223Z			EP, OB, combo	✓
7	204521392	7	-0.5	2249Z			EP, IB, combo	✓
8	204260853	8	-0.6	2302Z			MP, IB	✓
9	204420095	1	-0.7	2312Z			Center #2 CPA	✓
10	204420091	2	-0.6	2326Z		ONR	QP, OB, late winds	X
11	204260884	3	-0.5	2327Z			" " backup	✓
12	204350382	4	-0.5	2333Z		NWS	MP, OB	✓
13	204260885	5	-0.5	2346Z			EP, OB	✓
14	204350381	6	0.0	0009Z			EP, IB	✓
15	204260868	7	-0.6	0024Z			MP, IB, no winds	X
16	204420096	8	-0.6	0025Z			" " backup	✓
17	204260903	1	0.0	0031Z		ONR	QP, IB	✓
18	204270031	2	-0.5	0032Z		NWS	Center CPA	✓
19	204330665	3	-0.5	0045Z		ONR	QP OB	✓
20	205050402	4	0.0	0054Z		ONR	Saildrone, combo	✓
21	204270041	5	-0.5	0103Z		NWS	MP, OB	✓
22	204270044	6	-0.5	0115Z			EP, OB	✓
23								
24								
25								
26								
27								
28								
29								
30								
31								

Serial

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: HURR 21 Mission: Henri Flight ID: 20210821H1

Take Off: 0757 Landing: _____ Flt Dir: LUNDRY Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204 260 855	1	-0.5	0954	SCP	NWS	IP 1 combo	✓
2	204 270 037	~~0~~	~~0~~	0959	SCP	NWS	MP	✓
3	204 270 043	3	-0.4	1006	SCP	NWS	Center	✓
4	204 270 042	4	~~0~~	1012	SCP	ONR	QP	✓
5	204 270 032	1	-0.6	1019	SCP	NWS	MP	✓
6	204 270 008	2	-0.6	1031	SCP	NWS	EP~~3~~ 1 combo	✓
7	204 850 206	3	-0.7	1056	SCP	NWS	IP 2 combo	✓
8	205 050 379	4	-0.5	1108	SCP	NWS	MP	✓
9	204 241 107	1	-0.5	1114	SCP	ONR	QP	✓
10	204 270 009	2	-0.5	1131	SCP	ONR	QP	✓
11	204 620 006	3	-0.4	1137	SCP	NWS	MP	✓
12	204 620 005	4	-0.5	1147	SCP	NWS	EP2 combo	✓
13	204 620 002	1	-0.8	1217	SCP	NWS	IP3 combo	✓
14	204 260 893	2	-0.4	1230	SCP	NWS	MP	✓
15	204 521 406	3	-0.4	1234	SCP	ONR	QP	✓
16	204 610 652	4	-0.4	1249	SCP	NWS	C combo	✓
17	204 270 039	1	-0.4	1251	SCP	ONR	QP	✓
18	204 620 013	2	-0.4	1258	SCP	NWS	MP	✓
19	204 610 868	3	~~0~~	1313	SCP	NWS	EP3	✓
20	~~204 610 675~~	~~4~~	~~0~~		~~SCP~~	~~NWS~~		
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

NOAA • AOC • SED N42RF AVAPS DROP LOG

Project: Hurricane ~~2018~~ 2021 Mission: Hurricane Henri Flight ID: 2021082/H2 Lead Tech: Mike Mascaro

Take Off : _____ Landing: _____ Flt Dir : Carpenter

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	20450285	1	0.0	2157Z	NGU	NWS	IP, IB, combo	✓
2	20461067 5	2	-0.6	2209Z	|	|	MP, IB	✓
3	20505098	3	0.0	2219Z	|	ONR	QP, IB	✓
4	20461066 9	4	-0.5	2235Z	|	NWS	Center #1, combo	✓
5	20427003 3	5	0.0	2244Z	|	ONR	QP, OB	✓
6	20461086 6	6	-0.7	2249Z	|	NWS	MP, OB	✓
7	20426087 4	7	-0.5	2258Z	|	|	EP, OB combo	✓
8	20450284	8	-0.5	2321Z	|	|	EP, IB combo	✓
9	20442009 8	1	-0.5	2332Z	|	|	MP, IB	✓
10	20461067 1	2	-0.5	2342Z	|	ONR	QP, IB	✓
11	20461086 9	3	-0.6	2345Z	|	NWS	Center #2	✓
12	20462000 1	4	-0.6	2350Z	|	ONR	QP, OB RMW	✓
13	20426090 2	5	0.0	2358Z	|	NWS	MP, OB	✓
14	20426089 2	6	-0.5	0012Z	|	|	EP, OB, combo	✓
15	20461067 7	7	-0.6	0125Z	|	|	EP, IB	✓
16	20484075 0	8	0.0	0139Z	|	|	MP, IB	✓
17	20462000 3	1	-0.6	0147Z	|	ONR	QP, IB	✓
18	20484056 7	2	0.0	0157Z	|	NWS	Center #3 CPA	✓
19	20450283	3	-0.6	0203Z	|	ONR	QP, OB	✓
20	20505108	4	-0.5	0208Z	|	NWS	MP, OB	✓
21	20484048 2	5	0.0	0221Z	|	|	EP, OB, combo	✓
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								

Drop Station Operator Notes

Charge $$ To Options: AOC, NWS, [redacted], SAT (Special NESDIS/HRD), IR/SST or HRD ONLY – Do not use funding codes!!!

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and full Flight ID (example 20150118I1).
- Update the Frequency band allocation as required:
  Band A - W53rd, Band B - N42RF, Band C - N43RF, Band D - N49RF, Band E - not allocated
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights. Verify data is available on Remote AVAPS at the FD Station, then terminate the sonde by selecting **Abort** to cancel the sonde initialization. Verify the AVAPS Data mission folder has been created.
- Verify AVAPS PC Time is correct
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled between the PCB ears. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Eyewall drop performance is improved when using sondes manufactured after 7/2016
- Perform RH Regeneration on all sondes – this must be done prior to sonde initialization -

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset. The latest AVAPS inserts a default offset value. Adjust if pressure offset is 0.4 mB or greater
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Select "begin data collection" and verify good data (including Winds) prior to putting sonde in launch tube
- Failure to keep good lock on GPS is likely due to the GPS antenna connector on the sonde PCB needing to be rotated away from surface mount components – do this if needed.
- Cut off about ½ of ribbon, loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing starboard
- Verify the sonde is actively tracking GPS data prior to launch and no Early Launch detect