AVAPS Drop Log

Project: 2021 Hurriseason Mission: Hurricane Ida Flight ID: 20210827H1

Take Off: 1600L Landing: _____ Flt Dir: Landry Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204610672	2	Ø	2106Z	Mac	HRD	IPNW/BT Combo	
2	204640102	1	Ø	2114Z			1st MID IN NW	
3	204610666	3	-0.6	2124Z			1st IN RMW NW	
4	204650370	4	-0.3	2145Z			1st OUT MID SE	
5	204840593	5	-0.2	2157Z			1st END PT SE	
6	204610668	6	-0.4	2232Z			MICROPHYS SPIRAL	
7	204031025	7	-0.4	2312Z			2nd IP NE/Combo	
8	204521412	8	-0.4	2321Z			2nd MID IN NE	
9	204650358	1	-0.9	2344Z			2nd OUT 1/4 SW	
10	204260854	2	-0.6	2350Z		HRD	2nd MID OUT SW	
11	204620004	3	-0.5	0004Z		ONR	2nd End PT SW	
12	204610654	4	-0.6	0022Z			3rd IP South	
13	204420094	5	-0.6	0033Z			3rd MID IN SOUTH	
14	204260861	6	-0.6	0051Z			1st CB Module NW	
15	204270045	7	-0.4	0057Z			2nd CB Module NW	
16	204620016	8	-0.6	0127Z			3rd MID OUT N/Combo	
17	204260873	1	-0.5	0139Z			3rd END PT N/Combo	
18	204640459	2	-0.5	0212Z			4th IP West/Combo	
19	204031021	3	-0.3	0224Z			4th MID IN West	
20	204330611	4	-0.7	0238Z			4th, NB RMW	
21	204610809	5	-0.7	0244Z			4th CTR maybe	
22	204260891	6	-0.7	0252Z			4th RMW out	
23	204840594	7	-0.3	0258Z			4th MID OUT EAST	
24	204530193	8	-0.6	0307Z			4th END PT EAST	
25	204650368	1	-0.4	0308Z	Mac	ONR	B/U END PT / LATENT GPS ON DROP 4	
26								
27								
28								
29								
30								
31								

08:50:30
54:30
20:55:00

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: 2021 Season Mission: Hurricane Ida Flight ID: 20210828H1

Take Off: 2000Z Landing: _____ Flt Dir: Hathaway Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204840485	1	-0.5	2044	MAC	EMC	IP1 NE Combo	
2	204260901	2	-0.7	2057		EMC	1st MID IN NE Combo	
3	204330607	3	-0.9	2104		ONR	1st RMW.1	
4	203250885	4	-0.4	2106		ONR	1st RMW.2 Combo	
5	204260653	5	-0.6	2108		ONR	1st RMW.3	
6	205050314	6	-0.4	2113		EMC	1st CTR	
7	204540667	7	-0.5	2117		ONR	1st OUT RMW.1 SW	
8	205050307	8	-0.4	2118		ONR	1st OUT RMW.2 Combo	
9	204031023	1	-0.5	2119		ONR	1st OUT RMW.3	
10	204270001	2	-0.5	2127		EMC	1st MID OUT Combo	
11	204540646	3	-0.4	2139		EMC	1st END PT SW	
12	204530740	4	-0.2	2209		EMC	2nd IP South	
13	204650345	5	-0.2	2219		EMC	2nd MID IN, S, Combo	
14	204640093	6	-0.4	2228		ONR	2nd RMW IN, S, Combo	
15	204650372	7	-0.1	2232		EMC	2nd CTR	
16	204260610	8	-0.8	2235		ONR	2nd RMW OUT, N, Combo	
17	204650343	1	-0.3	2246		EMC	2nd MID OUT, N, Combo	
18	204640121	2	-0.4	2259		EMC	2nd END PT, N, Combo	
BAD * 19	204610667	3	-0.8	NO LAUNCH		ONR	Microphys Spiral	BAD *
20	204640094	4	-0.7	2328		ONR	Microphys Spiral	
21	204031035	5	-0.4	2353		EMC	Leg 2-3 repo mid, Combo	
22	203310045	6	-0.4	0006		EMC	IP3, Combo	
23	204260632	7	-0.2	0017		EMC	3rd MID IN, Combo	
24	203310499	8	-0.2	0028		EMC	3rd IN RMW, Combo	
25	203250878	1	-0.2	0033		NWS	3rd IN RMW Again	
26	204621172	2	-0.8	0034		EMC	3rd CTR	
27	204530197	3	-0.9	0040		EMC	3rd RMW out	
BAD * 28	204031038	4	-0.9	0049		EMC	3rd MID OUT, NO LAUNCH	*
29	204640097	5	-0.7	0049		EMC	3rd MID out, Combo	
30	204260633	6	-1.0	0101	MAC	EMC	3rd END PT, Combo	
~~31~~	~~204530503~~	~~7~~	~~-0.7~~					

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: '21 HWX Mission: Hurricane Ida Flight ID: 20210829H1

Take Off: 1700Z Landing: _____ Flt Dir: Landry, Hathaway, Paul Flaherty Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203310059	1	-0.2	1836Z	MAC	HRD	IP1 W-E Coastal Run	
2	203210091	2	Ø	1844Z		HRD	Bad GPS	X
3	203250049	3	-0.3	1845Z		HRD	W-E Drop 2	
4	205050316	4	-0.5	1847Z		HRD	W-E Drop 3	
5	204270005	5	-0.6	1907Z		HRD	W-E Drop 4 Late GPS	
6	204270048	6	-0.6	1911Z		HRD	W-E Drop 5	
7	204650359	7	-0.3	1915Z		HRD	W-E Last Drop	
8	204950415	8	-0.3	1928Z		HRD	W-E Last Drop	
9	205050320	1	-0.3	1937Z		ONR	Combo Pt 6	
10	204840483	2	-0.5	1949Z		ONR	Combo Pt 7	
11	204610674	3	-1.2	1957		ONR	Combo Pt 8	
12	205050308	4	-0.2	2004Z		ONR	Pt 9	
13	204840484	5	-0.2	2026Z		ONR	Pt 11	
14	204530503	6	Ø	2029Z		HRD	MID OUT COMBO	
15	204270013	7	-1.1	2034Z		ONR	Pt 12 Combo	
16	203250061	8	-0.6	2045Z		ONR	Pt 13 Combo End Pt	
17	205050106	1	-0.5	2118Z		ONR	Microphysics Spiral	
18	204521410	2	-0.9	2121Z		ONR	Microphys B/U	
19	[redacted]	[redacted]	[redacted]					
20		[redacted]						
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect